

EPAM Systems, RD Dep.

Philip Morris International DWH



PHILIP MORRIS

Contents

1. BUSINESS DESCRIPTION	3
1.1. BUSINESS BACKGROUND	3
1.2. PROBLEMS BECAUSE OF POOR DATA MANAGEMENT	3
1.3. BENEFITS FROM IMPLEMENTING A DATA WAREHOUSE	4
2. DIMENSIONS OF A BUSINESS.....	4
3. LOGICAL SCHEMA.....	5
4. DATA FLOW	27
5. FACT TABLE PARTITIONING STRATEGY	30
6. STRATEGY OF PARALLEL LOAD	31
7. REPORT LAYOUTS	32
8. ADDITIONAL FEATURES	33

1. Business Description

1.1. Business background

Philip Morris International Inc. (PMI) (NYSE: PM) is an American global cigarette and tobacco company, with products sold in over 180 countries outside the United States. The most recognized and best selling product of the company is Marlboro.

The company's operational headquarters are in Lausanne, Switzerland, although the corporate headquarters remain in New York. It does not operate in the United States, with Philip Morris brands there still owned by PMI's former owner Altria.

Because tobacco, the main constituent of cigarettes, is the single greatest cause of preventable death globally[3] and is addictive, the company's operations (and its competitors') are highly controversial and are increasingly the subject of litigation and restrictive legislation from governments concerned about the health impacts of its products.

Philip Morris International has six multi-billion US\$ brands including:

1. Dji Sam Soe 234 was launched in 1913 and is a brand of Kretek cigarettes. It is the best seller of Kretek cigarettes in Indonesia.
2. L&M was launched by Liggett & Myers in 1953 with the tagline: "American cigarettes of the highest quality with the best filter." L&M variants include full flavor shorts, full flavor 100s, lights, ultra lights, menthol shorts, menthol 100s, menthol light shorts, menthol light 100s, Turkish Blend shorts, Turkish Blend 100s, and L&M Mild Kretek.
3. Longbeach include in Australia and Indonesia in 1999. Longbeach variant include: Longbeach Filter and Longbeach Mild.
4. Marlboro was launched in 1904. Marlboro is the premium brand. Marlboro variants include: Marlboro Special, Marlboro Menthol, Marlboro Lights, Marlboro Lights Menthol, Marlboro Mix-9 Filter Kretek, Marlboro Flavor Plus, Marlboro Black Menthol, and Heatsticks, a heated tobacco product.[10]
5. ST Dupont Paris is the brand cigarette designed by Simon Tissot Dupont in 1902. With the black packaging. ST Dupont Paris variants include: filter, lights, menthol, and menthol lights.
6. U Mild was launched in Indonesia in May 22, 1998 after Indonesian revolution. U Mild is a Mild Kretek cigarette sold in Indonesia.

In the end of 2016 Philip Morris presented the new product called IQOS - smokeless cigarette—one of the latest products from Philip Morris International, manufacturers of the legendary Marlboro cigarettes. The product is a hybrid between the benefits of electronic cigarettes and the design of traditional types – making it perfect for smokers looking to switch to vaping or even for occasional use. Given the known dangers of smoking traditional cigarettes, switching to vaping or just implementing a sporadic alternative is a good option.

The iQOS uses refills of real tobacco, but doesn't burn it like the conventional cigarette which prevents the ingestion of combusive, charred materials. Rather, the iQOS ecig heats the tobacco just prior to the point of combustion, producing tobacco-flavored vapor.

1.2. Problems because of poor data management

A brand new product (iQOS) appeared in the last year, but due to the poor management, it didn't get much popularity worldwide. As a result new production items had produced very little profit compared to the forecasts and the amount of resources that was spent on its production. All of this caused financial problems of the company and damaged the economic policy in 2017.

1.3. Benefits from implementing a Data Warehouse

So as to recover the company's brand name, the board of directors decided to build a detailed plan of the economic situation on the current date and to provide detailed information about all products and its sales amounts along with new company's production items. The main goal of the research is to get proper information about popularity and economic profitability of new products. Another task is to gather information about "old" production items. The research should be based on prebuild Data Warehouse. Data Warehouse should also be able to aggregate all information about sales for future years till 2030.

2. Dimensions of a Business

Starting with identifying 4 steps of creating data warehouse

1. Select the business process
Getting detailed information about brand-new product contribution to the company's production process
2. Declare the Grain
Total sales and quantity amount of new products compared
3. Identify the Dimensions
 - Products;
 - Departments;
 - Consumers;
 - Time;
 - Promotion;
4. Identify the Facts
"Total sales amount" as FACT_SALES

Entities:

- **Product Category**
Categories of the products
Examples: cigarette, tobacco heating products, vapor products
- **Product**
Brands, produced by PMI company
Examples: Marlboro, Most popular product of the company, global,
- **Location**
Addresses, cities, countries and regions
Example: 10-3 Hyde Park, NY, USA, North America
- **Consumers**
Consumers of the PMI products
Examples: Japan retail agency
- **Departments**
PMI agency all over the world
Example: St. Petersburg Main Agency, 2201

- **Promotions**

Promotions, which take place in some parts of the year

Example: Promotion #276421 Brand-new product

- **Sale**

Sale of some product to the customer

Example: PRODUCT, PRICE, QUANTITY, CONSUMER, DEPARTMENT, DATE

As a result, we get such **DIMENSIONS**:


3. Logical schema

Provided dimensions and fact table build the Star schema of data warehouse. Star schema was chosen for the following reasons:

- Maximum performance and ease of access;
PMI Corporation is ready to invest much in local storage to get rid of redundant connections so as to make access to all data without extra joins and do not pay much attention about redundancy in data.
- Simplification of preparing data for reporting
Using Star makes does not require special IT staff for ETL and building data marts for appropriate report because almost everything will be aggregated in dimensions and the only thing to do will be some simple grouping operations,

As far as dimensions were defined in the previous chapter, PMI data warehouse gets next model:




















Star schema:





Picture – PMI Star schema model

List of tables in Star schema:















DIM_CONSUMERS

COLUMN NAME	DATATYPE	NOT NULL	COMMENTS
 CONSUMER_SURR_ID	NUMBER(8)	True	
 CONSUMER_ID	NUMBER(8)	False	
 CONSUMER_DESC	VARCHAR2(50)	False	
 RATE_ID	NUMBER(8)	False	
 RATE_DESC	VARCHAR2(50)	False	
 RESPONSIBLE_ID	NUMBER(8)	False	
 RESPONSIBLE_DESC	VARCHAR2(100)	False	
 ADDRESS_ID	NUMBER(8)	False	
 ADDRESS_DESC	VARCHAR2(50)	False	
 CITY_ID	NUMBER(8)	False	
 CITY_DESC	VARCHAR2(50)	False	
 COUNTRY_ID	NUMBER(8)	False	
 COUNTRY_DESC	VARCHAR2(50)	False	
 SUBREGION_ID	NUMBER(8)	False	
 SUBREGION_DESC	VARCHAR2(50)	False	
 REGION_ID	NUMBER(8)	False	
 REGION_DESC	VARCHAR2(50)	False	
 POSTAL_CODE	VARCHAR2(50)	False	
 PHONE	VARCHAR2(50)	False	

COLUMN NAME	DATATYPE	NOT NULL	COMMENTS
 UPDATE_DT	DATE	False	
 INSERT_DT	DATE	False	

PRIMARY KEY NAME	COLUMNS	COMMENTS
 PK_DIM_CONSUMERS	CONSUMER_SURR_ID	



















DIM_DATE







COLUMN NAME	DATATYPE	NOT NULL	COMMENTS
 DATE_ID	DATE	True	
 DAY_WEEK	NUMBER(8)	False	
 DAY_SHORT	VARCHAR2(50)	False	
 DAY_LONG	VARCHAR2(50)	False	
 DAY_MONTH	NUMBER(8)	False	
 LASTDAY_MONTH	DATE	False	
 DAY_YEAR	NUMBER(8)	False	
 MONTH_YEAR	NUMBER(8)	False	
 MONTH_SHORT	VARCHAR2(50)	False	
 MONTH_LONG	VARCHAR2(50)	False	
 MONTH_DESC	VARCHAR2(50)	False	
 QUARTER	NUMBER(8)	False	
 YEAR_HALF	NUMBER(8)	False	
 YEAR	NUMBER(8)	False	

PRIMARY KEY NAME	COLUMNS	COMMENTS
	DATE_ID	

 PK_DIM_DATE		
---	--	--











DIM_DEPARTMENTS





COLUMN NAME	DATATYPE	NOT NULL	COMMENTS
 DEPARTMENT_SURR_ID	NUMBER(8)	True	
 DEPARTMENT_ID	NUMBER(8)	False	
 DEPARTMENT_DESC	VARCHAR2(50)	False	
 ADDRESS_ID	NUMBER(8)	False	
 ADDRESS_DESC	VARCHAR2(50)	False	
 PHONE	VARCHAR2(20)	False	
 POSTAL_CODE	VARCHAR2(50)	False	
 CITY_ID	NUMBER(8)	False	
 CITY_DESC	VARCHAR2(50)	False	
 COUNTRY_ID	NUMBER(8)	False	
 COUNTRY_DESC	VARCHAR2(50)	False	
 SUBREGION_ID	NUMBER(8)	False	
 SUBREGION_DESC	VARCHAR2(50)	False	
 REGION_ID	NUMBER(8)	False	
 REGION_DESC	VARCHAR2(50)	False	
 START_DT	DATE	False	
 END_DT	DATE	False	
 IS_ACTIVE	VARCHAR2(1)	False	


COLUMN NAME	DATATYPE	NOT NULL	COMMENTS
 UPDATE_DT	DATE	False	
 INSERT_DT	DATE	False	
 PRODUCT_ID	NUMBER	False	
 CONSUMER_ID	NUMBER	False	
 PROMO_ID	NUMBER	False	
 DATE_ID	DATE	False	

PRIMARY KEY NAME	COLUMNS	COMMENTS
 PK_DIM_DEPARTMENTS	DEPARTMENT_SURR_ID	











DIM_PRODUCTS

COLUMN NAME	DATATYPE	NOT NULL	COMMENTS
 PRODUCT_SURR_ID	NUMBER(8)	True	
 PRODUCT_ID	NUMBER(8)	False	
 PRODUCT_DESC	VARCHAR2(50)	False	
 PRODUCT_PRICE	NUMBER(8,2)	False	
 CATEGORY_ID	NUMBER(8)	False	
 CATEGORY_DESC	VARCHAR2(50)	False	
 SUBCATEGORY_ID	VARCHAR2(50)	False	
 SUBCATEGORY_DESC	VARCHAR2(50)	False	
 SUBCATEGORY_SIZE	NUMBER(8,2)	False	
 SUBCATEGORY_TOBACCO	NUMBER(8,2)	False	
	NUMBER(8)	False	

COLUMN NAME	DATATYPE	NOT NULL	COMMENTS
 LOCALIZATION_ID			
 LOCALIZATION_DESC	VARCHAR2(50)	False	
 UPDATE_DT	DATE	False	
 INSERT_DT	DATE	False	



PRIMARY KEY NAME	COLUMNS	COMMENTS
 PK_DIM_PRODUCTS	PRODUCT_SURR_ID	


DIM_PROMOTION

COLUMN NAME	DATATYPE	NOT NULL	COMMENTS
 PROMO_SURR_ID	NUMBER(8)	True	
 PROMO_ID	NUMBER(8)	False	
 PROMO_NAME	VARCHAR2(100)	False	
 PROMO_DESC	VARCHAR2(100)	False	
 PROMO_COST	NUMBER(8,2)	False	
 START_DT	DATE	False	
 END_DT	DATE	False	
 IS_ACTIVE	VARCHAR(1)	False	
 UPDATE_DT	DATE	False	
 INSERT_DT	DATE	False	








PRIMARY KEY NAME	COLUMNS	COMMENTS
 PK_DIM_PROMOTIONS	PROMO_SURR_ID	


DIM_SALE_STATE




COLUMN NAME	DATATYPE	NOT NULL	COMMENTS
 STATE_ID	NUMBER(8)	True	
 STATE_DESC	VARCHAR2(50)	False	

PRIMARY KEY NAME	COLUMNS	COMMENTS
 PK_SALE_STATE	STATE_ID	

FCT_SALES


COLUMN NAME	DATATYPE	NOT NULL	COMMENTS
 PRODUCT_ID	NUMBER(8)	True	
 DEPARTMENT_ID	NUMBER(8)	True	
 CONSUMER_ID	NUMBER(8)	True	
 PROMO_ID	NUMBER(8)	True	
 DATE_ID	DATE	True	
 COST	NUMBER(8,2)	False	
 AMOUNT	NUMBER(8,2)	False	

PRIMARY KEY NAME	COLUMNS	COMMENTS
 PK_FACT_SALES	PRODUCT_ID, DEPARTMENT_ID, CONSUMER_ID, PROMO_ID, DATE_ID	

FOREIGN KEY NAME	COLUMNS	REFERENCES
 FK_FACT_SALES_DIM_DATE	DATE_ID	DIM_DATE(DATE_ID)
 FK_FACT_SALES_DIM_PRODUCTS	PRODUCT_ID	DIM_PRODUCTS(PRODUCT_SURR_ID)
 FK_FACT_SALES_DIM_CONSUMERS	CONSUMER_ID	DIM_CONSUMERS(CONSUMER_SURR_ID)









 FK_FACT_SALES_DIM_PROMOTIONS	PROMO_ID	DIM_PROMOTIONS(PROMO_SURR_ID)
 FK_FACT_SALES_DIM_DEPARTMENTS	DEPARTMENT_ID	DIM_DEPARTMENTS(DEPARTMENT_SURR_ID)


As far as star schema is built, the model of PMI database in 3rd normal form can be seen below.


3NF model:Picture – PMI 3rd normal form model

Description of PMI tables can be seen below:






CE_ADDRESSES


COLUMN NAME	DATATYPE	NOT NULL	COMMENTS
 ADDRESS_ID	NUMBER(8,2)	True	
 ADDRESS_CODE	VARCHAR2(50)	False	
 ADDRESS	VARCHAR2(50)	False	
 POSTAL_CODE	VARCHAR2(50)	False	
 PHONE	VARCHAR2(50)	False	
 CITY_ID	NUMBER(8,2)	False	
 UPDATE_DT	DATE	False	
 INSERT_DT	DATE	False	Initial value: TRUNC(SYSDATE)


PRIMARY KEY NAME	COLUMNS	COMMENTS
 PK_ADDRESSES	ADDRESS_ID	

FOREIGN KEY NAME	COLUMNS	REFERENCES
 FK_ADDRESSES_CITIES	CITY_ID	CE_CITIES(CITY_ID)

CE_CITIES









COLUMN NAME	DATATYPE	NOT NULL	COMMENTS
 CITY_ID	NUMBER(8,2)	True	
 CITY_CODE	VARCHAR2(10)	False	
 CITY_NAME	VARCHAR2(50)	False	
 COUNTRY_ID	NUMBER(8,2)	False	
 UPDATE_DT	DATE	False	


COLUMN NAME	DATATYPE	NOT NULL	COMMENTS
 INSERT_DT	DATE	False	Initial value: TRUNC(SYSDATE)



PRIMARY KEY NAME	COLUMNS	COMMENTS
 PK_CITIES	CITY_ID	


FOREIGN KEY NAME	COLUMNS	REFERENCES
 FK_CITIES_COUNTRIES	COUNTRY_ID	CE_COUNTRIES(COUNTRY_ID)

CE_CONSUMERS



COLUMN NAME	DATATYPE	NOT NULL	COMMENTS
 CONSUMER_ID	NUMBER(8,2)	True	
 CONSUMER_CODE	NUMBER(8,2)	False	
 CONSUMER_TITLE	VARCHAR2(50)	False	
 CONSUMER_RATE_ID	NUMBER(8,2)	False	
 ADDRESS_ID	NUMBER(8,2)	False	
 RESP_ID	NUMBER(8,2)	False	
 UPDATE_DT	DATE	False	
 INSERT_DT	DATE	False	Initial value: TRUNC(SYSDATE)

PRIMARY KEY NAME	COLUMNS	COMMENTS
 PK_CONSUMERS	CONSUMER_ID	

FOREIGN KEY NAME	COLUMNS	REFERENCES
 FK_CONSUMERS_CONSUMER_RATE	CONSUMER_RATE_ID	CE_CONSUMER_RATE(CONSUMER_RATE_ID)
 FK_CONSUMERS_RESPONSIBLE	RESP_ID	CE_RESPONSIBLE(RESP_ID)








 FK_CONSUMERS_ADDRESSES	ADDRESS_ID	CE_ADDRESSES(ADDRESS_ID)
--	------------	--------------------------

CE_CONSUMER_RATE

COLUMN NAME	DATATYPE	NOT NULL	COMMENTS
 CONSUMER_RATE_ID	NUMBER(8,2)	True	
 RATE_TITLE	VARCHAR2(50)	False	


PRIMARY KEY NAME	COLUMNS	COMMENTS
 PK_CONSUMER_RAT_01	CONSUMER_RATE_ID	

CE_COUNTRIES










COLUMN NAME	DATATYPE	NOT NULL	COMMENTS
 COUNTRY_ID	NUMBER(8,2)	True	
 COUNTRY_CODE2	VARCHAR2(10)	False	
 COUNTRY_CODE3	VARCHAR2(10)	False	
 COUNTRY_NAME	VARCHAR2(100)	False	
 SUBREGION_ID	NUMBER(8,2)	False	
 UPDATE_DT	DATE	False	
 INSERT_DT	DATE	False	Initial value: TRUNC(SYSDATE)

PRIMARY KEY NAME	COLUMNS	COMMENTS
 PK_COUNTRIES	COUNTRY_ID	

FOREIGN KEY NAME	COLUMNS	REFERENCES

 FK_COUNTRIES_SUBREGIONS	SUBREGION_ID	CE_SUBREGIONS(SUBREGION_ID)
---	--------------	-----------------------------



CE_DEPARTMENTS

COLUMN NAME	DATATYPE	NOT NULL	COMMENTS
 DEPARTMENT_ID	NUMBER(8,2)	True	
 DEPARTMENT_CODE	VARCHAR2(10)	False	
 DEPARTMENT_DESC	VARCHAR2(50)	False	
 ADDRESS_ID	NUMBER(8,2)	False	
 UPDATE_DT	DATE	False	
 INSERT_DT	DATE	False	Initial value: TRUNC(SYSDATE)
 START_DT	DATE	False	
 END_DT	DATE	False	
 IS_ACTIVE	VARCHAR2(1)	False	

PRIMARY KEY NAME	COLUMNS	COMMENTS
 PK_DEPARTMENTS	DEPARTMENT_ID	

FOREIGN KEY NAME	COLUMNS	REFERENCES
 FK_DEPARTMENTS_ADDRESSES	ADDRESS_ID	CE_ADDRESSES(ADDRESS_ID)






CE_LOCALIZATION


COLUMN NAME	DATATYPE	NOT NULL	COMMENTS
 LOCALIZATION_ID	NUMBER(8,2)	True	
 LOCALIZATION_NAME	VARCHAR2(50)	False	

COLUMN NAME	DATATYPE	NOT NULL	COMMENTS







PRIMARY KEY NAME	COLUMNS	COMMENTS
 PK_LOCALIZATION	LOCALIZATION_ID	




CE_OCCUPATION


COLUMN NAME	DATATYPE	NOT NULL	COMMENTS
 OCCUPATION_ID	NUMBER(8,2)	True	
 OCCUPATION_CODE	VARCHAR2(10)	False	
 OCCUPATION_NAME	VARCHAR2(50)	False	
 UPDATE_DT	DATE	False	
 INSERT_DT	DATE	False	Initial value: TRUNC(SYSDATE)


PRIMARY KEY NAME	COLUMNS	COMMENTS
 PK_	OCCUPATION_ID	

CE_PAYMENTS



COLUMN NAME	DATATYPE	NOT NULL	COMMENTS
 PAYMENT_ID	NUMBER(8,2)	True	
 PAYMENT_CODE	VARCHAR2(10)	False	
 CONSUMER_ID	NUMBER(8,2)	False	
 SALE_ID	NUMBER(8,2)	False	
 DEPARTMENT_ID	NUMBER(8,2)	False	
 COST	NUMBER(8,2)	False	

COLUMN NAME	DATATYPE	NOT NULL	COMMENTS
 AMOUNT	NUMBER(8,2)	False	
 UPDATE_DT	DATE	False	
 INSERT_DT	DATE	False	Initial value: SYSDATE

PRIMARY KEY NAME	COLUMNS	COMMENTS
 PK_PAYMENTS	PAYMENT_ID	






FOREIGN KEY NAME	COLUMNS	REFERENCES
 FK_PAYMENTS_SALES	SALE_ID	CE_SALES(SALE_ID)






CE_PAY_STATE


COLUMN NAME	DATATYPE	NOT NULL	COMMENTS
 PAY_STATE_ID	NUMBER(8,2)	True	
 PAY_STATE_NAME	VARCHAR2(50)	False	



PRIMARY KEY NAME	COLUMNS	COMMENTS
 PK_PAY_STATE	PAY_STATE_ID	

CE_PRODUCTS






COLUMN NAME	DATATYPE	NOT NULL	COMMENTS
 PRODUCT_ID	NUMBER(8,2)	True	
 PRODUCT_CODE	NUMBER(8,2)	False	
 PRODUCT_NAME	VARCHAR2(50)	False	
 LOCALIZATION_ID	NUMBER(8,2)	False	
 CATEGORY_ID	NUMBER(8,2)	False	

COLUMN NAME	DATATYPE	NOT NULL	COMMENTS
 START_DT	DATE	False	Initial value: SYSDATE
 END_DT	DATE	False	Initial value: '31-DEC-1999'
 IS_ACTIVE	VARCHAR2(1)	True	Initial value: 'Y'
 UPDATE_DT	DATE	False	
 INSERT_DT	DATE	False	Initial value: TRUNC(SYSDATE)

PRIMARY KEY NAME	COLUMNS	COMMENTS
 PK_PRODUCTS	PRODUCT_ID	

FOREIGN KEY NAME	COLUMNS	REFERENCES
 FK_PRODUCTS_PRODUCT_CATEGORY	CATEGORY_ID	CE_PRODUCT_CATEGORY(CATEGORY_ID)
 FK_PRODUCTS_LOCALIZATION	LOCALIZATION_ID	CE_LOCALIZATION(LOCALIZATION_ID)









CE_PRODUCT_CATEGORY


COLUMN NAME	DATATYPE	NOT NULL	COMMENTS
 CATEGORY_ID	NUMBER(8,2)	True	
 CATEGORY_CODE	VARCHAR2(50)	False	
 CATEGORY_NAME	VARCHAR2(50)	False	
 UPDATE_DT	DATE	False	
 INSERT_DT	DATE	False	Initial value: TRUNC(SYSDATE)


PRIMARY KEY NAME	COLUMNS	COMMENTS

 PK_PRODUCT_CATEGORY	CATEGORY_ID	
---	-------------	--


CE_PRODUCT_SUBCATEGORY










COLUMN NAME	DATATYPE	NOT NULL	COMMENTS
 SUBCATEGORY_ID	NUMBER(8,2)	True	
 SUBCATEGORY_CODE	VARCHAR2(50)	False	
 SUBCATEGORY_NAME	VARCHAR2(50)	False	
 CATEGORY_ID	NUMBER(8,2)	False	
 SIZE	NUMBER(3)	False	
 TOBACCO	NUMBER(3,1)	False	
 UPDATE_DT	DATE	False	
 INSERT_DT	DATE	False	Initial value: TRUNC(SYSDATE)


PRIMARY KEY NAME	COLUMNS	COMMENTS
 PK_PRODUCT_SUBC_01	SUBCATEGORY_ID	

FOREIGN KEY NAME	COLUMNS	REFERENCES
 FK_PRODUCT_SUBC_PRODUCT_CAT_01	CATEGORY_ID	CE_PRODUCT_CATEGORY(CATEGORY_ID)






CE_PROMOTIONS

COLUMN NAME	DATATYPE	NOT NULL	COMMENTS
 PROMO_ID	NUMBER(8,2)	True	

COLUMN NAME	DATATYPE	NOT NULL	COMMENTS
 PROMO_CODE	VARCHAR2(50)	False	
 PROMO_NAME	VARCHAR2(50)	False	
 PROMO_DESC	VARCHAR2(50)	False	
 START_DT	DATE	False	
 END_DT	DATE	False	
 PROMO_COST	NUMBER(8,2)	False	
 IS_ACTIVE	VARCHAR2(1)	False	Initial value: 'Y'
 UPDATE_DT	DATE	False	
 INSERT_DT	DATE	False	Initial value: TRUNC(SYSDATE)

PRIMARY KEY NAME	COLUMNS	COMMENTS
 PK_PROMOTIONS	PROMO_ID	












CE_REGIONS

COLUMN NAME	DATATYPE	NOT NULL	COMMENTS
 REGION_ID	NUMBER(8,2)	True	
 REGION_CODE	VARCHAR2(3)	False	
 REGION_NAME	VARCHAR2(50)	False	
 UPDATE_DT	DATE	False	
 INSERT_DT	DATE	False	Initial value: TRUNC(SYSDATE)


PRIMARY KEY NAME	COLUMNS	COMMENTS
 PK_REGIONS	REGION_ID	

--	--	--

CE_RESPONSIBLE










COLUMN NAME	DATATYPE	NOT NULL	COMMENTS
 RESP_ID	NUMBER(8,2)	True	
 RESP_CODE	VARCHAR2(50)	False	
 FIRST_NAME	VARCHAR2(50)	False	
 LAST_NAME	VARCHAR2(50)	False	
 PHONE	VARCHAR2(50)	False	
 EMAIL	VARCHAR2(50)	False	
 BIRTHDAY	DATE	False	
 AGE	NUMBER(8,2)	False	
 OCCUPATION_ID	NUMBER(8,2)	False	
 UPDATE_DT	DATE	False	
 INSERT_DT	DATE	False	Initial value: TRUNC(SYSDATE)


PRIMARY KEY NAME	COLUMNS	COMMENTS
 PK_RESPONSIBLE	RESP_ID	






FOREIGN KEY NAME	COLUMNS	REFERENCES
 FK_RESPONSIBLE_OCCUPATION	OCCUPATION_ID	CE_OCCUPATION(OCCUPATION_ID)

CE_SALES

COLUMN NAME	DATATYPE	NOT NULL	COMMENTS







COLUMN NAME	DATATYPE	NOT NULL	COMMENTS
 SALE_ID	NUMBER(8,2)	True	
 SALE_DATE	DATE	False	
 DEPARTMENT_ID	NUMBER(8,2)	False	
 CONSUMER_ID	NUMBER(8,2)	False	
 PRODUCT_ID	NUMBER(8,2)	False	
 PROMO_ID	NUMBER(8,2)	False	
 AMOUNT	NUMBER(10,2)	False	
 UPDATE_DT	DATE	False	
 INSERT_DT	DATE	False	Initial value: TRUNC(SYSDATE)


PRIMARY KEY NAME	COLUMNS	COMMENTS
 PK_SALES	SALE_ID	


FOREIGN KEY NAME	COLUMNS	REFERENCES
 FK_SALES_PRODUCTS	PRODUCT_ID	CE_PRODUCTS(PRODUCT_ID)
		CE_PAY_STATE()
 FK_SALES_PROMOTIONS	PROMO_ID	CE_PROMOTIONS(PROMO_ID)
 FK_SALES_DEPARTMENTS	DEPARTMENT_ID	CE_DEPARTMENTS(DEPARTMENT_ID)
 FK_SALES_CONSUMERS	CONSUMER_ID	CE_CONSUMERS(CONSUMER_ID)

CE_SUBREGIONS

COLUMN NAME	DATATYPE	NOT NULL	COMMENTS


COLUMN NAME	DATATYPE	NOT NULL	COMMENTS
 SUBREGION_ID	NUMBER(8,2)	True	
 SUBREGION_CODE	VARCHAR2(4)	False	
 SUBREGION_NAME	VARCHAR2(100)	False	
 REGION_ID	NUMBER(8,2)	False	
 UPDATE_DT	DATE	False	
 INSERT_DT	DATE	False	Initial value: TRUNC(SYSDATE)

PRIMARY KEY NAME	COLUMNS	COMMENTS
 PK_SUBREGIONS	SUBREGION_ID	

FOREIGN KEY NAME	COLUMNS	REFERENCES
 FK_SUBREGIONS_REGIONS	REGION_ID	CE_REGIONS(REGION_ID)

4. Data flow

Here you can see the example of data flow that will be built during the process of building DWH:



Picture – PMI data flow model

Data flow has 3 areas:

- 1) Data source area;
- 2) Staging area;
- 3) Warehouse area.

Data source area

On the first step main task is to choose appropriate sources with PMI company data and combine it in flat files so as to prepare data for ETL processes. **Official website of PMI Company** is used as the main data source for product and department description. Some information about outdated products will be gathered from other **different sources** like Wikipedia, Numbeo, and some others. Some information like sales and date dimension will be generated manually in the **local database** and provided as .sql file that would be used in operational data store (ODS).

Staging area

Second step is to make **ETL** processes that will combine operations like:

- Extract;
- Clean;
- Conform;
- Transform
- Load.

External tables will be actively used on this stage. As the result of these operations, tables with cleaned data will be gained. Cleaned data will be sent to the ODS, where database in the 3rd normal form will be created.

Another step will be to transform 3rd normal form database into Star schema through some additional ETL processes.

Users:**SA_SRC**

- starts the process of getting data from sources to external tables in the staging area;

BL_CL

- converts external (ext) tables to working (wrk) to get better performance in work with data;
- truncates & inserts data to tables (cl);
- prepares data from external table to 3nf schema by cleaning data and allocation to appropriate tables;
- merges data with tables from 3nf layer (ce).

3NF

- operates with ready-build 3nf schema.

BL_CL2

- 2nd cleaning layer used for preparing data to DWH schema;
- truncates & inserts data to tables (CLS);
- prepares data from external table to 3nf schema by cleaning data and allocation to appropriate tables;
- merges data with tables from DWH.

DWH

- operates with ready-build DWH schema.

Warehouse area

The result of these processes will be ready-made Data Warehouse for PMI Corporation.

Methods, rules and the process of generation source data are the following:

- Product description and whole information will be taken from the PMI website and Wikipedia;
- Information about departments will be taken from additional sources, which provide appropriate information about PMI deps;
- Prices for products will be taken from the source https://www.numbeo.com/cost-of-living/prices_by_country.jsp?displayCurrency=USD&itemId=17 where there is an information about pricing in different countries. Other product pricing will be generated on the basis of this source so as to provide approximately true information about different brands of PMI;
- Pricing Index will be set up for location on the basis of source above;


- Data on different years will be generated manually;
- Data on amount of sales will be generated manually (within the framework of global brand share);
- Data on quantity of products sold will be generated manually (within the framework of global brand share).

5. Fact Table Partitioning Strategy

Data Warehouse is going to have a great amount of records when it starts a production usage. And, moreover, the amount of records will be rising dramatically. It means that performance will be fallen every time when new sales appear and it will have been continuing till the end of 2030 year at least. So PMI Data Warehouse is needed to be correctly partitioned.

Approximately in every 5 years company make another big step in smoking industry and provides market with brand new products. And every 5 year company have a new economic plan that regulates it sales policy in the future years. So, it was decided to build partition on mentioned date (partition on every 5 years and subpartitions on every year) periods and it will be manually added range partitions. Despite it will make a great performance gain it can be not enough to manipulate with such data warehouse in a comfort way. So, additional department partitioning can be added so as to divided every 5 years by department sales in approximately equal proportions due to the techniques of hash partition.

As a result PMI data warehouse will have partition structure like it shown on the picture below:



6. Strategy of parallel load

Parallel load is an essential feature that will be used to insert data on cls level in table CLS_CONSUMERS. Consumers have been chosen because of great amount of records and large amount of records in table. So parallel insert helps to improve loading time a lot.

Screenshot below to shows the difference in executing equivalent statements:

Statistics		Statistics	
643	CPU used by this session	9	CPU used by this session
643	CPU used when call started	9	CPU used when call started
1921	DB time	796	DB time
3	Requests to/from client	3	Requests to/from client
1820	enqueue releases	17	enqueue conversions
1822	enqueue requests	20	enqueue releases
205	messages sent	38	enqueue requests
3217	non-idle wait count	781	in call idle wait time
1279	non-idle wait time	10	messages sent
13	opened cursors cumulative	46	non-idle wait count
2	opened cursors current	6	non-idle wait time
2122	physical read total IO requests	107	opened cursors cumulative
28729344	physical read total bytes	2	opened cursors current
1	pinned cursors current	2	physical read total IO requests
124	recursive calls	16384	physical read total bytes
8	recursive cpu usage	1	pinned cursors current
4525270	session logical reads	221	recursive calls
-65536	session pga memory	3	recursive cpu usage
203920	session uga memory	892	session logical reads
1907000	session uga memory max	-393216	session pga memory
2	user I/O wait time	3342336	session pga memory max
5	user calls	-799104	session uga memory
		1587096	session uga memory max
		5	user calls

Insert without/with parallelism

It can be also seen the different ways of implementing same statement (different number of opened cursors and used memory)

7. Report layouts

One of the concepts of final report is shown on the screenshot below:



Picture – concept of final report

This report shows some main goals that were set on the first step of building DWH. One of the task was to find the difference between sales start of new product compared to the already known production. This question appeared because of the small profit after new production line had started.

This concept report was built in TIBCO Spotfire on the example-basis values and real production items. It includes:

- 2 KPI charts (on the left of the screen) where
 - 1st chart shows total Quantity sold per category on its the first year on market;
 - 2nd chart shows total profit per category on its first year on market;
 - * total profit is a calculated column where [quantity] was multiplied on [cost per item]
- Bar Chart (on the right of the screen) where there is a quantity and profit on value axis per products (grouped by categories). There is also a line that shows average quantity sold in the first year of the product on the market.

Such charts provides easy-to-understand access to the success of the products in their market sales starts.

8. Additional features

Data Warehouse brings company a great performance in getting results from database. Statements below shows that aggregate info about products in 3nf schema and dwh have the same result but great difference in speed of executing information.

The screenshot displays two SQL query results side-by-side, comparing the performance of a 3NF schema and a Data Warehouse (DWH) for the same data.

Top Query (3NF Schema):

```
1 -- Getting information about random sale in RM
2 SELECT cepr.product_id, ced.department_id, cec.consumer_id, cep.promo_id, sale_date, amount*PRICE AS Cost, amou
3 FROM ce_sales ces
4 LEFT JOIN ce_products cepr on cepr.product_id = ces.product_id
5 LEFT JOIN ce_departments ced on ced.department_id = ces.department_id
6 LEFT JOIN ce_consumers cec on cec.consumer_id = ces.consumer_id
7 LEFT JOIN ce_promotions cep on cep.promo_id = ces.promo_id
8 WHERE
9 cepr.product_id = 73 AND
10 ced.department_id = 6 AND
```

Query Result: All Rows Fetched: 1 in 0.044 seconds

PRODUCT_ID	DEPARTMENT_ID	CONSUMER_ID	PROMO_ID	SALE_DATE	COST	AMOUNT
1	73	6	679204	85 01-DEC-12	84	20

Bottom Query (DWH):

```
8 SELECT DISTINCT product_id FROM fct_sales;
9
10
11
12 -- Getting information about random sale in DM
13 SELECT * FROM fct_sales WHERE
14 product_id = 73 AND
15 department_id = 6 AND
16 consumer_id = 679204
17 AND DATE_id > '10-NOV-10';
18
```

Query Result: All Rows Fetched: 1 in 0.001 seconds

PRODUCT_ID	DEPARTMENT_ID	CONSUMER_ID	PROMO_ID	DATE_ID	COST	AMOUNT	UPDATE_DT	INSERT_DT
1	73	6	679204	85 01-DEC-12	84	20	05-DEC-17	05-DEC-17

Results of aggregate executions

```
17 -- DWH
18 SELECT
19     dmp.product_id, dmp.product_desc,
20     dmd.department_id, dmd.department_desc,
21     dic.consumer_id, dic.consumer_desc,
22     dip.promo_id, dip.promo_name,
23     dmd.city_id, dmd.city_desc,
24     date_id,
25     cost
26 FROM fct_sales f
27     INNER JOIN dim_PRODUCTS dmp ON f.product_id = dmp.product_surr_id
28     INNER JOIN dim_DEPARTMENTS dmd ON f.department_id = dmd.department_surr_id
29     INNER JOIN dim_PRODUCTS dmp ON f.product_id = dmp.product_surr_id
30     INNER JOIN dim_PROMOTIONS dip ON f.promo_id = dip.promo_surr_id
31     INNER JOIN dim_CONSUMERS dic ON f.consumer_id = dic.consumer_surr_id;
```

Script Output x Query Result x

Task completed in 0.502 seconds

Only 5,000 rows currently supported in a script results
5,000 rows selected

Plan hash value: 1889229228

Id	Operation	Name	Rows	Bytes	Cost (%CPU)	Time
0	SELECT STATEMENT		498K	66M	1219 (1)	00:00:01
1	HASH JOIN		498K	66M	1219 (1)	00:00:01
2	TABLE ACCESS FULL	DIM_PRODUCTS	823	13168	5 (0)	00:00:01
3	HASH JOIN		498K	58M	1213 (1)	00:00:01
4	TABLE ACCESS FULL	DIM DEPARTMENTS	639	27477	7 (0)	00:00:01

DWH cost

```
32 -- 3nf
33 SELECT
34     product_id, product_name,
35     department_id, department_desc,
36     consumer_id, consumer_title,
37     promo_id, promo_name,
38     cec.city_id, cec.city_name,
39     sale_date,
40     price*amount AS cost
41 FROM ce_sales f
42     INNER JOIN ce_products USING (product_id)
43     INNER JOIN ce_departments ced USING (department_id)
44     INNER JOIN ce_consumers USING (consumer_id)
45     INNER JOIN ce_PROMOTIONS USING (promo_id)
46     INNER JOIN ce_ADDRESSES cea ON cea.address_id = ced.address_id
47     INNER JOIN ce_cities cec ON cec.city_id = cea.city_id;
```

Script Output x Query Result x

Task completed in 0.526 seconds

Plan hash value: 3148934997

Id	Operation	Name	Rows	Bytes	Cost (%CPU)	Time
0	SELECT STATEMENT		494K	65M	1558 (1)	00:00:01
1	HASH JOIN		494K	65M	1558 (1)	00:00:01

3NF cost

Other used techniques are:

- **Implicit cursor** [cls_Consumer_rate] & **Explicit cursor** [cls_Products, cls_Product_category, cls_Product_subcategory], which run on the small tables so as not to decrease performance much.

Implicit:

```

BEGIN
FOR cat IN (
  SELECT seq_product_category.nextval AS prod_category_id, prod_category FROM (
    SELECT prod_category
    FROM wrk_products
    WHERE PROD_category IS NOT NULL
    GROUP BY prod_category))
LOOP
  INSERT INTO cls_product_category (
    CATEGORY_id,
    CATEGORY_NAME)
  VALUES (
    cat.prod_category_id,
    cat.prod_category);
END LOOP;
END;
/
```

Explicit:

```


-- CLS_PRODUCTS
DECLARE CURSOR prod IS SELECT DISTINCT(product_code) FROM wrk_products;
p VARCHAR(10);

BEGIN
  OPEN prod;
  LOOP
    FETCH prod INTO p;
    EXIT WHEN prod%notfound;
    EXECUTE IMMEDIATE ('TRUNCATE TABLE CLS_PRODUCTS');
    INSERT INTO CLS_PRODUCTS (
      PRODUCT_CODE,
      PRODUCT_NAME,
      LOCALIZATION_CODE,
      CATEGORY_CODE,
      PRICE,
      UPDATE_DT,
      INSERT_DT)
    SELECT DISTINCT
      PRODUCT_CODE,
      PRODUCT,
      LOCALIZATION,
      PROD_CATEGORY_CODE,
      prod_price,
      sysdate,
      sysdate
    FROM WRK_PRODUCTS
      WHERE product IS NOT NULL;
  END LOOP;
  close prod;
  commit;
END;
/
```

- Bulk collect & Forall

```
-- CE_LOCALIZATION
PROCEDURE CE_LOCALIZATION AS
type TObjectTable is table of cls_localization%ROWTYPE;
t TObjectTable;
begin
    EXECUTE IMMEDIATE ('TRUNCATE TABLE ce_localization');
    select *
        BULK COLLECT INTO t
    from cls_localization;
forall x in t.First..t.Last
insert into ce_localization values t(x) ;
COMMIT;
end;
```

- Partitioning
- Package data contribution:



- SCD1 & SCD2 tables

```
-- CE_DEPARTMENTS
execute pkg_drop.DROP_proc('BL_3NF"."CE_DEPARTMENTS','table');
CREATE TABLE "BL_3NF"."CE_DEPARTMENTS"
(
    "DEPARTMENT_ID" NUMBER(8,2) NOT NULL,
    "DEPARTMENT_CODE" VARCHAR(10),
    "DEPARTMENT_DESC" VARCHAR2(50),
    "ADDRESS_ID" NUMBER(10),
    "START_DT" DATE,
    "END_DT" DATE,
    "IS_ACTIVE" VARCHAR(1),
    "UPDATE_DT" DATE,
    "INSERT_DT" DATE DEFAULT TRUNC(SYSDATE)
)
;

execute pkg_drop.DROP_proc('seq_departments','sequence');
CREATE SEQUENCE seq_departments
    INCREMENT BY 1
    START WITH 1
    MINVALUE 1
    NOCYCLE;
```

```
-- CE_PROMOTIONS
execute pkg_drop.DROP_proc('BL_3NF"."CE_PROMOTIONS','table');
CREATE TABLE "BL_3NF"."CE_PROMOTIONS"
(
    "PROMO_ID" NUMBER(8,2) NOT NULL,
    "PROMO_CODE" VARCHAR2(50),
    "PROMO_NAME" VARCHAR2(50),
    "PROMO_DESC" VARCHAR2(50),
    "PROMO_COST" NUMBER(8,2),
    "START_DT" DATE,
    "END_DT" DATE,
    "IS_ACTIVE" VARCHAR2(1),
    "UPDATE_DT" DATE,
    "INSERT_DT" DATE
)
;

execute pkg_drop.DROP_proc('seq_promotion','sequence');
CREATE SEQUENCE seq_promotion
    INCREMENT BY 1
    START WITH 1
    MINVALUE 1
    NOCYCLE;
```

- Hierarchy

```
1 SELECT * FROM dim_consumers;
2 SELECT * FROM dim_departments;
3
4 WITH t AS (
5     SELECT
6         department_id,
7         region AS child_code,
8         null AS parent_code
9     FROM dim_departments
10    UNION ALL
11    SELECT
12        department_id,
13        country,
14        region
15    FROM dim_departments
16    UNION ALL
17    SELECT
18        department_id,
19        city,
20        country
21    FROM dim_departments)
22 SELECT
23     ltrim(sys_connect_by_path(child_code, '==>'), '==>') AS path
24 FROM t
25 START WITH
26     parent_code IS NULL
27 CONNECT BY
28     PRIOR child_code = parent_code;
```

PATH	
1	Americas
2	Americas==>Canada
3	Americas==>Canada==>Toronto
4	Americas==>United States of America
5	Americas==>United States of America==>Seattle