



НАЦИОНАЛЬНЫЙ ИССЛЕДОВАТЕЛЬСКИЙ
УНИВЕРСИТЕТ

Dependency grammar and dependency parsing


Francis M. Tyers


ftyers@hse.ru

<https://www.hse.ru/org/persons/209454856>

Национальный исследовательский университет
«Высшая школа экономики» (Москва)

26 марта 2018 г.








Сегодня я сдаю экзамен
Я сегодня вечером сдаю экзамен
Экзамен сегодня вечером я сдаю

Bigrams

я сдаю, сдаю экзамен
вечером сдаю, сдаю экзамен
я сдаю, сдаю EOS

- Generalise over linear order
- Generalise long-distance



Bigrams


я сдаю, сдаю экзамен


Я сдаю, сдаю экзамен

я сдаю, сдаю экзамен

- Word based
- No non-terminals
- Words are linked by one-way binary relations
- Relations may be typed or untyped


Они состоят из водяного льда с включениями органики .








- Labels describe functional relations


Superior	Inferior
Head	Dependent
Governor	Modifier
Regent	Subordinate
Mother	Daughter
Parent	Child











Dependency structures explicitly represent:

- head-dependent relations (directed arcs)
- functional categories (arc labels)



Phrase structures explicitly represent:

- phrases (non-terminal nodes)
- structural categories (non-terminal labels)



- Criteria for a syntactic relation between a head H and a dependent D in a construction C (Zwicky, 1985)¹
 1. H determines the syntactic category of C ; H can replace C
 2. H determines the semantic category of C ; D specifies H
 3. H is obligatory, D may be optional
 4. H selects D and determines optionality of D
 5. The form of D depends on H (agreement or government)
 6. Linear position of D is specified with reference to H
- An issue:
 - Syntactic (and morphological) versus semantic criteria

¹Zwicky, A. (1985) "Heads" *Journal of Linguistics*, 21:1–29



- **Complex verb groups** (auxiliary–main verb)
- Subordinate clauses (complementiser–verb)
- Coordination (coordinator–conjuncts)
- Adpositional phrases (adposition–nominal)
- Punctuation




- Complex verb groups (auxiliary–main verb)
- **Subordinate clauses** (complementiser–verb)
- Coordination (coordinator–conjuncts)
- Adpositional phrases (adposition–nominal)
- Punctuation




- Complex verb groups (auxiliary–main verb)
- Subordinate clauses (complementiser–verb)
- **Coordination** (coordinator–conjuncts)
- Adpositional phrases (adposition–nominal)
- Punctuation



- Complex verb groups (auxiliary–main verb)
- Subordinate clauses (complementiser–verb)
- Coordination (coordinator–conjuncts)
- **Adpositional phrases** (adposition–nominal)
- Punctuation



- Complex verb groups (auxiliary–main verb)
- Subordinate clauses (complementiser–verb)
- Coordination (coordinator–conjuncts)
- Adpositional phrases (adposition–nominal)
- **Punctuation**




A dependency graph, G

- a set of V nodes, $V = \{0, 1, 2, 3, 4\}$
- a set of A arcs, $A = \{0 \rightarrow 2, 2 \rightarrow 1, 2 \rightarrow 4, 4 \rightarrow 3\}$
- a linear precedence order $<$ on V

Labelled graphs:

- Nodes in V are labelled with word forms (and annotation)
- Arcs in A are labelled with dependency types


- **Connectedness:** The syntactic structure must be complete, every word must be covered by the structure
- **Acyclicity:** The structure must be hierarchical, no cycles,
- **Single-headedness:** Each word must have at most one head



- Projectivity = no crossing arcs
- Non-projective → more complex to parse

Transition-based

...



Transition-based



Data structures:

- Stack:
 - Starts as containing only the ROOT
- Buffer
 - Starts as containing the full sentence
- Arcs
 - Starts as empty

Operations:

- SHIFT: Take the word on top of the buffer and put it on the stack
- LEFT-ARC: Make the word at the top of the stack the head of the word below it
 - Then remove the word at the top
- RIGHT-ARC: Make the word second from top the head of the word above it
 - Then remove the second from top word

ROOT Мы пошли домой

Stack

Buffer

ROOT Мы пошли домой

SHIFT

ROOT Мы пошли домой

Stack

Buffer

ROOT Мы пошли домой

SHIFT


ROOT Мы пошли домой

Stack


Buffer

ROOT Мы пошли домой


LEFT-ARC




SHIFT



RIGHT-ARC



RIGHT-ARC



A **configuration** is a snapshot of the state of the parser at a given time.

- A stack: Representing the word(s) currently being processed
- A buffer: Representing the remaining words
- A set of arcs representing a (partial) tree

We can conceive parsing as transitioning from one configuration to another via an operation.

How do we get the sequence of operations?

Deterministic algorithm:

- LEFT-ARC: Configuration has arc from the top of stack to the word below
- RIGHT-ARC: Configuration has arc from the of the stack to the first word in the input buffer
 - In addition: The dependent must have no dependents of its own
- SHIFT: All other cases




How do we get the sequence of operations?


Deterministic algorithm:

- LEFT-ARC: Configuration has arc from the top of stack to the word below
- RIGHT-ARC: Configuration has arc from the of the stack to the **first word in the input buffer**
 - In addition: The **dependent** must have no dependents of its own
- SHIFT: All other cases







- Is there an arc from the first word in the buffer to the top of the stack?
 - (Мы, ROOT)
- Is there an arc from the top of the stack to the first word in the buffer?
 - (ROOT, Мы)
- → then SHIFT



- Is there an arc from the first word in the buffer to the top of the stack?
 - (пошли, Мы) — YES, LEFT-ARC
- Is there an arc from the top of the stack to the first word in the buffer?
 - (Мы, пошли)



- Is there an arc from the first word in the buffer to the top of the stack?
 - (пошли, ROOT)
- Is there an arc from the top of the stack to the first word in the buffer?
 - (ROOT, пошли) – YES, but *пошли* still has dependents
- → then SHIFT



- Is there an arc from the first word in the buffer to the top of the stack?
 - (домой, пошли)
- Is there an arc from the top of the stack to the first word in the buffer?
 - (пошли, домой) – YES, and *домой* has no dependents
 - → RIGHT-ARC

The “only” training data required is a treebank.


- Collection of sentences annotated for dependency structure
- Universal dependencies: 67 languages, 100s of treebanks

Data trains a classifier to predict a transition from a configuration.

<http://universaldependencies.org>

🇿🇦	Afrikaans	1	49K	📄
🇬🇷	Ancient Greek	2	414K	📄
🇸🇦	Arabic	3	1,042K	📄
🇸🇩	Bambara	1	<1K	📄
🇪🇸	Basque	1	121K	📄
🇧🇪	Belarusian	1	8K	📄
🇧🇬	Bulgarian	1	156K	📄
🇲🇳	Buryat	1	10K	📄
🇮🇹	Cantonese	1	<1K	📄
🇪🇸	Catalan	1	531K	📄
🇨🇳	Chinese	4	153K	📄
🇪🇬	Coptic	1	11K	📄
🇮🇷	Croatian	1	197K	📄
🇨🇪	Czech	5	2,222K	📄
🇩🇰	Danish	1	100K	📄
🇳🇱	Dutch	2	310K	📄
🇬🇧	English	6	576K	📄
🇷🇺	Erzya	1	<1K	📄
🇪🇪	Estonian	1	106K	📄
🇫🇮	Finnish	3	377K	📄
🇫🇷	French	6	1,099K	📄
🇮🇸	Galician	2	164K	📄
🇩🇪	German	2	313K	📄
🇬🇴	Gothic	1	55K	📄
🇬🇷	Greek	1	63K	📄
🇮🇱	Hebrew	1	161K	📄
🇮🇳	Hindi	2	375K	📄
🇭🇺	Hungarian	1	42K	📄
🇮🇩	Indonesian	2	147K	📄
🇮🇪	Irish	1	23K	📄
🇮🇹	Italian	4	436K	📄
🇯🇵	Japanese	3	402K	📄

🇰🇪	Kazakh	1	11K	📄
🇰🇷	Korean	5	97K	📄
🇰🇲	Kurmanji	1	10K	📄
🇵🇹	Latin	3	491K	📄
🇱🇻	Latvian	1	90K	📄
🇱🇮	Lithuanian	2	5K	📄
🇲🇹	Maltese	1	2K	📄
🇮🇳	Marathi	1	3K	📄
🇳🇮	Najja	1	12K	📄
🇳🇴	North Sami	1	26K	📄
🇳🇴	Norwegian	3	625K	📄
🇷🇺	Old Church Slavonic	1	57K	📄
🇮🇷	Persian	1	152K	📄
🇵🇱	Polish	2	214K	📄
🇵🇹	Portuguese	3	570K	📄
🇷🇴	Romanian	2	239K	📄
🇷🇺	Russian	3	1,226K	📄
🇮🇳	Sanskrit	1	1K	📄
🇷🇸	Serbian	1	86K	📄
🇸🇰	Slovak	1	106K	📄
🇸🇮	Slovenian	2	170K	📄
🇪🇸	Spanish	3	1,004K	📄
🇸🇪	Swedish	3	195K	📄
🇸🇪	Swedish Sign Language	1	1K	📄
🇵🇭	Tagalog	1	<1K	📄
🇮🇳	Tamil	1	9K	📄
🇮🇳	Telugu	1	6K	📄
🇹🇭	Thai	1	23K	📄
🇹🇷	Turkish	2	74K	📄
🇺🇦	Ukrainian	1	100K	📄
🇷🇺	Upper Sorbian	1	10K	📄
🇮🇳	Urdu	1	138K	📄
🇺🇾	Uyghur	1	15K	📄
🇻🇳	Vietnamese	1	43K	📄



Features indexed by address (in stack or buffer) and attribute name.

Traditional:

- (Stack[0], Form) = пошли
- (Buffer[0], Form) = домой
- (Stack[0], UPOS) = VERB
- (Stack[1], Form) = ROOT

Indicator:

- Combinations of such features, e.g.
 - (Stack[0], Form) = пошли & (Buffer[0], UPOS) = ADP

Can return NULL.


Instead of all of those features, what do people do nowadays?

- Use embeddings
 - For words, POS tags, characters, features etc.

Why? Defining features is easy enough, but defining all those indicator features is tiresome.

- **Labelled parsing:** Instead of having three transitions, the LEFT-ARC and RIGHT-ARC transitions are expanded for the number of labels,
 - e.g. LEFT-ARC_{nsubj}
- **Non-projective parsing:** Add an extra transition which “swaps” adjacent nodes

Graph-based




- Represent sentence as directed graph
- Score every edge
- Running the spanning tree algorithm



Where do the scores come from ?


- ...


- Higher score
- Contains all nodes
- Each node has at most one incoming edge
- Originates from a single, predefined root





- Links between all nodes
- Except the root


- For each node in the graph
 - pick the incoming arc with the highest weight.
 - if this makes a tree \rightarrow it's the MST
- Otherwise:
 - For each cycle
 - contract the cycle
 - find the incoming arc with highest weight
 - remove incompatible arcs in the cycle
 - repeat

















Modern:

- UDPipe <http://github.com/ufal/udpipe>
- SyntaxNet <https://github.com/tensorflow/models/tree/master/research/syntaxnet>
- BiST <https://github.com/elikip/bist-parser>
 - Both MST and transition variants
- Stanford Parser <https://nlp.stanford.edu/software/nndep.html>

Historical:

- MaltParser
- MSTParser

Simple evaluation:

- Unlabelled attachment score, **UAS**: correct heads/total heads
- Labelled attachment score, **LAS**: (correct heads+labels)/total heads



Ace the exam!