

Your **definitive** source for quality pre-owned equipment.

#### **Artisan Technology Group**

(217) 352-9330 | sales@artisantg.com | artisantg.com

#### Full-service, independent repair center

with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment along with credit for buybacks and trade-ins.

#### **Custom engineering**

so your equipment works exactly as you specify.

- Critical and expedited services
- Leasing / Rentals / Demos

In stock / Ready-to-ship

• ITAR-certified secure asset solutions


Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Visit our website - Click HERE

requiring 1 sq in. of panel space is designed for electrical interlock systems, remote control monitoring of equipment controlled by the switch and other applications. Colored plastic button can be heatstamped with legend. It has two 6 v or 28 v lamps, 5 amp switch and integral solenoid. Solenoids are also available on 1-lamp models. Firm also has available in-line digital readout which can project any character or image produced on film. The Digilite measures 1 by 1½ by 5 in, and can be relamped from front. New environment-free limit switches in 1, 2 and 3-pole models are also announced.

CIRCLE NO. 298 READER SERVICE CARD



## Program Selector switch type

AMP INC., Harrisburg, Pa. Double throw program selector switch permitting selection of 2 distinct circuit combinations was designed for such applications as missile instrumentation. It has up to 1,500 poles. Ratings are 5 amp max current, continuous duty; 1,500 vdc between adjacent contacts at sea level. Switch is fully sealed and wiping action pre-cleans contacts. Wiring to switch rear is accomplished with taper pins. A variation is a combination plug board and dt switch with all throw positions independently patched.

CIRCLE NO. 299 READER SERVICE CARD



## LIS Networks two models

STODDARD AIRCRAFT RADIO Co., INC., 6644 Santa Monica Blvd., Hollywood, Calif. Models 91221-1 (50




#### before the bird takes off

During preflight checkout, ground power supplies must be meticulously monitored to avoid limping undervoltage, crippling overvoltage.

How?

BECKMAN Expanded Scale Voltmeters—with accuracy to a fraction...readability to hundredths! That's vital volt-splitting at the moment of "Go—No Go," when operation depends upon precise power input with no room for guesswork. (And no trifling with "average" readings: BECKMAN AC meters give honest, direct rms readings on all wave forms.)



# splitting

Helipot offers you hundreds of models ...either AC or DC...in divers shapes, sizes and voltage ranges. (Not to mention voltage monitoring packages, which may include our expanded scale frequency meters and linear scale ammeters, too.) All have uncommon accuracy in common, plus resolution ten times that of conventional meters!

Incredible?

Make us prove it by asking for Data File A324.

Beckman Helipot

Helipot Division of Beckman Instruments, Inc. Fullerton, California Engineering representatives in 29 cities

potentiometers • dials • delay lines • expanded scale meters • servomotors • breadboard parts

ampere) and 91222-1 (100 ampere) are line impedance stabilization networks. Either, when inserted in an a-c/d-c power line, presents a definite r-f impedance to the interference-producing equipment and to the power source. Thus isolated, accurate and repeatable interference acceptance tests may be performed upon the equipment in conjunction with radio-interference measuring equipment.

CIRCLE NO. 300 READER SERVICE CARD



## Milli-Volt/Ammeter d-c measuring

WESTON INSTRUMENTS DIV., Daystrom, Inc., 614 Frelinghuysen Ave., Newark 12, N. J. Model 1477, an electronic milli-volt/ammeter measures d-c currents of 10-1,000 μa and d-c voltages of 1-1,000 mv. Power drain from source is essentially zero but gain supplies 1 ma to drive meter and external load up to 5 kilohms. Essentially zero drift, its long time drift is less than 2 μv. A servo amplifier stabilizes the meter. Accuracy is 2 percent in lowest range and 1 percent in others; resolution 2 µv or 0.02 µa; gain stability and output linearity, within 0.1 percent above 1 mv or 200 μa. Precision resistor calibration avoids tube replacement selection.

CIRCLE NO. 103 READER SERVICE CARD

### Other New Products

## Capacitor rectangular type

©1959 B.I.1.

PLASTIC CAPACITORS, INC., 2620 N. Clybourn Ave., Chicago 14, Ill. Type LK rectangular capacitor features smaller size and four times the life of MIL-C-25A. Other advantages include superior resistance; better power factor; withstands greater overloads; may

## Artisan Technology Group is an independent supplier of quality pre-owned equipment

### **Gold-standard solutions**

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

## We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

### Learn more!

Visit us at artisantg.com for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today? (217) 352-9330 | sales@artisantg.com | artisantg.com

