

Getting started with Transact-SQL



Agenda



- Introduction to Transact-SQL
- SQL Server System Databases
- Using the SELECT Statement

1: Introduction to Transact-SQL



What is Transact-SQL?

Structured Query Language (SQL)


- Developed in the 1970s as a language for querying databases
- Adopted as a standard by ANSI and ISO standards bodies
- Widely used across multiple database systems

Microsoft's implementation is Transact-SQL


- Often referred to as T-SQL
- Query language for SQL Server, Azure SQL Database, and other Microsoft relational database services

SQL is *declarative*, not *procedural*

- Describe what you want, don't specify steps




Relational databases



Entities are represented as *relations* (tables), in which their attributes are represented as domains (columns)

Most relational databases are *normalized*, with relationships defined between tables through primary and foreign *keys*

Schemas and object names



Schemas are namespaces for database objects

- Fully-qualified names:
`[server_name.][database_name.][schema_name.]object_name`
- Within database context, best practice is to include schema name:
`schema_name.object_name`

SQL statement types

Data Manipulation Language (DML)	Data Definition Language (DDL)	Data Control Language (DCL)
Statements for querying and modifying data: <ul style="list-style-type: none">• SELECT• INSERT• UPDATE• DELETE	Statements for defining database objects: <ul style="list-style-type: none">• CREATE• ALTER• DROP	Statements for assigning security permissions: <ul style="list-style-type: none">• GRANT• REVOKE• DENY



Focus of this course

2: SQL Server System Databases



System Databases

In SQL Server, **system databases** are essential for the operation and management of the database engine.

master

- Stores system-level information such as login accounts, system configuration settings, and information about all other databases.
- Critical for SQL Server startup.

model

- Serves as a template for all newly created databases.
- Any changes made to the model database (like default settings) will be inherited by new databases.

msdb

- Used by SQL Server Agent for scheduling jobs, alerts, and automation tasks.
- Stores backup and restore history.

tempdb

- A workspace for temporary objects like temp tables, cursors, and intermediate result sets.
- Recreated every time SQL Server restarts.

```
select * from sys.databases
```

```
SELECT name AS DatabaseName, physical_name, type_desc  
FROM sys.master_files  
WHERE database_id = 5; --AdventureWorks2022
```

```
use AdventureWorks2022;  
SELECT * FROM Production.Product;  
GO
```

3: Using the SELECT statement



The SELECT statement

	Element	Expression	Role
5	SELECT	<select list>	Defines which columns to return
1	FROM	<table source>	Defines table(s) to query
2	WHERE	<search condition>	Filters rows using a predicate
3	GROUP BY	<group by list>	Arranges rows by groups
4	HAVING	<search condition>	Filters groups using a predicate
6	ORDER BY	<order by list>	Sorts the output

```
SELECT OrderDate, COUNT(OrderID) AS Orders
FROM Sales.SalesOrder
WHERE Status = 'Shipped'
GROUP BY OrderDate
HAVING COUNT(OrderID) > 1
ORDER BY OrderDate DESC;
```

Basic SELECT query examples

All columns

```
SELECT * FROM Production.Product;
```

Specific columns

```
SELECT Name, ListPrice  
FROM Production.Product;
```

Expressions and aliases

```
SELECT Name AS Product, ListPrice * 0.9 AS SalePrice  
FROM Production.Product;
```

Data types

Exact numeric	Approximate numeric	Character	Date/time	Binary	Other
tinyint	float	char	date	binary	cursor
smallint	real	varchar	time	varbinary	hierarchyid
int		text	datetime	image	sql_variant
bigint		nchar	datetime2		table
bit		nvarchar	smalldatetime		timestamp
decimal/numeric		ntext	datetimeoffset		uniqueidentifier
numeric					xml
money					geography
smallmoney					geometry

- Compatible data types can be implicitly converted
- Explicit conversion requires an explicit conversion function:
CAST / TRY_CAST
CONVERT / TRY_CONVERT
PARSE / TRY_PARSE
STR

NULL values

NULL represents a *missing* or *unknown* value

ANSI behaviour for NULL values:

- The result of any expression containing a NULL value is NULL

`2 + NULL = NULL`

`'MyString: ' + NULL = NULL`

- Equality comparisons (=) always return false for NULL values, use IS NULL

`NULL = NULL` returns false

`NULL IS NULL` returns true


Useful functions:

`ISNULL(column/variable, value)`: Returns *value* if the column or variable is NULL

`NULLIF(column/variable, value)`: Returns NULL if the column or variable is *value*

`COALESCE(column/variable1, column/variable2, ...)`: Returns the value of the first non-NULL column or variable in the list

Review



1 You must return the *Name* and *Price* columns from a table named *Product* in the *Production* schema. In the resulting rowset, you want the *Name* column to be named *ProductName*. Which of the following Transact-SQL statements should you use?

- ☐ `SELECT * FROM Product AS Production.Product;`
- ☒ `SELECT Name AS ProductName, Price FROM Production.Product;`
- ☐ `SELECT ProductName, Price FROM Production.Product;`

2 You must retrieve data from a column that is defined as `char(1)`. If the value in the column is a digit between 0 and 9, the query should return it as an integer value. Otherwise, the query should return NULL. Which function should you use?

- ☐ `CAST`
- ☐ `NULLIF`
- ☒ `TRY_CONVERT`

3 You must return the *Cellphone* column from the *Sales.Customer* table. *Cellphone* is a `varchar` column that permits NULL values. For rows where the *Cellphone* value is NULL, your query should return the text 'None'. What query should you use?

- ☒ `SELECT ISNULL(Cellphone, 'None') AS Cellphone FROM Sales.Customer;`
- ☐ `SELECT NULLIF(Cellphone, 'None') AS Cellphone FROM Sales.Customer;`
- ☐ `SELECT CONVERT(varchar, Cellphone) AS None FROM Sales.Customer;`

Tutorial



Lab: Get started with Transact-SQL



- [Get Started with Transact-SQL | dp-080-Transact-SQL](#)
 - Explore the *AdventureWorks* database
 - Use SELECT queries to retrieve data
 - Handle NULL values
 - Work with data types