



## 6: Using built-in functions

# Agenda



- Getting started with scalar functions
- Grouping aggregated results

# 1: Getting started with scalar functions



# Introduction to built-in functions

Function category	Description
Scalar	Operate on a single row, return a single value
Logical	Compare multiple values to determine a single output
Ranking	Operate on a partition (set) of rows
Rowset	Return a virtual table that can be used subsequently in a Transact-SQL statement
Aggregate	Take one or more input values, return a single summarizing value

*Note: Ranking and Rowset functions are advanced features of SQL Server and will not be covered in this course.*

# Scalar functions

Operate on elements from a single row as inputs, return a single value as output

- Return a single (scalar) value
- Can be used like an expression in queries
- May be deterministic or non-deterministic

```
SELECT UPPER(ProductName) AS Product,  
       ROUND(ListPrice, 0) AS ApproxPrice,  
       YEAR(SaleStartDate) AS SoldSince  
FROM Production.Product;
```

## Scalar function categories

- Configuration
- Conversion
- Cursor
- Date and Time
- Mathematical
- Metadata
- Security
- String
- System
- System Statistical
- Text and Image

## Scalar functions (cont...)

```
SELECT AVG(ListPrice) AS AveragePrice,  
       MIN(ListPrice) AS MinimumPrice,  
       MAX(ListPrice) AS MaximumPrice  
FROM Production.Product;
```

```
SELECT AVG(ListPrice) AS AveragePrice,  
       MIN(ListPrice) AS MinimumPrice,  
       MAX(ListPrice) AS MaximumPrice  
FROM Production.Product;  
WHERE ProductCategoryID = 15;
```

## Nested Scalar functions (cont...)

SQL

```
SELECT MIN(YEAR(OrderDate)) AS Earliest,  
       MAX(YEAR(OrderDate)) AS Latest  
FROM Sales.SalesOrderHeader;
```

SQL

```
SELECT COUNT(DISTINCT CustomerID) AS UniqueCustomers  
FROM Sales.SalesOrderHeader;
```

# Logical functions

Output is determined by comparative logic

IIF

- Evaluate logical expression, return first value if true and second value if false

```
SELECT AddressType,  
       IIF(AddressType = 'Main Office', 'Billing', 'Mailing') AS UseFor  
FROM Sales.CustomerAddress;
```

CHOOSE

- Return value based ordinal position of expression in 1-based list

```
SELECT SalesOrderID, Status,  
       CHOOSE(Status, 'Ordered', 'Shipped', 'Delivered') AS OrderStatus  
FROM Sales.SalesOrderHeader;
```



# Aggregate functions

Functions that operate on sets, or rows of data

- Summarize input rows
- Without GROUP BY clause, all rows are arranged as one group

```
SELECT COUNT(*) AS OrderLines,  
       SUM(OrderQty*UnitPrice) AS TotalSales  
FROM Sales.OrderDetail;
```



OrderLines	TotalSales
542	714002.9136

## 2: Grouping aggregated results



## Grouping with GROUP BY

- GROUP BY creates groups for output rows, according to unique combination of values specified in the GROUP BY clause
- GROUP BY calculates a summary value for aggregate functions in subsequent phases
- Detail rows are not available after GROUP BY clause is processed

```
SELECT CustomerID, COUNT(*) AS OrderCount  
FROM Sales.SalesOrderHeader  
GROUP BY CustomerID;
```

## Filtering groups with HAVING

- HAVING clause provides a search condition that each group must satisfy
- WHERE clause is processed before GROUP BY, HAVING clause is processed after GROUP BY

```
SELECT CustomerID, COUNT(*) AS Orders
FROM Sales.SalesOrderHeader
GROUP BY CustomerID
HAVING COUNT(*) > 10;
```

The clauses in a SELECT statement are applied in the following order:

1. FROM
2. WHERE
3. GROUP BY
4. HAVING
5. SELECT
6. ORDER BY

## Column Aliases in Aggregated Queries

- Column aliases are assigned in the SELECT clause, which occurs *after* the GROUP BY clause but *before* the ORDER BY clause.
- You can reference a column alias in the ORDER BY clause, but not in the GROUP BY clause.

SQL

```
SELECT CustomerID AS Customer,  
       COUNT(*) AS OrderCount  
FROM Sales.SalesOrderHeader  
GROUP BY Customer  
ORDER BY Customer;
```

```
SELECT CustomerID AS Customer,  
       COUNT(*) AS OrderCount  
FROM Sales.SalesOrderHeader  
GROUP BY CustomerID  
ORDER BY Customer;
```

## Troubleshooting GROUP BY errors

Msg 8120, Level 16, State 1,  
Line 2 Column  
<column\_name> is invalid in  
the select list because it is not  
contained in either an  
aggregate function or the  
GROUP BY clause.

```
SELECT CustomerID,  
       COUNT(*) AS OrderCount  
FROM Sales.SalesOrderHeader  
GROUP BY CustomerID;
```

```
SELECT CustomerID,  
       PurchaseOrderNumber,  
       COUNT(*) AS OrderCount  
FROM Sales.SalesOrderHeader  
GROUP BY CustomerID;
```

ERROR! PurchaseOrderNumber isn't  
part of the GROUP BY, and it isn't used  
with an aggregate function.

## Troubleshooting GROUP BY errors

```
SELECT CustomerID,  
       PurchaseOrderNumber,  
       COUNT(*) AS OrderCount  
FROM Sales.SalesOrderHeader  
GROUP BY CustomerID,  
         PurchaseOrderNumber;
```

# Lab: Using built-in functions



- <https://microsoftlearning.github.io/dp-080-Transact-SQL/Instructions/Labs/04-built-in-functions.html>
- Use scalar functions
- Use logical functions
- Use aggregate functions
- Group aggregated results with GROUP BY clause
- Filter groups with the HAVING clause



# Review



- 1 Which OrderState value does this query return for rows with a Status value of 2:  

```
SELECT OrderNo, CHOOSE(Status, 'Ordered', 'Shipped', 'Delivered') AS OrderState FROM Sales.Order;
```

  - ☒ Shipped
  - ☐ Delivered
  - ☐ NULL
  
- 2 Which query returns the number of customers in each city?
  - ☐

```
SELECT City, COUNT(*) AS CustomerCount FROM Sales.Customer;
```
  - ☒

```
SELECT City, COUNT(*) AS CustomerCount FROM Sales.Customer GROUP BY City;
```
  - ☐

```
SELECT City, COUNT(*) AS CustomerCount FROM Sales.Customer ORDER BY City;
```
  
- 3 Which query returns a row for each category with an average price over 10.00?
  - ☐

```
SELECT Category, AVG(Price) FROM Store.Product WHERE AVG(Price) > 10.00;
```
  - ☐

```
SELECT Category, AVG(Price) FROM Store.Product GROUP BY Category WHERE AVG(Price) > 10.00;
```
  - ☒

```
SELECT Category, AVG(Price) FROM Store.Product GROUP BY Category HAVING AVG(Price) > 10.00;
```

