



Crackz Documentation

AI Image Analysis

Version: 0.69.0

© 2026 Anaxiatech AB

Contents

- 01. [Home](#)
- 02. [Getting Started](#)
- 03. [Installation](#)
- 04. [User Guide](#)
- 05. [CLI Cookbook](#)
- 06. [GUI](#)
- 07. [Dashboard](#)
- 08. [AI Chat Assistant](#)
- 09. [Configuration](#)
- 10. [Training Configuration](#)
- 11. [Data Splits & Import](#)
- 12. [Map Viewer](#)
- 13. [Report Generation](#)
- 14. [Docker](#)
- 15. [Azure Batch](#)
- 16. [Azure VM with CUDA](#)
- 17. [VM vs Batch Comparison](#)
- 18. [Advanced Performance](#)
- 19. [Migration Guide](#)
- 20. [Shell Completion](#)
- 21. [Project Scope](#)
- 22. [Current Tasks](#)
- 23. [Architecture](#)
- 24. [Architecture Guidelines](#)
- 25. [API Reference](#)
- 26. [CLI Reference](#)
- 27. [Model Evaluation](#)
- 28. [MCP Integration](#)
- 29. [Tracing & Observability](#)
- 30. [Async Callbacks](#)
- 31. [Contributing](#)
- 32. [Release Flow](#)
- 33. [PR Review Workflow](#)
- 34. [Distribution](#)
- 35. [Customer Guide](#)
- 36. [Customer Access Management](#)
- 37. [Printable PDF](#)
- 38. [License](#)

Home

Crackz



-
-
-
-

-
-
-
-
-

-
-
-
-



crackz

crackz-gui



```
my-project/
├─ images/      # Source images by split (raw/train/val/test)
├─ masks/      # Ground truth for training
├─ artifacts/   # Detection results and training metrics
├─ logs/       # Complete audit trail
└─ project.yaml # Configuration snapshot
```

```
# Create project
crackz init --name demo

# Import images
crackz import-images --project demo --src ./photos --type raw --size 512 512

# Run detection
crackz detect run --project demo

# View results in demo/artifacts/detections/
```

```
crackz-gui
# File → New Project → Import Images → Run Detection
```

-
-
-
-

- _____
- _____
- _____

- _____
- _____
- _____
- _____
- _____
- _____
- _____

- _____
- _____
- _____
- _____

- _____
- _____
- _____

Getting Started

Getting Started with Crackz

-
-
-
-

-
-
-
-

-
-
-
-

```
# Install UV package manager
curl -Lsf https://astral.sh/uv/install.sh | sh # macOS/Linux
# OR
irm https://astral.sh/uv/install.ps1 | iex # Windows PowerShell

# Authenticate with GitHub
gh auth login

# Download and install Crackz
gh release download --repo anaxiatech/crackz --pattern '*.whl'
uv pip install crackz-*.whl

# Verify installation
crackz --version
```

```
# Pull the Docker image
docker pull ghcr.io/anaxiatech-ab/crackz:latest

# Verify it works
docker run --rm ghcr.io/anaxiatech-ab/crackz:latest --version
```

```
# Create a new project
crackz init --name my-first-project

# This creates a structured directory:
# my-first-project/
```

```
# |— images/      # Your photos organized by type
# |— masks/      # Ground truth (for training)
# |— artifacts/   # Results and metrics
# |— logs/       # Audit trail
```

```
crackz-gui
# Then: File → New Project (Ctrl/Cmd+N)
```

```
# Import images for crack detection
crackz import-images \
  --project my-first-project \
  --src ./your-photos \
  --type raw \
  --size 512 512
```

```
# Run detection using the pre-trained model
crackz detect run --project my-first-project
```

```
my-first-project/artifacts/detections/
project/artifacts/detections/metrics.json my-first-
```

```
# 1. Create project
crackz init --name harbor-inspection

# 2. Get pre-trained model checkpoint
# (Contact your Crackz provider or use a partner model)
# Place it in: harbor-inspection/artifacts/training/checkpoints/best.ckpt

# 3. Import images
crackz import-images --project harbor-inspection --src ./photos --type raw --size 512 512

# 4. Run detection (uses the pre-trained model automatically)
crackz detect run --project harbor-inspection
```

```
# 1. Create project
crackz init --name custom-harbor

# 2. Import labeled training data
crackz import-images \
  --project custom-harbor \
  --src ./labeled/images \
  --src-masks ./labeled/masks \
  --type train \
  --size 512 512

# 3. Import validation data
crackz import-images \
  --project custom-harbor \
  --src ./labeled/val_imgs \
  --src-masks ./labeled/val_masks \
  --type val \
  --size 512 512

# 4. Train your custom model
crackz detect train --project custom-harbor --epochs 20

# 5. Run detection with your trained model
crackz detect run --project custom-harbor
```

```
my-first-project/  
├─ images/  
│  ├─ raw/      # Original images for detection  
│  ├─ train/    # Training images (if training a model)  
│  ├─ val/      # Validation images  
│  └─ test/     # Test images  
├─ masks/  
│  ├─ train/    # Ground truth masks for training  
│  ├─ val/      # Validation masks  
│  └─ test/     # Test masks  
├─ artifacts/  
│  ├─ training/ # Model checkpoints and training metrics  
│  └─ detections/ # Detection results (images + JSON)  
├─ logs/        # Project-specific logs  
└─ project.yaml # Configuration file
```

```
my-first-project/my-first-project_project.yaml
```

```
ai:  
  model:  
    threshold: 0.5 # Increase to 0.7 for fewer false positives  
                # Decrease to 0.3 to catch more cracks
```

```
# Process several inspection campaigns  
for project in site-A site-B site-C; do  
  crackz detect run --project $project  
done
```

```
# Run detection in container  
docker run --rm \  
  -v $(pwd)/my-first-project:/home/app \  
  ghcr.io/anaxiatech-ab/crackz:latest \  
  detect run --project /home/app
```

--	--	--	--

```
# Verify CUDA installation
nvidia-smi

# Check PyTorch CUDA support
python -c "import torch; print(torch.cuda.is_available())"


# Reinstall with CUDA support (see Installation Guide)
```

images/raw/ .jpg .jpeg .png .bmp .tif .tiff
project.yaml

```
# Reduce batch size
crackz detect train --project my-project --batch-size 1

# Or reduce image size during import
crackz import-images --project my-project --src ./data --type train --size 256 256
```

- _____
- _____
- _____
- _____
- _____



```
crackz init --name my-first-project
```

Installation

Installation

uv sync

LICENSE

-
-
-
-

gh auth login

curl -LsSf https://astral.sh/uv/install.sh | sh

irm https://astral.sh/uv/install.ps1 | iex

Login to GitHub
gh auth login

Download the latest wheel
gh release download --repo anaxiatech/crackz --pattern '*.whl'

Install with uv
uv pip install crackz-*.whl

Verify installation
crackz --version

crackz-VERSION-py3-none-any.whl

uv pip install crackz-VERSION-py3-none-any.whl

crackz

crackz-gui


```
# Using pip with GitHub authentication
pip install git+https://github.com/OWNER/crackz.git@vVERSION

# Or download the wheel from the private repository's Releases page
# (Requires GitHub authentication - use personal access token)
pip install https://USERNAME:TOKEN@github.com/OWNER/crackz/releases/download/vVERSION/crackz-VERSION-py3-none-any.whl
```

```
pip install git+https://github.com/OWNER/crackz.git
```

```
# Login with GitHub CLI
gh auth login

# Download release asset
gh release download vVERSION --repo OWNER/crackz --pattern '*.whl'

# Install the downloaded wheel
pip install crackz-VERSION-py3-none-any.whl
```

```
# Create a personal access token with 'repo' scope at:
# https://github.com/settings/tokens

# Set your token (keep it secure!)
export GITHUB_TOKEN="ghp_XXXXXXXXXX" # gitleaks:allow

# Install using token authentication
pip install git+https://${GITHUB_TOKEN}@github.com/OWNER/crackz.git@vVERSION
```

```
https://github.com/OWNER/crackz
crackz-VERSION-py3-none-any.whl
```

```
pip install crackz-VERSION-py3-none-any.whl
```

```
# Download wheel using GitHub token
curl -L \
  -H "Authorization: token ${GITHUB_TOKEN}" \
  -o crackz.whl \
  https://github.com/OWNER/crackz/releases/download/vVERSION/crackz-VERSION-py3-none-any.whl

# Install the downloaded wheel
pip install crackz.whl
```

```
# If your organization has configured a private index
pip install --index-url https://pypi.company.com/simple/ crackz
```

```
# Using the provided index URL and credentials
pip install crackz --index-url https://INDEX_URL/simple/

# Example with authentication (if required):
pip install crackz --index-url https://USERNAME:TOKEN@pypi.company.com/simple/
```

```
~/.config/pip/pip.conf
```

```
%APPDATA%\pip\pip.ini
```

```
[global]
index-url = https://USERNAME:TOKEN@pypi.company.com/simple/
```

```
pip install crackz
pip install --upgrade crackz # For updates
```

```
# Set credentials via environment variables
export PIP_INDEX_URL="https://pypi.company.com/simple/"
export PIP_EXTRA_INDEX_URL="https://pypi.org/simple" # Fallback to PyPI for dependencies

pip install crackz
```

```
https://dl.cloudsmith.io/TOKEN/org/repo/python/simple/
https://artifactory.company.com/artifactory/api/pypi/pypi-local/simple/
https://pypi.fury.io/TOKEN/USERNAME/
https://aws:TOKEN@domain.d.codeartifact.region.amazonaws.com/pypi/repo/simple/
https://pkgs.dev.azure.com/org/_packaging/feed/pypi/simple/ https://devpi.company.com/username/index/+simple/
```

```
chmod 600 ~/.config/pip/pip.conf # Linux/macOS
```

```
pip install --trusted-host pypi.company.com crackz
# Or add CA cert:
pip install --cert /path/to/ca-bundle.crt crackz
```

```
pip install crackz --extra-index-url https://pypi.org/simple/
```

crackz-gui.exe

crackz

crackz-gui

crackz

crackz-gui

crackz.exe

```
REM Download the executables from GitHub Releases
REM Move them to a permanent location
mkdir C:\Program Files\Crackz
move crackz.exe "C:\Program Files\Crackz\"
move crackz-gui.exe "C:\Program Files\Crackz\"

REM Add to PATH (optional, for CLI access from anywhere)
setx PATH "%PATH%;C:\Program Files\Crackz"
```

```
# Download the executables from GitHub Releases
chmod +x crackz crackz-gui

# Move to a system directory (optional)
sudo mv crackz /usr/local/bin/
sudo mv crackz-gui /usr/local/bin/

# Or keep in a local directory and add to PATH
mkdir -p ~/Applications/crackz
mv crackz crackz-gui ~/Applications/crackz/
echo 'export PATH="$HOME/Applications/crackz:$PATH"' >> ~/.bashrc
source ~/.bashrc
```

```
# Run CLI directly (no Python needed)
crackz --help
crackz init --name myproject

# Run GUI by double-clicking crackz-gui.exe (Windows)
# Or run from command line:
crackz-gui
```

cuda.exe

crackz-cuda.exe

crackz-gui-

```
crackz --help
python -c "import crackz; import importlib.metadata as m; print(m.version('crackz'))"
```

- crackz-VERSION-py3-none-any.whl
- crackz_cu118-VERSION-py3-none-any.whl
- crackz_cu128-VERSION-py3-none-any.whl

```
pip install https://github.com/Anaxiatech-AB/crackz/releases/download/vVERSION/crackz-VERSION-py3-none-any.whl
```

```
# Step 1: Install PyTorch with CUDA 11.8
pip install torch torchvision --index-url https://download.pytorch.org/whl/cu118

# Step 2: Install crackz CUDA variant
pip install https://github.com/Anaxiatech-AB/crackz/releases/download/vVERSION/crackz_cu118-VERSION-py3-none-any.whl
```

```
# Step 1: Install PyTorch with CUDA 12.8
pip install torch torchvision --index-url https://download.pytorch.org/whl/cu128

# Step 2: Install crackz CUDA variant
pip install https://github.com/Anaxiatech-AB/crackz/releases/download/vVERSION/crackz_cu128-VERSION-py3-none-any.whl
```

```
nvidia-smi
```

```
nvcc --version
# Or check driver
nvidia-smi | grep "CUDA Version"
```

crackz_cu118

crackz_cu128

crackz

```
# Login first
gh auth login

# Download and install CPU version (one step)
gh release download vVERSION --repo OWNER/crackz --pattern 'crackz-*.whl'
pip install crackz-VERSION-py3-none-any.whl
```

```
# Login first
gh auth login
```

```
# Step 1: Install PyTorch with CUDA 12.8
pip install torch torchvision --index-url https://download.pytorch.org/whl/cu128

# Step 2: Download and install crackz CUDA variant
gh release download vVERSION --repo OWNER/crackz --pattern 'crackz_cu128-*.whl'
pip install crackz_cu128-VERSION-py3-none-any.whl
```

```
# Check CUDA availability
python -c "import torch; print(f'CUDA available: {torch.cuda.is_available()}')"

# Check PyTorch version (should include +cu118 or +cu128 suffix)
python -c "import torch; print(f'PyTorch version: {torch.__version__}')"

# Check GPU device name
python -c "import torch; print(f'Device: {torch.cuda.get_device_name(0)} if torch.cuda.is_available() else \"CPU\"')"
```

```
CUDA available: True
PyTorch version: 2.5.0+cu128
Device: NVIDIA GeForce RTX 4090
```

```
# Step 1: Install specific PyTorch version
pip install torch torchvision --index-url https://download.pytorch.org/whl/cu121

# Step 2: Install crackz CUDA variant (cu118 or cu128, either works)
pip install https://github.com/Anaxiatech-AB/crackz/releases/download/vVERSION/crackz_cu118-VERSION-py3-none-any.whl
```

cpu cu128

```
# This installs CPU PyTorch even with the cu128 extra - BROKEN!
pip install "crackz-VERSION-py3-none-any.whl[cu128]"
```

```
# Step 1: Install PyTorch with CUDA
pip install torch torchvision --index-url https://download.pytorch.org/whl/cu128

# Step 2: Install crackz
pip install crackz_cu128-VERSION-py3-none-any.whl
```

keyring

```
# With uv
uv add keyring

# With pip
pip install keyring
```

```

from crackz_gui.state.secure_storage import (
    store_api_key,
    retrieve_api_key,
    is_secure_storage_available,
)

# Check availability
if is_secure_storage_available():
    store_api_key("your-api-key")
    api_key = retrieve_api_key()

```

1.

```

mkdir crackz_wheels
cd crackz_wheels

# Download Crackz wheel
wget https://github.com/Anaxiatech-AB/crackz/releases/download/vVERSION/crackz-VERSION-py3-none-any.whl

# Download all dependencies
pip download -r <(pip show -f crackz | grep Requires) -d .
# Or download from the wheel itself:
pip download crackz-VERSION-py3-none-any.whl -d .

```

2.

3.

```

pip install --no-index --find-links crackz_wheels crackz-VERSION-py3-none-any.whl

```

```

pip install .

```

```

pyproject.toml

```

```

# Download the new version from GitHub Releases
pip install --upgrade https://github.com/Anaxiatech-AB/crackz/releases/download/vNEW_VERSION/crackz-NEW_VERSION-py3-none-any.whl

# Or if using a private index:
pip install -U --index-url https://pypi.company.com/simple/ crackz

```

```

pip uninstall crackz

```

```

crackz --version
crackz init --name sanity-test
crackz detect run --project sanity-test # (Will use default config; may download model weights)

```

```
torch.__version__
```

```
No module named crackz
```

```
CUDA not available
```

```
torch.__version__
```

```
ModuleNotFoundError: No module named
'torch'
```

```
CRACKZ_LOG_DIR
```

```
pip install --force-reinstall crackz-VERSION.whl
```

```
pyproject.toml
```

```
# Check if CUDA is available
python -c "import torch; print(f'CUDA available: {torch.cuda.is_available()}')"
python -c "import torch; print(f'CUDA device: {torch.cuda.get_device_name(0)}')"
```

```
CUDA available: True
CUDA device: NVIDIA GeForce RTX 3080
```

```
# These commands automatically use GPU if available:
crackz detect train --project my_project
crackz detect run --project my_project
crackz-gui # GUI will use GPU automatically
```

```
cpu
```

```
cuda
```

```
mps
```

```
# Force GPU usage (will error if CUDA not available)
crackz detect train --project my_project --device cuda

# Force CPU usage (useful for debugging)
crackz detect train --project my_project --device cpu

# Let Crackz auto-detect (default)
crackz detect train --project my_project
```

```
<project>/<project>_project.yaml
```

```
ai:
  model:
    device: cuda # or cpu, or mps
```

```
crackz detect train --project my_project
```

```
GPU available: True, used: True
TPU available: False, using: 0 TPU cores
IPU available: False, using: 0 IPUs
HPU available: False, using: 0 HPUs
```

```
# NVIDIA GPUs
watch -n 1 nvidia-smi
```

```
# Should show Python process using GPU memory and compute
```

```
crackz_cu118-VERSION-py3-none-any.whl
```

```
crackz_cu128-VERSION-py3-none-any.whl
```

```
crackz_cu118-VERSION-py3-none-any.whl
```

```
nvcc --version # If CUDA toolkit installed
nvidia-smi # Shows driver version (different from CUDA toolkit)
```

1.

```
python -c "import torch; print(torch.__version__)"
# Should show: 2.5.0+cu118 or 2.5.0+cu128
# If it shows just 2.5.0, you have CPU-only version!
```

2.

```
pip uninstall torch torchvision
pip install torch torchvision --index-url https://download.pytorch.org/whl/cu118
```

3.

```
python -c "import torch; print(f'CUDA available: {torch.cuda.is_available()}')"
```

```
# GUI: Project → Settings → Training → Batch Size
```

```
# CLI:
```

```
crackz detect train --project my_project --batch-size 2
```

- `nvidia-smi`
-
-



```
CRACKZ_LOG_DIR=my_logs crackz detect run --project myproj
```

```
$Env:CRACKZ_LOG_DIR='my_logs'
```

- `pip install --require-hashes -r requirements.txt`
-

-
-
-

```
crackz migrate --project ./my_project # applies changes + backup
crackz migrate --project ./my_project --dry-run # preview only
```

```
CRACKZ_AUTO_MIGRATE=1
```

User Guide

User Guide

-
-
-
-
-
-

crackz detect train

crackz detect run

```
graph LR
  A[Create Project] --> B[Import Images]
  B --> C{Need Custom Model?}
  C -->|Yes| D[Train Model]
  C -->|No| E[Run Detection]
  D --> E
  E --> F[View Results]
  F --> G{Satisfied?}
  G -->|No| H[Adjust Config]
  H --> D
  G -->|Yes| I[Export/Package]
```

-
-
-

-
-

```
nvidia-smi
```

```
# Install from GitHub Release (replace VERSION with actual version)
pip install https://github.com/Anaxiatech-AB/crackz/releases/download/vVERSION/crackz-VERSION-py3-none-any.whl

# Or download first, then install
wget https://github.com/Anaxiatech-AB/crackz/releases/download/v0.30.2/crackz-0.30.2-py3-none-any.whl
pip install crackz-0.30.2-py3-none-any.whl

# Verify installation
crackz --help
```

```
# Install PyTorch with CUDA support first
pip install torch torchvision --index-url https://download.pytorch.org/whl/cu121

# Then install Crackz from GitHub Release
pip install https://github.com/Anaxiatech-AB/crackz/releases/download/vVERSION/crackz-VERSION-py3-none-any.whl
```

```
# CPU version
docker pull ghcr.io/anaxiatech-ab/crackz:latest

# GPU version (requires nvidia-docker)
docker pull ghcr.io/anaxiatech-ab/crackz:gpu

# Slim version (minimal runtime)
docker pull ghcr.io/anaxiatech-ab/crackz:slim
```

```
crackz --version
python -c "import crackz; print('Crackz installed successfully')"
```

```
crackz init --name my-first-project
cd my-first-project
```

```
my-first-project/
├── images/           # Image storage by split
│   ├── raw/         # Unprocessed images for inference
│   ├── train/       # Training images
│   ├── val/         # Validation images
│   └── test/        # Test images
├── masks/           # Ground truth masks (optional for raw)
│   ├── train/
│   ├── val/
│   └── test/
├── artifacts/       # Model outputs (metrics, plots)
├── detections/      # Detection results (annotated images, JSON)
├── models/          # Saved model weights (or checkpoints/ in older projects)
├── logs/            # Project-specific logs
└── project.yaml     # Project configuration
```

checkpoints/

models/

crackz migrate --project <project> --migrate-files

```
# Import sample images for detection (no training)
crackz import-images \
  --project my-first-project \
  --src ./samples \
  --type raw \
  --size 512 512
```

images/raw/

```
# Use pre-trained model
crackz detect run --project my-first-project
```

detections/

artifacts/metrics.json

```
# Import training images with masks
crackz import-images \
  --project my-first-project \
  --src ./training-data/images \
  --src-masks ./training-data/masks \
  --type train \
  --size 512 512
```

```
# Quick training (1 epoch for testing)
crackz detect train --project my-first-project --epochs 1 --batch-size 2
```

```
# Check detection outputs
ls my-first-project/detections/
```

```
# View metrics
cat my-first-project/artifacts/metrics.json
```

```
# Open annotated images
open my-first-project/detections/*.png # macOS
xdg-open my-first-project/detections/*.png # Linux
```

```
# Launch Streamlit dashboard for advanced analysis
crackz dashboard --project my-first-project
```

```
# Open project in GUI and launch dashboard
crackz-gui
# Then: Tools → Launch Dashboard
```

train/val/test/

images/

masks/

raw/

detections/

logs/

project.yaml

models/

artifacts/

checkpoints/

confusion_matrix.png

metrics.json

loss_curve.png

detections/

metrics.json

CRACKZ_LOG_DIR

<project>/logs/

Set central log directory
export CRACKZ_LOG_DIR=~/crackz-logs

Both central and project logs will be written
crackz detect run --project my-project

--debug--quiet

schema_version: "1.0"
project:
 name: my-project
 # ... rest of config

crackz migrate --project old-project

num_classes: 1

num_classes: 3

efficientnet-b3

efficientnet-b0
resnet34
efficientnet-b7
resnet50
resnet101
mobilenet_v2
resnet18
densenet121

```
<project>/<project>_project.yaml
```

```
ai:
  model:
    encoder: resnet34          # Choose encoder backbone
    encoder_weights: imagenet # Use transfer learning (recommended)
    in_channels: 3            # RGB images (use 1 for grayscale)
    num_classes: 1            # Binary segmentation
    threshold: 0.5            # Detection sensitivity (0.3=more sensitive, 0.7=less)

  training:
    epochs: 20                # Number of training iterations
    batch_size: 8              # Images per batch (reduce if out of memory)
    learning_rate: 0.001       # Optimizer learning rate
```

```
crackz model import --project ./my_project --model pretrained_model.zip
```

```
crackz model export --project ./my_project --out my_model.zip
```

```
project <name> project.yaml ai.model.encoder crackz detect train --
```

```
crackz init --name harbor-inspection-2025 --description "Q1 2025 harbor crack survey"
```

crackz-gui

```
# Create with custom settings
crackz init --name custom-project --force # Overwrite if exists

# Initialize from template (future)
crackz init --name new-project --template harbor-config.yaml
```

```
crackz import-images \
--project harbor-inspection-2025 \
--src ~/Pictures/harbor-photos \
--type raw \
--size 512 512
```

```
crackz import-images \
--project harbor-inspection-2025 \
--src ~/labeled-data/images \
--src-masks ~/labeled-data/masks \
--type train \
--size 512 512
```

```
# Training data
crackz import-images --project my-project --src train_imgs --src-masks train_masks --type train --size 512 512

# Validation data
crackz import-images --project my-project --src val_imgs --src-masks val_masks --type val --size 512 512

# Test data
crackz import-images --project my-project --src test_imgs --src-masks test_masks --type test --size 512 512
```

`.jpg` `.jpeg` `.png` `.bmp` `.tif` `.tiff` `.png`

crackz-gui

images/train/

B

E

masks/train/

•

-
-
-
-
-

B

E

Ctrl+Z

B E Ctrl+Z

--	--	--

```
crackz detect train --project my-project
```

```
crackz detect train \  
--project my-project \  
--epochs 20 \  
--batch-size 8 \  
--learning-rate 0.001
```

project.yaml

```
# Automatically uses GPU if available  
crackz detect train --project my-project --epochs 50  
  
# Verify GPU is being used (check logs)  
tail -f my-project/logs/crackz.log | grep -i cuda
```

```
# Watch loss in real-time  
tail -f my-project/artifacts/metrics.json  
  
# Or use TensorBoard (if enabled)  
tensorboard --logdir my-project/artifacts/tensorboard
```

project.yaml

```
crackz detect run --project my-project
```

```
# Uses GPU automatically if available
crackz detect run --project my-project

# Force CPU (even with GPU available)
CUDA_VISIBLE_DEVICES="" crackz detect run --project my-project
```

```
--model
```

```
# Auto-select (default): best.ckpt > last.ckpt > final.ckpt
crackz detect run --project my-project

# Explicitly use best checkpoint
crackz detect run --project my-project --model best

# Use most recent checkpoint (useful during iterative development)
crackz detect run --project my-project --model last

# Use final checkpoint
crackz detect run --project my-project --model final

# Use specific epoch checkpoint (e.g., epoch-0.9234.ckpt)
crackz detect run --project my-project --model epoch-0.9234
```

```
--model
```

```
--model last
```

```
--model best
```

```
--model final
```

```
--model epoch-X
```

```
# Run detection with different checkpoints to compare results
crackz detect run --project my-project --model best
mv my-project/detections my-project/detections-best

crackz detect run --project my-project --model last
mv my-project/detections my-project/detections-last

crackz detect run --project my-project --model epoch-0.8532
mv my-project/detections my-project/detections-epoch-0.8532

# Compare detection outputs side by side
```

```
# Detect on raw images (default)
crackz detect run --project my-project

# Detect on test set (with metrics if masks available)
crackz detect run --project my-project --split test
```

```
# Process multiple projects
for project in project1 project2 project3; do
  crackz detect run --project $project
done
```

```
# CPU
docker run --rm \
  -v $(pwd)/my-project:/home/app/my-project \
  ghcr.io/anaxiatech-ab/crackz-cli:latest \
  detect run --project /home/app/my-project

# GPU
docker run --gpus all --rm \
  -v $(pwd)/my-project:/home/app/my-project \
  ghcr.io/anaxiatech-ab/crackz-cli:gpu \
  detect run --project /home/app/my-project
```

```
project.yaml
```

```
training:
  tensorboard: true
```

```
# tensorboard-config.yaml
training:
  tensorboard: true
```



```
# After training with tensorboard enabled
tensorboard --logdir my-project/artifacts/tensorboard

# Open browser to http://localhost:6006
```

```
# Quick summary
cat my-project/artifacts/metrics.json | python -m json.tool

# Extract specific metrics
cat my-project/artifacts/metrics.json | jq '.final_val_iou'
```

```
crackz clean --project my-project --dry-run
```

```
crackz clean --project my-project
```

```
crackz clean --project my-project --logs-only
```

```
*.log
```

```
project.yaml
```

```
training:
  checkpoint:
    save_top_k: 3 # Keep top 3 checkpoints by validation loss
```

```
# Remove all but the last checkpoint
rm my-project/checkpoints/*.ckpt
# (except last-*.ckpt)

# Or keep only best checkpoint
rm my-project/checkpoints/epoch*.ckpt
# (keep best-*.ckpt)
```

```
# Train on 50-100 manually labeled images
crackz detect train --project harbor-project --epochs 10
```

```
# Prioritize top 50 images from raw/unlabeled pool
uv run crackz active-learning run \
  --project harbor-project \
  --split raw \
  --top-n 50 \
  --method entropy \
  --out priorities.json
```

variance

entropy

mean_confidence

max_probability

```
# Use GUI mask editor or external tools
# Focus on top-ranked images from priorities.json
```

```
# Move annotated images to train split
crackz import-images --project harbor-project \
  --src annotated_batch \
  --src-masks annotated_masks \
  --type train

# Retrain with expanded dataset
crackz detect train --project harbor-project --epochs 15
```

wall_section_01.jpg

```
# Preview similarity scores
uv run crackz propagate-masks find-similar \
  --project harbor-project \
  --reference wall_section_01.jpg \
  --split raw \
  --out similarities.json
```

```
# Copy mask to similar images (>80% similarity)
uv run crackz propagate-masks run \
  --project harbor-project \
  --reference wall_section_01.jpg \
  --mask wall_section_01_mask.png \
  --split raw \
  --threshold 0.8 \
  --out propagated_masks/
```

```
# Import propagated masks
crackz import-images --project harbor-project \
  --src images_with_propagated \
  --src-masks propagated_masks \
  --type train

# Review in GUI mask editor - correct errors before training
```

```
# More permissive (more propagations, less reliable)
--threshold 0.6 --min-matches 5

# Stricter (fewer propagations, higher quality)
--threshold 0.9 --min-matches 20 --sift
```

```
crackz detect train --project harbor-project
```

```
uv run crackz active-learning run \
  --project harbor-project \
  --top-n 20 \
  --method entropy \
  --out uncertain.json
```

```
# For each reference image
uv run crackz propagate-masks run \
  --reference refl.jpg --mask refl_mask.png \
  --project harbor-project --threshold 0.8

# Propagate remaining references...
```

```
# Import all propagated masks
crackz import-images --project harbor-project \
  --src propagated_images \
  --src-masks propagated_masks \
  --type train

# Retrain with 50 original + ~40 propagated = 90 annotations
crackz detect train --project harbor-project --epochs 15
```

```
crackz export-config \
  --project my-project \
  --out my-project-snapshot.yaml
```

```
# Create archive (excluding large files)
tar -czf my-project.tar.gz \
  --exclude='checkpoints' \
  --exclude='detections' \
  my-project/

# Send to collaborator
# They extract and run:
tar -xzf my-project.tar.gz
crackz detect run --project my-project # Downloads default checkpoint if missing
```

```
latest
slim
gpu
```

```
# Full image
docker build -t crackz-cli .

# Slim image
docker build -f Dockerfile.slim -t crackz-cli:slim .

# GPU image
docker build -f Dockerfile.gpu -t crackz-cli:gpu .
```

```
# CPU
docker run --rm \
-v $(pwd)/my-project:/home/app/my-project \
crackz-cli detect run --project /home/app

# GPU
docker run --gpus all --rm \
-v $(pwd)/my-project:/home/app/my-project \
crackz-cli:gpu detect run --project /home/app
```

```
docker run -it --rm \
-v $(pwd)/my-project:/home/app/my-project \
crackz-cli bash
```

Makefile

```
# Build documentation
make docs

# Run tests
make test

# Build Docker image
make docker-build

# Clean artifacts
make clean
```

```
# Add to $PROFILE
function Invoke-Crackz {
    docker run --rm -v $(pwd):/home/app ghcr.io/anaxiatech-ab/crackz-cli:latest @args
}
Set-Alias crackz Invoke-Crackz

# Usage
crackz detect run --project /home/app/my-project
```

```
# process-all.ps1
$projects = Get-ChildItem -Directory -Filter "*-project"
foreach ($project in $projects) {
    Write-Host "Processing $($project.Name)..."
    crackz detect run --project $project.FullName
}
```

```
crackz-gui
```

```
python -m crackz_gui.qt.app
```

`project.yaml``images/raw``detections/`

-
-
-

```
# Install from GitHub Release
pip install https://github.com/Anaxiatech-AB/crackz/releases/download/vVERSION/crackz-VERSION-py3-none-any.whl
crackz init --name local-project
```

```
docker pull ghcr.io/anaxiatech-ab/crackz-cli:latest
docker run --rm -v $(pwd)/project:/home/app crackz-cli detect run --project /home/app
```

```
# Create Batch pool
./scripts/azure/azure_batch.sh \
  --batch-account myaccount \
  --storage-account mystorage
```

```
# Submit job
./scripts/azure/submit_batch_job.sh \
--project my-project \
--pool-id crackz-pool
```

Solution:

```
# Update pip and setuptools
pip install --upgrade pip setuptools

# Download and install from GitHub Release
wget https://github.com/Anaxiatech-AB/crackz/releases/download/vVERSION/crackz-VERSION-py3-none-any.whl
pip install crackz-VERSION-py3-none-any.whl
```

Solution:

```
# Verify CUDA installation
nvidia-smi

# Check PyTorch CUDA support
python -c "import torch; print(torch.cuda.is_available())"

# Reinstall PyTorch with CUDA
pip uninstall torch torchvision
pip install torch torchvision --index-url https://download.pytorch.org/whl/cu121
```

No images found in training split

Solution:

```
images/train/      images/raw/      .jpg .jpeg .png .bmp .tif .tiff
--type train
```

Solution:

```
masks/train/
```

Solution:

```
# Reduce batch size
crackz detect train --project my-project --batch-size 1

# Or reduce image size
crackz import-images --project my-project --src ./data --type train --size 256 256

# Monitor GPU memory
nvidia-smi -l 1 # Update every second
```

Solution:

```
tail my-project/logs/crackz.log      raw/
ls my-project/models/      my-project/checkpoints/      crackz detect run --project my-project --debug
```

Solution: project.yaml

```
detection:
  threshold: 0.5 # Pixel-level binarization threshold
                # Increase to reduce false positives (0.7)
                # Decrease to catch more cracks (0.3)

# Severity categorization thresholds (crack area %)
min_confidence: 0.005 # Min to save (0.5% crack area)
medium_confidence: 0.02 # "Probable Crack" threshold (2%)
high_confidence: 0.05 # "Crack Detected" threshold (5%)
min_crack_area_px: 100 # Filter out detections < 100 pixels
```

Solution:

```
# Check permissions
ls -la $(python -c "import tempfile; print(tempfile.gettempdir())")/crackz_logs

# Set explicit log directory
export CRACKZ_LOG_DIR=~/.crackz-logs
mkdir -p ~/.crackz-logs
crackz detect run --project my-project
```

Solution:

```
# Clean old logs
rm -rf $CRACKZ_LOG_DIR/*.log

# Or set retention policy (future feature)
# See configuration.md for log rotation settings
```

Missing --project or --cfg	--project <name>	--cfg <file>
CUDA out of memory	--batch-size	
Schema version mismatch	crackz migrate --project <name>	
Permission denied writing logs		CRACKZ_LOG_DIR
No checkpoint found	crackz detect train --project <name>	



<project>/logs/ \$CRACKZ_LOG_DIR /tmp/crackz_logs

```
crackz detect train --project my-project --epochs 50 --batch-size 8
```

project.yaml

```
crackz detect run --cfg my-custom-config.yaml
```

```
crackz export-config --project my-project --out snapshot.yaml
crackz detect run --cfg snapshot.yaml
```

.jpg .jpeg .png .bmp .tif .tiff

segmentation-models-pytorch
--checkpoint <path>

project.yaml model.encoder

512 512 --batch-size mobilenet_v2 resnet50 --size 256 256

&

```
for p in project1 project2 project3; do
  crackz detect run --project $p &
done
wait
```

CRACKZ_LOG_DIR

.ckpt

project.yaml

raw train val test

1. _____
2. _____
3. _____

1. _____
2. _____
3. _____

1. _____
2. _____
3. _____

1. _____
2. _____
3. _____

• _____
• _____
• _____

Crackz User Guide v1.0 · Copyright © 2025 Theresia Sofia Snow · Commercial Software

CLI Cookbook

CLI Cookbook

```
crackz init --name demo-project
```

```
demo-project/
images/
  raw/ train/ val/ test/
masks/
artifacts/
detections/
checkpoints/
project.yaml
```

- `crackz --help` `--help`
- `--project` `--cfg`
- `--debug` `--quiet`
-

```
crackz init --name demo-project
```

```
crackz init --name demo-project --force
```

```
# Preview what will be cleaned (safe)
crackz clean --project demo-project --dry-run

# Clean logs and artifacts
crackz clean --project demo-project

# Clean only logs, keep checkpoints and detections
crackz clean --project demo-project --logs-only
```

```
--logs-only *.log --logs-only
```

```
--type
```

```
crackz import-images \
--project demo-project \
--src ./samples \
--type raw \
--size 512 512 \
--quality 90
```

```
crackz import-images --project demo-project --src ./samples --type train --size 512 512
crackz import-images --project demo-project --src ./samples --type val --size 512 512
crackz import-images --project demo-project --src ./samples --type test --size 512 512
```

```
crackz import-images \
--project demo-project \
--src ./samples \
--split \
--train-ratio 0.7 \
--val-ratio 0.15 \
--test-ratio 0.15 \
--size 512 512
```

```
--split
```

```
--split
```

```
--type
```

```
--random-seed
```

```
crackz import-images --project demo-project --src ./samples --split --random-seed 42
```

```
--src/masks
```

```
crackz import-images --project demo-project --src ./samples --masks_src ./samples/masks --type train
```

```
crackz import-images --project demo-project --src ./samples --type train --overwrite
```

```
train
```

```
images/train  
train/
```

```
val test  
crackz detect train
```

```
raw/  
--split
```

```
--type
```

```
scripts/import_masks.py
```

```
# Basic usage - import from organized mask directories
```

```
python scripts/import_masks.py <project_dir> <masks_source_dir>
```

```
# Example: Import masks for skytteren_projekt from smasks directory
```

```
python scripts/import_masks.py ./skytteren_projekt ./smasks
```

```
# Custom size and quality
```

```
python scripts/import_masks.py ./my_project ./mask_sources --size 1024 1024 --quality 95
```

```
masks_source_dir
```

```
masks_source_dir/  
train/  
mask_001.jpg  
mask_002.png  
...  
val/  
mask_101.jpg  
...  
test/  
mask_201.png  
...
```

```
data.mask_threshold  
_mask
```

```
--size WIDTH HEIGHT
```

```
--quality QUALITY
```

```
data.mask_threshold
```

```
val/
```

```
# Basic usage - edit an image (mask path auto-derived)
```

```
crackz masks edit images/train/crack_001.jpg
```

```
# With custom mask path
```

```
crackz masks edit photo.jpg --mask output/my_mask.png
```

```
# With project context (smart path derivation)
```

```
crackz masks edit images/raw/inspection.jpg --project my_harbor_project
```

```
--mask
```

1.

```
--project
```

```
Image: project/images/train/crack_001.jpg
```

```
Mask: project/masks/train/crack_001.png ← Auto-derived
```

2.

```
Image: data/images/train/photo.jpg
```

```
Mask: data/masks/train/photo.png ← Auto-derived
```

3.

```
Image: /tmp/photo.jpg
```

```
Mask: /tmp/masks/photo.png ← Auto-derived
```

pyside6

```
for img in images/train/*.jpg; do
    crackz masks edit "$img" --project my_project
done
```

```
ssh -X user@server
```

```
crackz masks edit /data/harbor/crack.jpg
```

```
# Convert all masks in a project (uses project threshold)
crackz masks convert --project my_harbor_project
```

```
# Convert with custom threshold
```

```
crackz masks convert --project my_harbor_project --threshold 128
```

-
- train val test raw
- raw/

1. train val test image_01.jpg
image_01.png
2. raw/
3. crackz detect train
4. crackz detect run --project <p> raw/
5. test

```
--type train
```

```
train val test
```

1. labelme labelme
 2. pip install labelme
 3. image_001.png images/train/image_001.jpg
 4. masks/train/image_001.png masks/<split>/ masks/train/ masks/val/ masks/test/
 - 5.
 - 6.
 7. crackz import-images --masks_src masks/
- ```
--split
```

```
cv2.threshold
```

```
crackz detect run --project demo-project
```

```
--project
```

```
crackz detect run --cfg config/detect.yaml
```

```
best.ckpt last.ckpt final.ckpt
```

```
--model
```

```
Use specific checkpoint by name
crackz detect run --project demo-project --model best
crackz detect run --project demo-project --model last
crackz detect run --project demo-project --model final

Use specific epoch checkpoint (e.g., epoch-0.9234.ckpt)
crackz detect run --project demo-project --model epoch-0.9234
```

```
--model
final.ckpt
```

```
best.ckpt
```

```
last.ckpt
```

```
--model last
```

```
--model best
```

```
--model epoch-X
```

```
crackz detect train --project demo-project
train/val/test
```

```
crackz detect train --project demo-project --epochs 1 --batch-size 1
```

```
Auto-selects best checkpoint, outputs to <project-name>_model.zip
crackz model export --project demo-project

Specify output path
crackz model export --project demo-project --out models/harbor_v1.zip

Export specific checkpoint (best, last, or final)
crackz model export --project demo-project --checkpoint best --out best_model.zip
```

```
crackz model export -p demo-project -o my_model.zip
crackz model export -p demo-project -c final -o final_model.zip
```

```
.ckpt
```

```
best.ckpt last.ckpt final.ckpt
```

```
<project_name>_model.zip --out
```

```
Import model package
crackz model import --project demo-project --model harbor_v1.zip

Overwrite existing checkpoint with same name
crackz model import --project demo-project --model harbor_v1.zip --force
```

```
crackz model import -p demo-project -m my_model.zip
crackz model import -p demo-project -m my_model.zip --force
```

```
checkpoints/
```

```
--force
```

```
Team member A: Export trained model
crackz model export -p training-project -o shared/harbor_crack_v1.zip

Team member B: Import into their project
crackz model import -p deployment-project -m shared/harbor_crack_v1.zip
```

```
Export base model trained on general cracks
crackz model export -p general-cracks -o pretrained/base_model.zip

Import into specialized project for fine-tuning
crackz model import -p harbor-specific -m pretrained/base_model.zip

Fine-tune on harbor-specific data
crackz detect train -p harbor-specific --epochs 10
```

```
Backup current best model before trying new hyperparameters
crackz model export -p demo-project -c best -o backups/before_experiment.zip

Run experiment
crackz detect train -p demo-project --epochs 50

If results are worse, can import the backup
crackz model import -p demo-project -m backups/before_experiment.zip --force
```

```
Export with timestamp
crackz model export -p demo-project -o models/model_2025-10-11.zip

Or use git-style versioning
crackz model export -p demo-project -o models/v1.0.0.zip
```

```
Export from training environment
crackz model export -p training-project -o production/model.zip

Transfer to production server and import
crackz model import -p production-project -m production/model.zip

Run detection in production
crackz detect run -p production-project
```

<checkpoint\_name>.ckpt

metadata.json

```
Linux/Mac
unzip -l my_model.zip

Windows PowerShell
Expand-Archive -Path my_model.zip -DestinationPath temp -Force
cat temp\metadata.json
```

metadata.json

```
{
 "project_name": "harbor_detection",
 "checkpoint_name": "best.ckpt",
 "model_config": {
 "encoder": "resnet34",
 "encoder_weights": "imagenet",
 "in_channels": 3,
 "num_classes": 1,
 "threshold": 0.5,
 "loss_name": "combo",
 "dice_weight": 0.7,
 "focal_weight": 0.3
 }
}
```

```
Generate map for raw split (default)
crackz geo create-map --project demo-project --output harbor_map.html

Map for specific split (train/val/test)
crackz geo create-map --project demo-project --output train_map.html --split train
```

```
crackz geo create-map -p demo-project -o map.html -s raw
```

```
Export all images with GPS data
crackz geo export-geojson --project demo-project --output detections.geojson

Export specific split
crackz geo export-geojson --project demo-project --output train.geojson --split train
```

```
crackz geo export-geojson -p demo-project -o data.geojson -s raw
```

```
{
 "type": "FeatureCollection",
 "features": [
 {
 "type": "Feature",
 "geometry": {
 "type": "Point",
 "coordinates": [longitude, latitude]
 },
 "properties": {
 "image_name": "IMG_0001.jpg",
 "image_path": "/path/to/image.jpg",
 "has_detection": true,
 "latitude": 59.123456,
 "longitude": 10.123456
 }
 }
],
 "metadata": {
 "project": "demo-project",
 "split": "raw",
 "total_images": 42,
 "images_with_detections": 15
 }
}
```

```
Linux/Mac
exiftool image.jpg | grep GPS

Python (Pillow)
from PIL import Image
img = Image.open("image.jpg")
exif = img.getexif()
gps_ifd = exif.get_ifd(0x8825) # 0x8825 is GPS IFD tag
print(gps_ifd)
```

```
1. Import drone photos (GPS data preserved in EXIF)
crackz import-images --project harbor --src ./drone_photos --type raw --size 512 512

2. Run detection
crackz detect run --project harbor

3. Generate map to visualize results
```



```
crackz geo create-map --project harbor --output harbor_results.html

4. Export to GeoJSON for GIS analysis
crackz geo export-geojson --project harbor --output harbor.geojson

5. Open map in browser to review
(or import GeoJSON into QGIS/ArcGIS)
```

```
crackz --debug detect run --project demo-project
crackz --quiet detect run --project demo-project
crackz --log-dir run_logs detect run --project demo-project
```

```
CRACKZ_LOG_DIR=logs_debug crackz detect run --project demo-project
```

```
--debug
```

```
Start training
crackz detect train --project demo-project

Press Ctrl+C to cancel at any time
The operation will be cancelled gracefully
Partial results (e.g., checkpoints) are preserved
```

```
crackz detect run --cfg configs/detect.yaml
crackz detect train --cfg configs/train.yaml
```

```
for P in demo-project other-project; do
 crackz detect run --project "$P" || echo "Failed: $P" >&2
done
```

```
/home/app
```

```
Init project (host ./project mapped to /home/app)
mkdir -p project
docker run --rm -v %cd%\project:/home/app crackz-cli init --name demo-project

Import images (mount samples to /data)
docker run --rm -v %cd%\project:/home/app -v %cd%\samples:/data \
 crackz-cli import-images --project /home/app/demo-project --src /data --type raw --size 512 512

Detection
docker run --rm -v %cd%\project:/home/app crackz-cli detect run --project /home/app/demo-project
```

```
docker run --gpus all --rm -v %cd%\project:/home/app crackz-cli:gpu detect run --project /home/app/demo-project
```

`--project --cfg``--src``images/train``raw``torch.cuda.is_available()`

```
Generate report with default name (project_name_report.docx)
crackz report generate --project demo-project

Specify custom output path
crackz report generate --project demo-project --output inspection_report.docx

Use config file instead of project path
crackz report generate --cfg project.yaml --output report.docx
```

`crackz detect run`

```
Find top 50 most uncertain images
uv run crackz active-learning run \
 --project demo-project \
 --top-n 50 \
 --method entropy \
 --out priorities.json
```

entropy  
variance

`mean_confidence``max_probability``uv run crackz active-learning info`

```
Prioritize images in 'raw' split (default)
uv run crackz active-learning run --project demo-project --split raw

Prioritize images in 'train' split
uv run crackz active-learning run --project demo-project --split train
```

```
{
 "method": "entropy",
 "total_images": 500,
 "prioritized_count": 50,
 "images": [
 {
 "path": "image_042.jpg",
 "uncertainty_score": 0.8234,
 "rank": 1
 }
]
}
```

```

}
}

```

```

Find similar images and propagate mask
uv run crackz propagate-masks run \
 --project demo-project \
 --reference wall_01.jpg \
 --mask wall_01_mask.png \
 --split raw \
 --threshold 0.8 \
 --out ./propagated_masks

```

```

sift --orb --threshold --min-matches --

```

```

uv run crackz propagate-masks find-similar \
 --project demo-project \
 --reference wall_01.jpg \
 --split raw \
 --out similarities.json

```

```

More permissive matching (more propagations, less accurate)
uv run crackz propagate-masks run \
 --reference ref.jpg \
 --mask ref.png \
 --project demo-project \
 --threshold 0.6 \
 --min-matches 5

Stricter matching (fewer propagations, more reliable)
uv run crackz propagate-masks run \
 --reference ref.jpg \
 --mask ref.png \
 --project demo-project \
 --threshold 0.9 \
 --min-matches 20 \
 --sift

```

```

uv run crackz propagate-masks run \
 --reference ref.jpg \
 --mask ref.png \
 --project demo-project \
 --orb

```

- [api.md](#) [detect\(\)](#) [train\(\)](#)

---

[crackz export-config](#)

## GUI

---


# GUI Guide

```
crackz-gui
```

```
After installing Crackz
crackz-gui
```

```
gui crackz-gui.exe ./crackz-
```


```
uv run python scripts/capture_qt_screenshots.py --project oslo_project
```




- 1.
- 2.
- 3.
- 4.

- 1.
- 2.
- 3.

project.yaml



•  
•  
•  
•  
•  
•



A macOS-style settings dialog box titled "Settings: test\_project". It features a tabbed interface with tabs for "Project", "Paths", "Logging", "Data", "AI · Model", "AI · Training", and "AI · Detection". The "Project" tab is selected. Below the tabs, there are two text input fields: "Name" (containing "test\_project") and "Description" (empty). At the bottom, there are three blue buttons: "Reload", "Save", and "Cancel".


Settings: test\_project

Project Paths Logging Data AI · Model AI · Training AI · Detection

Name test\_project

Description

Reload Save Cancel



Settings: test\_project

Project Paths Logging Data AI · Model AI · Training

Encoder

resnet34

Encoder Weights

imagenet

Device

mps

 Recommended: 'mps' - Apple Silicon GPU detected! Up to 5-20x faster than CPU.

Available devices: cpu, mps

Input Channels

3

Num Classes

1

Checkpoint Path

Threshold

0.5

Norm Mean (comma)

0.485,0.456,0.406

Norm Std (comma)

0.229,0.224,0.225

Loss Function

combo

Dice Weight

0.7

Focal Weight

0.3

Input Size (width,height)

512,512

Reload

Save

Cancel





Settings: test\_project

Project Paths Logging Data AI · Model AI · Training AI · Detection

|                                    |                                     |
|------------------------------------|-------------------------------------|
| Batch Size                         | 2                                   |
| Num Workers                        | 4                                   |
| Epochs                             | 2                                   |
| Learning Rate                      | 0.001                               |
| Shuffle (True/False)               | True                                |
| Loss                               |                                     |
| Metrics                            |                                     |
| Enable TensorBoard                 | <input type="checkbox"/>            |
| Random Seed (optional)             |                                     |
| Precision (optional)               |                                     |
| Devices (optional)                 |                                     |
| Strategy (optional)                |                                     |
| Save Top K Checkpoints             | 1                                   |
| Save Last Checkpoint               | <input checked="" type="checkbox"/> |
| Auto-Prune After Training          | <input type="checkbox"/>            |
| Checkpoints to Keep (when pruning) | 3                                   |

ReloadSaveCancel

⋮

Settings: test\_project

ProjectPathsLoggingDataAI · ModelAI · TrainingAI · Detection

Threshold

0.5

Learning Rate

0.001

Batch Size

8

Shuffle (True/False)


True


Output Dir Name


detections

Random Seed (optional)

ReloadSaveCancel









## AI Model

|                  |         |
|------------------|---------|
| Encoder:         | resnet3 |
| Encoder Weights: | imagen  |
| Device:          | mps     |
| Input Size:      | 512 x 5 |
| Threshold:       | 0.50    |
| Loss Function:   | combo   |



## Training Configuration

|                |                                           |
|----------------|-------------------------------------------|
| Batch Size:    | 2                                         |
| Epochs:        | 2                                         |
| Learning Rate: | 0.00100                                   |
| Workers:       | 4                                         |
| TensorBoard:   | <input checked="" type="checkbox"/> Disab |
| Shuffle:       | Yes                                       |

Project: /Users/tess/Project/subbaltica/crackz/test\_project

- 1.
- 2.
- 3.
- 4.
- 5.
- 6.

- 1.
- 2.
- 3.
- 4.
- 5.
- 6.



Import Images with Split



## Import Images with Automatic Split

Select a source directory with images and masks.  
They will be automatically split into train/val/test sets based on the ratios below.

### Source Directory:

Select a directory containing images/ and optionally masks/ subdirectories.  
Masks will be automatically matched to images by filename.

No directory selected

 Select Source Directory...

### Split Ratios (auto-adjusting)

Train:

Validation:

Test:

Total: 1.00 ✓

### Random Seed (Optional)

Set a seed for reproducible splits

Import

Cancel

Import Images with Split

Split Ratios (auto-adjusting)

Train: 0.7

Validation: 0.1

Test: 0.2

Total: 1.00 ✓

Random Seed (Optional)

Set a seed for reproducible splits

☐ Use random seed:

Image Processing Settings


Image Size (width x height):

x  pixels

Image Quality: 0.9

Import

Cancel



Page 1 of 1

 Previous

Project: /Users/tess/Project/subbaltica/crackz/test\_project

images/

images/

images/

masks/

- 
- 
- 
- 
- 



B  
E  
Ctrl+Z    Cmd+Z  
Ctrl+Y    Cmd+Shift+Z  
  
Ctrl+S    Cmd+S  
Esc

```
project/
├── images/
│ └── train/
│ └── crack_001.jpg # Original image
├── masks/
│ └── train/
│ └── crack_001.png # Binary mask (auto-created)
```

---

- 1.
- 2.
- 3.
- 4.



- 1.
- 2.
- 3.
- 4.
- 5.

- 
- 
- 
- 
- 
- 
- 

|  |   |  |
|--|---|--|
|  |   |  |
|  | A |  |
|  | R |  |
|  | E |  |

|  |             |  |
|--|-------------|--|
|  |             |  |
|  | Right Arrow |  |
|  | Left Arrow  |  |

masks/

- 
- 
- 

R

E

A

---

raw/


raw/


```
Move annotated images from raw to train split
crackz move-images --project ./my-project --source raw --target train --pattern "crack_*.jpg"
```

images/raw/  
train val test


---


1.






- 1.
  - 2.
  - 3.
  - 4.
- raw








- 
- 1.
  - 2.
  - 3.
  - 4.





- 1.
- 2.
- 3.
- 4.

.ckpt

Import Model Package: test\_project

 **Import Model Package**

Import a trained model checkpoint from a package file

**Select model package file:**

Browse...


**Package Information:**

Select a model package file to view details...

☐ Overwrite existing checkpoint if it exists

- 1.
- 2.
- 3.
- 4.

- 5.
- 6.





## System Information


Operating System: Darwin 25.0.0  
Python: 3.13.7



Recommended: 'mps' - Apple Silicon

Note: Device can be selected in project settings

Project: /Users/tess/Project/subbaltica/crackz/test\_project



- 1.
- 2.

Project Info - test\_project

 **test\_project**

 **Project Details**

**Name:**

test project

**Description:**

N/A

**Created:**

2025-09-30 08:38

**Schema Version:**

2

 **Paths**

**Project Path:**

/Users/tess/Project/subbaltica/crackz/test project


**Images:**

/Users/tess/Project/subbaltica/crackz/test project/images

 Settings

Clo








Project: /Users/tess/Project/subbaltica/crackz/test\_project

- 
- 1.
  - 2.
  - 3.





- 
- 1.
  - 2.
  - 3.
  - 4.
  - 5.
  - 6.
  - 7.

- 
- 
- 
- 
-

~

\$

---

- 
- 
- 
- 

\$ ~ Cmd/Ctrl+/

assets/gui/chat\_history\_panel.png

assets/gui/chat\_prompt\_templates\_panel.png

~/.crackz/chat\_history.db

---

```
Check installation
python -c "from PySide6.QtWidgets import QApplication; print('PySide6 OK')"
```

```
Launch with debug output
crackz-gui --debug
```

- 
- 
- 

- 
- 

CRACKZ\_LOG\_DIR/gui\_app.log

<project>/logs/gui\_operations.log

---

```
Create and configure in GUI
crackz-gui
```

```
Batch process via CLI
crackz detect run --project my-project --batch-size 16
```

```
Review results in GUI
crackz-gui
```

- 
- 
- 
- 

# Dashboard



# Streamlit Dashboard

app

 Detection Results

 GPS Map

 Training Metrics

 Parameter Tuning

Project Selection

Project Path

oslo\_project

✓ Loaded: oslo\_project

Navigation

Use the sidebar to navigate between:

 **Detection Results** -

View crack detections

 **GPS Map** -

Geographic visualization

 **Training Metrics** -

Compare training runs

 **Parameter Tuning** -

Adjust detection settings



## Crackz - Crack Detection Dashboard

AI-powered analysis for harbor and bridge inspection

### Project Overview

Project Name

oslo\_project

Crackz Version

0.58.0

 Use the **Pages** menu in the sidebar to navigate to different views

app

 **Detection Results**

 GPS Map

 Training Metrics

 Parameter Tuning



# Detection Results

View crack detection results with visualizations and statistics

 No project loaded. Please select a project from the home page.

app

 Detection Results

 **GPS Map**

 Training Metrics

 Parameter Tuning



# GPS Map Visualization

View crack detections on an interactive map

 No project loaded. Please select a project from the home page.

app

 Detection Results

 GPS Map

 **Training Metrics**

 Parameter Tuning



# Training Metrics

Monitor training progress and model performance

 No project loaded. Please select a project from the home page.

app

 Detection Results

 GPS Map

 Training Metrics

 **Parameter Tuning**



# Parameter Tuning

Interactively adjust detection parameters and preview results

 No project loaded. Please select a project from the home page.

•  
•  
•  
•  
•

```
Launch with a specific project
crackz dashboard --project my-project

Launch with custom port
crackz dashboard --project my-project --port 8502
```

1. `crackz-gui`
- 2.
- 3.
- 4.
- 5.
- 6.

```
streamlit run core/src/crackz/dashboard/app.py -- --project my-project
```

```
from crackz.dashboard import launch_dashboard
launch_dashboard(project_name="my-project", port=8501)
```

```
crackz geo extract-gps --project <name>
```

```
artifacts/training/training_metrics.json
```

```
crackz train --project <name>
```

```
core/src/crackz/dashboard/
├── init .py # Launch function
├── app.py # Main dashboard app
├── pages/ # Dashboard pages
│ ├── 1_0_Detection_Results.py
│ ├── 2_0_GPS_Map.py
│ ├── 3_0_Training_Metrics.py
│ └── 4_0_Parameter_Tuning.py
├── utils/ # Utility modules
│ ├── data_loader.py # Data loading functions
│ ├── image_utils.py # Image processing utilities
│ ├── map_utils.py # GPS mapping utilities
│ └── viz_utils.py # Visualization functions
```

```
artifacts/detections/visualizations/
artifacts/detections/detection_results.json
artifacts/training/training_metrics.json
data/{test,val,train,raw}/
```

```
crackz dashboard --project my-project --port 8080
```

```
.streamlit/config.toml
```

```
[server]
port = 8501
headless = true

[theme]
primaryColor = "#FF4B4B"
backgroundColor = "#FFFFFF"
secondaryBackgroundColor = "#F0F2F6"
```

```
textColor = "#262730"
font = "sans serif"
```

- streamlit>=1.30.0
- streamlit-folium>=0.15.0
- folium>=0.15.0
- plotly>=5.18.0
- pandas>=2.0.0

1.

```
crackz detect --project my-project
```

2.

3.

1.

```
crackz geo extract-gps --project my-project
```

2.

3.

1.

2.

3.

1.

2.

3.

8502

```
uv sync
```

```
pip install streamlit
```

```
--port
```



```
crackz detect --project <name>
```

```
artifacts/detections/visualizations/
```

```
crackz geo extract-gps
```

```
crackz train --project <name>
```

```
artifacts/training/training_metrics.json
```

- 1.
- 2.
- 3.
- 4.

```
1. Initialize project
crackz init my-project

2. Import images
crackz import-images --source ./photos --project my-project

3. Train model
crackz train --project my-project

4. Run detection
crackz detect --project my-project

5. Launch dashboard to view results
crackz dashboard --project my-project
```

```
from crackz.dashboard import launch_dashboard

Launch dashboard programmatically
launch_dashboard(
 project_name="my-project", # Optional: project to load
 port=8501 # Optional: server port
)
```

```
Show help
crackz dashboard --help

Launch with project
crackz dashboard --project my-project

Launch with custom port
crackz dashboard --project my-project --port 8080

Launch without initial project
crackz dashboard
```

```
1. Create and setup project
crackz init harbor-inspection
crackz import-images --source ./drone-photos --project harbor-inspection

2. Train model
crackz train --project harbor-inspection --epochs 50

3. View training progress
crackz dashboard --project harbor-inspection
Navigate to "Training Metrics" page to review

4. Run detection on test set
crackz detect --project harbor-inspection --split test

5. Analyze results
crackz dashboard --project harbor-inspection
Navigate to "Detection Results" page
Navigate to "GPS Map" page to see locations

6. Tune parameters if needed
Use "Parameter Tuning" page to optimize thresholds

7. Re-run with optimized parameters
crackz detect --project harbor-inspection --threshold 0.6

8. Generate final report
crackz report generate --project harbor-inspection --format pdf
```

- \_\_\_\_\_
- \_\_\_\_\_
- \_\_\_\_\_
- \_\_\_\_\_
- \_\_\_\_\_

1. \_\_\_\_\_
2. \_\_\_\_\_
3. \_\_\_\_\_ dashboard

# AI Chat Assistant

# AI Chat Assistant

---

- 
- 
- 
- 
- 

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

- 
- 
- 

```
Install keyring support
uv add keyring

Or with pip
pip install keyring
```

```
from crackz_gui.state.secure_storage import (
 store_api_key,
 retrieve_api_key,
 is_secure_storage_available,
)
```

```
Check if keyring is available
if is_secure_storage_available():
 # Store API key securely
 store_api_key("your-api-key-here")

 # Retrieve API key
 api_key = retrieve_api_key()

 # Delete API key
 from crackz_gui.state.secure_storage import delete_api_key
 delete_api_key()
else:
 print("Keyring not available - falling back to plaintext storage")
```

- 
- 
- 
- 
- 

- 1.
2. \$
3. ~
4. Ctrl+ / Cmd+ /
- 5.
- 6.
- 7.
8.
  - 
  -
9.
  - 
  - sk-ant-... sk-or-...
- 10.
- 11.



- 1.
- 2.
- 3.
- 4.

- \$
- ~
- Ctrl+ / Cmd+ /

- 
- 
-

•  
•  
•  
•

•  
•  
•  
•

•  
•  
•  
•

•  
•  
•  
•

•  
•  
•



•  
•  
•  
•  
•

You: My detection is finding too many false positives. How can I reduce them?

AI: Based on your project, I recommend:

1. Increase confidence\_threshold from 0.25 to 0.4
2. Adjust iou\_threshold to 0.5 for stricter overlap filtering
3. Consider retraining with more negative examples

Would you like me to explain how to adjust these in your project?

You: How many epochs should I train for?

AI: For your dataset with 150 training images:

- Start with 50 epochs as a baseline
- Monitor validation loss - it should decrease steadily
- If validation loss plateaus before 50 epochs, you can stop early
- If still improving at 50, try 75-100 epochs

Your current batch\_size of 8 is good for this dataset size.

You: Analyze my project configuration

AI: Here's what I found in your oslo\_project:

- Good splits: 70/20/10 train/val/test distribution
- △ Low image count (150 total) - consider data augmentation
- Reasonable batch size (8) for dataset
- Suggestion: Enable data augmentation in training config
- Suggestion: Consider collecting more diverse training data

You: How do I export detection results to CSV?

AI: To export detection results:

1. Run detection: ``crackz detect run <project>``
2. Results are saved in `project/artifacts/detections/`
3. Use export command: ``crackz export --format csv <project>``

Or in GUI:

1. Click "Run Detection" button
2. Results appear in Detection Results panel
3. Click "Export" → "CSV Format"

•  
•  
•

•  
•  
•

- 
- 
- 

\_\_\_\_\_

5-20251001    claude-opus-4-1-20250805

claude-sonnet-4-5-20250929    claude-haiku-4-

§   ~   Ctrl+ /

- 1.
- 2.
- 3.
- 4.
- 5.
- 6.
- 7.

\_\_\_\_\_

\_\_\_\_\_

`chat_window.py`

- 
- 
- 
- 

`ai_chat.py`

- 
- 
- 
- 

`chat_settings_dialog.py`

- 
- 
- 

- 
- 
- 

- 
- 
- 

- 
- 
- 

1. `ai_chat.py` `_get_context()`

```
def _get_context(self) -> str:
 if self.app_state is None or self.app_state.project is None:
```



```
 return "No project loaded"

 project = self.app_state.project

 # Add your new context here
 return f"""
 Current project: {project.name}

 Your new context:
 - Additional info: {project.additional_info}
 """
```

2.

```
uv run task tests
```

- \_\_\_\_\_
- \_\_\_\_\_
- \_\_\_\_\_

---

# Configuration

---

# Configuration Reference

```
crackz init
```

```
CLI flag > ENV var > Project YAML > Code default
```

```
crackz init --name demo-project
```

```
demo-project/_project.yaml
```

```
<name>_project.yaml
```

```
project:
 name: demo-project
 description: Demo project
 created: 2025-01-01T12:00:00+00:00
paths:
 project_path: demo-project
 image_path: demo-project/images
 image_mask_path: demo-project/masks
 artifacts_path: demo-project/artifacts
logging:
 level: INFO
 log_dir: logs
ai:
 model:
 encoder: resnet34
 encoder_weights: imagenet
 device: cpu
 in_channels: 3
 num_classes: 1
 input_size: [512, 512]
 threshold: 0.5
 loss_name: combo
 dice_weight: 0.7
 focal_weight: 0.3
 training:
 batch_size: 8
 num_workers: 4
 epochs: 10
 learning_rate: 0.001
 shuffle: true
 detection:
 threshold: 0.5
 learning_rate: 0.001
 batch_size: 8
 shuffle: true
 output_dir_name: detections
data:
 mask_threshold: 50
schema_version: 2
```

```
ProjectConfig
```

```
from pathlib import Path
from crackz.config.project_config import ProjectConfig

pc = ProjectConfig(
 name="demo-project",
 project_path=Path("demo-project"),
 image_path=Path("demo-project/images"),
 image_mask_path=Path("demo-project/masks"),
 artifacts_path=Path("demo-project/artifacts"),
)
pc.save(Path("project_config.yaml"))

Later
loaded = ProjectConfig.load(Path("project_config.yaml"))
project = loaded.to_project()
```

```
Project
```

```
from crackz.config.project_config import ProjectConfig
pc = ProjectConfig.from_project(project)
pc.save(Path("backup_config.yaml"))
```

|  |                 |  |
|--|-----------------|--|
|  |                 |  |
|  | ModelConfig     |  |
|  | TrainingConfig  |  |
|  | DetectionConfig |  |

|  |  |  |
|--|--|--|
|  |  |  |
|--|--|--|

segmentation-models-pytorch

|                 |      |          |      |     |
|-----------------|------|----------|------|-----|
|                 |      |          |      |     |
| efficientnet-b0 |      |          |      |     |
| efficientnet-b3 |      |          |      |     |
| efficientnet-b7 |      |          |      |     |
| resnet18        |      |          |      |     |
| resnet34        |      |          |      |     |
| resnet50        |      |          |      |     |
| resnet101       |      |          |      |     |
| densenet121     |      |          |      |     |
| mobilenet_v2    |      |          |      |     |
| vgg16           |      |          |      |     |
|                 | swsl | imagenet | None | ssl |
|                 |      |          | null |     |

Binary Segmentation (Default)

```
ai:
 model:
 encoder: resnet34
 num_classes: 1 # Single output channel
 threshold: 0.5 # Probability threshold for crack/no-crack
```

Multi-Class Segmentation

```
ai:
 model:
 encoder: efficientnet-b0
 num_classes: 3 # E.g., background=0, crack=1, corrosion=2, spalling=3
 threshold: 0.5 # Applied per-class
```

Grayscale Input

```
ai:
 model:
 encoder: mobilenet_v2
 in_channels: 1 # Grayscale images
```

```
normalization:
 mean: [0.5]
 std: [0.5]
```

Training from Scratch (No Pretrained Weights)

```
ai:
 model:
 encoder: resnet34
 encoder_weights: null # Random initialization
```



TrainingConfig

int int | str

```
tensorboard
artifacts/runtime/tensorboard/
 getattr(project.ai.training, "tensorboard", False) False
```

```
Safe access pattern inside runtime code
use_tb = getattr(project.ai.training, "tensorboard", False)
if use_tb:
 ... # create logger
```

getattr(..., default)

False tests/unit/crackz/ai/test\_detection.py::test\_tensorboard\_logger\_disabled\_by\_default model\_fields

TrainingConfig

|  |  |  |
|--|--|--|
|  |  |  |
|--|--|--|

min\_confidence medium\_confidence high\_confidence

- 
- 
- 

|  |  |  |
|--|--|--|
|  |  |  |
|--|--|--|

```
ai:
 detection:
 min_confidence: 0.005 # Save detections with ≥0.5% crack area
 medium_confidence: 0.02 # "Probable Crack" at ≥2% crack area
 high_confidence: 0.05 # "Crack Detected" at ≥5% crack area
 min_crack_area_px: 100 # Suppress detections smaller than 100 pixels
```

data

|  |  |  |
|--|--|--|
|  |  |  |
|--|--|--|

DataConfig

|  |  |  |
|--|--|--|
|  |  |  |
|--|--|--|

mask\_threshold

- 
- 
- 

|  |  |  |
|--|--|--|
|  |  |  |
|--|--|--|

```
data:
 mask_threshold: 50 # Default - balanced filtering
```

```
crackz import-images --masks_src <path>
scripts/import_masks.py
```

```
project.import_images()
```

```
crackz migrate
```

```
mask_threshold:
```

```
50
```

```
crackz export-config --project demo-project --out tuned_config.yaml
```

```
from crackz.config.project_config import ProjectConfig
pcfg = ProjectConfig.from_project(project)
pcfg.save(Path("tuned_config.yaml"))
```

```
CRACKZ_LOG_DIR=run_logs crackz detect run --project demo-project
```

```
$env:CRACKZ_LOG_DIR='run_logs'; crackz detect run --project demo-project
```

```
ai.model.device
resolve_device_and_accelerator
cuda python -c "import torch; print(torch.cuda.is_available())"
```

```
ai.model.device:
```

```
tensorboard: true
```

```
ai:
 training:
 tensorboard: true
 epochs: 10
 batch_size: 8
```

```
from crackz import Project

project = Project.load(Path("demo-project"))
project.ai.training.tensorboard = True
project.save()
```

```
<artifacts_path>/runtime/tensorboard/
```

```
tensorboard --logdir demo-project/artifacts/runtime/tensorboard
```

```
docker run --rm -v $(pwd)/demo-project:/workspace -p 6006:6006 crackz-cli \
 tensorboard --logdir /workspace/artifacts/runtime/tensorboard
```

```
crackz detect run --project p --cfg cfg.yaml
```

```
training.epochs batch_size
```

```
detection.batch_size
```

```
<artifacts_path>/models/ best.ckpt last.ckpt
epoch={N}-val_iou={score}.ckpt epoch=9-val_iou=0.8234.ckpt
<artifacts_path>/checkpoints/
```

```
ai:
 training:
 save_top_k: 1 # Keep N best checkpoints (by val_iou), default: 1
 save_last: true # Always save last.ckpt, default: true
 auto_prune_checkpoints: false # Auto-prune after training, default: false
 checkpoint_keep: 3 # Checkpoints to keep when auto-pruning, default: 3
```

1. save\_top\_k: 1, save\_last: true
2. save\_top\_k: 3, auto\_prune\_checkpoints: true, checkpoint\_keep: 3
3. save\_top\_k: 1, save\_last: false, auto\_prune\_checkpoints: true, checkpoint\_keep: 1

```
crackz detect prune-checkpoints --project demo-project --keep 3
```

```
docker run --gpus all --rm -v %cd%\project:/workspace crackz-cli:gpu \
detect prune-checkpoints --project /workspace/demo-project --keep 2
```

```
from crackz.ai.checkpoints import prune_checkpoints
removed = prune_checkpoints(project, keep=2)
```

|             |           |           |      |
|-------------|-----------|-----------|------|
| 0.8234.ckpt | last.ckpt | best.ckpt | 003- |
|-------------|-----------|-----------|------|

<artifacts\_path>/detections/detection\_results.json

```
from crackz.ai.results import load_detection_results
from crackz.ai.eval import basic_summary
results = load_detection_results(project)
print(basic_summary(results))
```

crack\_severity

seed

```
project_config.yaml (unified example)
name: demo-project
description: Example project
project_path: demo-project
image_path: demo-project/images
image_mask_path: demo-project/masks
artifacts_path: demo-project/artifacts
logging:
 level: INFO
 log_dir: logs
model:
 encoder: resnet34
 device: cpu
 input_size: [512, 512]
training:
 epochs: 5
 batch_size: 4
 learning_rate: 0.0005
 tensorboard: false # Set to true to enable TensorBoard logging
detection:
 threshold: 0.55
 batch_size: 4
```

schema\_version

```
crackz migrate --project ./my_project
```

|       |                |                   |              |
|-------|----------------|-------------------|--------------|
| false | schema_version | schema_version: 1 | tensorboard: |
|       | .bak           |                   |              |



```
crackz migrate --cfg ./my_project/my_project_project.yaml
```

```
crackz migrate --project ./my_project --dry-run
```

```
crackz migrate --project ./my_project --no-backup
```

up-to-date noop

```
for d in projects/*; do
[-d "$d"] && crackz migrate --project "$d" --no-backup;
done
```

---

ProjectConfig

---

## Training Configuration

---

# TrainingConfig Contract

|                  |                                                          |              |
|------------------|----------------------------------------------------------|--------------|
| TrainingConfig   | crackz.project.config                                    | ai.training  |
|                  |                                                          |              |
| batch_size       |                                                          |              |
| num_workers      |                                                          |              |
| epochs           |                                                          |              |
| learning_rate    |                                                          |              |
| shuffle          |                                                          |              |
| loss             |                                                          |              |
| metrics          |                                                          |              |
| seed             |                                                          |              |
| precision        |                                                          |              |
| devices          |                                                          |              |
| strategy         |                                                          |              |
| tensorboard      | artifacts/training/tensorboard                           |              |
|                  |                                                          |              |
|                  | tests/unit/crackz/project/test_training_config_schema.py |              |
| TrainingConfig   |                                                          |              |
| 1.               |                                                          |              |
| 2.               |                                                          |              |
| 3.               |                                                          |              |
| 4.               | CURRENT_SCHEMA_VERSION                                   |              |
|                  |                                                          |              |
| 1.               |                                                          |              |
| 2.               |                                                          |              |
| 3.               |                                                          |              |
| 4.               |                                                          |              |
|                  |                                                          |              |
|                  | --epochs                                                 | --batch-size |
|                  |                                                          |              |
| tensorboard=True | <project>/artifacts/training/tensorboard                 |              |
|                  |                                                          |              |
| seed             |                                                          |              |

# Data Splits & Import

# Data Splits and Import Guide

---

- 1. \_\_\_\_\_
  - 2. \_\_\_\_\_
  - 3. \_\_\_\_\_
  - 4. \_\_\_\_\_
  - 5. \_\_\_\_\_
- 



images/raw/

raw/

```
crackz import-images --project my-project --src ./photos --type raw --size 512 512
```

---

images/train/    masks/train/

img001.jpg    img001.png

---

images/val/    masks/val/

---

`images/test/` `masks/test/`

---

`--type raw`

```
crackz import-images \
--project my-project \
--src ./labeled-data/images \
--src-masks ./labeled-data/masks \

```

```
--split-ratios 0.7 0.15 0.15 \
--size 512 512
```

```
crackz import-images \
--project my-project \
--src ./labeled-data/images \
--src-masks ./labeled-data/masks \
--split-ratios 0.7 0.15 0.15 \
--seed 42 \
--size 512 512
```

```
Small dataset: larger validation set
crackz import-images \
--project my-project \
--src ./small-dataset/images \
--src-masks ./small-dataset/masks \
--split-ratios 0.6 0.25 0.15 \
--size 512 512

Large dataset: more for training
crackz import-images \
--project my-project \
--src ./large-dataset/images \
--src-masks ./large-dataset/masks \
--split-ratios 0.8 0.1 0.1 \
--size 512 512
```

- 1.
- 2.
- 3.
- 4.
- 5.
- 6.
- 7.
- 8.
- 9.
- 10.
- 11.
- 12.
- 13.
- 14.
- 15.
- 16.
- 17.
- 18.
- 19.
- 20.
- 21.
- 22.

- 
-

23.  
24.  
25.  
26.

- 
- 
- 
- 

```
crackz init --name harbor-inspection
cd harbor-inspection
```

```
crackz import-images \
--project . \
--src ~/datasets/harbor-cracks/images \
--src-masks ~/datasets/harbor-cracks/masks \
--split-ratios 0.7 0.15 0.15 \
--seed 42 \
--size 512 512
```

images/train/  
masks/

images/val/

images/test/

```
Count images
ls images/train/ | wc -l # Should show 140
ls images/val/ | wc -l # Should show 30
ls images/test/ | wc -l # Should show 30

Count masks (should match images)
ls masks/train/ | wc -l # Should show 140
ls masks/val/ | wc -l # Should show 30
ls masks/test/ | wc -l # Should show 30
```

```
crackz detect train --epochs 50 --batch-size 8
```

images/val/

masks/val/

images/train/

masks/train/

artifacts/metrics.json

artifacts/loss\_curve.png

checkpoints/best.ckpt

```
crackz detect run --split test
```

masks/test/

images/test/

detections/

```
Import new unlabeled images
crackz import-images \
 --project . \
 --src ~/new-harbor-photos \
 --type raw \
 --size 512 512

Run detection
crackz detect run --split raw
```

detections/

---

1.

```
--seed 42 # Same split every time
```

2.

```
cp -r original-data backup/
```

3.

```
Check if splits are representative
ls images/train/ | wc -l
ls images/val/ | wc -l
```

4.

```
For 50 images: 0.6, 0.25, 0.15 ensures val gets ~13 images
--split-ratios 0.6 0.25 0.15
```

5.

```
In project documentation
split_info:
 seed: 42
 ratios: [0.7, 0.15, 0.15]
 date: 2025-10-19
```

1.

2.

3.

4.

5.

6.

- - 
  - 
  - 
  - 
  - 
  -
-

```
Wrong: 0.7 + 0.2 + 0.2 = 1.1 x
Right: 0.7 + 0.15 + 0.15 = 1.0
--split-ratios 0.7 0.15 0.15
```

images/val/

```
If you have 10 images and use 0.7/0.15/0.15:
train=7, val=1, test=2 (works)

If you have 5 images and use 0.8/0.1/0.1:
train=4, val=0, test=1 (val is empty!)

Solution: Use larger val ratio or more images
--split-ratios 0.6 0.25 0.15 # Ensures val gets at least 1
```

```
Image: images/crack_001.jpg
Mask must be: masks/crack_001.png (same stem)

Check your filenames:
ls images/ > image_list.txt
ls masks/ > mask_list.txt
Compare the stems (filename without extension)
```

```
Add --seed for reproducible splits
--seed 42
```

```
Increase validation ratio
--split-ratios 0.65 0.25 0.1 # Gives more to validation
```

```
Import with smaller size
--size 256 256 # Instead of 512 512

Or reduce batch size during training
crackz detect train --batch-size 2 # Instead of 8
```



```
Separate images by class first
mkdir temp/crack temp/no-crack

Move files to class folders
... organize manually or with script ...

Import each class separately with same ratio
crackz import-images --src temp/crack --split-ratios 0.7 0.15 0.15 --seed 42
crackz import-images --src temp/no-crack --split-ratios 0.7 0.15 0.15 --seed 42
```

```
Import full dataset to train
crackz import-images --src data --type train --size 512 512

Manually create folds by moving files between train/val
Train 5 models with different train/val splits
Average results for robust performance estimate
```

```
Import new batch with same seed and ratios
crackz import-images \
 --src new-data \
 --split-ratios 0.7 0.15 0.15 \
 --seed 42 \
 --size 512 512

WARNING: This adds to existing splits
Consider fresh re-import of all data for clean splits
```

```
images/raw/
images/train/
images/val/
images/test/
```

```
Import for training (with split)
crackz import-images --src data/images --src-masks data/masks \
 --split-ratios 0.7 0.15 0.15 --seed 42 --size 512 512

Import for detection (no split)
crackz import-images --src photos --type raw --size 512 512

Train on train split, validate on val split
crackz detect train --epochs 50 --batch-size 8

Test on test split
crackz detect run --split test

Detect on raw split
crackz detect run --split raw
```

- 
- 
-

- \_\_\_\_\_
- \_\_\_\_\_
- \_\_\_\_\_
- \_\_\_\_\_
- \_\_\_\_\_


---

# Map Viewer

---


# Map Viewer Feature

---






•  
•  
•  
•







*Interactive map view opened in web browser with geotagged images displayed as markers*



- 
- 
- 

- 
- 
- 

- `gui/src/crackz_gui/components/map_viewer.py`
- 
- 
- `webbrowser.open()`
- 

- 1.
- 2.
- 3.
- 4.
- 5.

```
from pathlib import Path
from crackz_gui.qt.views.map_viewer_view import MapViewerDialog
from crackz.project.project import load_project

Load a project
project = load_project(Path("path/to/project"))

Note: MapViewerDialog requires a parent GUI app instance and is typically
used within the Crackz GUI application. For command-line access to GPS data, use:
from crackz.project.geoposition import get_project_geopositions

Get GPS data for all images in the project
gps_data = get_project_geopositions(project)
for image_path, geo_pos in gps_data.items():
 print(f"{image_path}: {geo_pos.latitude}, {geo_pos.longitude}")
```

- 
- 
- 

- 
- 
-

- 
- 
- 

`tests/test_data/`      `oslo_project/`

- `tests/test_data/images/`
- `oslo_project/images/`

`scripts/add_test_gps_data.py`

```
python scripts/add_test_gps_data.py
```

- 1.
2. `logs/crackz.log`
- 3.

- 
- `crackz.project.geoposition.get_project_geopositions()`
- `python scripts/add_test_gps_data.py`

- 
- 
- 

- 
- 
- 

- `gui/src/crackz_gui/components/map_viewer.py`
- `gui/src/crackz_gui/components/browser/toolbar.py`

- `core/src/crackz/project/geoposition.py`
- `scripts/add_test_gps_data.py`

---

## Report Generation

---

# Report Generation

---

- 
- 
- 
- 
- 

```
crackz report generate --project demo-project
demo-project_report.docx
```

```
crackz report generate --project demo-project --output inspection_report.docx
```

```
crackz report generate --cfg project_config.yaml --output report.docx
```

- 
- 
- 
-

- 
- 
- 

```
ai:
 detection:
 min_confidence: 0.005 # 0.5% - Possible Crack threshold
 medium_confidence: 0.02 # 2% - Probable Crack threshold
 high_confidence: 0.05 # 5% - Crack Detected threshold
```

detections/

```
crackz report generate --project harbor_inspection_2024 \
 --output "Harbor_Inspection_Report_2024-Q4.docx"
```

```
Monthly reports
crackz report generate --project monthly_monitoring \
 --output "reports/2024-11_monitoring.docx"
```

```
crackz report generate --project compliance_check \
 --output "compliance/inspection_$(date +%Y%m%d).docx"
```

```
crackz report generate --project qa_validation \
 --output "internal/qa_review.docx"
```

- 
- 
- 
- 

- 
- 
- 

```
crackz detect run
```

```
crackz detect run --project demo-project
```

```
Check for visualization images (new structure)
ls -la demo-project/artifacts/detections/visualizations/

Or legacy location (older projects)
ls -la demo-project/artifacts/detections/*.png
```

```
crackz detect run --project demo-project
```

```
artifacts/detections/visualizations/
```

```
data:
size: [512, 512] # Use smaller images
```

```
--output
```

```
crackz report generate --project harbor_main \
--output "Harbor_Main_Inspection_2024-11-05.docx"
```

```
for project in project1 project2 project3; do
 crackz report generate --project "$project" \
 --output "reports/${project}_${date +%Y%m%d}.docx"
done
```

```
crackz report generate --project demo-project # Creates demo-project/demo-project_report.docx
```

```
Add to project notes
project:
 notes: "Report generated 2024-11-05 with default thresholds"
```

- \_\_\_\_\_
- \_\_\_\_\_
- \_\_\_\_\_
- \_\_\_\_\_

---

# Docker

---

# Docker Usage

```
Pull from registry
docker pull ghcr.io/anaxiatech-ab/crackz:latest
docker pull ghcr.io/anaxiatech-ab/crackz:slim
docker pull ghcr.io/anaxiatech-ab/crackz:gpu

Run from registry
docker run --rm ghcr.io/anaxiatech-ab/crackz:latest --help
```

|        |                 |  |  |
|--------|-----------------|--|--|
|        |                 |  |  |
| latest | Dockerfile      |  |  |
| slim   | Dockerfile.slim |  |  |
| gpu    | Dockerfile.gpu  |  |  |

```
Full
docker build -t crackz-cli .
Slim
docker build -f Dockerfile.slim -t crackz-cli:slim .
GPU (CUDA 12.8)
docker build -f Dockerfile.gpu -t crackz-cli:gpu .
```

```
docker build --build-arg PYTHON_VERSION=3.13 -t crackz-cli .
```

1.

ghcr.io/astral-sh/uv:bookworm-slim

uv build --wheel
2.
3.

python:3.13-slim
4.

nvidia/cuda:12.8.0-runtime-ubuntu22.04
5.
6.

--build-arg TORCH\_INDEX\_URL=...

- uv build
- 
- 
- 

- nvidia/cuda:12.8.0-runtime-ubuntu22.04
- 
- git libglib2.0-0 libjpeg-turbo8 libgomp1 ca-certificates
- 
-



```
Default: CUDA 12.8 (recommended, matches PyTorch cu128)
docker build -f Dockerfile.gpu -t crackz-cli:gpu .

Override for CUDA 12.1
docker build -f Dockerfile.gpu \
 --build-arg TORCH_INDEX_URL=https://download.pytorch.org/whl/cu121 \
 -t crackz-cli:gpu-cu121 .

Override for CUDA 12.4 (if needed for compatibility)
docker build -f Dockerfile.gpu \
 --build-arg TORCH_INDEX_URL=https://download.pytorch.org/whl/cu124 \
 -t crackz-cli:gpu-cu124 .
```

TORCH\_INDEX\_URL

```
#18 [runtime 7/9] RUN /app/.venv/bin/python3 -c 'import torch; print("Torch:", torch.__version__, "CUDA available:", torch.cuda.is_available())'
#18 0.699 Torch: 2.8.0+cpu CUDA available: False
```

CUDA available: False

linux/amd64

/home/app


```
Help
docker run --rm crackz-cli --help

Init project (creates /home/app/demo-project inside container)
mkdir -p project
docker run --rm -v "$(pwd)/project:/home/app" crackz-cli init --name demo-project

Import images (mount samples to /data)
mkdir -p samples
(populate samples/ with images and optional masks/ first)
docker run --rm \
 -v "$(pwd)/project:/home/app" \
 -v "$(pwd)/samples:/data" \
 crackz-cli import-images --project /home/app/demo-project --src /data --type raw --size 512 512

Detection
docker run --rm -v "$(pwd)/project:/home/app" crackz-cli detect run --project /home/app/demo-project
```

```
docker run --gpus all --rm -v "$(pwd)/project:/home/app" crackz-cli:gpu detect run --project /home/app/demo-project
```



|                  |      |
|------------------|------|
| CRACKZ_LOG_DIR   | logs |
| PYTHONUNBUFFERED | 1    |

/home/app/central\_logs

```
docker run --rm -e CRACKZ_LOG_DIR=central_logs -v "$(pwd)/project:/home/app" \
 crackz-cli detect run --project /home/app/demo-project
```

/home/app

```
make build # full image
make build-slim # slim image
make build-gpu # gpu image (CUDA 12.8)
make init NAME=demo-project # creates project under /home/app
make import PROJECT=demo-project DATA_DIR=./samples
make detect PROJECT=demo-project
make detect-gpu PROJECT=demo-project # GPU detection
make train-gpu PROJECT=demo-project # GPU training
```

act

```
Install act (macOS)
brew install act

Test GPU build with make targets
make act-gpu-dryrun # Dry-run to validate workflow
make act-gpu # Actually run the GPU build locally
make act-docker-build # Test all Docker builds (full, slim, gpu)
```

|     |                 |
|-----|-----------------|
|     |                 |
|     | latest          |
|     | slim            |
|     | gpu             |
| gpu | TORCH_INDEX_URL |

|  |  |  |
|--|--|--|
|  |  |  |
|--|--|--|

CRACKZ\_LOG\_DIR

--gpus all

TORCH\_INDEX\_URL

- \_\_\_\_\_
- \_\_\_\_\_
- \_\_\_\_\_

# Azure Batch

# Azure Batch Deployment

---

- 
- 
- 
- 

- 1.
- 2.
- 3.
4. `az login`

```
./scripts/azure/azure_batch.sh \
--batch-account mycrackzaccount \
--storage-account mycrackzstorage
```

mycrackzaccount

mycrackzstorage

```
Get storage account key
STORAGE_KEY=$(az storage account keys list \
--account-name mycrackzstorage \
--resource-group subbaltica-crackz-rg \
--query "[0].value" -o tsv)
```

```
Upload project directory
az storage blob upload-batch \
--account-name mycrackzstorage \
--account-key "$STORAGE_KEY" \
--destination crackz-data \
--source ./my-project
```

```
Create job
az batch job create \
--id crackz-detection-job \
--pool-id crackz-pool

Add tasks to the job
az batch task create \
--job-id crackz-detection-job \
--task-id detect-task-1 \
--command-line "docker run crackz-cli:latest detect run --project /mnt/batch/tasks/fsmounts/crackz-data/my-project"
```

```

--batch-account
--resource-group subbaltica-crackz-rg
--location swedencentral
--pool-id crackz-pool
--vm-size Standard_D2s_v3
--node-count 2
--image crackz-cli:latest
--storage-account
--container crackz-data

```

```

Standard_D2s_v3
Standard_D4s_v3
Standard_D8s_v3
Standard_NC6s_v3
Standard_NC4as_T4_v3

```

```

./scripts/azure/azure_batch.sh \
--batch-account crackz-batch \
--pool-id high-performance-pool \
--vm-size Standard_D8s_v3 \
--node-count 10 \
--storage-account crackzstore

```

```

./scripts/azure/azure_batch.sh \
--batch-account crackz-batch-gpu \
--pool-id gpu-pool \
--vm-size Standard_NC4as_T4_v3 \
--node-count 2 \
--image crackz-cli:gpu

```

```

Enable auto-scaling
az batch pool autoscale enable \
--pool-id crackz-pool \
--account-name mycrackzaccount \
--auto-scale-formula '
 startingNumberOfVMs = 2;
 maxNumberOfVMs = 10;
 pendingTaskSamplePercent = $PendingTasks.GetSamplePercent(180 * TimeInterval_Second);
 pendingTaskSamples = pendingTaskSamplePercent < 70 ? startingNumberOfVMs : avg($PendingTasks.GetSample(180 * TimeInterval_Second));
 $TargetDedicatedNodes = min(maxNumberOfVMs, pendingTaskSamples);
'

```

```
#!/bin/bash
Create job
az batch job create --id multi-project-job --pool-id crackz-pool

Submit tasks for each project
for project in project1 project2 project3; do
 az batch task create \
 --job-id multi-project-job \
 --task-id "detect-$project" \
 --command-line "docker run crackz-cli:latest detect run --project /data/$project"
done
```

```
Training task
az batch task create \
 --job-id pipeline-job \
 --task-id train \
 --command-line "docker run crackz-cli:latest detect train --project /data/my-project --epochs 50"

Detection task (depends on training)
az batch task create \
 --job-id pipeline-job \
 --task-id detect \
 --depends-on train \
 --command-line "docker run crackz-cli:latest detect run --project /data/my-project"
```

```
az batch task create \
 --job-id output-job \
 --task-id detect-with-output \
 --command-line "docker run -v /mnt/output:/output crackz-cli:latest detect run --project /data/project" \
 --resource-files '["httpUrl":"https://mystorage.blob.core.windows.net/input/data.zip","filePath":"data.zip"]' \
 --output-files '["filePattern":"/mnt/output/**/*","destination":{"container":{"containerUrl":"https://mystorage.blob.core.windows.net/results"}}, {"uploadOptions":{"uploadC
```

```
az batch pool show \
 --pool-id crackz-pool \
 --account-name mycrackzaccount \
 --query "{State:allocationState, DedicatedNodes:currentDedicatedNodes}"
```

```
az batch job list \
 --account-name mycrackzaccount \
 -o table
```

```
az batch task list \
 --job-id crackz-detection-job \
 --account-name mycrackzaccount \
 -o table
```

```
az batch task file download \
 --job-id crackz-detection-job \
 --task-id detect-task-1 \
 --file-path stdout.txt \
 --destination ./task-stdout.txt \
 --account-name mycrackzaccount
```

```
After pool creation, modify to use low-priority nodes
az batch pool resize \
```

```
--pool-id crackz-pool \
--account-name mycrackzaccount \
--target-dedicated-nodes 0 \
--target-low-priority-nodes 4
```

```
./scripts/azure/azure_batch.sh \
--batch-account mycrackzaccount \
--pool-id crackz-pool \
--destroy
```

```
az batch location quotas show --location <region>
az batch task file download
```

```
az batch account login
```

```
Get task details
az batch task show \
--job-id crackz-detection-job \
--task-id detect-task-1 \
--account-name mycrackzaccount

Download stderr
az batch task file download \
--job-id crackz-detection-job \
--task-id detect-task-1 \
--file-path stderr.txt \
--destination ./task-stderr.txt \
--account-name mycrackzaccount
```

```
Check current quotas
az batch location quotas show --location swedencentral

Submit quota increase request through Azure Portal
Support > New support request > Issue type: Service and subscription limits
```

```
name: Azure Batch Processing
on:
 push:
 branches: [main]
jobs:
 batch-process:
 runs-on: ubuntu-latest
 steps:
 - uses: actions/checkout@v5

 - name: Azure Login
 uses: azure/login@v1
 with:
 creds: ${ secrets.AZURE_CREDENTIALS }

 - name: Create Batch Pool
 run: |
 ./scripts/azure/azure_batch.sh \
 --batch-account ${ secrets.BATCH_ACCOUNT } \
 --storage-account ${ secrets.STORAGE_ACCOUNT }

 - name: Submit Batch Job
 run: |
```

```
az batch job create --id ci-job-{{ github.run_number }} --pool-id crackz-pool
az batch task create \
 --job-id ci-job-{{ github.run_number }} \
 --task-id detect \
 --command-line "docker run crackz-cli:latest detect run --project /data/project"
```

- 1.
- 2.
- 3.
- 4.
- 5.

taskSlotsPerNode

```
Modify pool to allow multiple tasks per node
az batch pool set \
 --pool-id crackz-pool \
 --account-name mycrackzaccount \
 --json-file pool-config.json
```

pool-config.json

```
{
 "taskSlotsPerNode": 4
}
```

```
ai:
 detection:
 batch_size: 16 # Adjust based on VM size
```

- \_\_\_\_\_
- \_\_\_\_\_
- \_\_\_\_\_
- \_\_\_\_\_
- \_\_\_\_\_

- \_\_\_\_\_
- \_\_\_\_\_
- \_\_\_\_\_

---

## Azure VM with CUDA

---

# Azure Windows VM with CUDA for Crackz

---

```
azure_vm_cuda.sh
```

- 
- 
- 
- 
- 
- 

```
Deploy default GPU VM
./scripts/azure/azure_vm_cuda.sh

Deploy with custom configuration
./scripts/azure/azure_vm_cuda.sh \
 --name ml-workstation \
 --size Standard_NC12s_v3 \
 --location westus2

Connect via RDP and verify
RDP to the public IP, then run:
nvidia-smi
cd C:\Crackz && .venv\Scripts\Activate.ps1
python -m crackz --version
```

|  |  |  |  |  |  |  |
|--|--|--|--|--|--|--|
|  |  |  |  |  |  |  |
|--|--|--|--|--|--|--|

```
Standard_NC6s_v3
Standard_NC12s_v3
Standard_NC24s_v3
```

|  |  |  |  |  |  |  |
|--|--|--|--|--|--|--|
|  |  |  |  |  |  |  |
|--|--|--|--|--|--|--|

```
Standard_NC6s_v2
Standard_NV6
```

```
Default deployment (V100 GPU, East US)
./scripts/azure/azure_vm_cuda.sh

Custom name and location
./scripts/azure/azure_vm_cuda.sh --name gpu-crackz --location westeurope

Specific GPU configuration
./scripts/azure/azure_vm_cuda.sh --size Standard_NC12s_v3 --location northeurope
```



| Option                | Value            |
|-----------------------|------------------|
| --name NAME           | crackz-gpu-vm    |
| --location REGION     | eastus           |
| --size SIZE           | Standard_NC6s_v3 |
| --user USERNAME       | crackzuser       |
| --password PASSWORD   | CrackzGpu2024!   |
| --mode MODE           | standard         |
| --data-disk-size SIZE | 1024             |
| --storage-type TYPE   | Premium_LRS      |
| --no-data-disk        |                  |
| --no-cuda             |                  |
| --no-crackz           |                  |
| --enable-nested-virt  |                  |
| --destroy             |                  |
| --help                |                  |

```
Production inference server
./scripts/azure/azure_vm_cuda.sh \
--name crackz-prod \
--size Standard_NC12s_v3 \
--location westus2 \
--mode production

Development environment with large storage
./scripts/azure/azure_vm_cuda.sh \
--name crackz-dev \
--size Standard_NV6 \
--mode development \
--data-disk-size 2048 \
--storage-type Premium_LRS

Budget setup without data disk
./scripts/azure/azure_vm_cuda.sh \
--name crackz-simple \
--size Standard_NV6 \
--no-data-disk

Manual setup (no auto-install)
./scripts/azure/azure_vm_cuda.sh \
--name crackz-manual \
--size Standard_NC6s_v3 \
--no-cuda \
--no-crackz

Docker development (with nested virtualization)
./scripts/azure/azure_vm_cuda.sh \
--name crackz-docker \
--size Standard_NC6s_v3 \
--enable-nested-virt

Clean up resources
./scripts/azure/azure_vm_cuda.sh --name crackz-gpu-vm --destroy
```

| Option                | Value |
|-----------------------|-------|
| --data-disk-size SIZE |       |
| --storage-type TYPE   |       |
| --no-data-disk        |       |

```
C:\ (OS Disk - 127 GB)
├─ Windows/
├─ Program Files/
├─ Users/crackzuser/Desktop/Crackz/ # Crackz installation
└─ ...

D:\ (Data Disk - configurable size)
├─ Projects/ # ML project workspace
├─ │ datasets/ # Training datasets
├─ │ models/ # Model checkpoints
├─ │ outputs/ # Detection results
```

|  |             |                        |
|--|-------------|------------------------|
|  | └─ exports/ | # Exported models      |
|  | └─ temp/    | # Temporary processing |

|  |  |  |  |
|--|--|--|--|
|  |  |  |  |
|--|--|--|--|

```
Production: High-performance storage
./scripts/azure/azure_vm_cuda.sh \
--name ml-prod \
--data-disk-size 2048 \
--storage-type Premium_LRS

Development: Cost-effective storage
./scripts/azure/azure_vm_cuda.sh \
--name ml-dev \
--data-disk-size 512 \
--storage-type Standard_LRS

Simple setup: No separate disk
./scripts/azure/azure_vm_cuda.sh \
--name ml-simple \
--no-data-disk
```

- 1.
  - 2.
  - 3.
  - 4.
  - 5.
  - 6.
  - 7.
  8. C:\Crackz\.venv
  - 9.
  - 10.
  - 11.
  - 12.
  - 13.
  - 14.
  - 15.
  - 16.
- - 
  - 
  - 
  - 
  - 
  -

```
1. Connect via RDP to the VM
2. Double-click "File Upload Server" desktop shortcut
3. Open browser and go to: http://localhost:8080
4. Or access remotely: http://<VM-PUBLIC-IP>:8080
```

```
From your local computer:
Windows: \\<VM-PUBLIC-IP>\CrackzUploads
Mac/Linux: smb://<VM-PUBLIC-IP>/CrackzUploads

Credentials: crackzuser / CrackzGpu2024!
```

```
Using any SFTP client (WinSCP, FileZilla, etc.)
sftp crackzuser@<VM-PUBLIC-IP>
Upload to: /d/Projects/uploads/images/
```

```
D:\Projects\uploads\
├─ images/ # Individual images for analysis
└─ batch/ # Batch processing folders
```

```
Use Windows built-in Remote Desktop
mstsc /v:<PUBLIC_IP>

Or download RDP file
az vm show -d -g crackz-gpu-rg -n crackz-gpu-vm --query publicIps -o tsv
```

```
Check GPU status
nvidia-smi

Test CUDA availability
python -c "import torch; print(f'CUDA available: {torch.cuda.is_available()}')"
python -c "import torch; print(f'GPU count: {torch.cuda.device_count()}')"
```

```
Activate virtual environment
cd C:\Crackz
.\.venv\Scripts\Activate.ps1

Check Crackz version
python -m crackz --version

Test GPU detection
python -m crackz gui # Should detect CUDA device
```

```
Activate virtual environment
cd C:\Crackz
.\.venv\Scripts\Activate.ps1

Option 1: Direct analysis on uploaded images
python -m crackz detect run --images "D:\Projects\uploads\images" --device cuda

Option 2: Create project and import uploaded images
python -m crackz init harbor-inspection
python -m crackz import-images "D:\Projects\uploads\images" harbor-inspection/images/raw
python -m crackz detect run harbor-inspection --device cuda

Option 3: Batch processing multiple folders
python -m crackz detect run --images "D:\Projects\uploads\batch*" --device cuda

View results
explorer "harbor-inspection\artifacts\detection_results"
```

```
Create test project
python -m crackz init test-project

Import sample images
python -m crackz import-images C:\path\to\images test-project/images/raw

Run GPU-accelerated detection
python -m crackz detect run test-project --device cuda
```

- 
- 
- 
- 

```
az vm deallocate
```

- 
- 
- 
- 

- 
- 
- 
- 
- 
- 
- 
- 

```
CrackzGpu2024!
```

```
Manually install CUDA
Download from: https://developer.nvidia.com/cuda-11-8-0-download-archive
Choose Windows x86_64 local installer
```

```
Manual installation
cd C:\Crackz
.\.venv\Scripts\Activate.ps1
uv pip install --find-links https://download.pytorch.org/whl/cu118 torch torchvision
Download wheel from GitHub releases and install
```

```
Check drivers
nvidia-smi

Verify CUDA installation
nvcc --version
```

```
Check PyTorch CUDA
python -c "import torch; print(torch.version.cuda)"
```

- `nvidia-smi -l 1`
- 
- 
- 

```
Windows Event Logs
eventvwr.msc

CUDA installation logs
Get-Content C:\ProgramData\NVIDIA Corporation\CUDA Installer\log.txt

Crackz logs
Get-Content $env:TEMP\crackz-*.log
```

```
az vm list-sizes --location eastus --query "[?contains(name, 'NC')]"
```

```
Use spot instances (60-90% discount)
az vm create --priority Spot --max-price -1 ...

Auto-shutdown schedule
az vm auto-shutdown --name crackz-gpu-vm --resource-group crackz-gpu-rg --time 1800

Deallocate when not in use
az vm deallocate --name crackz-gpu-vm --resource-group crackz-gpu-rg
```

- 

```
%TEMP%\crackz-*.log
```

---

# VM vs Batch Comparison

---

# Azure Deployment Comparison

---

|  |  |  |
|--|--|--|
|  |  |  |
|--|--|--|

- 
- 
- 
- 
- 

```
Create Windows 11 VM
./scripts/azure/azure_vm.sh \
 --name crackz-dev \
 --size Standard_D4s_v3

Connect via RDP and use GUI
IP address displayed after creation
```

- 
- 
- 

-

- 
- 
- 
- 

```
Create batch pool with 10 nodes
./scripts/azure/azure_batch.sh \
 --batch-account mybatchaccount \
 --storage-account mystorage \
 --node-count 10 \
 --vm-size Standard_D4s_v3

Submit 100 detection jobs
for i in {1..100}; do
 az batch task create \
 --job-id detection-job \
 --task-id "task-$i" \
 --command-line "docker run crackz-cli:latest detect run --project /data/project-$i"
done
```

- 
- 
- 

- 1.
- 2.
- 3.
- 4.
- 5.
- 6.
- 7.
- 8.
- 9.
- 10.

```
Phase 1: Development on VM
./scripts/azure/azure_vm.sh --name crackz-dev --size Standard_D4s_v3
RDP in, use GUI to develop and test
Export config: crackz export-config --project demo --out optimized.yaml

Phase 2: Production on Batch
./scripts/azure/azure_batch.sh \
 --batch-account prod-batch \
 --pool-id production-pool \
```



```
--node-count 20 \
--vm-size Standard_D8s_v3

Upload optimized config and data to storage
Submit batch jobs with optimized parameters
```

|  |             |                |
|--|-------------|----------------|
|  |             |                |
|  | azure_vm.sh | azure_batch.sh |

- 1.
- 2.
- 3.
- 4.

- 1.
- 2.
- 3.
- 4.
- 5.

- 1.
- 2.
- 3.
- 4.

- 
- 
- 
- 
- 
- 
- 
- 
- 
-

```
1. Develop on VM
./scripts/azure/azure_vm.sh --name dev-vm

2. Test configuration
crackz detect train --project my-project --epochs 50
crackz detect run --project my-project

3. Export configuration
crackz export-config --project my-project --out batch-config.yaml

4. Upload to Azure Storage
az storage blob upload-batch \
 --account-name mystorage \
 --destination crackz-data \
 --source my-project

5. Create Batch pool
./scripts/azure/azure_batch.sh \
 --batch-account mybatch \
 --storage-account mystorage \
 --node-count 10

6. Submit batch jobs
az batch job create --id production-job --pool-id crackz-pool
... add tasks
```

- `scripts/azure/azure_vm.sh --help`
- `_____`
- `_____`
- `_____`

`--size Standard_NC*`

`az batch task file download`

- `_____`
- `_____`
- `_____`
- `_____`

---

# Advanced Performance

---

# Advanced Performance & Reproducibility

|           | ai.training | ai.detection | ProjectConfig |
|-----------|-------------|--------------|---------------|
|           |             |              |               |
| precision | ai.training |              |               |
| devices   | ai.training |              |               |
| strategy  | ai.training |              | ddp           |
| seed      | ai.training | ai.detection |               |

321616-mixedbf16-mixed

```
ai:
 training:
 precision: 16-mixed
 batch_size: 16
```

```
crackz detect train --project demo-project
```

devicesstrategyddp

```
ai:
 training:
 devices: 2
 strategy: ddp
 batch_size: 8
 precision: bf16-mixed
```

```
crackz detect train --project demo-project
```

```
docker run --gpus all --rm -v %cd%\project:/home/app crackz-cli:gpu \
detect train --project /home/app/demo-project
```

```
ddp
ddp_spawn
auto
```

seed

```
ai:
 training:
```

```
seed: 1234
detection:
seed: 1234
```

```
PYTHONHASHSEED
```

```
random
```

```
import torch
torch.use_deterministic_algorithms(True)
```

- 
- 

```
project:
 name: demo-project
 description: Perf tuned
paths:
 project_path: demo-project
 image_path: demo-project/images
 image_mask_path: demo-project/masks
 artifacts_path: demo-project/artifacts
logging:
 level: INFO
 log_dir: logs
ai:
 model:
 encoder: resnet34
 device: cuda
 input_size: [512, 512]
 threshold: 0.5
 training:
 batch_size: 16
 epochs: 20
 learning_rate: 0.0005
 precision: 16-mixed
 devices: 2
 strategy: ddp
 seed: 4242
 detection:
 batch_size: 8
 seed: 4242
```

```
crackz export-config
```


```
crackz export-config --project demo-project --out tuned_config.yaml
```

```
tuned_config.yaml
```

```
ai.detection.seed
```

```
ddp_spawn
```

```
torch.use_deterministic_algorithms(True)
```



---

# Migration Guide

---

# Project Schema Migration

ai.training.tensorboard schema\_version

CURRENT\_SCHEMA\_VERSION crackz.project.migration schema\_version schema\_version

```
schema_version ai.training.tensorboard
schema_version: 1 ai.training.tensorboard: false
data mask_threshold: 1
project.crackz_version
```

```
schema_version: 3
project:
 name: my project
 description: My crack detection project
 created: '2025-01-15T10:30:00Z'
 crackz_version: '0.50.0' # NEW: Tracks Crackz app version
```

```
project.crackz_version
checkpoints/ models/ runtime/
detections/visualizations/
checkpoints_path checkpoints/
models/ runtime/ crackz_version
```

data

```
data:
 mask_threshold: 1
 schema_version: 2
```

data.mask\_threshold

detect train detect run

- 1.
- 2. Project schema v0 < v1. Migrate now? [y/N]:
- 3. .bak
- 4.
- 5. CRACKZ\_AUTO\_MIGRATE=1
- 6.

```
crackz migrate --project <path-to-project-dir>
or
crackz migrate --cfg <path-to-project-yaml>
```

```
-migrate-files --dry-run --no-backup <file>.bak -
```

```
Using project directory
crackz migrate --project my_project --dry-run
crackz migrate --project my_project

Using direct YAML file path
crackz migrate --cfg my_project/my_project_project.yaml
```

```
Preview what files would be moved
crackz migrate --project my_project --migrate-files --dry-run

Migrate both schema AND files
crackz migrate --project my_project --migrate-files
```

```
runtime/lightning_logs/ checkpoints/ models/ training/tensorboard/ runtime/tensorboard/ training/lightning_logs/
detections/*.png detections/visualizations/
```

```
{filename}.v{version}.{timestamp}.bak
```

```
myproject_project.v2.20250115_143022.bak
```

```
v2
```

```
20250115_143022
```

```
myproject_project.v2.20250115_143022.bak
.v2.20250115_143022.bak
```

```
CRACKZ_AUTO_MIGRATE=1
```

```
from pathlib import Path
from crackz.project.migration import migrate_project_file

result = migrate_project_file(Path("my_project")) # or path/to_yaml
print(result)
Example result:
{
'status': 'migrated',
'from_version': 2,
'to_version': 3,
'steps': ['2->3: updated to artifacts structure v3 + added crackz_version tracking'],
'path': 'my_project/my_project_project.yaml',
'backup_path': 'my_project/my_project_project.v2.20250115_143022.bak',
```

```
'dry_run': False
}
```

|         | status | from_version | to_version  |
|---------|--------|--------------|-------------|
| steps   |        |              |             |
| dry_run |        | path         | backup_path |

- 1.
- 2.

|  |  |  |
|--|--|--|
|  |  |  |
|--|--|--|

.bak

.bak

# Shell Completion



# Shell Completion

crackz

- 
- 
- 
- 

```
crackz --show-completion bash
crackz --show-completion zsh
crackz --show-completion fish
crackz --show-completion powershell
```

`source` `Invoke-Expression`

```
crackz --install-completion SHELL
```

`SHELL` `bash` `zsh` `fish` `powershell`

```
crackz det<TAB>
```

```
crackz detect
```

```
crackz --install-completion bash
New shell OR
source ~/.bash_completion
```

`bash-completion`

`--show-completion`

```
crackz --install-completion zsh
Then restart shell or:
autoload -U compinit && compinit
```

`$fpath`

`fpath`

```
crackz --install-completion fish
Typically installs into ~/.config/fish/completions/
Reload:
exec fish
```

```
pwsh -File scripts/setup_completion.ps1
Or force re-install:
pwsh -File scripts/setup_completion.ps1 -Force
```

`crackz`


`crackz --install-completion powershell`

```
crackz --show-completion powershell | Out-String | Invoke-Expression
```

. \$PROFILE

```
crackz --install-completion powershell
If the profile wasn't updated, add manually:
Add-Content $PROFILE "crackz --show-completion powershell | Out-String | Invoke-Expression"
. $PROFILE
```

```
crackz --show-completion bash > /tmp/crackz.sh && source /tmp/crackz.sh
source <(crackz --show-completion zsh)
crackz --show-completion fish | source
crackz --show-completion powershell | Out-String | Invoke-Expression
```



```
crackz --show-completion bash > .crackz_comp.sh
source .crackz_comp.sh
run tests that exercise completion
```

⋮

# Project Scope

# Project Scope

---

- 1.
- 2.
- 3.
- 4.
- 5.

- 
- 
- 
- 
- 

- 1.
- 2.
- 3.
- 4.
- 5.
- 6.
- 7.
- 8.
- 9.
- 10.
- 11.
- 12.

- 1.
- 2.
- 3.

-

- 
- 
- 

- 
- 
- 
- 
- 

- 
- 
- 

- 
- 
- 
- 
- 
- 

- 
- 
- 
- 

- 
- 
- 
- 
- 

- 
- 
- 
- 
- 

- 1.
- 2.
- 3.
- 4.
- 5.

- 1.
- 2.

- 3.
- 4.
- 5.

- 1.
- 2.
- 3.
- 4.
- 5.

- 1.
- 2.
- 3.
- 4.
- 5.

- 1.
- 2.
- 3.
- 4.
- 5.
- 6.

- 
- 
- 
- 
- 
- 

- 
- 
- 
- 
- 

- 
- 
- 
- 
- 

- 
- 
- 
- 
-

- 
- 

- 
- 
- 
- 

- 
- 
- 
- 
- 

- 
- 
- 
- 

---

# Current Tasks

---

## Current Tasks & Backlog

- - [x] Task description
- 
- 
- 

- [illegible]

- •  
•  
•

crackz-gui

crackz.app

crackz-gui

crackz.app.active\_learning

crackz-core

crackz-gui

crackz

crackz-gui

- 

- 

- ○  
○  
○  
○

docs/superpowers/plans/2026-04-21-multiclass-defect-segmentation.md

- 

- 

- 

- 

- 

- 

-

- 
- 
- 
- 
- 
- 
- 
- 
- 
- 
- 
- 
- 
- 

crackz report export --format docx

- 
- 
- 
- 
- 
- 
- 
- 
- 
- 
- 
- 
- 
- 

\_\_\_\_\_

- 
- 
- 
- 
- 
- 
- 
- 
- 
- 
- 
- 
- 
-



•  
•  
•  
•

•  
•  
•

•

•

•  
•  
•

•  
•  
•

•

•

•  
•

•

•

•  
•  
•

•  
•  
•

•

•

•  
•

•

•

•  
•  
•

•  
•  
•  
•

—

•  
•  
•  
•

•  
•  
•

—

•  
•  
•  
•  
•  
•  
•

•  
•  
•  
•  
•  
•  
•

•  
•  
•  
•  
•  
•  
•

—

•  
•  
•  
•  
•  
•  
•  
•

- \_\_\_\_\_
- 

- 
- \_\_\_\_\_
- 
- 
- 

- 
- 
- 
- 

- 1.
- 2.
3. \_\_\_\_\_
4. \_\_\_\_\_
- 5.

update task list

docs:

# Architecture

# System Architecture

```
crackz/
├── pyproject.toml # Workspace root
├── core/ # Workspace config, dev deps, tool settings (no [project])
│ ├── pyproject.toml # crackz-core package
│ ├── src/crackz/ # Package metadata and dependencies
│ ├── tests/ # Core library (AI, CLI, config, logging, project)
│ └── gui/ # Core unit + integration tests
│ ├── pyproject.toml # crackz-gui package (depends on crackz-core)
│ ├── src/crackz gui/ # Package metadata, dependency on crackz-core
│ └── tests/ # PySide6 Qt GUI application
└── tests/ # GUI unit + integration tests
 # Root-level tests (cross-package, legacy)
```

```
core/
crackz_gui.qt import ...

uv sync --dev

gui/
from crackz.ai import ...

core/
from
```



```
graph TD
 subgraph L4["Layer 4 – Presentation"]
 CLI["crackz.cli"]
 GUI["crackz_gui"]
 DASH["crackz.dashboard"]
 end
 subgraph L3["Layer 3 – Application Façade"]
 APP["crackz.app"]
 end
 subgraph L2["Layer 2 – Domain"]
 AI["crackz.ai"]
 PROJECT["crackz.project"]
 REPORT["crackz.report"]
 end
 subgraph L1["Layer 1 – Infrastructure"]
 CONFIG["crackz.config"]
 LOG["crackz.log"]
 TRACING["crackz.tracing"]
 UTIL["crackz.util"]
 end

 CLI --> APP
 GUI --> APP
 DASH --> APP
 APP --> AI
 APP --> PROJECT
 APP --> REPORT
 AI --> CONFIG
 AI --> LOG
 AI --> UTIL
 PROJECT --> CONFIG
 PROJECT --> LOG
 PROJECT --> UTIL
 REPORT --> CONFIG
 REPORT --> LOG
 CONFIG --> LOG
 CONFIG --> UTIL
```

```
crackz.cli crackz_gui crackz.dashboard
crackz_gui crackz.dashboard crackz.cli
crackz.dashboard crackz.cli crackz_gui
crackz.app
crackz.ai
crackz.project
crackz.report
crackz.config crackz.project crackz.log crackz.util crackz.ai crackz.report
crackz.log
crackz.tracing crackz.log
crackz.util crackz.log

 .importlinter scripts/check_architecture.py

run task pre_commit
```

uv

```
graph LR
 Dataset[Dataset] --> raw_train_val_test[raw/ train/ val/ test/]
 raw_train_val_test --> pydantic_settings[pydantic-settings]
 raw_train_val_test --> CrackzDataset[CrackzDataset]
 loguru[loguru] --> artifacts_models[artifacts/models/]
 artifacts_models --> artifacts_runtime[artifacts/runtime/]
```

- 1.
- 2.
- 3.
4. `crackz detect train`
- 5.
- 6.
- 7.
8. `artifacts/models/`
9. `crackz detect run`
10. `segmentation-models-pytorch`

```
project.yaml
```

```
ai:
 model:
 encoder: resnet34 # or efficientnet-b0, mobilenet_v2, etc.
 encoder weights: imagenet # or None for random initialization
```

```

C4Container
title Crackz - Container View (Implemented)
Person(user, "User")
System Boundary(crackz, "Crackz Local System") {
 Container(cli, "CLI", "Typer", "Command parsing & dispatch")
 Container(gui, "GUI", "PySide6 (Qt 6)", "Desktop inspection & invocation")
 Container(core, "Core Library", "Python Packages", "project, ai, config, logging")
 Container(fs, "Local Filesystem", "images/ + artifacts/", "Images, masks, checkpoints, metrics")
}
Rel(user, cli, "Runs commands")
Rel(user, gui, "Interacts (point & click)")
Rel(cli, core, "Invokes APIs")
Rel(gui, core, "Invokes APIs")
Rel(core, fs, "read/write images, masks, checkpoints, metrics")

```

```

C4Context
title Crackz - System Context (Local)
Person(user, "User", "Engineer / Operator")
System(local, "Crackz Application", "CLI + GUI + Core Library")
System_Ext(osfs, "Host Filesystem", "Images + Artifacts")
Rel(user, local, "Invoke CLI / Launch GUI")
Rel(local, osfs, "read / write")

```

```

C4Component
title Core Library Components (Implemented)
Container(core, "core", "Python")
Component(project, "Project & Paths", "pydantic", "Project metadata & path helpers")
Component(config, "Configuration", "pydantic-settings", "Merge defaults / env / YAML")
Component(importer, "Image Importer", "Pillow", "Resize, quality, organize splits & masks")
Component(dataset, "Dataset Layer", "Torch Dataset", "CrackzDataset + DataLoader factory")
Component(train, "Training Orchestrator", "PyTorch Lightning", "Fit/validate/test + callbacks")
Component(detect, "Detection Pipeline", "PyTorch", "Batch inference over dataset splits (raw/test)")
Component(metrics, "Metrics & Checkpoints", "Lightning + JSON", "Save val/test metrics & best.ckpt/last.ckpt")
Component(perf, "Performance Utilities", "Seeding", "Seed + trainer overrides")
Component(logging, "Logging", "loguru", "Structured log sink & setup")
Component(evaluation, "Evaluation Framework", "Metrics", "IoU, precision, recall, F1, accuracy")
Component(reporter, "Report Generator", "python-docx", "Branded Word reports")
Component(viz, "Visualization", "Matplotlib", "Detection overlays (3-panel)")
Component(pipeline_orch, "Pipeline Orchestrator", "Workflow", "Train-detect + cancellation")
Component(device_mgmt, "Device Management", "Abstraction", "CPU/GPU/MPS selection")
Component(severity, "Severity Classifier", "Categorization", "3-tier crack severity")
Component(suggester, "Mask Suggester", "Semi-automation", "Model-assisted annotation")
Component(perf_est, "Performance Estimator", "RuntimeTracker", "Time estimates")
Component(async_cb, "Async Callbacks", "Janus", "Sync/async bridging")
Component(tracing_mod, "Tracing", "OpenTelemetry", "AI API observability")
Component(ai_chat_svc, "AI Chat", "Anthropic", "User assistance")
Rel(importer, project, "Uses path layout")
Rel(dataset, project, "Resolves split directories")
Rel(train, dataset, "Consumes (train/val/test) loaders")
Rel(detect, dataset, "Consumes detection loader (raw or test)")

```

```

Rel(train, metrics, "Saves checkpoints + metrics")
Rel(detect, metrics, "Writes detection results JSON/PNGs")
Rel(project, config, "Initializes from effective settings")
Rel(train, perf, "Reads overrides / seed")
Rel(detect, perf, "Sets seed (optional)")
Rel(dataset, logging, "Reports warnings (missing masks / size mismatch)")
Rel(detect, evaluation, "Evaluates performance")
Rel(evaluation, metrics, "Calculates metrics")
Rel(detect, viz, "Visualizes results")
Rel(detect, reporter, "Generates reports")
Rel(train, pipeline_orch, "Orchestrated by")
Rel(detect, pipeline_orch, "Orchestrated by")
Rel(train, device_mgmt, "Selects device")
Rel(detect, device_mgmt, "Selects device")
Rel(detect, severity, "Categorizes cracks")
Rel(suggester, detect, "Uses model")
Rel(train, perf_est, "Tracks runtime")
Rel(detect, perf_est, "Tracks runtime")
Rel(train, async_cb, "Reports progress")
Rel(detect, async_cb, "Reports progress")
Rel(ai_chat_svc, tracing_mod, "Optionally traced")

```

#### flowchart LR

```

A["Test Dataset"] --> B["Evaluator"]
B --> C["Metrics Calculator"]
C --> D["Evaluation Results"]
D --> E["JSON/CSV Reporter"]
E --> F["Report Generator"]
F --> G["Branded Word Document"]
I["Detection Results"] --> J["Visualization"]
J --> K["Detection Overlays"]
I --> F

```

#### flowchart TB

```

A["Training Thread (sync)"] --> B["CallbackDispatcher.sync_q"]
B --> C["Janus Queue"]
C --> D["CallbackDispatcher.async_q"]
D --> E["GUI Event Loop (async)"]
E --> F["UI Update"]

```

#### flowchart LR

```

A["Import Command / GUI Action"] --> B["Image Importer"]
B --> C["Split Directories (images/*, masks/*)"]
C --> D["Train Command"]
D --> E["Training Orchestrator
(Trainer.fit)"]
E --> F["Checkpoints & Metrics
(best.ckpt / last.ckpt / JSON)"]
F --> G["Detect Command"]
G --> H["Inference Loop
(sigmoid + threshold)"]
H --> I["Annotated Output
(PNGs + detection_results.json)"]

```

#### sequenceDiagram

```

participant User
participant CLI as CLI / GUI
participant Project
participant Import as ImageImporter
participant FS as Filesystem
User->>CLI: import-images --src ./samples --type train
CLI->>Project: load_project(path|yaml)
CLI->>Import: iterate source images
Import->>FS: resize + normalize + write split file
Import->>FS: write mask (if provided)
Import-->>CLI: progress callback
CLI-->>User: summary (count, skipped)

```

```
sequenceDiagram
 participant User
 participant CLI as CLI / GUI
 participant Project
 participant DS as CrackzDataset
 participant Trainer as Lightning Trainer
 participant Model
 participant FS as Filesystem
 User->>CLI: detect train --project P
 CLI->>Project: load_project()
 CLI->>DS: build train/val/test datasets
 DS-->>CLI: DataLoaders
 CLI->>Trainer: fit(model, loaders)
 Trainer->>FS: save best.ckpt / last.ckpt
 Trainer-->>CLI: metrics (val/test)
 CLI->>User: training summary
 User->>CLI: detect run --project P
 CLI->>Project: load_project()
 CLI->>Model: load checkpoint (best or last)
 CLI->>DS: build raw dataset (or test)
 DS-->>CLI: DataLoader
 CLI->>Model: forward (batched)
 Model-->>CLI: probabilities
 CLI->>CLI: threshold -> mask
 CLI->>FS: write annotated PNG + JSON metrics
 CLI-->>User: detection summary
```

```
flowchart TD
 Defaults[Built-in Defaults] --> Merge
 YAML[Project YAML] --> Merge
 Env[Environment] --> Merge
 Merge --> Effective[Effective Settings]
```

```
flowchart LR
 User([User]) --> CLI["CLI (Typer)"]
 User --> GUI["GUI (PySide6)"]
 CLI --> CORE["Core Library"]
 GUI --> CORE
 CORE --> FS["Filesystem
images / artifacts/models / artifacts/runtime"]
 CORE -.optional.-> GPU["GPU"]

 subgraph Optional_Docker [Optional Docker]
 IMG["Container Image
(Python 3.13 + deps)"]
 end

 %% Show that container can host CLI/GUI
 IMG --> CLI
 IMG --> GUI
```

|  |                            |  |
|--|----------------------------|--|
|  |                            |  |
|  | crackz.project.project     |  |
|  | pydantic-settings          |  |
|  | project.import_images      |  |
|  | crackz.ai.data             |  |
|  | crackz.ai.detection.train  |  |
|  | crackz.ai.detection.detect |  |
|  | crackz.ai.model            |  |
|  | crackz.ai.checkpoints      |  |
|  | crackz.ai.device           |  |
|  | crackz.util                |  |
|  | crackz.ai.performance      |  |
|  | crackz.log.crackz_logger   |  |
|  | crackz_gui.*               |  |
|  | crackz.ai.evaluation       |  |
|  | crackz.report.generator    |  |
|  | crackz.ai.visualization    |  |



crackz.ai.pipeline  
crackz.ai.pipeline.cancellation  
crackz.ai.detection.severity  
crackz.ai.mask\_suggester  
crackz.ai.performance.runtime\_estimation  
crackz.ai.core.async\_callbacks  
crackz.tracing  
crackz\_gui.services.ai\_chat

test/

raw/

train/

val/

- 
- - 
  - 
  - 
  - 
  - 
  - 
  - 
  - 
  - 
  -
- 


core/

gui/

*Last updated: synchronized with repository implementation on commit timeline of current editing session.*

# Architecture Guidelines

# Architecture Guidelines



|                                       |                      |
|---------------------------------------|----------------------|
| User Interfaces (CLI, GUI)            | ↳ Entry points       |
| Business Logic (Commands, Operations) | ↳ Use cases          |
| Core Domain (Project, AI, Config)     | ↳ Domain models      |
| Infrastructure (Logging, Storage)     | ↳ Technical concerns |

```
[] GOOD: Clear separation
core/src/crackz/cli/detection_cli.py - CLI commands only
core/src/crackz/ai/detection.py - Detection logic only
core/src/crackz/project/structure.py - Project layout only

x BAD: Mixed concerns
core/src/crackz/everything.py - CLI, detection, project management all in one file
```

```
[] GOOD: Depend on protocol
from typing import Protocol

class ModelProtocol(Protocol):
 def predict(self, image: torch.Tensor) -> torch.Tensor: ...

def run_detection(model: ModelProtocol, image: torch.Tensor) -> dict:
 """Works with any model implementing the protocol."""
 return {"mask": model.predict(image)}

x BAD: Depend on concrete class
def run_detection(model: SegmentationModel, image: torch.Tensor) -> dict:
 """Tightly coupled to SegmentationModel."""
 return {"mask": model.predict(image)}
```

```
[] GOOD: Single responsibility
class ProjectLoader:
 """Loads project configuration from disk."""
 def load(self, path: Path) -> ProjectConfig: ...

class ProjectValidator:
 """Validates project structure and configuration."""
 def validate(self, project: ProjectConfig) -> list[str]: ...

x BAD: Multiple responsibilities
class ProjectManager:
 """Loads, validates, trains models, exports results."""
 def load(self, path: Path) -> ProjectConfig: ...
 def validate(self, project: ProjectConfig) -> list[str]: ...
 def train_model(self, project: ProjectConfig) -> None: ...
 def export_results(self, project: ProjectConfig) -> None: ...
```

```
[] GOOD: Extensible via configuration
def create_model(config: ModelConfig) -> nn.Module:
 """Factory method - add new encoders via config."""
 if config.encoder in SUPPORTED_ENCODERS:
 return create_segmentation_model(config)
 raise ValueError(f"Unsupported encoder: {config.encoder}")

x BAD: Requires code changes for new models
def create_model(encoder_name: str) -> nn.Module:
 if encoder_name == "resnet34":
 return ResNet34Model()
 elif encoder_name == "efficientnet":
 return EfficientNetModel()
 # Must modify this function for each new encoder!
```

```
[] GOOD: Explicit parameters
def train_model(
 project_path: Path,
 epochs: int,
 batch_size: int,
 learning_rate: float,
) -> dict[str, float]:
 """All parameters explicit."""
 pass
```

```
x BAD: Implicit global state
GLOBAL_CONFIG = {} # Modified elsewhere

def train_model():
 """What parameters? Where do they come from?"""
 epochs = GLOBAL_CONFIG["epochs"] # Implicit dependency
```

```
core/src/crackz/ # Core library (crackz-core package)
├─ ai/ # AI/ML pipeline (domain logic)
│ ├── data.py # Dataset, data loading
│ ├── models.py # Model definitions
│ ├── training.py # Training pipeline
│ └── detection.py # Inference pipeline
├─ cli/ # CLI interface (entry points)
│ ├── options.py # Shared CLI options
│ ├── exceptions.py # CLI error handling
│ ├── project_cli.py
│ └── detection_cli.py
├─ config/ # Configuration (domain models)
│ ├── project.py # ProjectConfig
│ ├── ai.py # AIConfig
│ └── logging.py # LogConfig
├─ log/ # Logging (infrastructure)
│ ├── setup.py # Loguru configuration
├─ project/ # Project management (domain logic)
│ └── structure.py # Directory layout

gui/src/crackz_gui/ # GUI package (crackz-gui, depends on crackz-core)
├─ qt/ # PySide6 Qt application
│ ├── app_state.py # QtAppState (reactive state)
│ └── async_bridge.py # TaskSignals, run_in_background
├─ services/ # External service integrations
├─ state/ # State management
└─ util/ # GUI utilities
```

```
CLI (core) → Business Logic → Domain Models → Infrastructure
GUI (gui) → (ai/, project/) (config/) (log/)
```

Examples:

```
- core: cli/detection_cli.py → ai/detection.py → config/ai.py → log/setup.py □
- gui: crackz_gui/qt/panels/train.py → crackz.ai.training → crackz.config □
- gui: crackz-gui depends on crackz-core (declared in gui/pyproject.toml) □
```

```
Domain →X- GUI/CLI # Domain shouldn't know about UI
Infrastructure →X- Domain # Infrastructure shouldn't depend on business logic
GUI →X- CLI # GUI shouldn't import CLI modules
```

Examples:

```
- ai/detection.py → cli/options.py x # Domain shouldn't import from CLI
- log/setup.py → config/project.py x # Infrastructure shouldn't import domain
- crackz_gui → crackz.cli x # GUI should use core APIs, not CLI
```

```
x BAD: Domain imports from CLI
from crackz.cli.options import PROJECT_PATH_OPTION
def train_model(project_path: Path = PROJECT_PATH_OPTION): ...

□ GOOD: CLI calls domain with explicit parameters
from crackz.cli.options import PROJECT_PATH_OPTION
from crackz.ai.training import train_model

def train_cli(project_path: Path = PROJECT_PATH_OPTION):
 train_model(project_path) # Domain function has no CLI dependency
```

core/src/crackz/ai/models.py

```
def create_segmentation_model(config: ModelConfig) -> nn.Module:
 """Factory for creating segmentation models."""
 import segmentation_models_pytorch as smp

 return smp.Unet(
 encoder_name=config.encoder,
 encoder_weights=config.encoder_weights,
 in_channels=config.in_channels,
 classes=config.num_classes,
)
```

core/src/crackz/ai/detection.py

```
class DetectionStrategy(Protocol):
 def detect(self, images: list[Path]) -> dict[Path, np.ndarray]: ...

class SingleImageDetection:
 def detect(self, images: list[Path]) -> dict[Path, np.ndarray]:
 """Process one at a time."""
 return {img: self._detect_one(img) for img in images}

class BatchDetection:
 def detect(self, images: list[Path]) -> dict[Path, np.ndarray]:
 """Process in batches for efficiency."""
 results = {}
 for batch in chunk_list(images, self.batch_size):
 results.update(self._detect_batch(batch))
 return results
```

core/src/crackz/config/project.py

```
class ProjectConfig(BaseModel):
 """Pydantic acts as builder with validation."""
 name: str
 project_path: Path
 training: TrainingConfig = Field(default_factory=TrainingConfig)
 logging: LogConfig = Field(default_factory=LogConfig)

 @classmethod
 def load(cls, path: Path) -> ProjectConfig:
 """Build from YAML with defaults."""
 with open(path) as f:
 data = yaml.safe_load(f)
 return cls(**data) # Validation + defaults applied
```

core/src/crackz/cli/\*.py

```
@app.command(name="train")
def train_command(
 project_path: Path = PROJECT_PATH_OPTION,
 epochs: int | None = EPOCHS_OPTION,
) -> None:
 """Each CLI command is a self-contained operation."""
 try:
 # Load configuration
 config = ProjectConfig.load(project_path / f"{project_path.name}_project.yaml")

 # Override with CLI args
 if epochs:
 config.training.epochs = epochs

 # Execute
 train_model(config)
```

```
typer.secho("[] Training completed", fg=typer.colors.GREEN)
except Exception as e:
 cli_failure(e, "Training")
```

core/src/crackz/project/structure.py

```
class ProjectRepository:
 """Abstracts project storage."""

 def load(self, path: Path) -> ProjectConfig:
 """Load project from filesystem."""
 return ProjectConfig.load(path / f"{path.name}_project.yaml")

 def save(self, project: ProjectConfig) -> None:
 """Save project to filesystem."""
 project.save(project.project_path / f"{project.name}_project.yaml")

 def exists(self, path: Path) -> bool:
 """Check if project exists."""
 return (path / f"{path.name}_project.yaml").exists()
```

core/src/crackz/ai/core/async\_callbacks.py

RuntimeError: no running event loop

sync\_q

async\_q

```
from crackz.ai.core.async_callbacks import CallbackDispatcher

In training setup (main thread)
dispatcher = CallbackDispatcher(maxsize=100)

In PyTorch Lightning callback (training thread)
sync_reporter = dispatcher.create_sync_progress_reporter()
sync_reporter(0.5, "Training epoch 5/10") # Thread-safe put

In GUI (async event loop)
async for progress, message in dispatcher.iter_progress():
 update_progress_bar(progress, message) # Async get
```

AsyncProgressReporter AsyncMetricsReporter

core/src/crackz/tracing/

--extra tracing

```
In core/src/crackz/tracing/setup.py
from crackz.tracing import setup_tracing, is_tracing_enabled

Automatic instrumentation on setup
if is_tracing_enabled():
 setup_tracing() # Instruments Anthropic client automatically

The instrumentation happens automatically via AnthropicInstrumentor
No manual client instrumentation needed
```

```
Install tracing dependencies
uv sync --extra tracing

Enable at runtime
export CRACKZ_TRACING_ENABLED=1
```

```
core/src/crackz/ai/evaluation/reporter.py core/src/crackz/report/generator.py
```

```
from crackz.ai.evaluation.reporter import export_json, export_csv
from crackz.report.generator import ReportGenerator

Aggregation (format-agnostic)
results = {
 "accuracy": 0.95,
 "precision": 0.92,
 "recall": 0.89,
 "f1_score": 0.90,
 "iou": 0.85
}

Export to JSON (lightweight)
export_json(
 results,
 output_path=project_path / "evaluation_results.json"
)

Export to CSV (analysis-friendly)
export_csv(
 results,
 output_path=project_path / "evaluation_results.csv"
)

Export to DOCX (rich formatting)
generator = ReportGenerator(
 project_path=project_path,
 template_path=template_path
)
generator.generate_report(
 detection_results=results,
 output_path=project_path / "report.docx"
)
```

```
core/src/crackz/ai/device/device.py
```

```
torch.device("cuda")
```

```
from crackz.ai.device.device import AIDevice

Auto-select best available device
device = AIDevice.default() # Returns CUDA if available, else MPS, else CPU

Check availability
available = AIDevice.available_devices() # [AIDevice.CPU, AIDevice.CUDA]

Test device works
success, message, details = AIDevice.test_device("cuda")
if success:
 print(f"CUDA available: {details['device_name']}")

Use in model
model = SegmentationModel()
model.to(device.value) # device.value is "cuda", "mps", "cpu", etc.
```

core/src/crackz/ai/detection/severity.py

```
from crackz.ai.detection.severity import categorize_crack_severity

Default thresholds: 5% (high), 2% (medium)
severity = categorize_crack_severity(confidence=0.08) # "Crack Detected"
severity = categorize_crack_severity(confidence=0.03) # "Suspected Crack"
severity = categorize_crack_severity(confidence=0.01) # "No Crack"

Custom thresholds via config
severity = categorize_crack_severity(
 confidence=0.04,
 high_threshold=0.06, # Raise "Crack Detected" threshold
 medium_threshold=0.03 # Raise "Suspected" threshold
) # "Suspected Crack" (was "Crack Detected" with defaults)

Override with has_crack flag (confidence + area thresholds met)
severity = categorize_crack_severity(confidence=0.01, has_crack=True)
"Crack Detected" (flag indicates combined criteria met)
```

```
project.yaml
ai:
 detection:
 high_confidence_threshold: 0.05 # 5% crack area
 medium_confidence_threshold: 0.02 # 2% crack area
 min_confidence: 0.005 # 0.5% minimum to save
```

```
core/src/crackz/cli/options.py
PROJECT_PATH_OPTION = typer.Option(
 None,
 "--project",
 help="Path to project directory",
)

FORCE_OPTION = typer.Option(
 False,
 "--force",
 help="Force operation without confirmation",
)

core/src/crackz/cli/some_command.py
from crackz.cli.options import PROJECT_PATH_OPTION, FORCE_OPTION

def my_command(
 project_path: Path | None = PROJECT_PATH_OPTION,
 force: bool = FORCE_OPTION,
) -> None:
 pass
```



```
print() logger typer.echo()
```

```
from crackz.log import logger
import typer

User-facing success/error messages
typer.secho("[] Detection completed", fg=typer.colors.GREEN)
typer.secho("x Training failed", fg=typer.colors.RED)

Technical/operational logs
logger.info("Loading {} images from {}", len(images), path)
logger.debug("Model config: {}", config.model_dump())
logger.error("Failed to load checkpoint: {}", error, exc_info=True)
```

```
typer.secho()
```

```
logger.*
```

```
print() typer.echo()
```

```
from crackz.cli.exceptions import cli_failure

def train_command():
 try:
 # Business logic
 result = train_model(project_path)
 typer.secho("[] Training completed", fg=typer.colors.GREEN)
 except FileNotFoundError as e:
 cli_failure(e, "File access")
 except RuntimeError as e:
 cli_failure(e, "Training execution")
 except Exception as e:
 cli_failure(e, "Unexpected error")
```

```
cli_failure
```

```
logger.error()
```


```
typer.secho()
```

```
class AIConfig(BaseModel):
 model: ModelConfig = Field(default_factory=ModelConfig)
 training: TrainingConfig = Field(default_factory=TrainingConfig)

Usage
config = AIConfig() # Loads from defaults only
config_from_yaml = AIConfig(**yaml_data) # Loads from YAML + defaults

CLI override (doesn't persist to YAML)
if cli_epochs:
 config.training.epochs = cli_epochs # Runtime only
```

```
logger.info("message")
↓
```



```

from loguru import logger

Configure at startup
logger.add(
 central_log_path,
 format="{time} {level} {message}",
 level="INFO",
)

Add project-specific handler when project opens
logger.add(
 project_log_path,
 format="{time} {level} {message}",
 level="DEBUG",
 filter=lambda record: record["extra"].get("project") == project_name,
)

Usage
logger.bind(project=project.name).info("Training started") # Goes to both logs

```

frozen=False

schema\_version

Field(description=...)

```

class ProjectConfig(BaseModel):
 """Project configuration with validation and versioning."""

 schema_version: int = Field(
 default=2,
 ge=1,
 description="Config schema version for migration support",
)

 name: str = Field(
 ..., # Required
 min_length=1,
 max_length=100,
 pattern=r"^[a-zA-Z0-9_-]+$",
 description="Project name (alphanumeric, underscore, hyphen)",
)

 root: Path = Field(
 ..., # Required
 description="Project root directory",
)

 ai: AIConfig = Field(
 default_factory=AIConfig,
 description="AI/ML configuration",
)

 @field_validator("root")
 @classmethod
 def root_must_exist(cls, v: Path) -> Path:
 """Validate project root exists."""
 if not v.exists():
 raise ValueError(f"Project root does not exist: {v}")
 return v

 @model_validator(mode="after")
 def name_matches_root(self) -> Self:
 """Validate name matches root directory."""
 if self.root.name != self.name:
 raise ValueError(f"Name '{self.name}' doesn't match directory '{self.root.name}'")
 return self

```

schema\_version: int

crackz migrate &lt;project&gt;

```
def migrate_v1_to_v2(config_data: dict) -> dict:
 """Migrate project config from v1 to v2."""
 if config_data.get("schema_version", 1) == 1:
 # v2 added 'ai.detection.batch_size'
 if "ai" not in config_data:
 config_data["ai"] = {}
 if "detection" not in config_data["ai"]:
 config_data["ai"]["detection"] = {}
 if "batch_size" not in config_data["ai"]["detection"]:
 config_data["ai"]["detection"]["batch_size"] = 8

 config_data["schema_version"] = 2

 return config_data
```

- 1.
- 2.
- 3.
- 4.
- 5.
- 6.
- 7.
- 8.
- 9.
- 10.
- 11.
- 12.

```
class CrackzError(Exception):
 """Base exception for all Crackz errors."""
 pass

class ConfigurationError(CrackzError):
 """Invalid configuration."""
 pass

class ProjectError(CrackzError):
 """Project-related error."""
 pass

class ModelError(CrackzError):
 """Model loading/execution error."""
 pass
```

```
def command():
 try:
 # Business logic
 result = operation()
 typer.secho("✅ Success", fg=typer.colors.GREEN)


 except FileNotFoundError as e:
 # User error: file doesn't exist
 logger.error("File not found: {}", e)
 typer.secho(f"❌ File not found: {e}", fg=typer.colors.RED)
 raise typer.Exit(1)

 except ConfigurationError as e:
 # User error: invalid config
 logger.error("Configuration error: {}", e)
 typer.secho(f"❌ Configuration error: {e}", fg=typer.colors.RED)
 raise typer.Exit(1)

 except MemoryError:
 # System error: out of memory
 logger.error("Out of memory during operation")
 typer.secho("❌ Out of memory. Try reducing batch size.", fg=typer.colors.RED)
 raise typer.Exit(1)

 except Exception as e:
 # Programmer error: unexpected
 logger.exception("Unexpected error: {}", e)
```

```
typer.secho("x Unexpected error. Check logs for details.", fg=typer.colors.RED)
raise typer.Exit(1)
```



```
core/tests/
├── unit/ # Fast, isolated, no I/O
│ ├── crackz/
│ │ ├── ai/
│ │ │ ├── test_models.py # Model creation, logic
│ │ │ ├── test_training.py # Training loop logic
│ │ │ └── test_detection.py # Detection logic
│ │ ├── cli/
│ │ │ ├── test_options.py # CLI option validation
│ │ │ └── test_commands.py # Command parsing
│ │ └── config/
│ │ └── test_project.py # Config validation
│ └── integration/ # Slower, system-level, I/O allowed
│ ├── crackz/
│ │ ├── test_cli_workflows.py # End-to-end CLI
│ │ └── test_training_pipeline.py # Full training
│ └── docs/
│ └── test_docs_build.py # Documentation build
└── gui/tests/
 ├── unit/ # GUI unit tests
 └── integration/ # GUI integration tests
```

```
def test_model_creation():
 """Test model factory with different configs."""
 # Arrange
 config = ModelConfig(encoder="resnet34", num_classes=1)

 # Act
 model = create_segmentation_model(config)

 # Assert
 assert isinstance(model, nn.Module)
 assert hasattr(model, "encoder")
 assert hasattr(model, "decoder")
```

```
@pytest.mark.integration
def test_full_training_workflow(tmp_path):
 """Test complete training workflow."""
 # Arrange
 project = create_test_project(tmp_path, num_images=10)

 # Act
 result = train_model(project, epochs=1)

 # Assert
 assert result["final_loss"] < result["initial_loss"]
 assert (project.project_path / "artifacts" / "models" / "checkpoint.ckpt").exists()
```

```
@pytest.mark.benchmark
def test_detection_performance(benchmark, sample_images):
 """Ensure detection meets performance targets."""
 model = load_model(TEST_CHECKPOINT)

 result = benchmark(detect_cracks, model, sample_images)

 # Verify performance target: <5s per image on CPU
 assert result.mean < 5.0
```

core/tests/conftest.py

```
@pytest.fixture
def tiny_model():
 """Fast model for unit tests."""
 return create_segmentation_model(ModelConfig(
 encoder="resnet18",
 encoder_weights=None, # No pre-trained weights
 num_classes=1,
))

@pytest.fixture
def sample_project(tmp_path):
 """Sample project with test data."""
 project_dir = tmp_path / "test_project"
 initialize_project(project_dir, name="test_project")

 # Add minimal test data
 (project_dir / "images" / "raw").mkdir(parents=True)
 create_test_image(project_dir / "images" / "raw" / "test.png")

 return project_dir

@pytest.fixture
def mock_model(mocker):
 """Mock model for testing without actual inference."""
 mock = mocker.Mock(spec=nn.Module)
 mock.predict.return_value = torch.zeros(1, 1, 512, 512)
 return mock
```

```
x BAD: Load everything into memory
all_images = [Image.open(p) for p in image_paths] # OOM for large datasets
for img in all_images:
 process(img)

[] GOOD: Process in batches
for batch_paths in chunk_list(image_paths, batch_size=8):
 batch = [Image.open(p) for p in batch_paths]
 process_batch(batch)
 # batch garbage collected after each iteration
```

```
def train_with_cleanup():
 try:
 # Training code
 model.train()
 for batch in dataloader:
 loss = model.training_step(batch)
 loss.backward()
 optimizer.step()
 finally:
 # Always clean up GPU memory
 if torch.cuda.is_available():
 torch.cuda.empty_cache()
```

```
class Project:
 def __init__(self, root: Path):
 self.root = root
 self.config: ProjectConfig | None = None # Not loaded yet
 self.images: list[Path] | None = None # Not loaded yet

 @property
 def config(self) -> ProjectConfig:
 """Lazy load configuration."""
 if self._config is None:
 self._config = ProjectConfig.load()
```

```

 self.root / f"{self.root.name}_project.yaml"
)
 return self._config

@property
def images(self) -> list[Path]:
 """Lazy load image list."""
 if self._images is None:
 self._images = list((self.root / "images").rglob("*.png"))
 return self._images

```

- 1.
- 2.
- 3.
- 4.
- 5.

```

from pydantic import BaseModel, Field, validator

class ProjectConfig(BaseModel):
 name: str = Field(
 ...,
 min_length=1,
 max_length=100,
 pattern=r"^[a-zA-Z0-9_-]+$", # Prevent path traversal
)

 @validator("name")
 def no_path_traversal(cls, v: str) -> str:
 """Prevent directory traversal attacks."""
 if "." in v or "/" in v or "\\" in v:
 raise ValueError("Invalid project name: contains path separators")
 return v

```

```

def safe_path_join(base: Path, *parts: str) -> Path:
 """Join paths safely, preventing traversal attacks."""
 result = base
 for part in parts:
 if "." in part or part.startswith("/") or part.startswith("\\"):
 raise ValueError(f"Unsafe path component: {part}")
 result = result / part

 # Verify result is still under base
 if not result.resolve().is_relative_to(base.resolve()):
 raise ValueError("Path traversal detected")

 return result

```

1. `core/src/crackz/cli/my_command.py`
- 2.

```

from __future__ import annotations

import typer
from crackz.cli.options import PROJECT_PATH_OPTION
from crackz.cli.exceptions import cli_failure
from crackz.log import logger

app = typer.Typer(no_args_is_help=True)

@app.command(name="my-command")
def my_command(
 project_path: Path = PROJECT_PATH_OPTION,
) -> None:
 """Description shown in --help."""

```

```

try:
 # Business logic
 logger.info("Starting operation")
 result = do_operation(project_path)
 typer.secho("[] Operation completed", fg=typer.colors.GREEN)
except Exception as e:
 cli_failure(e, "Operation name")

```

3. `core/src/crackz/cli/main.py`
4. `core/tests/unit/crackz/cli/test_my_command.py`
- 5.

1. `core/src/crackz/config/my_feature.py`

```

from pydantic import BaseModel, Field

class MyFeatureConfig(BaseModel):
 """Configuration for my feature."""

 enabled: bool = Field(
 default=False,
 description="Enable my feature",
)

 option: str = Field(
 default="default_value",
 description="Feature option",
)

```

2. `core/src/crackz/config/project.py`

```

class ProjectConfig(BaseModel):
 # ... existing fields ...
 my_feature: MyFeatureConfig = Field(default_factory=MyFeatureConfig)

```

3. `core/src/crackz/project/migrations.py`
- 4.
- 5.

1. `core/src/crackz/ai/models/my_model.py`

2.

```

class MyCustomModel(nn.Module):
 def __init__(self, config: ModelConfig):
 super().__init__()
 # Model setup

 def forward(self, x: torch.Tensor) -> torch.Tensor:
 # Forward pass
 return x

 def predict(self, x: torch.Tensor) -> torch.Tensor:
 """Inference interface."""
 self.eval()
 with torch.no_grad():
 return self(x)

```

3. `core/src/crackz/ai/models/__init__.py`

```

def create_model(config: ModelConfig) -> nn.Module:
 if config.type == "segmentation":
 return create_segmentation_model(config)
 elif config.type == "my_custom":
 return MyCustomModel(config)
 else:
 raise ValueError(f"Unknown model type: {config.type}")

```

4. `core/src/crackz/config/ai.py`
- 5.

1. `core/src/crackz/ai/detection/my_strategy.py`

2.

```

class MyDetectionStrategy:
 def __init__(self, model: nn.Module, config: DetectionConfig):
 self.model = model
 self.config = config

 def detect(self, images: list[Path]) -> dict[Path, np.ndarray]:
 """Run detection with my strategy."""
 results = {}
 for image_path in images:
 mask = self._detect_single(image_path)
 results[image_path] = mask
 return results

```

3. `core/src/crackz/ai/detection/__init__.py`

4. `core/src/crackz/config/ai.py`
5.

- \_\_\_\_\_
- \_\_\_\_\_
- \_\_\_\_\_
- \_\_\_\_\_

- \_\_\_\_\_
- \_\_\_\_\_
- \_\_\_\_\_
- \_\_\_\_\_
- \_\_\_\_\_

---

# API Reference

---



# API Reference

---

```
from pathlib import Path
from crackz.project.project import load_project_from_path
from crackz.ai.detection import detect

project = load_project_from_path(Path("demo-project"))
Optional: custom progress reporter
progress = lambda p, msg=None: print(f"{p:.0%}", msg or "")

detect(project, progress_reporter=progress)
```

```
from crackz.project.project import load_project_from_path
from crackz.ai.training import train

project = load_project_from_path("demo-project")
train(project) # writes checkpoints & metrics under project.artifacts/checkpoints
```

```
from pathlib import Path
from crackz.project.project import (
 ProjectMetadata, ProjectPaths, create_project, save_project
)

project = create_project(
 metadata=ProjectMetadata(name="demo-project", description="Example"),
 paths=ProjectPaths(
 project_path=Path("demo-project"),
 image_path=Path("demo-project/images"),
 image_mask_path=Path("demo-project/masks"),
 artifacts_path=Path("demo-project/artifacts"),
),
 force=False,
)
save_project(project)
```

```
from crackz.project.project import load_project_from_path
project = load_project_from_path("demo-project")
Uses same logic as CLI import-images (see project.import_images signature)
project.import_images(
 source_path="./samples", # directory with raw images
 masks_source_path="./samples/masks", # optional
 image_type=project.ImagesType.RAW if hasattr(project, 'ImagesType') else None, # or enum from crackz.ImagesType
 size=(512, 512),
 quality=90,
 overwrite=False,
)
```

CrackzSettings

CRACKZ\_

CRACKZ\_LOG\_LEVEL=DEBUG

BaseSettings

► core/src/crackz/config/crackz\_settings.py

classmethod

from\_conf(conf\_file)

► core/src/crackz/config/crackz\_settings.py

CrackzError

► core/src/crackz/config/exceptions.py

[ConfigError](#)

► core/src/crackz/config/exceptions.py

[ConfigError](#)

► core/src/crackz/config/exceptions.py

project.project

Project  
Project

BaseModel

► `core/src/crackz/config/project_config.py`

`classmethod`

`load(path)`

► `core/src/crackz/config/project_config.py`

`save(path)`

► `core/src/crackz/config/project_config.py`

`to_project()`

`Project`

`ProjectConfig`

► `core/src/crackz/config/project_config.py`

`classmethod`

`from_project(project)`

`ProjectConfig`

`Project`

► `core/src/crackz/config/project_config.py`

---

`Project`

`BaseModel`

► `core/src/crackz/project/project.py`

`property`

`name`

`property`

root

property

config\_file

property

detections\_path

Path Path

property

models\_path

Path Path

property

checkpoints\_path

Path Path

property

runtime\_path

Path Path

property

training\_path

property

detections\_visualizations\_path

Path

Path

property

detection\_results\_path

property

training\_metrics\_path

property

tensorboard\_logs\_path

property

registry\_db\_path

property

lightning\_logs\_path

property

val\_path

Path

Path

property

test\_path

Path

Path

property

train\_path

Path Path

property

train\_mask\_path

Path Path

property

val\_mask\_path

Path Path

property

test\_mask\_path

Path Path

property

raw\_path

Path Path

property

raw\_mask\_path

Path Path

property

project\_file\_path

map\_type\_to\_dir(image\_type)

test val raw train

Path

None

► core/src/crackz/project/project.py

map\_type\_to\_masks\_dir(image\_type)

test val raw train

Path

None

► core/src/crackz/project/project.py

save\_project()

model\_dump

model\_dump

► core/src/crackz/project/project.py

```
import_image_files(
 files,
 dest_dir,
 size=(512, 512),
 quality=90,
 *,
 overwrite=False,
 progress_cb=None,
)
```

•  
•  
•

► core/src/crackz/project/project.py

```
import_images(
 source_path,
 masks_source_path=None,
 image_type=ImagesType.RAW,
```

```

size=(512, 512),
quality=90,
*,
overwrite=False,
progress_cb=None,
split=False,
train_ratio=0.7,
val_ratio=0.15,
test_ratio=0.15,
random_seed=None,
)

```

- 
- 
- 
- 
- 

► `core/src/crackz/project/project.py`

```
create_project_dir(*, force)
```

`force`

`project_path`

`artifacts_path`

► `core/src/crackz/project/project.py`

```
clean(*, logs_only=False, keep_best_model=True)
```

► `core/src/crackz/project/project.py`

```

create_project_and_save(
 metadata,
 paths,
 ai=default_ai_config,
 logging=default_logging_config,
 *,
 force=False,
)

```

► `core/src/crackz/project/project.py`

```

create_project(
 metadata, paths, ai=None, logging=None, *, force=False
)

```



► `core/src/crackz/project/project.py`

`save_project(project)`

`Project.save_project`

► `core/src/crackz/project/project.py`

`load_project(project_file_path)`

`Project`

|                                |                   |  |                 |
|--------------------------------|-------------------|--|-----------------|
|                                |                   |  |                 |
| <code>project_file_path</code> | <code>Path</code> |  | <i>required</i> |

|  |  |
|--|--|
|  |  |
|--|--|

|                         |                      |
|-------------------------|----------------------|
| <a href="#">Project</a> | <code>Project</code> |
|-------------------------|----------------------|

|                         |                   |
|-------------------------|-------------------|
| <a href="#">Project</a> | <code>None</code> |
|-------------------------|-------------------|

► `core/src/crackz/project/project.py`

`load_project_from_path(project_path)`

► `core/src/crackz/project/project.py`

`load_from_project_path_or_cfg(cfg, project_path)`

► `core/src/crackz/project/project.py`

StrEnum

RAW

TRAIN

TEST

VAL

► core/src/crackz/project/types.py

CrackzError

► core/src/crackz/project/exceptions.py

[ProjectError](#)

► core/src/crackz/project/exceptions.py

[ProjectError](#)

► core/src/crackz/project/exceptions.py

[ProjectError](#)

► core/src/crackz/project/exceptions.py

[ProjectError](#)

► core/src/crackz/project/exceptions.py

[ProjectError](#)

► core/src/crackz/project/exceptions.py

---

BaseModel

► core/src/crackz/ai/detection/results.py

```
def categorize_crack_severity(
 confidence,
 *,
 high_threshold=DEFAULT_HIGH_CONFIDENCE,
 medium_threshold=DEFAULT_MEDIUM_CONFIDENCE,
 has_crack=False,
)
```

| confidence       | float |  | required                  |
|------------------|-------|--|---------------------------|
| high_threshold   | float |  | DEFAULT_HIGH_CONFIDENCE   |
| medium_threshold | float |  | DEFAULT_MEDIUM_CONFIDENCE |
| has_crack        | bool  |  | False                     |

str

```
>>> categorize_crack_severity(0.08) # 8% crack area
'Crack Detected'
>>> categorize_crack_severity(0.03) # 3% crack area
'Suspected Crack'
>>> categorize_crack_severity(0.01) # 1% crack area
'No Crack'
>>> categorize_crack_severity(0.01, has_crack=True)
'Crack Detected' # has_crack flag indicates both confidence and area thresholds met
```

► core/src/crackz/ai/detection/severity.py

```
create_tensorboard_logger(project)
```

project [Project](#) required

TensorBoardLogger | None

► core/src/crackz/ai/training/tensorboard.py

```
train(
 project,
 progress_reporter=None,
 cancellation_token=None,
 metrics_callback=None,
 ckpt_path=None,
)
```

|                    |                                          |          |
|--------------------|------------------------------------------|----------|
| project            | <a href="#">Project</a>                  | required |
| progress_reporter  | ProgressReporter   None                  | None     |
| cancellation_token | <a href="#">CancellationToken</a>   None | None     |
| metrics_callback   | MetricsReporter   None                   | None     |
| ckpt_path          | Path   None                              | None     |

CancellationError

► core/src/crackz/ai/training/training\_runner.py

```
detect(
 project,
 progress_reporter=None,
 cancellation_token=None,
 checkpoint_name=None,
 result_callback=None,
 *,
 on_incompatible="original",
)
```

|                    |                                          |                                                      |
|--------------------|------------------------------------------|------------------------------------------------------|
| project            | <a href="#">Project</a>                  | required                                             |
| progress_reporter  | ProgressReporter   None                  | None                                                 |
| cancellation_token | <a href="#">CancellationToken</a>   None | None                                                 |
| checkpoint_name    | str   None                               | None                                                 |
| result_callback    | Callable[[dict[str, Any]], None]   None  | None                                                 |
| on_incompatible    | IncompatibleMode                         | <div>"untrained" "original" "raise" 'original'</div> |

None

None detection\_results.json

CancellationError

CheckpointIncompatibleError on\_incompatible "raise"

► core/src/crackz/ai/detection/detection\_runner.py

\_\_getattr\_\_(name)

► `core/src/crackz/ai/detection/__init__.py`

► `core/src/crackz/ai/data/dataset.py`

`apply(im)`

► `core/src/crackz/ai/data/dataset.py`

`Dataset[Sample]`

► `core/src/crackz/ai/data/dataset.py`

`load_image_with_crackz_image(image_path)`

`image_path` `Path` *required*

`Image`

[ImageLoadingError](#)

► `core/src/crackz/ai/data/dataset.py`

```
CrackzDetectionDataset(
 image_dir, transform=None, normalization_config=None
)
```

|                      |                            |  |          |
|----------------------|----------------------------|--|----------|
|                      |                            |  |          |
| image_dir            | Path   str                 |  | required |
| transform            | ImageTransform   None      |  | None     |
| normalization_config | NormalizationConfig   None |  | None     |

|  |  |
|--|--|
|  |  |
|--|--|

[CrackzDataset](#)

► core/src/crackz/ai/data/dataset.py

```
create_training_datasets(
 train_path,
 train_mask_path,
 val_path,
 val_mask_path,
 test_path,
 test_mask_path,
)
```

|                 |      |  |          |
|-----------------|------|--|----------|
|                 |      |  |          |
| train_path      | Path |  | required |
| train_mask_path | Path |  | required |
| val_path        | Path |  | required |
| val_mask_path   | Path |  | required |
| test_path       | Path |  | required |
| test_mask_path  | Path |  | required |

|  |  |
|--|--|
|  |  |
|--|--|

tuple[[CrackzDataset](#), [CrackzDataset](#), [CrackzDataset](#)]



► core/src/crackz/ai/data/dataset.py

```
create_dataset(
 project,
 transforms,
 mask_transforms,
 image_dir=None,
 image_masks_dir=None,
)
```

| project         | <a href="#">Project</a> |  | required |
|-----------------|-------------------------|--|----------|
| transforms      | ImageTransform   None   |  | required |
| mask_transforms | MaskTransform   None    |  | required |
| image_dir       | Path   None             |  | None     |
| image_masks_dir | Path   None             |  | None     |

[CrackzDataset](#)

► core/src/crackz/ai/data/dataset.py

```
collate(batch)
```

► core/src/crackz/ai/data/dataloader.py

```
make_crackz_loader(
 dataset, batch_size=32, num_workers=8, *, shuffle=True
)
```

► core/src/crackz/ai/data/dataloader.py

```
create_training_data loaders(
 train_ds,
 val_ds,
 test_ds,
 batch_size,
 num_workers,
 *,
 shuffle_train=True,
)
```



|               |                               |      |          |
|---------------|-------------------------------|------|----------|
|               |                               |      |          |
| train_ds      | <a href="#">CrackzDataset</a> |      | required |
| val_ds        | <a href="#">CrackzDataset</a> |      | required |
| test_ds       | <a href="#">CrackzDataset</a> |      | required |
| batch_size    | int                           |      | required |
| num_workers   | int                           |      | required |
| shuffle_train | bool                          | True |          |

|                                           |                                       |  |
|-------------------------------------------|---------------------------------------|--|
|                                           |                                       |  |
| tuple[DataLoader, DataLoader, DataLoader] |                                       |  |
| ►                                         | core/src/crackz/ai/data/dataloader.py |  |
|                                           | CrackzModel                           |  |
|                                           | ComboLoss                             |  |
|                                           | <a href="#">dataclass</a>             |  |
|                                           | CrackzModel                           |  |

|                           |                                                |         |
|---------------------------|------------------------------------------------|---------|
|                           |                                                |         |
| lr                        | float                                          |         |
| backbone                  | str                                            |         |
| in_channels               | int                                            |         |
| num_classes               | int                                            |         |
| threshold                 | float                                          |         |
| ►                         | core/src/crackz/ai/model/segmentation/model.py |         |
|                           | staticmethod                                   |         |
| from_project(project, lr) |                                                |         |
|                           | CrackzConfig                                   | Project |
| ►                         | core/src/crackz/ai/model/segmentation/model.py |         |

## Module

► `core/src/crackz/ai/model/segmentation/model.py`

```
forward(y_pred, y_true)
```

► `core/src/crackz/ai/model/segmentation/model.py`

## LightningModule

► `core/src/crackz/ai/model/segmentation/model.py`

```
training_step(batch, _batch_idx)
```

► `core/src/crackz/ai/model/segmentation/model.py`

```
validation_step(batch, _batch_idx)
```

► `core/src/crackz/ai/model/segmentation/model.py`

```
test_step(batch, _batch_idx)
```

► `core/src/crackz/ai/model/segmentation/model.py`

```
on_train_epoch_end()
```

► `core/src/crackz/ai/model/segmentation/model.py`

```
on_validation_epoch_end()
```

► `core/src/crackz/ai/model/segmentation/model.py`

```
on_test_epoch_end()
```

► `core/src/crackz/ai/model/segmentation/model.py`

```
configure_optimizers()
```

► `core/src/crackz/ai/model/segmentation/model.py`

```
get_loss_function(config)
```

► `core/src/crackz/ai/model/segmentation/model.py`

## Callback

► `core/src/crackz/ai/training/callbacks.py`

```
on_train_start(trainer, pl_module)
```

► `core/src/crackz/ai/training/callbacks.py`

```
on_train_batch_end(
 trainer, pl_module, outputs, batch, batch_idx
)
```

► `core/src/crackz/ai/training/callbacks.py`

```
on_train_epoch_end(trainer, pl_module)
```

► `core/src/crackz/ai/training/callbacks.py`

```
on_validation_epoch_end(trainer, pl_module)
```

► `core/src/crackz/ai/training/callbacks.py`

```
on_test_epoch_end(trainer, pl_module)
```

► `core/src/crackz/ai/training/callbacks.py`

```
on_fit_end(trainer, pl_module)
```

► `core/src/crackz/ai/training/callbacks.py`

Callback

► `core/src/crackz/ai/training/callbacks.py`

```
__call__(progress, message=None)
```

► `core/src/crackz/ai/training/callbacks.py`

```
on_train_start(trainer, pl_module)
```

► `core/src/crackz/ai/training/callbacks.py`

```
on_train_epoch_start(trainer, pl_module)
```

► `core/src/crackz/ai/training/callbacks.py`

```
on_train_batch_end(
 trainer, pl_module, outputs, batch, batch_idx
)
```

► `core/src/crackz/ai/training/callbacks.py`

```
on_train_epoch_end(trainer, pl_module)
```

► core/src/crackz/ai/training/callbacks.py

```
on_fit_end(trainer, pl_module)
```

► core/src/crackz/ai/training/callbacks.py

```
on_test_end(trainer, pl_module)
```

► core/src/crackz/ai/training/callbacks.py

Callback

► core/src/crackz/ai/training/callbacks.py

```
on_validation_epoch_end(trainer, pl_module)
```

► core/src/crackz/ai/training/callbacks.py

```
make_reporter(ui_callback)
```

► core/src/crackz/ai/training/callbacks.py

```
create_training_callbacks(
 project,
 val_ds,
 tb_logger,
 progress_reporter,
 runtime_tracker,
 cancellation_token,
)
```

|         |                         |  |          |
|---------|-------------------------|--|----------|
|         |                         |  |          |
| project | <a href="#">Project</a> |  | required |
| val_ds  | CrackzDataset           |  | required |

|                    |                           |  |          |
|--------------------|---------------------------|--|----------|
|                    |                           |  |          |
| tb_logger          | TensorBoardLogger   None  |  | required |
| progress_reporter  | ProgressReporter   None   |  | required |
| runtime_tracker    | RuntimeTracker            |  | required |
| cancellation_token | CancellationTokens   None |  | required |

|           |                                          |
|-----------|------------------------------------------|
|           |                                          |
| list[Any] |                                          |
| ▶         | core/src/crackz/ai/training/callbacks.py |

get\_available\_checkpoints(checkpoints\_dir)

|                 |      |  |          |
|-----------------|------|--|----------|
|                 |      |  |          |
| checkpoints_dir | Path |  | required |

|            |                                         |
|------------|-----------------------------------------|
|            |                                         |
| list[Path] |                                         |
| ▶          | core/src/crackz/ai/model/checkpoints.py |

has\_trained\_model(project)

|         |                         |  |          |
|---------|-------------------------|--|----------|
|         |                         |  |          |
| project | <a href="#">Project</a> |  | required |

|      |                                         |
|------|-----------------------------------------|
|      |                                         |
| bool |                                         |
| ▶    | core/src/crackz/ai/model/checkpoints.py |

select\_checkpoint(checkpoints\_dir)

checkpoints\_dir

Path

required

Path | None

▶

core/src/crackz/ai/model/checkpoints.py

peek\_checkpoint\_backbone(checkpoint\_path)

▶

core/src/crackz/ai/model/checkpoints.py

get\_checkpoint\_compatibility(project)

▶

core/src/crackz/ai/model/checkpoints.py

load\_model\_from\_checkpoint(  
 project,  
 lr,  
 checkpoint\_name=None,  
 \*,  
 on\_incompatible="original",  
)

project

[Project](#)

required

lr

float

required

checkpoint\_name

str | None

None

on\_incompatible

IncompatibleMode

"original"

"raise"

"untrained"

CheckpointIncompatibleError

'original'

[CrackzModel](#)

[CheckpointIncompatibleError](#) *on\_incompatible* "raise"

► `core/src/crackz/ai/model/checkpoints.py`

```
create_checkpoint_callback(project)
```

project [Project](#) *required*

ModelCheckpoint

► `core/src/crackz/ai/model/checkpoints.py`

```
prune_checkpoints(project, keep)
```

project [Project](#) *required*

keep int *required*

list[Path]

► `core/src/crackz/ai/model/checkpoints.py`



```
plot_image(img_path, out_file, pred_mask)
```

► `core/src/crackz/ai/visualization/visualization.py`

```
save_detection_figure(fig, out_file)
```

► `core/src/crackz/ai/visualization/visualization.py`

```
save_metrics_json(results, output_dir)
```

► `core/src/crackz/ai/visualization/visualization.py`

```
save_training_metrics_json(results, output_dir)
```

► `core/src/crackz/ai/visualization/visualization.py`

```
show_image(ax, index, title, img, alpha=None, cmap='gray')
```

► `core/src/crackz/ai/visualization/visualization.py`

```
to_numpy_img(tensor)
```

► `core/src/crackz/ai/visualization/visualization.py`

Enum

► `core/src/crackz/ai/device/device.py`

`staticmethod`

available\_devices()

▶ core/src/crackz/ai/device/device.py

staticmethod

default()

▶ core/src/crackz/ai/device/device.py

staticmethod

test\_device(device\_name)

device\_name str required

bool

str •

dict[str, str | None] •

tuple[bool, str, dict[str, str | None]] •

▶ core/src/crackz/ai/device/device.py

get\_accelerator()

▶ core/src/crackz/ai/device/utils.py

resolve\_device\_and\_accelerator(project)

project [Project](#) required

str

► `core/src/crackz/ai/device/utls.py`

[AIPipelineError](#)

[ModelNotFoundError](#)

[DataLoadingError](#)

CrackzError

► `core/src/crackz/ai/exceptions.py`

CrackzError

► `core/src/crackz/ai/exceptions.py`

[AIPipelineError](#)

► `core/src/crackz/ai/exceptions.py`

[AIPipelineError](#)

► `core/src/crackz/ai/exceptions.py`

[AIPipelineError](#)

► `core/src/crackz/ai/exceptions.py`

[AIPipelineError](#)

► `core/src/crackz/ai/exceptions.py`

`detection_results.json`



`save_metrics_json`

`crackz.ai.eval`

[BaseModel](#)

► `core/src/crackz/ai/detection/results.py`

```
load_detection_results(project_or_path, *, strict=False)
```

► `core/src/crackz/ai/detection/results.py`

`iter_iou(results)`

► `core/src/crackz/ai/detection/results.py`

`DetectionResult`

`aggregate_iou(results)`

► `core/src/crackz/ai/detection/eval.py`

`basic_summary(results)`

► `core/src/crackz/ai/detection/eval.py`

`get_available_checkpoints(checkpoints_dir)`

|                              |                   |  |                 |
|------------------------------|-------------------|--|-----------------|
|                              |                   |  |                 |
| <code>checkpoints_dir</code> | <code>Path</code> |  | <i>required</i> |

`list[Path]`

► `core/src/crackz/ai/model/checkpoints.py`

`has_trained_model(project)`

```
project Project required
```

```
bool
▶ core/src/crackz/ai/model/checkpoints.py
```

```
select_checkpoint(checkpoints_dir)
```

```
checkpoints_dir Path required
```

```
Path | None
▶ core/src/crackz/ai/model/checkpoints.py
```

```
peek_checkpoint_backbone(checkpoint_path)
```

```
▶ core/src/crackz/ai/model/checkpoints.py
```

```
get_checkpoint_compatibility(project)
```

```
▶ core/src/crackz/ai/model/checkpoints.py
```

```
load_model_from_checkpoint(
 project,
 lr,
 checkpoint_name=None,
 *,
 on_incompatible="original",
)
```

|                 |                         |                                                                 |                                                              |
|-----------------|-------------------------|-----------------------------------------------------------------|--------------------------------------------------------------|
|                 |                         |                                                                 |                                                              |
| project         | <a href="#">Project</a> |                                                                 | <i>required</i>                                              |
| lr              | float                   |                                                                 | <i>required</i>                                              |
| checkpoint_name | str   None              |                                                                 | None                                                         |
| on_incompatible | IncompatibleMode        | <div>"original"</div> <div>"untrained"</div> <div>"raise"</div> | <div>CheckpointIncompatibleError</div> <div>'original'</div> |

[CrackzModel](#)

[CheckpointIncompatibleError](#)

*on\_incompatible* "raise"

► core/src/crackz/ai/model/checkpoints.py

create\_checkpoint\_callback(project)

project [Project](#) *required*

ModelCheckpoint

► core/src/crackz/ai/model/checkpoints.py

prune\_checkpoints(project, keep)

project [Project](#) *required*

keep int *required*

list[Path]

► core/src/crackz/ai/model/checkpoints.py

► core/src/crackz/ai/pipeline/cancellation.py

\_\_init\_\_()

► core/src/crackz/ai/pipeline/cancellation.py

cancel()

► core/src/crackz/ai/pipeline/cancellation.py

is\_cancelled()

bool

► core/src/crackz/ai/pipeline/cancellation.py

check\_cancelled()



CancellationError

► core/src/crackz/ai/pipeline/cancellation.py

---

Handler

► core/src/crackz/log/crackz\_logger.py

emit(record)

► core/src/crackz/log/crackz\_logger.py

use\_rich\_console()

bool

► core/src/crackz/log/crackz\_logger.py

setup\_logging(level=None, log\_dir=None, \*, use\_rich=None)

level str | None None

|          |                |  |      |
|----------|----------------|--|------|
|          |                |  |      |
| log_dir  | Path  <br>None |  | None |
| use_rich | bool  <br>None |  | None |

|  |  |
|--|--|
|  |  |
|--|--|

Logger

► core/src/crackz/log/crackz\_logger.py

get\_logger(name, filename=None, log\_dir='logs')

|   |                                      |                  |          |
|---|--------------------------------------|------------------|----------|
|   | logging                              | InterceptHandler | filename |
| ► | core/src/crackz/log/crackz_logger.py |                  |          |

TyperGroup

► core/src/crackz/cli/crackz\_cli.py

```
main(
 args=None,
 prog_name=None,
 complete_var=None,
 standalone_mode=True,
 windows_expand_args=True,
 **extra,
)
```

► core/src/crackz/cli/crackz\_cli.py

list\_commands(ctx)

► core/src/crackz/cli/crackz\_cli.py

get\_command(ctx, cmd\_name)

► `core/src/crackz/cli/crackz_cli.py`

```
format_commands(ctx, formatter)
```

► `core/src/crackz/cli/crackz_cli.py`

```
root_callback(
 ctx,
 version=False,
 debug=False,
 quiet=False,
 log_dir=None,
)
```

► `core/src/crackz/cli/crackz_cli.py`

```
main()
```

► `core/src/crackz/cli/crackz_cli.py`

```
init_project(
 name=NAME_OPTION,
 image_path=IMAGE_PATH_OPTION,
 image_mask_path=IMAGE_MASK_PATH_OPTION,
 artifacts_path=ARTIFACTS_PATH_OPTION,
 description=DESCRIPTION_OPTION,
 log_dir=LOG_DIR_OPTION,
 *,
 force=FORCE_OPTION,
)
```

► `core/src/crackz/cli/project_cli.py`

```
export_project_config(
 cfg=CFG_OPTION,
 project_path=PROJECT_PATH_OPTION,
 out=EXPORT_OUTPUT_OPTION,
)
```

► `core/src/crackz/cli/project_cli.py`

```
migrate_project_config(
 cfg=CFG_OPTION,
```

```
project_path=PROJECT_PATH_OPTION,
*,
dry_run=DRY_RUN_OPTION,
no_backup=NO_BACKUP_OPTION,
migrate_files=typer.Option(
 default=False,
 help="Also migrate artifacts directory structure (checkpoints to models, etc.)",
),
),
)
```

► core/src/crackz/cli/project\_cli.py

```
clean_project(
 project_path=PROJECT_PATH_OPTION,
 *,
 dry_run=DRY_RUN_OPTION,
 logs_only=LOGS_ONLY_OPTION,
 keep_best_model=KEEP_BEST_MODEL_OPTION,
)
```

► core/src/crackz/cli/project\_cli.py

```
import_images(
 cfg=CFG_OPTION,
 project_path=PROJECT_PATH_OPTION,
 source_path=SOURCE_PATH_OPTION,
 masks_source_path=MASKS_SOURCE_PATH_OPTION,
 image_type=TYPE_OPTION,
 image_size=SIZE_OPTION,
 quality=QUALITY_OPTION,
 target_size=TARGET_SIZE_OPTION,
 *,
 overwrite=OVERWRITE_OPTION,
 split=SPLIT_OPTION,
 train_ratio=TRAIN_RATIO_OPTION,
 val_ratio=VAL_RATIO_OPTION,
 test_ratio=TEST_RATIO_OPTION,
 random_seed=RANDOM_SEED_OPTION,
)
```

| cfg          | Path   None | CFG_OPTION          |
|--------------|-------------|---------------------|
| project_path | Path   None | PROJECT_PATH_OPTION |
| source_path  | Path        | SOURCE_PATH_OPTION  |

|                   |                            |             |                          |
|-------------------|----------------------------|-------------|--------------------------|
|                   |                            |             |                          |
| masks_source_path | Path   None                | source_path | MASKS_SOURCE_PATH_OPTION |
| image_type        | <a href="#">ImagesType</a> |             | TYPE_OPTION              |
| image_size        | SizeType                   |             | SIZE_OPTION              |
| quality           | int                        |             | QUALITY_OPTION           |
| target_size       | int   None                 |             | TARGET_SIZE_OPTION       |
| overwrite         | bool                       |             | OVERWRITE_OPTION         |
| split             | bool                       |             | SPLIT_OPTION             |
| train_ratio       | float                      |             | TRAIN_RATIO_OPTION       |
| val_ratio         | float                      |             | VAL_RATIO_OPTION         |
| test_ratio        | float                      |             | TEST_RATIO_OPTION        |
| random_seed       | int   None                 |             | RANDOM_SEED_OPTION       |

BadParameter

Exit

None

► core/src/crackz/cli/image\_import\_cli.py

```
run_detection(
 cfg=CFG_OPTION,
 project_path=PROJECT_PATH_OPTION,
 model=CHECKPOINT_NAME_OPTION,
)
```

► core/src/crackz/cli/detection\_cli.py

```
detection_train(
 cfg=CFG_OPTION,
 project_path=PROJECT_PATH_OPTION,
 epochs=EPOCHS_OPTION,
 batch_size=BATCH_SIZE_OPTION,
 resume=RESUME_FROM_OPTION,
)
```

| cfg          | Path  <br>None | project_path | CFG_OPTION          |
|--------------|----------------|--------------|---------------------|
| project_path | Path  <br>None | cfg          | PROJECT_PATH_OPTION |
| epochs       | int  <br>None  |              | EPOCHS_OPTION       |
| batch_size   | int  <br>None  |              | BATCH_SIZE_OPTION   |
| resume       | str  <br>None  |              | RESUME_FROM_OPTION  |

```
BadParameter cfg project_path

Exit

► core/src/crackz/cli/detection_cli.py
```

```
prune_checkpoints_cmd(
 keep=KEEP_CHECKPOINTS_OPTION,
 cfg=CFG_OPTION,
 project_path=PROJECT_PATH_OPTION,
)
```

```
► core/src/crackz/cli/detection_cli.py
```

|  | CrackzModel                    |  |
|--|--------------------------------|--|
|  | CrackzDataset                  |  |
|  | MetricsLoggerCallback          |  |
|  | resolve_device_and_accelerator |  |
|  | DetectionResult                |  |
|  | Pipeline                       |  |

```
1.
2.
3.
4. DetectionResult
5. evaluation.py
6.
7.
8.
9.
10.
11.
12.
13.
14.
15.
16.
17.
18. ProjectConfig
19.
20.
21.
22. Pipeline
```

---

```
Project -> load_model_from_checkpoint -> CrackzModel.eval() -> DataLoader -> forward -> sigmoid -> threshold -> mask -> metrics(json)
```

---

```
requirements.txt
```

---

---

# CLI Reference

---

# app

[OPTIONS] COMMAND [ARGS]...

|                      |                                                                                                                                                     |
|----------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------|
| -v, --version        | Show version and exit                                                                                                                               |
| --debug              | Enable debug logging                                                                                                                                |
| --quiet              | Only warnings and errors                                                                                                                            |
| --log-dir DIRECTORY  | Central log directory (precedence: env CRACKZ_LOG_DIR > --log-dir > system temp). Created if missing. Project logs are always under <project>/logs. |
| --install-completion | Install completion for the current shell.                                                                                                           |
| --show-completion    | Show completion for the current shell, to copy it or customize the installation.                                                                    |

## dashboard

crackz dashboard --project my-project

http://localhost:8501

crackz dashboard --project my-project --port 8080

crackz dashboard

- 1.
- 2.
- 3.
- 4.
- 5.
- 6.
- 7.
- 8.
- 9.
- 10.
- 11.
- 12.
- 13.
- 14.
- 15.
- 16.



17.  
18.

```
crackz detect --project my-project
crackz dashboard --project my-project
Navigate to "Detection Results" page
```

```
crackz train --project my-project --epochs 50
crackz dashboard --project my-project
Navigate to "Training Metrics" page
```

```
crackz dashboard --project my-project
Navigate to "GPS Map" page
```

```
crackz dashboard --project my-project
Navigate to "Parameter Tuning" page
Adjust thresholds and preview results
```



clean

```
crackz clean --project ./my_project
```

```
crackz clean -p ./my_project
```

- \*.log
- 
- models/ checkpoints/
- 
- 

```
crackz clean --project ./my_project --dry-run
```

Dry run: The following would be cleaned:

- /path/to/project/logs/crackz.log
- /path/to/project/artifacts/training/tensorboard
- /path/to/project/artifacts/models
- /path/to/project/artifacts/detections

Re-run without --dry-run to apply changes.

```
crackz clean --project ./my_project --logs-only
```

`*.log`

`models/`

`checkpoints/`

```
$ crackz clean --project ./my_project
```

Project cleaned! Removed 5 items (logs and artifacts).

`--logs-only`

```
$ crackz clean --project ./my_project --logs-only
```

Project cleaned! Removed 2 items (logs).

```
crackz clean -p ./my_project
```

```
crackz clean -p ./my_project --logs-only
```

```
crackz clean -p ./my_project --dry-run
```

`migrate`

```
1 ai.training.tensorboard false data.mask_threshold: 1 schema_version:
 crackz_version

 training/tensorboard/ runtime/tensorboard/ checkpoints/ models/
 runtime/lightning_logs/ detections/*.png detections/visualizations/ training/lightning_logs/
```

```
crackz migrate --project ./my_project
```

```
crackz migrate --project ./my_project --migrate-files
```

```
crackz migrate --cfg ./my_project/my_project_project.yaml --migrate-files
```

```
crackz migrate -p ./my_project --migrate-files
```

```
crackz migrate -c ./my_project/my_project_project.yaml --migrate-files
```

```
Schema changes only
crackz migrate --project ./my_project --dry-run

Schema + file changes
crackz migrate --project ./my_project --migrate-files --dry-run
```

*would*

`.v{version}.{timestamp}.bak`

```
crackz migrate --project ./my_project --no-backup
```

```
[migrated] my_project schema 0 -> 1 (current=1) steps: 0->1: added tensorboard default + schema_version=1
```

```
[up-to-date] my_project schema 1 -> 1 (current=1) steps: none
```

```
build.yml
integration-tests.yml pytest -m integration
release.yml
docker-build.yml
smoke-tests.yml
benchmark-tests.yml pytest -m benchmark
docs.yml
```

```
pytest -m integration -vv
```

```
pytest -m "not integration"
```

```
pytest -m benchmark --benchmark-only
```

`crackz/cli/*_cli.py`

`schema_version`

- `.bak`
- `CRACKZ_AUTO_MIGRATE=1`

```
crackz migrate --project <project-dir>
```

```
--dry-run --no-backup
```

```
migration.md
```

```
model
```

```
crackz model export --project ./my_project --out my_model.zip
```

```
crackz model export -p ./my_project -o my_model.zip
```

```
<project_name>_model.zip
```

```
crackz model export -p ./my_project -c final -o final_model.zip
```

```
best last final
```

```
crackz model import --project ./my_project --model my_model.zip
```

```
crackz model import -p ./my_project -m my_model.zip
```

```
crackz model import -p ./my_project -m my_model.zip --force
```

```
--force
```

```
Export from training project
crackz model export -p ./training_project -o harbor_crack_v1.zip

Import into deployment project
crackz model import -p ./deployment_project -m harbor_crack_v1.zip
```

```
Export pre-trained model
crackz model export -p ./pretrained_project -o base_model.zip

Import into new project for fine-tuning
crackz model import -p ./finetuning_project -m base_model.zip
```

```
Export after successful training
crackz model export -p ./my_project -o backups/model_$(date +%Y%m%d).zip
```

&lt;checkpoint\_name&gt;.ckpt

metadata.json

```
{
 "project_name": "harbor_detection",
 "checkpoint_name": "best.ckpt",
 "model_config": {
 "encoder": "resnet34",
 "encoder_weights": "imagenet",
 "in_channels": 3,
 "num_classes": 1,
 "threshold": 0.5,
 "loss_name": "combo",
 "dice_weight": 0.7,
 "focal_weight": 0.3
 }
}
```

## Model Evaluation

---

# Model Evaluation

---

```
Run evaluation on test dataset
crackz evaluate run --project my_harbor

Specific metrics
crackz evaluate run --project my_harbor --metrics accuracy,iou

Export results
crackz evaluate run --project my_harbor --output results.json
crackz evaluate run --project my_harbor --output results.csv
```

```
from pathlib import Path
from crackz.ai.evaluation import evaluate_model, export_json

Run evaluation
results = evaluate_model(
 project_path=Path("my_harbor"),
 metrics=["accuracy", "precision", "recall", "iou"]
)

Display results
print(results)

Export to JSON
export_json(results, Path("evaluation_results.json"))
```

$$\text{Accuracy} = (TP + TN) / (TP + TN + FP + FN)$$
$$\text{Precision} = TP / (TP + FP)$$
$$\text{Recall} = TP / (TP + FN)$$
$$F1 = 2 * (Precision * Recall) / (Precision + Recall)$$
$$\text{IoU} = \text{Area of Overlap} / \text{Area of Union}$$

```
Default threshold (0.5)
crackz evaluate run --project my_harbor
```

```
Custom threshold
crackz evaluate run --project my_harbor --threshold 0.7
```

```
All metrics (default)
crackz evaluate run --project my_harbor
```

```
Specific metrics
crackz evaluate run --project my_harbor --metrics accuracy,precision,recall
crackz evaluate run --project my_harbor --metrics iou # Only IoU
```

```
accuracy precision recall f1 iou
```

```
Evaluation Results (500 images)
```

```
=====
Accuracy: 92.3%
Precision: 89.1%
Recall: 94.8%
F1 Score: 91.9%
Mean IoU: 0.847
Threshold: 0.5
```

```
{
 "num_images": 500,
 "threshold": 0.5,
 "metrics": {
 "accuracy": 0.923,
 "precision": 0.891,
 "recall": 0.948,
 "f1_score": 0.919,
 "iou": 0.847
 }
}
```

```
Metric,Value
Num Images,500
Threshold,0.5
Accuracy,0.9230
Precision,0.8910
Recall,0.9480
F1 Score,0.9190
IoU,0.8470
```

```
project/
├─ images/
│ └─ test/ # Test images
│ ├── img1.png
│ ├── img2.png
│ └─ ...
└─ masks/
 └─ test/ # Ground truth masks
 └─ img1.png
```

```
└─ img2.png
└─ ...
```

```
def evaluate_model(
 project_path: Path,
 test_images: list[Path] | None = None,
 test_masks: list[Path] | None = None,
 metrics: list[str] | None = None,
 threshold: float = 0.5,
) -> EvaluationResults:
 """Evaluate crack detection model on test dataset."""
```

```

 project_path test_images
test_masks metrics
 threshold
 EvaluationResults
```

```
@dataclass
class EvaluationResults:
 accuracy: float
 precision: float
 recall: float
 f1_score: float
 iou: float
 num_images: int
 threshold: float
```

```
Export to JSON
export_json(results, Path("results.json"))

Export to CSV
export_csv(results, Path("results.csv"))
```

```
ValueError: No test images found
```

```
<project>/images/test/
```

```
ls <project>/images/test/
```

```
ValueError: Image/mask count mismatch: 100 vs 98
```

```
Check counts
ls <project>/images/test/ | wc -l
ls <project>/masks/test/ | wc -l

Find missing masks
diff <(ls <project>/images/test/) <(ls <project>/masks/test/)
```

```
FileNotFoundError: No trained model checkpoint found
```



```
crackz detect train --project <project>
```

- 
- 
- 
- 

- 
- 
- 
- 

- 
- 
- 
- 

- 
- 
- 
- 

- 
- 
- 
- 
- 
- 

- [\\_\\_\\_\\_\\_](#)
- [\\_\\_\\_\\_\\_](#)
- [\\_\\_\\_\\_\\_](#)

---

# MCP Integration

---

# MCP (Model Context Protocol) Integration

- 
- 
- 
- 

- 1.
- 2.
- 3.
- 4.

`.github/copilot-instructions.md`

| Development Agents                                                                                                                     | GitHub Copilot                                                           | End-User GUI                                                              |
|----------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------|---------------------------------------------------------------------------|
| <div><div>4 MCP Servers</div><ul style="list-style-type: none"><li>filesystem</li><li>github</li><li>python</li><li>uv</li></ul></div> | <div><div>× No MCP</div><div>IDE context<br/>Workspace files</div></div> | <div><div>× No MCP</div><div>Simple API<br/>Project info only</div></div> |
| Tools: Claude Desktop, Cline                                                                                                           | Tools: VS Code, IDE                                                      | Tools: Crackz GUI Chat Panel                                              |

- 
- 
- 
-

```

TOOL CALL: filesystem.readDirectory("src/")
→ returns 50 files in context

TOOL CALL: filesystem.readFile("src/file1.py")
→ returns full file in context

TOOL CALL: filesystem.readFile("src/file2.py")
→ returns full file in context

```

```

Discover and filter in code
files = await filesystem.readDirectory("src/")
python_files = [f for f in files if f.endswith(".py")]

Load only what's needed
for filename in python_files[:5]: # Top 5 only
 content = await filesystem.readFile(f"src/{filename}")
 # Process in code, log summary only
 print(f"{filename}: {len(content)} lines")

```

- 1.
- 2.
- 3.
- 4.

<type>/<scope>-<short-slug>

```

feat/gui-live-preview # New GUI feature
fix/pdf-rendering-crash # Bug fix in PDF generation
perf/dataloader-cache # Performance improvement
docs/api-reference-update # Documentation update
refactor/config-cleanup # Code refactoring

```

<type>(<scope>): <description>

```

feat(gui): add real-time detection preview
fix(cli): correct path handling in Windows
perf(dataloader): implement batch caching
docs(api): update training configuration reference

```

<type>(<scope>): <description>

```

feat(gui): add export panel for detection results
fix(pdf): handle missing hero image gracefully
perf(training): optimize data loading pipeline

```

```

Fix GUI bugs and add new feature
Update documentation
Add export functionality

```

```

feat: feat(<scope>):
perf: perf(<scope>):

```

```

fix: fix(<scope>):

```

```

test: docs:
chore:

```

```

refactor:
ci:

```

```

build:

```

```
typer.secho()
crackz.cli.options

logger
crackz.log

print()
```

```
uv run task tests
```

```
uv run task mypy
```

```
crackz mcp init
```

```
.mcp/config.json
```

```
crackz mcp show
```

```
crackz mcp validate
```

```
.mcp/config.json
```

```
{
 "mcpServers": {
 "filesystem": {
 "type": "stdio",
 "command": "npx",
 "args": ["-y", "@modelcontextprotocol/server-filesystem", "."],
 "description": "Filesystem operations with progressive disclosure"
 },
 "github": {
 "type": "stdio",
 "command": "npx",
 "args": ["-y", "@modelcontextprotocol/server-github"],
 "env": {
 "GITHUB_PERSONAL_ACCESS_TOKEN": "${GITHUB_TOKEN}"
 },
 "description": "GitHub operations (issues, PRs, releases)"
 },
 "python": {
 "type": "stdio",
 "command": "npx",
 "args": ["-y", "@modelcontextprotocol/server-python"],
 "description": "Python code execution environment"
 },
 "uv": {
 "type": "stdio",
 "command": "npx",
 "args": ["-y", "@modelcontextprotocol/server-uv"],
 "description": "UV package manager operations"
 }
 }
}
```

```
{
 "metadata": {
 "project": "Crackz",
 "language": "python",
 "version": "3.13",
 "package_manager": "uv",
 "framework": "pytorch-lightning",
 "cli": "typer",
 "gui": "pyside6",
 "testing": "pytest",
 "ci": "github-actions",
 "release": "semantic-release",
 "code_execution": true,
 "progressive_disclosure": true
 }
}
```

```
{
 "patterns": {
 "code_execution": {
 "enabled": true,
 "description": "Use code execution to interact with MCP servers efficiently",
 "examples": [
 "Filter large datasets in code before returning results",
 "Loop over operations without alternating tool calls",
 "Compose multiple MCP operations in a single execution"
]
 },
 "progressive_disclosure": {
 "enabled": true,
 "description": "Load tool definitions on-demand",
 "workflow": [
 "List directories to discover modules",
 "Read specific files as needed",
 "Load documentation when relevant"
]
 }
 }
}
```

```
--output -o
```

```
.mcp/config.json
```

```
--force -f
```

```
Create with defaults
crackz mcp init

Create in custom location
crackz mcp init --output custom/mcp.json

Overwrite existing config
crackz mcp init --force
```

```
--config -c
```

```
.mcp/config.json
```

```
Show default config
crackz mcp show

Show custom config
crackz mcp show --config custom/mcp.json
```

`--config -c``.mcp/config.json`

```
Validate default config
crackz mcp validate

Validate custom config
crackz mcp validate --config custom/mcp.json
```

`.mcp/config.json`

```
{
 "mcpServers": {
 "filesystem": { ... },
 "custom-api": {
 "type": "stdio",
 "command": "node",
 "args": ["/custom-mcp-server.js"],
 "description": "Custom MCP server for specialized operations"
 }
 }
}
```

```
{
 "metadata": {
 "project": "Crackz",
 "language": "python",
 "team": "ML Ops",
 "repository": "https://github.com/Anaxiatech-AB/crackz",
 "custom_field": "your_value"
 }
}
```

- 1.
- 2.
- 3.
- 4.
- 5.

```
List Python files in src/
files = await filesystem.readDirectory("src/crackz")
py_files = [f for f in files if f.endswith(".py")]

Read only the first 3 for initial analysis
for filename in py_files[:3]:
 content = await filesystem.readFile(f"core/src/crackz/{filename}")
 lines = len(content.split('\n'))
 print(f"{filename}: {lines} lines")
```

```
Get recent PRs and filter in code
prs = await github.listPullRequests(repo="Anaxiatech-AB/crackz", state="open")
priority_prs = [pr for pr in prs if "feat:" in pr.title or "fix:" in pr.title]

print(f"Found {len(priority_prs)} priority PRs out of {len(prs)} total")
for pr in priority_prs[:5]: # Show top 5 only
 print(f"#{pr.number}: {pr.title}")
```

```
Install multiple packages in one operation
packages = ["pytest", "ruff", "mypy"]
for pkg in packages:
 await uv.install(package=pkg)
print(f"✓ Installed {pkg}")
```

- 
- 
- 
- 

## logger

`print()`

- 1.
2. `CRACKZ_LOG_DIR` `--log-dir`
- 3.
- 4.
5. `<project>/logs/`
- 6.
- 7.
- 8.

## Info level - operational progress

---



## Warning level - non-critical issues

---

## Error level - failures with details

---

## Debug level - detailed troubleshooting info

---

- \_\_\_\_\_
- \_\_\_\_\_
- \_\_\_\_\_
- \_\_\_\_\_

---

## Tracing & Observability

---

# Tracing with OpenTelemetry

---

```
uv sync --extra tracing
```

```
opentelemetry-instrumentation-anthropic
opentelemetry-exporter-otlp-proto-http
```

```
opentelemetry-sdk
```

```
Ctrl+Shift+P Cmd+Shift+P
```

```
AI Toolkit: Open Tracing
```

```
ai-mlstudio.tracing.open
```

```
export CRACKZ_TRACING_ENABLED=1
crackz-gui # Tracing auto-enabled
```

```
from crackz.tracing import setup_tracing

Initialize with default AI Toolkit endpoint
setup_tracing()

Or custom endpoint
setup_tracing(
 endpoint="http://custom-collector:4318/v1/traces",
 service_name="crackz-production"
)
```

- 
- 
- 
- 
- 

```
crackz
└─ anthropic.messages.create
 └─ model: claude-sonnet-4-5-20250929
 └─ input_tokens: 1245
 └─ output_tokens: 382
 └─ duration: 2.3s
```

- 
- 
- 
- 

|                        |   |
|------------------------|---|
| CRACKZ_TRACING_ENABLED | 0 |
|------------------------|---|

|   |   |
|---|---|
| 1 | 0 |
|---|---|

<http://localhost:4318/v1/traces>
<http://localhost:4317>

```
setup_tracing(endpoint="http://your-collector:4318/v1/traces")
```

```
Enable tracing for all CLI operations
export CRACKZ_TRACING_ENABLED=1
crackz detect run --project my_project
```

```
Disable for specific run
export CRACKZ_TRACING_ENABLED=0
crackz detect run --project my_project
```

```
In main.py or startup script
from crackz.tracing import setup_tracing
```

```
Enable before starting GUI
if os.getenv("CRACKZ_TRACING_ENABLED") == "1":
 setup_tracing()
```

```
Run GUI
from crackz_gui.qt.app import main
main()
```

```
from crackz.tracing import setup_tracing, shutdown_tracing
```

```
Initialize tracing
setup_tracing(service_name="crackz-batch-processor")
```

```
Your AI operations (automatically traced)
from crackz_gui.services.ai_chat import AIChatService
chat = AIChatService(...)
chat.send_message("Analyze this crack detection result")
```

```
Clean shutdown (flushes pending spans)
shutdown_tracing()
```

```
uv sync --extra tracing
```

Ctrl+Shift+P → AI Toolkit: Open Tracing

CRACKZ\_TRACING\_ENABLED=1

uv sync --extra tracing

shutdown\_tracing()

```
import atexit
from crackz.tracing import shutdown_tracing
atexit.register(shutdown_tracing)
```

CRACKZ\_TRACING\_ENABLED=1

```
from opentelemetry import trace
tracer = trace.get_tracer(__name__)

with tracer.start_as_current_span("custom-operation") as span:
 span.set_attribute("project.name", "harbor_alpha")
 span.set_attribute("image.count", 1024)
 # Your code here
```

```
from opentelemetry.sdk.trace.sampling import TraceIdRatioBased

Sample 10% of traces
sampler = TraceIdRatioBased(0.1)

Pass to setup_tracing (requires custom implementation)
```

- \_\_\_\_\_
- \_\_\_\_\_
- \_\_\_\_\_
- \_\_\_\_\_

⋮

---

## Async Callbacks

---

# Async Callback Architecture

---

- 
- 
- 
- 

```
from crackz.ai.core.async_callbacks import CallbackDispatcher

dispatcher = CallbackDispatcher(maxsize=100)

Create sync reporter for PyTorch Lightning (training thread)
progress_reporter = dispatcher.create_sync_progress_reporter()

Use in training (synchronous context)
train(project, progress_reporter=progress_reporter)

Consume updates asynchronously (main thread)
async for progress, message in dispatcher.iter_progress():
 update_progress_bar(progress, message)
```

```
from crackz.ai.core.async_callbacks import (
 create_async_progress_consumer,
 create_async_metrics_consumer,
)

Define callback
def update_ui(progress: float, message: str | None = None) -> None:
 progress_bar.set_value(progress)

Create async consumer
consumer = create_async_progress_consumer(dispatcher, update_ui)

Run in async context
await consumer()
```

```
from crackz_gui.qt.async_bridge import (
 start_gui_callback_consumers,
 stop_gui_callback_consumers,
)

Start consumers (manages event loop)
loop, tasks = start_gui_callback_consumers(
 dispatcher,
 progress_callback=update_progress,
 metrics_callback=update_metrics,
)

... run training ...
```



```
Cleanup
stop_gui_callback_consumers(dispatcher, loop)
```

TaskSignals

async\_bridge.py

```
from crackz_gui.qt.async_bridge import TaskSignals, run_in_background

def _do_work(signals: TaskSignals) -> None:
 signals.progress.emit(0.5) # Safe from any thread
 signals.status.emit("Processing...")
 result = expensive_operation()
 signals.data.emit(result)
 signals.finished.emit()

signals = run_in_background(_do_work)
signals.progress.connect(self._on_progress)
signals.finished.connect(self._on_complete)
signals.error.connect(self._on_error)
```

threading.Lock

after()

crackz\_gui.qt.async\_bridge

```
def progress_callback(progress: float, message: str | None = None) -> None:
 print(f"Progress: {progress:.2%}")

train(project, progress_reporter=progress_callback)
```

```
dispatcher = CallbackDispatcher(maxsize=100)

Create sync reporters
progress_reporter = dispatcher.create_sync_progress_reporter()
metrics_reporter = dispatcher.create_sync_metrics_reporter()

Start training in background
training_thread = threading.Thread(
 target=train,
 args=(project,),
 kwargs={
 "progress_reporter": progress_reporter,
 "metrics_callback": metrics_reporter,
 }
)
training_thread.start()

Consume updates asynchronously
async def consume_updates():
 async for progress, message in dispatcher.iter_progress():
 print(f"Progress: {progress:.2%} - {message}")

asyncio.run(consume_updates())
```

```
from crackz.ai.core.async_callbacks import CallbackDispatcher
from crackz_gui.qt.async_bridge import (
 start_gui_callback_consumers,
 stop_gui_callback_consumers,
)

dispatcher = CallbackDispatcher(maxsize=100)

Start async consumers with Qt-thread-safe GUI updates
loop, tasks, emitters = start_gui_callback_consumers(
 dispatcher,
 progress_callback=self.update_progress_bar,
```

```

 metrics_callback=self.update_metrics_display,
)
 self.qt_emitters = emitters # Keep signal emitters alive

Create reporters
progress_reporter = dispatcher.create_sync_progress_reporter()
metrics_reporter = dispatcher.create_sync_metrics_reporter()

try:
 # Run training in background thread
 training_thread = threading.Thread(
 target=train,
 args=(project,),
 kwargs={
 "progress_reporter": progress_reporter,
 "metrics_callback": metrics_reporter,
 }
)
 training_thread.start()
 training_thread.join()
finally:
 stop_gui_callback_consumers(dispatcher, loop)

```

```

Training Loop:
 Process batch → Update metrics → **Wait for UI** → Next batch
 ↑ 1-5ms overhead

```

```

Training Loop:
 Process batch → Put in queue → Next batch (no wait!)
 ↓ 0.1ms
 Async Consumer: Takes from queue → Updates UI

```

```
dispatcher = CallbackDispatcher(maxsize=100)

... use reporters ...

Check progress queue stats
stats = dispatcher.progress_stats
print(f"Total items put: {stats.total_put}")
print(f"Total items retrieved: {stats.total_get}")
print(f"Total items dropped: {stats.total_dropped}")
print(f"Current queue size: {stats.current_size}")
print(f"Max queue size: {stats.max_size}")


Check metrics queue stats
metrics_stats = dispatcher.metrics_stats
```

```
total_dropped
```

```

• sync_q
•
• async_q
• threading.Event
•

```





```

Before (still works)
train(project, progress_reporter=my_callback)

After (optional upgrade for better performance)
dispatcher = CallbackDispatcher()
train(project, progress_reporter=dispatcher.create_sync_progress_reporter())

```

```

from crackz.ai.core.async_callbacks import CallbackDispatcher
from crackz_gui.qt.async_bridge import start_gui_callback_consumers

dispatcher = CallbackDispatcher(maxsize=100)
loop, tasks = start_gui_callback_consumers(
 dispatcher,
 progress_callback=update_progress,
 metrics_callback=update_metrics,
)

Use dispatcher's sync reporters in training
train(
 project,
 progress_reporter=dispatcher.create_sync_progress_reporter(),
 metrics_callback=dispatcher.create_sync_metrics_reporter(),
)

stop_gui_callback_consumers(dispatcher, loop)

```

### crackz.ai.core.async\_callbacks

- CallbackDispatcher
- QueueStats
- create\_async\_progress\_consumer()
- create\_async\_metrics\_consumer()

### crackz\_gui.qt.async\_bridge

- AsyncEventLoop
- create\_threadsafe\_gui\_callback()
- create\_threadsafe\_metrics\_callback()
- start\_gui\_callback\_consumers()
- stop\_gui\_callback\_consumers()

help()

```

from crackz.ai.core.async_callbacks import CallbackDispatcher
help(CallbackDispatcher)

```

[docs/examples/async\\_callbacks\\_example.py](https://crackz.ai/docs/examples/async_callbacks_example.py)


- \_\_\_\_\_
- \_\_\_\_\_
- \_\_\_\_\_

---

# Contributing

---

# Contributing Guide



- 
- [.github/copilot-instructions.md](#)
- [.github/workflows/copilot-setup-steps.yml](#)

<type>/<scope>--<short-slug>

```
AI creates feature branch
git checkout -b feat/gui-export-panel

AI makes changes with proper commit messages
git commit -m "feat(gui): add export panel component"
git commit -m "feat(gui): integrate export panel with main view"

When creating PR, AI suggests proper title
[] PR Title: "feat(gui): add export panel for detection results"
This triggers a MINOR version release (e.g., 1.2.0 → 1.3.0)
```



- 
- 
- 
- 
- 
- 
- 



```
create & activate venv
uv venv
source .venv/bin/activate # Windows: .venv\Scripts\activate

install with dev dependencies
uv sync --dev

run CLI help
uv run crackz --help

run GUI (optional)
uv run crackz-gui
```

pyproject.toml [tool.taskipy.tasks]

```
uv run task lint # ruff lint (auto-fix)
uv run task format # ruff format
uv run task mypy # static type check
uv run task tests # unit tests only
uv run task integration # integration tests
uv run task all_tests # full test matrix
uv run task docs # live docs (mkdocs serve)
uv run task build_docs # strict build
```

- `tests/unit` `core/tests/unit` `gui/tests/unit`
- `tests/integration` `@pytest.mark.integration`
- `backend/backend/tests/unit/crackz/cli/test_cli_benchmark.py` `@pytest.mark.benchmark`

- `tests/test_data`
- `core/tests` `gui/tests`

```
uv run task tests
```

```
uv run task all_tests
```

```
uv run task benchmark
```

```
pyproject.toml fail_under = 75
```

```
tests/integration/crackz/gui/
```

```
Run all integration tests (includes GUI smoke tests)
uv run task integration

Run only GUI smoke tests
uv run pytest tests/integration/crackz/gui/test_gui_smoke.py

Run GUI in smoke mode (auto-close after initialization)
set CRACKZ_GUI_SMOKE=1 # Windows CMD
export CRACKZ_GUI_SMOKE=1 # Linux/macOS
uv run crackz-gui
```

```
CRACKZ_GUI_SMOKE=1
```

```
CI GITHUB_ACTIONS
```

```
tests/integration/crackz/gui/
├─ test_gui_smoke.py # Smoke tests for GUI initialization
└─ ... # Future GUI integration tests
```

1.

```
env = os.environ.copy()
env["CRACKZ_GUI_SMOKE"] = "1"
subprocess.run([sys.executable, "gui/src/crackz_gui/crackz_gui.py"], env=env)
```

2.

```
@pytest.mark.skipif(not has_display() or os.environ.get("CI"),
 reason="Requires display")
def test_component(qapp):
 component = MyComponent()
 assert component is not None
```

3.

```
def test_no_unsupported_parameters():
 # Ensure widget initialization works without errors
 browser.toggle_toolbar_buttons(visible=True) # Should not raise
```

### benchmark

```
Run benchmarks - compares to last saved baseline and fails on regression
uv run task benchmark
```

```
Update the baseline after intentional performance-impacting changes
uv run task benchmark_save
```

```
Manual benchmark with comparison
uv run pytest -m benchmark --benchmark-only --benchmark-autosave --benchmark-compare --benchmark-compare-fail=mean:20%
```

.benchmarks/

- uv run task format lint
- 
- 
- loguru print
- 

<type>(<optional-scope>): <description>

```
feat: feat(<scope>): fix: fix(<scope>):
perf: perf(<scope>):
docs: refactor:
build: test: chore: ci:
style:
```

```
feat(gui): add return-to-run-view functionality
fix(pdf): correct missing hero image
perf(dataloader): optimize batch processing
```

```
Fix GUI image display and add return-to-run-view functionality
Add new feature to handle user authentication
Update documentation for new feature
```

```
feat: fix: :
feat(gui): fix(cli): :
Feat: Fix:
```

```
Install pre-commit hooks (one-time setup)
pip install pre-commit # or: uv tool install pre-commit
pre-commit install
pre-commit install --hook-type commit-msg
```

```
Test with a valid message
echo "feat(gui): add export panel" > temp_msg.txt
cz check --commit-msg-file temp_msg.txt

Test with an invalid message
echo "Fix bug" > temp_msg.txt
cz check --commit-msg-file temp_msg.txt
```

```
git commit --no-verify -m "your message"
```

---

- - 
  - 
  - 
  -
- 

```
uv run task docs # serves at http://127.0.0.1:8000
```

```
uv run task build_docs
```

```
scripts/export_pdf.py
```

```
uv run task pdf
```

---

- main  
pyproject.toml

cz bump  
CHANGELOG.md

main
  - 
  - 
  - 
  -
- 

```
logs/crackz.log
```

---



main

<type>/<scope>-<short-slug>

optimization

feat/gui-live-preview

docs/api-reference-update

fix/pdf-rendering-crash

perf/dataloader-refactor/config-module-cleanup

feat(gui): add live preview panel

fix/pdf-crash

feat/gui-live-preview

fix(pdf): handle null hero image

- main

<type>/<scope>-<short-slug>

feat/gui-live-preview

fix/pdf-hero-image

refactor/logging-bootstrap

perf/dataloader-prefetch

chore/ci-release-step

hotfix/0.17.1-pdf-null-crash

exp/vector-db-poc

chore

feat

refactor

ci

build

fix

docs

test

perf

hotfix

wip

style

hotfix/\*

main

fix:

<type>(<optional-scope>): <imperative summary>

<body – optional>

<footer – BREAKING CHANGE / issue refs>

feat(gui): add real-time detection preview panel

fix(pdf): correct missing hero when logo == cover image

refactor(logging): unify central + project logger bootstrap

chore(ci): refine release workflow version verification

feat!: remove legacy --batch flag

BREAKING CHANGE: The --batch flag was replaced by --batch-size.

feat

fix

!

BREAKING CHANGE:

- 
- feat(gui): add live preview
- fix(cli): correct path handling
- docs: update installation guide
- Fix GUI bugs
- Add new feature
- 
- 
- 
- 
- 

fix: docs: <type>(<scope>): <description> feat:

Dev Build <base>.devYYYYMMDD+<shortsha>  
dev-<computed-dev-version> dev-

1. main  
2. cz bump  
3.  
4. CHANGELOG.md vX.Y.Z main  
5.  
6.  
7. :X.Y.Z :latest  
8.  
9.  
10.  
11.  
12. v0.35.0 latest  
13.  
14.

1. hotfix/<next-patch>-<short-desc> main  
2. fix:  
3. cz bump

TrainingConfig  
tests/unit/crackz/project/test\_training\_config\_schema.py  
.pre-commit-config.yaml

```
pip install pre-commit # or uv tool install pre-commit
pre-commit install
```

test\_project.py

docs/configuration.md TrainingConfig Contract & Compatibility  
CHANGELOG.md

ModelConfig    DetectionConfig

```
feat/cli-batch-export
fix/train-metrics-path
perf/dataloader-cache
refactor/model-config
docs/pdf-section
test/cli-train-e2e
chore/update-ruff
ci/release-tag-fix
build/multiarch-images
style/ruff-cleanup
hotfix/0.17.2-threshold-null
exp/alt-model-head
wip/gui-layout-pass1
```

feat(gui):

BREAKING CHANGE:

- - 
  -
- feat/\*

typer.secho

```
Success messages
typer.secho("✅ Operation completed successfully", fg=typer.colors.GREEN)

Error messages
typer.secho("❌ Operation failed", fg=typer.colors.RED)

Warning messages
typer.secho("⚠️ Warning message", fg=typer.colors.YELLOW)

Info messages
typer.secho("ℹ️ Information", fg=typer.colors.CYAN)
```

logger

```
from crackz.log import logger

Detailed progress, technical info, debugging
logger.info("Detailed operational information")
logger.warning("Warning about internal state")
logger.error("Error details for troubleshooting")
```

NEVER USE

- print()
- typer.echo()            typer.secho()
- console.print()

- 

#### core/src/crackz/cli/options.py

```
from crackz.cli.options import PROJECT_PATH_OPTION, FORCE_OPTION

def command_function(
 project_path: Path | None = PROJECT_PATH_OPTION,
 force: bool = FORCE_OPTION,
) -> None:
```

```
Only for options not reused elsewhere
LOCAL_OPTION = typer.Option(
 None,
 "--local-flag",
 help="Module-specific option not reused elsewhere",
)
```

## NEVER

- 
- `typer.Option()`
- `FORCE_OPTION`

```
"""Module docstring explaining CLI command purpose."""

from __future__ import annotations

from pathlib import Path
import typer

from crackz.cli.exceptions import cli_failure
from crackz.cli.options import PROJECT_PATH_OPTION, FORCE_OPTION
from crackz.log import logger # Always import logger

app = typer.Typer(no_args_is_help=True)

@app.command(name="command")
def command_function(
 project_path: Path | None = PROJECT_PATH_OPTION,
 force: bool = FORCE_OPTION,
) -> None:
 """Command description."""
 try:
 # Business logic here
 logger.info("Processing started")
 typer.secho("✅ Operation completed", fg=typer.colors.GREEN)
 except Exception as e:
 cli_failure(e, "Operation name")
```

- 
- 
- 
- `loguru`
- `print()`

- 
- 
- 
-

- - 
  - 
  -
- ```
tests/unit/  
    tests/integration/  
        @pytest.mark.integration    @pytest.mark.benchmark
```

- 1.
 - 2.
 - 3.
 - 4.
 - 5.
 - 6.
- ```
options.py

uv run task lint && uv run task format
 uv run task mypy
 uv run task tests
```

- 1.
  - 2.
  - 3.
  - 4.
  - 5.
- ```
typer.secho()  
logger  
  
options.py
```

- 1.
 - 2.
 - 3.
 - 4.
 - 5.
 - 6.
 - 7.
- ```
print()
typer.echo() typer.secho()


options.py
```

---

# Release Flow

---

# Release Flow



- CHANGELOG.md
- 
- 

uv lock

uv.lock

main

- HEAD main
- 

version-bump

- 
- vx.Y.Z CHANGELOG.md

- build-wheels

- 
- 

- build-sdist

- .tar.gz

crackz

release

- 
- dist/
- site/crackz-docs.pdf .0
- CHANGELOG.md
- SHA256SUMS.txt
- 
- 
- --draft=false

- 
- cu118 cu128
- 
- CHANGELOG.md
- SHA256SUMS.txt
- .0

dist-combined

- ai-release-notes.yml
- 
- 
- pyinstaller-build.yml
- 
- 
- docker-build.yml
- 
- 

- 
- 
- 
- 

- feat: fix: perf: main
- 

- 
- 
- 
- .0

```
gh run list --limit 10
gh run view <run-id>
gh run watch
```

# PR Review Workflow

---



# Pull Request Review Workflow with Claude Code

- gh
- 
- 

```
List open PRs
gh pr list

View PR details
gh pr view <number>

View PR diff
gh pr diff <number>

Check CI status
gh pr checks <number>

Review PR
gh pr review <number> --approve
gh pr review <number> --comment -b "your comment"
gh pr review <number> --request-changes -b "needs changes"
```

```
List all open PRs
gh pr list

List PRs with specific labels
gh pr list --label "ready-for-review"

List your own PRs
gh pr list --author @me
```

```
View PR summary
gh pr view 254

View PR with comments
gh pr view 254 --comments

Open PR in browser
gh pr view 254 --web
```

```
fix(docs): resolve build failures and clarify release standards #254
Open • theresiasnow wants to merge 4 commits into main from fix/docs-build-and-standards

This PR fixes critical documentation build failures...

View this pull request on GitHub: https://github.com/owner/repo/pull/254
```

```
View full diff
gh pr diff 254

View only changed filenames
gh pr diff 254 --name-only

View diff in browser
gh pr diff 254 --web
```

```
View all checks
gh pr checks 254
```

```
View only required checks
gh pr checks 254 --required

Watch checks until completion
gh pr checks 254 --watch

Open checks in browser
gh pr checks 254 --web
```

```
✓ Build and Test (ubuntu-latest) – pass
✓ Build and Test (windows-latest) – pass
✓ Integration Tests – pass
✓ Lint and Format – pass
```

```
Checkout PR to review code locally
gh pr checkout 254

This creates/switches to the PR branch
Now you can:
- Run tests: uv run task tests
- Run linting: uv run task lint
- Build docs: uv run task build_docs
- Run the code locally
```

```
Review the changes in scripts/validate_commit_msg.py for:
- Code quality and readability
- Error handling
- Edge cases
- Documentation completeness
```

```
Review the changes in docs/contributing.md for:
- Clarity and completeness
- Correct formatting
- Broken links
- Consistency with existing docs
```

```
Check if the changes need additional tests and identify any edge cases not covered.
```

```
gh pr review 254 --approve -b "LGTM! Code quality looks good, tests pass."
```

```
gh pr review 254 --comment -b "Good work! Minor suggestion: consider adding error handling for X."
```

```
gh pr review 254 --request-changes -b "Please address the linting issues in validate_commit_msg.py before merging."
```

```
gh pr review 254 --approve -b "$(cat <<'EOF'
Great PR! Here's my review:

☐ Code quality: Excellent
☐ Tests: All passing
☐ Documentation: Clear and complete
☐ Linting: All checks pass

Minor suggestions:
- Consider adding a note about pre-commit hook in README
- The error messages are very helpful

Approved for merge.
EOF
)"
```

```
After review, switch back to main
git checkout main
```

```
List all PRs and store numbers
gh pr list

Review each PR in sequence
for pr in 254 255 256; do
 echo "Reviewing PR #$pr"
 gh pr view $pr
 gh pr diff $pr --name-only
 gh pr checks $pr
 # Ask Claude Code to review changes
done
```

```
Get PR data as JSON
gh pr view 254 --json title,body,author,createdAt,additions,deletions,files

Get check status as JSON
gh pr checks 254 --json name,state,completedAt
```

```
Continuously monitor checks until completion
gh pr checks 254 --watch --interval 30

This will update every 30 seconds until all checks complete
```

## Always Check CI Before Reviewing

```
Wait for checks to complete before reviewing
gh pr checks 254 --watch
```

## Review Locally for Complex Changes

```
For complex PRs, checkout and test locally
gh pr checkout 254
uv run task lint
uv run task tests
uv run task build_docs
```

## Use Claude Code for Deep Review

## Provide Constructive Feedback

```
Instead of just "needs work"
gh pr review 254 --request-changes -b "$(cat <<'EOF'
Thanks for the PR! A few items to address:

1. Linting: Please run 'uv run task lint' to fix PLR2004 error
2. Tests: Add test case for empty commit message
3. Docs: Update contributing.md with hook installation steps

Otherwise looks great!
EOF
)"
```

## Verify Release Triggers

```
Check PR title format
gh pr view 254 --json title

Should match: <type>(<scope>): <description>
Examples:
```

```
[] feat(gui): add export panel
[] fix(docs): resolve build failures
x Fix bugs
```

```
1. View the PR
gh pr view <number>

2. Check what files changed
gh pr diff <number> --name-only

3. View the actual changes
gh pr diff <number>

4. Checkout and test the fix
gh pr checkout <number>
Test the fix...

5. Run all pre-commit checks (lint, format, mypy, tests)
uv run task pre_commit

6. Approve if all looks good
gh pr review <number> --approve -b "Bug fix verified, all pre-commit checks pass."
```

```
1. View the PR
gh pr view <number>

2. Checkout the branch
gh pr checkout <number>

3. Build docs to check for errors
uv run task build_docs

4. Review locally with live server
uv run task docs
Opens at http://127.0.0.1:8000

5. Ask Claude Code to review
"Review the documentation changes for clarity, completeness, and broken links"

6. Approve or request changes
gh pr review <number> --approve
```

```
1. View PR and check size
gh pr view <number> --json additions,deletions,files

2. Check CI status
gh pr checks <number>

3. Checkout locally
gh pr checkout <number>

4. Run full test suite
uv run task all_tests

5. Test the feature manually
... manual testing ...

6. Ask Claude Code for code review
"Review this feature for:
- Code quality and maintainability
- Test coverage
- Documentation completeness
- Potential edge cases"

7. Provide detailed review
gh pr review <number> --approve -b "Feature works well, tests comprehensive."
```

- 1.
- 2.
- 3.
- 4.

```
👉 Release workflow completed successfully
👉 New release published: v0.52.1
👉 Artifacts built and uploaded
👉 CHANGELOG updated
👉 Git tag created
```

```
ⓘ Release workflow completed - No release created
👉 Reason: No conventional commits found that trigger releases
👉 This is expected behavior for documentation and maintenance commits
```

```
gh auth login
```

```
Make sure you're in the right repository
gh repo view

Or specify repository explicitly
gh pr view 254 -R Anaxiatech-AB/crackz
```

```
Stash local changes first
git stash

Then checkout PR
gh pr checkout <number>

Restore changes later
git stash pop
```

- \_\_\_\_\_
- \_\_\_\_\_
- \_\_\_\_\_

---

## Distribution

---

# Distribution & Commercial Delivery

```
.github/workflows/docker-build.yml
```

```
.github/workflows/docker-build.yml
```

```
uv build --wheel
python scripts/build_cuda_wheel.py
uv build --sdist
uv run task build_exe
docker build -f Dockerfile -t crackz-cli:latest .
docker build -f Dockerfile.slim -t crackz-cli:slim .
docker build -f Dockerfile.gpu -t crackz-cli:gpu .
```

```
Build with CUDA 11.8 (default, most compatible for Windows)
python scripts/build_cuda_wheel.py

Build with CUDA 12.1
python scripts/build_cuda_wheel.py --cuda-version cu121

Build with CUDA 12.8 (default for Linux)
python scripts/build_cuda_wheel.py --cuda-version cu128

Build without cleaning artifacts first
python scripts/build_cuda_wheel.py --no-clean
```

```
Method 1: Install with specific CUDA index
pip install dist/crackz-*.whl --extra-index-url https://download.pytorch.org/whl/cu118

Method 2: Install with CUDA extra (uses pyproject.toml config)
pip install dist/crackz-*.whl[cu128] # For CUDA 12.8 on Linux

Method 3: Install CPU-only version
pip install dist/crackz-*.whl[cpu]
```

```
cu118 cu121

cu128

index-url pyproject.toml --extra-
python -c "import torch; print(f'CUDA available: {torch.cuda.is_available()}')"
```

```
Build both CLI and GUI executables (CPU-only)
uv run task build_exe

Build only CLI
uv run task build_exe_cli

Build only GUI
uv run task build_exe_gui

Clean and rebuild
uv run task build_exe_clean
```

```
Build with CUDA 11.8 (default, recommended for Windows)
python scripts/build_cuda_exe.py
```

```
Build with CUDA 12.8 (for newer GPUs/Linux)
python scripts/build_cuda_exe.py --cuda-version cu128

Build only GUI with CUDA
python scripts/build_cuda_exe.py --gui-only

Skip CUDA check if already installed
python scripts/build_cuda_exe.py --skip-cuda-check
```

dist/crackz

dist/crackz-gui

```
Use the build script directly for more control
python scripts/build_exe.py --help
python scripts/build_exe.py --clean # Clean then build both
python scripts/build_exe.py --no-build # Only clean, don't build

CUDA build script
python scripts/build_cuda_exe.py --help
python scripts/build_cuda_exe.py --clean --cuda-version cu128
```

- - 
  -
- upload\_to\_pypi = false

dist/

v0.14.0

- 1.
- 2.
- 3.
- 4.

```
Install specific version from GitHub release
pip install https://github.com/OWNER/REPO/releases/download/v0.30.2/crackz-0.30.2-py3-none-any.whl

Or download then install
wget https://github.com/OWNER/REPO/releases/download/v0.30.2/crackz-0.30.2-py3-none-any.whl
pip install crackz-0.30.2-py3-none-any.whl
```

```
Set GitHub token
export GITHUB_TOKEN="ghp_XXXXXXXXXX" # gitleaks:allow
```

```
Download using gh CLI
gh release download v0.30.2 --pattern '*.whl' --repo OWNER/REPO
pip install crackz-*.whl

Or use curl with authentication
curl -L \
 -H "Authorization: token $GITHUB_TOKEN" \
 -o crackz.whl \
 https://github.com/OWNER/REPO/releases/download/v0.30.2/crackz-0.30.2-py3-none-any.whl
pip install crackz.whl
```

PRIVATE\_INDEX\_USER

\_\_token\_\_

PRIVATE\_INDEX\_PASSWORD

PRIVATE\_INDEX\_URL

```
pip install --index-url https://pypi.company.com/simple/ crackz
```

.github/workflows/release.yml

```
name: release
on:
 push:
 tags:
 - 'v*.*.*'
jobs:
 build-release:
 runs-on: ubuntu-latest
 permissions:
 contents: write # allow releasing
 steps:
 - uses: actions/checkout@v4
 - uses: actions/setup-python@v5
 with:
 python-version: '3.13'
 - name: Install uv
 run: pip install uv
 - name: Sync deps (locked)
 run: uv sync --frozen
 - name: Build wheel + sdist
 run: uv build --wheel --sdist
 - name: Build documentation PDF
 run: |
 uv run mkdocs build --clean --strict
 uv run playwright install chromium
 uv run python scripts/export_pdf.py --outline \
 --cover-image 'assets/crackz-logo.png' \
 --logo 'assets/crackz-logo.png' \
 --out site/crackz-docs.pdf
 cp site/crackz-docs.pdf dist/
 - name: Upload to private index (twine)
 if: env.PRIVATE_INDEX_URL != ''
 env:
 TWINE_USERNAME: ${ secrets.PRIVATE_INDEX_USER }
 TWINE_PASSWORD: ${ secrets.PRIVATE_INDEX_PASSWORD }
 run: |
 pip install twine
 twine upload --repository-url ${ secrets.PRIVATE_INDEX_URL } dist/*.whl dist/*.tar.gz
 - name: Attach artifacts to Release
 uses: softprops/action-gh-release@v2
 with:
 files: dist/*
```

publish-release.yml

crackz-gui

v0.35.0

latest

https://pypi.company.com/simple/

PRIVATE\_INDEX\_USER

PRIVATE\_INDEX\_URL

\_\_token\_\_



PRIVATE\_INDEX\_PASSWORD

`.github/workflows/docker-build.yml``.github/workflows/docker-build.yml`

```

docker login ghcr.io -u USER -p TOKEN
Build variants
docker build -f Dockerfile -t ghcr.io/anaxiatech-ab/crackz:latest .
docker build -f Dockerfile.slim -t ghcr.io/anaxiatech-ab/crackz:slim .
docker build -f Dockerfile.gpu -t ghcr.io/anaxiatech-ab/crackz:gpu .
Push
for tag in latest slim gpu; do docker push ghcr.io/anaxiatech-ab/crackz:$tag; done

```

```

docker pull ghcr.io/anaxiatech-ab/crackz:slim

```

```

pip install --index-url https://pypi.company.com/simple/ crackz
pip install https://github.com/OWNER/REPO/releases/download/vVERSION/crackz-VERSION-py3-none-any.whl
pip install torch torchvision --index-url <TORCH_URL> && pip install <crackz-wheel-url>
pip install --no-index --find-links wheelhouse crackz-VERSION-py3-none-any.whl
pip install --require-hashes -r requirements.txt

```

1.

```

Download Crackz wheel from GitHub Release first
wget https://github.com/OWNER/REPO/releases/download/vVERSION/crackz-VERSION-py3-none-any.whl

Create wheelhouse directory and download all dependencies
mkdir wheelhouse
pip download crackz-VERSION-py3-none-any.whl -d wheelhouse

```

2.

```

(cd wheelhouse && shasum -a 256 * > SHA256SUMS.txt)

```

3.

4.

```

pip install --no-index --find-links wheelhouse crackz-VERSION-py3-none-any.whl

```

- 
- `pip install pip-audit` `cyclonedx-bom` `.asc`
- 

---

`~/.config/pip/pip.conf`

```
[global]
extra-index-url = https://TOKEN@pkg.company.com/simple

%APPDATA%/pip/pip.ini
```

- 
- - `escrow-*`

- 
- 
- 

---

```
Build wheel
uv build --wheel
Build + attach release (manual example)
git tag v0.14.0 && git push origin v0.14.0
Install from private index
pip install --index-url https://pypi.company.com/simple/ crackz
Install from GitHub Release
pip install https://github.com/OWNER/REPO/releases/download/vVERSION/crackz-VERSION-py3-none-any.whl
Offline install
pip install --no-index --find-links wheelhouse crackz-VERSION-py3-none-any.whl
```


---

# Customer Guide

---

# Customer Guide: Crackz for Infrastructure Management

---



## What is a Mask?

| Original Image      | Mask Image                          | Result                                  |
|---------------------|-------------------------------------|-----------------------------------------|
| [photo of concrete] | → [white lines on black background] | = Trained model learns to detect cracks |

## When Do You Need Masks?

- 
- 
- 
- 
- 

## Recommended Tools for Creating Masks

1. CVAT (Computer Vision Annotation Tool) - Best for Teams

```
Self-hosted option (Docker)
docker run -d -p 8080:8080 cvat/server
Or use cloud-hosted version at app.cvat.ai
```

2. Labelme - Best for Individual Users

```
pip install labelme
labelme
```

labelme\_json\_to\_dataset <json\_file>      label.png

3. Photoshop / GIMP - Best for Fine Control

masks/val/      masks/test/      masks/train/

4. Python Scripting - Best for Automation

```
Example: Convert polygon annotations to masks
from PIL import Image, ImageDraw
import json

def polygon_to_mask(image_path, polygon_coors, output_path):
 # Load original image to get dimensions
 img = Image.open(image_path)
 width, height = img.size

 # Create black background
 mask = Image.new('L', (width, height), 0)
 draw = ImageDraw.Draw(mask)

 # Draw white polygon for crack
 draw.polygon(polygon_coors, fill=255)

 # Save mask
 mask.save(output_path)

Usage
polygon_coors = [(100, 200), (150, 250), (200, 230), ...]
polygon_to_mask('image_01.jpg', polygon_coors, 'masks/train/image_01.png')
```

Best Practices for Mask Creation

Quality Guidelines

- 
- 
- 
- 
- image\_01.jpg      image\_01.png

File Naming Convention

```
✓ CORRECT:
images/train/harbor_crack_001.jpg
masks/train/harbor_crack_001.png

✗ INCORRECT:
```

```
images/train/harbor_crack_001.jpg
masks/train/harbor_crack_001_mask.png ← Extra suffix
masks/train/HarborCrack001.png ← Different name
```

Organizational Tips

- 1.
- 2.
- 3.
- 4.
- 5.

Train/Val/Test Split

```
masks/
train/ # 70% of labeled data (200-350 images)
val/ # 15% of labeled data (30-50 images)
test/ # 15% of labeled data (30-50 images)
```

images/

```
images/
train/ # Same filenames as masks/train/
val/ # Same filenames as masks/val/
test/ # Same filenames as masks/test/
```

Using Crackz with Your Masks

images/train/

```
Automatic mask detection (if masks are in source_folder/masks/)
crackz import-images \
--project my-project \
--src ./labeled-data \
--type train \
--size 512 512

Explicit mask source
crackz import-images \
--project my-project \
--src ./images \
--masks_src ./masks \
--type train \
--size 512 512
```

```
crackz import-images \
--project my-project \
--src ./labeled-data \
--masks_src ./labeled-data/masks \
--split \
--train-ratio 0.7 \
--val-ratio 0.15 \
--test-ratio 0.15 \
--size 512 512 \
--random-seed 42
```

Troubleshooting Mask Issues

|  |  |  |
|--|--|--|
|  |  |  |
|--|--|--|

masks/train/

masks/

Advanced: Semi-Automated Mask Generation

Time Estimates

Professional Labeling Services


```
inspection-campaign-2025/
 images/ # Organized by train/val/test/raw splits
 masks/ # Ground truth for training (if available)
 artifacts/ # Detection results, metrics, checkpoints
 logs/ # Complete audit trail
 project.yaml # Configuration snapshot
```

- 
- 
- 
- 



- 
- 
- 
- 






- 
- 
- 
- 

- 
- 
- 
- 

- 
- 
- 
- 



---



---

---

---



Copyright © 2025 Theresia Sofia Snow. All rights reserved. Crackz is commercial software. See LICENSE for terms.

# Customer Access Management

- 1.
- 2.
- 3.
- 4.

- 1.
2. `templates/welcome-email.md`
3. `templates/access-revocation-email.md`
4. `templates/renewal-reminder-email.md`
- 5.
- 6.
- 7.
- 8.

- 1.
- 2.
- 3.

# Customer Access Management

---

1.

2.

3.
- `pip install crackz`

`pip install crackz`

1.

2.
- # Via GitHub web UI:  
# Settings > Teams > New Team  
# Team name: "Customer-Acme-Corp"  
# Privacy: Secret  
# Repository access: crackz (Read)

- 3.
- 4.
- 5.

Subject: Crackz Access - Welcome to [Customer Name]

Hi [Contact Name],

Thank you for your Crackz license purchase!

To access Crackz packages and Docker images, please:

1. Create a GitHub account (if you don't have one): <https://github.com/signup>
2. Reply with your GitHub username
3. We'll add you to the private repository

Once added, you can access:

- Releases: <https://github.com/Anaxiatech-AB/crackz/releases>
- Docker images: [https://github.com/anaxiatech?tab=packages&repo\\_name=crackz](https://github.com/anaxiatech?tab=packages&repo_name=crackz)
- Documentation: <https://github.com/Anaxiatech-AB/crackz/tree/main/docs>

License: [LICENSE-KEY or CONTRACT-REF]

Now the `release.yml` workflow will automatically publish to Azure Artifacts when configured!

Best regards,  
Theresia

Subject: Crackz Access Confirmed

Hi [Contact Name],

You now have access to the Crackz repository!

Installation instructions:  
<https://github.com/Anaxiatech-AB/crackz/blob/main/docs/installation.md>

Getting started:  
<https://github.com/Anaxiatech-AB/crackz/blob/main/docs/getting-started.md>

Docker registry:  
ghcr.io/anaxiatech-ab/crackz:latest

Need help? Email [theresia.sofia.snow@gmail.com](mailto:theresia.sofia.snow@gmail.com)

Best regards,  
Theresia

```
Find latest version at: https://github.com/Anaxiatech-AB/crackz/releases
pip install https://github.com/Anaxiatech-AB/crackz/releases/download/v0.30.2/crackz-0.30.2-py3-none-any.whl
```

```
Download from GitHub Releases page
wget https://github.com/Anaxiatech-AB/crackz/releases/download/v0.30.2/crackz-0.30.2-py3-none-any.whl

Install locally
pip install crackz-0.30.2-py3-none-any.whl
```

```
Install GitHub CLI: https://cli.github.com/
gh auth login

Download latest release
gh release download --repo anaxiatech/crackz --pattern '*.whl'

Install
pip install crackz-*.whl
```

```
Generate GitHub Personal Access Token

1. Go to: https://github.com/settings/tokens/new
```

2. Note: "Crackz Docker Access"
3. Expiration: 1 year (or custom)
4. Scopes: Select ONLY:
  - ☐ read:packages
5. Click "Generate token"
6. Copy the token (starts with ghp\_)

```
Customer runs this once
export CR_PAT=ghp_XXXXXXXXXXXXXXXXXXXX # Their PAT # gitleaks:allow
echo $CR_PAT | docker login ghcr.io -u GITHUB_USERNAME --password-stdin
```

```
Now they can pull
docker pull ghcr.io/anaxiatech-ab/crackz:latest
docker pull ghcr.io/anaxiatech-ab/crackz:slim
docker pull ghcr.io/anaxiatech-ab/crackz:gpu
```

```
Use as normal
docker run --rm ghcr.io/anaxiatech-ab/crackz:latest --version
```

- 1.
- 2.
- 3.
- 4.

```
Via Azure DevOps UI:
Artifacts > Create Feed
Name: crackz-packages
Visibility: Private (organization)
Upstream sources: Enable PyPI (optional)
```

- 5.
- 6.
- 7.
- o
  - o
- 8.

```
https://pkgs.dev.azure.com/YOUR-ORG/_packaging/crackz-packages/pypi/simple/
```

```
Settings > Secrets and variables > Actions > New repository secret
```

```
PRIVATE_INDEX_URL: https://pkgs.dev.azure.com/YOUR-ORG/_packaging/crackz-packages/pypi/upload
PRIVATE_INDEX_USER: azure
PRIVATE_INDEX_PASSWORD: <Azure-PAT-with-Packaging-Write-scope> # gitleaks:allow
```

```
publish-release.yml
```

```
Option 1: Install with explicit index
pip install crackz \
 --index-url https://pkgs.dev.azure.com/YOUR-ORG/_packaging/crackz-packages/pypi/simple/

Option 2: Configure pip globally
Linux/macOS: ~/.config/pip/pip.conf
Windows: %APPDATA%\pip\pip.ini
```

```
[global]
index-url = https://YOUR-PAT@pkgs.dev.azure.com/YOUR-ORG/_packaging/crackz-packages/pypi/simple/
```

```
pip install crackz
crackz --version
```

- 
- 
- 

```
Install devpi
pip install devpi-server devpi-web

Initialize server
devpi-init

Start server
devpi-server --start --host=0.0.0.0 --port=3141

Create user for yourself
devpi use http://localhost:3141
devpi user -c admin password=SECRET # gitleaks:allow

Create index
devpi index -c crackz bases=root/pypi
devpi use crackz
```

```
Install devpi client
pip install devpi-client

Login
devpi use http://YOUR-SERVER:3141
devpi login admin --password=SECRET # gitleaks:allow
devpi use admin/crackz

Upload wheel
devpi upload dist/crackz-*.whl
```

```
Customer configures pip
pip install --index-url http://YOUR-SERVER:3141/admin/crackz/+simple/ crackz
```

```
docker run -p 3141:3141 mucg/devpi
```

- 2.
- 3.
- 4.
- 5.
- 6.
- 7.
- 8.
- 9.

```
Subject: Crackz License Expired - Access Revoked

Hi [Contact],

Your Crackz license expired on [DATE].
Repository and package access has been revoked.

To renew, please contact theresia.sofia.snow@gmail.com

Thank you for using Crackz.
```

- 1.
- 2.
- 3.

- 1.
  - 2.
  - 3.
  - 4.
- 

```
Ask customer to verify:
1. Go to: https://github.com/Anaxiatech-AB/crackz
2. If you see "404 Not Found", you don't have access yet
3. Reply with your GitHub username for access
```

```
read:packages
```

```
Ask customer to:
1. Generate new PAT: https://github.com/settings/tokens/new
2. Select ONLY: read:packages
3. Run: echo PAT | docker login ghcr.io -u USERNAME --password-stdin
4. Try again: docker pull ghcr.io/anaxiatech-ab/crackz:latest
```

```
Recommend:
pip install https://github.com/Anaxiatech-AB/crackz/releases/download/v0.30.2/crackz-0.30.2-py3-none-any.whl
```

```
You prepare:
pip download crackz -d wheelhouse
tar -czf crackz-offline-bundle.tar.gz wheelhouse/

Customer installs:
tar -xzf crackz-offline-bundle.tar.gz
pip install --no-index --find-links wheelhouse crackz
```

1.

```
Customer pulls and retags
docker pull ghcr.io/anaxiatech-ab/crackz:latest
docker tag ghcr.io/anaxiatech-ab/crackz:latest registry.company.com/crackz:latest
docker push registry.company.com/crackz:latest
```

2.

```
Get release download counts
gh api repos/anaxiatech/crackz/releases \
--jq '.[] | {name: .name, downloads: [.assets[]|download_count] | add}'
```

```
{"name": "v0.30.2", "downloads": 47}
{"name": "v0.30.1", "downloads": 23}
```

```
Requires GitHub GraphQL API (complex)
Easier to use web UI for now
```

```
Crackz Usage Report - October 2025
```

```
Active Customers: 5
```

| Customer  | License | Status  | Last Access |
|-----------|---------|---------|-------------|
| Acme Corp | LIC-001 | Active  | 2025-10-08  |
| Beta Inc  | LIC-002 | Active  | 2025-10-05  |
| Gamma LLC | LIC-003 | Expired | 2025-09-30  |

```
Download Statistics
```

```
- Total releases: 12
- Total downloads (wheels): 156
- Docker pulls (latest): 89
- Docker pulls (gpu): 34
```

```
Top Versions
```

```
1. v0.30.2: 47 downloads
2. v0.30.1: 23 downloads
```

3. v0.30.0: 18 downloads

## Action Items

- [ ] Contact Gamma LLC for renewal
- [ ] Send v0.31.0 release announcement

- 1.
2. PRIVATE\_INDEX\_\*
- 3.
- 4.
- 5.
- 6.
- 7.
- 8.
- 9.
- 10.
- 11.
- 12.

- 1.
- 2.
3. read:packages
- 4.
- 5.
- 6.
- 7.
- 8.
- 9.
- 10.
- 11.
- 12.



```
#!/bin/bash
scripts/customer-access/onboard-customer.sh

set -euo pipefail

CUSTOMER_NAME="$1"
GITHUB_USERNAME="$2"
LICENSE_KEY="$3"

echo "👤 Onboarding customer: $CUSTOMER_NAME"
echo "GitHub username: $GITHUB_USERNAME"
echo "License: $LICENSE_KEY"

Create GitHub team (requires gh CLI with admin access)
TEAM_SLUG="customer-$(echo $CUSTOMER_NAME | tr '[:upper:]' '[:lower:]' | tr ' ' '-')"
gh api orgs/YOUR-ORG/teams -f name="Customer-$CUSTOMER_NAME" -f privacy=secret

Add member to team
gh api orgs/YOUR-ORG/teams/$TEAM_SLUG/memberships/$GITHUB_USERNAME -X PUT

Add team to repository
gh api orgs/YOUR-ORG/teams/$TEAM_SLUG/repos/YOUR-ORG/crackz -X PUT -f permission=pull

echo "👤 Customer onboarded successfully!"
echo ""
echo "Next steps:"
echo "1. Send welcome email to customer"
echo "2. Add to tracking spreadsheet"
echo "3. Schedule renewal reminder for 1 year from now"
```

```
#!/bin/bash
scripts/customer-access/revoke-customer.sh

set -euo pipefail

CUSTOMER_NAME="$1"
REASON="${2:-License expired}"

echo "👤 Revoking access for: $CUSTOMER_NAME"
echo "Reason: $REASON"

TEAM_SLUG="customer-$(echo $CUSTOMER_NAME | tr '[:upper:]' '[:lower:]' | tr ' ' '-')"

Remove team from repository
gh api orgs/YOUR-ORG/teams/$TEAM_SLUG/repos/YOUR-ORG/crackz -X DELETE

Optionally delete team entirely
read -p "Delete team entirely? (y/n) " -n 1 -r
echo
if [[$REPLY =~ ^[Yy]$]]; then
 gh api orgs/YOUR-ORG/teams/$TEAM_SLUG -X DELETE
 echo "👤 Team deleted"
else
 echo "👤 Team kept (access removed from repository only)"
fi

echo "👤 Access revoked successfully!"
echo ""
echo "Next steps:"
echo "1. Send termination notice to customer"
echo "2. Update tracking spreadsheet"
echo "3. Archive customer records"
```

```
pip install crackz
```

```
PRIVATE_INDEX_*
```

---

## Printable PDF

---

# Printable / PDF Export

---

site/crackz-docs.pdf

*The cover automatically injects the current project version from `pyproject.toml` and © Anaxiatech AB.*

```
uv run task pdf
```

```
mkdocs build --clean --strict python scripts/export_pdf.py
```

site/crackz-docs.pdf

```
make docs-pdf
```

```
uv run task pdf_fast
```

```
site/crackz-docs-fast.pdf
```

```
pwsh scripts/windows/export_pdf.ps1 -Outline -CoverTitle "Crackz Documentation"
```

```
-NoCover -NoHeader
```

```
uv run mkdocs build --clean --strict
uv run playwright install chromium # one time
uv run python scripts/export_pdf.py \
 --outline \
 --cover-image 'assets/crackz-logo.png' \
 --logo 'assets/crackz-logo.png' \
 --cover-title 'Crackz Documentation' \
 --cover-subtitle 'AI Image Analysis' \
 --out site/crackz-docs.pdf
```

```
uv run python scripts/export_pdf.py --out site/my-custom-docs.pdf
```

nav :

--no-bookmarks

<article>

```
- name: Build docs + PDF
run: |
 uv sync --dev
 uv run mkdocs build --clean --strict
 uv run playwright install chromium
 uv run python scripts/export_pdf.py --outline --cover-image 'assets/crackz-logo.png' --logo 'assets/crackz-logo.png' --out site/crackz-docs.pdf
- uses: actions/upload-artifact@v4
 with:
 name: crackz-docs-pdf
 path: site/crackz-docs.pdf
```

```
https://<your-user>.github.io/crackz/crackz-docs.pdf
```

# License

# License

---

Copyright (C) 2025 Theresia Sofia Snow

This program is free software: you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation, either version 3 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program. If not, see <http://www.gnu.org/licenses/>.