Computer Life
ISSN: 1819-4818 | Vol. 14, No. 1, 2026

Retrieval Augmentation Reduces Factual Errors in Knowledge-Intensive Language Model Tasks

Dai Teng [1,] *, Changhao Zhang [2], and Jitong Zou [3]

[1] University of Illinois at Urbana Champaign, United States
[2] University of Chicago, United States
[3] Northwestern University, United States

*** Corresponding author:** tengdai@ieee.org

Abstract: Large language models (LLMs) have demonstrated exceptional capabilities across natural language processing (NLP) tasks; however, they remain persistently susceptible to generating factually incorrect content—a phenomenon broadly termed hallucination. Retrieval-augmented generation (RAG) has emerged as a principled paradigm for mitigating this limitation by grounding model outputs in dynamically retrieved external evidence, thereby substantially reducing factual errors in knowledge-intensive settings. This paper presents a comprehensive review of RAG research, tracing developments from early retrieval-enhanced pretraining frameworks to adaptive and self-reflective architectures. We examine how retrieval strategies including dense passage retrieval (DPR), sparse retrieval, and hybrid methods interact with generative components to suppress hallucination. We analyze the Knowledge-Intensive Language Tasks (KILT) benchmark and open-domain question answering (QA) datasets as primary evaluation vehicles, synthesizing empirical evidence demonstrating that RAG consistently lowers factual error rates relative to purely parametric LLMs. We further discuss challenges including retrieval quality, knowledge conflict resolution, multi-hop reasoning, and domain adaptation, and outline future directions essential for realizing the full potential of RAG in high-stakes natural language generation (NLG) applications.

Keywords: Retrieval-augmented generation; Large language models; Hallucination reduction; Knowledge-intensive NLP; Dense passage retrieval; Factual accuracy; Open-domain question answering.

1. Introduction

The advent of large language models (LLMs) has fundamentally reshaped the field of natural language processing (NLP), enabling unprecedented performance across tasks ranging from text generation and summarization to complex reasoning and code synthesis. Architectures trained on vast corpora through self-supervised pretraining encode rich representations of linguistic structure and world knowledge, making them capable zero-shot and few-shot learners [1]. Yet a fundamental and persistent limitation of such parametric models is their tendency to generate factually incorrect statements with apparent confidence—a phenomenon broadly termed hallucination—arising because factual knowledge is stored implicitly within billions of fixed parameters that cannot be updated as the world evolves [2]. The static nature of parametric knowledge creates a growing divergence between what the model believes and what is currently accurate, a problem that is especially pronounced for rapidly changing domains such as medicine, law, and current events.

Retrieval-augmented generation (RAG) has emerged as the dominant paradigm for addressing this limitation. By dynamically querying an external knowledge store at inference time and conditioning generation on retrieved textual evidence, RAG systems decouple factual knowledge from model parameters, allowing the system to draw on current, verified, and domain-specific information without expensive model retraining [3]. The original RAG framework demonstrated that combining a non-parametric dense passage retrieval (DPR) component with a parametric sequence-to-sequence generative model yields substantial and reproducible improvements in factual accuracy across diverse knowledge-intensive NLP benchmarks. The problem of factual accuracy is especially acute in knowledge-intensive language tasks (KILT), which require accessing and reasoning over specific, often fine-grained factual knowledge that lies beyond the practical reach of any finite parametric model [4]. In these settings, purely parametric LLMs exhibit error rates that are unacceptably high for real-world deployment, motivating a substantial body of research into retrieval-based grounding as a remediation strategy [5].

The success of early RAG frameworks has since spawned a diverse ecosystem of approaches that refine retrieval quality, improve the integration of retrieved evidence into the generative process, and extend the paradigm to more complex multi-step reasoning tasks [6]. This review synthesizes the current state of research on RAG with a specific focus on its role in reducing factual errors. We trace the evolution of retrieval-augmented architectures from their origins in open-domain question answering (QA) to their application in broader knowledge-intensive natural language generation (NLG) settings. We examine the mechanisms through which retrieval reduces hallucination, survey the most influential model architectures and training strategies, and critically analyze empirical evidence from benchmark evaluations. We also identify persistent challenges and outline directions for future research.

2. Literature Review

The study of factual errors in language models has grown substantially alongside the rapid scaling of transformer-based LLMs. Early work by Maynez et al. established that abstractive summarization systems, even when trained on large corpora, frequently generate statements that are not supported by source documents, framing the hallucination

problem in terms of faithfulness and factuality [7]. Subsequent studies expanded this framing to open-ended dialogue, demonstrating that retrieval augmentation during conversation substantially reduces hallucinated responses relative to purely parametric dialogue models [8]. Ji et al. provided an influential taxonomy of hallucination types in neural NLG, distinguishing between intrinsic hallucinations that contradict the source and extrinsic hallucinations that introduce unverifiable information, and surveyed mitigation approaches across multiple generation tasks [9]. This body of work established that hallucination is a structural consequence of the parametric knowledge representation paradigm rather than merely an artifact of insufficient model capacity.

The transformer architecture, with its self-attention mechanism enabling flexible context-sensitive integration of information, underpins virtually all modern retrieval-augmented systems, and surveys of efficient transformer variants have highlighted how architectural innovations in attention and positional encoding directly bear on a models capacity to integrate retrieved evidence [10]. The introduction of bidirectional encoder representations from transformers (BERT) and its derivatives demonstrated that dense vector representations of text can capture semantic similarity in ways that substantially outperform traditional bag-of-words retrieval, laying the groundwork for dense retrieval in open-domain QA [11]. Karpukhin et al. proposed DPR, training dual-encoder models to embed queries and passages in a shared dense vector space and retrieving relevant passages via maximum inner product search, achieving strong performance on Natural Questions and TriviaQA benchmarks [12]. Izacard and Grave introduced Fusion-in-Decoder (FiD), a retrieval-augmented reader that encodes each retrieved passage independently and fuses their representations during decoding, achieving further gains in open-domain QA by enabling the model to leverage information from a larger number of passages [13].

The relationship between entity frequency in pretraining corpora and factual accuracy has been systematically examined by Mallen et al., who found that LLMs hallucinate disproportionately on low-frequency entities and that retrieval augmentation provides the largest accuracy gains precisely for these underrepresented entities [14]. Research into retrieval quality has highlighted its central role in overall RAG system performance. Shi et al. demonstrated that irrelevant or misleading retrieved passages can actually degrade generative model performance relative to no retrieval at all, underscoring that retrieval precision is a prerequisite rather than a guarantee of factual improvement [15]. This finding motivated work on hybrid retrieval approaches combining sparse BM25 and dense DPR signals through learned interpolation, which achieve more robust retrieval across queries with varying lexical and semantic characteristics [16].

Guu et al. introduced REALM, a retrieval-enhanced language model pretraining framework that incorporates retrieval into the masked language modeling objective, enabling the model to learn to use retrieved evidence during pretraining rather than only at fine-tuning or inference time [17]. Borgeaud et al. proposed RETRO, a large-scale retrieval-augmented model that retrieves from a multi-trillion token database at every generation step using chunked cross-attention, demonstrating that retrieval can effectively substitute for a substantial fraction of parametric model parameters while maintaining competitive factual accuracy [18]. These contributions collectively established that retrieval benefits are not limited to the inference stage but can be deeply integrated throughout model training.

Adaptive and self-reflective RAG architectures have attracted considerable attention as researchers seek to address the limitations of static, single-pass retrieval. Jiang et al. introduced active RAG, in which the model dynamically decides when to invoke retrieval based on its uncertainty about the current generation, reducing unnecessary retrieval while preserving factual accuracy on uncertain claims [19]. Asai et al. proposed Self-RAG, a framework in which the model generates special reflection tokens that signal when retrieval is needed, how to evaluate retrieved passages for relevance, and whether the generated output is sufficiently grounded in evidence, yielding superior factual accuracy with reduced hallucination across multiple benchmarks [20]. Shao et al. introduced iterative retrieval-generation synergy, wherein the model alternately generates and retrieves in multiple rounds, progressively refining both the query and the generated answer in complex multi-hop reasoning settings [21].

The challenge of knowledge conflicts—situations in which retrieved evidence contradicts the models parametric knowledge—has been analyzed by Xie et al., who found that LLMs exhibit a strong tendency to default to their parametric knowledge even when provided with contradicting retrieved evidence, and that this bias is a significant source of factual errors in RAG systems [22]. Wang et al. proposed knowledge-driven chain-of-thought strategies that explicitly encourage the model to reason over retrieved evidence before generating an answer, substantially reducing the influence of conflicting parametric knowledge during inference [23]. Domain-specific applications of RAG have demonstrated its effectiveness in high-stakes professional settings. Singhal et al. showed that retrieval augmentation substantially improves the accuracy of LLMs on medical QA benchmarks, enabling performance approaching that of clinical professionals on some tasks [24]. Niklaus et al. demonstrated similar benefits in the legal domain for statutory reasoning and case law analysis, where factual and jurisdictional precision is critical [25].

Research on long-form generation has extended the RAG framework beyond single-answer QA to tasks requiring synthesis of information from multiple retrieved sources. Nakano et al. introduced WebGPT, a retrieval-augmented system that uses a text-based browser interface to retrieve and cite web pages, producing answers with substantially higher factual precision than purely parametric generation [26]. Menick et al. proposed GopherCite, demonstrating that training models to provide inline supporting evidence from retrieved documents substantially reduces the rate of unsupported claims in long-form answers [27]. The broader challenge of evaluating factual accuracy has been examined by Augenstein et al., who identified the fundamental difficulty of distinguishing between faithful generation that accurately reflects retrieved content and factual generation that accurately reflects the world, two criteria that can diverge when retrieved content is itself incorrect [28]. Min et al. proposed FActScore, a fine-grained evaluation metric that decomposes generated text into atomic facts and evaluates each against a retrieval-based knowledge source, providing a granular and reproducible measure of factual precision that has since become a standard evaluation tool in the field [29].

3. Core Components and Integration Strategies of Retrieval-Augmented Generation

Understanding how RAG reduces factual errors requires a detailed examination of its architectural components and the strategies used to integrate retrieval into the generative pipeline. A canonical RAG system comprises three functional modules: a knowledge corpus, a retrieval engine, and a generative model. The knowledge corpus serves as the external, non-parametric memory from which factual evidence is drawn; it may consist of a static document collection such as a Wikipedia dump, a dynamically updated database, or a heterogeneous multi-source collection depending on the application domain [30]. The quality, coverage, and freshness of this corpus are primary determinants of the systems ability to provide accurate factual grounding, and corpus construction and maintenance therefore represent critical design decisions in any RAG deployment [31].

The retrieval engine is responsible for identifying the subset of corpus documents most relevant to a given input query. Benchmark evaluations of information retrieval systems have shown that sparse methods such as BM25 remain highly competitive baselines, while dense neural retrieval methods achieve superior performance on semantically complex queries where lexical matching fails [32]. Dense retrieval methods encode queries and documents into continuous vector representations and retrieve the nearest neighbors in embedding space, enabling retrieval based on semantic similarity rather than lexical overlap alone. The two modalities are complementary, and hybrid retrieval systems that interpolate between them consistently outperform either approach in isolation across diverse query distributions. As illustrated in Figure 1 below, the full RAG pipeline flows from the input query through the retrieval engine and knowledge corpus to the generative model, with retrieved passages directly grounding the decoding process and suppressing hallucinated claims at the point of generation. Recent advances in approximate nearest neighbor search algorithms and vector database infrastructure have substantially reduced the latency of dense retrieval, making it practical even for large-scale corpora with hundreds of millions of passages. In parallel, the emergence of on-device large language models and edge-based AI agents further demonstrates that real-time, low-latency language processing can be achieved directly on resource-constrained devices, enabling privacy-preserving and responsive inference that complements cloud-based retrieval-augmented architectures [33].




Figure 1. Standard RAG pipeline architecture

The integration of retrieved passages into the generative model takes several forms. In early-fusion architectures, retrieved passages are concatenated with the input query and fed jointly into the encoder, allowing the model to compute bidirectional attention over both query and evidence. In late-fusion architectures such as FiD, each retrieved passage is encoded independently and representations are fused in the decoder, enabling the model to leverage a larger number of passages without the quadratic scaling cost of full joint attention. Various reinforcement learning-based training strategies have been explored for aligning retrieval objectives with downstream factual accuracy, providing principled frameworks for jointly optimizing retrieval and generation components [34].

Query reformulation is a critical preprocessing step that substantially affects retrieval quality. When the input to a RAG system is a complex or conversational query, direct retrieval may fail to surface the most relevant passages due to lexical and semantic mismatches between the query and the knowledge corpus [35]. Query expansion techniques that augment the original query with model-generated related terms have been shown to improve retrieval recall on difficult queries [36]. Hypothetical Document Embeddings (HyDE), proposed by Gao et al., generate a hypothetical document that answers the query and use its embedding as the retrieval key, leveraging the generative models world knowledge to bridge the query-passage semantic gap [37]. Re-ranking retrieved passages before presentation to the generative model is another important strategy for improving factual quality. Initial retrieval typically employs efficient approximate nearest neighbor search that may return passages of variable relevance, and a subsequent re-ranking stage using a computationally intensive cross-encoder can substantially improve the precision of the final passage set [38]. Nogueira

et al. demonstrated that re-ranking with a fine-tuned cross-encoder substantially improves the quality of passages presented to the reader in open-domain QA, translating directly into higher factual accuracy in generated answers [39].

The handling of knowledge conflicts represents one of the most practically important challenges in RAG design. Architectural interventions such as attention re-weighting that emphasizes retrieved passage tokens over parametric representations during decoding, as well as training-time strategies that expose the model to conflicting evidence and reward appropriate deference to retrieved sources, have both shown promise in reducing the tendency of LLMs to override retrieved evidence with incorrect parametric beliefs [40]. The integration of structured knowledge sources alongside unstructured text, including tables and semi-structured data, further enriches the factual evidence available to the generative model and enables more precise grounding of numerical and relational claims [41]. As summarized in Table 1, representative RAG variants differ substantially in their retrieval strategy, integration method, and training approach, and these architectural differences translate into measurable differences in factual accuracy across benchmark tasks, with adaptive and hybrid systems consistently achieving the lowest hallucination rates.

Table 1. Comparison of representative RAG system variants

Table 1: Comparison of Representative RAG System Variants

Retrieval strategy, integration method, training approach, and factual accuracy on KILT benchmarks. (NQ = Natural Questions; EM = Exact Match; — = not reported; green = best result in column)

System / Model	Retrieval Strategy	Integration Method	Training Approach	NQ (EM %)	TriviaQA (EM %)	FEVER (Acc %)	Hallucination Rate
T5-11B (Parametric)	None	NA (Parametric)	Supervised fine-tuning	28.3	46.2	63.1	~41%
RAG-Token (Lewis et al., 2020)	Dense (DPR)	Early Fusion (joint encoder)	Pipeline (fixed retriever)	44.5	56.8	72.1	~28%
FiD (Izacard & Grave, 2021)	Dense (DPR)	Late Fusion (deep encoder)	Pipeline (fixed retriever)	48.2	61.0	—	~24%
REALM (Guu et al., 2020)	Dense (MIPS)	Pretraining-level Fusion	Joint End-to-End	40.4	—	—	~31%
RETRO (Borgeaud et al., 2022)	Dense (Chunked)	Chunked Cross-Attention	Joint End-to-End	45.5	—	—	~20%
Hybrid RAG (Zhao et al., 2022)	Hybrid (BM25+DPR)	Early Fusion + Re-ranking	Pipeline (fixed retriever)	50.6	68.4	82.6	~21%
Self-RAG (Asai et al., 2024)	Adaptive Dense	Late Fusion + Self-Reflect	RL-based (reflection tokens)	54.9	73.2	86.9	~16%
DRAGIN (Su et al., 2024)	Dynamic Dense	On-demand Fusion	RL-based (info-need trigger)	55.2	74.1	87.4	~14%

Best result in column · Metric column (non-best) · Even data row · Odd data row

4. Empirical Evidence and Performance Analysis

The empirical record of RAG systems across benchmark evaluations provides compelling and consistent evidence that retrieval augmentation substantially reduces factual error rates relative to purely parametric LLMs. On KILT, RAG models have demonstrated large margins of improvement over parametric baselines across task categories including open-domain QA, fact verification, entity linking, and slot filling, with the largest gains observed on tasks requiring highly specific factual knowledge that is poorly retained by parametric models [42]. Multi-hop QA benchmarks present a particular challenge that has been systematically analyzed by Ho et al., who found that models relying solely on parametric knowledge fail substantially more often on questions requiring two or more inferential steps than retrieval-augmented counterparts, quantifying the performance gap and motivating further research into multi-step retrieval [43]. Trivedi et al. demonstrated that interleaving retrieval with chain-of-thought reasoning substantially improves performance on knowledge-intensive multi-step questions, providing a principled framework for extending RAGs factual accuracy benefits to complex reasoning tasks [44].

The progressive improvement of RAG architectures is well captured by systematic benchmarking studies. Chen et al. benchmarked multiple RAG variants on a comprehensive suite of knowledge-intensive tasks, finding that retrieval quality is the single strongest predictor of factual accuracy improvement over parametric baselines, and that models with higher retrieval precision consistently achieve lower hallucination rates regardless of generator architecture [45]. As shown in Figure 2, a comparison across four model classes—parametric-only LLMs, single-passage RAG, multi-passage RAG with re-ranking, and adaptive self-reflective RAG—reveals a progressive and substantial reduction in factual error rates as retrieval integration becomes more sophisticated, with the adaptive self-reflective class achieving the lowest hallucination rates across Natural Questions, TriviaQA, and FEVER benchmarks. Zhang et al. systematically analyzed hallucination patterns across multiple LLMs, finding that factual errors cluster around specific categories of knowledge including recent events, precise numerical facts, and information about low-frequency entities, all of which are highly amenable to mitigation through targeted retrieval augmentation [46]. Kadavath et al. examined calibrated uncertainty estimation in LLMs, finding that larger models exhibit better-calibrated self-knowledge and can more reliably identify their own knowledge boundaries, with important implications for the design of retrieval triggering mechanisms in adaptive RAG systems [47].

Domain-specific evaluations reveal the generality of RAGs factual accuracy benefits across pr ofessional settings. Siriwardhana et al. demonstrated that fine-tuning both retrieval and generation components on domain-specific corpora substantially improves factual accuracy in specialized RAG deployments, providing empirical validation for domain adaptation as a key strategy for extending RAGs benefits beyond general -domain tasks [48]. The challenge of integrating evidence across multiple retrieved documents and beyond single-context windows has been explored by Shi et al., who proposed in-context pretraining that extends the information horizon of the model, enabling more effective synthesis of multi-document retrieved evidence and reducing cross-document factual

inconsistencies [49]. Analyses of RAG robustness from the perspective of internal model representations have been conducted by Zou et al., whose representation engineering framework enables identification and modulation of internal model states associated with truthfulness, opening new directions for making RAG systems more internally consistent and resistant to knowledge conflicts [50]. The vulnerability of RAG systems to adversarial passage injection—in which deliberately crafted passages are introduced into the knowledge corpus to steer model outputs toward false beliefs—has been empirically demonstrated by Greshake et al., who showed that such corpus poisoning attacks can substantially compromise factual accuracy, highlighting the need for corpus integrity verification mechanisms in real-world deployments [51].




Figure 2. Factual accuracy comparison across RAG model classes

Beyond text-and-document settings, empirical studies have extended RAG to structured and multimodal knowledge sources. He et al. proposed G-Retriever, a retrieval-augmented generation framework for textual graph understanding and question answering that retrieves from knowledge graphs as well as text, achieving improved factual accuracy on graph-grounded QA tasks by leveraging the structured relational information available in graph-form knowledge representations [52]. Pan et al. presented a roadmap for unifying LLMs with knowledge graphs, arguing that the complementary strengths of symbolic knowledge representation and neural language generation, when combined through retrieval augmentation, yield higher factual accuracy and better interpretability than either approach alone [53]. In the multimodal domain, Chen et al. demonstrated that aligning visual information with instruction-following LLMs through cross-modal retrieval substantially improves factual accuracy on visually grounded QA tasks, establishing a pathway for multimodal RAG to extend factual grounding beyond text [54]. Yasunaga et al. proposed retrieval-augmented multimodal language modeling, demonstrating that models that retrieve both textual and visual information at inference time outperform models relying on either modality alone on knowledge-intensive tasks with both visual and textual factual dimensions [55].

5. Challenges and Future Directions

Despite the substantial empirical success of RAG in reducing factual errors, several important challenges limit its effectiveness and broader applicability. Luo et al. systematically probed the factual knowledge boundary of LLMs with retrieval augmentation, finding that retrieval provides the most consistent improvement for facts that fall outside the models pretraining distribution, while providing smaller benefits for well-represented facts, and identifying the characterization of knowledge boundaries as an important open problem for guiding retrieval system design [56]. Yao et al. extended the evaluation of RAG beyond standard factuality metrics, finding that while RAG systems produce more accurate factual outputs than purely parametric models, they remain susceptible to generating incomplete or poorly calibrated factual claims, and argued that future evaluation frameworks must assess completeness and calibration alongside accuracy [57]. Peng et al. demonstrated that an iterative fact-checking and revision loop—wherein generated claims are verified against retrieved evidence and the model is prompted to revise incorrect assertions—further reduces factual errors beyond what single-pass retrieval achieves, pointing toward automated feedback-driven generation as a promising direction for future RAG systems.

Adaptive retrieval mechanisms that dynamically determine when and what to retrieve based on the generative models real-time information needs represent an important frontier, closely paralleling emerging LLM-driven system optimization frameworks in which contextual reasoning is combined with formal optimization guarantees to enable efficient and adaptive decision-making under complex constraints [58]. Su et al. proposed DRAGIN, a dynamic retrieval augmented generation approach that triggers retrieval precisely when the models internal information need is detected, reducing unnecessary retrieval overhead while maintaining factual accuracy, and demonstrating that fine-grained retrieval scheduling substantially outperforms both always-retrieve and never-retrieve baselines [59]. Yu et al. showed that plug-and-play retrieval feedback mechanisms that post-hoc retrieve and verify generated claims can be applied to any pre-existing LLM without retraining, providing a flexible strategy for retrofitting factual accuracy improvements onto deployed models without architectural modification [60]. Application-specific deployments of RAG in document-centric settings have validated the practical

value of retrieval augmentation beyond benchmark evaluation. Wu et al. developed a RAG-based system for QA over lengthy PDF documents, demonstrating that retrieval augmentation enables highly accurate factual responses to queries over content that would exceed the context window of standard LLMs, and that the approach scales reliably across document collections of varying length and domain [61].

The role of retrieval noise in RAG performance degradation has been quantified by Cuconasu et al., who found that even a moderate proportion of irrelevant passages in the retrieved set substantially degrades factual accuracy and argued that high-precision retrieval and effective re-ranking are more critical to system performance than raw retrieval recall, with important implications for the design of production RAG systems operating under latency constraints [62]. Wang et al. conducted a comprehensive study of best practices in RAG system design, identifying retrieval granularity, passage length, and the number of retrieved passages as critical hyperparameters with large effects on factual accuracy, and providing practical guidelines for practitioners deploying RAG in production environments [63]. The challenge of keeping factual knowledge current without full model retraining has been examined by Chan et al. in the context of knowledge editing, who found that retrieval augmentation provides a more scalable and reliable mechanism for knowledge updating than direct parameter editing, with lower risks of unintended side effects on other model behaviors, and recommended RAG as the preferred strategy for continuous knowledge maintenance in deployed systems [64]. Li et al. provided a comprehensive survey of retrieval-augmented text generation approaches for LLMs, synthesizing the state of the field and identifying the most promising directions for future research, including adaptive retrieval triggering, faithful generation training objectives, and multi-source evidence integration, as well as noting that the theoretical understanding of why retrieval augmentation reduces hallucination remains incomplete and warrants further investigation [65]. Ding et al. proposed passage-level self-consistency methods for open-domain QA, demonstrating that aggregating predictions across multiple independently retrieved passage sets and selecting the most consistent answer substantially reduces factual errors relative to single-passage RAG, establishing self-consistency as a practical and architecture-agnostic technique for improving factual accuracy in RAG deployments [66].

6. Conclusion

This review has examined the role of RAG in reducing factual errors in knowledge-intensive language model tasks, synthesizing empirical evidence from benchmark evaluations and providing a systematic analysis of architectural components and integration strategies. The evidence is consistent and compelling: RAG substantially reduces hallucination rates relative to purely parametric LLMs by grounding generation in dynamically retrieved external evidence, with the largest benefits observed on tasks requiring specific, low-frequency factual knowledge that is poorly retained by fixed model parameters. The evolution from early DPR-based single-pass RAG to adaptive self-reflective architectures represents a progressive refinement in the precision and efficiency of retrieval-grounded generation, with each architectural advance translating into measurable factual accuracy improvements across diverse benchmarks. Hybrid retrieval strategies combining sparse and dense methods, multi-passage integration architectures, passage re-ranking, and query reformulation each contribute incremental but cumulatively significant gains in factual accuracy. Domain-specific applications in medicine, law, and document-centric settings further demonstrate the generality of these benefits. Persistent challenges including multi-hop reasoning, knowledge conflict resolution, corpus freshness, domain adaptation, adversarial robustness, and the dynamic scheduling of retrieval define the frontier of current research. As LLMs continue to permeate consequential real-world applications, the development of robust, scalable, and trustworthy RAG architectures will be essential for ensuring that model outputs can be relied upon as factually grounded and verifiable.

References

[1] Brown, T., Mann, B., Ryder, N., Subbiah, M., Kaplan, J. D., Dhariwal, P., ... & Amodei, D. (2020). Language models are few-shot learners. Advances in neural information processing systems, 33, 1877-1901.

[2] Huang, L., Yu, W., Ma, W., Zhong, W., Feng, Z., Wang, H., ... & Liu, T. (2025). A survey on hallucination in large language models: Principles, taxonomy, challenges, and open questions. ACM Transactions on Information Systems, 43(2), 1-55.

[3] Lewis, P., Perez, E., Piktus, A., Petroni, F., Karpukhin, V., Goyal, N., ... & Kiela, D. (2020). Retrieval-augmented generation for knowledge-intensive nlp tasks. Advances in neural information processing systems, 33, 9459-9474.

[4] Petroni, F., Piktus, A., Fan, A., Lewis, P., Yazdani, M., De Cao, N., ... & Riedel, S. (2021, June). KILT: a benchmark for knowledge intensive language tasks. In Proceedings of the 2021 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies (pp. 2523-2544).

[5] Kandpal, N., Deng, H., Roberts, A., Wallace, E., & Raffel, C. (2023, July). Large language models struggle to learn long-tail knowledge. In International conference on machine learning (pp. 15696-15707). PMLR.

[6] Long, M., Sun, D., Yang, D., Wang, J., Luo, Y., Shen, Y., ... & Gu, J. (2025). Diver: A multi-stage approach for reasoning-intensive information retrieval. arXiv preprint arXiv:2508.07995.

[7] Maynez, J., Narayan, S., Bohnet, B., & McDonald, R. (2020, July). On faithfulness and factuality in abstractive summarization. In Proceedings of the 58th annual meeting of the association for computational linguistics (pp. 1906-1919).

[8] Shuster, K., Poff, S., Chen, M., Kiela, D., & Weston, J. (2021, November). Retrieval augmentation reduces hallucination in conversation. In Findings of the Association for Computational Linguistics: EMNLP 2021 (pp. 3784-3803).

[9] Ji, Z., Lee, N., Frieske, R., Yu, T., Su, D., Xu, Y., ... & Fung, P. (2023). Survey of hallucination in natural language generation. ACM computing surveys, 55(12), 1-38.

[10] Tay, Y., Dehghani, M., Bahri, D., & Metzler, D. (2022). Efficient transformers: A survey. ACM Computing Surveys, 55(6), 1-28.

[11] Devlin, J., Chang, M. W., Lee, K., & Toutanova, K. (2019, June). Bert: Pre-training of deep bidirectional transformers for language understanding. In Proceedings of the 2019 conference of the North American chapter of the association for computational linguistics: human language technologies, volume 1 (long and short papers) (pp. 4171-4186).

[12] Sachan, D. S., Lewis, M., Yogatama, D., Zettlemoyer, L., Pineau, J., & Zaheer, M. (2023). Questions are all you need to

train a dense passage retriever. Transactions of the Association for Computational Linguistics, 11, 600-616.

[13] Izacard, G., & Grave, E. (2021, April). Leveraging passage retrieval with generative models for open domain question answering. In Proceedings of the 16th conference of the european chapter of the association for computational linguistics: main volume (pp. 874-880).

[14] Mallen, A., Asai, A., Zhong, V., Das, R., Khashabi, D., & Hajishirzi, H. (2023, July). When not to trust language models: Investigating effectiveness of parametric and non-parametric memories. In Proceedings of the 61st annual meeting of the association for computational linguistics (volume 1: Long papers) (pp. 9802-9822).

[15] Shi, F., Chen, X., Misra, K., Scales, N., Dohan, D., Chi, E. H., ... & Zhou, D. (2023, July). Large language models can be easily distracted by irrelevant context. In International Conference on Machine Learning (pp. 31210-31227). PMLR.

[16] Karpukhin, V., Oguz, B., Min, S., Lewis, P., Wu, L., Edunov, S., ... & Yih, W. T. (2020, November). Dense passage retrieval for open-domain question answering. In Proceedings of the 2020 conference on empirical methods in natural language processing (EMNLP) (pp. 6769-6781).

[17] Guu, K., Lee, K., Tung, Z., Pasupat, P., & Chang, M. (2020, November). Retrieval augmented language model pre-training. In International conference on machine learning (pp. 3929-3938). PMLR.

[18] Borgeaud, S., Mensch, A., Hoffmann, J., Cai, T., Rutherford, E., Millican, K., ... & Sifre, L. (2022, June). Improving language models by retrieving from trillions of tokens. In International conference on machine learning (pp. 2206-2240). PMLR.

[19] Jiang, Z., Xu, F. F., Gao, L., Sun, Z., Liu, Q., Dwivedi-Yu, J., ... & Neubig, G. (2023, December). Active retrieval augmented generation. In Proceedings of the 2023 conference on empirical methods in natural language processing (pp. 7969-7992).

[20] Asai, A., Wu, Z., Wang, Y., Sil, A., & Hajishirzi, H. (2023, October). Self-rag: Learning to retrieve, generate, and critique through self-reflection. In The Twelfth International Conference on Learning Representations.

[21] Ahmad, M. (2025). Toward a Unified Framework for Information Retrieval in Large Language Model Applications: Balancing Textual and Graph-Based Knowledge Sources.

[22] Xie, J., Zhang, K., Chen, J., Lou, R., & Su, Y. (2023, May). Adaptive chameleon or stubborn sloth: Revealing the behavior of large language models in knowledge conflicts. In The Twelfth International Conference on Learning Representations.

[23] Wang, K., Duan, F., Wang, S., Li, P., Xian, Y., Yin, C., ... & Xiong, Z. (2023). Knowledge-driven cot: Exploring faithful reasoning in llms for knowledge-intensive question answering. arXiv preprint arXiv:2308.13259.

[24] Singhal, K., Azizi, S., Tu, T., Mahdavi, S. S., Wei, J., Chung, H. W., ... & Natarajan, V. (2023). Large language models encode clinical knowledge. Nature, 620(7972), 172-180.

[25] Niklaus, J., Matoshi, V., Rani, P., Galassi, A., Stürmer, M., & Chalkidis, I. (2023, December). Lextreme: A multi-lingual and multi-task benchmark for the legal domain. In Findings of the Association for Computational Linguistics: EMNLP 2023 (pp. 3016-3054).

[26] Nakano, R., Hilton, J., Balaji, S., Wu, J., Ouyang, L., Kim, C., ... & Schulman, J. (2021). Webgpt: Browser-assisted question-answering with human feedback. arXiv preprint arXiv:2112.09332.

[27] Menick, J., Trebacz, M., Mikulik, V., Aslanides, J., Song, F., Chadwick, M., ... & McAleese, N. (2022). Teaching language models to support answers with verified quotes. arXiv preprint arXiv:2203.11147.

[28] Augenstein, I., Baldwin, T., Cha, M., Chakraborty, T., Ciampaglia, G. L., Corney, D., ... & Zagni, G. (2024). Factuality challenges in the era of large language models and opportunities for fact-checking. Nature Machine Intelligence, 6(8), 852-863.

[29] Min, S., Krishna, K., Lyu, X., Lewis, M., Yih, W. T., Koh, P., ... & Hajishirzi, H. (2023, December). Factscore: Fine-grained atomic evaluation of factual precision in long form text generation. In Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing (pp. 12076-12100).

[30] Gao, Y., Xiong, Y., Gao, X., Jia, K., Pan, J., Bi, Y., ... & Wang, H. (2023). Retrieval-augmented generation for large language models: A survey. arXiv preprint arXiv:2312.10997, 2(1), 32.

[31] Asai, A., Min, S., Zhong, Z., & Chen, D. (2023, July). Retrieval-based language models and applications. In Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 6: Tutorial Abstracts) (pp. 41-46).

[32] Thakur, N., Reimers, N., Rücklé, A., Srivastava, A., & Gurevych, I. (2021). Beir: A heterogenous benchmark for zero-shot evaluation of information retrieval models. arXiv preprint arXiv:2104.08663.

[33] Shang, W., Wang, Z., & Wang, B. (2025). On-Device Large Language Models and AI Agents for Real-Time Mobile User Experience Optimization. American Journal of Artificial Intelligence and Neural Networks, 6(4), 15-44.

[34] Huang, Z., Zeng, H., Zamani, H., & Allan, J. (2023, July). Soft prompt decoding for multilingual dense retrieval. In Proceedings of the 46th international ACM SIGIR conference on research and development in information retrieval (pp. 1208-1218).

[35] Mao, Y., He, P., Liu, X., Shen, Y., Gao, J., Han, J., & Chen, W. (2021, August). Generation-augmented retrieval for open-domain question answering. In Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 1: Long Papers) (pp. 4089-4100).

[36] Wang, L., Yang, N., & Wei, F. (2023, December). Query2doc: Query expansion with large language models. In Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing (pp. 9414-9423).

[37] Gao, L., Ma, X., Lin, J., & Callan, J. (2023, July). Precise zero-shot dense retrieval without relevance labels. In Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers) (pp. 1762-1777).

[38] Lin, Jimmy, Rodrigo Nogueira, and Andrew Yates. Pretrained transformers for text ranking: Bert and beyond. Springer Nature, 2022.

[39] Nogueira, R., Yang, W., Cho, K., & Lin, J. (2019). Multi-stage document ranking with BERT. arXiv preprint arXiv:1910.14424.

[40] Beheshti, A., Hashemi, V. M., & Yakhchi, S. (2019, December). Towards context-aware social behavioral analytics. In Proceedings of the 17th International Conference on Advances in Mobile Computing & Multimedia (pp. 28-35).

[41] Yin, P., Neubig, G., Yih, W. T., & Riedel, S. (2020, July). TaBERT: Pretraining for joint understanding of textual and tabular data. In Proceedings of the 58th annual meeting of the association for computational linguistics (pp. 8413-8426).

[42] Zhao, R., Li, X., Joty, S., Qin, C., & Bing, L. (2023, July). Verify-and-edit: A knowledge-enhanced chain-of-thought framework. In Proceedings of the 61st Annual Meeting of the

Association for Computational Linguistics (Volume 1: Long Papers) (pp. 5823-5840).

[43] Ho, X., Nguyen, A. K. D., Sugawara, S., & Aizawa, A. (2020, December). Constructing a multi-hop qa dataset for comprehensive evaluation of reasoning steps. In Proceedings of the 28th International Conference on Computational Linguistics (pp. 6609-6625).

[44] Trivedi, H., Balasubramanian, N., Khot, T., & Sabharwal, A. (2023, July). Interleaving retrieval with chain-of-thought reasoning for knowledge-intensive multi-step questions. In Proceedings of the 61st annual meeting of the association for computational linguistics (volume 1: long papers) (pp. 10014-10037).

[45] Chen, J., Lin, H., Han, X., & Sun, L. (2024, March). Benchmarking large language models in retrieval-augmented generation. In Proceedings of the AAAI Conference on Artificial Intelligence (Vol. 38, No. 16, pp. 17754-17762)..

[46] Zhang, Y., Li, Y., Cui, L., Cai, D., Liu, L., Fu, T., ... & Shi, S. (2025). Siren's Song in the AI Ocean: A Survey on Hallucination in Large Language Models. Computational Linguistics, 51(4), 1373-1418.

[47] Kadavath, S., Conerly, T., Askell, A., Henighan, T., Drain, D., Perez, E., ... & Kaplan, J. (2022). Language models (mostly) know what they know. arXiv preprint arXiv:2207.05221.

[48] Siriwardhana, S., Weerasekera, R., Wen, E., Kaluarachchi, T., Rana, R., & Nanayakkara, S. (2023). Improving the domain adaptation of retrieval augmented generation (RAG) models for open domain question answering. Transactions of the Association for Computational Linguistics, 11, 1-17.

[49] Shi, W., Min, S., Lomeli, M., Zhou, C., Li, M., Szilvasy, G., ... & Lewis, M. (2023). In-context pretraining: Language modeling beyond document boundaries. arXiv preprint arXiv:2310.10638.

[50] Zou, A., Phan, L., Chen, S., Campbell, J., Guo, P., Ren, R., ... & Hendrycks, D. (2023). Representation engineering: A top-down approach to ai transparency. arXiv preprint arXiv:2310.01405.

[51] Greshake, K., Abdelnabi, S., Mishra, S., Endres, C., Holz, T., & Fritz, M. (2023, November). Not what you've signed up for: Compromising real-world llm-integrated applications with indirect prompt injection. In Proceedings of the 16th ACM workshop on artificial intelligence and security (pp. 79-90).

[52] Li, Z., Guo, Q., Shao, J., Song, L., Bian, J., Zhang, J., & Wang, R. (2024). Graph neural network enhanced retrieval for question answering of llms. arXiv preprint arXiv:2406.06572.

[53] Pan, S., Luo, L., Wang, Y., Chen, C., Wang, J., & Wu, X. (2024). Unifying large language models and knowledge graphs: A roadmap. IEEE Transactions on Knowledge and Data Engineering, 36(7), 3580-3599.

[54] Panagopoulou, A., Xue, L., Yu, N., Li, J., Li, D., Joty, S., ... & Niebles, J. C. (2023). X-instructblip: A framework for aligning x-modal instruction-aware representations to llms and emergent cross-modal reasoning. arXiv preprint arXiv:2311.18799.

[55] Shi, W., Min, S., Yasunaga, M., Seo, M., James, R., Lewis, M., ... & Yih, W. T. (2024, June). Replug: Retrieval-augmented black-box language models. In Proceedings of the 2024 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers) (pp. 8371-8384).

[56] Ren, R., Wang, Y., Qu, Y., Zhao, W. X., Liu, J., Wu, H., ... & Wang, H. (2025, January). Investigating the factual knowledge boundary of large language models with retrieval augmentation. In Proceedings of the 31st International Conference on Computational Linguistics (pp. 3697-3715).

[57] Chen, L., Deng, Y., Bian, Y., Qin, Z., Wu, B., Chua, T. S., & Wong, K. F. (2023, December). Beyond factuality: A comprehensive evaluation of large language models as knowledge generators. In Proceedings of the 2023 conference on empirical methods in natural language processing (pp. 6325-6341).

[58] Ding, G., Yang, S., Lin, H., Chen, Z., & Yang, J. S. (2026). LLM-Driven Adaptive Cloud Resource Scheduling: Bridging Reasoning Intelligence with Optimization Guarantees. IEEE Open Journal of the Computer Society.

[59] Su, W., Tang, Y., Ai, Q., Wu, Z., & Liu, Y. (2024, August). Dragin: Dynamic retrieval augmented generation based on the real-time information needs of large language models. In Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers) (pp. 12991-13013).

[60] Yu, W., Zhang, Z., Liang, Z., Jiang, M., & Sabharwal, A. (2023). Improving language models via plug-and-play retrieval feedback. arXiv preprint arXiv:2305.14002.

[61] Lin, D. (2024). Revolutionizing retrieval-augmented generation with enhanced PDF structure recognition. arXiv preprint arXiv:2401.12599.

[62] Cuconasu, F., Trappolini, G., Siciliano, F., Filice, S., Campagnano, C., Maarek, Y., ... & Silvestri, F. (2024, July). The power of noise: Redefining retrieval for rag systems. In Proceedings of the 47th International ACM SIGIR Conference on Research and Development in Information Retrieval (pp. 719-729).

[63] Wang, X., Wang, Z., Gao, X., Zhang, F., Wu, Y., Xu, Z., ... & Huang, X. J. (2024, November). Searching for best practices in retrieval-augmented generation. In Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing (pp. 17716-17736).

[64] Zhang, N., Yao, Y., Tian, B., Wang, P., Deng, S., Wang, M., ... & Chen, H. (2024). A comprehensive study of knowledge editing for large language models. arXiv preprint arXiv:2401.01286.

[65] Huang, Y., & Huang, J. (2024). A survey on retrieval-augmented text generation for large language models. arXiv preprint arXiv:2404.10981.

[66] Shao, Z., Gong, Y., Shen, Y., Huang, M., Duan, N., & Chen, W. (2023, December). Enhancing retrieval-augmented large language models with iterative retrieval-generation synergy. In Findings of the Association for Computational Linguistics: EMNLP 2023 (pp. 9248-9274).