


# SQL Project On PizzaHut Sales







# Hello!

*Analyzing PizzaHut Sales with SQL Queries*


*Presented by: Anchal Saini*




*Introduction: I am Anchal Saini, a recent MSc Computer Science graduate with a strong background in data analysis and technological proficiency. My expertise spans cloud computing, data analysis, and developing AI models, particularly in fraud detection systems.*





**Project Overview:** In this project, I applied my SQL expertise to analyze PizzaHut sales data. By formulating and executing precise SQL queries, I was able to address various business questions and extract meaningful insights. The focus was on identifying sales trends, customer behavior, and key performance metrics. This analytical approach provided a deeper understanding of the sales dynamics at PizzaHut, facilitating data-driven decision-making.







# Questions

## Basic:

- Retrieve the total number of orders placed.
- Calculate the total revenue generated from pizza sales.
- Identify the highest-priced pizza.
- Identify the most common pizza size ordered.
- List the top 5 most ordered pizza types along with their quantities.

## Intermediate:

- Join the necessary tables to find the total quantity of each pizza category ordered.
- Determine the distribution of orders by hour of the day.
- Join relevant tables to find the category-wise distribution of pizzas.
- Group the orders by date and calculate the average number of pizzas ordered per day.
- Determine the top 3 most ordered pizza types based on revenue.

## Advanced:

- Calculate the percentage contribution of each pizza type to total revenue.
- Analyze the cumulative revenue generated over time.
- Determine the top 3 most ordered pizza types based on revenue for each pizza category.





# Retrieve the total number of orders placed.

```
SELECT  
    COUNT(order_id) AS total_orders  
FROM  
    orders;
```

	total_orders
▶	21350





# Calculate the total revenue generated from pizza sales.

```
SELECT
    ROUND(SUM(order_details.quantity * pizzas.price),
          2) AS total_Revenue
FROM
    order_details
    JOIN
    pizzas ON pizzas.pizza_id = order_details.pizza_id
```

	total_Revenue
▶	817860.05



# Identify the highest-priced pizza.



```
SELECT
    pizza_types.name, pizzas.price
FROM
    pizza_types
    JOIN
        pizzas ON pizza_types.pizza_type_id = pizzas.pizza_type_id
ORDER BY pizzas.price DESC
LIMIT 1;
```

	name	price
▶	The Greek Pizza	35.95







# Identify the most common pizza size ordered.

```
SELECT
    pizzas.size, COUNT(order_details.order_details_id)
FROM
    pizzas
    JOIN
        order_details ON pizzas.pizza_id = order_details.pizza_id
GROUP BY pizzas.size;
```

	size	COUNT(order_details.order_details_id)
▶	M	15385
	L	18526
	S	14137
	XL	544
	XXL	28





# List the top 5 most ordered pizza types along with their quantities.

```
SELECT
    pizza_types.name, SUM(order_details.quantity) AS quantity
FROM
    pizza_types
    JOIN
    pizzas ON pizza_types.pizza_type_id = pizzas.pizza_type_id
    JOIN
    order_details ON order_details.pizza_id = pizzas.pizza_id
GROUP BY pizza_types.name
ORDER BY quantity DESC
LIMIT 5;
```

	name	quantity
►	The Classic Deluxe Pizza	2453
	The Barbecue Chicken Pizza	2432
	The Hawaiian Pizza	2422
	The Pepperoni Pizza	2418
	The Thai Chicken Pizza	2371

# Join the necessary tables to find the total quantity of each pizza category ordered.

```
SELECT
    pizza_types.category,
    SUM(order_details.quantity) AS quantity
FROM
    pizza_types
    JOIN
    pizzas ON pizza_types.pizza_type_id = pizzas.pizza_type_id
    JOIN
    order_details ON order_details.pizza_id = pizzas.pizza_id
GROUP BY pizza_types.category
ORDER BY quantity DESC;
```

	category	quantity
▶	Classic	14888
	Supreme	11987
	Veggie	11649
	Chicken	11050

# Determine the distribution of orders by hour of the day.

```
SELECT
    HOUR(order_time) AS hour, COUNT(order_id) AS order_count
FROM
    orders
GROUP BY HOUR(order_time);
```

	hour	order_count
▶	11	1231
	12	2520
	13	2455
	14	1472
	15	1468
	16	1920
	17	2336
	18	2399
	19	2009

**Join relevant tables to find the category-wise distribution of pizzas.**

```
select category, count(name) from pizza_types  
group by category
```

	category	count(name)
▶	Chicken	6
	Classic	8
	Supreme	9
	Veggie	9

**Group the orders by date and calculate the average number of pizzas ordered per day.**

```
SELECT
    ROUND(AVG(quantity), 0) as avg_pizza_order_per_day
FROM
    (SELECT
        orders.order_date, SUM(order_details.quantity) AS quantity
    FROM
        orders
    JOIN order_details ON orders.order_id = order_details.order_id
    GROUP BY orders.order_date) AS order_quantity;
```

	avg_pizza_order_per_day
▶	138

# Determine the top 3 most ordered pizza types based on revenue.

```
SELECT
    pizza_types.name,
    SUM(order_details.quantity * pizzas.price) AS revenue
FROM
    pizza_types
    JOIN
    pizzas ON pizzas.pizza_type_id = pizza_types.pizza_type_id
    JOIN
    order_details ON order_details.pizza_id = pizzas.pizza_id
GROUP BY pizza_types.name
```

	name	revenue
►	The Thai Chicken Pizza	43434.25
	The Barbecue Chicken Pizza	42768
	The California Chicken Pizza	41409.5

# Calculate the percentage contribution of each pizza type to total revenue.

```
-- pizza type to total revenue
SELECT
  pizza_types.category,
  ROUND((SUM(order_details.quantity * pizzas.price) / (SELECT
    ROUND(SUM(order_details.quantity * pizzas.price),
    2) AS total_sales
  FROM
    order_details
    JOIN
    pizzas ON pizzas.pizza_id = order_details.pizza_id)) * 100,
  2) AS revenue
FROM
  pizza_types
  JOIN
  pizzas ON pizzas.pizza_type_id = pizza_types.pizza_type_id
  JOIN
  order_details ON order_details.pizza_id = pizzas.pizza_id
GROUP BY pizza_types.category
ORDER BY revenue DESC;
```

	category	revenue
►	Classic	26.91
	Supreme	25.46
	Chicken	23.96
	Veggie	23.68



# Analyze the cumulative revenue generated over time.



```
select order_date,  
sum(revenue) over(order by order_date) as cum_revenue  
from  
(select orders.order_date,  
sum(order_details.quantity * pizzas.price) as revenue  
from order_details join pizzas  
on order_details.pizza_id = pizzas.pizza_id  
join orders  
on orders.order_id = order_details.order_id  
group by orders.order_date) as sales;
```

	order_date	cum_revenue
▶	2015-01-01	2713.8500000000004
	2015-01-02	5445.75
	2015-01-03	8108.15
	2015-01-04	9863.6
	2015-01-05	11929.55
	2015-01-06	14358.5
	2015-01-07	16560.7
	2015-01-08	19399.05
	2015-01-09	21526.4



# Determine the top 3 most ordered pizza types based on revenue for each pizza category.



```
select
name, revenue from
(select category, name, revenue,
rank() over(partition by category order by revenue desc) as rn
from
(select pizza_types.category, pizza_types.name,
sum((order_details.quantity) * pizzas.price) as revenue
from pizza_types join pizzas
on pizza_types.pizza_type_id = pizzas.pizza_type_id
join order_details
on order_details.pizza_id = pizzas.pizza_id
group by pizza_types.category, pizza_types.name) as a) as b
where rn <= 3;
```

	name	revenue
►	The Thai Chicken Pizza	43434.25
	The Barbecue Chicken Pizza	42768
	The California Chicken Pizza	41409.5
	The Classic Deluxe Pizza	38180.5
	The Hawaiian Pizza	32273.25
	The Pepperoni Pizza	30161.75
	The Spicy Italian Pizza	34831.25
	The Italian Supreme Pizza	33476.75
	The Sicilian Pizza	30940.5



**Thankyou**  
**Like**

