

Key-Value Stores

Sometimes rDBs are too cumbersome ~~in~~ ~~when~~ weighed against the services they offer. Also, they impose a tabular struc. on data viz not reqd. everytime. In those cases, we use non-rDBs for more flexibility and ease.

Key-Value store → i) A popular non-rDB (i.e. nosql)
 ii) Data stored as k-v pairs
 iii) Allows mapping of keys (~~strings~~ usually strings) to ~~values~~ arbitrary values.

eg 1:

<u>Key</u>	<u>Value</u>
foo	-48.8
bleh	Apple Pie
whut	[x, y, z]

eg 2: hashTables

k-v store

- flexible → not rigorous as no imposed struc.
- simple → nothing simpler to store data compared to a k-v map.
- fast

Use:

i) Caching : Values → Responses to network reqs.
 Keys → Hash, IP address, username

Date: _____
M T W T F S S

2) Dynamic config: Basically just storing a parameter that diff. parts of your sys. rely on in a separate place so all these parts can access it

eg:- using config when you wanna switch what code you wanna run dependin on what envmt. you're in \rightarrow (development, prod, testing)

Here, this param. is stored in a k-v store (usually an obj. in .json or .yaml file) ~~and~~ as workin with diff. values of this same param (key) is a lot easier

NOTE: Advantage of using a k-v store \rightarrow \because values are accessed directly thru keys, no search thru db or any other fancy lookup reqd.

\therefore Latency \downarrow , Throughput \uparrow of our sys.

eg:- DynamoDB, Redis, Etcd, Zookeeper

NOTE: ~~Storage~~ 2 types of k-v stores based on where they write their data to:

i) Write data to disc \rightarrow a) How to get back data from disc
b) Data persists even after k-v store server itself crashes

ii) Write data to mem \rightarrow a) Faster to retrieve data from mem
b) Data lost if k-v store server crashes

Use: - Caching \rightarrow As honestly, it doesn't affect the sys much if caches crash but we do want readin from cache = fast

Page.

Page.

- Page.

```
server.js — key_value_stores

JS server.js x JS database.js

JS server.js > app.get('/nocache/index.html') callback
1  const database = require('./database');
2  const express = require('express');
3  const redis = require('redis').createClient();
4
5  const app = express();
6
7  app.get('/nocache/index.html', (req, res) => {
8    database.get('index.html', page => {
9      res.send(page);
10    });
11  });
12
13  app.get('/withcache/index.html', (req, res) => {
14    redis.get('index.html', (err, redisRes) => {
15      if (redisRes) {
16        res.send(redisRes);
17        return;
18      }
19
20      database.get('index.html', page => {
21        redis.set('index.html', page, 'EX', 10);
22        res.send(page);
23      });
24    });
25  });
26
27  app.listen(3001, function() {
28    console.log('Listening on port 3001!');
29  });
```

