

PROXIES


PROXY:

Just a machine-server set up to hide the IP address and other details of an interacting machine (eg:- client, server, etc.)

- 2 types (primary) :-
- Forward proxy (usually ref-ed to as - 'proxy')
 - Reverse proxy

Forward Proxy (F.P.) and Reverse Proxy (R.P.)

- 1] Forward Proxy (F.P.) → on client's team
- It is a server located b/w client/set of clients & server/set of servers
 - It acts on behalf of clients/set of clients by hiding clients IP address from server and instead supplying its own IP address.
 - When a client sends a req. to the server and this ~~req~~ F.P. has been properly configured by client, the req. goes as



communicates on behalf of C

server has no idea abt the client and that an F.P. exists
doesn't get req. directly from C. It gets it from F.P.


- F.P. serves as a way to hide the identity of client ~~from~~ in req. from server by changing source IP address sent in req. to its own IP address (i.e. IPA) instead of client's IPA eg:- VPN &

v) Some types of ~~proxies~~ F.P.s make client ~~IP~~ visit to server in some way, but, typically original source IP is replaced


NOTE: VPN → a fund proxy b/w client and server that hides the client's identity
∴ client can access servers restricted to it.
Thus, client can, for eg, access a website not avail. in his/her country but avail. in other.

2] Reverse Proxy (R.P.) → on server's team.

- i) A server b/w client / set of clients and server / set of servers
- ii) When a client interacts with a server. eg:-
sendin a req.



eg:- say google.com sets up an R.P.



LINK TO CODE EXAMPLE OF PROXIES

Date:

M T W T F S S

Use of R.P.s → Powerful tool for sys. des.

- 1) eg: - Config. R.P. to filter out reqs. you want your sys to ignore
- 2) eg: - Log stuff, gather metrics → can be done by R.P.
- 3) eg 3: - R.P. can also cache stuff (eg: - HTML pages) thus, server doesn't get bothered a lot
- 4) eg 4: - As a load balancer → a server that can distri req. load amongst a bunch of servers

NOTE : 1] ~~Malicious~~ Malicious client → sends a fuckload of reqs. to a server to bring it down.

Now R.P. acting as load balancer will distri these req.s across all servers, thereby safeguarding sys. from malicious clients, viruses etc.

2] NginX is a popular web server that can be used as an R.P.

eg: - Code on app page:

- 1) We set up an R.P. for any req. coming to port 8081 of our web service
- 2) Each time a req. is directed to the endpoint = `/` at port 8081, the req. header on the req. ~~known~~ as `'systemexpert-tutorial'` and set it to `'true'`
- 3) Then we gonna fwd this req. to the server that pts. to localhost:3000 (its name is `models-backend`)

nginx.conf — proxies

nginx.conf x JS server.js

nginx.conf

```
1  events { }
2
3  http {
4      upstream nodejs-backend {
5          server localhost:3000;
6      }
7
8      server {
9          listen 8081;
10
11         location / {
12             proxy_set_header systemexpert-tutorial true;
13             proxy_pass http://nodejs-backend;
14         }
15     }
16 }
```

nginx.conf JS server.js x

JS server.js > app.get('/hello') callback

```
1  const express = require('express');
2  const app = express();
3
4  app.listen(3000, () => console.log('Listening on port 3000.'));
5
6  app.get('/hello', (req, res) => {
7      console.log(req.headers);
8      res.send('Hello.\n');
9  });
```

Ln 9, Col 18 (4 selected) Spaces: 3 UTF-8 LF Properties

proxies — node server.js — 93x23

~/Documents/Content/Design_Fundamentals/Examples/proxies — node server.js

```
Clements-MBP:proxies clementmihailescu$ node server.js
Listening on port 3000.
```

proxies — -bash — 93x24

~/Documents/Content/Design_Fundamentals/Examples/proxies — -bash

```
Clements-MBP:proxies clementmihailescu$ curl localhost:3000/hello
```

algoexpert.io