

## EL2450 HOMEWORK 2

Andreas Fröderberg - 19880730-7577  
Martin Favre - 19920130-0010

# 1 Rate Monotonic scheduling

**Task 1: Explain what Rate Monotonic scheduling means.**

In Rate Monotonic scheduling, each task is given a fixed priority based on its task rate, shorter task rate equals higher priority. The task with the highest priority is then run at all times.

**Task 2: Are the three tasks schedulable?**

Calculating the utilization factor  $U$  from

$$U = \sum_{i=1}^n \frac{C_i}{T_i} = \frac{6}{20} + \frac{6}{29} + \frac{6}{35} = 0.68 \quad (1)$$

To be schedulable, the condition

$$U \leq n(2^{\frac{1}{n}} - 1), \quad (2)$$

where  $n$  is the number of processes. Calculating for this example with 3 tasks, the condition becomes

$$0.68 \leq 3(2^{\frac{1}{3}} - 1) = 0.78 \quad (3)$$

which holds, therefore the taskset is schedulable with RM scheduling.

**Task 3: What are the differences in control performance between the different pendulums?**

All pendulums are asymptotically stable and have similar control performance. The performance is shown in Figure 1.




Figure 1: Performance of pendulums under rate monotonic scheduling.

**Task 4: Compare against the schedule in the model. Does it match?**

In Figure 2, the execution of tasks in Matlab is shown.




Figure 2: Schedule for pendulums when computation time of all is 6 ms. Yellow is small pendulum, blue is medium and red is big.

In the figure below, Figure 3, the execution order as calculated by hand is shown. It can be seen that the schedules both are consistent.




Figure 3: Hand drawn and calculated execution order with Rate Monotonic scheduling. Task  $J_1$  represents the small pendulum and rising index represents bigger pendulums.

**Task 5: Setting the execution time for all three processes to 10ms, what are the differences with respect to control performance?**  
For this execution time, the CPU utilization factor becomes

$$U = \sum_{i=1}^n \frac{C_i}{T_i} = \frac{10}{20} + \frac{10}{29} + \frac{10}{35} = 1.1. \quad (4)$$

The utilization factor is thus larger than Equation 3 which means that the processes is not schedulable. This is seen in Figure 4 where the small pendulum is no longer stable because of the fact that the deadlines are missed.




Figure 4: Performance of pendulums under rate monotonic scheduling with computation time 10 ms for each task.

The schedule in the simulations is shown in Figure 5.




Figure 5: Schedule for Rate Monotonic scheduling when computation time is 10 ms

When viewing the hand-drawn and the real schedule, the following are shown.




Figure 6: Schedule when computation time is 10 ms. Task  $J_1$  is smallest pendulum, higher index represents larger pendulum.

## 2 Earliest Deadline First, EDF

**Task 1: Explain how EDF works. What are the advantages and disadvantages of the approach compared to RM?**

In EDF, the task that has the closest deadline to the current time is always run. The advantage of this is that the processor can be fully utilized if the the scheme is schedulable. Another advantage is that tasks will not get starved if the processor is overloaded and deadlines are missed since the dynamic prioritization will handle allow all tasks to get processing time. One disadvantage is that tasks can not be given predefined priorities which might be important depending on the implementation.

**Task 2: Assume the execition time is changed back to 6 ms. Are the tasks schedulable with the EDF? Please motivate your answer and costruct part of the corresponding schedule manually.**

EDF is schedulable as long as CPU utilization is lower than 100 %. The utilization factor is the same as the answer q2 from RM, 0.68. Since  $U = 0.68 \leq 1$  holds, the task set is schedulable with EDF. The hand calculated schedule is shown below in Figure 7.




Figure 7: Schdule for EDF with 6 ms calculation time. Task  $J_1$  represents the smallest pendulum, higher index represents larger pendulums.

**Task 3: Using EDF - what are the differences in control performance between the different pendulums?**

All pendulums are asymptotically stable and have similar control performance. The performance is shown in Figure 1.




Figure 8: Performance of pendulums under earliest deadline first scheduling with computation time 6 ms for each task.

**Task 4: Compare against the schedule in the model. Does it match?**

The schedule in the model is shown in Figure 9.




Figure 9: Performance of pendulums under earliest deadline first scheduling with computation time 6 ms for each task.

It is consistent with the schedule presented in task 2.

**Task 5: Setting the execution time for all three processes to 10ms, what are the differences with respect to control performance?**

For this execution time, the CPU utilization factor becomes

$$U = \sum_{i=1}^n \frac{C_i}{T_i} = \frac{10}{20} + \frac{10}{29} + \frac{10}{35} = 1.1. \quad (5)$$

The utilization factor is thus larger than one which means that the processes is not schedulable.

However looking at Figure 10 the system is still stable although with deteriorated control performance for all three pendulums. This is a result of the disability to meet all the deadlines but still meeting enough for the system to stabilize.




Figure 10: Performance of pendulums under earliest deadline first scheduling with computation time 10 ms for each task.

**Task 6: Does the controllers perform better with EDF compared to RM-scheduling?**

Comparing the systems with 6 ms execution time in Figure 1 and Figure 8 little difference can be seen. However with execution time of 10 ms in Figure 4 and Figure 10 the control performance is much better with EDF-scheduling.

A relation can be drawn with the different utilization factors of EDF and RM, where RM is limited to a factor of 0.68 from Q2 whilst EDF can handle 1.0 and is therefore better.

### 3 Networked Control Systems

**Task 1: Do analytical calculations of the closed-loop equations.**

With

$$\dot{x}(t) = Iu(t) \quad (6)$$

$$y(t) = Cx(t) \quad (7)$$

and

$$u(kh) = -Kx(kh). \quad (8)$$

Sampling the system with a period h gives:

$$\Phi = e^{Ah} \quad (9)$$



$$\Gamma_0(\tau_A) = I \int_0^{h-\tau_k} ds = (h - \tau_k)I \quad (10)$$

$$\Gamma_1(\tau_A) = I \int_{h-\tau_k}^h ds = -\tau_k I \quad (11)$$

Defining  $z(kh) = [x^T(kh), u^T((k-1)h)]^T$  as the augmented state vector, the augmented closed-loop system is

$$z((k+1)h) = \tilde{\phi}(k)z(kh) \quad (12)$$

where

$$\tilde{\phi}(k) = \begin{bmatrix} \Phi - \Gamma_0(\tau_k)K & \Gamma_1(\tau_k) \\ -K & 0 \end{bmatrix} = \begin{bmatrix} 1 - (h - \tau_A)I & -\tau_A I \\ -K & 0 \end{bmatrix}. \quad (13)$$

Which results in:

$$z((k+1)h) = \begin{bmatrix} 1 - (h - \tau_A)I & -\tau_A I \\ -K & 0 \end{bmatrix} z(kh). \quad (14)$$

**Task 2: Calculate stuff**

Present stuff

**Task 3: Construct and draw the DES that models  $M_1$ ,  $M_2$  and**

$B$

Easy

**Task 4: Construct and draw the DES that models  $M_1$ ,  $M_2$  and**

$B$

Easy