

Shiny for Python: : CHEAT SHEET




Build an App

A **Shiny** app is an interactive web page (**ui**) powered by a live Python session run by a **server** or a browser (with Shinylive).



Users can manipulate the UI, which will cause the server to update the UI's displays (by running Python code).

Save your app as **app.py** in a directory with the files it uses.



Share

Share your app in three ways:

1. **Host it on shinyapps.io**, a cloud based service from Posit. To deploy Shiny apps:

- Create a free or professional account at **shinyapps.io**
- Use the **reconnect-python** package to publish with **reconnect deploy shiny** `<path to directory>`

2. **Purchase Posit Connect**, a publishing platform for R and Python.

posit.co/connect


3. **Use open source deployment options**

shiny.posit.co/py/docs/deploy.html



Shinylive

Shinylive apps run entirely in a browser, without the need for a separate server to run Python.



Edit and/or host Shinylive apps at shinylive.io

Create a Shinylive version of an app to deploy with **shinylive export myapp site**

Embed Shinylive apps in Quarto sites, blogs, etc.

```
---
filters:
- shinylive
---
An embedded Shinylive app:
```{shinylive-python}
#| standalone: true
[App.py code here...]
```
```

To embed a Shinylive app in a Quarto doc, include the bold syntax.

Nest Python functions to build an HTML interface

Add Inputs with **ui.input_***() functions

Add Outputs with **ui.output_***() functions

Designate output functions with the **@output** decorator

Save each output as a function that can generate the output

Call the values of UI inputs with **input.<id>()**

Run **shiny create .** in the terminal to generate a template **app.py** file

```
from shiny import App, render, ui
import matplotlib.pyplot as plt
import numpy as np
```

```
app_ui = ui.page_fluid(
  ui.input_slider(
    "n", "Sample Size", 0, 1000, 20
  ),
  ui.output_plot("dist")
)

def server(input, output, session):
```

```
  @output
  @render.plot
  def dist():
    x = np.random.randn(input.n())
    plt.hist(x, range=[-3, 3])
```


```
  app = App(app_ui, server)
```

Layout the UI with Layout Functions

Specify the type of output with a **@render.** decorator


Call **App()** to combine **app_ui** and **server** into an interactive app

Launch apps with **shiny run app.py --reload**



Outputs


Match **ui.output_*** functions to **@render.*** decorators to link Python output to the UI.



ui.output_data_frame(id)
@render.data_frame



ui.output_image(id, width, height, click, dblclick, hover, brush, inline)
@render.image



ui.output_plot(id, width, height, click, dblclick, hover, brush, inline)
@render.plot

ui.output_table(id)
@render.table

foo

ui.output_text_verbatim(id, ...)
ui.output_text(id, container, inline)
@render.text



ui.output_ui(id, inline, container, ...)
ui.output_html(id, inline, container, ...)
@render.ui

Download

ui.download_button(id, label, icon, ...)
@session.download

Inputs

Use a **ui.** function to make an input widget that saves a value as **<id>**. Input values are *reactive* and need to be called as **<id>()**.

Action

ui.input_action_button(id, label, icon, width, ...)

Link

ui.input_action_link(id, label, icon, ...)

☒ Check me

ui.input_checkbox(id, label, value, width)

☒ Choice 1

ui.input_checkbox_group(id, label, choices, selected, inline, width)


☒ Choice 2

☐ Choice 3

ui.input_date(id, label, value, min, max, format, startview, weekstart, language, width, autoclose, datesdisabled, daysofweekdisabled)



ui.input_date_range(id, label, start, end, min, max, format, startview, weekstart, language, separator, width, autoclose)



Choose File

ui.input_file(id, label, multiple, accept, width, buttonLabel, placeholder, capture)

1

ui.input_numeric(id, label, value, min, max, step, width)

ui.input_password(id, label, value, width, placeholder)

☒ Choice A

ui.input_radio_buttons(id, label, choices, selected, inline, width)

☐ Choice B

ui.input_select(id, label, choices, selected, multiple, selectize, width, size)
Also **ui.input_selectize()**

☐ Choice C

Choice 1

Choice 2

ui.input_slider(id, label, min, max, value, step, ticks, animate, width, sep, pre, post, timeFormat, timezone, dragRange)

Choice 1

Choice 2

0 1 2 3 4 5 6 7 8 9 10

0 1 2 3 4 5 6 7 8 9 10

0 1 2 3 4 5 6 7 8 9 10

0 1 2 3 4 5 6 7 8 9 10

0 1 2 3 4 5 6 7 8 9 10

0 1 2 3 4 5 6 7 8 9 10

0 1 2 3 4 5 6 7 8 9 10

0 1 2 3 4 5 6 7 8 9 10

0 1 2 3 4 5 6 7 8 9 10

0 1 2 3 4 5 6 7 8 9 10

0 1 2 3 4 5 6 7 8 9 10

0 1 2 3 4 5 6 7 8 9 10

0 1 2 3 4 5 6 7 8 9 10

0 1 2 3 4 5 6 7 8 9 10


ui.input_switch(id, label, value, width)

Enter text

ui.input_text(id, label, value, width, placeholder, autocomplete, spellcheck)
Also **ui.input_text_area()**

Reactivity

Reactive values work together with reactive functions. Call a reactive value from within the arguments of one of these functions to avoid the error **Operation not allowed without an active reactive context.**



CREATE YOUR OWN REACTIVE VALUES

```
# ...
app_ui = ui.page_fluid(
  ui.input_text("a", "A")
)

def server(
  input, output, session
):
  rv = reactive.Value()
  rv.set(5)
# ...
```

ui.input_*() makes an input widget that saves a reactive value as **input.<id>()**.

reactive.value() Creates an object whose value you can set.

CREATE REACTIVE EXPRESSIONS

```
# ...
def server(
  input, output, session
):
  @reactive.Calc
  def re():
    return input.a() + input.b()
# ...
```

@reactive.Calc Makes a function a reactive expression. Shiny notifies functions that use the expression when it becomes invalidated, triggering recomputation. Shiny caches the value of the expression while it is valid to avoid unnecessary computation.

REACT BASED ON EVENT

```
# ...
def server(
  input, output, session
):
  @reactive.Calc
  @reactive.event(input.a)
  def re():
    return input.b()
# ...
```

@reactive.event() Makes a function react *only when* a specified value is invalidated, here input.a.

DISPLAY REACTIVE OUTPUT

```
app_ui = ui.page_fluid(
  ui.input_text("a", "A"),
  ui.output_text("b"),
)

def server(
  input, output, session
):
  @output
  @render.text
  def b():
    return input.a()
```

ui.output_*() adds a display object to the UI.

@output
@render.* Decorators to identify and render outputs

def <id>(): Instructions to run to regenerate the object

PERFORM SIDE EFFECTS

```
# ...
def server(
  input, output, session
):
  @reactive.Effect
  @reactive.event(input.a)
  def print():
    print("Hi")
# ...
```

@reactive.Effect Makes a function that returns a side effect reactive. Call a reactive value or use **@reactive.event** to specify when the function will be invalidated, and thus rerun.

REMOVE REACTIVITY

```
# ...def server(
  input, output, session
):
  @output
  @render.text
  def a():
    with reactive.isolate():
      return input.a()
# ...
```

reactive.isolate() Create a non-reactive scope within a reactive scope. Calling a reactive value within this scope will *not* cause the calling function to re-execute should the value become invalid.

Layouts

Combine multiple elements into a "single element" that has its own properties with a panel function:

```
ui.panel_absolute()
ui.panel_conditional()
ui.panel_fixed()
ui.panel_main()

ui.panel_sidebar()
ui.panel_title()
ui.panel_well()
ui.row() / ui.column()
```

```
ui.panel_well(
  ui.input_date(...),
  ui.input_action_button(...)
)
```

Layout panels with a layout function. Add elements as arguments of the layout functions.

ui.layout_sidebar()

```
app_ui = ui.page_fluid(
  ui.panel_title(),
  ui.layout_sidebar(
    ui.panel_sidebar(),
    ui.panel_main(),
  )
)
```

ui.row()

```
app_ui = ui.page_fluid(
  ui.row(
    ui.column(width = 4),
    ui.column(width = 2, offset = 3),
  ),
  ui.row(ui.column(width = 12))
)
```

Layer **ui.nav()** s on top of each other, and navigate between them, with:

```
ui.page_fluid(ui.navset_tab(
  ui.nav("tab 1", "contents"),
  ui.nav("tab 2", "contents"),
  ui.nav("tab 3", "contents")))

ui.page_fluid(ui.navset_pill_list(
  ui.nav("tab 1", "contents"),
  ui.nav("tab 2", "contents"),
  ui.nav("tab 3", "contents")))

ui.page_navbar(
  ui.nav("tab 1", "contents"),
  ui.nav("tab 2", "contents"),
  ui.nav("tab 3", "contents"),
  title = "Page")
```

Themes

Use the **shinyswatch** package to add existing bootstrap themes to your Shiny app ui.

```
import shinyswatch

app_ui = ui.page_fluid(
  shinyswatch.theme.darkly(),
  ...
)
```

Shiny for R Comparison

Shiny for Python is quite similar to Shiny for R with a few important differences:



1. Call inputs as **input.<id>()**

input\$x input.x()

2. Use **decorators** to create and render outputs. Define outputs as functions **def <id>():**

output\$y <- renderText(z()) @output
@renderText
def y():
 return z()

3. To create a reactive expression, use **@reactive.Calc**

z <- reactive({
 input\$x + 1
}) @reactive.Calc
def z():
 return input.x()+1

4. To create an observer, use **@reactive.Effect**

a <- observe({
 print(input\$x)
}) @reactive.Effect
def a():
 print(input.x())

5. Combine these with **@reactive.event**

b <- eventReactive(
 i(),
 {input\$x + 1}
) @reactive.Calc
@reactive.event(i())
def b():
 return input.x()+1

6. Use **reactive.value()** instead of **reactiveValues()**

values <- reactiveValues(
 x = 1,
 y = 2
) values = {
 "x": reactive.Value(1),
 "y": reactive.Value(2),
 }

7. Use **nav_***() instead of ***Tab()**

insertTab()
appendTab()
etc. nav_insert()
nav_append()
etc.

8. Functions are intuitively organized into submodules

dateInput()
textInput()
etc. ui.input_date()
ui.input_text()
etc.