

HANDLING USER AUTHENTICATION

Open pom.xml add dependencies

```
<?xml version="1.0" encoding="UTF-8"?>
<project xmlns="http://maven.apache.org/POM/4.0.0"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xsi:schemaLocation="http://maven.apache.org/POM/4.0.0
https://maven.apache.org/xsd/maven-4.0.0.xsd">
  <modelVersion>4.0.0</modelVersion>
  <parent>
    <groupId>org.springframework.boot</groupId>
    <artifactId>spring-boot-starter-parent</artifactId>
    <version>2.4.3</version>
    <relativePath /> <!-- lookup parent from repository -->
  </parent>
  <groupId>com.project</groupId>
  <artifactId>Authentication</artifactId>
  <version>0.0.1-SNAPSHOT</version>
  <name>Authentication</name>
  <description>Demo project for Spring Boot</description>
  <properties>
    <java.version>1.8</java.version>
  </properties>
  <dependencies>
    <dependency>
      <groupId>org.springframework.boot</groupId>
      <artifactId>spring-boot-starter-data-jpa</artifactId>
    </dependency>
    <dependency>
      <groupId>org.springframework.boot</groupId>
      <artifactId>spring-boot-starter-jersey</artifactId>
    </dependency>
    <dependency>
      <groupId>org.springframework.boot</groupId>
      <artifactId>spring-boot-starter-web</artifactId>
    </dependency>
    <dependency>
      <groupId>org.springframework.boot</groupId>
      <artifactId>spring-boot-devtools</artifactId>
      <scope>runtime</scope>
      <optional>true</optional>
    </dependency>
    <dependency>
      <groupId>org.springframework.boot</groupId>
      <artifactId>spring-boot-starter-test</artifactId>
      <scope>test</scope>
    </dependency>
    <dependency>
      <groupId>org.apache.tomcat.embed</groupId>
      <artifactId>tomcat-embed-jasper</artifactId>
```

```

        <scope>provided</scope>
    </dependency>

    <dependency>
        <groupId>javax.xml.bind</groupId>
        <artifactId>jaxb-api</artifactId>
    </dependency>

    <dependency>
        <groupId>org.javassist</groupId>
        <artifactId>javassist</artifactId>
        <version>3.25.0-GA</version>
    </dependency>
    <dependency>
        <groupId>javax.servlet</groupId>
        <artifactId>jstl</artifactId>
        <version>1.2</version>
    </dependency>
    <dependency>
        <groupId>org.projectlombok</groupId>
        <artifactId>lombok-maven-plugin</artifactId>
        <version>1.18.18.0</version>
        <type>maven-plugin</type>
    </dependency>

    <dependency>
        <groupId>com.h2database</groupId>
        <artifactId>h2</artifactId>
        <scope>runtime</scope>
    </dependency>
</dependencies>

<build>
    <plugins>
        <plugin>
            <groupId>org.springframework.boot</groupId>
            <artifactId>spring-boot-maven-plugin</artifactId>
            <configuration>
            </configuration>
        </plugin>
        <plugin>
            <groupId>org.projectlombok</groupId>
            <artifactId>lombok-maven-plugin</artifactId>
            <version>1.18.18.0</version>
        </plugin>
    </plugins>
</build>

</project>

```

Create package com.project.Authentication

Create AuthenticationApplication.java

package com.project.Authentication;

```

import org.springframework.boot.SpringApplication;
import org.springframework.boot.autoconfigure.SpringBootApplication;
import org.springframework.context.annotation.Import;
import com.project.Authentication.controllers.AuthenticationController;
import com.project.Authentication.entities.User;
import com.project.Authentication.exceptions.UserNotFoundException;
import com.project.Authentication.services.AuthenticationService;

@SpringBootApplication
@Import({
    AuthenticationController.class,
    UserNotFoundException.class,
    AuthenticationService.class,
    User.class
})
public class AuthenticationApplication {

    public static void main(String[] args) {
        SpringApplication.run(AuthenticationApplication.class, args);
    }

}

```

Create package com.project.Authentication.controller

Create AuthenticationController.java

```

package com.project.Authentication.controllers;

import org.slf4j.Logger;

import org.slf4j.LoggerFactory;

import org.springframework.beans.factory.annotation.Autowired;

import org.springframework.stereotype.Controller;

import org.springframework.web.bind.annotation.GetMapping;

import org.springframework.web.bind.annotation.PostMapping;

import org.springframework.web.bind.annotation.RequestParam;

import com.project.Authentication.entities.User;

import com.project.Authentication.services.AuthenticationService;

@Controller

public class AuthenticationController {

    Logger logger = LoggerFactory.getLogger(AuthenticationController.class);

    @Autowired

    AuthenticationService authService;

```

```

    @GetMapping("/")

    public String showGreeting() {

        return "greeting";

    }

    @GetMapping("/Auth")

    public String showLogin() {

        return "authenticate";

    }

    @PostMapping("/Auth")

    public String authenticateUser(@RequestParam("username") String username,
    @RequestParam("password") String pswd) {

        User user = authService.getUserByName(username);

        logger.info(user.getName() + " attempted to login with " + user.getPassword());

        String path = (authService.isValidPassword(pswd, user.getPassword())) ? "success" : "failure";

        logger.info("The path return: " + path);

        return path;

    }

}

```

Create package com.project.Authentication.entities

Crate User.java

```

package com.project.Authentication.entities;

import javax.persistence.Column;
import javax.persistence.Entity;
import javax.persistence.GeneratedValue;
import javax.persistence.GenerationType;
import javax.persistence.Id;
import javax.persistence.Table;
import javax.validation.constraints.NotNull;

```

@Entity

@Table(name = "user")

public class User {

 @Id

 @GeneratedValue(strategy = GenerationType.AUTO)

 @NotNull

 private Integer id;

 @Column(name = "name")

 @NotNull

 private String name;

 @Column(name = "email")

 @NotNull

 private String email;

 @Column(name = "password")

 @NotNull

 private String password;

 public User() {

 super();

 }

 public User(@NotNull String name, @NotNull String password) {

 this.name = name;

 this.password = password;

 }

 public User(@NotNull String name, @NotNull String email, @NotNull String password) {

```
        super();  
        this.name = name;  
        this.email = email;  
        this.password = password;  
    }  
  
    public Integer getId() {  
        return id;  
    }  
  
    public void setId(Integer id) {  
        this.id = id;  
    }  
  
    public String getName() {  
        return name;  
    }  
  
    public void setName(String name) {  
        this.name = name;  
    }  
  
    public String getEmail() {  
        return email;  
    }  
  
    public void setEmail(String email) {  
        this.email = email;  
    }  
  
    public String getPassword() {
```

```

        return password;
    }

    public void setPassword(String password) {
        this.password = password;
    }

    @Override
    public String toString() {
        return "User [id=" + id + ", name=" + name + ", email=" + email + ", password=" +
password + "]\n";
    }
}

```

Create package **com.project.Authentication.exceptions**

Create **UserNotFoundException.java**

```

package com.project.Authentication.exceptions;

public class UserNotFoundException extends RuntimeException {
    private static final long serialVersionUID = 1L;
}

```

Create package **com.project.Authentication.repositories**

Create **AuthenticationRepository.java**

```

package com.project.Authentication.repositories;

import java.util.Optional;

import org.springframework.data.repository.CrudRepository;
import org.springframework.stereotype.Repository;

import com.project.Authentication.entities.User;

@Repository
public interface AuthenticationRepository extends CrudRepository<User, Integer> {

    public Optional<User> findUserByName(String name);

}

```

Create package **com.project.Authentication.services**

Create **AuthenticationService.java**

```

package com.project.Authentication.services;

import java.util.Optional;

import org.springframework.beans.factory.annotation.Autowired;

import org.springframework.stereotype.Service;

import com.project.Authentication.entities.User;

import com.project.Authentication.exceptions.UserNotFoundException;

import com.project.Authentication.repositories.AuthenticationRepository;

@Service

public class AuthenticationService {

    @Autowired

    AuthenticationRepository authRepo;

    public User GetUserByName(String name) {

        Optional<User> found = authRepo.findUserByName(name);

        if(found.isPresent()) return found.get();

        else throw new UserNotFoundException();

    }

    public Boolean isValidPassword(String cmp, String actual) {

        return ((cmp.equals(actual)) ? true : false);

    }

}

```

Src/main/resources

application.properties

```

spring.jpa.hibernate.ddl-auto=update
spring.datasource.url=jdbc:mysql://localhost:3306/mywork
spring.datasource.username=root
spring.datasource.password=password

logging.level.org.springframework.web: DEBUG
spring.mvc.view.prefix=/WEB-INF/jsp/
spring.mvc.view.suffix=.jsp
server.port=8080

```

Open src/main/webapp/jsp

Create authenticate.jsp

```
<%@ page language="java" contentType="text/html; charset=ISO-8859-1"
pageEncoding="ISO-8859-1"%>
<%@ taglib prefix="form" uri="http://www.springframework.org/tags/form"%>

<!DOCTYPE html>
<html>
<head>
<meta charset="ISO-8859-1">
<title>Authentication Page</title>
</head>
<h2>Login Page</h2>
<body>
welcome to the authentication page

<form:form action="Auth" method="post" commandName="login">
    <label for="username"> Username:</label>
    <input name="username" id="username" type="text" placeholder="Username" required/>
    <label for="password"> Password:</label>
    <input name="password" id="password" type="password" placeholder="Password"
required/>
    <input type="submit" name="Submit"/>
</form:form>
</body>
</html>
```

Create failure.jsp

```
<%@ page language="java" contentType="text/html; charset=ISO-8859-1"
pageEncoding="ISO-8859-1"%>
<!DOCTYPE html>
<html>
<head>
<meta charset="ISO-8859-1">
<title>Failed Login</title>
</head>
<body>
<h1>You failed your login pal!
</h1><br/>
<a href="/Auth">Attempt Login again</a>
</body>
</html>
```

Create greeting.jsp

```
<%@ page language="java" contentType="text/html; charset=ISO-8859-1"
pageEncoding="ISO-8859-1"%>
<!DOCTYPE html>
<html>
<head>
<meta charset="ISO-8859-1">
<title>Landing Page</title>
</head>
<h2>Welcome Page</h2>
<body>
```

you reached the landing page

```
<a href="Auth">Login</a>
</body>
</html>
```

Create success.jsp

```
<%@ page language="java" contentType="text/html; charset=ISO-8859-1"
pageEncoding="ISO-8859-1"%>
<!DOCTYPE html>
<html>
<head>
<meta charset="ISO-8859-1">
<title>Successful Login Page</title>
</head>
<body>
<h1>Successful Login</h1>
</body>
</html>
```