

# Last Time

# Last Time

- What tools do we have to solve MDPs with continuous  $S$  and  $A$ ?

Value Iteration - Function Approximation

LQR

Policy Search - Cross Entropy

Model Predictive Control

# Course Map

# Course Map

- Outcome Uncertainty, Immediate vs Future Rewards (MDP)

Value Function



# Course Map

- Outcome Uncertainty, Immediate vs Future Rewards (MDP)
- Model Uncertainty (Reinforcement Learning)

# Course Map

- Outcome Uncertainty, Immediate vs Future Rewards (MDP)
- Model Uncertainty (Reinforcement Learning)
- State Uncertainty (POMDP)

# Course Map

- Outcome Uncertainty, Immediate vs Future Rewards (MDP)
- Model Uncertainty (Reinforcement Learning)
- State Uncertainty (POMDP)
- Interaction Uncertainty (Game)

# Course Map

- Outcome Uncertainty, Immediate vs Future Rewards (MDP)
- Model Uncertainty (Reinforcement Learning)
- State Uncertainty (POMDP)
- Interaction Uncertainty (Game)





# Course Map

- Outcome Uncertainty, Immediate vs Future Rewards (MDP)
- Model Uncertainty (Reinforcement Learning)
- State Uncertainty (POMDP)
- Interaction Uncertainty (Game)



# Guiding Questions

# Guiding Questions

- What is Reinforcement Learning?
- What are the main challenges in Reinforcement Learning?

# Guiding Questions

- What is Reinforcement Learning?
- What are the main challenges in Reinforcement Learning?
- How do we categorize RL approaches?

# Reinforcement Learning

~~In python, typically~~

~~s, r = step(env, a)~~

# Reinforcement Learning

Previously:  $(S, A, T, R, \gamma)$

In python, typically  
`s, r = step(env, a)`

# Reinforcement Learning

Previously:  $(S, A, \cancel{T}, \cancel{R}, \gamma)$

Unknown!

In python, typically

```
s, r = step(env, a)
```

# Reinforcement Learning

Previously:  $(S, A, \cancel{T}, \cancel{R}, \gamma)$

Unknown!

Env


Agent

In python, typically  
`s, r = step(env, a)`



# Reinforcement Learning


Previously:  $(S, A, \cancel{T}, \cancel{R}, \gamma)$   
*Unknown!*



In python, typically  
`s, r = step(env, a)`

# Reinforcement Learning

Previously:  $(S, A, \cancel{T}, \cancel{R}, \gamma)$   
*Unknown!*




`r = act!(env, a)`

In python, typically  
`s, r = step(env, a)`

# Reinforcement Learning

Previously:  $(S, A, \cancel{T}, \cancel{R}, \gamma)$

Unknown!




`r = act!(env, a)`

In python, typically  
`s, r = step(env, a)`

# Reinforcement Learning

Previously:  $(S, A, \cancel{T}, \cancel{R}, \gamma)$

Unknown!



`r = act!(env, a)`


`s = observe(env)`

In python, typically

~~`s, r = step(env, a)`~~  
`s, r = env.step(a)`

# Reinforcement Learning

Previously:  $(S, A, \cancel{T}, \cancel{R}, \gamma)$   
*Unknown!*



`r = act!(env, a)`


`s = observe(env)`

In python, typically  
`s, r = step(env, a)`


Note: Different from  $s', r = G(\underset{\gamma}{s}, a)$

# Learning Curve

# Learning Curve



# Learning Curve







# Learning Curve




# Learning Curve



# Learning Curve



# Breakout Rooms



$T$  ?  
 $R$  ?

$$-10 \leq R(s,a) \leq 10$$

How should we approach this?  
What are challenges?

- 1) MC-based equal prob actions  
log rewards, transition  
value iteration
- 2) ~~try all actions~~, estimate rewards + transitions, update policy every 100 steps
- 3) Cross Entropy Policy Search

Exploration

Exploitation


# Challenges

# Challenges

## 1. Exploration vs Exploitation

# Challenges

1. Exploration vs Exploitation
2. Credit Assignment



# Challenges

1. Exploration vs Exploitation
2. Credit Assignment
3. Generalization



# Classifications

# Classifications

- **Model Based:** Attempt to learn  $T$  and  $R$ , then find  $\pi^*$  by solving MDP

# Classifications

① ②

- **Model Based:** Attempt to learn  $T$  and  $R$ , then find  $\pi^*$  by solving MDP
- **Model Free:** Attempt to find  $Q^*$  or  $\pi^*$  directly without estimating  $T$  or  $R$

③

# Classifications

- **Model Based:** Attempt to learn  $T$  and  $R$ , then find  $\pi^*$  by solving MDP
- **Model Free:** Attempt to find  $Q^*$  or  $\pi^*$  directly without estimating  $T$  or  $R$
- **On-Policy:** Learn only using experience generated with the current policy.

# Classifications

- **Model Based:** Attempt to learn  $T$  and  $R$ , then find  $\pi^*$  by solving MDP
- **Model Free:** Attempt to find  $Q^*$  or  $\pi^*$  directly without estimating  $T$  or  $R$
- **On-Policy:** Learn only using experience generated with the current policy.
- **Off-Policy:** Learn using experience generated from the current policy *and* previous policies.

# Classifications

- **Model Based:** Attempt to learn  $T$  and  $R$ , then find  $\pi^*$  by solving MDP
- **Model Free:** Attempt to find  $Q^*$  or  $\pi^*$  directly without estimating  $T$  or  $R$
- **On-Policy:** Learn only using experience generated with the current policy.
- **Off-Policy:** Learn using experience generated from the current policy *and* previous policies.
- **Batch:** Learn only from previously-generated experience.

# Classifications

- **Model Based:** Attempt to learn  $T$  and  $R$ , then find  $\pi^*$  by solving MDP
- **Model Free:** Attempt to find  $Q^*$  or  $\pi^*$  directly without estimating  $T$  or  $R$
- **On-Policy:** Learn only using experience generated with the current policy.
- **Off-Policy:** Learn using experience generated from the current policy *and* previous policies.
- **Batch:** Learn only from previously-generated experience.
  - **Tabular:** Keep track of learned values for each state in a table

# Classifications

- **Model Based:** Attempt to learn  $T$  and  $R$ , then find  $\pi^*$  by solving MDP
- **Model Free:** Attempt to find  $Q^*$  or  $\pi^*$  directly without estimating  $T$  or  $R$

$$\pi_{\theta} \xrightarrow{\theta} \pi_{\theta'}$$

- **On-Policy:** Learn only using experience generated with the current policy.
- **Off-Policy:** Learn using experience generated from the current policy *and* previous policies.
- **Batch:** Learn only from previously-generated experience.

$$\pi_{\theta_t} \xrightarrow{\theta_{t+1}, \theta_{t+2}, \dots} \pi_{\theta_{t+1}}$$

- **Tabular:** Keep track of learned values for each state in a table
- **Deep:** Use a neural network to approximate learned values



# Tabular Maximum Likelihood Model-Based RL

given  $\text{env}, |S|, |A|$

$$N \leftarrow 0$$

$$P \leftarrow 0$$

$$s \leftarrow \text{observe}(\text{env})$$

$$\pi \leftarrow \text{random policy}$$

loop

$$a \leftarrow \begin{cases} \text{rand}(A) & \text{w.p. } \epsilon \\ \pi(s) & \text{otherwise} \end{cases}$$

← exploration  
ε-greedy

$$r \leftarrow \text{act}!(\text{env}, a)$$

$$s' \leftarrow \text{observe}(\text{env})$$

$$N[s, a, s'] += 1$$

$$P[s, a] += r$$

$$T[a][s, s'] \leftarrow \frac{N[s, a, s']}{\sum_{s'} N[s, a, s']} \quad \forall s, a, s'$$

$$R[s, a] \leftarrow \frac{P[s, a]}{\sum_{s'} N[s, a, s']} \quad \forall s, a$$

$$\pi \leftarrow \text{solve}(T, R) \quad \leftarrow \text{expensive}$$

$$s \leftarrow s'$$

$$N \in \mathbb{N}^{|S| \times |A| \times |S|}$$

$$P \in \mathbb{R}^{|S| \times |A|}$$

$$N[s, a, s']$$

$$P[s, a] = \text{cumulative reward}$$

# SARSA

# Guiding Questions

# Guiding Questions

- What is Reinforcement Learning?
- What are the main challenges in Reinforcement Learning?

# Guiding Questions

- What is Reinforcement Learning?
- What are the main challenges in Reinforcement Learning?
- How do we categorize RL approaches?