

Homework 1

Andey Nunes, MS

Jordan Hilton

additional team member name(s) here

January 12, 2019

Document Setup

The first step for this week is to set up the R Markdown document options.

Next step, load the data sets for the homework and summarize.

```
catalog <- read_excel("catalog.xls")
customers <- read_excel("customers.xls")
order_lines <- read_excel("order_lines.xlsx")
orders <- read_excel("orders.xls")
```

Summary tables

```
catalog_summary <- summary(catalog)
glimpse(catalog)
```

```
## Observations: 761
## Variables: 7
## $ id          <dbl> 446, 455, 445, 444, 443, 442, 438, 439, 440, 441...
## $ product_code <chr> "G79761", "plastic", "G75329", "G75328", "G75231...
## $ catalog_price <dbl> 9.9, 0.0, 11.9, 10.9, 12.9, 11.9, 9.5, 6.0, 6.0,...
## $ category1    <chr> "accessories", NA, "fishing", "fillet", "fillet"...
## $ manufact_id  <dbl> 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, ...
## $ vendor_id    <dbl> 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, ...
## $ name         <chr> "Exchange-A-Blade Sheath for 7 inch saw", "Plast..."
```

```
pander(catalog_summary, caption = "catalog summary table")
```

Table 1: catalog summary table (continued below)

id	product_code	catalog_price	category1
Min. : 307	Length:761	Min. : 0	Length:761
1st Qu.: 525	Class :character	1st Qu.: 18	Class :character
Median : 728	Mode :character	Median : 34	Mode :character
Mean : 725	NA	Mean : 49	NA
3rd Qu.: 930	NA	3rd Qu.: 57	NA
Max. :1125	NA	Max. :654	NA

manufact_id	vendor_id	name
Min. :0.0	Min. :0.0	Length:761
1st Qu.:1.0	1st Qu.:1.0	Class :character
Median :1.0	Median :1.0	Mode :character
Mean :1.2	Mean :1.2	NA
3rd Qu.:1.0	3rd Qu.:1.0	NA

manufact_id	vendor_id	name
Max. :8.0	Max. :8.0	NA

```
head(catalog)
```

```
## # A tibble: 6 x 7
##   id product_code catalog_price category1 manufact_id vendor_id name
##   <dbl> <chr>          <dbl> <chr>          <dbl>    <dbl> <chr>
## 1  446 G79761          9.95 accessori~      1        1 Excha~
## 2  455 plastic          0    <NA>          1        1 Plast~
## 3  445 G75329         12.0 fishing          1        1 Silve~
## 4  444 G75328         11.0 fillet          1        1 Silve~
## 5  443 G75231         13.0 fillet          1        1 "Gato~
## 6  442 G75230         12.0 fillet          1        1 "Gato~
```

```
customers_summary <- summary(customers)
glimpse(customers)
```

```
## Observations: 22,070
## Variables: 10
## $ cust_id      <dbl> 20696, 15465, 19830, 25532, 16044, 32394, 29572, 3...
## $ merchant_id  <dbl> 2, 1, 2, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, ...
## $ firstName    <chr> "Kristina", "Paige", "Sherri", "Gretchen", "Karen"...
## $ lastName     <chr> "Chung", "Chen", "Melton", "Hill", "Puckett", "Son...
## $ bt_city      <chr> "Piedmont", "Cincinnati", "Shelbyville", "North ri...
## $ bt_state     <chr> "OK", "OH", "TN", "AZ", "ON", "OR", "GA", "VA", "K...
## $ bt_country   <chr> "United States", "United States", "United States",...
## $ bt_zip       <chr> "73078", "45227", "37160", "86052", "K8H 2X3", "97...
## $ cc_type      <chr> "Visa", "Visa", "Mastercard", "Visa", "Visa", "Mas...
## $ custcode     <chr> "P20696", "G15465", "P19830", "G25532", "G16044", ...
```

```
pander(customers_summary, caption = "customers summary table")
```

Table 3: customers summary table (continued below)

cust_id	merchant_id	firstName	lastName
Min. :10000	Min. :1.00	Length:22070	Length:22070
1st Qu.:15930	1st Qu.:1.00	Class :character	Class :character
Median :21448	Median :1.00	Mode :character	Mode :character
Mean :21408	Mean :1.05	NA	NA
3rd Qu.:26965	3rd Qu.:1.00	NA	NA
Max. :32482	Max. :2.00	NA	NA

Table 4: Table continues below

bt_city	bt_state	bt_country	bt_zip
Length:22070	Length:22070	Length:22070	Length:22070
Class :character	Class :character	Class :character	Class :character
Mode :character	Mode :character	Mode :character	Mode :character
NA	NA	NA	NA
NA	NA	NA	NA
NA	NA	NA	NA

cc_type	custcode
Length:22070	Length:22070
Class :character	Class :character
Mode :character	Mode :character
NA	NA
NA	NA
NA	NA

```
head(customers)
```

```
## # A tibble: 6 x 10
##   cust_id merchant_id firstName lastName bt_city bt_state bt_country bt_zip
##   <dbl>      <dbl> <chr>      <chr>    <chr>  <chr>    <chr>      <chr>
## 1   20696          2 Kristina  Chung    Piedmo~ OK        United St~ 73078
## 2   15465          1 Paige   Chen     Cincin~ OH        United St~ 45227
## 3   19830          2 Sherri  Melton   Shelby~ TN        United St~ 37160
## 4   25532          1 Gretchen Hill     North ~ AZ        United St~ 86052
## 5   16044          1 Karen   Puckett  Petawa~ ON        Canada     K8H 2~
## 6   32394          1 Patrick Song     Winche~ OR        United St~ 97495
## # ... with 2 more variables: cc_type <chr>, custcode <chr>
```

```
order_lines_summary <- summary(order_lines)
glimpse(order_lines)
```

```
## Observations: 1,356
## Variables: 2
## $ `Sum of Shipped Total` <chr> "Row Labels", "411", "Multi-PlierÃ 800...
## $ X__1 <chr> "Total", "27507.100000000122", "27507.1..."
```

```
pander(order_lines_summary, caption = "order_lines summary table")
```

Table 6: order_lines summary table

Sum of Shipped Total	X__1
Length:1356	Length:1356
Class :character	Class :character
Mode :character	Mode :character

```
head(order_lines)
```

```
## # A tibble: 6 x 2
##   `Sum of Shipped Total` X__1
##   <chr>                <chr>
## 1 Row Labels          Total
## 2 411                 27507.100000000122
## 3 Multi-PlierÃ 800 - Legend 27507.100000000122
## 4 757                 21591.649999999994
## 5 LMFâ„¢ II Infantry - Black 21591.649999999994
## 6 395                 20355.900000000009
```

```
orders_summary <- summary(orders)
glimpse(orders)
```

```
## Observations: 23,256
```

```
## Variables: 18
## $ order_id      <dbl> 14035, 14034, 14033, 14032, 14031, 14030, 14...
## $ merchant_id   <dbl> 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1,...
## $ order_date     <dtm> 2003-10-17, 2003-10-16, 2003-10-16, 2003-10...
## $ po_number      <chr> NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, ...
## $ cust_id        <dbl> 10034, 10033, 10032, 10031, 10030, 10029, 10...
## $ order_status   <chr> "S", "S", "S", "S", "S", "S", "S", "S", "S", "S",...
## $ ship_method     <chr> "GND", "3DS", "GND", "GND", "3DS", "1DA", "G...
## $ items_amount   <dbl> 58.9, 8.9, 50.0, 11.9, 9.9, 109.9, 23.9, 40....
## $ amt_bracket     <chr> "C", "A", "B", "B", "A", "D", "B", "B", "A",...
## $ total_weight    <dbl> 2.3, 1.0, 1.0, 1.0, 1.0, 1.0, 1.0, 1.2, 1.0,...
## $ total_ship      <dbl> 5.5, 9.0, 5.2, 5.4, 9.0, 27.3, 5.3, 6.1, 5.4...
## $ total_hand      <dbl> 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0,...
## $ total_tax       <dbl> 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0,...
## $ total_amount    <dbl> 64, 18, 55, 17, 19, 137, 29, 46, 15, 23, 29,...
## $ order_status_date <dtm> 2003-10-17, 2003-10-17, 2003-10-17, 2003-10...
## $ send_inv_to_bill <dbl> 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0,...
## $ coupon_code     <lgl> NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, ...
## $ spec_instr      <lgl> NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, ...
```

```
pander(orders_summary, caption = "orders summary table")
```

Table 7: orders summary table (continued below)

order_id	merchant_id	order_date	po_number
Min. :14000	Min. :1.00	Min. :2003-10-10 00:00:00	Length:23256
1st Qu.:20134	1st Qu.:1.00	1st Qu.:2006-04-28 00:00:00	Class :character
Median :25948	Median :1.00	Median :2007-07-02 00:00:00	Mode :character
Mean :25918	Mean :1.05	Mean :2007-08-11 16:51:42	NA
3rd Qu.:31761	3rd Qu.:1.00	3rd Qu.:2008-12-19 00:00:00	NA
Max. :37575	Max. :2.00	Max. :2011-01-21 00:00:00	NA

Table 8: Table continues below

cust_id	order_status	ship_method	items_amount
Min. : 0	Length:23256	Length:23256	Min. : 0
1st Qu.:15778	Class :character	Class :character	1st Qu.: 28
Median :21302	Mode :character	Mode :character	Median : 48
Mean :21295	NA	NA	Mean : 73
3rd Qu.:26849	NA	NA	3rd Qu.: 80
Max. :32482	NA	NA	Max. :9590

Table 9: Table continues below

amt_bracket	total_weight	total_ship	total_hand	total_tax
Length:23256	Min. : 0	Min. : 0	Min. :0	Min. :0
Class :character	1st Qu.: 1	1st Qu.: 7	1st Qu.:0	1st Qu.:0
Mode :character	Median : 2	Median : 8	Median :0	Median :0
NA	Mean : 3	Mean : 11	Mean :0	Mean :0
NA	3rd Qu.: 3	3rd Qu.: 10	3rd Qu.:0	3rd Qu.:0
NA	Max. :483	Max. :631	Max. :0	Max. :0

Table 10: Table continues below

total_amount	order_status_date	send_inv_to_bill	coupon_code
Min. : 6	Min. :2003-10-10 00:00:00	Min. :0.00	Mode:logical
1st Qu.: 36	1st Qu.:2006-05-30 18:00:00	1st Qu.:0.00	NA's:23256
Median : 57	Median :2007-07-12 00:00:00	Median :0.00	NA
Mean : 84	Mean :2007-08-21 21:51:27	Mean :0.05	NA
3rd Qu.: 94	3rd Qu.:2008-12-26 00:00:00	3rd Qu.:0.00	NA
Max. :9590	Max. :2011-01-21 00:00:00	Max. :1.00	NA

spec_instr
Mode:logical
NA's:23256
NA
NA
NA
NA

```
head(orders)
```

```
## # A tibble: 6 x 18
##   order_id merchant_id order_date      po_number cust_id order_status
##   <dbl>      <dbl> <dtm>          <chr>      <dbl> <chr>
## 1   14035          1 2003-10-17 00:00:00 <NA>      10034 S
## 2   14034          1 2003-10-16 00:00:00 <NA>      10033 S
## 3   14033          1 2003-10-16 00:00:00 <NA>      10032 S
## 4   14032          1 2003-10-16 00:00:00 <NA>      10031 S
## 5   14031          1 2003-10-16 00:00:00 <NA>      10030 S
## 6   14030          1 2003-10-16 00:00:00 <NA>      10029 S
## # ... with 12 more variables: ship_method <chr>, items_amount <dbl>,
## #   amt_bracket <chr>, total_weight <dbl>, total_ship <dbl>,
## #   total_hand <dbl>, total_tax <dbl>, total_amount <dbl>,
## #   order_status_date <dtm>, send_inv_to_bill <dbl>, coupon_code <lgl>,
## #   spec_instr <lgl>
```

column names (variables) | assign a type: “question”, “answer”, or “link” | variable class | count missing values | range = max - min |

This section is for building some custom functions that will come in handy later

```
countNA <- function(x) { sum(is.na(x)) }
get_range <- function(x) {diff(range(x))}
```

Homework Questions

For question B

```
### this function finds the number of NAs for each column
sapply(catalog, function(y) sum(is.na(y)))
```

```
##           id product_code catalog_price      category1  manufact_id
##           0             1              0             645              0
```

```
##      vendor_id      name
##           0           1
### note that only one row has a blank value for product code or name, find out which that is
which(is.na(catalog[,2]))

## [1] 267

catalog[267,]

## # A tibble: 1 x 7
##       id product_code catalog_price category1 manufact_id vendor_id name
##   <dbl> <chr>          <dbl> <chr>          <dbl>    <dbl> <chr>
## 1   596 <NA>              0 <NA>              1        1 <NA>
### load our table of answers about the catlog and display it
cataloganswer<-read_excel("cataloganswer.xlsx")
pander(cataloganswer)
```

Field	Q/A/L	Data Type	Nulls
id	Link	Integer	0
product_code	Link	Text	1
catalog_price	Answer	Currency	0
category1	Question	Text	645
manufact_id	Question	Integer	0
vendor_id	Question	Integer	0
name	Answer	Text	1

References