

FIM

System Start Up Routine



Pack

	Main menu	Description
0 :	Login	menu login,the default password is 1234
1 :	Set password	Password setting
2 :	Parameter	Parameter setting
3 :	Fault log	Fault menu
4 :	H.Way data	Hoistway learn data
5 :	IO state	IO monitor
6 :	Analog Test	Analog test
7 :	H.Way learn	Shaft learning
8 :	Level Adj	Level adjustment
9 :	Reset Para	Reset parameter

Parameter	Description	Reference	Unit	Remark
F01	Accelerate	0.550	m/s ²	
F02	Decelerate	0.550	m/s ²	
F03	S curve T0	1.200	s	Beginning acc. Time
F04	S curve T1	1.000	s	End acc. Time
F05	S curve T2	1.000	s	Beginning del. Time
F06	S curve T3	1.200	s	End del. Time
F07	Floor number			According to the contract
F08	Rated speed		m/s	Same as the "Max linear speed" of drive.
F09	Encoder type	2048	PPR	
F10	Rated moto RPM		RPM	Same as the "Full scale speed" of drive.
F11	Inspection speed	0.250	m/s	
F12	Open door speed	0.200	m/s	The maximum permission speed when door open.
F13	Stop speed	0.020	m/s	
F14	Releveling speed	0.030	m/s	
F15	Up adj	100	mm	Upward level adjust
F16	Down adj	100	mm	Downward level adjust
F17	100% Load comp.	100.0		100% pre-torque voltage
F18	80.0% Load comp.	80.0		80% pre-torque voltage
F19	50.0% Load comp.	50.0		50% pre-torque voltage
F20	25.0% Load comp.	25.0		25% pre-torque voltage
F21	10.0% Load comp.	10.0		10% pre-torque voltage
F22	Brake on delay	0.60	s	
F23	Brake off delay	0.60	s	
F24	Run enable	1		1: Normal; 0: Only INS or Self-study permitted
F25	Level delay	6	mm	
F26	Set speed gain	100.0		Percent of max. speed
F27	Start speed	0.000	m/s	
F28	Start time	0.00	s	
F29	Invert type	0		"0" for SIEI drive,"1" for other drive



西子奥的斯电梯有限公司

AMCB2 PARAMETER

FIM

System Start Up Routine



Pack

F30	Disable Lz	0		Reserved
F31	Brake SW type	0		Reserved
F32	Brake off delay1	0.10	s	Time for brake sequence in INS mode.
F33	DDP protect time	30	s	Time for not passed a door zone
F34	Zs speed	0.600	m/s	Correct run speed
F35	H.Way Lrn speed	0.250	m/s	Learn speed
F36	Zs enable	1		Reserved
F37	Brake off delay2	0.30	s	Time for brake off delay 2. (INS mode).
F38	Run Limit	0		Reserved
F39	DZ type	0		Reserved
F40	Zs.0 speed	0.150	m/s	Speed in door zone of terminal in ZS run
F41	LZ Length	250	mm	"250" for 1LV and 2LV;"150" for 1LV
F42	Ena off delay	0.6	s	Adjust the time delay for Enable off.
F43	Open delay	0.6	s	Adjust the time delay for DS code generate.
F44	N/A	0		Reserved
F45	N/A	0		Reserved
F46	N/A	0		Reserved
F47	N/A	0		Reserved
F48	N/A	0		Reserved
F49	N/A	0		Reserved
F50	ASR P0	70.00		Reserved