

Elements Of Data Science - F2024

Week 2: Python Intro/Review and Numpy

9/15/2024

TODOs

- Review Selections from PDSH Chapter 2
- Read Selections from PDSH Chapter 3
- Skim Selections from PDSH Chapter 4

- Complete Week 2 Quiz (Due 1 week from today, Sep 22 @11:59pm)

Announcements

Office hours

- Monday 6pm-6:50pm, location: DSI Conference room
- Skype, by appointment only, Tuesdays 6pm+. (link to be sent once OH requested)

TODOs

- Ch 2. Introduction to NumPy
 - Understanding Data Types in Python
 - The Basics of NumPy Arrays
 - Skim: Computation on NumPy Arrays: Universal Functions
 - Aggregations: Min, Max, and Everything In Between
 - Skim: Computation on Arrays: Broadcasting
 - Comparisons, Masks, and Boolean Logic
 - Fancy Indexing
 - Sorting Arrays
 - Structured Data: NumPy's Structured Arrays

TODOs

- Ch 3. Data Manipulation with Pandas
 - Introducing Pandas Objects
 - Data Indexing and Selection
 - Operating on Data in Pandas
 - Handling Missing Data
 - Hierarchical Indexing
 - Combining Datasets: Concat and Append
 - Combining Datasets: Merge and Join
 - Aggregation and Grouping
 - Pivot Tables
 - Skim: Vectorized String Operations
 - Working with Time Series
 - High-Performance Pandas: `eval()` and `query()`

TODOs

- Ch 4. Visualization with Matplotlib
 - Simple Line Plots
 - Simple Scatter Plots
 - Visualizing Errors
 - Density and Contour Plots
 - Histograms, Binnings, and Density
 - Customizing Plot Legends
 - Customizing Colorbars
 - Multiple Subplots
 - Text and Annotation
 - Customizing Ticks
 - Customizing Matplotlib: Configurations and Stylesheets
 - Three-Dimensional Plotting in Matplotlib
 - Geographic Data with Basemap
 - Visualization with Seaborn

Getting Changes from Git

1. `cd` to the cloned class repository
2. `git pull`

example:

```
$ cd ~/proj/eods-f24  
$ git pull
```

Questions?

TODAY

- Tools Review
- Getting "Help" Documentation
- Python (Review?)
- Numpy

Tools Review

- Starting Jupyter
- Notebooks, Kernels and Virtual Environments

Getting "Help" Documentation in Python

Getting "Help" Documentation in Python

```
In [1]: 1 help(print)
```

Help on built-in function print in module builtins:

```
print(...)
    print(value, ..., sep=' ', end='\n', file=sys.stdout, flush=False)

    Prints the values to a stream, or to sys.stdout by default.
    Optional keyword arguments:
    file: a file-like object (stream); defaults to the current sys.stdout.
    sep:   string inserted between values, default a space.
    end:   string appended after the last value, default a newline.
    flush: whether to forcibly flush the stream.
```

Getting "Help" Documentation in Python

```
In [1]: 1 help(print)
```

```
Help on built-in function print in module builtins:
```

```
print(...)  
    print(value, ..., sep=' ', end='\n', file=sys.stdout, flush=False)  
  
    Prints the values to a stream, or to sys.stdout by default.  
    Optional keyword arguments:  
    file: a file-like object (stream); defaults to the current sys.stdout.  
    sep:   string inserted between values, default a space.  
    end:   string appended after the last value, default a newline.  
    flush: whether to forcibly flush the stream.
```

Also, in ipython/jupyter:

```
print?           # show docstring  
print??          # show code as well  
print([SHIFT+TAB] # get help in a popup
```

Python (Review?)

- Whitespace Formatting
- Dynamic Typing
- Basic Data Types
- Functions
- String Formatting
- Exceptions and Try-Except
- Truthiness
- Comparisons and Logical Operators
- Control Flow
- Assert
- Sorting
- List/Dict Comprehensions
- Importing Modules
- collections Module
- Object Oriented Programming

Whitespace Formatting

- Instead of braces or brackets to delimit blocks, use whitespace

```
# The pound sign marks the start of a comment. Python itself  
# ignores the comments, but they're helpful for anyone reading the code.  
for i in [1, 2, 3, 4, 5]:  
    print(i) # first line in "for i" block  
  
    for j in [1, 2, 3, 4, 5]:  
        print(j) # first line in "for j" block  
        print(i + j) # last line in "for j" block  
    print(i) # last line in "for i" block
```

- 4 space indentations are conventional
- Style Guide : PEP 8 (<https://www.python.org/dev/peps/pep-0008/>)

Dynamic Typing

- don't need to specify type at variable creation (though they'll get one at runtime)

Dynamic Typing

- don't need to specify type at variable creation (though they'll get one at runtime)

```
In [2]: 1 x = 3
        2 x = 3.14
        3 x = 'apple'
        4 x
```

```
Out[2]: 'apple'
```


Dynamic Typing

- don't need to specify type at variable creation (though they'll get one at runtime)

```
In [2]: 1 x = 3
        2 x = 3.14
        3 x = 'apple'
        4 x
```

```
Out[2]: 'apple'
```

```
In [3]: 1 # to determine the current variable type
        2 type(x)
```

```
Out[3]: str
```

Basic Python Data Types

- **int** (integer): `42`
- **float**: `4.2`, `4e2`
- **bool** (boolean): `True`, `False`
- **str** (string): `'num 42 '`, `"num 42 "`,
`"""multi-line string"""`
- **None** (null): `None`
- also `long`, `complex`, `bytes`, etc.

Functions

Functions

```
In [4]: 1 def add_two(x):  
        2     """Adds 2 to the number passed in."""  
        3     return x+2  
        4  
        5  
        6 add_two(2)
```

```
Out[4]: 4
```

Functions

```
In [4]: 1 def add_two(x):  
        2     """Adds 2 to the number passed in."""  
        3     return x+2  
        4  
        5  
        6 add_two(2)
```

Out[4]: 4

```
In [5]: 1 help(add_two)
```

Help on function add_two in module __main__:

```
add_two(x)  
    Adds 2 to the number passed in.
```

Functions

```
In [4]: 1 def add_two(x):  
        2     """Adds 2 to the number passed in."""  
        3     return x+2  
        4  
        5  
        6 add_two(2)
```

Out[4]: 4

```
In [5]: 1 help(add_two)
```

Help on function add_two in module __main__:

```
add_two(x)  
    Adds 2 to the number passed in.
```

Reminder, also in ipython/jupyter:

- `add_two?` # show docstring
- `add_two??` # show code as well
- `add_two([SHIFT+TAB]` # get help in a popup

Function Arguments

Function Arguments

- positional arguments must be entered in order

Function Arguments

- positional arguments must be entered in order

```
In [6]: 1 def subtract(x,y):  
        2     return x-y  
        3  
        4 subtract(3,1)
```

```
Out[6]: 2
```

Function Arguments

- **positional arguments** must be entered in order

```
In [6]: 1 def subtract(x,y):  
        2     return x-y  
        3  
        4 subtract(3,1)
```

```
Out[6]: 2
```

- **keyword arguments** must follow positional
- can be called in any order

Function Arguments

- **positional arguments** must be entered in order

```
In [6]: 1 def subtract(x,y):  
        2     return x-y  
        3  
        4 subtract(3,1)
```

Out[6]: 2

- **keyword arguments** must follow positional
- can be called in any order

```
In [7]: 1 def proportion(numer,denom,precision=2):  
        2     return round(numer/denom,precision)  
        3  
        4 proportion(2,precision=2,denom=3)
```

Out[7]: 0.67

String Formatting

String Formatting

```
In [8]: 1 x = 3.1415  
        2  
        3 'the value of x is ' + str(x)
```

```
Out[8]: 'the value of x is 3.1415'
```

String Formatting

```
In [8]: 1 x = 3.1415  
2  
3 'the value of x is ' + str(x)
```

Out[8]: 'the value of x is 3.1415'

```
In [9]: 1 'the value of x is %0.2f' % x
```

Out[9]: 'the value of x is 3.14'

String Formatting

```
In [8]: 1 x = 3.1415
        2
        3 'the value of x is ' + str(x)
```

Out[8]: 'the value of x is 3.1415'

```
In [9]: 1 'the value of x is %0.2f' % x
```

Out[9]: 'the value of x is 3.14'

```
In [10]: 1 'the value of x is {:0.10f} and not {}'.format(x, 10)
```

Out[10]: 'the value of x is 3.1415000000 and not 10'

String Formatting

```
In [8]: 1 x = 3.1415
        2
        3 'the value of x is ' + str(x)
```

Out[8]: 'the value of x is 3.1415'

```
In [9]: 1 'the value of x is %0.2f' % x
```

Out[9]: 'the value of x is 3.14'

```
In [10]: 1 'the value of x is {:0.10f} and not {}'.format(x, 10)
```

Out[10]: 'the value of x is 3.1415000000 and not 10'

```
In [11]: 1 f'the value of x is {x:0.2f}'
        2 # note: f-string is a literal string, prefixed with 'f', which contains expressions inside braces.
```

Out[11]: 'the value of x is 3.14'

String Formatting

```
In [8]: 1 x = 3.1415
        2
        3 'the value of x is ' + str(x)
```

Out[8]: 'the value of x is 3.1415'

```
In [9]: 1 'the value of x is %0.2f' % x
```

Out[9]: 'the value of x is 3.14'

```
In [10]: 1 'the value of x is {:0.10f} and not {}'.format(x, 10)
```

Out[10]: 'the value of x is 3.1415000000 and not 10'

```
In [11]: 1 f'the value of x is {x:0.2f}'
        2 # note: f-string is a literal string, prefixed with 'f', which contains expressions inside braces.
```

Out[11]: 'the value of x is 3.14'

- often want to print variable values for debugging

String Formatting

```
In [8]: 1 x = 3.1415
        2
        3 'the value of x is ' + str(x)
```

Out[8]: 'the value of x is 3.1415'

```
In [9]: 1 'the value of x is %0.2f' % x
```

Out[9]: 'the value of x is 3.14'

```
In [10]: 1 'the value of x is {:0.10f} and not {}'.format(x, 10)
```

Out[10]: 'the value of x is 3.1415000000 and not 10'

```
In [11]: 1 f'the value of x is {x:0.2f}'
        2 # note: f-string is a literal string, prefixed with 'f', which contains expressions inside braces.
```

Out[11]: 'the value of x is 3.14'

- often want to print variable values for debugging

```
In [12]: 1 f'x = {x:0.2f}'
```

Out[12]: 'x = 3.14'

String Formatting

```
In [8]: 1 x = 3.1415
        2
        3 'the value of x is ' + str(x)
```

Out[8]: 'the value of x is 3.1415'

```
In [9]: 1 'the value of x is %0.2f' % x
```

Out[9]: 'the value of x is 3.14'

```
In [10]: 1 'the value of x is {:0.10f} and not {}'.format(x, 10)
```

Out[10]: 'the value of x is 3.1415000000 and not 10'

```
In [11]: 1 f'the value of x is {x:0.2f}'
        2 # note: f-string is a literal string, prefixed with 'f', which contains expressions inside braces.
```

Out[11]: 'the value of x is 3.14'

- often want to print variable values for debugging

```
In [12]: 1 f'x = {x:0.2f}'
```

Out[12]: 'x = 3.14'

```
In [13]: 1 f'{x = :0.2f}' # new in 3.8
```

Out[13]: 'x = 3.14'

String Formatting Cont.

String Formatting Cont.

```
In [14]: 1 """This is a multiline string.  
2 The value of x is {}.""".format(x)
```

```
Out[14]: 'This is a multiline string.\nThe value of x is 3.1415.'
```

String Formatting Cont.

```
In [14]: 1 """This is a multiline string.  
2 The value of x is {}.""".format(x)
```

```
Out[14]: 'This is a multiline string.\nThe value of x is 3.1415.'
```

```
In [15]: 1 print("""This is a multiline string.  
2 The value of x is {}.""".format(x))
```

```
This is a multiline string.  
The value of x is 3.1415.
```

String Formatting Cont.

```
In [14]: 1 """This is a multiline string.  
2 The value of x is {}.format(x)
```

```
Out[14]: 'This is a multiline string.\nThe value of x is 3.1415.'
```

```
In [15]: 1 print("""This is a multiline string.  
2 The value of x is {}.format(x))
```

```
This is a multiline string.  
The value of x is 3.1415.
```

- to learn more <https://realpython.com/python-string-formatting/>

Python Data Types Continued: `list`

Python Data Types Continued: **list**

```
In [22]: 1 # elements of a python list do not all have to be of the same type
          2 x = [42, 'e', 2.0]
          3 x
```

```
Out[22]: [42, 'e', 2.0]
```

Python Data Types Continued: **list**

```
In [22]: 1 # elements of a python list do not all have to be of the same type
          2 x = [42, 'e', 2.0]
          3 x
```

```
Out[22]: [42, 'e', 2.0]
```

```
In [23]: 1 x[0] # indexing
```

```
Out[23]: 42
```

Python Data Types Continued: **list**

```
In [22]: 1 # elements of a python list do not all have to be of the same type
          2 x = [42, 'e', 2.0]
          3 x
```

```
Out[22]: [42, 'e', 2.0]
```

```
In [23]: 1 x[0] # indexing
```

```
Out[23]: 42
```

```
In [24]: 1 x[-1] # reverse indexing
```

```
Out[24]: 2.0
```

Python Data Types Continued: `list`

```
In [22]: 1 # elements of a python list do not all have to be of the same type
          2 x = [42, 'e', 2.0]
          3 x
```

Out[22]: [42, 'e', 2.0]

```
In [23]: 1 x[0] # indexing
```

Out[23]: 42

```
In [24]: 1 x[-1] # reverse indexing
```

Out[24]: 2.0

```
In [25]: 1 x[2] = 4 # assignment
          2 x
```

Out[25]: [42, 'e', 4]

Python Data Types Continued: `list`

```
In [22]: 1 # elements of a python list do not all have to be of the same type
          2 x = [42, 'e', 2.0]
          3 x
```

Out[22]: [42, 'e', 2.0]

```
In [23]: 1 x[0] # indexing
```

Out[23]: 42

```
In [24]: 1 x[-1] # reverse indexing
```

Out[24]: 2.0

```
In [25]: 1 x[2] = 4 # assignment
          2 x
```

Out[25]: [42, 'e', 4]

```
In [26]: 1 x.append('a') # add a value to list
          2 x
```

Out[26]: [42, 'e', 4, 'a']

Python Data Types Continued: `list`

```
In [22]: 1 # elements of a python list do not all have to be of the same type
          2 x = [42, 'e', 2.0]
          3 x
```

Out[22]: [42, 'e', 2.0]

```
In [23]: 1 x[0] # indexing
```

Out[23]: 42

```
In [24]: 1 x[-1] # reverse indexing
```

Out[24]: 2.0

```
In [25]: 1 x[2] = 4 # assignment
          2 x
```

Out[25]: [42, 'e', 4]

```
In [26]: 1 x.append('a') # add a value to list
          2 x
```

Out[26]: [42, 'e', 4, 'a']

```
In [27]: 1 value_at_1 = x.pop(1) # remove/delete at index
          2 x
```

Out[27]: [42, 4, 'a']

Python Data Types Continued: `dict` (Dictionary)

- Stores key:value pairs

Python Data Types Continued: `dict` (Dictionary)

- Stores key:value pairs

```
In [28]: 1 x = {'b':[2,1], 'a':1, 'c':4}
          2 # or x = dict(b=2,a=1,c=4)
          3 x
```

```
Out[28]: {'b': [2, 1], 'a': 1, 'c': 4}
```


Python Data Types Continued: `dict` (Dictionary)

- Stores key:value pairs

```
In [28]: 1 x = {'b':[2,1], 'a':1, 'c':4}
          2 # or x = dict(b=2,a=1,c=4)
          3 x
```

```
Out[28]: {'b': [2, 1], 'a': 1, 'c': 4}
```

```
In [29]: 1 # index into dictionary using key
          2 x['b']
```

```
Out[29]: [2, 1]
```

Python Data Types Continued: `dict` (Dictionary)

- Stores key:value pairs

```
In [28]: 1 x = {'b':[2,1], 'a':1, 'c':4}
          2 # or x = dict(b=2,a=1,c=4)
          3 x
```

```
Out[28]: {'b': [2, 1], 'a': 1, 'c': 4}
```

```
In [29]: 1 # index into dictionary using key
          2 x['b']
```

```
Out[29]: [2, 1]
```

```
In [30]: 1 # assign a value to a (new or existing) key
          2 x['d'] = 3
          3 x
```

```
Out[30]: {'b': [2, 1], 'a': 1, 'c': 4, 'd': 3}
```

Python Data Types Continued: `dict` (Dictionary)

- Stores key:value pairs

```
In [28]: 1 x = {'b':[2,1], 'a':1, 'c':4}
          2 # or x = dict(b=2,a=1,c=4)
          3 x
```

```
Out[28]: {'b': [2, 1], 'a': 1, 'c': 4}
```

```
In [29]: 1 # index into dictionary using key
          2 x['b']
```

```
Out[29]: [2, 1]
```

```
In [30]: 1 # assign a value to a (new or existing) key
          2 x['d'] = 3
          3 x
```

```
Out[30]: {'b': [2, 1], 'a': 1, 'c': 4, 'd': 3}
```

```
In [31]: 1 # remove/delete
          2 # can specify a return a value if key does not exist (here it's None), otherwise throws an exception
          3 x.pop('eods', None)
```

Python Data Types Continued: `dict` (Dictionary)

- Stores key:value pairs

```
In [28]: 1 x = {'b':[2,1], 'a':1, 'c':4}
          2 # or x = dict(b=2,a=1,c=4)
          3 x
```

```
Out[28]: {'b': [2, 1], 'a': 1, 'c': 4}
```

```
In [29]: 1 # index into dictionary using key
          2 x['b']
```

```
Out[29]: [2, 1]
```

```
In [30]: 1 # assign a value to a (new or existing) key
          2 x['d'] = 3
          3 x
```

```
Out[30]: {'b': [2, 1], 'a': 1, 'c': 4, 'd': 3}
```

```
In [31]: 1 # remove/delete
          2 # can specify a return a value if key does not exist (here it's None), otherwise throws an exception
          3 x.pop('eods', None)
```

```
In [32]: 1 x
```

```
Out[32]: {'b': [2, 1], 'a': 1, 'c': 4, 'd': 3}
```

Python Data Types Continued: `dict` (Dictionary)

- Stores key:value pairs

```
In [28]: 1 x = {'b':[2,1], 'a':1, 'c':4}
          2 # or x = dict(b=2,a=1,c=4)
          3 x
```

```
Out[28]: {'b': [2, 1], 'a': 1, 'c': 4}
```

```
In [29]: 1 # index into dictionary using key
          2 x['b']
```

```
Out[29]: [2, 1]
```

```
In [30]: 1 # assign a value to a (new or existing) key
          2 x['d'] = 3
          3 x
```

```
Out[30]: {'b': [2, 1], 'a': 1, 'c': 4, 'd': 3}
```

```
In [31]: 1 # remove/delete
          2 # can specify a return a value if key does not exist (here it's None), otherwise throws an exception
          3 x.pop('eods', None)
```

```
In [32]: 1 x
```

```
Out[32]: {'b': [2, 1], 'a': 1, 'c': 4, 'd': 3}
```

```
In [33]: 1 x.pop('d', None)
```

Python Data Types Continued: `dict` Cont.

Python Data Types Continued: `dict` Cont.

```
In [34]: 1 # using the same dictionary  
        2 x
```

```
Out[34]: {'b': [2, 1], 'a': 1, 'c': 4}
```

Python Data Types Continued: dict Cont.

```
In [34]: 1 # using the same dictionary  
        2 x
```

```
Out[34]: {'b': [2, 1], 'a': 1, 'c': 4}
```

```
In [35]: 1 # get a set of keys  
        2 x.keys()
```

```
Out[35]: dict_keys(['b', 'a', 'c'])
```


Python Data Types Continued: dict Cont.

```
In [34]: 1 # using the same dictionary  
        2 x
```

```
Out[34]: {'b': [2, 1], 'a': 1, 'c': 4}
```

```
In [35]: 1 # get a set of keys  
        2 x.keys()
```

```
Out[35]: dict_keys(['b', 'a', 'c'])
```

```
In [36]: 1 # get a set of values  
        2 x.values()
```

```
Out[36]: dict_values([[2, 1], 1, 4])
```

Python Data Types Continued: dict Cont.

```
In [34]: 1 # using the same dictionary  
        2 x
```

```
Out[34]: {'b': [2, 1], 'a': 1, 'c': 4}
```

```
In [35]: 1 # get a set of keys  
        2 x.keys()
```

```
Out[35]: dict_keys(['b', 'a', 'c'])
```

```
In [36]: 1 # get a set of values  
        2 x.values()
```

```
Out[36]: dict_values([[2, 1], 1, 4])
```

```
In [37]: 1 # get a set of (key,value) tuples  
        2 x.items()
```

```
Out[37]: dict_items([('b', [2, 1]), ('a', 1), ('c', 4)])
```

Python Data Types Continued: dict Cont.

```
In [34]: 1 # using the same dictionary
        2 x
```

```
Out[34]: {'b': [2, 1], 'a': 1, 'c': 4}
```

```
In [35]: 1 # get a set of keys
        2 x.keys()
```

```
Out[35]: dict_keys(['b', 'a', 'c'])
```

```
In [36]: 1 # get a set of values
        2 x.values()
```

```
Out[36]: dict_values([[2, 1], 1, 4])
```

```
In [37]: 1 # get a set of (key,value) tuples
        2 x.items()
```

```
Out[37]: dict_items([('b', [2, 1]), ('a', 1), ('c', 4)])
```

```
In [38]: 1 # get a list of (key,value) pairs
        2 list(x.items())
```

```
Out[38]: [('b', [2, 1]), ('a', 1), ('c', 4)]
```

Python Data Types Continued: `tuple`

- like a list, but **immutable**

Python Data Types Continued: tuple

- like a list, but immutable

```
In [39]: 1 x = (2, 'e', 3, 4)
          2 x
```

```
Out[39]: (2, 'e', 3, 4)
```

Python Data Types Continued: tuple

- like a list, but immutable

```
In [39]: 1 x = (2, 'e', 3, 4)
          2 x
```

```
Out[39]: (2, 'e', 3, 4)
```

```
In [40]: 1 x[0] # indexing
```

```
Out[40]: 2
```

Python Data Types Continued: tuple

- like a list, but immutable

```
In [39]: 1 x = (2, 'e', 3, 4)
        2 x
```

```
Out[39]: (2, 'e', 3, 4)
```

```
In [40]: 1 x[0] # indexing
```

```
Out[40]: 2
```

```
In [41]: 1 x[0] = 3 # assignment? Nope, error: immutable`
```

```
-----
TypeError                                Traceback (most recent call last)
Cell In[41], line 1
----> 1 x[0] = 3

TypeError: 'tuple' object does not support item assignment
```

```
In [42]: 1 a = (1, 2, [10, 12])
```

```
In [43]: 1 a[2][0] = 15
```

```
In [44]: 1 a[2].append(10)
```

```
In [45]: 1 a
```

```
Out[45]: (1, 2, [15, 12, 10])
```

Python Data Types Continued: set

```
In [46]: 1 lst = [1,1,1,1,1,1,5,5,'Jack']  
        2 lst = list(set(lst))
```

```
In [47]: 1 lst
```

```
Out[47]: [1, 5, 'Jack']
```


Python Data Types Continued: set

```
In [46]: 1 lst = [1,1,1,1,1,1,5,5,'Jack']  
        2 lst = list(set(lst))
```

```
In [47]: 1 lst
```

```
Out[47]: [1, 5, 'Jack']
```

```
In [48]: 1 x = {2,'e','e'} # or set([2,'e','e'])  
        2 x
```

```
Out[48]: {2, 'e'}
```

Python Data Types Continued: set

```
In [46]: 1 lst = [1,1,1,1,1,1,5,5,'Jack']  
        2 lst = list(set(lst))
```

```
In [47]: 1 lst
```

```
Out[47]: [1, 5, 'Jack']
```

```
In [48]: 1 x = {2,'e','e'} # or set([2,'e','e'])  
        2 x
```

```
Out[48]: {2, 'e'}
```

```
In [49]: 1 x.add(1) # insert  
        2 x
```

```
Out[49]: {1, 2, 'e'}
```

Python Data Types Continued: set

```
In [46]: 1 lst = [1,1,1,1,1,1,5,5,'Jack']  
        2 lst = list(set(lst))
```

```
In [47]: 1 lst
```

```
Out[47]: [1, 5, 'Jack']
```

```
In [48]: 1 x = {2,'e','e'} # or set([2,'e','e'])  
        2 x
```

```
Out[48]: {2, 'e'}
```

```
In [49]: 1 x.add(1) # insert  
        2 x
```

```
Out[49]: {1, 2, 'e'}
```

```
In [50]: 1 x.remove('e') # remove/delete  
        2 x
```

```
Out[50]: {1, 2}
```

Python Data Types Continued: set

```
In [46]: 1 lst = [1,1,1,1,1,1,5,5,'Jack']  
        2 lst = list(set(lst))
```

```
In [47]: 1 lst
```

```
Out[47]: [1, 5, 'Jack']
```

```
In [48]: 1 x = {2,'e','e'} # or set([2,'e','e'])  
        2 x
```

```
Out[48]: {2, 'e'}
```

```
In [49]: 1 x.add(1) # insert  
        2 x
```

```
Out[49]: {1, 2, 'e'}
```

```
In [50]: 1 x.remove('e') # remove/delete  
        2 x
```

```
Out[50]: {1, 2}
```

```
In [51]: 1 x.intersection({2,3})
```

```
Out[51]: {2}
```

Python Data Types Continued: set

```
In [46]: 1 lst = [1,1,1,1,1,1,5,5,'Jack']  
        2 lst = list(set(lst))
```

```
In [47]: 1 lst
```

```
Out[47]: [1, 5, 'Jack']
```

```
In [48]: 1 x = {2,'e','e'} # or set([2,'e','e'])  
        2 x
```

```
Out[48]: {2, 'e'}
```

```
In [49]: 1 x.add(1) # insert  
        2 x
```

```
Out[49]: {1, 2, 'e'}
```

```
In [50]: 1 x.remove('e') # remove/delete  
        2 x
```

```
Out[50]: {1, 2}
```

```
In [51]: 1 x.intersection({2,3})
```

```
Out[51]: {2}
```

```
In [52]: 1 x.difference({2,3})
```

```
Out[52]: {1}
```

Python Data Types Continued: set

```
In [46]: 1 lst = [1,1,1,1,1,1,5,5,'Jack']  
        2 lst = list(set(lst))
```

```
In [47]: 1 lst
```

```
Out[47]: [1, 5, 'Jack']
```

```
In [48]: 1 x = {2,'e','e'} # or set([2,'e','e'])  
        2 x
```

```
Out[48]: {2, 'e'}
```

```
In [49]: 1 x.add(1) # insert  
        2 x
```

```
Out[49]: {1, 2, 'e'}
```

```
In [50]: 1 x.remove('e') # remove/delete  
        2 x
```

```
Out[50]: {1, 2}
```

```
In [51]: 1 x.intersection({2,3})
```

```
Out[51]: {2}
```

```
In [52]: 1 x.difference({2,3})
```

```
Out[52]: {1}
```

```
In [53]: 1 x[0] # cannot index into a set
```

Determining Length with `len`

Determining Length with `len`

```
In [54]: 1 len([1,2,3])
```

```
Out[54]: 3
```


Determining Length with `len`

```
In [54]: 1 len([1,2,3])
```

```
Out[54]: 3
```

```
In [55]: 1 len({'a':1, 'b':2, 'c':3})
```

```
Out[55]: 3
```

Determining Length with `len`

```
In [54]: 1 len([1,2,3])
```

```
Out[54]: 3
```

```
In [55]: 1 len({'a':1, 'b':2, 'c':3})
```

```
Out[55]: 3
```

```
In [56]: 1 len('apple')
```

```
Out[56]: 5
```

Exceptions

Exceptions

```
In [57]: 1 'a' + 2
```

```
-----  
TypeError                                Traceback (most recent call last)  
Cell In[57], line 1  
----> 1 'a' + 2  
  
TypeError: can only concatenate str (not "int") to str
```

Exceptions

```
In [57]: 1 'a' + 2
```

```
-----  
TypeError                                Traceback (most recent call last)  
Cell In[57], line 1  
----> 1 'a' + 2  
  
TypeError: can only concatenate str (not "int") to str
```

Common exceptions:

- SyntaxError
- IndentationError
- ValueError
- TypeError
- IndexError
- KeyError
- and many more <https://docs.python.org/3/library/exceptions.html>

Catching Exceptions with `try-except`

Catching Exceptions with `try-except`

```
In [58]: 1 try:
          2     'a' + 2
          3 except TypeError as e:
          4     print(f"We did this on purpose, and here's what's wrong:\n{e}")
```

```
We did this on purpose, and here's what's wrong:
can only concatenate str (not "int") to str
```

Catching Exceptions with `try-except`

```
In [58]: 1 try:
          2     'a' + 2
          3 except TypeError as e:
          4     print(f"We did this on purpose, and here's what's wrong:\n{e}")
```

We did this on purpose, and here's what's wrong:
can only concatenate str (not "int") to str

```
In [59]: 1 try:
          2     set([1,2,3])[0]
          3 except SyntaxError as e:
          4     print(f"Print this if there's a syntax error")
          5 except Exception as e:
          6     print(f"Print this for any other error")
```

Print this for any other error

Truthiness

Truthiness

- boolean: `True`, `False`
- These all translate to `False`:
 - `None`
 - `[]` (empty list)
 - `{}` (empty dictionary)
 - `''` (empty string)
 - `set()`
 - `0`
 - `0.0`

Comparison Operators

Comparison Operators

- equality: `==`
- inequality: `!=`

Comparison Operators

- equality: `==`
- inequality: `!=`

```
In [60]: 1 3 == 3
```

```
Out[60]: True
```

Comparison Operators

- equality: `==`
- inequality: `!=`

```
In [60]: 1 3 == 3
```

```
Out[60]: True
```

```
In [61]: 1 3 != 4
```

```
Out[61]: True
```

Comparison Operators

- equality: `==`
- inequality: `!=`

```
In [60]: 1 3 == 3
```

```
Out[60]: True
```

```
In [61]: 1 3 != 4
```

```
Out[61]: True
```

- less than: `<`
- greater than: `>`
- '(less than/greater than) or equal to: `<=` , `>=`

Comparison Operators

- equality: `==`
- inequality: `!=`

```
In [60]: 1 3 == 3
```

```
Out[60]: True
```

```
In [61]: 1 3 != 4
```

```
Out[61]: True
```

- less than: `<`
- greater than: `>`
- '(less than/greater than) or equal to: `<=` , `>=`

```
In [62]: 1 3 > 4
```

```
Out[62]: False
```


Logical Operators

Logical Operators

- logical operators: `and`, `or`, `not`

Logical Operators

- logical operators: `and`, `or`, `not`

```
In [63]: 1 ( (3 > 5) or ((3 < 4) and (5 > 4)) ) and not (3 == 5)
```

```
Out[63]: True
```

Logical Operators

- logical operators: `and`, `or`, `not`

```
In [63]: 1 ( (3 > 5) or ((3 < 4) and (5 > 4)) ) and not (3 == 5)
```

```
Out[63]: True
```

- `any ()`: at least one element is true

Logical Operators

- logical operators: `and`, `or`, `not`

```
In [63]: 1 ( (3 > 5) or ((3 < 4) and (5 > 4)) ) and not (3 == 5)
```

```
Out[63]: True
```

- `any()`: at least one element is true

```
In [64]: 1 any([0,0,0])
```

```
Out[64]: False
```

Logical Operators

- logical operators: `and`, `or`, `not`

```
In [63]: 1 ( (3 > 5) or ((3 < 4) and (5 > 4)) ) and not (3 == 5)
```

```
Out[63]: True
```

- `any()`: at least one element is true

```
In [64]: 1 any([0,0,0])
```

```
Out[64]: False
```

- `all()`: all elements are true

Logical Operators

- logical operators: `and`, `or`, `not`

```
In [63]: 1 ( (3 > 5) or ((3 < 4) and (5 > 4)) ) and not (3 == 5)
```

```
Out[63]: True
```

- `any()`: at least one element is true

```
In [64]: 1 any([0,0,0])
```

```
Out[64]: False
```

- `all()`: all elements are true

```
In [65]: 1 all([True,1,False])
```

```
Out[65]: False
```

Logical Operators

- logical operators: `and`, `or`, `not`

```
In [63]: 1 ( (3 > 5) or ((3 < 4) and (5 > 4)) ) and not (3 == 5)
```

```
Out[63]: True
```

- `any()`: at least one element is true

```
In [64]: 1 any([0,0,0])
```

```
Out[64]: False
```

- `all()`: all elements are true

```
In [65]: 1 all([True,1,False])
```

```
Out[65]: False
```

- bitwise operators (we'll see these in numpy and pandas): `&` (and), `|` (or), `~` (not)

Assert

Assert

- use `assert` to test anything we know should be true
- simple unit test
- raises exception when assertion is false, otherwise nothing

Assert

- use `assert` to test anything we know should be true
- simple unit test
- raises exception when assertion is false, otherwise nothing

```
In [66]: 1 assert 2+2 != 4
```

```
-----  
AssertionError                                Traceback (most recent call last)  
Cell In[66], line 1  
----> 1 assert 2+2 != 4  
  
AssertionError:
```

Assert

- use `assert` to test anything we know should be true
- simple unit test
- raises exception when assertion is false, otherwise nothing

```
In [66]: 1 assert 2+2 != 4
```

```
-----  
AssertionError                                Traceback (most recent call last)  
Cell In[66], line 1  
----> 1 assert 2+2 != 4  
  
AssertionError:
```

```
In [67]: 1 assert 1 == 0, 'if this is wrong what you want to display'
```

```
-----  
AssertionError                                Traceback (most recent call last)  
Cell In[67], line 1  
----> 1 assert 1 == 0, 'if this is wrong what you want to display'  
  
AssertionError: if this is wrong what you want to display
```

Assert

- use `assert` to test anything we know should be true
- simple unit test
- raises exception when assertion is false, otherwise nothing

```
In [66]: 1 assert 2+2 != 4
```

```
-----  
AssertionError                                Traceback (most recent call last)  
Cell In[66], line 1  
----> 1 assert 2+2 != 4  
  
AssertionError:
```

```
In [67]: 1 assert 1 == 0, 'if this is wrong what you want to display'
```

```
-----  
AssertionError                                Traceback (most recent call last)  
Cell In[67], line 1  
----> 1 assert 1 == 0, 'if this is wrong what you want to display'  
  
AssertionError: if this is wrong what you want to display
```

```
In [68]: 1 # can add an error message  
2 assert 1 == 0, "1 does not equal 0"
```

```
-----  
AssertionError                                Traceback (most recent call last)  
Cell In[68], line 2
```

Control Flow: **if**, **elif**, **else**

Control Flow: `if`, `elif`, `else`

- `if` then `elif` then `else`

Control Flow: `if`, `elif`, `else`

- `if` then `elif` then `else`

```
In [69]: 1 x = 3
          2 if x > 0:
          3     print('x > 0')
          4 elif x < 0:
          5     print('x < 0')
          6 else:
          7     print('x == 0')
```

x > 0

Control Flow: `if`, `elif`, `else`

- `if` then `elif` then `else`

```
In [69]: 1 x = 3
          2 if x > 0:
          3     print('x > 0')
          4 elif x < 0:
          5     print('x < 0')
          6 else:
          7     print('x == 0')
```

x > 0

- single-line `if` then `else`

Control Flow: `if`, `elif`, `else`

- `if` then `elif` then `else`

```
In [69]: 1 x = 3
          2 if x > 0:
          3     print('x > 0')
          4 elif x < 0:
          5     print('x < 0')
          6 else:
          7     print('x == 0')
```

x > 0

- single-line `if` then `else`

```
In [70]: 1 print("x < 0") if (x < 0) else print("x >= 0")
```

x >= 0

More Control Flow: **for** and **while**

More Control Flow: `for` and `while`

- `for` each element of an iterable: do something

More Control Flow: **for** and **while**

- **for** each element of an iterable: do something

```
In [71]: 1 a = []  
         2 for x in [0,1,2]:  
         3     a.append(x)  
         4 a
```

```
Out[71]: [0, 1, 2]
```

More Control Flow: **for** and **while**

- **for** each element of an iterable: do something

```
In [71]: 1 a = []  
        2 for x in [0,1,2]:  
        3     a.append(x)  
        4 a
```

```
Out[71]: [0, 1, 2]
```

- **while** something is true

More Control Flow: **for** and **while**

- **for** each element of an iterable: do something

```
In [71]: 1 a = []  
        2 for x in [0,1,2]:  
        3     a.append(x)  
        4 a
```

```
Out[71]: [0, 1, 2]
```

- **while** something is true

```
In [72]: 1 x = 0  
        2 while x < 3:  
        3     x += 1  
        4 x
```

```
Out[72]: 3
```

More Control Flow: `break` and `continue`

More Control Flow: `break` and `continue`

- `break` : break out of current loop

More Control Flow: **break** and **continue**

- **break** : break out of current loop

```
In [73]: 1 x = 0
          2 while True:
          3     x += 1
          4     if x == 10:
          5         print(x)
          6         break
```

10

More Control Flow: **break** and **continue**

- **break** : break out of current loop

```
In [73]: 1 x = 0
          2 while True:
          3     x += 1
          4     if x == 10:
          5         print(x)
          6         break
```

10

- **continue** : continue immediately to next iteration of loop

```
In [74]: 1 for name in ['John', 'Ben', 'Julia']:
          2     if name == 'Ben':
          3         continue
          4     print(name)
```

John
Julia

More Control Flow: `break` and `continue`

- `break` : break out of current loop

```
In [73]: 1 x = 0
          2 while True:
          3     x += 1
          4     if x == 10:
          5         print(x)
          6         break
```

10

- `continue` : continue immediately to next iteration of loop

```
In [74]: 1 for name in ['John', 'Ben', 'Julia']:
          2     if name == 'Ben':
          3         continue
          4     print(name)
```

John
Julia

```
In [75]: 1 for x in range(5):
          2     if x == 1:
          3         continue
          4     print(x)
```

0
2
3

Generate a Range of Numbers: `range`

Generate a Range of Numbers: `range`

```
In [76]: 1 # create list of integers from 0 up to but not including 4
          2 a = []
          3 for x in range(4):
          4     a.append(x)
          5 a
```

```
Out[76]: [0, 1, 2, 3]
```

```
In [77]: 1 range(4)
```

```
Out[77]: range(0, 4)
```

Generate a Range of Numbers: `range`

```
In [76]: 1 # create list of integers from 0 up to but not including 4
          2 a = []
          3 for x in range(4):
          4     a.append(x)
          5 a
```

Out[76]: [0, 1, 2, 3]

```
In [77]: 1 range(4)
```

Out[77]: range(0, 4)

```
In [78]: 1 list(range(4))
```

Out[78]: [0, 1, 2, 3]

Generate a Range of Numbers: `range`

```
In [76]: 1 # create list of integers from 0 up to but not including 4
          2 a = []
          3 for x in range(4):
          4     a.append(x)
          5 a
```

```
Out[76]: [0, 1, 2, 3]
```

```
In [77]: 1 range(4)
```

```
Out[77]: range(0, 4)
```

```
In [78]: 1 list(range(4))
```

```
Out[78]: [0, 1, 2, 3]
```

```
In [79]: 1 list(range(3,5)) # with a start and end+1
```

```
Out[79]: [3, 4]
```


Generate a Range of Numbers: `range`

```
In [76]: 1 # create list of integers from 0 up to but not including 4
          2 a = []
          3 for x in range(4):
          4     a.append(x)
          5 a
```

Out[76]: [0, 1, 2, 3]

```
In [77]: 1 range(4)
```

Out[77]: range(0, 4)

```
In [78]: 1 list(range(4))
```

Out[78]: [0, 1, 2, 3]

```
In [79]: 1 list(range(3,5)) # with a start and end+1
```

Out[79]: [3, 4]

```
In [80]: 1 list(range(0,10,2)) # with start, end+1 and step-size
```

Out[80]: [0, 2, 4, 6, 8]

Keep track of list index or for-loop iteration: **enumerate**

Keep track of list index or for-loop iteration: **enumerate**

```
In [81]: 1 for i,x in enumerate(['a','b','c']):  
        2     print(i,x)
```

```
0 a  
1 b  
2 c
```

Keep track of list index or for-loop iteration: **enumerate**

```
In [81]: 1 for i,x in enumerate(['a','b','c']):  
        2     print(i,x)
```

```
0 a  
1 b  
2 c
```

```
In [82]: 1 list(enumerate(['a','b','c']))
```

```
Out[82]: [(0, 'a'), (1, 'b'), (2, 'c')]
```

Sorting

Sorting

Two ways to sort a list:

Sorting

Two ways to sort a list:

1. by changing the list itself: `list.sort()`

Sorting

Two ways to sort a list:

1. by changing the list itself: `list.sort()`

```
In [83]: 1 x = [4,1,2,3]
          2 x.sort()
          3 assert x == [1,2,3,4], 'Not same lists'
```


Sorting

Two ways to sort a list:

1. by changing the list itself: `list.sort()`

```
In [83]: 1 x = [4,1,2,3]
          2 x.sort()
          3 assert x == [1,2,3,4], 'Not same lists'
```

2. without changing the list: `sorted()`

Sorting

Two ways to sort a list:

1. by changing the list itself: `list.sort()`

```
In [83]: 1 x = [4,1,2,3]
          2 x.sort()
          3 assert x == [1,2,3,4], 'Not same lists'
```

2. without changing the list: `sorted()`

```
In [84]: 1 x = [4,1,2,3]
          2 y = sorted(x)
          3 assert x == [4,1,2,3]
          4 assert y == [1,2,3,4]
```

Sorting Cont.

Sorting Cont.

- To sort descending, use `reverse=True`:

Sorting Cont.

- To sort descending, use `reverse=True`:

```
In [85]: 1 assert sorted([1,2,3,4], reverse=True) == [4,3,2,1]
```

Sorting Cont.

- To sort descending, use `reverse=True`:

```
In [85]: 1 assert sorted([1,2,3,4], reverse=True) == [4,3,2,1]
```

- Pass a `lambda` function to 'key=' to specify what to sort by:

Sorting Cont.

- To sort descending, use `reverse=True`:

```
In [85]: 1 assert sorted([1,2,3,4], reverse=True) == [4,3,2,1]
```

- Pass a `lambda` function to 'key=' to specify what to sort by:

```
In [86]: 1 # for example, to sort a dictionary by value
2 d = {'a':3, 'b':5, 'c':1}
3
4 # recall that .items() returns a set of key,value tuples
5 s = sorted(d.items(), key=lambda x: x[1])
6
7 assert s == [('c', 1), ('a', 3), ('b', 5)]
```

```
In [87]: 1 sorted(d.items(), key=lambda x: x[0])
```

```
Out[87]: [('a', 3), ('b', 5), ('c', 1)]
```

List Comprehensions

List Comprehensions

- Like a single line for loop over a list or other iterable

List Comprehensions

- Like a single line for loop over a list or other iterable

```
In [88]: 1 # which integers between 0 and 3 inclusive are divisible by 2?
          2 is_even = []
          3 for x in range(0,4):
          4     is_even.append(x%2 == 0)
          5 is_even
```

```
Out[88]: [True, False, True, False]
```

List Comprehensions

- Like a single line for loop over a list or other iterable

```
In [88]: 1 # which integers between 0 and 3 inclusive are divisible by 2?
          2 is_even = []
          3 for x in range(0,4):
          4     is_even.append(x%2 == 0)
          5 is_even
```

```
Out[88]: [True, False, True, False]
```

```
In [89]: 1 [x%2 == 0 for x in range(0,4)] # using a list comprehension
```

```
Out[89]: [True, False, True, False]
```

List Comprehensions

- Like a single line for loop over a list or other iterable

```
In [88]: 1 # which integers between 0 and 3 inclusive are divisible by 2?
          2 is_even = []
          3 for x in range(0,4):
          4     is_even.append(x%2 == 0)
          5 is_even
```

```
Out[88]: [True, False, True, False]
```

```
In [89]: 1 [x%2 == 0 for x in range(0,4)] # using a list comprehension
```

```
Out[89]: [True, False, True, False]
```

```
In [90]: 1 # what are the indices of the vowels in 'apple'?
          2 vowels = ['a','e','i','o','u']
          3 [i for i,x in enumerate('apple') if x not in vowels]
```

```
Out[90]: [1, 2, 3]
```

Dictionary Comprehension

Dictionary Comprehension

- list comprehension but for (key,value) pairs
- can add logic to dictionary creation

Dictionary Comprehension

- list comprehension but for (key,value) pairs
- can add logic to dictionary creation

```
In [91]: 1 pairs = [(1, 'e'), (2, 'f'), (3, 'g')]
```

Dictionary Comprehension

- list comprehension but for (key,value) pairs
- can add logic to dictionary creation

```
In [91]: 1 pairs = [(1, 'e'), (2, 'f'), (3, 'g')]
```

```
In [92]: 1 dict(pairs)
```

```
Out[92]: {1: 'e', 2: 'f', 3: 'g'}
```


Dictionary Comprehension

- list comprehension but for (key,value) pairs
- can add logic to dictionary creation

```
In [91]: 1 pairs = [(1, 'e'), (2, 'f'), (3, 'g')]
```

```
In [92]: 1 dict(pairs)
```

```
Out[92]: {1: 'e', 2: 'f', 3: 'g'}
```

```
In [93]: 1 # modify value and only include odd keys  
2 {key: 'value_' + val for key, val in pairs if key % 2 == 1}
```

```
Out[93]: {1: 'value_e', 3: 'value_g'}
```

Object Oriented

Object Oriented

```
In [96]: 1 class MyClass:
2         """A descriptive docstring."""
3
4         # constructor
5         def __init__(self, myvalue = 0): # what happens when created
6             # attributes
7             self.myvalue = myvalue
8
9         def __repr__(self): # what gets printed out (string repr.)
10            return f'MyClass(myvalue={self.myvalue})'
11
12        # any other methods
13
14        def get_value(self):
15            """Return the value in myvalue."""
16            return self.myvalue
```

Object Oriented

```
In [96]: 1 class MyClass:
2         """A descriptive docstring."""
3
4         # constructor
5         def __init__(self, myvalue = 0): # what happens when created
6             # attributes
7             self.myvalue = myvalue
8
9         def __repr__(self): # what gets printed out (string repr.)
10            return f'MyClass(myvalue={self.myvalue})'
11
12        # any other methods
13
14        def get_value(self):
15            """Return the value in myvalue."""
16            return self.myvalue
```

```
In [97]: 1 x = MyClass(100) # instantiate object
2
3         assert x.myvalue == 100 # access object attribute
4
5         assert x.get_value() == 100 # use object method
```

Importing Modules

- Want to import a module/library? Use `import`

Importing Modules

- Want to import a module/library? Use `import`

```
In [98]: 1 import math
          2
          3 math.sqrt(2)
```

```
Out[98]: 1.4142135623730951
```

Importing Modules

- Want to import a module/library? Use `import`

```
In [98]: 1 import math
          2
          3 math.sqrt(2)
```

```
Out[98]: 1.4142135623730951
```

- Want to import a submodule or function from a module? Use `from`

Importing Modules

- Want to import a module/library? Use `import`

```
In [98]: 1 import math
          2
          3 math.sqrt(2)
```

```
Out[98]: 1.4142135623730951
```

- Want to import a submodule or function from a module? Use `from`

```
In [99]: 1 from math import sqrt, floor
          2
          3 print(sqrt(2))
          4 print(floor(sqrt(2)))
```

```
1.4142135623730951
1
```


Importing Modules Cont.

- Want to import a module using an alias? Use 'as'

Importing Modules Cont.

- Want to import a module using an alias? Use 'as'

```
In [100]: 1 import math as m  
          2 m.sqrt(2)
```

```
Out[100]: 1.4142135623730951
```

Importing Modules Cont.

- Want to import a module using an alias? Use 'as'

```
In [100]: 1 import math as m
          2 m.sqrt(2)
```

```
Out[100]: 1.4142135623730951
```

- Don't do: `import *`

```
from math import *
```

```
# for example, what if there is a math.print() function?
```

```
# what happens when we then call print()?
```

collections Module

collections Module

```
In [101]: 1 from collections import Counter, defaultdict
```

collections Module

```
In [101]: 1 from collections import Counter, defaultdict
```

- `Counter` : useful for counting hashable objects
- `defaultdict` : create dictionaries without checking keys
- `OrderedDict` : key,value pairs returned in order added
- others : <https://docs.python.org/3.7/library/collections.html>

collections Module: **Counter**

collections Module: Counter

```
In [102]: 1 c = Counter(['red', 'blue', 'red', 'green', 'blue', 'blue'])  
          2 c
```

```
Out[102]: Counter({'red': 2, 'blue': 3, 'green': 1})
```


collections Module: Counter

```
In [102]: 1 c = Counter(['red', 'blue', 'red', 'green', 'blue', 'blue'])
          2 c
```

```
Out[102]: Counter({'red': 2, 'blue': 3, 'green': 1})
```

```
In [103]: 1 c = Counter()
          2 for word in ['red', 'blue', 'red', 'green', 'blue', 'blue']:
          3     c[word] += 1
```

collections Module: Counter

```
In [102]: 1 c = Counter(['red', 'blue', 'red', 'green', 'blue', 'blue'])
          2 c
```

```
Out[102]: Counter({'red': 2, 'blue': 3, 'green': 1})
```

```
In [103]: 1 c = Counter()
          2 for word in ['red', 'blue', 'red', 'green', 'blue', 'blue']:
          3     c[word] += 1
```

```
In [104]: 1 c.most_common()
```

```
Out[104]: [('blue', 3), ('red', 2), ('green', 1)]
```

collections Module Cont. : **defaultdict**

collections Module Cont. : defaultdict

```
In [105]: 1 %xmode Minimal
          2 # reduce the amount printed when an exception is thrown
```

```
Exception reporting mode: Minimal
```

collections Module Cont. : defaultdict

```
In [105]: 1 %xmode Minimal
          2 # reduce the amount printed when an exception is thrown
```

Exception reporting mode: Minimal

```
In [106]: 1 # create mapping from length of word to list of words
          2 colors = ['red', 'blue', 'purple', 'gold', 'orange']
          3 d = {}
          4 for word in colors:
          5     d[len(word)].append(word)
```

KeyError: 3

collections Module Cont. : defaultdict

```
In [105]: 1 %xmode Minimal
          2 # reduce the amount printed when an exception is thrown
```

Exception reporting mode: Minimal

```
In [106]: 1 # create mapping from length of word to list of words
          2 colors = ['red', 'blue', 'purple', 'gold', 'orange']
          3 d = {}
          4 for word in colors:
          5     d[len(word)].append(word)
```

KeyError: 3

```
In [107]: 1 d = {}
          2 for word in colors:
          3     if len(word) in d:
          4         d[len(word)].append(word)
          5     else:
          6         d[len(word)] = [word]
          7 d
```

```
Out[107]: {3: ['red'], 4: ['blue', 'gold'], 6: ['purple', 'orange']}
```

collections Module Cont. : defaultdict

```
In [105]: 1 %xmode Minimal
          2 # reduce the amount printed when an exception is thrown
```

Exception reporting mode: Minimal

```
In [106]: 1 # create mapping from length of word to list of words
          2 colors = ['red', 'blue', 'purple', 'gold', 'orange']
          3 d = {}
          4 for word in colors:
          5     d[len(word)].append(word)
```

KeyError: 3

```
In [107]: 1 d = {}
          2 for word in colors:
          3     if len(word) in d:
          4         d[len(word)].append(word)
          5     else:
          6         d[len(word)] = [word]
          7 d
```

Out[107]: {3: ['red'], 4: ['blue', 'gold'], 6: ['purple', 'orange']}

```
In [108]: 1 d = defaultdict(list)
          2 for word in colors:
          3     d[len(word)].append(word)
          4 d
```

Out[108]: defaultdict(list, {3: ['red'], 4: ['blue', 'gold'], 6: ['purple', 'orange']})

collections Module Cont. : defaultdict

```
In [105]: 1 %xmode Minimal
          2 # reduce the amount printed when an exception is thrown
```

Exception reporting mode: Minimal

```
In [106]: 1 # create mapping from length of word to list of words
          2 colors = ['red', 'blue', 'purple', 'gold', 'orange']
          3 d = {}
          4 for word in colors:
          5     d[len(word)].append(word)
```

KeyError: 3

```
In [107]: 1 d = {}
          2 for word in colors:
          3     if len(word) in d:
          4         d[len(word)].append(word)
          5     else:
          6         d[len(word)] = [word]
          7 d
```

Out[107]: {3: ['red'], 4: ['blue', 'gold'], 6: ['purple', 'orange']}

```
In [108]: 1 d = defaultdict(list)
          2 for word in colors:
          3     d[len(word)].append(word)
          4 d
```

Out[108]: defaultdict(list, {3: ['red'], 4: ['blue', 'gold'], 6: ['purple', 'orange']})

Contexts

Contexts

- a context is like applying a scope with helper functions
- For example: open and write to a file

Contexts

- a context is like applying a scope with helper functions
- For example: open and write to a file

```
In [110]: 1 with open('tmp_context_example.txt', 'w') as f:  
          2     f.write('test')
```

Contexts

- a context is like applying a scope with helper functions
- For example: open and write to a file

```
In [110]: 1 with open('tmp_context_example.txt', 'w') as f:
          2     f.write('test')
```

```
In [111]: 1 # instead of
          2 f = open('tmp_context_example.txt', 'w')
          3 f.write('test')
          4 f.close() # this is easy to forget to do
```

Contexts

- a context is like applying a scope with helper functions
- For example: open and write to a file

```
In [110]: 1 with open('tmp_context_example.txt', 'w') as f:
          2     f.write('test')
```

```
In [111]: 1 # instead of
          2 f = open('tmp_context_example.txt', 'w')
          3 f.write('test')
          4 f.close() # this is easy to forget to do
```

```
In [112]: 1 # remove the example file we just created
          2 %rm tmp_context_example.txt
```

Python (Review?)

- Dynamic Typing
- Whitespace Formatting
- Basic Data Types
- Functions
- String Formatting
- Exceptions and Try-Except
- Truthiness
- Comparisons and Logical Operators
- Control Flow
- Assert
- Sorting
- List/Dict Comprehensions
- Importing Modules
- collections Module
- Object Oriented Programming

Questions?

Working with Data

Working with Data

Want to:

- transform and select data quickly (numpy)
- manipulate datasets: load, save, group, join, etc. (pandas)
- keep things organized (pandas)

Intro to NumPy

Intro to NumPy



Provides (from numpy.org):

- a powerful N-dimensional array object
- sophisticated (broadcasting) functions
- linear algebra and random number capabilities
- (Fourier transform, tools for integrating C/C++ and Fortran code, etc.)

Python Dynamic Typing

Python Dynamic Typing

```
In [113]: 1 x = 5  
          2 x = 'five'
```

Python Dynamic Typing

```
In [113]: 1 x = 5  
          2 x = 'five'
```

- Note: still **strongly** typed
- Python is both a strongly typed and a dynamically typed language. Strong typing means that variables do have a type and that the type matters when performing operations on a variable. Dynamic typing means that the type of the variable is determined only during runtime.

Python Dynamic Typing

```
In [113]: 1 x = 5  
          2 x = 'five'
```

- Note: still **strongly** typed


- Python is both a strongly typed and a dynamically typed language. Strong typing means that variables do have a type and that the type matters when performing operations on a variable. Dynamic typing means that the type of the variable is determined only during runtime.

```
In [114]: 1 x,y = 5, 'five'  
          2 x+y
```

```
TypeError: unsupported operand type(s) for +: 'int' and 'str'
```

Python Dynamic Typing

Python Dynamic Typing



[PDHS Chap 2.](<https://jakevdp.github.io/PythonDataScienceHandbook/02.01-understanding-data-types.html>)


- A C integer is essentially a label for a position in memory whose bytes encode an integer value.
- A Python integer is a pointer to a position in memory containing all the Python object information, including the bytes that contain the integer value.
 - **ob_refcnt**, a reference count that helps Python silently handle memory allocation and deallocation
 - **ob_type**, which encodes the type of the variable
 - **ob_size**, which specifies the size
 - **ob_digit**, which contains the actual integer value that we expect the Python variable to

NumPy Array vs Python List

- The NumPy array essentially contains a single pointer to one contiguous block of data.
- The Python list, on the other hand, contains a pointer to a block of pointers, each of which in turn points to a full Python object like the Python integer we saw earlier.
- The advantage of the list is flexibility: because each list element is a full structure containing both data and type information, the list can be filled with data of any desired type. Fixed-type NumPy-style arrays lack this flexibility, but are much more efficient for storing and manipulating data.

NumPy Array vs Python List

- The NumPy array essentially contains a single pointer to one contiguous block of data.
- The Python list, on the other hand, contains a pointer to a block of pointers, each of which in turn points to a full Python object like the Python integer we saw earlier.
- The advantage of the list is flexibility: because each list element is a full structure containing both data and type information, the list can be filled with data of any desired type. Fixed-type NumPy-style arrays lack this flexibility, but are much more efficient for storing and manipulating data.



Importing NumPy

Importing NumPy

Often imported as alias `np`

```
In [115]: 1 a = 10
```

```
In [116]: 1 a??
```

Importing NumPy

Often imported as alias `np`

```
In [115]: 1 a = 10
```

```
In [116]: 1 a??
```

```
In [117]: 1 import numpy as np
          2
          3 np.random.randint(10,size=5)
```

```
Out[117]: array([0, 3, 8, 0, 9])
```

NumPy Datatypes

NumPy Datatypes

<code>bool_</code>	Boolean (True or False) stored as a byte
<code>int_</code>	Default integer type (same as C long; normally either int64 or int32)
<code>intc</code>	Identical to C int (normally int32 or int64)
<code>intp</code>	Integer used for indexing (same as C ssize_t; normally either int32 or int64)
<code>int8</code>	Byte (-128 to 127)
<code>int16</code>	Integer (-32768 to 32767)
<code>int32</code>	Integer (-2147483648 to 2147483647)
<code>int64</code>	Integer (-9223372036854775808 to 9223372036854775807)
<code>uint8</code>	Unsigned integer (0 to 255)
<code>uint16</code>	Unsigned integer (0 to 65535)
<code>uint32</code>	Unsigned integer (0 to 4294967295)
<code>uint64</code>	Unsigned integer (0 to 18446744073709551615)
<code>float_</code>	Shorthand for float64.
<code>float16</code>	Half precision float: sign bit, 5 bits exponent, 10 bits mantissa
<code>float32</code>	Single precision float: sign bit, 8 bits exponent, 23 bits mantissa
<code>float64</code>	Double precision float: sign bit, 11 bits exponent, 52 bits mantissa
<code>complex_</code>	Shorthand for complex128.
<code>complex64</code>	Complex number, represented by two 32-bit floats
<code>complex128</code>	Complex number, represented by two 64-bit floats

NumPy Arrays

NumPy Arrays

```
In [118]: 1 x = np.array([1,2,3])  
          2 x
```

```
Out[118]: array([1, 2, 3])
```

NumPy Arrays

```
In [118]: 1 x = np.array([1,2,3])  
          2 x
```

```
Out[118]: array([1, 2, 3])
```

```
In [119]: 1 type(x)
```

```
Out[119]: numpy.ndarray
```

NumPy Arrays

```
In [118]: 1 x = np.array([1,2,3])  
          2 x
```

```
Out[118]: array([1, 2, 3])
```

```
In [119]: 1 type(x)
```

```
Out[119]: numpy.ndarray
```

```
In [120]: 1 # use dtype to show the datatype of the array  
          2 x.dtype
```

```
Out[120]: dtype('int64')
```

NumPy Arrays

```
In [118]: 1 x = np.array([1,2,3])  
          2 x
```

```
Out[118]: array([1, 2, 3])
```

```
In [119]: 1 type(x)
```

```
Out[119]: numpy.ndarray
```

```
In [120]: 1 # use dtype to show the datatype of the array  
          2 x.dtype
```

```
Out[120]: dtype('int64')
```

```
In [121]: 1 # np arrays can only contain one datatype and default to the most flexible type  
          2 x = np.array([1,'two',3])  
          3 x
```

```
Out[121]: array(['1', 'two', '3'], dtype='<U21')
```

NumPy Arrays

```
In [118]: 1 x = np.array([1,2,3])  
          2 x
```

```
Out[118]: array([1, 2, 3])
```

```
In [119]: 1 type(x)
```

```
Out[119]: numpy.ndarray
```

```
In [120]: 1 # use dtype to show the datatype of the array  
          2 x.dtype
```

```
Out[120]: dtype('int64')
```

```
In [121]: 1 # np arrays can only contain one datatype and default to the most flexible type  
          2 x = np.array([1,'two',3])  
          3 x
```

```
Out[121]: array(['1', 'two', '3'], dtype='<U21')
```

```
In [122]: 1 x.dtype
```

```
Out[122]: dtype('<U21')
```

NumPy Arrays

```
In [118]: 1 x = np.array([1,2,3])  
          2 x
```

```
Out[118]: array([1, 2, 3])
```

```
In [119]: 1 type(x)
```

```
Out[119]: numpy.ndarray
```

```
In [120]: 1 # use dtype to show the datatype of the array  
          2 x.dtype
```

```
Out[120]: dtype('int64')
```

```
In [121]: 1 # np arrays can only contain one datatype and default to the most flexible type  
          2 x = np.array([1,'two',3])  
          3 x
```

```
Out[121]: array(['1', 'two', '3'], dtype='<U21')
```

```
In [122]: 1 x.dtype
```

```
Out[122]: dtype('<U21')
```

```
In [123]: 1 # many different ways to create numpy arrays  
          2 np.zeros(5,dtype=float)
```

```
Out[123]: array([0., 0., 0., 0., 0.])
```

NumPy Array Indexing

NumPy Array Indexing

- For single indices, works the same as list

NumPy Array Indexing

- For single indices, works the same as list

```
In [124]: 1 x = np.arange(1,6)
          2 x
```

```
Out[124]: array([1, 2, 3, 4, 5])
```

NumPy Array Indexing

- For single indices, works the same as list

```
In [124]: 1 x = np.arange(1,6)
          2 x
```

```
Out[124]: array([1, 2, 3, 4, 5])
```

```
In [125]: 1 x[0], x[-1], x[-2], x[-4]
```

```
Out[125]: (1, 5, 4, 2)
```

NumPy Array Slicing

NumPy Array Slicing

```
In [126]: 1 x = np.arange(5) # note that in numpy it's arange instead of range
          2 x
```

```
Out[126]: array([0, 1, 2, 3, 4])
```

NumPy Array Slicing

```
In [126]: 1 x = np.arange(5) # note that in numpy it's arange instead of range
          2 x
```

```
Out[126]: array([0, 1, 2, 3, 4])
```

```
In [127]: 1 # return first two items, start:end (exclusive)
          2 x[0:2]
```

```
Out[127]: array([0, 1])
```

NumPy Array Slicing

```
In [126]: 1 x = np.arange(5) # note that in numpy it's arange instead of range
          2 x
```

```
Out[126]: array([0, 1, 2, 3, 4])
```

```
In [127]: 1 # return first two items, start:end (exclusive)
          2 x[0:2]
```

```
Out[127]: array([0, 1])
```

```
In [128]: 1 # missing start implies position 0
          2 x[:4]
```

```
Out[128]: array([0, 1, 2, 3])
```

NumPy Array Slicing

```
In [126]: 1 x = np.arange(5) # note that in numpy it's arange instead of range
          2 x
```

```
Out[126]: array([0, 1, 2, 3, 4])
```

```
In [127]: 1 # return first two items, start:end (exclusive)
          2 x[0:2]
```

```
Out[127]: array([0, 1])
```

```
In [128]: 1 # missing start implies position 0
          2 x[:4]
```

```
Out[128]: array([0, 1, 2, 3])
```

```
In [129]: 1 # missing end implies length of array
          2 x[2:]
```

```
Out[129]: array([2, 3, 4])
```


NumPy Array Slicing

```
In [126]: 1 x = np.arange(5) # note that in numpy it's arange instead of range
          2 x
```

```
Out[126]: array([0, 1, 2, 3, 4])
```

```
In [127]: 1 # return first two items, start:end (exclusive)
          2 x[0:2]
```

```
Out[127]: array([0, 1])
```

```
In [128]: 1 # missing start implies position 0
          2 x[:4]
```

```
Out[128]: array([0, 1, 2, 3])
```

```
In [129]: 1 # missing end implies length of array
          2 x[2:]
```

```
Out[129]: array([2, 3, 4])
```

```
In [130]: 1 # return last two items
          2 x[-3:]
```

```
Out[130]: array([2, 3, 4])
```

NumPy Array Slicing with Steps

NumPy Array Slicing with Steps

```
In [131]: 1 x
```

```
Out[131]: array([0, 1, 2, 3, 4])
```

NumPy Array Slicing with Steps

```
In [131]: 1 x
```

```
Out[131]: array([0, 1, 2, 3, 4])
```

```
In [132]: 1 # return every other item from position 1 to 4 exclusive  
          2 # start:end:step_size  
          3 x[1:4:1]
```

```
Out[132]: array([1, 2, 3])
```

Reverse array with step-size of -1

Reverse array with step-size of -1

```
In [133]: 1 x
```

```
Out[133]: array([0, 1, 2, 3, 4])
```

Reverse array with step-size of -1

```
In [133]: 1 x
```

```
Out[133]: array([0, 1, 2, 3, 4])
```

```
In [134]: 1 x[::-1]
```

```
Out[134]: array([4, 3, 2, 1, 0])
```

NumPy Fancy Indexing

NumPy Fancy Indexing

- Accessing multiple, non-consecutive indices at once using a list

NumPy Fancy Indexing

- Accessing multiple, non-consecutive indices at once using a list

```
In [135]: 1 x = np.arange(5,10)
          2 x
```

```
Out[135]: array([5, 6, 7, 8, 9])
```

NumPy Fancy Indexing

- Accessing multiple, non-consecutive indices at once using a list

```
In [135]: 1 x = np.arange(5,10)
          2 x
```

```
Out[135]: array([5, 6, 7, 8, 9])
```

```
In [136]: 1 x[[0,3]]
```

```
Out[136]: array([5, 8])
```

NumPy Fancy Indexing

- Accessing multiple, non-consecutive indices at once using a list

```
In [135]: 1 x = np.arange(5,10)
          2 x
```

```
Out[135]: array([5, 6, 7, 8, 9])
```

```
In [136]: 1 x[[0,3]]
```

```
Out[136]: array([5, 8])
```

```
In [137]: 1 x[[0,2,-1]]
          2
```

```
Out[137]: array([5, 7, 9])
```

Boolean Indexing using a Boolean Mask

Boolean Indexing using a Boolean Mask

```
In [138]:
```

```
1 x
```

```
Out[138]: array([5, 6, 7, 8, 9])
```

Boolean Indexing using a Boolean Mask

```
In [138]: 1 x
```

```
Out[138]: array([5, 6, 7, 8, 9])
```

```
In [139]: 1 # Which indices have a value divisible by 2?  
2 # mod operator % returns remainder of division  
3 x%2 == 0
```

```
Out[139]: array([False,  True, False,  True, False])
```

Boolean Indexing using a Boolean Mask

```
In [138]: 1 x
```

```
Out[138]: array([5, 6, 7, 8, 9])
```

```
In [139]: 1 # Which indices have a value divisible by 2?
          2 # mod operator % returns remainder of division
          3 x%2 == 0
```

```
Out[139]: array([False,  True, False,  True, False])
```

```
In [140]: 1 # Which values are divisible by 2?
          2 x[x%2 == 0]
```

```
Out[140]: array([6, 8])
```


Boolean Indexing using a Boolean Mask

```
In [138]: 1 x
```

```
Out[138]: array([5, 6, 7, 8, 9])
```

```
In [139]: 1 # Which indices have a value divisible by 2?
          2 # mod operator % returns remainder of division
          3 x%2 == 0
```

```
Out[139]: array([False,  True, False,  True, False])
```

```
In [140]: 1 # Which values are divisible by 2?
          2 x[x%2 == 0]
```

```
Out[140]: array([6, 8])
```

```
In [141]: 1 # Which values are greater than 6?
          2 x[x >= 2]
```

```
Out[141]: array([5, 6, 7, 8, 9])
```

Boolean Indexing And Bitwise Operators

Boolean Indexing And Bitwise Operators

```
In [142]: 1 x
```

```
Out[142]: array([5, 6, 7, 8, 9])
```

Boolean Indexing And Bitwise Operators

```
In [142]: 1 x
```

```
Out[142]: array([5, 6, 7, 8, 9])
```

```
In [143]: 1 (x%2 == 0)
```

```
Out[143]: array([False,  True, False,  True, False])
```

Boolean Indexing And Bitwise Operators

```
In [142]: 1 x
```

```
Out[142]: array([5, 6, 7, 8, 9])
```

```
In [143]: 1 (x%2 == 0)
```

```
Out[143]: array([False,  True, False,  True, False])
```

```
In [144]: 1 (x > 6)
```

```
Out[144]: array([False, False,  True,  True,  True])
```

Boolean Indexing And Bitwise Operators

```
In [142]: 1 x
```

```
Out[142]: array([5, 6, 7, 8, 9])
```

```
In [143]: 1 (x%2 == 0)
```

```
Out[143]: array([False,  True, False,  True, False])
```

```
In [144]: 1 (x > 6)
```

```
Out[144]: array([False, False,  True,  True,  True])
```

```
In [145]: 1 # Which values are divisible by 2 AND greater than 6?  
2 # 'and' expects both elements to be boolean, not arrays of booleans!  
3 (x%2 == 0) and (x > 6)
```

```
ValueError: The truth value of an array with more than one element is ambiguous. Use a.any() or a.all()
```

Boolean Indexing And Bitwise Operators

```
In [142]: 1 x
```

```
Out[142]: array([5, 6, 7, 8, 9])
```

```
In [143]: 1 (x%2 == 0)
```

```
Out[143]: array([False,  True, False,  True, False])
```

```
In [144]: 1 (x > 6)
```

```
Out[144]: array([False, False,  True,  True,  True])
```

```
In [145]: 1 # Which values are divisible by 2 AND greater than 6?  
2 # 'and' expects both elements to be boolean, not arrays of booleans!  
3 (x%2 == 0) and (x > 6)
```

```
ValueError: The truth value of an array with more than one element is ambiguous. Use a.any() or a.all()
```

```
In [146]: 1 # & compares each element pairwise  
2 (x%2 == 0) & (x > 6)
```

```
Out[146]: array([False, False, False,  True, False])
```

```
In [147]: 1 x[np.array([False, False, False,  True, False])]
```

```
Out[147]: array([8])
```

Boolean Indexing And Bitwise Operators

```
In [142]: 1 x
```

```
Out[142]: array([5, 6, 7, 8, 9])
```

```
In [143]: 1 (x%2 == 0)
```

```
Out[143]: array([False,  True, False,  True, False])
```

```
In [144]: 1 (x > 6)
```

```
Out[144]: array([False, False,  True,  True,  True])
```

```
In [145]: 1 # Which values are divisible by 2 AND greater than 6?  
2 # 'and' expects both elements to be boolean, not arrays of booleans!  
3 (x%2 == 0) and (x > 6)
```

```
ValueError: The truth value of an array with more than one element is ambiguous. Use a.any() or a.all()
```

```
In [146]: 1 # & compares each element pairwise  
2 (x%2 == 0) & (x > 6)
```

```
Out[146]: array([False, False, False,  True, False])
```

```
In [147]: 1 x[np.array([False, False, False,  True, False])]
```

```
Out[147]: array([8])
```

```
In [148]: 1 x[(x%2 == 0) & (x > 6)]
```

```
Out[148]: array([8])
```


Boolean Indexing And Bitwise Operators

Boolean Indexing And Bitwise Operators

- and : `&` (ampersand)

Boolean Indexing And Bitwise Operators

- and : `&` (ampersand)

```
In [149]: 1 # Which values are even AND greater than 6?
          2 x[(x%2 == 0) & (x > 6)]
```

```
Out[149]: array([8])
```

Boolean Indexing And Bitwise Operators

- and : `&` (ampersand)

```
In [149]: 1 # Which values are even AND greater than 6?
          2 x[(x%2 == 0) & (x > 6)]
```

```
Out[149]: array([8])
```

- or : `|` (pipe)

Boolean Indexing And Bitwise Operators

- and : `&` (ampersand)

```
In [149]: 1 # Which values are even AND greater than 6?
          2 x[(x%2 == 0) & (x > 6)]
```

```
Out[149]: array([8])
```

- or : `|` (pipe)

```
In [150]: 1 # which values are even OR greater than 6?
          2 x[(x%2 == 0) | (x > 6)]
```

```
Out[150]: array([6, 7, 8, 9])
```

Boolean Indexing And Bitwise Operators

- and: `&` (ampersand)

```
In [149]: 1 # Which values are even AND greater than 6?
          2 x[(x%2 == 0) & (x > 6)]
```

```
Out[149]: array([8])
```

- or: `|` (pipe)

```
In [150]: 1 # which values are even OR greater than 6?
          2 x[(x%2 == 0) | (x > 6)]
```

```
Out[150]: array([6, 7, 8, 9])
```

- not: `~` (tilde)

```
In [151]: 1 ( (x%2 == 0) | (x > 6) )
```

```
Out[151]: array([False,  True,  True,  True,  True])
```

```
In [152]: 1 ~( (x%2 == 0) | (x > 6) )
```

```
Out[152]: array([ True, False, False, False, False])
```

Boolean Indexing And Bitwise Operators

- and: `&` (ampersand)

```
In [149]: 1 # Which values are even AND greater than 6?
          2 x[(x%2 == 0) & (x > 6)]
```

```
Out[149]: array([8])
```

- or: `|` (pipe)

```
In [150]: 1 # which values are even OR greater than 6?
          2 x[(x%2 == 0) | (x > 6)]
```

```
Out[150]: array([6, 7, 8, 9])
```

- not: `~` (tilde)

```
In [151]: 1 ( (x%2 == 0) | (x > 6) )
```

```
Out[151]: array([False,  True,  True,  True,  True])
```

```
In [152]: 1 ~( (x%2 == 0) | (x > 6) )
```

```
Out[152]: array([ True, False, False, False, False])
```

```
In [153]: 1 # which values are NOT (even OR greater than 6)
          2 x[~( (x%2 == 0) | (x > 6) )]
```

Boolean Indexing And Bitwise Operators

- and: `&` (ampersand)

```
In [149]: 1 # Which values are even AND greater than 6?
          2 x[(x%2 == 0) & (x > 6)]
```

```
Out[149]: array([8])
```

- or: `|` (pipe)

```
In [150]: 1 # which values are even OR greater than 6?
          2 x[(x%2 == 0) | (x > 6)]
```

```
Out[150]: array([6, 7, 8, 9])
```

- not: `~` (tilde)

```
In [151]: 1 ( (x%2 == 0) | (x > 6) )
```

```
Out[151]: array([False,  True,  True,  True,  True])
```

```
In [152]: 1 ~( (x%2 == 0) | (x > 6) )
```

```
Out[152]: array([ True, False, False, False, False])
```

```
In [153]: 1 # which values are NOT (even OR greater than 6)
          2 x[~( (x%2 == 0) | (x > 6) )]
```


Indexing Review

Indexing Review

- standard array indexing (including reverse/negative)
- slicing [start:end:step-size]
- fancy indexing (list/array of indices)
- boolean indexing (list/array of booleans)

Multidimensional Lists

Multidimensional Lists

```
In [154]: 1 x = [[1,2,3],[4,5,6]] # list of lists  
          2 x
```

```
Out[154]: [[1, 2, 3], [4, 5, 6]]
```

Multidimensional Lists

```
In [154]: 1 x = [[1,2,3],[4,5,6]] # list of lists  
          2 x
```

```
Out[154]: [[1, 2, 3], [4, 5, 6]]
```

```
In [155]: 1 # return first row  
          2 x[0]
```

```
Out[155]: [1, 2, 3]
```

Multidimensional Lists

```
In [154]: 1 x = [[1,2,3],[4,5,6]] # list of lists  
          2 x
```

```
Out[154]: [[1, 2, 3], [4, 5, 6]]
```

```
In [155]: 1 # return first row  
          2 x[0]
```

```
Out[155]: [1, 2, 3]
```

```
In [156]: 1 # return first row, second column  
          2 x[1][2]
```

```
Out[156]: 6
```

Multidimensional Lists

```
In [154]: 1 x = [[1,2,3],[4,5,6]] # list of lists  
          2 x
```

```
Out[154]: [[1, 2, 3], [4, 5, 6]]
```

```
In [155]: 1 # return first row  
          2 x[0]
```

```
Out[155]: [1, 2, 3]
```

```
In [156]: 1 # return first row, second column  
          2 x[1][2]
```

```
Out[156]: 6
```

```
In [157]: 1 # return second column?  
          2 [row[1] for row in x]
```

```
Out[157]: [2, 5]
```

NumPy Multidimensional Arrays

NumPy Multidimensional Arrays

```
In [158]: 1 x = np.array([[1,2,3],[4,5,6]])  
          2 x
```

```
Out[158]: array([[1, 2, 3],  
                 [4, 5, 6]])
```

NumPy Multidimensional Arrays

```
In [158]: 1 x = np.array([[1,2,3],[4,5,6]])  
          2 x
```

```
Out[158]: array([[1, 2, 3],  
                [4, 5, 6]])
```

```
In [159]: 1 x[0,1] # first row, second column
```

```
Out[159]: 2
```

NumPy Multidimensional Arrays

```
In [158]: 1 x = np.array([[1,2,3],[4,5,6]])  
          2 x
```

```
Out[158]: array([[1, 2, 3],  
                [4, 5, 6]])
```

```
In [159]: 1 x[0,1] # first row, second column
```

```
Out[159]: 2
```

```
In [160]: 1 x[:,1] # first row
```

```
Out[160]: array([2, 5])
```

NumPy Multidimensional Arrays

```
In [158]: 1 x = np.array([[1,2,3],[4,5,6]])  
          2 x
```

```
Out[158]: array([[1, 2, 3],  
                [4, 5, 6]])
```

```
In [159]: 1 x[0,1] # first row, second column
```

```
Out[159]: 2
```

```
In [160]: 1 x[:,1] # first row
```

```
Out[160]: array([2, 5])
```

```
In [161]: 1 x[0,:] # first row (first to last column)
```

```
Out[161]: array([1, 2, 3])
```

NumPy Multidimensional Arrays

```
In [158]: 1 x = np.array([[1,2,3],[4,5,6]])  
          2 x
```

```
Out[158]: array([[1, 2, 3],  
                [4, 5, 6]])
```

```
In [159]: 1 x[0,1] # first row, second column
```

```
Out[159]: 2
```

```
In [160]: 1 x[:,1] # first row
```

```
Out[160]: array([2, 5])
```

```
In [161]: 1 x[0,:] # first row (first to last column)
```

```
Out[161]: array([1, 2, 3])
```

```
In [162]: 1 x[:,1] # second column (first to last row)
```

```
Out[162]: array([2, 5])
```

NumPy Array Attributes

NumPy Array Attributes

```
In [163]: 1 x = np.array([[1,2,3],[4,5,6]])
```

NumPy Array Attributes

```
In [163]: 1 x = np.array([[1,2,3],[4,5,6]])
```

```
In [164]: 1 x.ndim # number of dimensions
```

```
Out[164]: 2
```


NumPy Array Attributes

```
In [163]: 1 x = np.array([[1,2,3],[4,5,6]])
```

```
In [164]: 1 x.ndim # number of dimensions
```

```
Out[164]: 2
```

```
In [165]: 1 x.shape # shape in each dimension
```

```
Out[165]: (2, 3)
```

NumPy Array Attributes

```
In [163]: 1 x = np.array([[1,2,3],[4,5,6]])
```

```
In [164]: 1 x.ndim # number of dimensions
```

```
Out[164]: 2
```

```
In [165]: 1 x.shape # shape in each dimension
```

```
Out[165]: (2, 3)
```

```
In [166]: 1 x.size # total number of elements
```

```
Out[166]: 6
```

NumPy Operations (UFuncs)

NumPy Operations (UFuncs)

```
In [167]: 1 x = [1, 2, 3]
          2 y = [4, 5, 6]
```

NumPy Operations (UFuncs)

```
In [167]: 1 x = [1,2,3]
          2 y = [4,5,6]
```

```
In [168]: 1 x+y
```

```
Out[168]: [1, 2, 3, 4, 5, 6]
```

NumPy Operations (UFuncs)

```
In [167]: 1 x = [1,2,3]
          2 y = [4,5,6]
```

```
In [168]: 1 x+y
```

```
Out[168]: [1, 2, 3, 4, 5, 6]
```

```
In [169]: 1 x = np.array([1,2,3])
          2 y = np.array([4,5,6])
```

NumPy Operations (UFuncs)

```
In [167]: 1 x = [1,2,3]
          2 y = [4,5,6]
```

```
In [168]: 1 x+y
```

```
Out[168]: [1, 2, 3, 4, 5, 6]
```

```
In [169]: 1 x = np.array([1,2,3])
          2 y = np.array([4,5,6])
```

```
In [170]: 1 x+y
```

```
Out[170]: array([5, 7, 9])
```

NumPy Operations (UFuncs)

```
In [167]: 1 x = [1,2,3]
          2 y = [4,5,6]
```

```
In [168]: 1 x+y
```

```
Out[168]: [1, 2, 3, 4, 5, 6]
```

```
In [169]: 1 x = np.array([1,2,3])
          2 y = np.array([4,5,6])
```

```
In [170]: 1 x+y
```

```
Out[170]: array([5, 7, 9])
```

```
In [171]: 1 %time sum(range(0,int(1e8)))
```

```
CPU times: user 1.38 s, sys: 5.57 ms, total: 1.39 s
Wall time: 1.38 s
```

```
Out[171]: 4999999950000000
```


NumPy Operations (UFuncs)

```
In [167]: 1 x = [1,2,3]
          2 y = [4,5,6]
```

```
In [168]: 1 x+y
```

```
Out[168]: [1, 2, 3, 4, 5, 6]
```

```
In [169]: 1 x = np.array([1,2,3])
          2 y = np.array([4,5,6])
```

```
In [170]: 1 x+y
```

```
Out[170]: array([5, 7, 9])
```

```
In [171]: 1 %time sum(range(0,int(1e8)))
```

```
CPU times: user 1.38 s, sys: 5.57 ms, total: 1.39 s
Wall time: 1.38 s
```

```
Out[171]: 4999999950000000
```

```
In [172]: 1 %time np.arange(0,int(1e8)).sum()
```

```
CPU times: user 289 ms, sys: 278 ms, total: 568 ms
Wall time: 591 ms
```

```
Out[172]: 4999999950000000
```

NumPy Broadcasting

NumPy Broadcasting

Allows for vectorized computation on arrays of different sizes

NumPy Broadcasting

Allows for vectorized computation on arrays of different sizes

```
In [173]: 1 # square every element in a list  
          2 x = [1,2,3]
```

NumPy Broadcasting

Allows for vectorized computation on arrays of different sizes

```
In [173]: 1 # square every element in a list  
          2 x = [1,2,3]
```

```
In [174]: 1 x**2
```

```
TypeError: unsupported operand type(s) for ** or pow(): 'list' and 'int'
```

NumPy Broadcasting

Allows for vectorized computation on arrays of different sizes

```
In [173]: 1 # square every element in a list  
          2 x = [1,2,3]
```

```
In [174]: 1 x**2
```

TypeError: unsupported operand type(s) for ** or pow(): 'list' and 'int'

```
In [175]: 1 # square every element in a numpy array  
          2 x = np.array([1,2,3])
```

NumPy Broadcasting

Allows for vectorized computation on arrays of different sizes

```
In [173]: 1 # square every element in a list  
          2 x = [1,2,3]
```

```
In [174]: 1 x**2
```

```
TypeError: unsupported operand type(s) for ** or pow(): 'list' and 'int'
```

```
In [175]: 1 # square every element in a numpy array  
          2 x = np.array([1,2,3])
```

```
In [176]: 1 x**2
```

```
Out[176]: array([1, 4, 9])
```

NumPy Broadcasting

Allows for vectorized computation on arrays of different sizes

```
In [173]: 1 # square every element in a list  
          2 x = [1,2,3]
```

```
In [174]: 1 x**2
```

TypeError: unsupported operand type(s) for ** or pow(): 'list' and 'int'

```
In [175]: 1 # square every element in a numpy array  
          2 x = np.array([1,2,3])
```

```
In [176]: 1 x**2
```

Out[176]: array([1, 4, 9])

```
In [177]: 1 a = np.array([1.0, 2.0, 3.0])  
          2 b = 2.0  
          3 a * b
```

Out[177]: array([2., 4., 6.])

NumPy Broadcasting

Allows for vectorized computation on arrays of different sizes

```
In [173]: 1 # square every element in a list
          2 x = [1,2,3]
```

```
In [174]: 1 x**2
```

TypeError: unsupported operand type(s) for ** or pow(): 'list' and 'int'

```
In [175]: 1 # square every element in a numpy array
          2 x = np.array([1,2,3])
```

```
In [176]: 1 x**2
```

Out[176]: array([1, 4, 9])

```
In [177]: 1 a = np.array([1.0, 2.0, 3.0])
          2 b = 2.0
          3 a * b
```

Out[177]: array([2., 4., 6.])

is equivalent to

NumPy Broadcasting

Allows for vectorized computation on arrays of different sizes

```
In [173]: 1 # square every element in a list  
          2 x = [1,2,3]
```

```
In [174]: 1 x**2
```

TypeError: unsupported operand type(s) for ** or pow(): 'list' and 'int'

```
In [175]: 1 # square every element in a numpy array  
          2 x = np.array([1,2,3])
```

```
In [176]: 1 x**2
```

Out[176]: array([1, 4, 9])

```
In [177]: 1 a = np.array([1.0, 2.0, 3.0])  
          2 b = 2.0  
          3 a * b
```

Out[177]: array([2., 4., 6.])

is equivalent to

NumPy **random** Submodule

NumPy **random** Submodule

Provides many random sampling functions

```
In [179]: 1 from numpy.random import seed, randn
```

```
In [180]: 1 seed(1991)
```

```
In [181]: 1 randn(10)
```

```
Out[181]: array([-0.94343179,  0.04928867, -1.28887945, -0.12919796,  0.73604408,  
                -0.27182505, -0.22028639, -0.2412858 ,  0.78027846, -0.95460321])
```

NumPy `random` Submodule

Provides many random sampling functions

```
In [179]: 1 from numpy.random import seed, randn
```

```
In [180]: 1 seed(1991)
```

```
In [181]: 1 randn(10)
```

```
Out[181]: array([-0.94343179,  0.04928867, -1.28887945, -0.12919796,  0.73604408,  
                -0.27182505, -0.22028639, -0.2412858 ,  0.78027846, -0.95460321])
```

```
from numpy.random import ...
```

- `rand` : random floats
- `randint` : random integers
- `randn` : standard normal distribution
- `permutation` : random permutation

1. Gaussian normal distribution

Questions?