<thesis_title>

PLACEHOLDER TITLE PAGE

please select the appropriate title page for your thesis type

Thesis
submitted to the
Media Computing Group
Prof. Dr. Jan Borchers
Computer Science Department
RWTH Aachen University

by
<author_name>

Thesis advisor:
Prof. Dr. Jan Borchers

Second examiner:
<second_examiner>

Registration date: <registration_date>
Submission date: <submission_date>

Eidesstattliche Versicherung

_____   _____

Name, Vorname   Matrikelnummer

Ich versichere hiermit an Eides Statt, dass ich die vorliegende Arbeit/Bachelorarbeit/ Masterarbeit* mit dem Titel

_____

_____

_____

selbständig und ohne unzulässige fremde Hilfe erbracht habe. Ich habe keine anderen als die angegebenen Quellen und Hilfsmittel benutzt. Für den Fall, dass die Arbeit zusätzlich auf einem Datenträger eingereicht wird, erkläre ich, dass die schriftliche und die elektronische Form vollständig übereinstimmen. Die Arbeit hat in gleicher oder ähnlicher Form noch keiner Prüfungsbehörde vorgelegen.

_____   _____

Ort, Datum   Unterschrift

*Nichtzutreffendes bitte streichen

Belehrung:

§ 156 StGB: Falsche Versicherung an Eides Statt

Wer vor einer zur Abnahme einer Versicherung an Eides Statt zuständigen Behörde eine solche Versicherung falsch abgibt oder unter Berufung auf eine solche Versicherung falsch aussagt, wird mit Freiheitsstrafe bis zu drei Jahren oder mit Geldstrafe bestraft.

§ 161 StGB: Fahrlässiger Falscheid; fahrlässige falsche Versicherung an Eides Statt

(1) Wenn eine der in den §§ 154 bis 156 bezeichneten Handlungen aus Fahrlässigkeit begangen worden ist, so tritt Freiheitsstrafe bis zu einem Jahr oder Geldstrafe ein.

(2) Straflosigkeit tritt ein, wenn der Täter die falsche Angabe rechtzeitig berichtigt. Die Vorschriften des § 158 Abs. 2 und 3 gelten entsprechend.

Die vorstehende Belehrung habe ich zur Kenntnis genommen:

_____   _____

Ort, Datum   Unterschrift

Contents

List of Figures

List of Tables

Abstract

Lorem ipsum dolor sit amet, consectetur adipisicing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua. Ut enim ad minim veniam, quis nostrud exercitation ullamco laboris nisi ut aliquip ex ea commodo consequat. Duis aute irure dolor in reprehenderit in voluptate velit esse cillum dolore eu fugiat nulla pariatur. Excepteur sint occaecat cupidatat non proident, sunt in culpa qui officia deserunt mollit anim id est laborum.Lorem ipsum dolor sit amet, consectetur adipisicing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua. Ut enim ad minim veniam, quis nostrud exercitation ullamco laboris nisi ut aliquip ex ea commodo consequat. Duis aute irure dolor in reprehenderit in voluptate velit esse cillum dolore eu fugiat nulla pariatur. Excepteur sint occaecat cupidatat non proident, sunt in culpa qui officia deserunt mollit anim id est laborum.Lorem ipsum dolor sit amet, consectetur adipisicing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua. Ut enim ad minim veniam, quis nostrud exercitation ullamco laboris nisi ut aliquip ex ea commodo consequat. Duis aute irure dolor in reprehenderit in voluptate velit esse cillum dolore eu fugiat nulla pariatur. Excepteur sint occaecat cupidatat non proident, sunt in culpa qui officia deserunt mollit anim id est laborum.Lorem ipsum dolor sit amet, consectetur adipisicing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua. Ut enim ad minim veniam, quis nostrud exercitation ullamco laboris nisi ut aliquip ex ea commodo consequat. Duis aute irure dolor in reprehenderit in voluptate velit esse cillum dolore eu fugiat nulla pariatur. Excepteur sint occaecat cupidatat non proident, sunt in culpa qui officia deserunt mollit anim id est laborum.

Überblick

Lorem ipsum dolor sit amet, consectetur adipisicing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua. Ut enim ad minim veniam, quis nostrud exercitation ullamco laboris nisi ut aliquip ex ea commodo consequat. Duis aute irure dolor in reprehenderit in voluptate velit esse cillum dolore eu fugiat nulla pariatur. Excepteur sint occaecat cupidatat non proident, sunt in culpa qui officia deserunt mollit anim id est laborum.Lorem ipsum dolor sit amet, consectetur adipisicing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua. Ut enim ad minim veniam, quis nostrud exercitation ullamco laboris nisi ut aliquip ex ea commodo consequat. Duis aute irure dolor in reprehenderit in voluptate velit esse cillum dolore eu fugiat nulla pariatur. Excepteur sint occaecat cupidatat non proident, sunt in culpa qui officia deserunt mollit anim id est laborum.Lorem ipsum dolor sit amet, consectetur adipisicing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua. Ut enim ad minim veniam, quis nostrud exercitation ullamco laboris nisi ut aliquip ex ea commodo consequat. Duis aute irure dolor in reprehenderit in voluptate velit esse cillum dolore eu fugiat nulla pariatur. Excepteur sint occaecat cupidatat non proident, sunt in culpa qui officia deserunt mollit anim id est laborum.Lorem ipsum dolor sit amet, consectetur adipisicing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua. Ut enim ad minim veniam, quis nostrud exercitation ullamco laboris nisi ut aliquip ex ea commodo consequat. Duis aute irure dolor in reprehenderit in voluptate velit esse cillum dolore eu fugiat nulla pariatur. Excepteur sint occaecat cupidatat non proident, sunt in culpa qui officia deserunt mollit anim id est laborum.

Acknowledgements

Thank you!

Conventions

Throughout this thesis we use the following conventions.

Text conventions

Definitions of technical terms or short excursus are set off in coloured boxes.

> **EXCURSUS:**
> Excursus are detailed discussions of a particular point in a book, usually in an appendix, or digressions in a written text.

Definition:
Excursus

Source code and implementation symbols are written in typewriter-style text.

```
myClass
```

The whole thesis is written in Canadian English.

Download links are set off in coloured boxes.

> File: myFile[a]
> _____
> [a]http://hci.rwth-aachen.de/public/folder/file_number.file

Chapter 1

Introduction

Lorem ipsum dolor sit amet, consectetur adipisicing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua. Ut enim ad minim veniam, quis nostrud exercitation ullamco laboris nisi ut aliquip ex ea commodo consequat. Duis aute irure dolor in reprehenderit in voluptate velit esse cillum dolore eu fugiat nulla pariatur. Excepteur sint occaecat cupidatat non proident, sunt in culpa qui officia deserunt mollit anim id est laborum.Lorem ipsum dolor sit amet, consectetur adipisicing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua. Ut enim ad minim veniam, quis nostrud exercitation ullamco laboris nisi ut aliquip ex ea commodo consequat. Duis aute irure dolor in reprehenderit in voluptate velit esse cillum dolore eu fugiat nulla pariatur. Excepteur sint occaecat cupidatat non proident, sunt in culpa qui officia deserunt mollit anim id est laborum.Lorem ipsum dolor sit amet, consectetur adipisicing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua. Ut enim ad minim veniam, quis nostrud exercitation ullamco laboris nisi ut aliquip ex ea commodo consequat. Duis aute irure dolor in reprehenderit in voluptate velit esse cillum dolore eu fugiat nulla pariatur. Excepteur sint occaecat cupidatat non proident, sunt in culpa qui officia deserunt mollit anim id est laborum.Lorem ipsum dolor sit amet, consectetur adipisicing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua. Ut enim ad minim veniam, quis nostrud exercitation ullamco laboris nisi ut aliquip ex ea commodo

consequat. Duis aute irure dolor in reprehenderit in voluptate velit esse cillum dolore eu fugiat nulla pariatur. Excepteur sint occaecat cupidatat non proident, sunt in culpa qui officia deserunt mollit anim id est laborum.

Chapter 2

Related work

In this chapter we first describe the basic differences between the two most popular touch input technologies and which is best suited for wearable scenarios. Then we give an overview of the latest related research in wearable touch input devices. We will focus on hardware prototypes and their underlying techniques. Wearable computation is a current field of research over the past years. Therefore a lot of different approaches were made to make textiles touch sensitive hence we only present some of them. An overview of the presented touch pad prototypes is shown in table2.1.

2.1   Resistive vs. Capacitive Touch

The two most popular touch input technologies are resistive and capacitive. Both serve the same purpose but the underlying principle differs making them more or less suited for wearable computing.

Capacitve touch uses a non-conducting material with conductive material underneath. The capacitance of the human body changes the electrical field of the sensor which is measurable. The advantages of capacitive touch is the easy support for multi-touch input and today's touch screens

Characteristics of Capacitive Touch

only need a slight touch without force. The main disadvantage is the human body itself, since it generates its own capacitive field which makes it hard to detect the intentional touch. This flaw is intensified by the body movement continuously changing the proximity between the sensor and the human body. Therefore complex isolation technique is required to isolate the sensor and the human body which is unfeasible for fast prototyping.

Characteristics of
Resistive Touch

Resistive touch technology uses two separated layers of striped electrodes such that it is arranged to a matrix. The spacing material in ordinary resistive touch screens is either an air filled chamber or a non-conductive material which separates both layers while no external force is applied. Therefore one can operate it with a stylus or with gloves since no conductivity is required. On the one hand this solves the main disadvantage of the capacitive method regarding wearable computing, on the other hand it is still prone to deformation and thus to unintentional contacts.

2.2   General Overview

Holleis et al. [2008] presented several prototypes based on capacitive sensing. They embroidered conductive wires to a phone case, a glove, and an apron resulting in small conductive buttons. Beside that they used conductive foil for buttons on an helmet as well. Their user study however only evaluated the apron with three different button layouts with different visibility. Based on the results they present guidelines for wearable controls.

Speir et al. [2014] built two prototypes, a wristband and a glove. The wristband prototype uses a circular conductive fabric surrounded by resistive linqstat. A conductive finger cap connects both of them an generates a value which is used to determine the location and the movement of the touch. The glove works on the same principle. They evaluated their prototypes as remote controls using one- and two-handed interaction and have found that the users have no clear preference.

Prototype	Touch technology	Gesture detection
Pinstripe	capacitive	detects size of pinch and movement of pinch in 1D
GesturePad	capacitive	not tested (theoretically able to detect 2D gestures)
Pocket touch	capacitive	multistroke gestures using N$ by Anthony and Wobbrock [2012]
FabriTouch	capacitive	swipes in 2D
Grabrics	resistive	detects axis of fold and movement of pinch in 2D
TextiPad ?	resistive	

Table 2.1: Current textile touch pad technologies.

A different application is presented by Smus and Gross [2010]. They used force-sensitive resistors and pull-down resistor circuits to sense percussive touch. They taped the sensor into the inside of a pair of jeans and to the sole of a shoe. They created a program that translates the sensor values to different parts of a drum.

Ubiquitous drums

[Wimmer and Baudisch, 2011] created 13 prototypes based on time domain reflectometry (TDR). For this approach only one pair of wires is needed. The change in capacitance caused by conductive objects close to the pair of wire is measured and the location determined. Distance between the wires and their shape have significant influence on reliability. Their prototypes include stretchable, curved, and arbitrary shaped surfaces. They can sense touch at a distance up to 20m but TDR is prone to radio interference of mobile phones.

Time Domain Reflectometry

2.3 Textile Touch Pads

Pinstripe is continous textile user interface prototype created by Karrer et al. [2010]. It detects pinching and rolling

ToDo: source for grabrics and textiPad

Pinstripe

of clothing by connecting conductive thread sewn on it. However, it is an unidimensional input device and not a touch pad. Nevertheless, when they introduced the users to the sensor they intuitively expected a touch pad.

GesturePad   Rekimoto [2001] presented GesturePad which is a capacitive touch pad integrated in clothing. They propose slightly different architectures consisting of the upper fabric, receiver, transmitter, and a shield layer to reduce the influence of the human body. However, their work was not further evaluated.

PocketTouch   Another capacitive approach was developed by Saponas et al. [2011]. PocketTouch is an eyes-free, calibrateable capacitive touch pad which can sense the proximity of a finger through a wide range of fabrics. They used a touch sensor of a touch screen and attached it to a base which makes it not bendable. The reliability of PocketTouch was not further evaluated.

FabriTouch   FabriTouch is a flexible, capacitive textile touch pad presented by Heller et al. [2014]. It consists of lining, piezoresistive foil, spacing mesh, conductive fabric, and outer garment together integrated into a pair of trousers. FabriTouch is able to reliably detect simple swipe gestures on rigid surfaces rather than on the human thigh. Also movement has a negative impact on the performance of the sensor.

Going for Resistive
Touch   After taking all characteristics into account we decided to go for the resistive touch technology, because we can drop all considerations of capacitive noise caused by the human body.

Chapter 3

Hardware Prototype and Software Development

Then we proceed with showing several iterations of the hardware prototypes using pinstripe material. Furthermore we describe the disadvantages and improvements of each iteration leading to the final prototype. The software implementation is described afterwards.

3.1 System Design

All prototypes presented here are using pinstripe, a fabric with separated conductive lines. For the first prototype we were using the Texas Instruments MSP430G2452 micro-controller. Each row and column of the pinstripe has to be connected to a *digitalRead* pin of the micro-controller. The MSP430 controller has 16 of these pins but only 14 can be used since two pins are used for serial communication. This results in a matrix resolution of 7 by 7 at maximum.

> **RESOLUTION IN PINSTRIPE CONTEXT:**
> When speaking of a certain resolution of our prototype, we talk about the number of connected rows and columns. Since the pinstripe fabric is of a static size, the higher the resolution the larger the prototype gets.

MSP430 for first prototype

ToDo: exact specification of pinstripe and micro-controller und den gripper probe Klemmkabeln!!

Definition: *Resolution in pinstripe context*

We are using the TI EK-TM4C1294XL for the advanced prototypes. This board has the ability to connect more than 40 pins for *digitalRead* to operate a 20 by 20 pinstripe matrix. The board is connected to a Computer via USB for serial communication.

Programming Environment: Energia IDE and Processing to gather, send and process input data

For programming the micro-controller we are using the Energia IDE[1]. It is an easy to use IDE to upload programs to the TI micro-controller. The micro-controller itself is solely responsible for sending the data of the sensor to the computer via serial communication. Meaning that it tests a pin against ground for each other line and column. A *1* is written to the serial-port when it is connected to another line or column and *0* otherwise. This is done for each pin where *numberOfPintripes* is the number of all lines and columns. For each prototype an integer array is declared and can easily be commented and uncommented depending on the prototype. The where the pin numbers are sorted such that the first pins correspond to the x-axis and the last pins to the negative y-axis. After all pins were tested we send a line-break to determine the end of the current input.

We are using Processing[2], a Java based IDE, to structure the input stream from the micro-controller for further analyses. This includes several programs which either displays the raw touch points for debugging purpose or filters and interprets the sensor data. The changes of software are described along with each hardware iteration.

3.2   Early Testing

better note something here

After deciding to go for the resistive approach, the essential challenge is to find a spacing material with certain characteristics. The material should

---

[1]http://energia.nu
[2]http://processing.org

- be flexible by means of being wearable.

- reliably separate the pinstripe fabric while no touch is intended.

- concede rather easily when intended force is applied.

We start by trying some leftovers from recent research projects. Then we place the materials between the pinstripe fabric to examine different behaviors. We glued both layers of the pinstripe fabric to sheets of paper to eliminate stretching and curling of the fabric. Some of the the materials are cut with a laser cutter. We cut equidistant circular holes to provide space for the pinstripe layers to connect. We attached 4 by 4 pinstripes to the MSP430 microcontroller. For displaying where a touch is present, we created a simple program with Processing. Almost all available materials are not well suited for our purpose, since they are either too thick, thin or stiff. When combining up to two materials, which are leading to permanent contacts on their own, the results are improving. Nonetheless it is still susceptible to the slightest bend and therefore not well suited. Therefore we are using foam for the latest prototype.

ToDo: Find names of the fabrics and materials

ToDo: insert picture here
Combine materials to improve results

3.3 The Prototype

In this section we will first talk about the materials and fabrics we use for our prototype and describe how it is built.

3.3.1 Material

 After numerous trials we gathered some knowledge about the key elements needed for this technique to work properly. The first and crucial aspect is the spacing material. The prototype uses a 3 mm thick layer of foam which is coated with thin layer of cotton. Foam has the properties we need to separate the pinstripe layer while no force is applied and yield rather easily when the user presses

3 mm foam as spacing material

on it. Another positive feature is the increased resistance to unintended pressure caused by bending or accidental contact with the sensor. When evaluating the prototype we will take a closer look to which extend we can bend the prototype and how it performs in marginal conditions.

We use a laser cutter to cut equidistant holes out of the foam to allow the pinstripe layers to connect. This procedure leaves enough foam between the holes to retain the properties we need.

Issues with flexibility and translatory movement

 Another problem we have to address is the stretchability and the translatory movement of the fabrics. Each time the user performs a gesture the upper layer moves in the respective direction due to the friction between the operating finger and the surface. This causes the the pinstripe fabric to shift such that the conductive stripes are not aligned to the holes properly, resulting in the prototype to stop working. When we started testing we used needles, clips, and nails to fix the materials to each other. Not only that these methods are not well suited for wearablity, also fixing the materials exclusively at the edges is not sufficient. Nonetheless the flexibility of the pinstripe fabric can cause the shift we want to eliminate.

Vliesofix for fixating the components of the prototype

 To deal with the issues described above we use Vliesofix. Vliesofix is an adhesive on paper which can be ironed on textile. The paper can be removed afterwards and another fabric can be ironed to the corresponding textile. This results in an extensive adhesive area between two fabrics. The application of Vliesofix not only resolves the translatory movement but also the curling of the pinstripe fabric.

3.3.2   Construction

We decide two to prototypes with different dimensions. The first prototype has a resolution of 14 by 14 pinstripes and the second prototype has a resolution of 20 by 20. Since the procedure of making the prototypes is similar we

only describe its building procedure for the smaller one.

We start by cutting out a x by x cm piece of the 3 mm foam using the laser cutter. Then we cut out two sheet of Vliesofix with the corresponding dimensions and proceed by ironing them on both sides of the foam. This has to be done carefully since the applying heat for two long can cause the foam to melt. After cooling down the foam looses the desired properties to a certain degree. When removing the iron too soon the Vliesofix might not be adhesive enough.

Once the material is cooled off we can remove the paper of the Vliesofix. We proceed with cutting the holes in the foam with the Vliesofix. Making the laser cutter cut more rows and columns of holes ensures that the resistance of the foam is the same throughout the touch sensitive area. Otherwise more force is needed at the edges than the center.

To prepare the two pinstripe layer to adhere it to the foam we again use Vliesofix first for preventing the fabric from curling and easy stretching. We do so before cutting out the pinstripe to make handling the fabric easier. Note that, while using Vliesofix with the pinstripe fabric, it is even more important to apply heat for too long. When the Vliesofix becomes liquid it gets soaked into the fabric. In some cases we ascertained that for this reason the conductivity of the pinstripes gets lost in some places. This immediately renders the sensor useless. Apart from that we do not remove the paper of the Vliesofix at this point.

We proceed with attaching the pinstripe layers to the foam. The stripes of each layer must be perpendicular to one another. Then we iron the untreated side of the one pinstripe fabric to the foam and after cooling off the other pinstripe to the other side. We have to make sure that the conductive stripes and the holes in the foam are aligned properly. Now we can remove the paper from the pinstripe fabric.

After that we iron a corresponding piece of polyester on the upper side of the sensor to reduce the friction between the finger and treated pinstripe layer. The last step is to connect the sensor to the micro controller. Furthermore we connect a Bluetooth module for wireless data stream. The

power source can either be a computer or an battery pack which are connected by a micro USB cable.

3.4   The Software

The software is divided into two parts, the code running on the micro controller and the application running on the computer. The code for the micro controller is straight forward. We define an one dimensional array for each prototype in which the pin numbers are stored such that the first half of the array denote the horizontal x-axis starting from left to right and the second half the vertical y-axis starting from top to bottom. Now we can check each pin of the array respectively if it is connected to ground. This means that the conductive stripe connected to that pin has a connection to another stripe and a *1* is sent via the serial communication and a *0* otherwise. The line break after the *for* loop lets us determine if a complete input set is received.

Code for TI EK-TM4C1294XL

In Processing we read the data from the serial communication and store it in a buffer including the time stamp. If at least one *1* per data set is read, we consider it to be a touch. Sometimes the contact of the pinstripe layer is lost while performing a gesture due to insufficient pressure or a undersized locating surface of the operating finger. Therefore we implemented a threshold in which we can read only *0* without the touch phase to end. This threshold is reset anytime if a *1* is read. The raw data is logged for potential analyses as shown in figure 3.1.

Receiving the data via serial communication in Processing

Since more than one vertical and horizontal pinstripe can be connected at the same time we apply a filter algorithm. This filter algorithm takes all x-coordinates and calculates the average and the same for the y-coordinates. The resulting triple composed of the coordinate and the time stamp is added to an *Arraylist* buffer. This is done for all input sets except for all those, who only consists of *0's*. There are two reasons for filtering the input data. The first is the resilience to noise caused by unintended connections

Use a filter algorithm to reduce the data

```
00001000000000000000110000000;4.0
00000100000000000000110000000;5.0
00000011000000000000110000000;5.0
00000000100000000000110000000;5.0
00000000010000000000100000000;70.0
00000000001110000000100000000;340.0
00000000000010000001000000000;340.0
00000000000010000010000000000;340.0
00000000000000000100000000000;340.0
00000000000000000000000000000;358.0
00000000001100001000000000000;433.0
00000000001000001000000000000;720.0
00000001100000000100000000000;720.0
00000001000000000010000000000;720.0
00000001000000000001000000000;721.0
00000001000000000000100000000;721.0
00000001100000000000010000000;789.0
00000001100000000000001100000;1071.0
00000000100000000000000010000;1071.0
00000000100000000000000001000;1071.0
00000001000000000000000000100;1072.0
00000000000000000000000000010;1090.0
00001000000000000000000000010;1141.0
00001000000000000000000000100;1403.0
00010000000000000000000001000;1404.0
00010000000000000000000010000;1404.0
00001000000000000000000110000;1404.0
00000100000000000000000100000;1438.0
00000011000000000000000100000;1489.0
00000000100000000000000110000;1754.0
00000000001000000000000010000;1754.0
00000000000010000000000010000;1754.0
00000000000010000000000010000;1754.0
00000000000010000000000010000;1805.0
00000000000010000000000000000;1856.0
00000000000000000000000000000;2094.0
```

Figure 3.1: Example of the raw data of one gesture. On the left-hand side the sensor input and on the right the time stamps in milliseconds.

or slow separation of the pinstripe layers. The second reason is fact that it is easier for implementing gesture recognition. Apart from this the user intends to press only one point at the sensor.

When a gesture starts we take the coordinates and subtract them from all filtered coordinates of this gesture. Therefore every gesture starts at $(0, 0)$ regardless where it is performed on the sensor. This is done for the graphical representation of the strokes and will be useful later on.

The next step is to actual recognize easy strokes performed on the prototype. Since our prototypes have a rather low

Implementing mark-based gesture recognition

Figure 3.2: Mark-based gestures. Gestures start at the dots.
Bragdon et al. [2011]

resolution compared to typical touch input devices we fo-
cus on rather simple unistroke gestures. These mark-based
gestures are shown in figure 3.2. We extend this gestures
set by adding 5 gestures. These gestures are a tab and for
each swipe gesture we expand it with a swipe in the op-
posite direction. This leads to a gesture set with 17 simple
gestures.

Our gesture recognition works as follows. First of all we
do not recognize in real-time. We analyze all filtered points,
stored in the buffer, after a gesture is considered finished.
Then the algorithm works as follows.

- check for tab

    - return $true$ if the size of the buffer is 1
    - return $true$ if the all coordinates have a $distance$
      smaller or equal to 1 respectively and the time
      elapsed is smaller than 200 milliseconds
    - else check for other gestures

- check for swipe

    - assume there is a swipe with the first and the last
      item of the buffer as terminal points
    - calculate the $distance$ of the line
    - return $false$ if the $distance$ is smaller than 3
    - for all other points calculate the $distanceToLine$

> – return $false$ if at some index the $distanceToLine$ is greater than 1

> – else determine the direction of the swipe and return $true$

- check for angle

> – check if there is a line between the point at $index - 1$ and last point in the buffer under the exact same conditions applied for swipe

> – return $false$ if at some index the $distanceToLine$ is greater than 1

> – calculate the directions of both lines and return $true$

- end of checking

This algorithm classifies each gesture as a tab, swipe, angle, or no gesture. In combination with the directions we calculate for each swipe we can distinguish between all 16 mark-based gestures. The orientation of a line is mapped to one of the four directions up, left, right, or down. Therefore our prototype is resilient to a certain degree of input error. With less effort we can further extend the gesture set by distinguish more directions.

When testing our gesture recognizer with our current prototypes we observe an almost 100% recognition rate. Based on this finding we decide to go beyond simple mark-based gestures and continue with recognizing more complex gestures. Therefore we make use of the 1$ Unistroke Recognizer by Wobbrock et al. [2007]. This is an easy to implement recognizer which does not require any training data. Providing a template for each gesture is sufficient. A template is an array of consecutive pairs of coordinates. We can pass the coordinates in the filtered buffer straight to the 1$ recognizer.

This recognizer is orientation independent. Meaning for the marked-based gestures that, without further analysis of orientation, we can only distinguish between a swipe, an angle to the right, and an angle to the left. However, we can recognize a set of free-form gestures shown in figure 3.3.

Using 1$ Unistroke Recognizer for complex gestures

Figure 3.3: Free-form gestures Bragdon et al. [2011]

Chapter 4

System Evaluation

In this chapter we will evaluate the robustness and amount of noise the system generates in different extreme conditions. We will take a closer look at the performance of the 14 by 14 prototype. Since the prototype is designed as a wearable, we are interested in its behavior under certain changing conditions. We conducted an informal user study to test the physical limitations of our prototype.

4.1   Physical Limitation Study

The human body is in motion almost all the time and the clothes we are wearing are not fixed to the skin. This *looseness* and the changing subsurface are variables that may influence the performance of our prototype. Another variable is the *friction* of the overlaying material. Depending on the fabric and method of fashioning, it can, more or less, likely, happen that the user slips of the touch-sensing area, or experiences an unpleasant feeling in the operating finger. Furthermore the *softness* of the underlying surface may influence the performance of our prototype. The human body has different softness almost everywhere. The amount of muscles, adipose tissue, and so forth also differs from hu-

Independent variables: friction, softness, looseness, and curvature

man to human. This, in the first place, affects the pressure needed by the user. Then there are the different levels of curvature. Our prototype has flexible spacing-material to separate the pinstripe layer. After a certain amount of bend the material starts creasing, causing some permanent contacts. In this study we will test our prototype in conditions which aim to simulate the in field circumstances. To test to which degree of bend the prototype breaks we used different foams with the same height but different softness.

4.2   Study Design

The participants had to perform 8 different gestures in different conditions. To control the curvature, we used aerosol cans with 53 mm diameter and 66mm diameter. As a baseline we also used the table with a flat surface. When we tried to perform gestures on a curvature below 53 mm we got permanent contacts immediately. To fixate the aerosol cans we build stands using a laser cutter. The prototype was fixed with duct tape to the surface of the cans and . To achieve the curvature with the foam, we used a book and wrapped the foam around the cover and

ToDo: brown farbric?
ToDo: insert pictures

clipped it in a vise. The fabrics (jeans, cotton,) were pinned with needles to the prototype. Nevertheless, there is still a certain amount of movement due to the flexibility of the fabrics. Since we aim to build a textile touch pad for eyes-free interaction, the user can not see the output on the screen.

The conditions, at least curvature and softness, were chosen at random. In order to shorten the time of the study, we tested all fabrics consecutively changing the order. Some prior testing has shown that the foam with a density of todofind that paper with the numbers xxxxxx and xxxxxxx perform alike. Thus we dropped the foam with higher density after the first participant tested both foams in one condition without significant differences in terms of input error.

The participants were filmed while interacting with the prototype. Furthermore the screen with our program was captured to determine the by eye, whether the gesture was recognized correctly or, if not, should have been recognized correctly. Additionally, our program created two log-files for every condition. One logged the filtered data and one the raw sensor data. Both files logged the time it took to perform each gesture.

ToDo: mention participants

4.3   Study Procedure

After the user arrived we introduced her to our prototype. We explained the basic functionality and demonstrated how the output looks like. Then we let the user test the eight gestures and some freestyle strokes. This was done without foam or any additional fabric. We pointed out that a certain amount of pressure is essential for our prototype to recognize the touch. When they felt familiar enough, about 2 minutes of testing, we prepared the first condition.

For each condition we setup a GoPro Hero 3 to capture the prototype and the acting hand of the user. When we were ready to start recording the screen and setup, we told the user to continue. Since the user cannot see the output during the study, we told the user when insufficient pressure was applied or when the touch-sensing area was left. In both cases we most likely recognized one or two wrong gestures. We represent the number of wrong gestures with an x in the respective chart.

When one condition is completed we asked the user about their impressions of the fabric, softness, and curvature.

4.4   Observation

Chapter 5

Summary and future work

Lorem ipsum dolor sit amet, consectetur adipisicing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua. Ut enim ad minim veniam, quis nostrud exercitation ullamco laboris nisi ut aliquip ex ea commodo consequat. Duis aute irure dolor in reprehenderit in voluptate velit esse cillum dolore eu fugiat nulla pariatur.

5.1 Summary and contributions

Lorem ipsum dolor sit amet, consectetur adipisicing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua. Ut enim ad minim veniam, quis nostrud exercitation ullamco laboris nisi ut aliquip ex ea commodo consequat. Duis aute irure dolor in reprehenderit in voluptate velit esse cillum dolore eu fugiat nulla pariatur. Excepteur sint occaecat cupidatat non proident, sunt in culpa qui officia deserunt mollit anim id est laborum.Lorem ipsum dolor sit amet, consectetur adipisicing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua. Ut enim ad minim veniam, quis nostrud exercitation ullamco laboris nisi ut aliquip ex ea commodo consequat. Duis aute irure dolor in reprehenderit in voluptate velit esse cillum

dolore eu fugiat nulla pariatur. Excepteur sint occaecat cupidatat non proident, sunt in culpa qui officia deserunt mollit anim id est laborum.Lorem ipsum dolor sit amet, consectetur adipisicing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua. Ut enim ad minim veniam, quis nostrud exercitation ullamco laboris nisi ut aliquip ex ea commodo consequat. Duis aute irure dolor in reprehenderit in voluptate velit esse cillum dolore eu fugiat nulla pariatur. Excepteur sint occaecat cupidatat non proident, sunt in culpa qui officia deserunt mollit anim id est laborum.Lorem ipsum dolor sit amet, consectetur adipisicing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua. Ut enim ad minim veniam, quis nostrud exercitation ullamco laboris nisi ut aliquip ex ea commodo consequat. Duis aute irure dolor in reprehenderit in voluptate velit esse cillum dolore eu fugiat nulla pariatur. Excepteur sint occaecat cupidatat non proident, sunt in culpa qui officia deserunt mollit anim id est laborum.

5.2   Future work

Lorem ipsum dolor sit amet, consectetur adipisicing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua. Ut enim ad minim veniam, quis nostrud exercitation ullamco laboris nisi ut aliquip ex ea commodo consequat. Duis aute irure dolor in reprehenderit in voluptate velit esse cillum dolore eu fugiat nulla pariatur. Excepteur sint occaecat cupidatat non proident, sunt in culpa qui officia deserunt mollit anim id est laborum.Lorem ipsum dolor sit amet, consectetur adipisicing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua. Ut enim ad minim veniam, quis nostrud exercitation ullamco laboris nisi ut aliquip ex ea commodo consequat. Duis aute irure dolor in reprehenderit in voluptate velit esse cillum dolore eu fugiat nulla pariatur. Excepteur sint occaecat cupidatat non proident, sunt in culpa qui officia deserunt mollit anim id est laborum.Lorem ipsum dolor sit amet, consectetur adipisicing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua. Ut enim ad minim veniam, quis nostrud exercitation ullamco laboris nisi ut aliquip ex ea commodo consequat. Duis aute irure dolor in reprehen-

derit in voluptate velit esse cillum dolore eu fugiat nulla
pariatur. Excepteur sint occaecat cupidatat non proident,
sunt in culpa qui officia deserunt mollit anim id est labo-
rum.Lorem ipsum dolor sit amet, consectetur adipisicing
elit, sed do eiusmod tempor incididunt ut labore et dolore
magna aliqua. Ut enim ad minim veniam, quis nostrud ex-
ercitation ullamco laboris nisi ut aliquip ex ea commodo
consequat. Duis aute irure dolor in reprehenderit in volup-
tate velit esse cillum dolore eu fugiat nulla pariatur. Excep-
teur sint occaecat cupidatat non proident, sunt in culpa qui
officia deserunt mollit anim id est laborum.

Appendix A

TITLE OF THE FIRST APPENDIX

Lorem ipsum dolor sit amet, consectetur adipisicing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua. Ut enim ad minim veniam, quis nostrud exercitation ullamco laboris nisi ut aliquip ex ea commodo consequat. Duis aute irure dolor in reprehenderit in voluptate velit esse cillum dolore eu fugiat nulla pariatur. Excepteur sint occaecat cupidatat non proident, sunt in culpa qui officia deserunt mollit anim id est laborum.Lorem ipsum dolor sit amet, consectetur adipisicing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua. Ut enim ad minim veniam, quis nostrud exercitation ullamco laboris nisi ut aliquip ex ea commodo consequat. Duis aute irure dolor in reprehenderit in voluptate velit esse cillum dolore eu fugiat nulla pariatur. Excepteur sint occaecat cupidatat non proident, sunt in culpa qui officia deserunt mollit anim id est laborum.Lorem ipsum dolor sit amet, consectetur adipisicing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua. Ut enim ad minim veniam, quis nostrud exercitation ullamco laboris nisi ut aliquip ex ea commodo consequat. Duis aute irure dolor in reprehenderit in voluptate velit esse cillum dolore eu fugiat nulla pariatur. Excepteur sint occaecat cupidatat non proident, sunt in culpa qui officia deserunt mollit anim id est laborum.Lorem ipsum dolor sit amet, consectetur adipisicing elit, sed do eiusmod tempor incididunt ut labore et dolore

magna aliqua. Ut enim ad minim veniam, quis nostrud exercitation ullamco laboris nisi ut aliquip ex ea commodo consequat. Duis aute irure dolor in reprehenderit in voluptate velit esse cillum dolore eu fugiat nulla pariatur. Excepteur sint occaecat cupidatat non proident, sunt in culpa qui officia deserunt mollit anim id est laborum.

Appendix B

TITLE OF THE SECOND APPENDIX

Lorem ipsum dolor sit amet, consectetur adipisicing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua. Ut enim ad minim veniam, quis nostrud exercitation ullamco laboris nisi ut aliquip ex ea commodo consequat. Duis aute irure dolor in reprehenderit in voluptate velit esse cillum dolore eu fugiat nulla pariatur. Excepteur sint occaecat cupidatat non proident, sunt in culpa qui officia deserunt mollit anim id est laborum.Lorem ipsum dolor sit amet, consectetur adipisicing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua. Ut enim ad minim veniam, quis nostrud exercitation ullamco laboris nisi ut aliquip ex ea commodo consequat. Duis aute irure dolor in reprehenderit in voluptate velit esse cillum dolore eu fugiat nulla pariatur. Excepteur sint occaecat cupidatat non proident, sunt in culpa qui officia deserunt mollit anim id est laborum.Lorem ipsum dolor sit amet, consectetur adipisicing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua. Ut enim ad minim veniam, quis nostrud exercitation ullamco laboris nisi ut aliquip ex ea commodo consequat. Duis aute irure dolor in reprehenderit in voluptate velit esse cillum dolore eu fugiat nulla pariatur. Excepteur sint occaecat cupidatat non proident, sunt in culpa qui officia deserunt mollit anim id est laborum.Lorem ipsum dolor sit amet, consectetur adipisicing elit, sed do eiusmod tempor incididunt ut labore et dolore

magna aliqua. Ut enim ad minim veniam, quis nostrud exercitation ullamco laboris nisi ut aliquip ex ea commodo consequat. Duis aute irure dolor in reprehenderit in voluptate velit esse cillum dolore eu fugiat nulla pariatur. Excepteur sint occaecat cupidatat non proident, sunt in culpa qui officia deserunt mollit anim id est laborum.

Bibliography

Lisa Anthony and Jacob O Wobbrock. $n-protractor: a fast and accurate multistroke recognizer. In *Proceedings of Graphics Interface 2012*, pages 117–120. Canadian Information Processing Society, 2012.

Andrew Bragdon, Eugene Nelson, Yang Li, and Ken Hinckley. Experimental analysis of touch-screen gesture designs in mobile environments. In *Proceedings of the SIGCHI Conference on Human Factors in Computing Systems*, CHI '11, pages 403–412, New York, NY, USA, 2011. ACM. ISBN 978-1-4503-0228-9. doi: 10. 1145/1978942.1979000. URL `http://doi.acm.org/ 10.1145/1978942.1979000`.

Florian Heller, Stefan Ivanov, Chat Wacharamanotham, and Jan Borchers. Fabritouch: Exploring flexible touch input on textiles. In *Proceedings of the 2014 ACM International Symposium on Wearable Computers*, ISWC '14, pages 59–62, New York, NY, USA, 2014. ACM. ISBN 978-1-4503-2969- 9. doi: 10.1145/2634317.2634345. URL `http://doi. acm.org/10.1145/2634317.2634345`.

Paul Holleis, Albrecht Schmidt, Susanna Paasovaara, Arto Puikkonen, and Jonna Häkkilä. Evaluating capacitive touch input on clothes. In *Proceedings of the 10th International Conference on Human Computer Interaction with Mobile Devices and Services*, MobileHCI '08, pages 81–90, New York, NY, USA, 2008. ACM. ISBN 978-1-59593-952- 4. doi: 10.1145/1409240.1409250. URL `http://doi. acm.org/10.1145/1409240.1409250`.

Thorsten Karrer, Moritz Wittenhagen, Florian Heller, and Jan Borchers. Pinstripe: Eyes-free continuous input anywhere on interactive clothing. In *Adjunct Proceedings*

of the 23Nd Annual ACM Symposium on User Interface Software and Technology, UIST '10, pages 429–430, New York, NY, USA, 2010. ACM. ISBN 978-1-4503-0462-7. doi: 10.1145/1866218.1866255. URL http://doi.acm.org/10.1145/1866218.1866255.

J. Rekimoto. Gesturewrist and gesturepad: unobtrusive wearable interaction devices. In *Wearable Computers, 2001. Proceedings. Fifth International Symposium on*, pages 21–27, 2001. doi: 10.1109/ISWC.2001.962092.

T. Scott Saponas, Chris Harrison, and Hrvoje Benko. Pockettouch: Through-fabric capacitive touch input. In *Proceedings of the 24th Annual ACM Symposium on User Interface Software and Technology*, UIST '11, pages 303–308, New York, NY, USA, 2011. ACM. ISBN 978-1-4503-0716-1. doi: 10.1145/2047196.2047235. URL http://doi.acm.org/10.1145/2047196.2047235.

Boris Smus and Mark D. Gross. Ubiquitous drums: A tangible, wearable musical interface. In *CHI '10 Extended Abstracts on Human Factors in Computing Systems*, CHI EA '10, pages 4009–4014, New York, NY, USA, 2010. ACM. ISBN 978-1-60558-930-5. doi: 10.1145/1753846.1754094. URL http://doi.acm.org/10.1145/1753846.1754094.

Jessica Speir, Rufino R. Ansara, Colin Killby, Emily Walpole, and Audrey Girouard. Wearable remote control of a mobile device: Comparing one- and two-handed interaction. In *Proceedings of the 16th International Conference on Human-computer Interaction with Mobile Devices & Services*, MobileHCI '14, pages 489–494, New York, NY, USA, 2014. ACM. ISBN 978-1-4503-3004-6. doi: 10.1145/2628363.2634221. URL http://doi.acm.org/10.1145/2628363.2634221.

Raphael Wimmer and Patrick Baudisch. Modular and deformable touch-sensitive surfaces based on time domain reflectometry. In *Proceedings of the 24th Annual ACM Symposium on User Interface Software and Technology*, UIST '11, pages 517–526, New York, NY, USA, 2011. ACM. ISBN 978-1-4503-0716-1. doi: 10.1145/2047196.2047264. URL http://doi.acm.org/10.1145/2047196.2047264.

Jacob O Wobbrock, Andrew D Wilson, and Yang Li. Gestures without libraries, toolkits or training: a $1 recognizer for user interface prototypes. In *Proceedings of the 20th annual ACM symposium on User interface software and technology*, pages 159–168. ACM, 2007.

Index

abbrv, *see* abbreviation

evaluation, 9–10

future work, 12–13