



Advanced Programming

Generics

Collections

The Context

- “Create a data structure that stores elements:
 - *a stack, a linked list, a vector*
 - *a graph, a tree, etc.*”
- What data type to use for representing the elements of the structure?

Homogenous structure

```
class Stack {  
    private int[] items;  
    public void push (int item) { ... }  
    public int peek() { ... }  
}  
...  
Stack stack = new Stack();  
stack.push(100);  
stack.push(200);  
stack.push("Hello World!");
```

Heterogeneous structure

```
class Stack {  
    private Object[] items;  
    public void push (Object item) { ... }  
    public Object peek() { ... }  
}  
...  
Stack stack = new Stack();  
stack.push(100);  
stack.push(new Rectangle());  
stack.push("Hello World!");  
String s = (String) stack.peek;
```

Generics

- Generics enable types (classes and interfaces) **to be parameters when defining classes**, interfaces and methods.

```
public Stack<String> { ... }
```

- Stronger **type checks at compile time**.

```
stack.push(new Rectangle());
```

- Elimination of casts.

```
String s = (String) stack.peek();
```

- Enabling generic algorithms.

Defining a Generic Type

```
class ClassName<T1, T2, ..., Tn> { ... }  
or  
interface IName<T1, T2, ..., Tn> { ... }
```

```
/**  
 * A generic version of the Stack class  
 * @param <E> the type of the elements  
 */
```

```
public class Stack<E> {
```

```
    // E is a generic data type
```

```
    private E[] items;
```

E is the type parameter

```
    public void push(E item) { ... }
```

```
    public E peek() { .. }
```

```
}
```

Type Parameter Naming Conventions

- **E - Element** (used extensively by the Java Collections Framework)
- **K - Key**
- **N - Number**
- **T - Type**
- **V - Value**
- **S,U,V etc. - 2nd, 3rd, 4th types**

```
public class Node<T> { ... }
```

```
public interface Pair<K, V> { ... }
```

```
public class PairImpl<K, V> implements Pair<K, V> {...}
```

Instantiating a Generic Type

- Generic Invocation

String is the type argument

```
Stack<String> stack = new Stack<String>();
```

```
Pair<Integer,String> pair =
```

```
    new PairImpl<Integer,String>(0, "ab");
```

```
Stack<Node<Integer>> nodes = new Stack<Node<Integer>>();
```

- *The Diamond* <>

```
Stack<String> stack = new Stack<>();
```

```
Pair<Integer,String> pair = new PairImpl<>(0, "ab");
```

```
Stack<Node<Integer>> nodes = new Stack<>();
```

The compiler can determine, or infer, the type arguments from the context.

Generic Methods

Generic methods are methods that introduce their own type parameters.

```
public class Util {  
    public static <T> int countNullValues(T[] anArray) {  
        int count = 0;  
        for (T e : anArray)  
            if (e == null) {  
                ++count;  
            }  
        return count;  
    }  
}  
Util.countNullValues(new String[]{"a", null, "b"});  
Util.countNullValues(new Integer[]{1, 2, null, 3, null});
```

Bounded Type Parameters


```
class D <T extends A & B & C> { /* ... */ }
```

```
public class Node<T extends Number> {  
    private T t;  
    public void set(T t) { this.t = t; }  
    public T get() { return t; }  
  
    // Generic Method  
    public <U extends Integer> void inspect(U u) {  
        System.out.println("T: " + t.getClass().getName());  
        System.out.println("U: " + u.getClass().getName());  
    }  
  
    public static void main(String[] args) {  
        Node<Double> node = new Node<>();  
        node.set(12.34); //OK  
        node.inspect(1234); //OK  
node.inspect(12.34); //compile error!  
node.inspect("some text"); //compile error!  
    }  
}
```


Generics, Inheritance, Subtypes

"is a"

- ✓ Integer extends Object
- ✓ Integer extends Number
- ~~Stack<Integer> extends Stack<Object>~~
- ~~Stack<Integer> extends Stack<Number>~~



Given two concrete types A and B (for example, *Number* and *Integer*), *MyClass<A>* has no relationship to *MyClass*, regardless of whether or not A and B are related. The common parent of *MyClass<A>* and *MyClass* is *Object*.

"This is a common misunderstanding when it comes to programming with generics, but it is an important concept to learn "

Wildcards

- Upper bounded

```
public double sumOfList(List<? extends Number> list) {  
    //it works on List<Integer>, List<Double>, List<Number>, etc.  
    double s = 0.0;  
    for (Number n : list)  
        s += n.doubleValue();  
    return s;  
}
```

- Unbounded

```
public void printList(List<?> list) {  
    for (Object elem: list)  
        System.out.print(elem + " ");  
}
```

- Lower bounded

```
public void addNumbers(List<? super Integer> list) {  
    //it works on List<Integer>, List<Number>, and List<Object> –  
    //anything that can hold Integer values.  
    for (int i = 1; i <= 10; i++) {  
        list.add(i);  
    }  
}
```

Java Collections Framework

Java Collections Framework

- A *collection* is an object that groups multiple elements into a single unit.
- *Vectors, Lists, Stacks, Sets, Dictionaries, Trees, Tables, etc.*
- Promotes software reuse
- Reduces programming effort
- Increases program speed and quality
- Benefits from *polymorphic algorithms*
- Uses *generics*

Collections Framework

- Interface



- Abstract class



- Concrete implementation

List




AbstractList



ArrayList
LinkedList
Vector

The Core Collection Interfaces




Implementations

Interfața	Hash	Array	Tree	Linked	Hash+Linked
Set	HashSet		TreeSet		LinkedHashSet
List		ArrayList Vector		LinkedList	
Queue					
Deque		ArrayDeque		LinkedDeque	
Map	HashMap Hashtable		TreeMap		LinkedHashMap

```
Set set = new HashSet(); --raw generic type (Object)
ArrayList<Integer> list = new ArrayList<>();
List<Integer> list = new ArrayList<>();
List<Integer> list = new LinkedList<>();
List<Integer> list = new Vector<>();
Map<Integer, String> map = new HashMap<>();
```

Collections Hierarchy



Iterating Over a Collection

- Indexed Collections

```
for (i=0; i < list.size(); i++) {  
    System.out.println( list.get(i) );  
}
```

- *Iterator* and *Enumeration*

```
for (Iterator it = set.iterator(); it.hasNext(); ) {  
    System.out.println(it.next());  
    it.remove();  
}
```

- *for-each*

```
List<Student> students = new ArrayList<Student>();  
...  
for (Student student : students) {  
    student.setGrade(10);  
}
```

ArrayList or LinkedList?

```
public class TestList {
    private final static int N = 100_000;
    public void testAdd(List<Integer> list) {
        long t1 = System.currentTimeMillis();
        for (int i = 0; i < N; i++) {
            list.add(i);
        }
        long t2 = System.currentTimeMillis();
        System.out.println("Add: " + (t2 - t1));
    }
    public void testGet(List<Integer> list) {
        long t1 = System.currentTimeMillis();
        for (int i = 0; i < N; i++) {
            list.get(i);
        }
        long t2 = System.currentTimeMillis();
        System.out.println("Get: " + (t2 - t1));
    }
    public void testRemove(List<Integer> list) {
        long t1 = System.currentTimeMillis();
        for (int i = 0; i < N; i++) {
            list.remove(0);
        }
        long t2 = System.currentTimeMillis();
        System.out.println("Remove : " + (t2 - t1));
    }
    public void runTests(List<Integer> list) {
        testAdd(list); testGet(list); testRemove(list);
    }
    public static void main(String args[]) {
        TestList app = new TestList();
        app.runTests(new ArrayList<>());
        app.runTests(new LinkedList<>());
    }
}
```

	ArrayList	LinkedList
add	6 ms	8 ms
get	3 ms	<u>4320</u> ms
remove	<u>868</u> ms	6 ms

Conclusion: Choosing a certain implementation depends on the nature of the problem being solved.

ArrayList or HashSet?

```
public class TestSet {
    final static int N = 100_000;
    public void testAdd(Collection<Integer> collection) {
        long t1 = System.currentTimeMillis();
        for (int i = 0; i < N; i++) {
            collection.add(i);
        }
        long t2 = System.currentTimeMillis();
        System.out.println("Add: " + (t2 - t1));
    }
    public void testIterate(Collection<?> collection) {
        long t1 = System.currentTimeMillis();
        for (Object obj : collection) {
            obj.toString(); //do something
        }
        long t2 = System.currentTimeMillis();
        System.out.println("Iterate: " + (t2 - t1));
    }
    public void testContains(Collection<?> collection) {
        long t1 = System.currentTimeMillis();
        for (int i = 0; i < N; i++) {
            collection.contains(i);
        }
        long t2 = System.currentTimeMillis();
        System.out.println("Contains: " + (t2 - t1));
    }
    public void runTests(Collection<Integer> collection) {
        testAdd(collection); testIterate(collection); testContains(collection);
    }
    public static void main(String args[]) {
        TestSet app = new TestSet();
        app.runTests(new ArrayList<>());
        app.runTests(new HashSet<>());
    }
}
```

	ArrayList	HashSet
add	6 ms	26 ms
iterate	51 ms	12 ms
contains	<u>3997</u> ms	7 ms
Memory	low	high

Conclusion: Choosing a certain implementation depends on the nature of the problem being solved.

Aggregate Operations

- **Stream** - sequence of elements supporting sequential and parallel aggregate operations.
- **Pipeline** - a sequence of aggregate operations.

```
persons.stream()  
    .filter(p -> p.getAge() >= 18)  
    .filter(p -> p.getName().endsWith("escu"))  
    .forEach(s -> System.out.println(s.getName()));
```

- **Reduction** and **Terminal** ops.

```
double averageAge = persons.stream()  
    .filter(p -> p.getAge() >= 18)  
    .mapToInt(Person::getAge)  
    .average()  
    .getAsDouble();
```

- **Source**
array, collection, ...
- **Intermediate** operations
filter, distinct, sorted, ...
- **Reduction** operations
map, mapToInt, ...
- **Terminal** operations
average, min, max, ...

Polymorphic Algorithms

`java.util.Collections`

- `sort`
- `shuffle`
- `binarySearch`
- `reverse`
- `fill`
- `copy`
- `min`
- `max`
- `swap`
- `enumeration`
- `unmodifiableCollectionType`

```
List<String> immutablelist = Collections.unmodifiableList(list);  
immutablelist.add("Oops...?!");
```
- `synchronizedCollectionType`



What DesignPattern?