Subsemnata Andra – Elena N. Paduraru declara pe propria raspundere ca acest cod nu a fost copiat din Internet sau din alte surse. Pentru documentare am folosit urmatoarele surse:

Link-uri:

https://profs.info.uaic.ro/~iasimin/Laborator%20C%20S%20H/Laborator%20WCF%202020.pdf

https://profs.info.uaic.ro/~iasimin/Laborator%20C%20S%20H/Laborator1-2016.pdf

https://stackoverflow.com/questions/8986975/c-sharp-return-different-types

https://www.c-sharpcorner.com/UploadFile/mahesh/create-a-text-file-in-C-Sharp/

https://stackoverflow.com/questions/34851800/export-data-from-sql-server-to-text-file-in-c-

sharpsaving-to-a-specific-folder

 $\underline{https://www.aspsnippets.com/Articles/Export-data-from-SQL-Server-to-Text-file-in-C-andVBNet.aspx}$

https://stackoverflow.com/questions/6062192/there-is-already-an-open-datareader-associated-with-

thiscommand-which-must-be-c

https://stackoverflow.com/questions/18475195/error-there-is-already-an-open-datareader-

associated with-this-command-which-mu/18475525

https://docs.microsoft.com/enus/dotnet/api/system.data.sqlclient.sqlparametercollection.addwithvalue?

view=netframework-4.8

https://stackoverflow.com/questions/1132422/open-a-folder-using-process-start

https://docs.microsoft.com/en-us/dotnet/framework/winforms/controls/how-to-bind-data-to-

thewindows-forms-datagridview-control

https://stackoverflow.com/questions/27874566/getting-values-from-sql-reader-c-sharp

https://forums.asp.net/t/1794939.aspx?How+to+read+output+of+sql+command+C+

Client:

S-a folosit GUI de la proiectul 1. A fost creat app.config si proxy.cs care arata in felul urmator:

```
App.config ≠ X
          <?xml version="1.0" encoding="utf-8" ?>
         □<configuration>
              <startup>
                  <supportedRuntime version="v4.0" sku=".NETFramework,Version=v4.7.2" />
              </startup>
         <basicHttpBinding>
                  <binding name="BasicHttpBinding_IMedia" />
                </basicHttpBinding>
             </bindings>
               <endpoint address="http://localhost:8000/PC" binding="basicHttpBinding"</pre>
                    bindingConfiguration="BasicHttpBinding_IMedia" contract="IMedia"
                    name="BasicHttpBinding_IMedia" />
            </system.serviceModel>
          </configuration>
```

```
proxy.cs ≠ X
C# Miscellaneous Files
          [System.Diagnostics.DebuggerStepThroughAttribute()]
[System.CodeDom.Compiler.GeneratedCodeAttribute("System.ServiceModel", "4.0.0.0")]
public partial class MediaClient: System.ServiceModel.ClientBase<IMedia>, IMedia
             public MediaClient(string endpointConfigurationName, System.ServiceModel.EndpointAddress remoteAddress) :
    base(endpointConfigurationName, remoteAddress)
             public void SaveMedia(string path, string events, string persons, string peisaj, string locatie, string altele, System.DateTime creationDate)
{
                base.Channel.SaveMedia(path, events, persons, peisaj, locatie, altele, creationDate);
             public System.Threading.Tasks.Task SaveMediaAsync(string path, string events, string persons, string peisaj, string locatie, string altele, System.DateTime creationDate)
             return base.Channel.SaveMediaAsync(path, events, persons, peisaj, locatie, altele, creationDate); }
             public void DeleteMedia(string path)
{
             base.Channel.DeleteMedia(path);
             public System.Threading.Tasks.Task DeleteMediaAsync(string path)
             return base.Channel.DeleteMediaAsync(path);
             public object ShowGridData()
             return base.Channel.ShowGridData();
}
             public System.Threading.Tasks.Task<object> ShowGridDataAsync()
{
                return base.Channel.ShowGridDataAsync();
```

In urma modificarii GUI prin adaugarea instantei clasei MediaClient codul arata in felul urmator, exemplu:

```
private void buttonEdit_Click(object sender, EventArgs e)
{
    string pathForEdit = textBoxDeleteEditPath.Text;
    string editEvent = textBoxDeleteEditEvent.Text;
    string editPerson = textBoxDeleteEditPerson.Text;
    string editPeisaj = textBoxDeleteEditPeisaj.Text;
    string editLoc = textBoxDeleteEditPeisaj.Text;
    string editLoc = textBoxDeleteEditLoc.Text;
    string editAltele = textBoxDeleteEditAltele.Text;
    newMediaClient.EditData(pathForEdit, editEvent, editPerson, editPeisaj, editLoc, editAltele);
}
```