

# Using Two-Level Type Theory for Staged Compilation

---

**András Kovács<sup>a</sup>**

18 January 2022, Programming Languages and Compilers Department Workshop

---

<sup>a</sup>The author was supported by the European Union, co-financed by the European Social Fund (EFOP-3.6.3-VEKOP-16-2017-00002).

# Staged Compilation

Programs which generate programs.

# Staged Compilation

Programs which generate programs.

With extra features:

- Guaranteed well-typed output.
- Lightweight syntax.
- Seamless integration of object-level and meta-level.

# Staged Compilation

Programs which generate programs.

With extra features:

- Guaranteed well-typed output.
- Lightweight syntax.
- Seamless integration of object-level and meta-level.

Price to pay: some metaprograms are not expressible.

# Two-Level Type Theory

Voevodsky's Homotopy Type System [[Voe13](#)], 2LTT [[ACKS19](#)].

Original motivation: metaprogramming, with HoTT as object theory

# Two-Level Type Theory

Voevodsky's Homotopy Type System [[Voe13](#)], 2LTT [[ACKS19](#)].

Original motivation: metaprogramming, with HoTT as object theory

Turns out to implement two-stage programming:

- Works for wide range of theories

# Two-Level Type Theory

Voevodsky's Homotopy Type System [[Voe13](#)], 2LTT [[ACKS19](#)].

Original motivation: metaprogramming, with HoTT as object theory

Turns out to implement two-stage programming:

- Works for wide range of theories
- Simple rules

# Two-Level Type Theory

Voevodsky's Homotopy Type System [[Voe13](#)], 2LTT [[ACKS19](#)].

Original motivation: metaprogramming, with HoTT as object theory

Turns out to implement two-stage programming:

- Works for wide range of theories
- Simple rules
- Fast staging with NbE



# Two-Level Type Theory

Voevodsky's Homotopy Type System [[Voe13](#)], 2LTT [[ACKS19](#)].

Original motivation: metaprogramming, with HoTT as object theory

Turns out to implement two-stage programming:

- Works for wide range of theories
- Simple rules
- Fast staging with NbE
- Nice model theory and standard semantics

- $U_0$  (object-level) and  $U_1$  (meta-level) universes, both closed under arbitrary type formers.
- Constructors and eliminators **stay within** universes!

- $U_0$  (object-level) and  $U_1$  (meta-level) universes, both closed under arbitrary type formers.
- Constructors and eliminators **stay within** universes!
- For  $A : U_0$ , we have  $\text{Code } A : U_1$

- $U_0$  (object-level) and  $U_1$  (meta-level) universes, both closed under arbitrary type formers.
- Constructors and eliminators **stay within** universes!
- For  $A : U_0$ , we have  $\text{Code } A : U_1$
- Quoting: for  $A : U_0$  and  $t : A$  we have  $\langle t \rangle : \text{Code } A$

- $U_0$  (object-level) and  $U_1$  (meta-level) universes, both closed under arbitrary type formers.
- Constructors and eliminators **stay within** universes!
- For  $A : U_0$ , we have  $\text{Code } A : U_1$
- Quoting: for  $A : U_0$  and  $t : A$  we have  $\langle t \rangle : \text{Code } A$
- Splicing: for  $t : \text{Code } A$ , we have  $\sim t : A$

- $U_0$  (object-level) and  $U_1$  (meta-level) universes, both closed under arbitrary type formers.
- Constructors and eliminators **stay within** universes!
- For  $A : U_0$ , we have  $\text{Code } A : U_1$
- Quoting: for  $A : U_0$  and  $t : A$  we have  $\langle t \rangle : \text{Code } A$
- Splicing: for  $t : \text{Code } A$ , we have  $\sim t : A$
- $\langle \sim t \rangle = t$
- $\sim \langle t \rangle = t$

- $U_0$  (object-level) and  $U_1$  (meta-level) universes, both closed under arbitrary type formers.
- Constructors and eliminators **stay within** universes!
- For  $A : U_0$ , we have  $\text{Code } A : U_1$
- Quoting: for  $A : U_0$  and  $t : A$  we have  $\langle t \rangle : \text{Code } A$
- Splicing: for  $t : \text{Code } A$ , we have  $\sim t : A$
- $\langle \sim t \rangle = t$
- $\sim \langle t \rangle = t$

Staging: computing away every meta-level subterm in an object-level term.

# Identity functions

$\text{id}_0 : (A : \mathcal{U}_0) \rightarrow A \rightarrow A$

$\text{id}_0 \text{ Bool}_0 \text{ true}_0 : \text{Bool}_0$



# Identity functions

$\text{id}_1 : (A : U_1) \rightarrow A \rightarrow A$

$\text{id}_1 \text{ Bool}_1 \text{ true}_1 : \text{Bool}_1$

$\text{id}_1 (\text{Code Bool}_0) \langle \text{true}_0 \rangle : \text{Code Bool}_0$

## Quantifying over $\text{Code } U_0$

Inlined object-level map:

$$\begin{aligned} \text{map} &: (A\ B : \text{Code } U_0) \rightarrow (\text{Code}(\sim A) \rightarrow \text{Code}(\sim B)) \rightarrow \text{Code}(\text{List}_0(\sim A)) \rightarrow \text{Code}(\text{List}_0(\sim B)) \\ \text{map } \langle \text{Nat}_0 \rangle \langle \text{Nat}_0 \rangle (\lambda x. \langle (\sim x) + 10 \rangle) &: \text{Code}(\text{List}_0 \text{Nat}_0) \rightarrow \text{Code}(\text{List}_0 \text{Nat}_0) \end{aligned}$$

$$\text{Vec} : \text{Nat}_1 \rightarrow \text{Code } U_0 \rightarrow \text{Code } U_0$$
$$\text{Vec zero}_1 \quad A = \langle \top_0 \rangle$$
$$\text{Vec (suc}_1 n) A = \langle (\sim A) \times_0 \sim (\text{Vec } n A) \rangle$$

# Staging Types, Inference

$$\begin{aligned}\text{Vec} &: \text{Nat}_1 \rightarrow \text{Code } U_0 \rightarrow \text{Code } U_0 \\ \text{Vec zero}_1 \quad A &= \langle \top_0 \rangle \\ \text{Vec (suc}_1 n) A &= \langle (\sim A) \times_0 \sim (\text{Vec } n A) \rangle\end{aligned}$$

With annotation inference:

$$\begin{aligned}\text{Vec} &: \text{Nat}_1 \rightarrow U_0 \rightarrow U_0 \\ \text{Vec zero}_1 \quad A &= \top_0 \\ \text{Vec (suc}_1 n) A &= A \times_0 \text{Vec } n A\end{aligned}$$

Demo: well-typed staged STLC interpreter, all annotations inferred.

# Weak Object Language + Strong Metalanguage

Simpler object theory  $\rightarrow$  better performance

2LTT recovers features for free: universe,  $\Pi$ ,  $\Sigma$

## Simple TT at Object-Level

A system for monomorphization.

## Simple TT at Object-Level

A system for monomorphization.

Universe of object types:  $Ty : U_1$ ,  $Code : Ty \rightarrow U_1$ .

$$id : (A : Ty) \rightarrow Code(A \rightarrow A)$$

## Simple TT at Object-Level

A system for monomorphization.

Universe of object types:  $Ty : U_1$ ,  $Code : Ty \rightarrow U_1$ .

$$id : (A : Ty) \rightarrow Code(A \rightarrow A)$$

Higher-rank polymorphism via inlining:

$$poly : ((A : Ty) \rightarrow Code A \rightarrow Code A) \rightarrow (Code Bool, Code Int)$$

What we can't do: store polymorphic functions in object-level data.



# First-Order Functions at Object-Level

A system for closure-free compilation.

# First-Order Functions at Object-Level

A system for closure-free compilation.

2LTT gives us higher-order functions for free.

# First-Order Functions at Object-Level

A system for closure-free compilation.

2LTT gives us higher-order functions for free.

What we can't do: store functions in object-level data.

# First-Order Functions at Object-Level

A system for closure-free compilation.

2LTT gives us higher-order functions for free.

What we can't do: store functions in object-level data.

Surprisingly expressive.

# Memory Layout-Indexed Types at Object-Level

A system for layout polymorphism (levity polymorphism).

$$\text{id} : (L : \text{Layout}) \rightarrow (A : U_0 L) \rightarrow \text{Code}(A \rightarrow A)$$

Staging computes layouts to closed canonical values.

Presheaves over the syntactic category of object theory.

Presheaves over the syntactic category of object theory.

Code is “dependent” Yoneda-embedding.

Presheaves over the syntactic category of object theory.

Code is “dependent” Yoneda-embedding.

Choice of morphisms in the base category:



Presheaves over the syntactic category of object theory.

Code is “dependent” Yoneda-embedding.

Choice of morphisms in the base category:

- Substitutions: only generative staging

Presheaves over the syntactic category of object theory.

Code is “dependent” Yoneda-embedding.

Choice of morphisms in the base category:

- Substitutions: only generative staging
- Weakenings: allows Code analysis, but fewer object theories

<https://github.com/AndrasKovacs/implicit-fun-elaboration/tree/staging>

WIP: <https://github.com/AndrasKovacs/staged>

Danil Annenkov, Paolo Capriotti, Nicolai Kraus, and Christian Sattler.

**Two-level type theory and applications.**

*ArXiv e-prints*, may 2019.

Vladimir Voevodsky.

**A simple type system with two identity types.**

*Unpublished note*, 2013.