

# Closure-Free Functional Programming in a Two-Level Type Theory

ANONYMOUS AUTHOR(S)

Many abstraction tools in functional programming rely heavily on general-purpose compiler optimization to achieve adequate performance. For example, monadic binding is a higher-order function which yields runtime closures in the absence of sufficient compile-time inlining and beta-reductions, thereby significantly degrading performance. In current systems such as the Glasgow Haskell Compiler, there is no strong guarantee that general-purpose optimization can eliminate abstraction overheads, and users only have indirect and fragile control over code generation through inlining directives and compiler options. We propose a two-stage language to simultaneously get strong guarantees about code generation and strong abstraction features. The object language is a simply-typed first-order language which can be compiled without runtime closures. The compile-time language is a dependent type theory. The two are integrated in a two-level type theory.

We demonstrate two applications of the system. First, we develop monads and monad transformers. Here, abstraction overheads are eliminated by staging and we can reuse almost all definitions from the existing Haskell ecosystem. Second, we develop pull-based stream fusion. Here we make essential use of dependent types to give a concise definition of a `concatMap` operation with guaranteed fusion. We provide an Agda implementation and a typed Template Haskell implementation of these developments.

CCS Concepts: • **Theory of computation** → **Type theory**; • **Software and its engineering** → **Source code generation**.

Additional Key Words and Phrases: two-level type theory, staged compilation

## ACM Reference Format:

Anonymous Author(s). 2024. Closure-Free Functional Programming in a Two-Level Type Theory. 1, 1 (June 2024), 33 pages. <https://doi.org/10.1145/nnnnnnn.nnnnnnn>

## 1 INTRODUCTION

Modern functional programming supports many convenient abstractions. These often come with significant runtime overheads. Sometimes the overheads are acceptable, but in other cases compiler optimization is crucial. Monads in Haskell is an example for the latter. Even the Reader monad, which is one of the simplest in terms of implementation, yields large overheads when compiled without optimizations. Consider the following:

```
f :: Int → Reader Bool Int
f x = do { b ← ask; if x then return (x + 10) else return (x + 20) }
```

With optimizations enabled, GHC compiles this roughly to the code below:

```
f :: Int → Bool → Int
f = λ x b. if b then x + 10 else x + 20
```

---

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for components of this work owned by others than the author(s) must be honored. Abstracting with credit is permitted. To copy otherwise, or republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee. Request permissions from [permissions@acm.org](mailto:permissions@acm.org).

© 2024 Copyright held by the owner/author(s). Publication rights licensed to ACM.

ACM XXXX-XXXX/2024/6-ART

<https://doi.org/10.1145/nnnnnnn.nnnnnnn>

Without optimizations we roughly get:

```
f = λ x. (>>=) monadReader (ask monadReaderReader) (λ b. if b
    then return monadReader (x + 10)
    else return monadReader (x + 20))
```

Here, `monadReader` and `monadReaderReader` are runtime dictionaries, respectively for the `Monad` and `MonadReader` instances, and, for example, `(>>=) monadReader` is a field projection from the dictionary. We get a runtime closure from the `λ b. ...` function, and `(>>=)`, `ask` and `return` also produce additional closures.

The difference between optimized and unoptimized code is already large here, and it gets even larger when we consider monad transformers or code that is polymorphic over monads. In Haskell, such code is pervasive, even in fairly basic programs which do not use fancy abstractions. Consider the `mapM` function from the Haskell Prelude:

```
mapM :: Monad m => (a -> m b) -> [a] -> m [b]
```

This is a third-order rank-2 polymorphic function in disguise, because its monad dictionary argument contains the polymorphic second-order method `(>>=)`. Compiling `mapM` efficiently relies on inlining the instance dictionary, then inlining the methods contained there, and also inlining the functions that the higher-order binding is applied to.

GHC's optimization efforts are respectable, and it has gotten quite adept over its long history of development. However, there is no strong guarantee that certain optimizations will happen. Control over optimizations remains tricky, fragile and non-compositional. `INLINE` and `REWRITE` pragmas can be used to control code generation [GHC developers 2024a], but without strong guarantees, and their advanced usage requires knowledge of GHC internals. For example, correctly specifying the *ordering* of certain rule applications is often needed. We also have to care about formal function arities. Infamously, the function composition operator is defined as `(.) f g = λ x -> f (g x)` in the base libraries, instead of as `(.) f g x = f (g x)`, to get better inlining behavior [GHC developers 2024b]. It is common practice in high-performance Haskell programming to visually review GHC's optimized code output.

### 1.1 Closure-Free Staged Compilation

In this paper we use staged compilation to address issues of robustness. The idea is to shift as much work as possible from general-purpose optimization to metaprograms.

Metaprograms can be deterministic, transparent, and can be run efficiently, using fast interpreters or machine code compilation. In contrast, general-purpose optimizers are slower to run, less transparent and less robust. Also, metaprogramming allows library authors to exploit domain-specific optimizations, while it is not realistic for general-purpose optimizers to know about all domains.

On the other hand, metaprogramming requires some additional care and input from programmers. Historically, there have been problems with ergonomics as well. In weakly-typed staged systems, code generation might fail *too late* in the pipeline, producing incomprehensible errors. Or, tooling that works for an object language (like debugging, profiling, IDEs) may not work for metaprogramming, or metaprogramming may introduce heavy noise and boilerplate, obscuring the logic of programs and imposing restrictions on code structure.

**Two-level type theory** (2LTT) [Annenkov et al. 2019; Kovács 2022] makes it possible to use expressive dependent type theories for metaprogramming for a wide range of object languages. In this paper, we use 2LTT to sweeten the deal of staged compilation, aiming for a combination of strong guarantees, good ergonomics, high level of abstraction and easy-to-optimize code output.

We develop a particular two-level type theory for this purpose, which we call **CFTT**, short for “closure-free type theory”. This consists of:

- A simply-typed object theory with first-order functions, general recursion and finitary algebraic data types. This language is easy to optimize and compile in the downstream pipeline, but it lacks many convenience features.
- A dependent type theory for the compile-time language. This allows us to recover many features by metaprogramming.

Since the object language is first-order, we guarantee that all programs in CFTT can be ultimately compiled without any dynamic closures, using only calls and jumps to statically known code. Why emphasize closures? They are the foundation to almost all abstraction tools in functional programming:

- Higher-order functions in essentially all functional languages are implemented with closures.
- Type classes in Haskell use dictionary-passing, which relies on closures for function methods [Wadler and Blott 1989].
- Functors and first-class modules in OCaml [Leroy et al. 2023] and other ML-s rely on closures.

Hence, doing functional programming without closures is a clear demonstration that we can get rid of abstraction overheads.

Perhaps surprisingly, little practical programming relies essentially on closures. Most of the time, programmers use higher-order functions for *abstraction*, such as when mapping over lists, where it is expected that the mapping function will be inlined. We note though that our setup is compatible with closures as well, and it can support two separate type formers for closure-based and non-closure-based “static” functions. Having both of these would be desirable in a practical system. In the current work we focus on the closure-free case because it is much less known and developed, and it is interesting to see how far we can go with it.

## 1.2 Contributions

- In Section 2 we present the two-level type theory CFTT, where the object level is first-order simply-typed and the meta level is dependently typed. The object language supports an operational semantics without runtime closures, and can be compiled with only statically known function calls. We provide a supplementary Agda formalization of the operational semantics of the object language.
- In Section 3 we build a staged library for monad transformers [Liang et al. 1995]. We believe that this is a good demonstration, because monads and monad transformers are the most widely used effect system in Haskell, and at the same time their compilation to efficient code can be surprisingly difficult. The continuation monad is well-known in staged compilation [Bondorf 1992], and staged state monads have also been used [Carette and Kiselyov 2011; Kiselyov et al. 2004; Swadi et al. 2006]. These works used specific monads as tools for domain-specific code generation. In contrast, we propose ubiquitous staging for general-purpose monadic programming, where users can write code that looks similar to monadic code in Haskell but with deterministic and robust compilation to efficient code.
- In Section 4 we build a pull-based stream fusion library. Here, we demonstrate essential usage of dependent types, in providing guaranteed fusion for arbitrary combinations of `concatMap` and `zip`. We use a state machine representation that is based on *sums-of-products* of object-level values. We show that CFTT is compatible with a *generativity* axiom, which internalizes the fact that metaprograms cannot inspect the structure of object-level terms.

We use this to show that the universe of sums-of-products is closed under  $\Sigma$ -types. This in turn enables a very concise definition of `concatMap`.

- We adapt the contents of the paper to typed Template Haskell [Xie et al. 2022], with some modifications, simplifications and fewer guarantees about generated code. In particular, Haskell does not have enough dependent types for the simple `concatMap` definition, but we can still work around this limitation. We also provide a precise Agda embedding of CFTT and our libraries as described in this paper. Here, the object theory is embedded as a collection of postulated operations, and we can use Agda’s normalization command to print out generated object code.

## 2 OVERVIEW OF CFTT

In the following we give an overview of CFTT features. We first review the meta-level language, then the object-level one, and finally the staging operations which bridge between the two.

### 2.1 The Meta Level

**MetaTy** is the universe of types in the compile-time language. We will often use the term “metatype” to refer to inhabitants of **MetaTy**, and use “metaprogram” for inhabitants of metatypes. **MetaTy** supports dependent functions,  $\Sigma$ -types and indexed inductive types [Dybjer 1994].

Formally, **MetaTy** is additionally indexed by universes levels (orthogonally to staging), and we have  $\text{MetaTy}_i : \text{MetaTy}_{i+1}$ . However, universe levels add noise and they are not too relevant to the current paper, so we will omit them.

Throughout this paper we use a mix of Agda and Haskell syntax for CFTT. Dependent functions and implicit arguments follow Agda. A basic example:

$$\begin{aligned} \text{id} &: \{A : \text{MetaTy}\} \rightarrow A \rightarrow A \\ \text{id} &= \lambda x. x \end{aligned}$$

Here, the type argument is implicit, and it gets inferred when we use the function. For example, `id True` is elaborated to `id {Bool} True`, where the braces mark an explicit application for the implicit argument. Inductive types can be introduced using a Haskell-like ADT notation, or with a GADT-style one:

$$\begin{aligned} &\text{data Bool}_M : \text{MetaTy} \text{ where} \\ &\quad \text{data Bool}_M : \text{MetaTy} = \text{True}_M \mid \text{False}_M & \text{True}_M &: \text{Bool}_M \\ & & \text{False}_M &: \text{Bool}_M \end{aligned}$$

Note that we added an  $_M$  subscript to the type; when analogous types can be defined both on the meta and object levels, we will sometimes use this subscript to disambiguate the meta-level version.

We use Haskell-like `newtype` notation, such as in `newtype Wrap A = Wrap {unwrap : A}`, and also a similar notation for (dependent) record types, for instance as in

$$\text{data Record} = \text{Record} \{ \text{field1} : A, \text{field2} : B \}.$$

All construction and elimination rules for type formers in **MetaTy** stay within **MetaTy**. For example, induction on meta-level values can only produce meta-level values.

### 2.2 The Object Level

**Ty** is the universe of types in the object language. It is itself a metatype, so we have  $\text{Ty} : \text{MetaTy}$ . All construction and elimination rules of type formers in **Ty** stay within **Ty**. We further split **Ty** to two sub-universes.

First, **ValTy** : MetaTy is the universe of *value types*. ValTy supports parameterized algebraic data types, where parameters can have arbitrary types, but all constructor field types must be in ValTy. Since ValTy is a sub-universe of Ty, we have that when  $A : \text{ValTy}$  then also  $A : \text{Ty}$ . Formally, this is specified as an explicit embedding operation, but we will use implicit subtyping for convenience.

Second, **CompTy** : MetaTy is the universe of *computation types*. This is also a sub-universe of Ty with implicit coercions. For now, we only specify that CompTy contains functions whose domains are value types:

$$- \rightarrow - : \text{ValTy} \rightarrow \text{Ty} \rightarrow \text{CompTy}$$

For instance, if  $\text{Bool} : \text{ValTy}$  is defined as an object-level ADT, then  $\text{Bool} \rightarrow \text{Bool} : \text{CompTy}$ , hence also  $\text{Bool} \rightarrow \text{Bool} : \text{Ty}$ . However,  $(\text{Bool} \rightarrow \text{Bool}) \rightarrow \text{Bool}$  is ill-formed, since the domain is not a value type. Let us look at an example for an object-level program, where we already have natural numbers declared as  $\text{data Nat} := \text{Zero} \mid \text{Suc Nat}$ :

```

add : Nat → Nat → Nat
add := letrec go n m := case n of
    Zero → m;
    Suc n → Suc (go n m);
go

```

Recursive definitions are introduced with **letrec**. The general syntax is **letrec**  $x : A := t; u$ , where the  $A$  type annotation can be omitted. **letrec** can be only used to define computations, not values (hence, only functions can be recursive so far).

Object-level definitions use  $:=$  as notation, instead of the  $=$  that is used for meta-level ones. We also have non-recursive **let**, which can be used to define computations and values alike, and can be used to shadow binders:

```

f : Nat → Nat
f x := let x := x + 10; let x := x + 20; x * 10

```

We also allow **newtype** definitions, both in ValTy and CompTy. These are assumed to be erased at runtime. In the Haskell implementation they are important for guiding type class resolution, and we think that the explicit wrapping makes many definitions more comprehensible in CFTT as well.

Values are call-by-value at runtime; they are computed eagerly in function applications and **let**-s. **let**-definitions can be used to define inhabitants of any type, and the type of the **let** body can be also arbitrary. Additionally, the right hand sides of **case** branches can also have arbitrary types. So the following is well-formed:

```

f : Bool → Nat → Nat
f b := case b of True → (λ x. x + 10); False → (λ x. x * 10)

```

In contrast, computations are call-by-name, and the only way we can compute with functions is to apply them to value arguments. The call-by-name strategy is fairly benign here and does not lead to significant duplication of computation, because functions cannot escape their scope; they cannot be passed as arguments or stored in data constructors. This makes it possible to run object programs without using dynamic closures. This point is not completely straightforward; consider the previous  $f$  function which has  $\lambda$ -expressions under a **case**.

However, the call-by-name semantics lets us transform  $f$  to  $\lambda b x. \text{case } b \text{ of True} \rightarrow x + 10; \text{False} \rightarrow x * 10$ , and more generally we can transform programs so that every function call becomes *saturated*. This means that every function call is of the form  $f \ t_1 \ t_2 \ \dots \ t_n$ , where  $f$  is a function variable and the definition of  $f$  immediately  $\lambda$ -binds  $n$  arguments. We do not detail this here. We provide formal

syntax and operational semantics of the object language in the Agda supplement. We formalized the specific translation steps that are involved in call saturation, but only specified the full translation informally.

**2.2.1 Object-level definitional equality.** This is a distinct notion from runtime semantics. Object programs are embedded in CFTT, which is a dependently typed language, so sometimes we need to decide definitional equality of object programs during type checking. The setup is simple: we have no  $\beta$  or  $\eta$  rules for object programs at all, nor any rule for **let**-unfolding. The main reason is the following: we care about the size and efficiency of generated code, and these properties are not stable under  $\beta\eta$ -conversion and **let**-unfolding. Moreover, since the object language has general recursion, we do not have a sensible and decidable notion of program equivalence anyway.

**2.2.2 Comparison to call-by-push-value.** We took inspiration from call-by-push-value (CBPV) [Levy 1999], and there are similarities to our object language, but there are also significant differences. Both systems have a value-computation distinction, with call-by-name computations and call-by-value values. However, our object theory supports variable binding at arbitrary types while CBPV only supports value variables. In CBPV, a let-definition for a function is only possible by first packing it up as a closure value (or “thunk”), which clearly does not suit our applications. Investigating the relation between CBPV and our object language could be future work.

## 2.3 Staging

With what we have seen so far, there is no interaction between the meta and object levels. We make such interaction possible with the following primitives.

- For  $A : \text{Ty}$ , we have  $\uparrow A : \text{MetaTy}$ , pronounced as “lift  $A$ ”. This is the type of metaprograms that produce  $A$ -typed object programs.
- For  $A : \text{Ty}$  and  $t : A$ , we have  $\langle t \rangle : \uparrow A$ , pronounced “quote  $t$ ”. This is the metaprogram which immediately returns  $t$ .
- For  $t : \uparrow A$ , we have  $\sim t : A$ , pronounced “splice  $t$ ”. This inserts the result of a metaprogram into an object term. *Notation:* splicing binds stronger than function application, so  $f \sim x$  is parsed as  $f (\sim x)$ . We borrow this from MetaML [Taha and Sheard 2000].
- We have  $\langle \sim t \rangle \equiv t$  and  $\sim \langle t \rangle \equiv t$  as definitional equalities.

We use **unstaging** to refer to the process of extracting object code from CFTT programs, by evaluating all metaprograms in splices. This term has been sporadically used in the literature, e.g. by Odersky and Rompf [Rompf and Odersky 2012] and also by Choi et al. [Choi et al. 2011] with a somewhat different meaning in a multi-stage context. The main precursor to this paper used “staging” instead of our “unstaging” [Kovács 2022]; we use the latter because the former conflicts with other common usages of “staging”.

Let us look at some basic examples. Recall the meta-level identity function; it can be used at the object-level too, by applying it to quoted terms:

$$\text{let } n : \text{Nat} := \sim(\text{id } \langle 10 + 10 \rangle); \dots$$

Here,  $\text{id}$  is used at type  $\uparrow \text{Nat}$ . During unstaging, the expression in the splice is evaluated, so we get  $\sim \langle 10 + 10 \rangle$ , which is definitionally the same as  $10 + 10$ , which is our code output here. Boolean short-circuiting is another basic use-case:

$$\text{and} : \uparrow \text{Bool} \rightarrow \uparrow \text{Bool} \rightarrow \uparrow \text{Bool}$$

$$\text{and } x \ y = \langle \text{case } \sim x \text{ of True} \rightarrow \sim y; \text{False} \rightarrow \text{False} \rangle$$

Since the  $y$  expression is inlined under a **case** branch at every use site, it is only computed at runtime when  $x$  evaluates to **True**. In many situations, staging can be used instead of laziness to



implement short-circuiting, and often with better runtime performance, avoiding the overhead of thunking. Consider the map function now:

```

map : {A B : ValTy} → (↑A → ↑B) → ↑(List A) → ↑(List B)
map f as = ⟨letrec go as := case as of
           Nil          → Nil;
           Cons a as    → Cons ~⟦f⟧(a) (go as);
           go ~as⟩

```

For example, this can be used as  $\text{let } f \text{ as : List Nat} \rightarrow \text{List Nat} := \sim(\text{map } (\lambda x. \langle \sim x + 10 \rangle) \langle \text{as} \rangle)$ . This is unstaged to a recursive definition where the mapping function is inlined into the Cons case as  $\text{Cons } a \text{ as} \rightarrow \text{Cons } (a + 10) (\text{go as})$ . Note that map has to abstract over value types, since lists can only contain values, not functions. Also, the mapping function has type  $\uparrow A \rightarrow \uparrow B$ , instead of  $\uparrow(A \rightarrow B)$ . The former type is often preferable to the latter; the former is a metafunction with useful computational content, while the latter is merely a black box that computes object code. If we have  $f : \uparrow(A \rightarrow B)$ , and  $f$  computes to  $\langle \lambda x. t \rangle$ , then  $\sim f u$  is unstaged to an undesirable “administrative”  $\beta$ -redex  $(\lambda x. t) u$ .

**2.3.1 Comparison to defunctionalization.** Defunctionalization is a program translation which represents higher-order functions using only first-order functions and inductive data [Danvy and Nielsen 2001; Reynolds 1998]. The idea is to represent each closure as a constructor of an inductive type, and implement closure application as a top-level first-order function which switches on all possible closure constructors. Hence, like our unstaging algorithm, defunctionalization produces first-order code from higher-order code. We summarize the differences.

- Defunctionalization mainly supports *compiler optimizations*, by making closures transparent to analysis. It is not an optimization by itself; it does not change the amount of dynamic control flow or dynamic allocations in a program. A dynamic closure call becomes a dynamic case-switch and a heap-allocated “functional” closure becomes a heap-allocated inductive constructor.
- Staging mainly supports optimization by *programmers* by providing control over code generation. Unstaging does not translate higher-order functions to anything in particular. Instead, it is the execution of higher-order metaprograms that produce first-order programs.

## 2.4 Staged Semantics of CFTT

We give an overview of the unstaging algorithm together with its correctness. Our main task is to extend [Kovács 2022] with identity types and inductive types in the metalanguage, since we use them in this paper. For inductive types, it is the most sensible to add W-types, since all inductive families can be faithfully derived from them in our setting [Hugunin 2020].

This however requires a substantial amount of technical background from [Kovács 2022], so we relegate it to Appendix A. Here we only give an overview.

- The input of unstaging is a CFTT term with an object-level type, which only depends on object-level free variables. The output is a term in the object theory. In the other direction, there is an evident embedding of object-theoretic terms as CFTT terms.
- *Soundness* means that unstaging followed by embedding is the identity map, up to conversion. In other words, unstaging respects conversion of CFTT terms.
- *Stability* means that embedding followed by unstaging is the identity map. In other words, unstaging has no action on terms which are already purely object-level (i.e. contain no splices).

In [Kovács 2022], there is one more property, called *strictness*, which means that unstaging does not perform  $\beta\eta$ -conversion in the object theory, but this holds trivially in our case since we do not have such conversion rules.

However, for CFTT we slightly depart from the above notion of soundness, for the following reason. We would like to assume certain propositional identities as *axioms* in the metalanguage, without blocking unstaging as a computation. We use such an axiom to good effect in Section 4.3.

Axioms clearly block computation, so they are incompatible with the mentioned notion of soundness. But we are only interested in equations which hold definitionally during unstaging. Hence, we can do the following: first, we erase all identity proofs and their transports from CFTT programs, then we proceed with unstaging as in [Kovács 2022]. This erasure can be formalized as a syntactic translation [Boulier et al. 2017] from CFTT to CFTT extended with the equality reflection principle, which says that propositional equality implies definitional equality (see e.g. [Hofmann 1995]). Thus, soundness of staging for CFTT holds up to erasure of identity proofs.

### 3 MONADS & MONAD TRANSFORMERS

In this section we build a library for monads and monad transformers. We believe that this is a good demonstration of CFTT's abilities, since monads are ubiquitous in Haskell programming and they also introduce a great amount of abstraction that should be optimized away.

#### 3.1 Binding-Time Improvements

We do a preliminary overview before getting to monads. In the staged compilation and partial evaluation literature, the term *binding time improvement* is used to refer to such conversions, where the “improved” version supports more compile-time computation [Jones et al. 1993, Chapter 12].

Translation from  $\uparrow A \rightarrow \uparrow B$  to  $\uparrow(A \rightarrow B)$  is a basic binding-time improvement, as an  $\eta$ -expansion [Danvy et al. 1996]. The two types are equivalent during unstaging, up to the runtime equivalence of object programs, and we can convert back and forth in CFTT, the same way as in MetaML [Taha and Sheard 2000, Section 9]:

$$\begin{array}{ll} \mathbf{up} : \uparrow(A \rightarrow B) \rightarrow \uparrow A \rightarrow \uparrow B & \mathbf{down} : (\uparrow A \rightarrow \uparrow B) \rightarrow \uparrow(A \rightarrow B) \\ \mathbf{up} \, f \, a = \langle \sim f \, \sim a \rangle & \mathbf{down} \, f = \langle \lambda a. \sim(f \, \langle a \rangle) \rangle \end{array}$$

We cannot show internally, using propositional equality, that these functions are inverses, since we do not have  $\beta\eta$ -rules for object functions; but we will not need this proof in the rest of the paper.

A general strategy for generating efficient “fused” programs, is to try to work as much as possible with improved representations, and only convert back to object code at points where runtime dependencies are unavoidable. Let us look at binding-time-improvement for product types now:

$$\begin{array}{ll} \mathbf{up} : \uparrow(A, B) \rightarrow (\uparrow A, \uparrow B) & \mathbf{down} : (\uparrow A, \uparrow B) \rightarrow \uparrow(A, B) \\ \mathbf{up} \, x = (\langle \mathbf{fst} \, \sim x \rangle, \langle \mathbf{snd} \, \sim x \rangle) & \mathbf{down} \, (x, y) = \langle (\sim x, \sim y) \rangle \end{array}$$

Here we overload Haskell-style product type notation, both for types and the pair constructor, at both levels. There is a problem with this conversion though: **up** uses  $x : \uparrow(A, B)$  twice, which can increase code size and duplicate runtime computations. For example, **down** (**up** ( $f \, x$ )) is staged to  $\langle (\mathbf{fst} \, (f \, x), \mathbf{snd} \, (f \, x)) \rangle$ . It would be safer to first let-bind an expression with type  $\uparrow(A, B)$ , and then only use projections of the newly bound variable. This is called *let-insertion* in staged compilation. But it is impossible to use let-insertion in **up** because the return type is in MetaTy, and we cannot introduce object binders in meta-level code.



### 3.2 The Code Generation Monad

A principled solution to the previous issue is to write code generators in continuation-passing style, as first proposed by Bondorf [Bondorf 1992]. This can be structured as a continuation monad, and later work used explicit monadic notation for it [Carette and Kiselyov 2011; Kiselyov et al. 2004; Swadi et al. 2006]. Our definition is as follows:

```
newtype Gen (A : MetaTy) = Gen {unGen : {R : Ty} → (A → ↑R) → ↑R}
```

This is a monad in MetaTy in a standard sense:

```
instance Monad Gen where
  return a = Gen $ λ k. k a
  ga ≫ f = Gen $ λ k. unGen ga (λ a. unGen (f a) k)
```

In [Kiselyov et al. 2004], [Carette and Kiselyov 2011] and [Swadi et al. 2006], the answer type is a parameter to the continuation monad, while we have it as polymorphic. We have found that polymorphic answer types are more convenient, because we do not have to anticipate the type of the code output when are defining a code generator. Hence, we can “run” actions as follows:

```
runGen : Gen (↑A) → ↑A
runGen ma = unGen ma id
```

From now on, we reuse Haskell-style type classes and **do**-notation in CFTT. We will use type classes in an informal way, without precisely specifying how they work. However, type classes are used in essentially the same way in the Agda and Haskell implementations, with modest technical differences. From the Monad instance, the Functor and Applicative instances can be also derived. We reuse ( $\langle \$ \rangle$ ) and ( $\langle * \rangle$ ) for applicative notation as well.

We can let-bind object expressions in Gen:

```
gen : {A : Ty} → ↑A → Gen (↑A)
gen a = Gen $ λ k. ⟨let x : A := ~a; ~⟨k ⟨x⟩⟩⟩
```

And also recursive definitions of computations:

```
genRec : {A : CompTy} → (↑A → ↑A) → Gen (↑A)
genRec f = Gen $ λ k. ⟨letrec x : A := ~⟨f ⟨x⟩⟩; ~⟨k ⟨x⟩⟩⟩
```

Now, using **do**-notation, we may write **do** { $x \leftarrow \text{gen } \langle 10 + 10 \rangle$ ;  $y \leftarrow \text{gen } \langle 20 + 20 \rangle$ }; **return**  $\langle x + y \rangle$ }, for a Gen (↑Nat) action. Running this with runGen yields  $\langle \text{let } x := 10 + 10; \text{let } y := 20 + 20; x + y \rangle$ . We can also define a “safer” binding-time improvement for products, using let-insertion:

```
up : ↑(A, B) → Gen (↑A, ↑B)          down : Gen (↑A, ↑B) → ↑(A, B)
up x = do x ← gen x                    down x = do (a, b) ← x
return (⟨fst ~x⟩, ⟨snd ~x⟩)             return ⟨(~a, ~b)⟩
```

Working in Gen is convenient, since we can freely generate object code and also have access to the full metalanguage. Also, the point of staging is that *eventually* all metaprograms will be used for the purpose of code generation, so we eventually runGen all of our actions. So why not just always work in Gen? The implicit nature of Gen may make it harder to reason about the size and content of generated code. This is a bit similar to the IO monad in Haskell [Jones 2001], where eventually everything needs to run in IO, but we may not want to write all of our code in IO.

### 3.3 Monads

First, following the style of Haskell’s monad transformer library `mtl` [mtl developers 2024], we define a class for monads that support code generation.

```
class Monad M ⇒ MonadGen M where
  liftGen : Gen A → M A
```

We also redefine `gen` and `genRec` to work in any `MonadGen`, so from now on we have:

```
gen    : MonadGen M ⇒ ↑A → M (↑A)
genRec : MonadGen M ⇒ (↑A → ↑A) → M (↑A)
```

In the rest of this paper, we shall only mention `ReaderT`, `MaybeT` and `StateT` as monad transformers. For all of these, we can define the `MonadGen` instance simply by `liftGen = lift ∘ liftGen`.

Let us look at the `Maybe` monad now. We have `data Maybe A := Nothing | Just A`, and `Maybe` itself is available as a `ValTy → ValTy` metafunction. However, we cannot directly fashion a monad out of `Maybe`, since we do not have polymorphism in `ValTy`, nor can we store functions inside `Maybe`. We could try to use the following type for binding:

$$(\gg) : \uparrow(\text{Maybe } A) \rightarrow (\uparrow A \rightarrow \uparrow(\text{Maybe } B)) \rightarrow \uparrow(\text{Maybe } B)$$

This would work, but the definition would necessarily use runtime case splits on `Maybe` values, many of which could be optimized away during staging. Also, not having a “real” monad is inconvenient for the purpose of code reuse.

Instead, our strategy is to only use proper monads in `MetaTy`, and convert between object types and meta-monads when necessary, as a form of binding-time improvement. We define a class for this conversion:

```
class MonadGen M ⇒ Improve (F : ValTy → Ty) (M : MetaTy → MetaTy) where
  up   : {A : ValTy} → ↑(F A) → M (↑A)
  down : {A : ValTy} → M (↑A) → ↑(F A)
```

Assume that `MaybeM` is the standard meta-level monad, and `MaybeTM` is the standard monad transformer, defined as follows:

$$\text{newtype MaybeT}_M M A = \text{MaybeT}_M \{ \text{runMaybeT}_M : M (\text{Maybe}_M A) \}$$

Now, the binding-time improvement of `Maybe` is as follows:

```
instance Improve Maybe (MaybeT_M Gen) where
  up ma = MaybeT_M $ Gen $ λ k.
    ⟨case ~ma of Nothing → ~(k Nothing_M); Just a → ~(k (Just_M ⟨a⟩))⟩
  down (MaybeT_M (Gen ma)) =
    ma (λ x. case x of Nothing_M → ⟨Nothing⟩; Just_M a → ⟨Just ~a⟩)
```

With this, we get the `Monad` instance for free from `MaybeTM` and `Gen`. A small example:

```
let n : Maybe Nat := ~(down $ do {x ← return ⟨10⟩; y ← return ⟨20⟩; return ⟨x + y⟩}); ...
```

Since `MaybeTM` is meta-level, its monadic binding fully computes at unstaging time. Thus, the above code is computed to

```
let n : Maybe Nat := Just (10 + 20); ...
```

We can also use `gen` for let-insertion in `MaybeT Gen`, since it has a `MonadGen` instance.

**3.3.1 Case splitting in monads.** We often want to case-split on object-level data inside a monadic action, and perform different actions in different branches. At first, this may seem problematic, because we cannot directly compute metaprograms from object-level case splits. Fortunately, with a little bit more work, this is possible in any `MonadGen`, for any value type, using a variation of the so-called “trick” [Danvy et al. 1996].

We demonstrate this for lists. An object-level `case` on lists introduces two points where code generation can continue. We define a metatype which gives us a “view” on these points:

```
data SplitList A = Nil' | Cons' (↑A) (↑(List A))
```

We can generate code for a case split, returning a view on it:

```
split : ↑(List A) → Gen (SplitList A)
split as = Gen $ λ k. {case ~as of Nil → ~(k Nil'); Cons a as → ~(k (Cons' ⟨a⟩ ⟨as⟩))}
```

Now, in any `MonadGen`, assuming `as : ↑(List A)`, we may write

```
do {sp ← liftGen (split as); (case sp of Nil' → ...; Cons' a as → ...)}
```

This can be generalized to splitting on any object value. In the Agda and Haskell implementations, we overload `split` with a class similar to the following:

```
class Split (A : ValTy) where
  SplitTo : MetaTy
  split    : ↑A → Gen SplitTo
```

In a native implementation of CFTT it may make sense to extend `do`-notation, so that we elaborate `case` on object values to an application of the appropriate `split` function. We adopt this in the rest of the paper, so when working in a `MonadGen`, we can write `case as of Nil → ...; Cons a as → ...`, binding `a : ↑A` and `as : ↑(List A)` in the `Cons` case.

### 3.4 Monad Transformers

At this point, it makes sense to aim for a monad transformer library where binding-time improvement is defined compositionally, by recursion on the transformer stack. The base case is the following:

```
newtype Identity A := Identity {runIdentity : A}
instance Improve Identity Gen where
  up x    = return ⟨runIdentity ~x⟩
  down x = unGen x $ λ a. ⟨Identity ~a⟩
```

We recover the object-level `Maybe` as `MaybeT Identity`, from the following `MaybeT`:

```
newtype MaybeT (M : ValTy → Ty) (A : ValTy) := MaybeT {runMaybeT : M (Maybe A)}
```

With this, improvement can be generally defined for MaybeT:

```

instance Improve F M  $\Rightarrow$  Improve (MaybeT F) (MaybeTM M) where
  up x = MaybeTM $ do
    ma  $\leftarrow$  up  $\langle$ runMaybeT ~x $\rangle$ 
    case ma of Nothing  $\rightarrow$  return NothingM
              Just a    $\rightarrow$  return (JustM a)
  down (MaybeTM x) =  $\langle$ MaybeT ~(down $ x  $\gg$   $\lambda$  case
    NothingM  $\rightarrow$  return  $\langle$ Nothing $\rangle$ 
    JustM a    $\rightarrow$  return  $\langle$ Just ~a $\rangle$ ) $\rangle$ 

```

In the **case** in **up**, we use our syntax sugar for matching on a Maybe value inside an M action. This is legal, since we know from the Improve F M assumption that M is a MonadGen. In **down** we also use  $\lambda$  **case** ... to shorten  $\lambda$  x. **case** x **of** ....

In the meta level, we can reuse essentially all definitions from mt1. From there, only the continuation monad transformer fails to support binding-time-improvement in CFTT, because of the obvious need for dynamic closures. In the following we only present StateT and ReaderT.

We start with StateT. We assume StateT<sub>M</sub> as the standard meta-level definition. The object-level StateT has type (S : ValTy)(F : ValTy  $\rightarrow$  Ty)(A : ValTy)  $\rightarrow$  ValTy; the state parameter S has to be a value type, since it is an input to an object-level function.

```

instance Improve F M  $\Rightarrow$  Improve (StateT S F) (StateTM ( $\uparrow$ S) M) where
  up x = StateTM $  $\lambda$  s. do
    as  $\leftarrow$  up  $\langle$ runStateT ~x ~s $\rangle$ 
    case as of (a, s)  $\rightarrow$  return (a, s)
  down x =  $\langle$ StateT ( $\lambda$  s. ~(down $ do
    (a, s)  $\leftarrow$  runStateTM x  $\langle$ s $\rangle$ 
    return  $\langle$ (~a, ~s) $\rangle$ ) $\rangle$ 

```

Like before in MaybeT, we rely on object-level case splitting in the definition of **up**. For Reader, the environment parameter also has to be a value type, and we define improvement as follows.

```

instance Improve F M  $\Rightarrow$  Improve (ReaderT R F) (ReaderTM ( $\uparrow$ R) M) where
  up x   = ReaderTM $  $\lambda$  r. up  $\langle$ runReaderT ~x ~r $\rangle$ 
  down x =  $\langle$ ReaderT ( $\lambda$  r. ~(down (runReaderTM x  $\langle$ r $\rangle$ ))) $\rangle$ 

```

**3.4.1 State and Reader operations.** If we use the modify function that we already have in State<sub>M</sub>, a curious thing happens. The meaning of modify ( $\lambda$  x.  $\langle$ ~x + ~x $\rangle$ ) is to replace the current state x, as an object expression, with the expression  $\langle$ ~x + ~x $\rangle$ , and this happens at unstaging time. This behaves as an “inline” modification which replaces every subsequent mention of the state with a different expression. For instance, ignoring newtype wrappers for now,

```

down $ do { modify ( $\lambda$  x.  $\langle$ ~x + ~x $\rangle$ ); modify ( $\lambda$  x.  $\langle$ ~x + ~x $\rangle$ ); return  $\langle$ () $\rangle$  }

```

is unstaged to

$$\langle \lambda x. ((), (x + x) + (x + x)) \rangle$$

which duplicates the evaluation of x + x. The duplication can be avoided by let-binding the result in the object language. A similar phenomenon happens with the local function in Reader. So we

define “stricter” versions of these operations. We also return  $\uparrow()$  from actions instead of  $()$  – the former is more convenient, because the **down** operation can be immediately used on it.

```

put' : (MonadState ( $\uparrow$ S) M, MonadGen M)  $\Rightarrow$   $\uparrow$ S  $\rightarrow$  M ( $\uparrow$ ())
put' s = do {s  $\leftarrow$  gen s; put s; return  $\langle$ () $\rangle$ }

modify' : (MonadState ( $\uparrow$ S) M, MonadGen M)  $\Rightarrow$  ( $\uparrow$ S  $\rightarrow$   $\uparrow$ S)  $\rightarrow$  M ( $\uparrow$ ())
modify' f = do {s  $\leftarrow$  get; put' (f s)}

local' : (MonadReader ( $\uparrow$ R) M, MonadGen M)  $\Rightarrow$  ( $\uparrow$ R  $\rightarrow$   $\uparrow$ R)  $\rightarrow$  M A  $\rightarrow$  M A
local' f ma = do {r  $\leftarrow$  ask; r  $\leftarrow$  gen (f r); local ( $\lambda \_.$  r) ma}

```

Now,

```
down $ do {modify' ( $\lambda x.$   $\langle \sim x + \sim x \rangle$ ); modify' ( $\lambda x.$   $\langle \sim x + \sim x \rangle$ )}
```

is unstaged to

```
 $\langle \lambda x.$  let  $x := x + x$ ; let  $x := x + x$ ;  $\langle$  (),  $x \rangle$  $\rangle$ 
```

### 3.5 Joining Control Flow in Monads

There is a deficiency in our library so far. Consider:

```

f : Bool  $\rightarrow$  StateT Nat (MaybeT Identity) ()
f b :=  $\sim$ (down $ do
  case  $\langle b \rangle$  of True  $\rightarrow$  put'  $\langle 10 \rangle$ ; False  $\rightarrow$  put'  $\langle 20 \rangle$ 
  modify' ( $\lambda x.$   $\langle \sim x + \sim x \rangle$ ))

```

This is unstaged to the following (omitting newtype wrappers):

```

f b s := case b of
  True  $\rightarrow$  let s := 10; let s := s + s; Just ( $\langle$  (), s $\rangle$ )
  False  $\rightarrow$  let s := 20; let s := s + s; Just ( $\langle$  (), s $\rangle$ )

```

Notice that the final state modification gets inlined into both branches. The duplication follows from the definition of monadic binding in Gen and the split function in the desugaring of **case**. Code generation is continued in both branches with the same action. If we have multiple Boolean **case** splits sequenced after each other, that yields exponential code size. A possible fix is to let-bind the branching action:

```

f b :=  $\sim$ (down $ do
  act  $\leftarrow$  gen $ down $ case  $\langle b \rangle$  of True  $\rightarrow$  put'  $\langle 10 \rangle$ ; False  $\rightarrow$  put'  $\langle 20 \rangle$ 
  up act
  modify ( $\lambda x.$   $\langle \sim x + \sim x \rangle$ ))

```

However, this yields suboptimal code:

```
f b s :=
  let act s := case b of True → let s := 10; Just((), s)
                    False → let s := 20; Just((), s);
  case act s of
    Just (_, s) → let s := s + s; Just ((), s)
    Nothing → Nothing
```

This solution is fairly good in a state monad, where **down** only introduces a runtime pair constructor, and it is feasible to compile object-level pairs as unboxed data, without overheads. However, for **Maybe**, **down** introduces a runtime **Just** or **Nothing**, and **up** introduces a runtime case split. A better solution would be to introduce two let-bound join points before the offending **case**, one for returning a **Just** and one for returning **Nothing**, but fusing away the actual runtime constructors:

```
f b s :=
  let joinNothing s := Nothing;
  let joinJust s := let s := s + s; Just ((), s);
  case b of
    True → let s := 10; joinJust s
    False → let s := 20; joinJust s
```

Here, **joinNothing** happens to be dead code, but it is easy to clean that up in downstream compilation. Such “fused” returns are possible whenever we have a **Gen A** action at the bottom of the transformer stack, such that **A** is isomorphic to a meta-level finite sum of value types. Recall that **Gen A** is defined as  $\{R : \text{ValTy}\} \rightarrow (A \rightarrow \uparrow R) \rightarrow \uparrow R$ . Here, if **A** is a finite sum, we can rearrange  $A \rightarrow \uparrow R$  to a finite product of functions.

We could proceed with finite sums, but we will need finite *sums-of-products* (SOP in short) later in Section 4, so we develop SOP-s. We view SOP-s as a Tarski-style universe consisting of a type of descriptions and a way of interpreting descriptions into **MetaTy** (“El” for “elements” of the type).

$$\begin{array}{ll} U_{\text{SOP}} : \text{MetaTy} & El_{\text{SOP}} : U_{\text{SOP}} \rightarrow \text{MetaTy} \\ U_{\text{SOP}} = \text{List} (\text{List ValTy}) & El_{\text{SOP}} A = \dots \end{array}$$

A type description is a list of lists of value types. We decode this to a sum of products of value types. We omit the definition here.  $U_{\text{SOP}}$  is closed under value types, finite product types and finite sum types. For instance, we have  $Either_{\text{SOP}} : U_{\text{SOP}} \rightarrow U_{\text{SOP}} \rightarrow U_{\text{SOP}}$  together with  $Left_{\text{SOP}} : El_{\text{SOP}} A \rightarrow El_{\text{SOP}} (Either_{\text{SOP}} A B)$ ,  $Right_{\text{SOP}} : El_{\text{SOP}} B \rightarrow El_{\text{SOP}} (Either_{\text{SOP}} A B)$  and a case splitting operation. It is more convenient to work with type formers in **MetaTy**, and only convert to SOP representations when needed, so we define a class for the representable types:

```
class IsSOP (A : MetaTy) where
  Rep : USOP
  rep : A ≈ ElSOP Rep
```

Above,  $A \approx \text{Rep}$  denotes a record containing a pair of back-and-forth functions, together with proofs (as propositional equalities) that they are inverses. We will overload **rep** as the forward conversion function with type  $A \rightarrow El_{\text{SOP}} \text{Rep}$ , and write  $\text{rep}^{-1}$  for its inverse. Now we define an



isomorphic presentation of  $\text{El}_{\text{SOP}} A \rightarrow \uparrow R$  as a product of object-level functions:

```

FunSOP↑ : USOP → Ty → MetaTy
FunSOP↑ Nil      R = ()
FunSOP↑ (Cons A B) R = (↑(foldr (→) R A), FunSOP↑ B R)

tabulate : (ElSOP A → ↑R) → FunSOP↑ A R
index    : FunSOP↑ A R → (ElSOP A → ↑R)

```

We omit here the definitions of `tabulate` and `index`. We will also need to let-bind all functions in a `FunSOP↑`:

```

genFunSOP↑ : {A : USOP} → FunSOP↑ A R → FunSOP↑ A R
genFunSOP↑ {Nil}      ()    = return ()
genFunSOP↑ {Cons _ A}(f, fs) = (,) <$> gen f <*> genFunSOP↑ {A} fs

```

We introduce a class for monads that support control flow joining.

```

class Monad M ⇒ MonadJoin M where
  join : IsSOP A ⇒ M A → M A

```

The most interesting instance is the “base case” for `Gen`:

```

instance MonadJoin Gen where
  join ma = Gen $ λ k. runGen $ do
    joinPoints ← genFunSOP↑ (tabulate (k ∘ rep-1))
    a ← ma
    return $ index joinPoints (rep a)

```

Here we first convert  $k : A \rightarrow \uparrow R$  to a product of join points and let-bind each one of them. Then we generate code that returns to the appropriate join point for each return value. Other `MonadJoin` instances are straightforward. In `StateTM`, we need the extra `IsSOP S` constraint because `S` is returned as a result value.

```

instance (MonadJoin M) ⇒ MonadJoin (MaybeTM M) where
  join (MaybeTM ma) = MaybeTM (join ma)
instance (MonadJoin M) ⇒ MonadJoin (ReaderTM R M) where
  join (ReaderTM ma) = ReaderTM (join ∘ ma)
instance (MonadJoin M, IsSOP S) ⇒ MonadJoin (StateTM S M) where
  join (StateTM ma) = StateTM (join ∘ ma)

```

Now, we can write the following in our running example:

```

f : Bool → StateT Nat (MaybeT Identity) ()
f b := ~(down $ do
  join $ case ⟨b⟩ of True → put' ⟨10⟩; False → put' ⟨20⟩
  modify' (λ x. ⟨~x + ~x⟩))

```

It might make sense to also have a simple “desugaring” rule that inserts a join whenever we have a object-level case split with more than one branch. At worst, this generates some noise and dead code that is easy to remove by conservative code optimization.

```

736 letrec f : Tree Nat → StateT (List Nat) (MaybeT Identity) (Tree Nat)
737   f t := ~ (down $ case t of
738     Leaf → return ⟨Leaf⟩
739     Node n l r → do
740       case ⟨~n == 0⟩ of True → fail
741                        False → return ()
742       ns ← get
743       n ← join $ case ns of Nil → return n
744                        Cons n ns → do {put ns; return n}
745       l ← up ⟨f ~l⟩
746       r ← up ⟨f ~r⟩
747       return ⟨Node ~n ~l ~r⟩
748
749
750
751
752
753
754
755
756

```

Fig. 1. Monadic source code

### 3.6 Code Example

We look at a slightly larger code example in Figure 1. We define annotated binary trees as

```

757 data Tree A := Leaf | Node A (Tree A) (Tree A).
758
759

```

We write `fail : MA` for returning `Nothing` in any monad transformer stack that contains `MaybeT`. We define a function which traverses a tree and replaces values with values taken from a list. If the tree contains 0, we throw an error. If we run out of list elements, we leave values unchanged. Here, all of the `case` matches are done on object-level values, so they are all desugared to applications of `split`.

- Note the `join`: without it, the recursive `Node` traversal code would be inlined in both case branches.
- We do not use `join` when checking `⟨~n == 0⟩`. Here, it happens to be superfluous, since the `fail` “destroys” all subsequent code generation in the branch, by short-circuiting at the meta-level.
- Also, we can use `put` instead of the “stricter” `put'` because the state modification immediately gets sequenced by the enclosing `join` point.
- To make object-level recursive calls, we just need to wrap them in `up`.

Here, we intentionally tuned the definition for a nice-looking staging output. However, we could also just default to “safe” choices everywhere: we could use a joint point in every `case` with two or more branches, and use the strict state modifications everywhere, and leave it up to the downstream compiler to clean up the code.

We show the unstaging output on Figure 2. We omit newtype wrappers and use nested pattern matching on pairs, but otherwise this is exactly the code that we get in our Agda implementation. Again, the only flaw in this code is the dead binding for `joinNothing`.

### 3.7 Discussion

So far, we have a monad transformer library with the following features:

```

785   letrec f : Tree Nat → StateT (List Nat) (MaybeT Identity) (Tree Nat)
786   f := λ t ns. case t of
787     Leaf → Just (Leaf, ns)
788     Node n l r → case (n == 0) of
789       True → Nothing
790       False →
791         let joinNothing := λ _ . Nothing;
792         let joinJust := λ n ns. case f l ns of
793           Nothing → Nothing
794           Just (l, ns) → case f r ns of
795             Nothing → Nothing
796             Just (r, ns) → Just (Node n l r, ns);
797         case ns of
798           Nil → joinJust n ns
799           Cons n ns → joinJust n ns
800
801
802
803
804
805
806
807
808

```

Fig. 2. Unstaged monadic code

- Almost all definitions from the well-known Haskell ecosystem of monads and monad transformers can be directly reused, in the meta level.
- We can pattern match on object-level values in monadic code, insert object-level **let**-s with **gen** and avoid code duplication with **join**.
- In monadic code, object-level data constructors are only ever created by **down**, and matching on object-level data is only created by **split** and **up**. Monadic operations are fully fused, and all function calls can be compiled to statically known saturated calls.

As to potential weaknesses, first, the system as described in this section has some syntactic noise and requires extra attention from programmers. We believe that the noise can be mitigated very effectively in a native CFTT implementation. It was demonstrated in a 2LTT implementation in [Kovács 2022] that almost all quotes and splices are unambiguously inferable, if we require that stages of **let**-definitions are always specified (as we do here). Moreover, **up** and **down** should be also effectively inferable, using bidirectional elaboration. With such inference, monadic code in CFTT would look only slightly more complicated than in Haskell.

Second, in CFTT we cannot store computations (e.g. functions or State actions) in runtime data structures, nor can we have computations in State state or in Reader environments. However, it would be possible to extend CFTT with a closure type former that converts computations to values, in which case there is no such limitation anymore. Here, closure-freedom would be still available; we would be able to pick where to use or avoid the closure type former.

### 3.8 Agda & Haskell Implementations

We implemented everything in this section in both Agda and typed Template Haskell. We summarize features and differences:

- The Haskell implementation can be used to generate code that can be further compiled by GHC; here the object language is taken to be Haskell itself. Since Haskell does not distinguish value and computation types, we do not track them in the library, and we do not get guaranteed closure-freedom from GHC.
- In Agda, we postulate all types and terms of the object theory in a faithful way (i.e. equivalently to the CFTT syntax presented here), and take Agda itself to be the metalanguage. Here, we can test “staging” by running Agda programs which compute object expressions. However, we can only inspect staging output and cannot compile or run object programs.
- For sums-of-products in Haskell, we make heavy use of *singleton types* [Eisenberg and Weirich 2012] to emulate dependent types. This adds significant noise. Also, in *IsSOP* instances we can only define the conversion functions and cannot prove that they are inverses, because Haskell does not have enough support for dependent types.

## 4 STREAM FUSION

Stream fusion refers to a collection of techniques for generating efficient code from declarative definitions involving streams of values, where intermediate data structures are eliminated. Stream fusion can be broadly grouped into *push* fusion, which is based on Church-encodings of inductive lists, and *pull* fusion, which is based on Church-encodings of coinductive lists; see e.g. [Hinze et al. 2010]. The two styles have different trade-offs, and in practical programming it is a good idea to support both, but in this section we focus on pull streams.

The reason is that pull streams have been historically more difficult to efficiently compile, and we can demonstrate significant improvements in CFTT. We also use dependent types in a more essential way than in the previous section.

### 4.1 Streams

A pull stream is a meta-level specification of a state machine:

```
data Step S A = Stop | Skip S | Yield A S
data Pull (A : MetaTy) : MetaTy where
  Pull : (S : MetaTy) → IsSOP S ⇒ Gen S → (S → Gen (Step S A)) → Pull A
```

In the Pull constructor, *S* is the type of the internal state which is required to be a sum-of-products of value types by the *IsSOP S* constraint. Borrowing terminology from Coutts [Coutts 2011], we call each product in the state a *state shape*.

The next field with type *Gen S* is the initial state, while transitions are represented by the *S → Gen (Step S A)* field. Possible transitions are stopping (Stop), transitioning to a new state while outputting a value (Yield) and making a silent transition to a new state (Skip).

Let us see some operations on streams now. Pull is evidently a Functor. It is not quite a “zippy” applicative functor, because its application operator requires an extra *IsSOP* constraint:

```
repeat : A → Pull A
repeat a = Pull () (return ()) (λ _ . return $ Yield a ())
```

```

883 ( $\langle * \rangle_{\text{Pull}}$ ) : IsSOP A  $\Rightarrow$  Pull (A  $\rightarrow$  B)  $\rightarrow$  Pull A  $\rightarrow$  Pull B
884 ( $\langle * \rangle_{\text{Pull}}$ ) (Pull S seed step) (Pull S' seed' step') =
885   Pull (S, S', Maybe A) ((,)  $\langle \$ \rangle$  seed  $\langle * \rangle$  ((, Nothing)  $\langle \$ \rangle$  seed')) $  $\lambda$  case
886     (s, s', Just a)  $\rightarrow$  step s  $\gg$   $\lambda$  case
887       Stop  $\rightarrow$  return Stop
888       Skip s  $\rightarrow$  return $ Skip (s, s', Just a)
889       Yield f s  $\rightarrow$  return $ Yield (f a) (s, s', Nothing)
890     (s, s', Nothing)  $\rightarrow$  step' s'  $\gg$   $\lambda$  case
891       Stop  $\rightarrow$  return Stop
892       Skip s'  $\rightarrow$  return $ Skip (s, s', Nothing)
893       Yield a s'  $\rightarrow$  return $ Skip (s, s', Just a)

```

In repeat, the state is the unit type, while in  $\langle * \rangle_{\text{Pull}}$  we take the product of states, and also add another Maybe A that is used to buffer a single value while we are stepping the Pull (A  $\rightarrow$  B) stream. The IsSOP constraints for the new machine states are implicitly dispatched by instance resolution; this works in the Agda and Haskell versions too. We can derive zip and zipWith from  $\langle * \rangle_{\text{Pull}}$  and  $\langle \$ \rangle$  for streams, with the restriction that the zipped streams must all produce IsSOP values.

Pull is also a monoid with stream appending as the binary operation.

```

904 empty : Pull A
905 empty = Pull () (return ()) ( $\lambda$  _ . return Stop)
906
907 ( $\langle > \rangle$ ) : Pull A  $\rightarrow$  Pull A  $\rightarrow$  Pull A
908 ( $\langle > \rangle$ ) (Pull S seed step) (Pull S' seed' step') = Pull (Either S S') (Left  $\langle \$ \rangle$  seed)  $\lambda$  case
909   Left s  $\rightarrow$  step s  $\gg$   $\lambda$  case Stop  $\rightarrow$  (Skip  $\circ$  Right)  $\langle \$ \rangle$  seed'
910                                     Skip s  $\rightarrow$  return $ Skip (Left s)
911                                     Yield a s  $\rightarrow$  return $ Yield a (Left s)
912   Right s'  $\rightarrow$  step s'  $\gg$   $\lambda$  case Stop  $\rightarrow$  return Stop
913                                     Skip s'  $\rightarrow$  return $ Skip (Right s')
914                                     Yield a s'  $\rightarrow$  return $ Yield a (Right s')

```

These definitions are standard for streams; compared to the non-staged definitions in previous literature, the only additional noise is just the Gen monad in the initial states and the transitions. Likewise, we can give standard definitions for usual stream functions such as filter, take or drop.

## 4.2 Running Streams with Mutual Recursion

How do we generate object code from streams? The state S is given as a finite sums of products, but the sums and the products are on the meta level, so we cannot directly use S in object code. Similarly as in the the treatment of join points, we tabulate the  $S \rightarrow \text{Gen Step } S \text{ A}$  transition function to a product of functions. However, these functions need to be *mutually recursive*, since it is possible to transition from any state to any other state, and each such transition is represented as a function call. This problem of generating well-typed mutual blocks was addressed by Yallop and Kiselyov in [Yallop and Kiselyov 2019]. In contrast to this work, which used control effects and mutable references in MetaOCaml, we present a solution that does not use side effects in the metalanguage.

The solution is to extend  $\text{CompTy}$  with finite products of computations, i.e. assume  $() : \text{CompTy}$  and  $(,) : \text{CompTy} \rightarrow \text{CompTy} \rightarrow \text{CompTy}$ , together with pairing and projections. These types, like functions, are call-by-name in the runtime semantics, and they also cannot escape the scope of their definition. Hence, we can also “saturate” programs that involve computational product types: every computation definition at type  $(A, B)$  can be translated to a pair, and every projection of a let-defined variable can be statically matched up with a pairing in the variable definition. Thus, a recursive let-definition at type  $(A \rightarrow B, A \rightarrow B)$  can be always compiled to a pair of mutual functions.

We redefine the previous  $\text{Fun}_{\text{SOP}\uparrow}$  to return a computation type instead:

$$\begin{aligned} \text{Fun}_{\text{SOP}\uparrow} &: \text{U}_{\text{SOP}} \rightarrow \text{Ty} \rightarrow \text{CompTy} \\ \text{Fun}_{\text{SOP}\uparrow} \text{Nil} &\quad \text{R} = () \\ \text{Fun}_{\text{SOP}\uparrow} (\text{Cons } A \text{ B}) &\text{R} = (\text{foldr } (\rightarrow) \text{R } A, \text{Fun}_{\text{SOP}\uparrow} \text{B } \text{R}) \\ \text{tabulate} &: (\text{El}_{\text{SOP}} A \rightarrow \uparrow\text{R}) \rightarrow \uparrow(\text{Fun}_{\text{SOP}\uparrow} A \text{R}) \\ \text{index} &: \uparrow(\text{Fun}_{\text{SOP}\uparrow} A \text{R}) \rightarrow (\text{El}_{\text{SOP}} A \rightarrow \uparrow\text{R}) \end{aligned}$$

Even for join points, this is just as efficient as the previous  $\text{Fun}_{\text{SOP}\uparrow}$  version, since a definition of a product of functions will get compiled to a sequence of function definitions. In addition, we can use it to generate object code from streams. There are several choices for this, but in CFTT the  $\text{foldr}$  function is as good as we can get.

$$\begin{aligned} \text{foldr} &: \{A : \text{MetaTy}\} \{B : \text{Ty}\} \rightarrow (A \rightarrow \uparrow B \rightarrow \uparrow B) \rightarrow \uparrow B \rightarrow \text{Pull } A \rightarrow \uparrow B \\ \text{foldr } \{A\} \{B\} f \text{ b } (\text{Pull } S \text{ seed step}) &= \langle \\ &\quad \text{letrec fs : Fun}_{\text{SOP}\uparrow} (\text{Rep } \{S\}) B := \sim(\text{tabulate } \$ \lambda s. \text{unGen } (\text{step } (\text{rep}^{-1} s)) \$ \lambda \text{case} \\ &\quad \text{Stop} \quad \rightarrow \text{b} \\ &\quad \text{Skip } s \quad \rightarrow \text{index } \langle \text{fs} \rangle (\text{rep } s) \\ &\quad \text{Yield } a \text{ s} \rightarrow f \text{ a } (\text{index } \langle \text{fs} \rangle (\text{rep } s))) ; \\ &\quad \sim(\text{unGen seed } \$ \lambda s. \text{index } \langle \text{fs} \rangle (\text{rep } s)) \rangle \end{aligned}$$

This  $\text{foldr}$  is quite flexible because it can produce object terms with computation types. For instance, we can define  $\text{foldl}$  from  $\text{foldr}$ :

$$\begin{aligned} \text{foldl} &: \{A : \text{MetaTy}\} \{B : \text{ValTy}\} \rightarrow (\uparrow B \rightarrow A \rightarrow \uparrow B) \rightarrow \uparrow B \rightarrow \text{Pull } A \rightarrow \uparrow B \\ \text{foldl } f \text{ b as} &= \sim(\text{foldr } (\lambda a \text{ g. } \langle \lambda b. \sim g \sim (f \langle b \rangle \sim a) \rangle) \langle \lambda b. b \rangle \text{as}) \sim b \end{aligned}$$

Note that since we abstract  $B$  in a runtime function, it must be a value type. Here, each  $\text{Stop}$  and  $\text{Yield}$  in the transition function gets interpreted as a  $\lambda$ -expression in the output. However, those  $\lambda$ -s will be lifted out in the scope, yielding a proper mutually tail-recursive definition with an accumulator for  $B$ . Contrast this to the GHC base library, where  $\text{foldl}$  for lists is also defined from  $\text{foldr}$ , to enable push-based fusion, but where a substantial *arity analysis* is used in the compiler to (incompletely) eliminate the intermediate closures [Breitner 2014].

### 4.3 concatMap for Streams

Can we have a list-like  $\text{Monad}$  instance for streams, with singleton streams for **return** and  $\text{concatMap}$  for binding? This is not possible. Aiming at

$$\text{concatMap} : (A \rightarrow \text{Pull } B) \rightarrow \text{Pull } A \rightarrow \text{Pull } B,$$



the  $A \rightarrow \text{Pull } B$  function can contain an infinite number of different machine state types, which cannot be represented in a finite amount of object code. Here by “infinite” we mean the notion that is internally available in the meta type theory. For instance, we can define a  $\text{Nat}_M \rightarrow \text{Pull } B$  function which for each  $n : \text{Nat}_M$  produces a concatenation of  $n$  streams. Hence, we shall have the following function instead:

$$\text{concatMap} : \text{IsSOP } A \Rightarrow (A \rightarrow \text{Pull } B) \rightarrow \text{Pull } A \rightarrow \text{Pull } B$$

The idea is the following: if  $U_{\text{SOP}}$  is closed under  $\Sigma$ -types, we can directly define this  $\text{concatMap}$ , by taking the appropriate dependent sum of the  $A \rightarrow U_{\text{SOP}}$  family of machine states, which we extract from the  $A \rightarrow \text{Pull } B$  function. Let us write  $\Sigma A B : \text{MetaTy}$  for dependent sums, for  $A : \text{MetaTy}$  and  $B : A \rightarrow \text{MetaTy}$ , and reuse  $(,)$  for pairing. We also use the following field projection functions:  $\text{projS} : \text{Pull } A \rightarrow \text{MetaTy}$ ,  $\text{projSeed} : (a : \text{Pull } A) \rightarrow \text{projS } a$ , and  $\text{projStep} : (a : \text{Pull } A) \rightarrow \text{projS } a \rightarrow \text{Gen } (\text{Step } (\text{projS } a) A)$ . For now, we assume that the following instance exists:

$$\text{instance } (\text{IsSOP } A, \{a : A\} \rightarrow \text{IsSOP } (B \ a)) \Rightarrow \text{IsSOP } (\Sigma A B)$$

Above,  $\{a : A\} \rightarrow \text{IsSOP } (B \ a)$  is a universally quantified instance constraint; this can be also represented in Agda. The definition of  $\text{concatMap}$  is as follows.

```
concatMap : IsSOP A => (A -> Pull B) -> Pull A -> Pull B
concatMap {A} {B} f (Pull S seed step) =
  Pull (S, Maybe (Σ A (projS ∘ f))) ((,) <$> seed <*> return Nothing) $ λ case
    (s, Nothing) -> step s >>= λ case
      Stop      -> return Stop
      Skip s    -> return $ Skip (s, Nothing)
      Yield a s -> do {s' ← projSeed (f a); return $ Skip (s, Just (a, s'))}
    (s, Just (a, s')) -> projStep (f a) s' >>= λ case
      Stop      -> return $ Skip (s, Nothing)
      Skip s'   -> return $ Skip (s, Just (a, s'))
      Yield b s' -> return $ Yield b (s, Just (a, s'))
```

Here, `Nothing` marks the states where we are in the “outer” loop, running the  $\text{Pull } A$  stream until we get its next value. `Just` marks the states of the “inner” loop, where we have a concrete  $a : A$  value and we run the  $(f \ a)$  stream until it stops. In the inner loop, the machine state type depends on the  $a : A$  value, hence the need for  $\Sigma$ . How do we get  $\text{IsSOP}$  for  $\Sigma$ ? The key observations are:

- Metaprograms cannot inspect the structure of object terms.
- Object types do not depend on object terms.

Hence, we expect that during staging, every  $f : \uparrow A \rightarrow \text{ValTy}$  function has to be constant. This is actually true in the staging semantics of CFTT. There, all metafunctions are stable under object-level parallel substitutions. Also, object types are untouched by substitution. Hence, a straightforward unfolding of semantic definitions validates the constancy of  $f$ .

Generally speaking, in the semantics, every function whose domain is a product of object types and whose codomain is a constant presheaf, is a constant function. We may call these constancy statements *generativity axioms*, since they reflect the inability of metaprograms to inspect terms, and “generativity” often refers to this property in the staged compilation literature.

Let us write  $U_P = \text{List ValTy}$  and  $\text{El}_P : U_P \rightarrow \text{MetaTy}$  for a universe of finite products of value types. Concretely, in CFTT and the Agda implementation, we assume the following:

**Axiom (generativity).** *For every  $f : \text{El}_P A \rightarrow U_{\text{SOP}}$  and  $a, a' : \text{El}_P A$ , we have that  $f a = f a'$ .*

We remark that there is no risk of staging getting stuck on this axiom, because propositional equality proofs get erased, as we described in Section 2.4.

From generativity, we derive  $\Sigma_{\text{SOP}} : (A : U_{\text{SOP}}) \rightarrow (B : \text{El}_{\text{SOP}} A \rightarrow U_{\text{SOP}}) \rightarrow U_{\text{SOP}}$  as follows. First, for each  $A : U_P$ , we define  $\text{loop}_A : \text{El}_P A$  as a product of non-terminating object programs. This is only needed to get arbitrary inhabitants with which we can call  $\text{El}_P A \rightarrow U_{\text{SOP}}$  functions.

Then,  $\Sigma_{\text{SOP}} A B$  is defined as the concatenation of  $A_i \times B (\text{inject}_i \text{loop}_{A_i})$  for each  $A_i \in A$ , where  $(\times)$  is the product type former in  $U_{\text{SOP}}$  and  $\text{inject}_i$  has type  $\text{El}_P A_i \rightarrow \text{El}_{\text{SOP}} A$ . This is similar to the definition of non-dependent products in  $U_{\text{SOP}}$ , except that we have to get rid of the type dependency by instantiating  $B$  with arbitrary programs.

Then, we can show using the generativity axiom that  $\Sigma_{\text{SOP}}$  supports projections, pairing and the  $\beta\eta$ -rules. These are all needed when we define the  $\text{lsSOP}$  instance, when we have to prove that encoding via  $\text{rep}$  is an isomorphism. Concretely, assuming  $\text{lsSOP } A$  and  $\{a : A\} \rightarrow \text{lsSOP } (B a)$ , we define  $\text{Rep}$  and  $\text{rep}$  for  $\Sigma A B$  as follows:

$$\text{Rep } \{\Sigma A B\} = \Sigma (\text{Rep } \{A\}) (\lambda x. \text{Rep } \{B (\text{rep}^{-1} x)\})$$

$$\text{rep } \{\Sigma A B\} (a, b) = (\text{rep } \{A\} a, \text{rep } \{B (\text{rep}^{-1} (\text{rep } x))\} b)$$

Note that  $\text{rep}$  is only well-typed up to the fact that  $\text{rep}^{-1} \circ \text{rep} = \text{id}$ ; the Agda definition contains an additional transport that we omit here. This is, in fact, our reason for including the isomorphism equations in  $\text{lsSOP}$ . This, in turn, necessitates using  $\text{SOP}$  instead of finite sums. We can define a product type former for finite sums of value types, by taking the pairwise products of components. However, we can only take the *object-level* products here, and since object-level products have no  $\beta\eta$ -rules, we cannot prove  $\beta\eta$  for the derived product type in finite sums, and likewise for the derived  $\Sigma$ -type. When we use  $\text{SOP}$  instead, we do not have to use object-level products and this issue does not appear.

We skip the full definition of  $\Sigma_{\text{SOP}}$  here. The reader may refer to the  $\text{SOP}$  module in the Agda implementation, which is altogether 260 lines with all  $\text{lsSOP}$  instances.

#### 4.4 Let-Insertion & Case Splitting in Monadic Style

While  $\text{Pull}$  is not a monad, and hence also not a  $\text{MonadGen}$ , we can still use a monadic style of stream programming with good ergonomics. First, we need singleton streams for “returning”:

$\text{single} : A \rightarrow \text{Pull } A$

$\text{single } a = \text{Pull Bool}_M \text{ True } \$ \lambda b. \text{return } \$ \text{if } b \text{ then Yield } a \text{ False else Stop}$

Now, we should use this operation with care, since it has two states and can contribute to a code size blow-up. For example,  $\text{concatMap}$  over  $\text{single}$  introduces at least a doubling of the number of state shapes. Although let-insertion and case splitting could be derived as  $\text{concatMap}$  over  $\text{single}$ , to avoid the size explosion we give more specialized definitions instead. First, we define an embedding

of Gen operations in streams.

```

bindGen : IsSOP A ⇒ Gen A → (A → Pull B) → Pull B
bindGen ga f =
  Pull (Σ A (projS ∘ f)) (do {a ← ga; s ← projSeed (f a); return (a, s)}) $ λ case
    (a, s) → projStep (f a) s ≫ λ case
      Stop    → return Stop
      Skip s   → return $ Skip (a, s)
      Yield b s → return $ Yield b (a, s)

```

We recover let-insertion and case splitting as follows:

```

genPull : ↑A → (↑A → Pull B) → Pull B
genPull a = bindGen (gen a)

casePull : (Split A, IsSOP (SplitTo {A})) ⇒ ↑A → (SplitTo {A} → Pull B) → Pull B
casePull a = bindGen (split a)

```

Let us look at small example. We write `forEach` for `concatMap` with flipped arguments.

```

forEach (take {100} (countFrom {0})) $ λ x.
  genPull {~x * 2} $ λ y.
  casePull {~x < 50} $ λ case
    True  → take y (countFrom x)
    False → single y

```

Here, in every `forEach` iteration, `genPull {~x * 2}` evaluates the given expression and saves the result to the machine state. Then, `casePull` branches on an object-level Boolean expression. If we use `foldr` to generate object code from this definition, we get *four* mutually defined functions. We get two state shapes from `single y` and one from `take y (countFrom x)`; we sum these to get three for the `casePull`, then finally we get an extra shape from `forEach` which introduces an additional `Maybe`.

## 4.5 Discussion

Our stream library has a strong support for programming in a monadic style, even though `Pull` is not literally a monad. We can bind object values with `concatMap`, and we can also do let-insertion and case splitting for them. We also get guaranteed well-typing, closure-freedom, and arbitrary mixing of zipping and `concatMap`.

We highlight the usage of the generativity axiom as well. Previously in staged compilation, intensional analysis (i.e. the ability to analyze object code) has been viewed as a desirable feature that increases the expressive power of a system. To our knowledge, our work is the first one that exploits the *lack* of intensional analysis in metaprogramming. This is a bit similar to parametricity in type theories, where the inability to analyze types has a payoff in the form of “free theorems” [Wadler 1989].

Regarding the practical application of our stream library, we think that it would make sense to support both push and pull fusion in a realistic implementation, and allow users to benefit from the strong points of both. Push streams, which we do not present in this paper, have proper `Monad` and `MonadGen` instances and are often more convenient to use in CFTT. They are also better for deep traversals of structures where they can utilize unbounded stack allocations, while pull streams need heap allocations for unbounded space in the machine state.

## 4.6 Agda & Haskell Implementations

In Agda, to avoid computation getting stuck on the generativity axiom, we use the `primTrustMe` built-in [Agda developers 2024] to automatically erase the axiom when the sides of the equation are definitionally equal. Otherwise the implementation closely follows this section.

In Haskell there are some limitations. First, in `concatMap`, the projection function `projS` cannot be defined, because Haskell is not dependently typed, and the other field projections are also out of reach. We only have a weaker “positive” recursion principle for existential types. It might be the case that a strongly typed `concatMap` is possible with only weak existentials, but we attempted this and found that it introduces too much technical complication.

So instead of giving a single generic definition for `concatMap` for `IsSOP` types, we define `concatMap` just for object types,<sup>1</sup> and define `casePull` separately for each object type, as an overloaded class method. In each of these definitions, we only need to deal with a concrete finite number of machine state types, which is feasible to handle with weak existentials.

Also, the generativity axiom is *false* in Template Haskell, since it is possible to look inside quoted expressions. Instead, we use type coercions that can fail at unstaging time. If library users do not violate generativity, these coercions disappear and the code output will not contain unsafe coercions.

## 5 RELATED WORK

*Two-level type theory.* Two-level lambda calculi were first developed in the context of abstract interpretation and partial evaluation [Nielson 1984; Nielson and Nielson 1992]. This line of research is characterized by simple types, having the same language features at different stages, and an emphasis on *binding time analysis*, i.e. automatically inferring stage annotations as part of a pipeline for partial evaluation and program optimization.

Later and independently, the same notion of level appeared in homotopy type theory, first in Voevodsky’s Homotopy Type System [Voevodsky 2013], and subsequently developed as 2LTT in [Annenkov et al. 2019]. Here, dependent types are essential, and we have different theories at the two stages. The application of 2LTT to staged compilation was developed in [Kovács 2022]. Binding-time analysis has not been developed in this setting; 2LTT-s have been meant to be used as surface languages to directly work in.

We build on both traditions. CFTT itself is a 2LTT and makes heavy use of dependent type theory. However, we are mostly concerned with code generation and optimization and borrow concepts from the partial evaluation literature.

*Tracking function arities and closures in types.* Downen et al.’s intermediate language  $\mathcal{I}\mathcal{L}$  has similar motivations as our object language [Downen et al. 2020]. In both systems, function types are distinguished from closure types, enjoy universal  $\eta$ -conversion and have an explicit calling arity. In fact, our object language can be almost viewed as a small simply-typed fragment of  $\mathcal{I}\mathcal{L}$ , with only `letrec` missing from  $\mathcal{I}\mathcal{L}$ .

*Sums-of-products.* SOP was proposed for generic Haskell programming by De Vries and Löb [de Vries and Löb 2014]. Our own SOP implementation in Haskell is mostly the same as in *ibid*. The SOP-of-object-code representation appeared as well in typed Template Haskell in [Pickering et al. 2020].

*CPS and binding-time improvement.* Our Gen monad can be viewed as a variation on the continuation-passing-style that has been often used in staged programming. Flanagan et al.’s ANF translation

<sup>1</sup>Recall that we do not distinguish value and computation types in Haskell.

algorithm uses let-insertion in CPS that works the same way as our gen [Flanagan et al. 1993]. Kiselyov et al. likewise uses essentially the same CPS, in MetaOCaml [Kiselyov et al. 2017]. Jones et al. discuss CPS and binding-time improvement in partial evaluation [Jones et al. 1993].  $\eta$ -expansion for object-level finite sums is known as “the trick” [Danvy et al. 1996].

*Join points.* The use join points in GHC’s core language is partly motivated by avoiding code duplication in case-of-case transformations [Maurer et al. 2017]. In our monad library, case-of-case is implicitly and eagerly computed during staging, and we similarly use join points to avoid code duplication.

*Stream fusion.* The staged stream fusion library *strymonas* by Kiselyov et al. is the primary prior art [Kiselyov et al. 2017]. Here, streams are represented as a sum type of push and pull representations, allowing both zipping and concatMap-ing. However, fusion is not guaranteed for all combinations; zipping two concatMap-s reifies one of the streams in a runtime closure. In newer versions of the library, fusion is reported to be complete and guaranteed [Kobayashi and Kiselyov 2024], however, an exposition of this has not yet been published. Another notable difference is that *strymonas* relies on mutable references in the object language, while we do not.

*Machine fusion* [Robinson and Lippmeier 2017] supports splitting streams to multiple streams while avoiding duplicated computation; this is not possible in *strymonas* or our library. Machine fusion also supports concatMap and zipping. However, its state machine representation is significantly more complicated than ours, and its fusion algorithm is not guaranteed to succeed on arbitrary stream programs.

Coutts developed pull stream fusion in depth in [Coutts 2011]. We borrowed the basic design and the basic stream combinator definitions from there. This account is also close to existing stream implementations in Haskell. Ibid. characterizes fusibility in a non-staged setting, in terms of “good consumers” and “good producers”. This scheme does not cover concatMap.

## 6 CONCLUSIONS AND FUTURE WORK

We believe that a programming language in the style of this paper would be highly useful, especially in high-performance functional programming and domain-specific programming. In particular, the pipeline for using and compiling monads could look like the following.

- Users write definitions in a style similar to Haskell, without quotes, splices, **up**-s and **down**-s, only marking stages in type annotations and in let-definitions, with  $:=$  and  $=$ . Storing monadic actions at runtime requires an explicit boxing operation that yields a closure type.
- Type- and stage-directed elaboration adds the missing operations, and also desugars case splitting using join and the underlying splitting function.
- In the downstream compiler, fast & conservative optimization passes are sufficient, since abstraction overheads are already eliminated by staging. Eliminating dead code and unused arguments would be important, since we have not yet addressed this through staging.
- A systematic way to de-duplicate code would be also needed, probably already during staging.

Going a bit further, we believe that a 2LTT-based language could be a good design point for programming in general, buying us plenty of control over code generation for a modest amount of extra complexity.

Also, rebuilding known abstractions in staged programming is valuable because it provides a *semantic explanation* of how abstractions can be compiled, and provides insights that could be reused even in non-staged settings. For instance, in this paper we demonstrated that compiling

monadic code can be done by using *the same monads* in the metalanguage, extended with code generation as an effect.

Continuing this line of thought, it could be interesting to also adapt to 2LTT the style of *binding-time analysis* that is well-known in partial evaluation. For example, we might do program optimization in the following way. First, start with monadic code in a non-staged language. Second, try to infer stages, inventing quotes, splices, **up**-s and **down**-s, thereby translating definitions to a 2LTT. Third, perform staging and proceed from there. This would be more fragile than unambiguous stage inference, but we would still benefit from shifting a lot of machinery into staging (which is deterministic and efficient).

We also find it interesting how little impact closure-freedom had on the developments in this paper. This provides some evidence that in staged functional programming, closures can be an opt-in feature instead of the pervasive default.

In this paper we only briefly looked at two applications. Both monad transformers and streams could be further developed, and many other programming abstractions could be revisited in the staged setting.

- We did not discuss the issue of *tail calls* in monadic code. For example, a tail call in *Maybe* should not case split on the result, while in our current library, making a call with **up** always does so. We did develop an abstraction for tail calls in the Agda and Haskell implementations, but omitted it here partly for lack of space, and partly because we have not yet explored much of the design space.
- In a practical stream library, it would be useful to further try to minimize the size of the machine state. In the Agda and Haskell versions, we additionally track whether streams can *Skip*, to provide more efficient zipping for non-skipping “synchronous” streams. However, this could be refined in many ways, and we could also try to represent the full transition graph in an observable way, thereby enabling merging or deleting states.
- It seems promising to look for synergies between push streams, pull streams and monad transformers. It seems that pull streams could be generalized from *Gen* to different monads, in the representation of transitions and initial states. This would allow putting a *Pull* *on the top* of a monad transformer stack. On the other hand, push streams form a proper monad, but they cannot be used to “transform” other monads, so they can be placed at the *bottom* of a transformer stack.
- We could try to lean more heavily on datatype-generic programming and generalize abstractions for more object types. For example, push and pull streams could be generalized to inductive and coinductive Church-codings of arbitrary value types.



## Appendix A STAGING IN CFTT

In this appendix we describe the semantics of CFTT, from which the unstaging algorithm is obtained, and also describe the soundness and completeness of the algorithm. We borrow the setup from [Kovács 2022]; we use terminology and definitions from there by default, and focus on differences and extensions.

*Notation 1.* In the following, we work in a mostly unspecified extensional type theory, writing  $\text{Set}$  for universes (omitting universe levels),  $(x : A) \rightarrow B$  for  $\Pi$ -types,  $(x : A) \times B$  for  $\Sigma$ -types and  $- = -$  for extensional identity.

### A.1 Models and Syntax of CFTT

We give an algebraic [?] specification for the models of CFTT and define the syntax of CFTT to be the initial model. In the following, all type and term formers are implicitly assumed to be stable under substitution.

*Definition A.1.* A model of CFTT consists of the following.

- A category with a terminal object; in the syntax this is the category of contexts and parallel substitutions. We use  $\text{Con} : \text{Set}$  for contexts,  $\text{Sub} : \text{Con} \rightarrow \text{Con} \rightarrow \text{Set}$  for morphisms and  $\bullet : \text{Con}$  for the terminal object (which is the empty context in the syntax).
- A family structure in the sense of category-with-families [?], specifying metatypes and terms. This structure is additionally indexed by universe levels, so we have  $\text{MetaTy}_i : \text{Con} \rightarrow \text{Set}$  and  $\text{MetaTm}_i : (\Gamma : \text{Con}) \rightarrow \text{MetaTy}_i \Gamma \rightarrow \text{Set}$  for  $i \in \mathbb{N}$ . We support basic type formers, identity types and W-types. We write  $\Gamma \triangleright A$  for an extended context. Additionally, we have Coquand-style universes, i.e.  $U_i : \text{MetaTy}_{i+1} \Gamma$  such that there is an isomorphism  $\text{MetaTm}_{i+1} \Gamma U_i \simeq \text{MetaTy}_i \Gamma$ . We use  $\text{El}$  and  $\text{code}$  to denote the components of this isomorphism.
- For object-level types, we have  $\text{Ty} : \text{MetaTy}_0 \Gamma$ ,  $\text{ValTy} : \text{MetaTy}_0 \Gamma$  and  $\text{CompTy} : \text{MetaTy}_0 \Gamma$ , together with all object-level type formers and inclusion operations  $V : \text{MetaTm} \Gamma \text{ValTy} \rightarrow \text{MetaTm} \Gamma \text{Ty}$  and  $C : \text{MetaTm} \Gamma \text{CompTy} \rightarrow \text{MetaTm} \Gamma \text{Ty}$ .
- For object-level terms, we have  $\text{Tm} : \text{MetaTm} \Gamma \text{Ty} \rightarrow \text{Set}$ , supporting context extension, i.e. we have  $\Gamma, \triangleright A$  for  $A : \text{MetaTm} \Gamma \text{Ty}$  such that  $\text{Sub} \Gamma (\Delta \triangleright A)$  is isomorphic to  $(\sigma : \text{Sub} \Gamma \Delta) \times \text{Tm} \Gamma (A[\sigma])$ . All object-level term formers are supported in  $\text{Tm}$ .
- Staging operations: we have  $\uparrow : \text{MetaTm} \Gamma \text{Ty} \rightarrow \text{MetaTy}_1 \Gamma$  together with isomorphisms  $\text{Tm} \Gamma A \simeq \text{MetaTm} \Gamma (\uparrow A)$ . We write  $\langle - \rangle$  and  $\sim$  for the components of the isomorphism.

This presentation is a bit more verbose than the surface syntax used in the paper. First, the meta level uses explicit coding and decoding operations for universes, while the surface syntax assumes Russell-style universes. Second, the object level has  $\text{ValTy}$  and  $\text{CompTy}$  as Tarski-style universes with explicit inclusion into  $\text{Ty}$ , while the surface syntax used implicit coercions.

Also, this is not the only possible presentation. Here, we follow the style of the informal syntax by having a separate *sort* for object-level terms, together with explicit quoting and splicing. However, we do not have a sort for object types and instead specify them as terms of metatypes. This is a mixture of two styles:

- The “classic” 2LTT style would have separate sorts and staging operations for all of  $\text{Ty}$ ,  $\text{CompTy}$  and  $\text{ValTy}$ . Here the two levels are specified independently and level-mixing is only possible through staging operations.
- The “higher-order abstract syntax” (HOAS) or “logical framework” style would only have metatypes and metaterms, no quoting or splicing, and would reuse metafunctions to represent object-level binders. Our Agda implementation actually follows this style.

In the context of CFTT, the choice between HOAS and 2LTT styles is a matter of taste, and the two are inter-derivable [?].

## A.2 Presheaf Model

Unstaging is defined as evaluation of the syntax of CFTT in a particular presheaf model.

- The *object theory* is the simple type theory supporting only value types and computation types as described in Section 2.2 and also in the Agda formalization. Object-theoretic terms are not quotiented by  $\beta\eta$ -conversion. Substitution is a recursively defined operation on terms.
- $\mathbb{O}$  is the category whose objects are contexts of the object theory, and morphisms are parallel substitutions, as lists of terms. With this, object-theoretic types form a constant presheaf which we denote as  $\text{Ty}_{\mathbb{O}} : \mathbb{O}^{\text{op}} \rightarrow \text{Set}$ , and terms form a dependent presheaf over  $\text{Ty}_{\mathbb{O}}$  which we write as  $\text{Tm}_{\mathbb{O}}$ .
- In the presheaf model of CFTT, every typing context (and also every closed type) is modeled as a presheaf over  $\mathbb{O}$ . The interpretation of meta-level type formers is standard, following Hofmann [Hofmann 1997] and Huber [Huber 2016].
- $\text{Ty} : \text{MetaTy}_{\mathbb{O}} \Gamma$  is the displayed presheaf which is constantly  $\text{Ty}_{\mathbb{O}}$ .  $\text{ValTy}$  and  $\text{CompTy}$  are modeled analogously.
- $\uparrow A : \text{MetaTy}_{\mathbb{O}} \Gamma$  is modeled as follows. We have that  $A : \text{MetaTy} \Gamma \text{ Ty}$ , but since  $\text{Ty}$  is defined as constantly  $\text{Ty}_{\mathbb{O}}$ , it follows that  $A$  is a natural transformation from  $\Gamma$  to  $\text{Ty}_{\mathbb{O}}$ . Hence, we define  $\uparrow A : \text{MetaTy}_{\mathbb{O}} \Gamma$  to be  $\text{Tm}_{\mathbb{O}}[A]$ , where  $[-]$  is substitution in presheaves, i.e. the reindexing of a displayed presheaf by a natural transformation.
- $\text{Tm} \Gamma A$  is simply defined to be  $\text{MetaTy} \Gamma (\uparrow A)$  in the model. Hence, quotation and splicing are both interpreted as identity maps.

Now, we can take a closed term  $t : \text{Tm} \bullet A$  in CFTT and evaluate it in the presheaf model to obtain an object-theoretic term whose type is the result of evaluating  $A$ .

## A.3 W-types

So far we have stayed close to [Kovács 2022], with only cosmetic changes. Supporting W-types, as a way to get inductive families [?], is the biggest extension here. We extend Section 5 of [Kovács 2022] here. In the syntax of CFTT, W-types are as follows. The formal specification of syntactic W-elim is rather gnarly, because of the usage of explicit substitutions, but we write it out here anyways.

*Notation 2.* We use  $p^N$  for  $N$ -fold weakening and we also use numerals as De Bruijn indices, to abbreviate  $q[p^N]$ . We write  $\text{app}$  and  $\text{lam}$  for  $\Pi$  application and abstraction. We write  $\multimap$  for non-dependent function types. Finally, for the sake of brevity we omit the component maps of the isomorphism  $\mathbb{R}_{\triangleright} : \mathbb{R} (\Gamma \triangleright A) \simeq ((\gamma : \mathbb{R} \Gamma) \times \mathbb{R} A \gamma)$ .

$$\begin{aligned}
W & : (A : \text{MetaTy}_i \Gamma) \rightarrow \text{MetaTy}_j (\Gamma \triangleright A) \rightarrow \text{MetaTy}_{\max(i,j)} \Gamma \\
\text{sup} & : (a : \text{MetaTm} \Gamma A) \rightarrow \text{MetaTm} \Gamma (B[\text{id}, a] \Rightarrow W A B) \rightarrow \text{MetaTm} \Gamma (W A B) \\
W\text{-elim} & : (P : \text{MetaTy} (\Gamma \triangleright W A B)) \\
& \rightarrow \text{MetaTm} (\Gamma \triangleright A \triangleright B \Rightarrow (W A B)[p] \triangleright \Pi (B[p]) (P[p^3, \text{app } 1\ 0])) (P[p^3, \text{sup } 2\ 1]) \\
& \rightarrow (w : \text{MetaTm} \Gamma (W A B)) \rightarrow \text{MetaTm} \Gamma (P[\text{id}, w]) \\
W\beta & : W\text{-elim } P s (\text{sup } a f) = s[\text{id}, a, f, \text{lam } (W\text{-elim } (P[p^2, q]) (s[p]) (\text{app } f\ 0))]
\end{aligned}$$

We shall omit the  $i$  and  $j$  universe levels in the following. In  $\widehat{\mathbf{Set}}$ , i.e. internally to presheaves over  $\mathbb{Q}$ , we also have the standard W-type.

$$\begin{aligned}
 \widehat{W} & : (A : \widehat{\mathbf{Set}}) \rightarrow (A \rightarrow \widehat{\mathbf{Set}}) \rightarrow \widehat{\mathbf{Set}} \\
 \widehat{\text{sup}} & : (a : A) \rightarrow (B a \rightarrow \widehat{W} A B) \rightarrow \widehat{W} A B \\
 \widehat{W\text{-elim}} & : (P : \widehat{W} A B \rightarrow \widehat{\mathbf{Set}}) \\
 & \rightarrow ((a : A)(f : B a \rightarrow \widehat{W} A B) \rightarrow ((b : B a) \rightarrow P(f b)) \rightarrow P(\widehat{\text{sup}} a f)) \\
 & \rightarrow (w : \widehat{W} A B) \rightarrow P w \\
 \widehat{W}\beta & : \widehat{W\text{-elim}} P s (\widehat{\text{sup}} a f) = s a f (\lambda b. \widehat{W\text{-elim}} P s (f b))
 \end{aligned}$$

In the presheaf model we interpret  $W$  using  $\widehat{W}$ .

$$\begin{aligned}
 \mathbb{E}(W A B) \gamma & := \widehat{W}(\mathbb{E} A \gamma) (\lambda \alpha. \mathbb{E} B(\gamma, \alpha)) \\
 \mathbb{E}(\text{sup } a f) \gamma & := \widehat{\text{sup}}(\mathbb{E} a \gamma) (\lambda \beta. \mathbb{E} f(\gamma, \beta)) \\
 \mathbb{E}(W\text{-elim } P s w) \gamma & := \widehat{W\text{-elim}}(\lambda w. \mathbb{E} P(\gamma, w)) (\lambda a f g. \mathbb{E} s(\gamma, a, f, g)) (\mathbb{E} w \gamma)
 \end{aligned}$$

Now, assuming  $A : \text{MetaTy } \Gamma$  and  $B : \text{MetaTy } (\Gamma \triangleright A)$ , we consider  $\mathbb{R}(W A B) : (\gamma : \mathbb{R} \Gamma) \rightarrow \widehat{\mathbf{Set}}$ . Externally, the elements of  $\mathbb{R}(W A B) \gamma$  are CFTT terms with a  $W$ -type in purely object-level contexts. We call such terms *restricted*. Now, we internalize the restriction of the sup constructor:

$$\mathbb{R}_{\text{sup}} : (\alpha : \mathbb{R} A \gamma) \rightarrow \mathbb{R}(B \Rightarrow (W A B)[p]) (\gamma, \alpha) \rightarrow \mathbb{R}(W A B) \gamma$$

Externally,  $\mathbb{R}_{\text{sup}}$  applies sup to restricted terms. Note that in  $\mathbb{R}(B \Rightarrow (W A B)[p]) (\gamma, \alpha)$ , the type  $B \Rightarrow (W A B)[p]$  is in the context  $(\Gamma \triangleright A)$ , which makes it possible to pass  $(\gamma, \alpha)$  as argument; this “instantiates”  $B$  to  $\alpha$ . With this, we can also show that  $\mathbb{R}$  preserves sup:

$$\mathbb{R}(\text{sup } t u) \gamma = \mathbb{R}_{\text{sup}}(\mathbb{R} t \gamma) (\mathbb{R} u \gamma)$$

Note that the type of  $\mathbb{R} u \gamma$  is  $\mathbb{R}(B[\text{id}, t] \Rightarrow W A B) \gamma$ , which is equal to  $\mathbb{R}((B \Rightarrow (W A B)[p])[\text{id}, t]) \gamma$ , which is in turn equal to  $\mathbb{R}(B \Rightarrow (W A B)[p]) (\gamma, \mathbb{R} t \gamma)$  by  $\mathbb{R}$ ’s preservation of substitutions, which makes the above equation well-typed.

Next, we give a logical relation interpretation for  $W$ . We define an inductive relation in  $\widehat{\mathbf{Set}}$  as follows.

$$\begin{aligned}
 W^{\approx} & : \Gamma^{\approx} \gamma \gamma' \rightarrow \mathbb{E}(W A B) \gamma \rightarrow \mathbb{R}(W A B) \gamma' \rightarrow \widehat{\mathbf{Set}} \\
 \text{sup}^{\approx} & : \{ \alpha : \mathbb{E} A \gamma \} \{ \alpha' : \mathbb{R} A \gamma' \} \{ \alpha^{\approx} : A^{\approx} \gamma^{\approx} \alpha' \} \\
 & \rightarrow \{ f : \mathbb{E} B(\gamma, \alpha) \rightarrow \mathbb{E}(W A B) \gamma \} \\
 & \rightarrow \{ f' : \mathbb{R}(B \Rightarrow (W A B)[p]) (\gamma', \alpha') \} \\
 & \rightarrow (f^{\approx} : (B \Rightarrow (W A B)[p])^{\approx} (\gamma^{\approx}, \alpha^{\approx}) f f') \\
 & \rightarrow W^{\approx} \gamma^{\approx} (\widehat{\text{sup}} \alpha f) (\mathbb{R}_{\text{sup}} \alpha' f')
 \end{aligned}$$

Here,  $(B \Rightarrow (W A B)[p])^{\approx}$  is the relational interpretation of the function type, which unfolds to pointwise preservation of relations. In short,  $W^{\approx}$  expresses that  $\widehat{\text{sup}} \alpha f$  is related  $\mathbb{R}_{\text{sup}} \alpha' f'$  when the arguments (inductively) related. We can immediately interpret  $W$  and sup:

$$\begin{aligned}
 (W A B)^{\approx} \gamma^{\approx} t t' & := W^{\approx} \gamma^{\approx} t t' \\
 (\text{sup } t u)^{\approx} \gamma^{\approx} & := \text{sup}^{\approx} (t^{\approx} \gamma^{\approx}) (u^{\approx} \gamma^{\approx})
 \end{aligned}$$

It only remains to interpret W-elimination and its  $\beta$ -rule. We need to define

$$(W\text{-elim } P s w)^\sim \gamma^\sim : P^\sim (\gamma^\sim, w^\sim \gamma^\sim) (\mathbb{E} (W\text{-elim } P s w) \gamma) (\mathbb{R} (W\text{-elim } P s w) \gamma')$$

We do this by induction on  $w^\sim \gamma^\sim : W^\sim \gamma^\sim (\mathbb{E} w \gamma) (\mathbb{R} w \gamma')$ . At this point it becomes rather tedious to compute and unfold the involved types, so we only give a compact definition here together with some informal explanation:

$$(W\text{-elim } P s w)^\sim \gamma^\sim :=$$

$$\begin{aligned} & W^\sim\text{-elim } (\lambda w^\sim. P^\sim (\gamma^\sim, w^\sim) (\mathbb{E} (W\text{-elim } P s w) \gamma) (\mathbb{R} (W\text{-elim } P s w) \gamma')) \\ & (\lambda a^\sim f^\sim hyp. s^\sim (\gamma^\sim, a^\sim, f^\sim, hyp)) \\ & (w^\sim \gamma^\sim) \end{aligned}$$

$W^\sim\text{-elim}$  is the eliminator for  $W^\sim$ . Its first argument is the induction motive, which matches the goal type. The second argument is the method for  $\text{sup}^\sim$ ; its  $a^\sim$  and  $f^\sim$  inputs are the relatedness witnesses stored in a  $\text{sup}^\sim$ , while  $hyp$  is induction hypothesis, witnessing the inductive motive for every output of  $f^\sim$ . In the body here, we need to witness the motive in the case where  $w$  is a  $\text{sup}$ , which causes both  $\mathbb{E} (W\text{-elim } P s w) \gamma$  and  $\mathbb{R} (W\text{-elim } P s w) \gamma'$  to compute further to applications of  $\mathbb{E} s \gamma$  and  $\mathbb{R} s \gamma'$  respectively. Hence, we use  $s^\sim$  to relate the two sides. This definition also respects  $W\beta$ , by the  $\beta$  rule for  $W^\sim$ .

#### A.4 Identity type

In this section we assume an *extensional* identity type in CFTT. As we mentioned in Section ??, we can show soundness of staging with extensional identity and certain *postulated* identities, but we cannot do the same with intensional identity. Hence, we formulate unstaging as consisting of two steps: first, a translation of intensional identity to extensional (which amounts to proof erasure), followed by evaluation in the presheaf model.

Extensional identity in CFTT type is interpreted as the standard extensional identity in presheaves, i.e. we have  $\mathbb{E} (\text{Id } A t u) \gamma := \mathbb{E} t \gamma = \mathbb{E} u \gamma$ . This supports refl, transport, uniqueness of identity and equality reflection; we omit the fairly trivial definitions here. We choose the relational interpretation to be trivial as well, i.e.  $(\text{Id } t u)^\sim \gamma^\sim p p' := \top$ .

This is because both  $\mathbb{E} (\text{Id } t u) \gamma$  and  $\mathbb{R} (\text{Id } t u) \gamma'$  are mere propositions — the latter because of equality reflection in the syntax. In particular, if we have a witness of  $\mathbb{R} (\text{Id } t u) \gamma'$ , we also have  $\mathbb{R} t \gamma' = \mathbb{R} u \gamma'$  by equality reflection. Thus, the rest of the relational interpretation of  $\text{Id}$  is also trivial. Another way to think about this is that soundness expresses a form of canonicity, but if we have equality reflection then syntactic identities are always canonical.

#### A.5 Generativity

The generativity axiom from Section ?? has the following type, in internal CFTT syntax:

$$(A : \mathbb{U}_P)(f : \mathbb{E}_P A \rightarrow \mathbb{U}_{\text{SOP}})(x y : \mathbb{E}_P A) \rightarrow f x = f y$$

In the presheaf model, we have the following:

- $\widehat{\mathbb{U}_P}$  is the set (constant presheaf) of lists of object-theoretic types.
- $\widehat{\mathbb{U}_{\text{SOP}}}$  is the set of lists of lists of object-theoretic types.
- $\mathbb{E}_P A$  is the presheaf such that  $\widehat{\mathbb{E}_P A \Gamma}$  is the set of products of object-theoretic terms in context  $\Gamma$ , with types of components taken from  $A$ .

Unfolding the type of generativity in the presheaf model, it suffices to show that assuming

- $A : \widehat{\mathbb{U}_P}, \Gamma : \text{Con}_\mathbb{O}, x, y : \widehat{\mathbb{E}_P A \Gamma}$

- and  $f : (\Delta : \text{Con}_0) \rightarrow \text{Sub}_0 \Delta \Gamma \rightarrow \widehat{\text{El}_p A} \Delta \rightarrow \widehat{\text{U}_{\text{SOP}}}$  such that  $f$  is natural with respect to object-theoretic substitution,

we have that  $f \Gamma \text{id } x = f \Gamma \text{id } y$ .

Now,  $\widehat{\text{El}_p A}$  is a representable presheaf since it is a finite product of object-theoretic terms. Also, since  $f$  is a natural transformation from the representable presheaf  $\text{Sub}_0 - \Gamma \times \widehat{\text{El}_p A}$  to the constant presheaf  $\widehat{\text{U}_{\text{SOP}}}$ , the Yoneda lemma implies that  $f$  is constant and hence the generativity axiom is validated.

Since the logical relation interpretation of identity is trivial, it is also trivial for the generativity axiom.

## A.6 Summary

By the presheaf and logical relations interpretation of CFTT as shown in this appendix, we obtain *unstaging* and *soundness* of unstaging, following [Kovács 2022].

*Strictness* of unstaging holds trivially, since there are no  $\beta$  and  $\eta$  rules in the object theory. *Completeness* of unstaging is shown by straightforward induction on the syntax of the object theory, the same way as in [Kovács 2022], and we omit it here.

## REFERENCES

- Agda developers. 2024. Agda documentation. <https://agda.readthedocs.io/en/v2.6.4.2/>
- Danil Annenkov, Paolo Capriotti, Nicolai Kraus, and Christian Sattler. 2019. Two-Level Type Theory and Applications. *ArXiv e-prints* (may 2019). <http://arxiv.org/abs/1705.03307>
- Anders Bondorf. 1992. Improving Binding Times Without Explicit CPS-Conversion. In *Proceedings of the Conference on Lisp and Functional Programming, LFP 1992, San Francisco, California, USA, 22-24 June 1992*, Jon L. White (Ed.). ACM, 1–10. <https://doi.org/10.1145/141471.141483>
- Simon Boulrier, Pierre-Marie Pédro, and Nicolas Tabareau. 2017. The Next 700 Syntactical Models of Type Theory. In *Proceedings of the 6th ACM SIGPLAN Conference on Certified Programs and Proofs (Paris, France) (CPP 2017)*. ACM, New York, NY, USA, 182–194. <https://doi.org/10.1145/3018610.3018620>
- Joachim Breitner. 2014. Call Arity. In *Trends in Functional Programming - 15th International Symposium, TFP 2014, Soesterberg, The Netherlands, May 26-28, 2014. Revised Selected Papers (Lecture Notes in Computer Science, Vol. 8843)*, Jurriaan Hage and Jay McCarthy (Eds.). Springer, 34–50. [https://doi.org/10.1007/978-3-319-14675-1\\_3](https://doi.org/10.1007/978-3-319-14675-1_3)
- Jacques Carette and Oleg Kiselyov. 2011. Multi-stage programming with functors and monads: Eliminating abstraction overhead from generic code. *Sci. Comput. Program.* 76, 5 (2011), 349–375. <https://doi.org/10.1016/J.SCICO.2008.09.008>
- Wontae Choi, Baris Aktemur, Kwangkeun Yi, and Makoto Tatsuta. 2011. Static analysis of multi-staged programs via unstaging translation. In *Proceedings of the 38th ACM SIGPLAN-SIGACT Symposium on Principles of Programming Languages, POPL 2011, Austin, TX, USA, January 26-28, 2011*, Thomas Ball and Mooly Sagiv (Eds.). ACM, 81–92. <https://doi.org/10.1145/1926385.1926397>
- Duncan Coutts. 2011. *Stream fusion : practical shortcut fusion for coinductive sequence types*. Ph.D. Dissertation. University of Oxford, UK. <http://ora.ox.ac.uk/objects/uuid:b4971f57-2b94-4fdf-a5c0-98d6935a44da>
- Olivier Danvy, Karoline Malmkjær, and Jens Palsberg. 1996. Eta-Expansion Does The Trick. *ACM Trans. Program. Lang. Syst.* 18, 6 (1996), 730–751. <https://doi.org/10.1145/236114.236119>
- Olivier Danvy and Lasse R. Nielsen. 2001. Defunctionalization at Work. In *Proceedings of the 3rd international ACM SIGPLAN conference on Principles and practice of declarative programming, September 5-7, 2001, Florence, Italy*. ACM, 162–174. <https://doi.org/10.1145/773184.773202>
- Edsko de Vries and Andres Löb. 2014. True sums of products. In *Proceedings of the 10th ACM SIGPLAN workshop on Generic programming, WGP 2014, Gothenburg, Sweden, August 31, 2014*, José Pedro Magalhães and Tiark Ropff (Eds.). ACM, 83–94. <https://doi.org/10.1145/2633628.2633634>
- Paul Downen, Zena M. Ariola, Simon Peyton Jones, and Richard A. Eisenberg. 2020. Kinds are calling conventions. *Proc. ACM Program. Lang.* 4, ICFP (2020), 104:1–104:29. <https://doi.org/10.1145/3408986>
- Peter Dybjer. 1994. Inductive Families. *Formal Aspects Comput.* 6, 4 (1994), 440–465. <https://doi.org/10.1007/BF01211308>
- Richard A. Eisenberg and Stephanie Weirich. 2012. Dependently typed programming with singletons. In *Proceedings of the 5th ACM SIGPLAN Symposium on Haskell, Haskell 2012, Copenhagen, Denmark, 13 September 2012*, Janis Voigtländer (Ed.). ACM, 117–130. <https://doi.org/10.1145/2364506.2364522>

- Cormac Flanagan, Amr Sabry, Bruce F. Duba, and Matthias Felleisen. 1993. The Essence of Compiling with Continuations. In *Proceedings of the ACM SIGPLAN'93 Conference on Programming Language Design and Implementation (PLDI), Albuquerque, New Mexico, USA, June 23-25, 1993*, Robert Cartwright (Ed.). ACM, 237–247. <https://doi.org/10.1145/155090.155113>
- GHC developers. 2024a. GHC documentation. [https://downloads.haskell.org/ghc/9.8.2/docs/users\\_guide/](https://downloads.haskell.org/ghc/9.8.2/docs/users_guide/)
- GHC developers. 2024b. GHC. Base source. <https://hackage.haskell.org/package/base-4.19.1.0/docs/src/GHC.Base.html#>.
- Ralf Hinze, Thomas Harper, and Daniel W. H. James. 2010. Theory and Practice of Fusion. In *Implementation and Application of Functional Languages - 22nd International Symposium, IFL 2010, Alphen aan den Rijn, The Netherlands, September 1-3, 2010, Revised Selected Papers (Lecture Notes in Computer Science, Vol. 6647)*, Jurriaan Hage and Marco T. Morazán (Eds.). Springer, 19–37. [https://doi.org/10.1007/978-3-642-24276-2\\_2](https://doi.org/10.1007/978-3-642-24276-2_2)
- Martin Hofmann. 1995. Conservativity of Equality Reflection over Intensional Type Theory.. In *TYPES 95*. 153–164.
- Martin Hofmann. 1997. Syntax and Semantics of Dependent Types. In *Semantics and Logics of Computation*. Cambridge University Press, 79–130.
- Simon Huber. 2016. *Cubical Interpretations of Type Theory*. Ph. D. Dissertation. University of Gothenburg.
- Jasper Hugunin. 2020. Why Not W?. In *26th International Conference on Types for Proofs and Programs, TYPES 2020, March 2-5, 2020, University of Turin, Italy (LIPIcs, Vol. 188)*, Ugo de'Liguoro, Stefano Berardi, and Thorsten Altenkirch (Eds.). Schloss Dagstuhl - Leibniz-Zentrum für Informatik, 8:1–8:9. <https://doi.org/10.4230/LIPICS.TYPES.2020.8>
- Neil D. Jones, Carsten K. Gomard, and Peter Sestoft. 1993. *Partial evaluation and automatic program generation*. Prentice Hall.
- Simon Peyton Jones. 2001. Tackling the awkward squad: monadic input/output, concurrency, exceptions, and foreign-language calls in Haskell. *NATO SCIENCE SERIES SUB SERIES III COMPUTER AND SYSTEMS SCIENCES* 180 (2001), 47–96.
- Oleg Kiselyov, Aggelos Biboudis, Nick Palladinos, and Yannis Smaragdakis. 2017. Stream fusion, to completeness. In *Proceedings of the 44th ACM SIGPLAN Symposium on Principles of Programming Languages, POPL 2017, Paris, France, January 18-20, 2017*, Giuseppe Castagna and Andrew D. Gordon (Eds.). ACM, 285–299. <https://doi.org/10.1145/3009837.3009880>
- Oleg Kiselyov, Kedar N. Swadi, and Walid Taha. 2004. A methodology for generating verified combinatorial circuits. In *EMSOFT 2004, September 27-29, 2004, Pisa, Italy, Fourth ACM International Conference On Embedded Software, Proceedings*, Giorgio C. Buttazzo (Ed.). ACM, 249–258. <https://doi.org/10.1145/1017753.1017794>
- Tomoaki Kobayashi and Oleg Kiselyov. 2024. Complete Stream Fusion for Software-Defined Radio. In *Proceedings of the 2024 ACM SIGPLAN International Workshop on Partial Evaluation and Program Manipulation, PEPM 2024, London, UK, 16 January 2024*, Gabriele Keller and Meng Wang (Eds.). ACM, 57–69. <https://doi.org/10.1145/3635800.3636962>
- András Kovács. 2022. Staged Compilation with Two-Level Type Theory. *Proc. ACM Program. Lang.* 6, ICFP (2022), 540–569. <https://doi.org/10.1145/3547641>
- András Kovács. 2022. Demo implementation for the paper "Staged Compilation With Two-Level Type Theory". <https://doi.org/10.5281/zenodo.6757373>
- Xavier Leroy, Damien Doligez, Alain Frisch, Jacques Garrigue, Didier Rémy, KC Sivaramakrishnan, and Jérôme Vouillon. 2023. The OCaml system release 5.1: Documentation and user's manual. <https://v2.ocaml.org/manual/>
- Paul Blain Levy. 1999. Call-by-Push-Value: A Subsuming Paradigm. In *Typed Lambda Calculi and Applications, 4th International Conference, TLCA'99, L'Aquila, Italy, April 7-9, 1999, Proceedings (Lecture Notes in Computer Science, Vol. 1581)*, Jean-Yves Girard (Ed.). Springer, 228–242. [https://doi.org/10.1007/3-540-48959-2\\_17](https://doi.org/10.1007/3-540-48959-2_17)
- Sheng Liang, Paul Hudak, and Mark P. Jones. 1995. Monad Transformers and Modular Interpreters. In *Conference Record of POPL'95: 22nd ACM SIGPLAN-SIGACT Symposium on Principles of Programming Languages, San Francisco, California, USA, January 23-25, 1995*, Ron K. Cytron and Peter Lee (Eds.). ACM Press, 333–343. <https://doi.org/10.1145/199448.199528>
- Luke Maurer, Paul Downen, Zena M. Ariola, and Simon L. Peyton Jones. 2017. Compiling without continuations. In *Proceedings of the 38th ACM SIGPLAN Conference on Programming Language Design and Implementation, PLDI 2017, Barcelona, Spain, June 18-23, 2017*, Albert Cohen and Martin T. Vechev (Eds.). ACM, 482–494. <https://doi.org/10.1145/3062341.3062380>
- mtl developers. 2024. mtl documentation. <https://hackage.haskell.org/package/mtl>
- Flemming Nielson. 1984. *Abstract interpretation using domain theory*. Ph. D. Dissertation. University of Edinburgh, UK. <https://ethos.bl.uk/OrderDetails.do?uin=uk.bl.ethos.350060>
- Flemming Nielson and Hanne Riis Nielson. 1992. *Two-level functional languages*. Cambridge tracts in theoretical computer science, Vol. 34. Cambridge University Press.
- Matthew Pickering, Andres Löb, and Nicolas Wu. 2020. Staged sums of products. In *Proceedings of the 13th ACM SIGPLAN International Symposium on Haskell, Haskell@ICFP 2020, Virtual Event, USA, August 7, 2020*, Tom Schrijvers (Ed.). ACM, 122–135. <https://doi.org/10.1145/3406088.3409021>
- John C. Reynolds. 1998. Definitional Interpreters for Higher-Order Programming Languages. *High. Order Symb. Comput.* 11, 4 (1998), 363–397. <https://doi.org/10.1023/A:1010027404223>



- Amos Robinson and Ben Lippmeier. 2017. Machine fusion: merging merges, more or less. In *Proceedings of the 19th International Symposium on Principles and Practice of Declarative Programming, Namur, Belgium, October 09 - 11, 2017*, Wim Vanhoof and Brigitte Pientka (Eds.). ACM, 139–150. <https://doi.org/10.1145/3131851.3131865>
- Tiark Rumpf and Martin Odersky. 2012. Lightweight modular staging: a pragmatic approach to runtime code generation and compiled DSLs. *Commun. ACM* 55, 6 (2012), 121–130. <https://doi.org/10.1145/2184319.2184345>
- Kedar N. Swadi, Walid Taha, Oleg Kiselyov, and Emir Pasalic. 2006. A monadic approach for avoiding code duplication when staging memoized functions. In *Proceedings of the 2006 ACM SIGPLAN Workshop on Partial Evaluation and Semantics-based Program Manipulation, 2006, Charleston, South Carolina, USA, January 9-10, 2006*, John Hatcliff and Frank Tip (Eds.). ACM, 160–169. <https://doi.org/10.1145/1111542.1111570>
- Walid Taha and Tim Sheard. 2000. MetaML and multi-stage programming with explicit annotations. *Theor. Comput. Sci.* 248, 1-2 (2000), 211–242. [https://doi.org/10.1016/S0304-3975\(00\)00053-0](https://doi.org/10.1016/S0304-3975(00)00053-0)
- Vladimir Voevodsky. 2013. A simple type system with two identity types. (2013). Unpublished note.
- Philip Wadler. 1989. Theorems for free!. In *Functional Programming Languages and Computer Architecture*. ACM Press, 347–359.
- Philip Wadler and Stephen Blott. 1989. How to Make ad-hoc Polymorphism Less ad-hoc. In *Conference Record of the Sixteenth Annual ACM Symposium on Principles of Programming Languages, Austin, Texas, USA, January 11-13, 1989*. ACM Press, 60–76. <https://doi.org/10.1145/75277.75283>
- Ningning Xie, Matthew Pickering, Andres Löb, Nicolas Wu, Jeremy Yallop, and Meng Wang. 2022. Staging with class: a specification for typed template Haskell. *Proc. ACM Program. Lang.* 6, POPL (2022), 1–30. <https://doi.org/10.1145/3498723>
- Jeremy Yallop and Oleg Kiselyov. 2019. Generating mutually recursive definitions. In *Proceedings of the 2019 ACM SIGPLAN Workshop on Partial Evaluation and Program Manipulation, PEPM@POPL 2019, Cascais, Portugal, January 14-15, 2019*, Manuel V. Hermenegildo and Atsushi Igarashi (Eds.). ACM, 75–81. <https://doi.org/10.1145/3294032.3294078>