


Control Flow Analysis

Copyright 2009, Pedro C. Diniz, all rights reserved.
Students enrolled in the Compilers class at Instituto Superior Técnico (IST/UTL) have explicit permission to make copies of these materials for their personal use.

Outline

- Overview of Optimizations
- Control-Flow Analysis
- Dominators
- Graph Traversal
- Reducible Graphs
- Interval Analysis
- Few Definitions

Anatomy of a Compiler



Example

```

int sumcalc(int a, int b, int N)
{
    int i;
    int x, y;
    x = 0;
    y = 0;
    for(i = 0; i <= N; i++) {
        x = x + (4*a/b)*i + (i+1)*(i+1);
        x = x + b*y;
    }
    return x;
}
  
```



Example in Assembly

```
test:
subu $fp, 16
sw zero, 0($fp)      # x = 0
sw zero, 4($fp)      # y = 0
sw zero, 8($fp)      # i = 0
lab1:                 # for(i=0; i<N; i++)
mul $t0, $a0, 4       # a*4
div $t1, $t0, $a1     # a*4/b
lw $t2, 8($fp)        # i
mul $t3, $t1, $t2     # a*4/b*i
lw $t4, 8($fp)        # i
addui $t4, $t4, 1     # i+1
lw $t5, 8($fp)        # i
addui $t5, $t5, 1     # i+1
mul $t6, $t4, $t5     # (i+1)*(i+1)
addu $t7, $t3, $t6     # a*4/b*i + (i+1)*(i+1)
lw $t8, 0($fp)        # x
add $t8, $t7, $t8     # x = x + a*4/b*i + (i+1)*(i+1)
sw $t8, 0($fp)
...
```



Example in Assembly

```
...
lw $t0, 4($fp)        # y
mul $t1, $t0, $a1     # b*y
lw $t2, 0($fp)        # x
add $t2, $t2, $t1     # x = x + b*y
sw $t2, 0($fp)

lw $t0, 8($fp)        # i
addui $t0, $t0, 1     # i+1
sw $t0, 8($fp)
ble $t0, $a3, lab1

lw $v0, 0($fp)
addu $fp, 16
b $ra
```



Let's Optimize...

```
int sumcalc(int a, int b, int N)
{
    int i;
    int x, y;
    x = 0;
    y = 0;
    for(i = 0; i <= N; i++) {
        x = x + (4*a/b)*i + (i+1)*(i+1);
        x = x + b*y;
    }
    return x;
}
```



Constant Propagation

```
int sumcalc(int a, int b, int N)
{
    int i;
    int x, y;
    x = 0;
    y = 0;
    for(i = 0; i <= N; i++) {
        x = x + (4*a/b)*i + (i+1)*(i+1);
        x = x + b*y;
    }
    return x;
}
```

Constant Propagation

```
int sumcalc(int a, int b, int N)
{
    int i;
    int x, y;
    x = 0;
    y = 0;
    for(i = 0; i <= N; i++) {
        x = x + (4*a/b)*i + (i+1)*(i+1);
        x = x + b*y;
    }
    return x;
}
```

Constant Propagation

```
int sumcalc(int a, int b, int N)
{
    int i;
    int x, y;
    x = 0;
    y = 0;
    for(i = 0; i <= N; i++) {
        x = x + (4*a/b)*i + (i+1)*(i+1);
        x = x + b*y;
    }
    return x;
}
```

Constant Propagation

```
int sumcalc(int a, int b, int N)
{
    int i;
    int x, y;
    x = 0;
    y = 0;
    for(i = 0; i <= N; i++) {
        x = x + (4*a/b)*i + (i+1)*(i+1);
        x = x + b*0;
    }
    return x;
}
```

Algebraic Simplification

```
int sumcalc(int a, int b, int N)
{
    int i;
    int x, y;
    x = 0;
    y = 0;
    for(i = 0; i <= N; i++) {
        x = x + (4*a/b)*i + (i+1)*(i+1);
        x = x + b*0;
    }
    return x;
}
```



Algebraic Simplification

```
int sumcalc(int a, int b, int N)
{
    int i;
    int x, y;
    x = 0;
    y = 0;
    for(i = 0; i <= N; i++) {
        x = x + (4*a/b)*i + (i+1)*(i+1);
        x = x + b*0;
    }
    return x;
}
```



Algebraic Simplification

```
int sumcalc(int a, int b, int N)
{
    int i;
    int x, y;
    x = 0;
    y = 0;
    for(i = 0; i <= N; i++) {
        x = x + (4*a/b)*i + (i+1)*(i+1);
        x = x + 0;
    }
    return x;
}
```



Algebraic Simplification

```
int sumcalc(int a, int b, int N)
{
    int i;
    int x, y;
    x = 0;
    y = 0;
    for(i = 0; i <= N; i++) {
        x = x + (4*a/b)*i + (i+1)*(i+1);
        x = x + 0;
    }
    return x;
}
```



Algebraic Simplification

```
int sumcalc(int a, int b, int N)
{
    int i;
    int x, y;
    x = 0;
    y = 0;
    for(i = 0; i <= N; i++) {
        x = x + (4*a/b)*i + (i+1)*(i+1);
        x = x;
    }
    return x;
}
```

Copy Propagation

```
int sumcalc(int a, int b, int N)
{
    int i;
    int x, y;
    x = 0;
    y = 0;
    for(i = 0; i <= N; i++) {
        x = x + (4*a/b)*i + (i+1)*(i+1);
        x = x;
    }
    return x;
}
```

Copy Propagation

```
int sumcalc(int a, int b, int N)
{
    int i;
    int x, y;
    x = 0;
    y = 0;
    for(i = 0; i <= N; i++) {
        x = x + (4*a/b)*i + (i+1)*(i+1);
    }
    return x;
}
```

Common Sub-expression Elimination (CSE)

```
int sumcalc(int a, int b, int N)
{
    int i;
    int x, y;
    x = 0;
    y = 0;
    for(i = 0; i <= N; i++) {
        x = x + (4*a/b)*i + (i+1)*(i+1);
    }
    return x;
}
```

Common Sub-expression Elimination (CSE)

```
int sumcalc(int a, int b, int N)
{
    int i;
    int x, y;
    x = 0;
    y = 0;
    for(i = 0; i <= N; i++) {
        x = x + (4*a/b)*i + (i+1)*(i+1);
    }
    return x;
}
```



Common Sub-expression Elimination (CSE)

```
int sumcalc(int a, int b, int N)
{
    int i;
    int x, y, t;
    x = 0;
    y = 0;
    for(i = 0; i <= N; i++) {
        t = i+1;
        x = x + (4*a/b)*i + t * t;
    }
    return x;
}
```



Dead Code Elimination

```
int sumcalc(int a, int b, int N)
{
    int i;
    int x, y, t;
    x = 0;
    y = 0;
    for(i = 0; i <= N; i++) {
        t = i+1;
        x = x + (4*a/b)*i + t * t;
    }
    return x;
}
```



Dead Code Elimination

```
int sumcalc(int a, int b, int N)
{
    int i;
    int x, y, t;
    x = 0;
    y = 0;
    for(i = 0; i <= N; i++) {
        t = i+1;
        x = x + (4*a/b)*i + t * t;
    }
    return x;
}
```



Dead Code Elimination

```
int sumcalc(int a, int b, int N)
{
    int i;
    int x, t;
    x = 0;

    for(i = 0; i <= N; i++) {
        t = i+1;
        x = x + (4*a/b)*i + t * t;
    }
    return x;
}
```



Loop Invariant Removal

```
int sumcalc(int a, int b, int N)
{
    int i;
    int x, t;
    x = 0;

    for(i = 0; i <= N; i++) {
        t = i+1;
        x = x + (4*a/b)*i + t * t;
    }
    return x;
}
```



Loop Invariant Removal

```
int sumcalc(int a, int b, int N)
{
    int i;
    int x, t;
    x = 0;

    for(i = 0; i <= N; i++) {
        t = i+1;
        x = x + (4*a/b)*i + t * t;
    }
    return x;
}
```



Loop Invariant Removal

```
int sumcalc(int a, int b, int N)
{
    int i;
    int x, t, u;
    x = 0;
    u = (4*a/b);
    for(i = 0; i <= N; i++) {
        t = i+1;
        x = x + u*i + t * t;
    }
    return x;
}
```



Strength Reduction

```
int sumcalc(int a, int b, int N)
{
    int i;
    int x, t, u;
    x = 0;
    u = (4*a/b);
    for(i = 0; i <= N; i++) {
        t = i+1;
        x = x + u*i + t * t;
    }
    return x;
}
```

Strength Reduction

```
int sumcalc(int a, int b, int N)
{
    int i;
    int x, t, u;
    x = 0;
    u = (4*a/b);
    for(i = 0; i <= N; i++) {
        t = i+1;
        x = x + u*i + t * t;
    }
    return x;
}
```

u*0,	v=0,
u*1,	v=v+u,
u*2,	v=v+u,
u*3,	v=v+u,
u*4,	v=v+u,
...	...

Strength Reduction

```
int sumcalc(int a, int b, int N)
{
    int i;
    int x, t, u, v;
    x = 0;
    u = (4*a/b);
    v = 0;
    for(i = 0; i <= N; i++) {
        t = i+1;
        x = x + u*i + t*t;
        v = v + u;
    }
    return x;
}
```

Strength Reduction

```
int sumcalc(int a, int b, int N)
{
    int i;
    int x, t, u, v;
    x = 0;
    u = (4*a/b);
    v = 0;
    for(i = 0; i <= N; i++) {
        t = i+1;
        x = x + v + t*t;
        v = v + u;
    }
    return x;
}
```

Strength Reduction

```
int sumcalc(int a, int b, int N)
{
    int i;
    int x, t, u, v;
    x = 0;
    u = (4*a/b);
    v = 0;
    for(i = 0; i <= N; i++) {
        t = i+1;
        x = x + v + t*t;
        v = v + u;
    }
    return x;
}
```


Strength Reduction

```
int sumcalc(int a, int b, int N)
{
    int i;
    int x, t, u, v;
    x = 0;
    u = (4*a/b);
    v = 0;
    for(i = 0; i <= N; i++) {
        t = i+1;
        x = x + v + t*t;
        v = v + u;
    }
    return x;
}
```

Strength Reduction

```
int sumcalc(int a, int b, int N)
{
    int i;
    int x, t, u, v;
    x = 0;
    u = ((a<<2)/b);
    v = 0;
    for(i = 0; i <= N; i++) {
        t = i+1;
        x = x + v + t*t;
        v = v + u;
    }
    return x;
}
```

Register Allocation

Local variable x
Local variable y
Local variable i

← fp

Register Allocation

Local variable x
Local variable y
Local variable i

← fp

```
$t9 = x
$t8 = t
$t7 = u
$t6 = v
$t5 = i
```

Optimized Example

```
int sumcalc(int a, int b, int N)
{
    int i;
    int x, t, u, v;
    x = 0;
    u = ((a<<2)/b);
    v = 0;
    for(i = 0; i <= N; i++) {
        t = i+1;
        x = x + v + t*t;
        v = v + u;
    }
    return x;
}
```

Optimized Example in Assembly

```
test:
    subu $fp, 16
    add $t9, zero, zero    # x = 0
    sll $t0, $a0, 2        # a<<2
    div $t7, $t0, $a1      # u = (a<<2)/b
    add $t6, zero, zero    # v = 0
    add $t5, zero, zero    # i = 0

lab1:
    # for(i=0; i<N; i++)
    addui $t8, $t5, 1      # t = i+1
    mul $t0, $t8, $t8      # t*t
    addu $t1, $t0, $t6     # v + t*t
    addu $t9, $t9, $t1     # x = x + v + t*t

    addu $6, $6, $7        # v = v + u

    addui $t5, $t5, 1      # i = i+1
    ble $t5, $a3, lab1

    addu $v0, $t9, zero
    addu $fp, 16
    b $ra
```

Optimized Example in Assembly

Unoptimized Code

```
test:
    subu $fp, 16
    sw zero, 0($fp)
    sw zero, 8($fp)
lab1:
    mul $t0, $a0, 4
    div $t1, $t0, $a1
    lw $t2, 16($fp)
    mul $t3, $t1, $t2
    sw $t3, 24($fp)
    addui $t4, $t4, 1
    lw $t5, 16($fp)
    addui $t5, $t5, 1
    mul $t6, $t5, $t5
    addu $t7, $t3, $t6
    addu $t8, $t7, $t4
    lw $t9, 24($fp)
    addu $t9, $t9, $t8
    sw $t9, 32($fp)
    lw $t0, 16($fp)
    mul $t1, $t0, $t1
    lw $t2, 32($fp)
    addu $t2, $t2, $t1
    lw $t3, 16($fp)
    addu $t3, $t3, $t2
    bne $t3, $a3, lab1

    lw $v0, 0($fp)
    addu $fp, 16
    b $ra

4*ld/st + 2*add/sub + br +
N*(9*ld/st + 6*add/sub + 4*mul + div + br)
= 7 + N*21
```

Execution time = 43 usec

Optimized Code

```
test:
    subu $fp, 16
    sw $t0, zero, zero
    sll $t0, $a0, 2
    div $t7, $t0, $a1
    add $t6, zero, zero
lab1:
    addui $t8, $t5, 1
    mul $t0, $t8, $t8
    addu $t1, $t0, $t6
    addu $t9, $t9, $t1
    addu $6, $6, $7
    addui $t5, $t5, 1
    ble $t5, $a3, lab1

    addu $v0, $t9, zero
    addu $fp, 16
    b $ra

6*add/sub + shift + div + br +
N*(5*add/sub + mul + br)
= 9 + N*7
```

Execution time = 17 usec

Question: Can you optimize...

```
int foobar(int N)
{
    int i, j, k, x, y;
    x = 0;
    y = 0;
    k = 256;
    for(i = 0; i <= N; i++) {
        for(j = i+1; j <= N; j++) {
            x = x + 4*(2*i+j)*(i+2*k);
            if(i>j)
                y = y + 8*(i-j);
            else
                y = y + 8*(j-i);
        }
    }
    return x;
}
```

Question: Can you optimize...

```
int foobar(int N)
{
    int i, j, k, x, y;
    x = 0;
    y = 0;
    k = 256;
    for(i = 0; i <= N; i++) {
        for(j = i+1; j <= N; j++) {
            x = x+8*i+4096*i+j*(4*i+2048);
        }
    }
    return x;
}
```

Question: Can you optimize...

```
int foobar(int N)
{
    int i, j, x, t0, t1;
    x = 0;
    t1 = 2048;
    for(i = 0; i <= N-1; i++) {
        t0 = (i*i)<<3 + i<<12;
        x = x + (N-i)*t0;
        for(j = i+1; j <= N; j++) {
            x = x + t1*j;
        }
        t1 = t1 + 4;
    }
    return x;
}
```

Question: Can you optimize...

```
int foobar(int N)
{
    int i, j, x, t0, t1;
    x = 0;
    t1 = 1024;
    for(i = 0; i <= N-1; i++) {
        t0 = (i*i)<<3 + i<<12;
        x = x + (N-i)*t0 + t1*(N*(N+1)-i*(i+1));
        t1 = t1 + 2;
    }
    return x;
}
```

Outline

- Overview of Optimizations
- Control-Flow Analysis
- Dominators
- Graph Traversal
- Reducible Graphs
- Interval Analysis
- Few Definitions

Constant Propagation

```
int sumcalc(int a, int b, int N)
{
    int i;
    int x, y;
    x = 0;
    y = 0;
    for(i = 0; i <= N; i++) {
        x = x + (4*a/b)*i + (i+1)*(i+1);
        x = x + b*y;
    }
    return x;
}
```

Constant Propagation

```
int sumcalc(int a, int b, int N)
{
    int i;
    int x, y;
    x = 0;
    y = 0;
    for(i = 0; i <= N; i++) {
        x = x + (4*a/b)*i + (i+1)*(i+1);
        x = x + b*y;
    }
    return x;
}
```

Constant Propagation

```
int sumcalc(int a, int b, int N)
{
    int i;
    int x, y;
    x = 0;
    y = 0;
    for(i = 0; i <= N; i++) {
        x = x + (4*a/b)*i + (i+1)*(i+1);
        x = x + b*y;
    }
    return x;
}
```

Constant Propagation

```
int sumcalc(int a, int b, int N)
{
    int i;
    int x, y;
    x = 0;
    y = 0;
    for(i = 0; i <= N; i++) {
        x = x + (4*a/b)*i + (i+1)*(i+1);
        x = x + b*0;
    }
    return x;
}
```

Implementing Constant Propagation

- Find an RHS expression that is a Constant
- Replace the use of the LHS variable with the RHS Constant given that:
 - All paths to the use of LHS passes the assignment of the LHS with the constant
 - There are no intervening definition of the RHS variable
- Need to know the “control-flow” of the program


Representing the Control Flow of a Program

- Most instructions
 - execute the next instruction
 - straight line control-flow
- Jump instructions
 - execute from different location
 - jump in control-flow
- Branch instructions
 - execute either the next instruction or from a different location
 - fork in the control-flow



Representing Control Flow


- Forms a Graph



- A Very Large Graph
- Observations
 - lots of straight-line connections
 - simplify the graph by grouping some instructions

Representing Control Flow


- Forms a Graph



- A Very Large Graph
- Observations
 - lots of straight-line connections
 - simplify the graph by grouping some instructions

Representing Control Flow

- Forms a Graph



- A Very Large Graph
- Observations
 - lots of straight-line connections
 - simplify the graph by grouping some instructions


Basic Blocks

- A Basic Block is a maximal sequence of instructions such that
 - Only the first instruction can be reached from outside the basic block
 - All the instructions are executed consecutively if the first instruction is executed
 - No branch or jump instructions in the basic block
 - Except the last instruction
 - No labels within the basic block
 - Except before the first instruction

Basic Blocks: Algorithm

- Input: Sequence of Three-Address Instructions
- Output: A list of Basic Blocks
- Algorithm:
 - Determine the set of *leaders*, the head of a basic block using the following:
 - The first statement of the program is a *leader*
 - Any statement that is the target of a goto (either conditional or not) is a *leader*
 - Any statement that immediately follows a goto or unconditional goto statement is a *leader*
 - For each *leader*, its basic block consists of the *leader* and all the statements up to but not including the next *leader* or the end of the program.

Basic Blocks: Example





Control Flow Graph (CFG)

- Control-Flow Graph $G = \langle N, E \rangle$
- Nodes(N): Basic Blocks
- Edges(E): $(x, y) \in E$ iff first instruction in the basic block y follows the last instruction in the basic block x
 - First instruction in y is the target of branch or jump instruction (last instruction) in the basic block x
 - first instruction of y is next after the last instruction of x in memory and the last instruction of x is not a jump instruction



Control Flow Graph (CFG)

- Block with the first instruction of the procedure is the entry node (block with the procedure label)
- The blocks with the return instruction (jsr) are the exit nodes.
 - Can make a single exit node by adding a special node



Why Control-flow Analysis ?

- Loops are important to optimize
 - Programs spend a lot of times in loops and recursive cycles
 - Many special optimizations can be done on loops
- Programmers organize code using structured control-flow (if-then-else, for-loops *etc*)
 - optimizer can exploit this
 - but need to discover them first



Challenges in Control-Flow Analysis

- Unstructured Control Flow
 - Use of goto's by the programmer
 - Only way to build certain control structures


```
L1: x = 0
    if (y > 0) goto L3
L2: if (y < 0) goto L1
L3: y = y + z
    goto L2
```
- Obscured Control Flow
 - Method Invocations
 - Procedure Variables
 - Higher-Order Functions
 - Jump Tables

```
Myobject->run()
```

Building CFGs


- Simple:
 - Programs are written in structured control flow
 - Has simple CFG patterns
- Not so!
 - Gotos can create different control-flow patterns than what is given by the structured control-flow
 - Need to perform analyses to identify true control-flow patterns

Identifying Recursive Structures Loops




Identifying Recursive Structures Loops

- Identify back edges




Identifying Recursive Structures Loops

- Identify back edges
- Find the nodes and edges in the loop given by the back edge




Identifying Recursive Structures Loops

- Identify back edges
- Find the nodes and edges in the loop given by the back edge
- Other than the back edge
 - Incoming edges only to the basic block with the back edge head
 - one outgoing edge from the basic block with the tail of the back edge



Identifying Recursive Structures Loops

- Identify back edges
- Find the nodes and edges in the loop given by the back edge
- Other than the back edge
 - Incoming edges only to the basic block with the back edge head
 - one outgoing edge from the basic block with the tail of the back edge
- How do I find the back edges?



Outline


- Overview of Optimizations
- Control-Flow Analysis
- Dominators
- Graph Traversal
- Reducible Graphs
- Interval Analysis
- Few Definitions

Dominators

- Node x dominates node y ($x \text{ dom } y$) if every possible execution path from entry to node y includes node x


Dominators

- Is bb1 dom bb5?




Dominators

- Is bb1 dom bb5?




Dominators

- Is bb1 dom bb5?




Dominators

- Is bb1 dom bb5?




Dominators

- Is bb1 dom bb5?




Dominators

- Is bb1 dom bb5? Yes!




Dominators

- Is bb1 dom bb5? Yes!
- Is bb3 dom bb6?




Dominators

- Is bb1 dom bb5? Yes!
- Is bb3 dom bb6?




Dominators

- Is bb1 dom bb5? Yes!
- Is bb3 dom bb6?




Dominators

- Is bb1 dom bb5? Yes!
- Is bb3 dom bb6?




Dominators

- Is bb1 dom bb5? Yes!
- Is bb3 dom bb6? No!



Dominators




Computing Dominators

- A dom b iff
 - $a = b$ or
 - a is the unique immediate predecessor of b or
 - a is a dominator of all immediate predecessor of b
- Algorithm
 - Make dominator set of the entry node has itself
 - Make dominator set of the rest have all the nodes
 - Visit the nodes in any order
 - Make dominator set of the current node intersection of the dominator sets of the predecessor nodes + the current node
 - Repeat until no change


Computing Dominators

- Algorithm
 - Make dominator set of the entry node has itself
 - Make dominator set of the rest have all the nodes
 - Visit the nodes in any order
 - Make dominator set of the current node intersection of the dominator sets of the predecessor nodes + the current node
 - Repeat until no change




Computing Dominators

- Algorithm
 - Make dominator set of the entry node has itself
 - Make dominator set of the rest have all the nodes
 - Visit the nodes in any order
 - Make dominator set of the current node intersection of the dominator sets of the predecessor nodes + the current node
 - Repeat until no change




Computing Dominators

- Algorithm
 - Make dominator set of the entry node has itself
 - Make dominator set of the rest have all the nodes
 - Visit the nodes in any order
 - Make dominator set of the current node intersection of the dominator sets of the predecessor nodes + the current node
 - Repeat until no change




Computing Dominators

- Algorithm
 - Make dominator set of the entry node has itself
 - Make dominator set of the rest have all the nodes
 - Visit the nodes in any order
 - Make dominator set of the current node intersection of the dominator sets of the predecessor nodes + the current node
 - Repeat until no change




Computing Dominators

- Algorithm
 - Make dominator set of the entry node has itself
 - Make dominator set of the rest have all the nodes
 - Visit the nodes in any order
 - Make dominator set of the current node intersection of the dominator sets of the predecessor nodes + the current node
 - Repeat until no change




Computing Dominators

- Algorithm
 - Make dominator set of the entry node has itself
 - Make dominator set of the rest have all the nodes
 - Visit the nodes in any order
 - Make dominator set of the current node intersection of the dominator sets of the predecessor nodes + the current node
 - Repeat until no change



Computing Dominators

- Algorithm
 - Make dominator set of the entry node has itself
 - Make dominator set of the rest have all the nodes
 - Visit the nodes in any order
 - Make dominator set of the current node intersection of the dominator sets of the predecessor nodes + the current node
 - Repeat until no change



-


-

-

-


Computing Dominators

- Algorithm
 - Make dominator set of the entry node has itself
 - Make dominator set of the rest have all the nodes
 - Visit the nodes in any order
 - Make dominator set of the current node intersection of the dominator sets of the predecessor nodes + the current node
 - Repeat until no change




Computing Dominators

- Algorithm
 - Make dominator set of the entry node has itself
 - Make dominator set of the rest have all the nodes
 - Visit the nodes in any order
 - Make dominator set of the current node intersection of the dominator sets of the predecessor nodes + the current node
 - Repeat until no change




Computing Dominators

- Algorithm
 - Make dominator set of the entry node has itself
 - Make dominator set of the rest have all the nodes
 - Visit the nodes in any order
 - Make dominator set of the current node intersection of the dominator sets of the predecessor nodes + the current node
 - Repeat until no change




Computing Dominators

- Algorithm
 - Make dominator set of the entry node has itself
 - Make dominator set of the rest have all the nodes
 - Visit the nodes in any order
 - Make dominator set of the current node intersection of the dominator sets of the predecessor nodes + the current node
 - Repeat until no change




Computing Dominators

- Algorithm
 - Make dominator set of the entry node has itself
 - Make dominator set of the rest have all the nodes
 - Visit the nodes in any order
 - Make dominator set of the current node intersection of the dominator sets of the predecessor nodes + the current node
 - Repeat until no change




Computing Dominators

- Algorithm
 - Make dominator set of the entry node has itself
 - Make dominator set of the rest have all the nodes
 - Visit the nodes in any order
 - Make dominator set of the current node intersection of the dominator sets of the predecessor nodes + the current node
 - Repeat until no change




Computing Dominators

- Algorithm
 - Make dominator set of the entry node has itself
 - Make dominator set of the rest have all the nodes
 - Visit the nodes in any order
 - Make dominator set of the current node intersection of the dominator sets of the predecessor nodes + the current node
 - Repeat until no change




Computing Dominators

- Algorithm
 - Make dominator set of the entry node has itself
 - Make dominator set of the rest have all the nodes
 - Visit the nodes in any order
 - Make dominator set of the current node intersection of the dominator sets of the predecessor nodes + the current node
 - Repeat until no change




Computing Dominators

- Algorithm
 - Make dominator set of the entry node has itself
 - Make dominator set of the rest have all the nodes
 - Visit the nodes in any order
 - Make dominator set of the current node intersection of the dominator sets of the predecessor nodes + the current node
 - Repeat until no change




Computing Dominators

- Algorithm
 - Make dominator set of the entry node has itself
 - Make dominator set of the rest have all the nodes
 - Visit the nodes in any order
 - Make dominator set of the current node intersection of the dominator sets of the predecessor nodes + the current node
 - Repeat until no change




Computing Dominators

- Algorithm
 - Make dominator set of the entry node has itself
 - Make dominator set of the rest have all the nodes
 - Visit the nodes in any order
 - Make dominator set of the current node intersection of the dominator sets of the predecessor nodes + the current node
 - Repeat until no change




Computing Dominators

- Algorithm
 - Make dominator set of the entry node has itself
 - Make dominator set of the rest have all the nodes
 - Visit the nodes in any order
 - Make dominator set of the current node intersection of the dominator sets of the predecessor nodes + the current node
 - Repeat until no change




Computing Dominators

- **Algorithm**
 - Make dominator set of the entry node has itself
 - Make dominator set of the rest have all the nodes
 - Visit the nodes in any order
 - Make dominator set of the current node intersection of the dominator sets of the predecessor nodes + the current node
 - **Repeat until no change**




Computing Dominators

- **Algorithm**
 - Make dominator set of the entry node has itself
 - Make dominator set of the rest have all the nodes
 - Visit the nodes in any order
 - **Make dominator set of the current node intersection of the dominator sets of the predecessor nodes + the current node**
 - Repeat until no change




Computing Dominators

- Algorithm
 - Make dominator set of the entry node has itself
 - Make dominator set of the rest have all the nodes
 - Visit the nodes in any order
 - Make dominator set of the current node intersection of the dominator sets of the predecessor nodes + the current node
 - Repeat until no change




Computing Dominators

- **Algorithm**
 - Make dominator set of the entry node has itself
 - Make dominator set of the rest have all the nodes
 - Visit the nodes in any order
 - **Make dominator set of the current node intersection of the dominator sets of the predecessor nodes + the current node**
 - Repeat until no change




Computing Dominators

- Algorithm
 - Make dominator set of the entry node has itself
 - Make dominator set of the rest have all the nodes
 - Visit the nodes in any order
 - Make dominator set of the current node intersection of the dominator sets of the predecessor nodes + the current node
 - Repeat until no change




Computing Dominators

- Algorithm
 - Make dominator set of the entry node has itself
 - Make dominator set of the rest have all the nodes
 - Visit the nodes in any order
 - Make dominator set of the current node intersection of the dominator sets of the predecessor nodes + the current node
 - Repeat until no change




Computing Dominators

- Algorithm
 - Make dominator set of the entry node has itself
 - Make dominator set of the rest have all the nodes
 - Visit the nodes in any order
 - Make dominator set of the current node intersection of the dominator sets of the predecessor nodes + the current node
 - Repeat until no change



Computing Dominators

- Algorithm
 - Make dominator set of the entry node has itself
 - Make dominator set of the rest have all the nodes
 - Visit the nodes in any order
 - Make dominator set of the current node intersection of the dominator sets of the predecessor nodes + the current node
 - Repeat until no change



Computing Dominators


- What we just witness was an iterative data-flow analysis algorithm in action
 - Initialize all the nodes to a given value
 - Visit nodes in some order
 - Calculate the node's value
 - Repeat until no value changes
- Will talk about this in the coming lectures

What is a Back Edge?

- An edge $(x, y) \in E$ is a back edge
iff $y \text{ dom } x$
 - is node y in the dominator set of node x


What is a Back Edge?

- An edge $(x, y) \in E$ is a back edge
iff $y \text{ dom } x$
 - is node y in the dominator set of node x



What is a Back Edge?

- An edge $(x, y) \in E$ is a back edge
iff $y \text{ dom } x$
 - is node y in the dominator set of node x




Outline

- Overview of Optimizations
- Control-Flow Analysis
- Dominators
- Graph Traversal
- Reducible Graphs
- Interval Analysis
- Few Definitions

Traversing the CFG

- Depth-First Traversal
 - Visit all the descendants of a node before visiting any siblings
- Depth-first spanning tree
 - a set of edges corresponding to a depth-first visitation of CFG

Depth-First Spanning Tree



Preorder and Postorder

- In preorder traversal, each node is processed before its descendants in the depth-first tree
- In postorder traversal, each node is processed after its descendants in the depth-first tree


Outline

- Overview of Optimizations
- Control-Flow Analysis
- Dominators
- Graph Traversal
- Reducible Graphs
- Interval Analysis
- Few Definitions


Reducible CFGs





- Reducibility formalizes well structuredness of a program
- A graph is reducible iff repeated application of the following two actions yields a graph with only one node
 - replace self loop by a single node
 - Replace a sequence of nodes such that all the incoming edges are to the first node and all the outgoing edges are to the last node





Reducible CFGs




Reducible CFGs








Irreducible graphs



Irreducible graphs



Outline

- Overview of Optimizations
- Control-Flow Analysis
- Dominators
- Graph Traversal
- Reducible Graphs
- Interval Analysis
- Few Definitions


Approaches of Control-Flow Analysis

- Iterative Analysis
 - Use a CFG
 - Propagate values
 - Iterate until no change
- Interval Based Analysis
 - Use a reducible CFG
 - Calculate in hierarchical graphs
 - No iterations (faster)


Interval Based Analysis

- If a node does not include a graph:
 - calculate value
- If a node includes a graph
 - Calculate values of the nodes in that graph
 - Propagate values (no back edges \Rightarrow no iteration)
 - Use entry (or exit) value as the value of the enclosing node


Interval Analysis







Interval Analysis



Interval Analysis






Outline

- Overview of Optimizations
- Control-Flow Analysis
- Dominators
- Graph Traversal
- Reducible Graphs
- Interval Analysis
- Few Definitions


Dominators

- Node **x dominates** node **y** ($x \text{ dom } y$) if every possible execution path from entry to node **y** includes node **x**



Dominators


- Node **x strictly dominates** node **y** ($x \text{ sdom } y$) if
 - $x \text{ dom } y$
 - $x \neq y$



Dominators


- Node **x immediately dominates** node **y** ($x \text{ idom } y$) if

- $x \text{ dom } y$
- $x \neq y$
- $\exists c \in N$ such that $c \neq x$ and $c \neq y$ and $x \text{ dom } c$ and $c \text{ dom } y$




Dominators


- Node x **post dominates** node y ($x \text{ pdom } y$) if every possible execution path from node x to the exit node includes node y




Dominators (dom)





Strictly Dominates (sdom)



Immediately Dominates (idom)





Summary

- Overview of Optimizations
- Control-Flow Analysis
- Dominators
- Graph Traversal
- Reducible Graphs
- Interval Analysis
- Few Definitions