

Register Allocation


Global Register Allocation
Webs and Graph Coloring
Node Splitting and Other Transformations

Copyright 2009, Pedro C. Diniz, all rights reserved.
Students enrolled in the Compilers class at Instituto Superior Técnico (IST/UTL) have explicit permission to make copies of these materials for their personal use.

What a Smart Allocator Needs to Do

- Determine ranges for each variable can benefit from using a register (webs)
- Determine which of these ranges overlap (interference)
- Find the benefit of keeping each web in a register (spill cost)
- Decide which webs gets a register (allocation)
- Split webs if needed (spilling and splitting)
- Assign hard registers to webs (assignment)
- Generate code including spills (code gen)

Global Register Allocation




This is an assignment problem, not an allocation problem !

What's harder across multiple blocks?

- Could replace a load with a move
- Good assignment would obviate the move
- Must build a control-flow graph to understand inter-block flow
- Can spend an inordinate amount of time adjusting the allocation

Global Register Allocation



What if one block has x in a register, but the other does not?

A more complex scenario

- Block with multiple predecessors in the control-flow graph
- Must get the "right" values in the "right" registers in each predecessor
- In a loop, a block can be its own predecessor

This adds tremendous complications



Outline

- What is Register allocation and Its Importance
- Simple Register Allocators
- Webs
- Interference Graphs
- Graph Coloring
- Splitting
- More Optimizations




Webs


- What needs to be Memorized is the Value
 - All definitions that reach a use are in the same web
 - All uses that use the value defined are in the same web
 - Divide the Variable into Live Ranges
- Implementation: use DU chains
 - A du-chain connects a definition to all uses reached by the definition
 - A web combines du-chains containing a common use









Example



Example







Webs (continued)


- In two Webs of the same Variable:
 - No use in one web will ever use a value defined by the other web
 - Thus, no value need to be carried between webs
 - Each web can be treated independently as values are independent
- Web is used as the unit of Register Allocation
 - If a web is allocated to a register, all the uses and definitions within that web don't need to load and store from memory
 - Solves the issue of cross Basic Block register assignment
 - Different webs may be assigned to different registers or one to register and one to memory

Outline


- What is Register Allocation
- A Simple Register Allocator
- Webs
- Interference Graphs
- Graph Coloring
- Splitting
- More Optimizations

Interference


- Two webs interfere if their live ranges overlap in time
 - What does time Mean, more precisely?
 - There exists an instruction common to both ranges where
 - They variable values of webs are operands of the instruction
 - If there is a single instruction in the overlap
 - and the variable for the web that ends at that instruction is an operands and
 - the variable for the web that starts at the instruction is the destination of the instruction
 - then the webs do not interfere
- Non-interfering webs can be assigned to the same register



Example




Example




Example

Webs s1 and s2 interfere
 Webs s2 and s3 interfere




Interference Graph

- Representation of webs and their interference
 - Nodes are the webs
 - An edge exists between two nodes if they interfere




Example



Example

Webs s1 and s2 interfere
 Webs s2 and s3 interfere




Outline

- What is Register Allocation
- A Simple Register Allocator
- Webs
- Interference Graphs
- Graph Coloring
- Splitting
- More Optimizations



Register Allocation Using Graph Coloring

- Each Web is Allocated a Register
 - each node gets a register (color)
- If two webs interfere they cannot use the same register
 - if two nodes have an edge between them, they cannot have the same color




Graph Coloring


- What is the minimum number of colors that takes to color the nodes of the graph such that any nodes connected with an edge does not have the same color?
- Classic Problem in Graph Theory



Graph Coloring Example




Graph Coloring Example




- **1 Color**

Graph Coloring Example




Graph Coloring Example




- 2 Colors

Graph Coloring Example




Graph Coloring Example




- Still 2 Colors

Graph Coloring Example



Graph Coloring Example



- **3 Colors**

Heuristics for Register Coloring


- Coloring a graph with N colors
- If $\text{degree} < N$ ($\text{degree of a node} = \# \text{ of edges}$)
 - Node can always be colored
 - After coloring the rest of the nodes, you'll have at least one color left to color the current node
- If $\text{degree} \geq N$
 - still may be colorable with N colors
 - exact solution is NP complete

Heuristics for Register Coloring

- Remove nodes that have $\text{degree} < N$
 - push the removed nodes onto a stack
- If all the nodes have $\text{degree} \geq N$
 - Find a node to spill (no color for that node)
 - Remove that node
- When empty, start the coloring step
 - pop a node from stack back
 - Assign it a color that is different from its connected nodes (since $\text{degree} < N$, a color should exist)


Coloring Example

$N = 3$




Coloring Example

$N = 3$



Coloring Example


$N = 3$







s4





Coloring Example





$N = 3$











s2
s4


















Another Coloring Example

$N = 3$




Outline





- What is Register Allocation
- A simple register Allocator
- Webs
- Interference Graphs
- Graph coloring
- Splitting
- More Optimizations





Spilling and Splitting



- When the graph is non-N-colorable
- Select a Web to Spill
 - Find the least costly Web to Spill
 - Use and Defs of that web are read and writes to memory
- Split the web
 - Split a web into multiple webs so that there will be less interference in the interference graph making it N-colorable
 - Spill the value to memory and load it back at the points where the web is split

Splitting Example









- Splitting**
- Identify a Program Point where the Graph is not R-colorable (point where # of webs > N)
 - Pick a web that is not used for the largest enclosing block around that point of the program
 - Split that web
 - Redo the interference graph
 - Try to re-color the graph

- Cost and benefit of splitting**
- Cost of splitting a node
 - Proportion to number of times splitted edge has to be crossed dynamically
 - Estimate by its loop nesting
 - Benefit
 - Increase colorability of the nodes the splitted web interferes with
 - Can approximate by its degree in the interference graph
 - Greedy heuristic
 - pick the live-range with the highest benefit-to-cost ratio to spill



Outline

- Overview of procedure optimizations
- What is register allocation
- A simple register allocator
- Webs
- Interference Graphs
- Graph coloring
- Splitting
- More Optimizations



More Transformations

- Register Coalescing
- Register Targeting (pre-coloring)
- Pre-Splitting of Webs
- Inter-procedural Register Allocation



Register Coalescing

- Find register copy instructions $s_j = s_i$
- If s_j and s_i do not interfere, combine their webs
- Pros
 - Similar to copy propagation
 - Reduce the number of instructions
- Cons
 - May increase the degree of the combined node
 - A colorable graph may become non-colorable



Register Targeting (pre-coloring)

- Some Variables need to be in Special Registers at Specific Points in the Execution
 - first 4 arguments to a function
 - return value
- Pre-color those webs and bind them to the appropriate register
- Will eliminate unnecessary copy instructions


Pre-splitting of the webs

- Some live ranges have very large “dead” regions.
 - Large region where the variable is unused
- Break-up the live ranges
 - need to pay a small cost in spilling
 - but the graph will be very easy to color
- Can find strategic locations to break-up
 - at a call site (need to spill anyway)
 - around a large loop nest (reserve registers for values used in the loop)

Inter-Procedural Register Allocation

- Saving Registers across Procedure boundaries is expensive
 - especially for programs with many small functions
- Calling convention is too general and inefficient
- Customize calling convention per function by doing inter-procedural register allocation

Chaitin-Briggs Allocator



Summary

- Register Allocation and Assignment
 - Very Important Transformations and Optimization
 - In General Hard Problem (NP-Complete)
- Many Approaches
 - Local Methods: Top-Down and Bottom-Up
 - Global Methods: Graph Coloring
 - Webs
 - Interference Graphs
 - Coloring
 - Other Transformations