

Supplementary Material

Automatic Detection of Morphological Anomalies in Altiplano Alpacas Using a Computer Vision System: A Curated Dataset, Compact Detector, and Ocular Anomaly Classification Feasibility Study

Vilca-Solórzano, R.A.; Yana-Yucra, D.M.; Ccopa-Acero, C.D.; Alemán-Gonzales, L.

These figures provide detailed diagnostics for the ocular-anomaly-classifier feasibility study (Section 3.2 of the main text). Because the leakage-free classifier performs at chance ($\text{AUC-ROC} = 0.506$, 95% CI $[0.366, 0.645]$), they are reported here as supporting evidence of the negative result rather than in the main text.




Figure S1: EfficientNet-B2 ocular anomaly classifier: leakage-free test-set metrics ($n = 70$, group-aware split). AUC-ROC = 0.506 sits on the chance line (dashed), with Average Precision = 0.195, F1 (anomaly) = 0.065 and Accuracy = 0.586.




Figure S2: ROC and precision–recall curves for the classifier under the leakage-free protocol (bootstrap $B = 1000$, seed = 42). The ROC lies on the chance diagonal ($\text{AUC} = 0.506$); the PR curve tracks the prevalence baseline ($\text{AP} = 0.195$).




Figure S3: Confusion matrices for the classifier: raw counts (left, $n = 70$) and row-normalised (right). Of 14 true anomalies only 1 is correctly identified, consistent with chance-level discrimination.