

## A. Comet Equation

It's a linear advection-diffusion PDE, featuring 2 parameters, each with a clear physical interpretation:

$$\begin{cases} -\mu\Delta u + 10(\cos\theta, \sin\theta) \cdot \nabla u = 10e^{-50\|\underline{x}-\underline{x}_0\|_2} & \underline{x} \in \Omega = [0, 1]^2 \\ u = 0 & \underline{x} \in \partial\Omega \end{cases}$$

- ▶  $\mu \in (0, \infty)$ : diffusion parameter
- ▶  $\theta \in (0, 2\pi)$ : angle of advection term
- ▶  $\underline{x}_0 = (0.5, 0.5)$ : centre of the forcing bump

Data is produced through simulation with fixed and known values of parameters and error scale:

$$\mu^* = 2$$

$$\theta^* = \pi$$

$$\tau^* = 10^{-4}$$


# A1. Comet with Different Grids

$u(\underline{\theta}, \underline{x})$  is approximated through Finite Element Method (FEM). The mesh refinement affects the accuracy of the numerical solution.

In MLDA, coarse and fine model differ for the mesh refinement.

Comparison of:

- ▶ Metropolis: 32x32 elements
- ▶ MLDA
  - ▶ Coarse model: 16x16 elements
  - ▶ Fine model: 32x32 elements




# A1. Comet with Different Grids

$u(\underline{\theta}, \underline{x})$  is approximated through Finite Element Method (FEM). The mesh refinement affects the accuracy of the numerical solution.

In MLDA, coarse and fine model differ for the mesh refinement.

Comparison of:

- ▶ Metropolis: 32x32 elements
- ▶ MLDA
  - ▶ Coarse model: 16x16 elements
  - ▶ Fine model: 32x32 elements





## A2. Comet with Surrogate Model

Metropolis overcomes MLDA evidently. Indeed, coarse solution in MLDA is too time consuming.

Hence, we place at coarse level a surrogate model, implemented through a Neural Network:

$$u_{\text{NN}} : (\mu, \theta, x, y) \mapsto u_{\text{NN}}(\mu, \theta, x, y)$$



$u_{\text{NN}}$  is trained on a dataset of 900 PDE solutions (each corresponding to a different  $(\mu_i, \theta_i)$ ), evaluated on a grid of  $\Omega$

+ Long training time


- Small execution time

## A2. Comet with Surrogate Model

Within this framework, we investigated the performances of Metropolis, DEMetropolisZ and MLDA for different:

- ▶ frequencies of subsampling (nsubs) of proposed samples from coarse level to fine level in MLDA
- ▶ grids of physical points where data is available
- ▶ choices of the priors for  $(\mu, \theta)$

Comparison of Metropolis, DEMetropolisZ and MLDA (nsubs = 5, 20):



## A2. Comet with Surrogate Model

Comparison of Metropolis, DEMetropolisZ and MLDA (nsubs = 5, 20):

