

Harmonomino: Tetris Agent Optimization

Using Harmony Search & Cross-Entropy Methods

Ezra Cerpac · Andrea Tomatis

Faculty of Electrical Engineering and Computer Science


2026-02-08

Background & Motivation

- Tetris is a well-studied AI benchmark with NP-hard piece placement
- Hand-tuning evaluation weights is infeasible for 16 features
- Metaheuristic search offers a practical alternative to exhaustive optimization

- Tetris is a well-studied AI benchmark with NP-hard piece placement
- Hand-tuning evaluation weights is infeasible for 16 features
- Metaheuristic search offers a practical alternative to exhaustive optimization
- **Goal:** automatically discover weight vectors that maximize rows cleared

- **RQ1** — How effective is Harmony Search (HSA) at optimizing Tetris agent weights?
- **RQ2** — How does Cross-Entropy Search (CES) compare to HSA?
- **RQ3** — Do the optimized weights converge to stable values?



Board → 16 evaluation functions → weighted sum → best placement


Approach & Results

Harmony Search (HSA)

- Population of 5 weight vectors
- 100 improvisation rounds
- HMCR: 0.95, PAR: 0.99
- Bandwidth: 0.1

Cross-Entropy Search (CES)

- 50 candidates per generation
- Top 10 elite selection
- 100 generations
- Gaussian sampling + shrinkage



HSA


Mean: 275.737 rows


Median: 210.000 rows

CES

Mean: 416.633 rows




Median: 351.000 rows





Most stable: w_{12} (Blocks Above Highest), w_8 (Weighted Blocks), and w_9 (Row Transitions)

High variance:



Conclusion

Contributions

- Both HSA and CES successfully optimize Tetris agent weights
- 16 feature evaluation covers pile, hole, well, row, and block metrics
- Subset of weights converge to stable values across runs
- Automated pipeline enables reproducible experiments

Limitations

- Single-piece lookahead only
- Fixed game length caps observable performance
- No T-spin or hold-piece strategies

- Multi-piece lookahead and hold-piece integration
- Hybrid algorithms combining HSA exploration with CES exploitation
- Neural-network evaluation functions trained on optimized weights
- Transfer learning across board sizes and rule variants

Thank You!

Ezra Cerpac · Andrea Tomatis

Scientific Computing
Technische Universität Berlin

Questions?