

DDoS attack: DNS Reflection and Amplification

Andreoli C. - Ligari D. - Alberti A. - Scardovi M. - Intini K.

University of Pavia, Italy

Department of Computer Engineering - Data Science

Abstract

[1] [2] [3] [4] [5] [6] [7] [8] [9] [10]

1 DNS based DDoS attacks

The DNS service is a critical part of the Internet infrastructure. Almost every communication exploits the DNS service, and attacking it could lead a significant number of networked applications to run out of service. The DNS service has been designed to provide fast responses and is less oriented towards security, which makes it vulnerable to different types of attacks. According to a recent Cloudflare's report^[6] the most used vector in DDoS is the DNS. The types of attacks involving DNS are of three main types: *DNS query flood*, *TCP flood*, *DNS reflection and amplification*, and *DNS water torture*.

DNS query flood

This is a direct attack aimed at consuming the server resources until run it out of service. The attacker sends a large number of DNS queries to the target recursive DNS server, leveraging a zombie devices army (botnet). The requests are structured in a way that the server has not the record cached and it is forced to perform recursive queries to provide the responses. It is easier to perform this type of attack on smaller DNS servers that may have limited resources to handle a large number of queries.

TCP flood

This is another type of attack aimed at consuming the server resources. These latter are consumed by the attacker sending lots of TCP connection requests without closing them. The server is forced to allocate resources to handle the TCP connections and, when the numbers get larger it may run out of resources.

DNS water torture

This is a type of indirect attack aimed at consuming the resources of a target authoritative DNS server. The attacker sends a huge number of queries about properly constructed hostnames. These are made up by two parts: the domain whose authoritative server is the target, and a random string such that the FQDN cannot exist. That way the recursive NS starts its search until it reaches the authoritative server. This latter notices the non-existence of the FQDN and sends NXDOMAIN response. All the queries travel until the authoritative server, which is forced to handle all of them until it is overwhelmed.

DNS reflection and amplification

This is an indirect attack aimed at consuming the target network bandwidth. It start with the spoofing of the target's IP address, then lots of queries are sent to the DNS server using as the source address the spoofed IP address. This latter will receives the responses from the DNS server (reflection). The queries are structured in a way that the responses are larger in size (amplification). That way the target's bandwidth is fulfilled, with the

attacker having used just a small quantity of its resources. The effectiveness of this attack is given by the amplification factor (AF), measured as the ratio between the size of the response and the size of the query. An easy but effective choice for the attacker is to perform a type ANY which provides a large AF.

Since according to the already cited report^[6] the most common type of attack is the DNS reflection and amplification, in this project we focus on this type of attack.

2 Methodologies and experimental setup

To ensure the success of the project, it is essential to establish a clear methodology and employ a well-defined set of tools. This section aims to provide a detailed explanation of the methodologies utilized to accomplish the project's objectives.

The selected methodologies encompass a systematic approach that allows for the accurate replication of a DDoS attack while maintaining ethical considerations and minimizing the potential impact on live networks. These methodologies were carefully chosen to ensure the reliability and validity of the experimental results. The methodological approach used is the following:

Why

The objective of this study is to assess the impact of a DoS attack, exploiting the DNS protocol and monitor the reachability of the targeted device and other network nodes. By simulating realistic attack scenarios, this study aims to understand the vulnerabilities within the DNS protocol, evaluate network resilience, and identify potential countermeasures.

Which/Who

The chosen target for the DDoS attack is a laptop (HP ENVY x360), which acts as a host for a DNS server running BIND9. Two

laptops, specifically a MacBook Pro 14 and another device (to be specified)!!!!!!!!!!!!!!!, are utilized as vantage points to initiate the attack.

What

The chosen metrics include measuring the response time for each ICMP or DNS message sent, accounting for potential timeouts. Furthermore, the CPU and memory utilization of the DNS server were also monitored during the simulation.

Where

The vantage point is a MacBook Air inside the network and passive to the attack.

To ensure the security and stability of public networks and devices, the DDoS attack simulations were conducted within a local area network (LAN) environment.

3 Tools used

Ping

Ping is a network utility tool used to test the connectivity between two networked devices. It sends a small packet of data to a specific IP address or hostname and measures the time it takes for that packet to be received and returned. The result shows the round trip time (RTT), as well as the number of packets sent and received, and any packet loss that may have occurred.

While it is a useful tool for testing network connectivity, it has some limitations, it uses the ICMP protocol to send and receive packets, which may not always be allowed by network firewalls or routers, and it does not support different protocols like TCP or UDP. This means that if a network is configured to block ICMP traffic, the ping command may not work. Moreover ping provides only basic information about network connectivity, it does not provide information about bandwidth or the structure of the network.

Dig

The `dig` command (short for "domain information groper") is a popular network administration tool used to perform DNS queries. It allows users to perform DNS lookups to check DNS records and obtain information about DNS configurations. It is a versatile tool that allows users to specify different query types, such as A, AAAA, MX, TXT, and others. It can also be used to perform reverse DNS queries, where an IP address is used to retrieve the corresponding domain name. In addition to provide detailed DNS query results, the `dig` command can also be used to troubleshoot DNS issues, such as misconfigured DNS servers, slow DNS resolution times, or DNS cache issues.

Top

The `top` command provides real-time monitoring of system resources, such as CPU usage, memory utilization, running processes, and more. When executed, the `top` command displays an interactive, dynamic table that continually updates, allowing users to view the

current state of their system and identify any processes consuming excessive resources. The `top` command also provides options to manipulate the displayed information and perform actions on running processes, such as terminating or changing their priority.

Wireshark

Wireshark is a open-source network protocol analyzer. It is designed to capture, analyze, and display network traffic in real-time. Wireshark allows users to inspect and interpret the data packets transmitted over a network, providing detailed information about the communication between different devices.

In addition to passive packet capturing, Wireshark offers powerful filtering and search capabilities, allowing users to focus on specific types of traffic or specific packets of interest. It also provides features for advanced analysis, such as the ability to reconstruct and view streams of data, perform statistical analysis, and even export captured data for further investigation or reporting

References

- [1] Admir Dizdar. DNS Amplification Attack: How they Work, Detection and Mitigation, October 2021. URL <https://brightsec.com/blog/dns-amplification-attack/>.
- [2] Lei Fang, Hongbin Wu, Kexiang Qian, Wenhui Wang, and Longxi Han. A comprehensive analysis of ddos attacks based on dns. *Journal of Physics: Conference Series*, 2024:012027, 09 2021. doi: 10.1088/1742-6596/2024/1/012027.
- [3] Li Wei-min, Chen Lu-ying, and Lei Zhen-ming. Alleviating the impact of dns ddos attacks. *2010 Second International Conference on Networks Security, Wireless Communications and Trusted Computing*, 1:240–243, 2010. doi: 10.1109/NSWCTC.2010.63.
- [4] Rebekah Taylor. Four major DNS attack types and how to mitigate them, August 2021. URL <https://bluecatnetworks.com/blog/four-major-dns-attack-types-and-how-to-mitigate-them/>.
- [5] Admir Dizdar. 5 dns attack types and how to prevent them, May 2022. URL <https://brightsec.com/blog/dns-attack/>.
- [6] Pacheco Yoachimik. Ddos threat report for 2023 q1_2023, Apr 2023. URL <http://blog.cloudflare.com/ddos-threat-report-2023-q1/>.
- [7] G. Usha Devi. Detection of ddos attack using optimized hop count filtering technique. *Indian Journal of Science and Technology*, 8(1):1–6, Jan 2015. ISSN 09746846, 09745645. doi: 10.17485/ijst/2015/v8i26/83981.
- [8] Wouter de Vries, Ricardo Schmidt, and Aiko Pras. Anycast and its potential for ddos mitigation. *ResearchGate*, Jun 2016. doi: 10.1007/978-3-319-39814-3_16.
- [9] Irom Meitei, Johnson kh, and Tanmay De. Detection of ddos dns amplification attack using classification algorithm, 08 2016.
- [10] Jared Mathews, Prosenjit Chatterjee, Shankar Banik, and Cory Nance. A deep learning approach to create dns amplification attacks. In *2022 4th International Conference on Management Science and Industrial Engineering (MSIE)*, page 429–435, Apr 2022. doi: 10.1145/3535782.3535838. URL <http://arxiv.org/abs/2206.14346>. arXiv:2206.14346 [cs].