

Discovery: Introduction Mechanisms

Kunihiko Toumura

October 20, 2020


Outline

- Overview
- Current described mechanisms:
 - Direct
 - Well-known URI
 - DNS-based service discovery
 - CoRE Link Format and Core Resource Directory
 - Decentralized Identifier (DID) documents
- Discussions
 - Security/Privacy
 - Any other introduction mechanisms?

Overview

- Introduction Mechanism:
 - Find an URL which points to Thing Description of Thing or Thing Directory.
 - Consumer may issue HTTP GET request to the URL to retrieve a TD.
 - Accessing to TD SHOULD be authenticated
 - Utilize existing discovery mechanisms. Avoid inventing mechanisms.
 - TD's Content-type MUST be: **application/td+json**
 - "@type" of Directory TD MUST be **"Directory"**
 - Type for Thing TD is **"Thing"**, but not mandatory.

Introduction Mechanisms



Direct

- Any mechanism that result in a single URL.
 - Bluetooth beacons, Matrix barcodes, and written URL.
- A GET on all such URLs **MUST** result in a TD.



QR code that contains an URL
 ‘http://kotorpi.local:1880/.well-known/wot-thing-description’

Well-known URI


- RFC8615: Well-Known Uniform Resource Identifiers (URIs)
- Thing or Directory Service can host their Thing Description as a site-wide metadata
- “wot-thing-description” (tentative) for URL suffix
 - Example 1: a Consumer heuristically get a FQDN of some site: tdd.example.com, then issue HTTP request
`GET https://tdd.example.com/.well-known/wot-thing-description`
to try to retrieve a Thing Description
 - Example 2: Broadcast/multicasting CoAP request
`GET /.well-known/wot-thing-description`

DNS-based service discovery (1/2)

- DNS-based Service Discovery (RFC6763)
- Multicast DNS (RFC6762)
- Use (multicast) DNS query to discover Things or Directory Services
- DNS-SD Service Instance Name:
 - *<Instance>.<Service>.<Domain>*
- *<Service>* MUST be:
 - Thing: *_wot._tcp* (HTTP or HTTPS) or *_wot._udp* (CoAP)
 - Directory Service: *_directory._sub._wot._tcp* or *_directory._sub._wot._udp*
- When Consumer resolves above domain name, it receives following TXT records:
 - *td*: Absolute pathname of the Thing Description of the Things or Directory Service
 - *type*: Type of the Things Description, i.e. *Thing* or *Directory*.

DNS-based service discovery (2/2)

- Example sequence of Directory Discovery by mDNS



CoRE Resource Directory (CoRE-RD)

- draft-ietf-core-resource-directory-25
- We can use CoRE-RD as an introduction mechanism of Thing or Directory Service.
- Link for a Thing Description is stored as a CoRE Link (RFC6690).
- Endpoint type(et):
 - TD for Thing: **wot.thing**
 - TD for Directory Service: **wot.directory**





Figure 3: ER Model of the content of the RD

Decentralized Identifier (DID)

- DID can be used for pointing a Thing Description of Thing or Thing Directory.
- DID is resolved to DID documents, by DID resolver.
- DID document can contain a Service Endpoint which point to Thing or Thing Directory



```
{
  ...
  "service": [{
    "id": "did:example:wotdiscoveryexample#td",
    "type": "WotThingDescription",
    "serviceEndpoint": "https://wot.example.com/td"
  }]
}
```

Example Service Endpoint description in DID document

Discussions

- Security/Privacy Considerations
 - Some introduction mechanisms should be used in trusted environment...
 - Direct, well-known URL and DNS-SD are not protected from unauthorized access.
 - We should use them in a private network which is protected by authentication (WPA, 802.1x, VPN, etc.), or in a space that is protected by physical security.
 - ... and/or TD should be protected by authentication
 - HTTP basic/digest auth, OAuth, etc.
- Are there any other mechanisms that should be included in the specification?