



Practical Network Defense

Master's degree in Cybersecurity 2024-25

OpenVPN activity

Angelo Spognardi
spognardi@di.uniroma1.it

Dipartimento di Informatica
Sapienza Università di Roma



Aim of the lab

- 1) Highlight the tunneling concept
- 2) Use openvpn to make the boundary to be the VPN tunnel end-point
 - The kali/host will have the access to the **internal** subnet passing through an encrypted channel
 - Two scenarios
 - Static key configuration
 - Dynamic key configuration
 - Using certificates



To do the activities

- We will use Kathará (formerly known as netkit)
 - A container-based framework for experimenting computer networking:
<http://www.kathara.org/>
- A virtual machine is made ready for you
 - https://drive.google.com/file/d/1W6JQzWVyH5_LKLD20R6XH1ugPDP5LWP5/view?usp=sharing
- For not-Cybersecurity students, please have a look at the Network Infrastructure Lab material
 - http://stud.netgroup.uniroma2.it/~marcos/network_infrastructures/current/cyber/
 - Instructions are for netkit, we will use kathara



The kathara VM


- It should work in both Virtualbox and VMware
- It should work in Linux, Windows and MacOS
- There are some alias (shortcuts) prepared for you
 - Check with **alias**
- All the exercises can be found in the git repository:
 - <https://github.com/vitome/pnd-labs.git>
- You can move in the directory and run lstart
 - **NOTE:** launch docker first or the first lstart attempt can (...will...) fail



Lab activity: ex1

pnd-labs/lab5/ex1

- You have to setup the IPv4 addressing
 - Follow README instructions






Fundamentals: simple tunneling

- Universal tun/tap drive
 - Creates a virtual interface that encapsulates network traffic
- Any application can use that interface without any need to change its code
- Usually identified with names tun* or tap*
- tun* encapsulate IP layer
- tap* encapsulate Ethernet layer
- Reference:
 - <http://man7.org/linux/man-pages/man8/ip-tunnel.8.html>
 - https://developers.redhat.com/blog/2019/05/17/an-introduction-to-linux-virtual-interfaces-tunnels#ipip_tunnel

Universal tun driver (L3)





Create a tunnel (r1-r2)

- Let's check our local interfaces

`ip link`

- Create a new tun virtual interface (use root user)

`ip tunnel add tun0 mode ipip remote <ipaddressR> local <ipaddressL>`

- ipaddressR is the IP address of the remote machine
- ipaddressL is the IP address of our local machine
 - alternatively use the `ip link add name tun0 type ipip ...` command

- Let's check again our local interfaces

`ip link`

- Let's activate the new interface

`ip addr add 10.0.0.1/30 dev tun0`
`ip link set tun0 up`

- the IP address of the remote machine **MUST be different!!**

Analyze the traffic

- Open wireshark to sniff the traffic
 - Use tcpdump to save the traffic from different observation points
- Generate some traffic in the tunnel
 - `ping 10.0.0.2`
- What do you notice?
 - See the difference between tun0 and the eth0
- Can you see the basic principle of a VPN?



Use the tunnel to connect lanA and lanB


- You have to setup the routes
- Who will r1 forward the packets for lanB?
 - In order to use the tunnel?
- Properly set up the routing tables
- Check what happens when pc1 tries to reach pc2
 - Use wireshark in r1 or r2
 - You can join the wan network



Lab activity: ex2

pnd-labs/lab5/ex2

- Same topology than ex1
- Must run with the option – **privileged**
 - Use `lstart.sh` script
- You have to setup the IPv4 addressing
 - Follow README instructions
- Check that openvpn is installed in both r1 and r2



OpenVPN

- Open-source software to realize VPN, namely encrypted tunnels
- Usually uses UDP with one single port
 - Can also use TCP
- Can be used also through firewalls or NAT
- OpenSSL based
- Multiple modes
 - Static: symmetric shared key
 - Dynamic: Public Key Infrastructure



<https://community.openvpn.net/openvpn/wiki/SecurityOverview>




OpenVPN static key

- The endpoints share a key generated with `openvpn` command
- Very easy to configure
- No CA or certificates
 - No TLS!
- NOTE: requires a secure channel to exchange the keys
- The key never changes: no forward secrecy

OpenVPN static key: keys

- Uses 4 independent keys:
 - K_{AB} (to encrypt $A \rightarrow B$)
 - $HMAC_{AB}$ (to authenticate $A \rightarrow B$)
 - K_{BA} (to encrypt $B \rightarrow A$)
 - $HMAC_{BA}$ (to authenticate $B \rightarrow A$)
- This is required to reduce the risks of Replay and DoS attacks

OpenVPN static key: traffic exchange





Standard crypto

Blowfish

Block cipher: **64-bit block**

Key length: **32 bits to 448 bits**

Designed by **Bruce Schneier**

Much **faster** than DES and IDEA
Unpatented and royalty-free

No license required

Free **source code available**

SHA-1

Published: **1995**

Designed by: **NSA**

Output length: **160 bit**

- OpenVPN standard
- 128 bit keys
- CBC (Cipher-block Chaining)
- You can choose the default with the cipher option in the configuration file
- Many others available
 - `openvpn --show-ciphers`
- OpenVPN standard
- Uses a different key than the encryption one



OpenVPN static key: key generation

- Generate the shared key on one side of the tunnel (say r1)
 - `openvpn --genkey secret secret.key`
- Exchange the secret.key file with scp
- OR, if you don't send it with scp:
 - Encrypt the key (because we'll use an insecure channel)
 - `openssl enc -aes-128-cbc -e -a -in secret.key -out secret.key.enc`
 - Exchange the shared key
 - Prepare to receive the shared key on the other side of the tunnel (say r2):
 - `r2# nc -l -p 9000 > secret.key.enc`
 - Send the shared key
 - `r1# nc <r2IPAddress> 9000 < secret.key.enc`
 - Decrypt the key on the other side of the channel
 - `openssl enc -aes-128-cbc -d -a -in secret.key.enc -out secret.key`

OpenVPN static key: file conf

r1

```
port 1194
proto udp
dev tun
secret secret.key
cipher AES-256-CBC
ifconfig 10.10.10.1 10.10.10.2
```

r2

```
remote <r1IPAddress>
port 1194
proto udp
dev tun
secret secret.key
cipher AES-256-CBC
ifconfig 10.10.10.2 10.10.10.1
```

- r1 plays the role of the passive actor → waits for connections
- Create a new file r1.conf/r2.conf and use the above conf
 - You can check the path `/usr/share/doc/openvpn/examples/`



OpenVPN static key: file conf

- Start openvpn
 - `r1# openvpn --config r1.conf`
 - `r2# openvpn --config r2.conf`
- Check the connectivity on the new interfaces and analyze the traffic with wireshark
- To give visibility of another subnet (i.e., the **lanA** network), you can use the **route** option
 - `route <network> <netmask> <host>`
 - Network and netmask in dotted decimal
 - Host is the next-hop for reaching the network



OpenVPN dynamic key

- Uses SSL/TLS and certificates for authentication and key exchange
- Certificates for both endpoints
- If the certificates are valid
 - HMAC and encryption keys are dynamically generated with OpenSSL
 - This assures Forward Secrecy
- Both parties contribute to key generation





OpenVPN dynamic key: cert generation

- We should have a certification authority issuing the certs
 - This should be done using the → [easy-rsa scripts](#), that can be found in the `/usr/share/easy-rsa` directory
 - Alternatively, we can use the ones provided by openvpn for test purposes in `/usr/share/doc/openvpn/examples/sample-keys`
- Needed ingredients/files
 - {client,server}.crt : CA signed public key
 - {client,server}.key: CA signed private key
 - Certificates are issued after signing the requests (client!=server)
 - dh.pem: Diffie-Hellman key exchange parameters
 - ta.key: for TLS HMAC authentication (optional)



OpenVPN dynamic key: file conf

- Start from the sample configuration files in the directory
`/usr/share/doc/openvpn/examples/sample-config-files/`
- Server (VPN gateway):
 - `.../sample-config-files/server.conf`
- client:
 - `.../sample-config-files/client.conf`



OpenVPN dynamic key: run

- Start openvpn
- Server:
 - `openvpn --config server.conf`
- Client:
 - `openvpn --config client.conf`
- Check the connectivity on the new interfaces and analyze the traffic with wireshark

That's all for today

- Questions?
- Resources:
 - <https://openvpn.net/community-resources/how-to/>
 - <https://wiki.wireshark.org/OpenVPN>
 - Chapter 24 textbook
 - Virtual private networking, Gilbert Held, Wiley ed.
 - Guide to IPsec VPNs, NIST800-77
 - Guide to SSL VPNs, NIST-SP800-113
 - http://www.tcpipguide.com/free/t_IPSecurityIPSecProtocols.htm