

Quantum Computing

Experimenting with Qiskit

Paolo Zuliani

Dipartimento di Informatica
Università di Roma “La Sapienza”, Rome, Italy



SAPIENZA
UNIVERSITÀ DI ROMA

Agenda

Building and running the EPR circuit with Qiskit's Sampler class on:


- ① the state vector simulator
- ② the 'fake' backend simulator
- ③ a genuine quantum computer

Agenda

Building and running the EPR circuit with Qiskit's Sampler class on:

- 1 the state vector simulator
- 2 the 'fake' backend simulator
- 3 a genuine quantum computer

The EPR circuit that produces the state $\frac{1}{\sqrt{2}}(|01\rangle + |10\rangle)$ is:



State Vector Simulator

- It simulates **exactly** any unitary gate
- Measurement outcomes are sampled **pseudo-randomly**
- File: `EPR-simSampler.ipynb`

NB: quantum circuits ran with Sampler must ALWAYS have measurements at the end!

Fake Backend Simulator

- It simulates a quantum computer with **noise** in both unitary gates and measurement gates
- Measurement outcomes are sampled **pseudo-randomly** (with noise added)
- File: `EPR-simFake.ipynb`

Quantum Backend

- The real thing: using an IBM quantum computer!
- You need to register for a free IBM Quantum account (10 minutes of QPU time over one month)
- Follow the instructions on the Qiskit website to save your API key and instance info in your Qiskit's python environment
- File: `EPR-qSampler.ipynb`