

DRAFT

OpenWISP User Management System RESTful API documentation



OpenWISP User Management System - ***Version 1.1.5b***

Copyright © 2012 OpenWISP.org



Except where otherwise noted, this document is licensed under
[Creative Commons Attribution ShareAlike 3.0 License](http://creativecommons.org/licenses/by-sa/3.0/legalcode)

<http://creativecommons.org/licenses/by-sa/3.0/legalcode>

Table on contents

General information	7
<i>HTTP error codes</i>	<i>7</i>
<i>Application localization</i>	<i>8</i>
<i>Authenticated request</i>	<i>8</i>
Account Session	9
<i>Create</i>	<i>9</i>
Required roles	9
HTTP Request	9
HTTP Response	9
Examples	9
User	11
<i>Create</i>	<i>11</i>
Required roles	11
HTTP Request	11
HTTP Response	11
Examples	11
<i>Read</i>	<i>13</i>
Required roles	13
HTTP Request	13
HTTP Response	13
Examples	14
<i>Update</i>	<i>15</i>
Required roles	15
HTTP Request	15
HTTP Response	16
Examples	16
<i>Destroy</i>	<i>17</i>
Required roles	17
HTTP Request	17

HTTP Response	17
Examples	17
Radius Group	19
Create	19
Required roles	19
HTTP Request	19
HTTP Response	19
Examples	19
Read	20
Required roles	20
HTTP Request - List	20
HTTP Response - List	21
HTTP Request - Show	21
HTTP Response - Show	21
Examples	22
Update	22
Required roles	22
HTTP Request	22
HTTP Response	23
Examples	23
Destroy	24
Required roles	24
HTTP Request	24
HTTP Response	24
Examples	24
Users' Radius Checks	25
External documentation	25
Create	25
Required roles	25
HTTP Request	25
HTTP Response	25
Examples	26

<i>Read</i>	26
HTTP Request - List	26
HTTP Response - List	27
HTTP Request - Show	27
HTTP Response - Show	27
Examples	28
<i>Update</i>	28
HTTP Request	29
HTTP Response	29
Examples	29
<i>Destroy</i>	30
HTTP Request	30
HTTP Response	30
Examples	30
Users' Radius Replies	32
<i>External documentation</i>	32
<i>Create</i>	32
Required roles	32
HTTP Request	32
HTTP Response	32
Examples	33
<i>Read</i>	33
HTTP Request - List	33
HTTP Response - List	34
HTTP Request - Show	34
HTTP Response - Show	34
Examples	35
<i>Update</i>	36
HTTP Request	36
HTTP Response	36
Examples	37
<i>Destroy</i>	37

HTTP Request	38
HTTP Response	38
Examples	38
RADIUS Groups' Radius Checks	39
<i>External documentation</i>	39
<i>Create</i>	39
Required roles	39
HTTP Request	39
HTTP Response	39
Examples	39
<i>Read</i>	40
HTTP Request - List	40
HTTP Response - List	41
HTTP Request - Show	41
HTTP Response - Show	41
Examples	42
<i>Update</i>	42
HTTP Request	42
HTTP Response	43
Examples	43
<i>Destroy</i>	44
HTTP Request	44
HTTP Response	44
Examples	44
RADIUS Groups' Radius Replies	45
<i>External documentation</i>	45
<i>Create</i>	45
Required roles	45
HTTP Request	45
HTTP Response	45
Examples	46
<i>Read</i>	46

HTTP Request - List	46
HTTP Response - List	47
HTTP Request - Show	47
HTTP Response - Show	47
Examples	48
<i>Update</i>	49
HTTP Request	49
HTTP Response	49
Examples	50
<i>Destroy</i>	50
HTTP Request	50
HTTP Response	51
Examples	51

General information

HTTP error codes

The following table list error codes supported by the application.

Result Message	Code	Meanings
Successful results		
OK	200	Operation successfully executed
CREATED	201	New resource created
ACCEPTED	202	The request has been accepted for processing, but the processing has not been completed.
Client errors		
BAD REQUEST	400	The request could not be understood by the server due to malformed syntax. The client SHOULD NOT repeat the request without modifications.
FORBIDDEN	403	Insufficient privileges to access the addressed resource
NOT FOUND	404	Resource was not found
NOT ACCEPTABLE	406	The resource identified by the request is only capable of generating response entities which have content characteristics not acceptable according to the accept headers sent in the request.
REQUEST TIMEOUT	408	Timeout accessing the requested resource
UNPROCESSABLE ENTITY	422	The 422 (Unprocessable Entity) status code means the server understands the content type of the request entity, and the syntax of the request entity is correct (thus a 400 (Bad Request) status code is inappropriate) but was unable to process the contained instructions. For Examples, this error condition may occur if an XML request body contains well-formed (i.e., syntactically correct), but semantically erroneous, XML instructions.
Server errors		
INTERNAL SERVER ERROR	500	The server encountered an unexpected condition which prevented it from fulfilling the request.

Application localization

Error messages generated by the application are localized.

To retrieve these messages in a particular language the “locale” parameter can be appended to URL parameters.

At present time only “en” (for English) and “it” (for Italian) languages are supported. If no locale is specified, “it” is used.

Examples

```
http://<your server>/<your resource>?locale=en
```

Authenticated request

Resources that require some role will also require an authentication to be accessed are marked with an asterisk. Required roles are specified in each section. Requested authentication method is the “Basic HTTP Authentication”.

Account Session

Create

Required roles

No role required

HTTP Request

Verb	URLs	XML POSTDATA
POST	/account_session.xml /login.xml	<pre><account_session> <username>USERNAME</username> <password>PASSWORD</password> </account_session></pre>

HTTP Response

HTTP Code	Meaning	Content
201	CREATED	
422	UNPROCESSABLE ENTITY	<pre><?xml version="1.0" encoding="UTF-8"?> <errors> <error>error1</error> <error>error2</error> ... <error>errorN</error> </errors></pre>

Examples

Failed request

```
# curl -i -H 'Content-type: text/xml' -X POST http://localhost:3000/account_session.xml?locale=en -d "<account_session>
  <username>mario</username>
  <password>mario01</password>
</account_session>
"
HTTP/1.1 422
X-Ua-Compatible: IE=Edge
Connection: Keep-Alive
Content-Type: application/xml; charset=utf-8
Date: Thu, 10 May 2012 14:50:09 GMT
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)
X-Runtime: 0.225505
Content-Length: 102
Cache-Control: no-cache
Set-Cookie: _session_id=8d75fd3d53900ecc8599de64e767949d; path=/; HttpOnly

<?xml version="1.0" encoding="UTF-8"?>
<errors>
  <error>Wrong username or password</error>
</errors>
```

Successful request

```
# curl -i -H 'Content-type: text/xml' -X POST http://localhost:3000/account_session.xml?locale=en -d "<account_session>
  <username>user</username>
  <password>realpassword</password>
</account_session>
"
HTTP/1.1 201 Created
X-Ua-Compatible: IE=Edge
Connection: Keep-Alive
Content-Type: application/xml; charset=utf-8
Date: Thu, 10 May 2012 14:54:06 GMT
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)
X-Runtime: 0.326763
Content-Length: 1
Cache-Control: no-cache
Set-Cookie: _session_id=d3be989ee55eeaf2ade5c4f140372d22; path=/; HttpOnly
Set-Cookie:
account_credentials=b6001d2a51cf24803d83935d86253091c33e65190005ce5783fe9f22d6e5555d70d278ffa722541efe8f0a1
59249b936ea8b98556b4eb686146633be3ef76f25%3A%3A1; path=/"
```

User

Create

Required roles

users_manager
users_registrant

HTTP Request

Verb	URLs	POSTDATA (XML)
POST	/users.xml	<pre><user> <i>User attributes</i> </user></pre>

HTTP Response

HTTP Code	Meaning	Content
422	UNPROCESSABLE ENTITY	<pre><?xml version="1.0" encoding="UTF-8"?> <errors> <error>error1</error> <error>error2</error> ... <error>errorN</error> </errors></pre>
201	CREATED	<pre><?xml version="1.0" encoding="UTF-8"?> <user> <i>User attributes</i> </user></pre>

Examples

Failed request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X POST http://localhost:3000/users.xml?locale=en -d "
<user>
  <given-name>MyName</given-name>
  <surname>MySurname</surname>
  <address>Via con il vento</address>
  <city>Roma</city>
  <zip>00100</zip>
  <birth-date>1976-05-23</birth-date>
  <username>username</username>
  <password>password1</password>
  <password_confirmation>password1</password_confirmation>
  <email>me@email.com</email>
  <email_confirmation>me@email.com</email_confirmation>
```

```

    <verification-method>no_identity_verification</verification-method>
    <privacy-acceptance>true</privacy-acceptance>
    <eula-acceptance>true</eula-acceptance>
    <verified>true</verified>
    <active>true</active>
    <state>Italy</state>
    <radius-group-ids type='array'>
      <radius-group-id>2</radius-group-id>
    </radius-group-ids>
  </user>
"
HTTP/1.1 422
X-Ua-Compatible: IE=Edge
Connection: Keep-Alive
Content-Type: application/xml; charset=utf-8
Date: Mon, 14 May 2012 09:28:10 GMT
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)
X-Runtime: 0.398303
Content-Length: 153
Cache-Control: no-cache
Set-Cookie: _session_id=5582194a04b7cdc0b8ccaabd12c8465c; path=/; HttpOnly

<?xml version="1.0" encoding="UTF-8"?>
<errors>
  <error>Username has already been taken</error>
  <error>Email has already been taken</error>
</errors>

```

Successful request

```

# curl -i -u admin:admin -H 'Content-type: text/xml' -X POST http://localhost:3000/users.xml?locale=en -d "
<user>
  <given-name>MyName</given-name>
  <surname>MySurname</surname>
  <address>Via con il vento</address>
  <city>Roma</city>
  <zip>00100</zip>
  <birth-date>1976-05-23</birth-date>
  <username>username</username>
  <password>password1</password>
  <password-confirmation>password1</password-confirmation>
  <email>me@email.com</email>
  <email-confirmation>me@email.com</email-confirmation>
  <verification-method>no_identity_verification</verification-method>
  <privacy-acceptance>true</privacy-acceptance>
  <eula-acceptance>true</eula-acceptance>
  <verified>true</verified>
  <active>true</active>
  <state>Italy</state>
  <radius-group-ids type='array'>
    <radius-group-id>2</radius-group-id>
  </radius-group-ids>
</user>
"
HTTP/1.1 201 Created
X-Ua-Compatible: IE=Edge
Connection: Keep-Alive
Content-Type: application/xml; charset=utf-8
Date: Mon, 14 May 2012 09:42:22 GMT
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)
X-Runtime: 0.503151
Content-Length: 2001
Cache-Control: no-cache
Set-Cookie: _session_id=fb1cf0dc11d16a8568a3cf4f3a6d3538; path=/; HttpOnly

<?xml version="1.0" encoding="UTF-8"?>
<user>
  <address>Via con il vento</address>
  <city>Roma</city>
  <image-file-data type="binary" nil="true" encoding="base64"></image-file-data>
  <created-at type="datetime">2012-05-14T11:42:22+02:00</created-at>
  <last-request-at type="datetime" nil="true"></last-request-at>
  <verified-at type="datetime">2012-05-14T11:42:22+02:00</verified-at>
  <zip>00100</zip>
  <email-confirmation type="NilClass">me@email.com</email-confirmation>
  <notes nil="true"></notes>
  <updated-at type="datetime">2012-05-14T11:42:22+02:00</updated-at>
  <mobile-prefix nil="true"></mobile-prefix>
  <recovered-at type="datetime" nil="true"></recovered-at>
  <username>username</username>
  <birth-date type="date">1976-05-23</birth-date>
  <current-login-ip nil="true"></current-login-ip>

```

```

<failed-login-count type="integer">0</failed-login-count>
<id type="integer">11</id>
<mobile-suffix nil="true"></mobile-suffix>
<privacy-acceptance type="boolean">true</privacy-acceptance>
<recovered type="boolean" nil="true"></recovered>
<verification-method>no_identity_verification</verification-method>
<current-login-at type="datetime" nil="true"></current-login-at>
<eula-acceptance type="boolean">true</eula-acceptance>
<login-count type="integer">0</login-count>
<given-name>MyName</given-name>
<last-login-ip nil="true"></last-login-ip>
<verified type="boolean">true</verified>
<last-login-at type="datetime" nil="true"></last-login-at>
<surname>MySurname</surname>
<active type="boolean">true</active>
<email>me@email.com</email>
<state>Italy</state>
<radius-groups type="array">
  <radius-group>
    <name>Users</name>
    <created-at type="datetime">2009-12-28T14:36:50+01:00</created-at>
    <notes>Default groups for users</notes>
    <updated-at type="datetime">2012-05-10T12:53:53+02:00</updated-at>
    <priority type="integer">2</priority>
    <id type="integer">2</id>
  </radius-group>
</radius-groups>
</user>

```

Read

Required roles

users_browser
users_finder

HTTP Request

Verb	URLs	POSTDATA (XML)
GET	/users/ :id.xml /users/ :username.xml	

HTTP Response

HTTP Code	Meaning	Content
200	OK	<pre> <?xml version="1.0" encoding="UTF-8"?> <user> <i>User attributes</i> </user> </pre>
404	NOT FOUND	

Examples

Failed request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X GET http://localhost:3000/users/10.xml?locale=en
HTTP/1.1 404 Not Found
X-Ua-Compatible: IE=Edge
Connection: Keep-Alive
Content-Type: text/html; charset=utf-8
Date: Mon, 14 May 2012 09:44:30 GMT
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)
X-Runtime: 0.379873
Content-Length: 1
Cache-Control: no-cache
Set-Cookie: _session_id=57b95bb2e32b14344613a4fc7185472b; path=/; HttpOnly
```

Successful request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X GET http://localhost:3000/users/11.xml?locale=en
HTTP/1.1 200 OK
X-Ua-Compatible: IE=Edge
Etag: "c8552fdca13e4b1d199d877d3854ee94"
Connection: Keep-Alive
Content-Type: application/xml; charset=utf-8
Date: Mon, 14 May 2012 09:44:57 GMT
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)
X-Runtime: 0.374612
Content-Length: 2032
Cache-Control: max-age=0, private, must-revalidate
Set-Cookie: _session_id=fddb1c4ce9b71dc86fd21e4d1c0a86f6; path=/; HttpOnly

<?xml version="1.0" encoding="UTF-8"?>
<user>
  <address>Via con il vento</address>
  <city>Roma</city>
  <image-file-data type="binary" nil="true" encoding="base64"></image-file-data>
  <created-at type="datetime">2012-05-14T11:42:22+02:00</created-at>
  <last-request-at type="datetime" nil="true"></last-request-at>
  <verified-at type="datetime">2012-05-14T11:42:22+02:00</verified-at>
  <zip>00100</zip>
  <notes nil="true"></notes>
  <updated-at type="datetime">2012-05-14T11:42:22+02:00</updated-at>
  <mobile-prefix nil="true"></mobile-prefix>
  <recovered-at type="datetime" nil="true"></recovered-at>
  <username>username</username>
  <birth-date type="date">1976-05-23</birth-date>
  <current-login-ip nil="true"></current-login-ip>
  <failed-login-count type="integer">0</failed-login-count>
  <id type="integer">11</id>
  <mobile-suffix nil="true"></mobile-suffix>
  <privacy-acceptance type="boolean">true</privacy-acceptance>
  <recovered type="boolean" nil="true"></recovered>
  <verification-method>no_identity_verification</verification-method>
  <current-login-at type="datetime" nil="true"></current-login-at>
  <eula-acceptance type="boolean">true</eula-acceptance>
  <login-count type="integer">0</login-count>
  <given-name>MyName</given-name>
  <last-login-ip nil="true"></last-login-ip>
  <verified type="boolean">true</verified>
  <last-login-at type="datetime" nil="true"></last-login-at>
  <surname>MySurname</surname>
  <active type="boolean">true</active>
  <email>me@email.com</email>
  <state>Italy</state>
  <radius-groups type="array">
    <radius-group>
      <name>Users</name>
      <created-at type="datetime">2009-12-28T14:36:50+01:00</created-at>
      <notes>Default groups for users</notes>
      <updated-at type="datetime">2012-05-10T12:53:53+02:00</updated-at>
      <priority type="integer">2</priority>
      <id type="integer">2</id>
      <user-id type="NilClass">11</user-id>
      <radius-group-id type="NilClass">2</radius-group-id>
    </radius-group>
  </radius-groups>
</user>
```

Update

Required roles

users_manager

HTTP Request

Verb	URLs	POSTDATA (XML)
PUT	/users/: id .xml /users/: username .xml	<?xml version="1.0" encoding="UTF-8"?> <user> <i>User attributes to be changed</i> </user>

HTTP Response

HTTP Code	Meaning	Content
422	UNPROCESSABLE ENTITY	<?xml version="1.0" encoding="UTF-8"?> <errors> <error> error1 </error> <error> error2 </error> ... <error> errorN </error> </errors>
200	OK	

Examples

Failed request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X PUT http://localhost:3000/users/11.xml?locale=en -d
"
<user>
  <email>invalid_email</email>
  <email_confirmation>invalid_email</email_confirmation>
</user>
"
HTTP/1.1 422
X-Ua-Compatible: IE=Edge
Connection: Keep-Alive
Content-Type: application/xml; charset=utf-8
Date: Mon, 14 May 2012 09:56:18 GMT
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)
X-Runtime: 0.425134
Content-Length: 116
Cache-Control: no-cache
Set-Cookie: _session_id=8e0ac4db9962d51416c15e1ced2c2b81; path=/; HttpOnly

<?xml version="1.0" encoding="UTF-8"?>
<errors>
  <error>Email should look like an e-mail address</error>
</errors>
```


Successful request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X PUT http://localhost:3000/users/11.xml?locale=en -d
"
<user>
  <radius-group-ids type='array'>
    <radius-group-id>1</radius-group-id>
    <radius-group-id>2</radius-group-id>
  </radius-group-ids>
</user>
"
HTTP/1.1 200 OK
X-Ua-Compatible: IE=Edge
Etag: "0ce4f7827a074f31dc77a8aa295e7037"
Connection: Keep-Alive
Content-Type: application/xml; charset=utf-8
Date: Mon, 14 May 2012 09:52:42 GMT
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)
X-Runtime: 0.500385
Content-Length: 1
Cache-Control: max-age=0, private, must-revalidate
Set-Cookie: _session_id=3aef73c5a4dc3e6fc73a6c53b747990c; path=/; HttpOnly
```

Destroy

Required roles

users_destroyer

HTTP Request

Verb	URLs	POSTDATA (XML)
DELETE	/users/: id .xml /users/: username .xml	

HTTP Response

HTTP Code	Meaning	Content
404	NOT FOUND	
200	OK	

Examples

Failed request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X DELETE http://localhost:3000/users/11.xml?locale=en
HTTP/1.1 404 Not Found
X-Ua-Compatible: IE=Edge
Connection: Keep-Alive
Content-Type: text/html; charset=utf-8
Date: Mon, 14 May 2012 10:12:59 GMT
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)
X-Runtime: 0.328074
Content-Length: 1
Cache-Control: no-cache
Set-Cookie: _session_id=8929f422f04d061975524d845e14948b; path=/; HttpOnly
```

Successful request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X DELETE http://localhost:3000/users/11.xml?locale=en
HTTP/1.1 200 OK
X-Ua-Compatible: IE=Edge
Connection: Keep-Alive
Content-Type: application/xml; charset=utf-8
Date: Mon, 14 May 2012 10:12:43 GMT
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)
X-Runtime: 0.469990
Content-Length: 1
Cache-Control: no-cache
Set-Cookie: _session_id=5dfa997a7b3921d3d21b5339f1b5a036; path=/; HttpOnly
```

Radius Group

Create

Required roles

radius_groups_creator

HTTP Request

Verb	URLs	POSTDATA (XML)
POST	/radius_groups.xml	<pre><radius-group> <name>RADIUS GROUP NAME</name> <notes>NOTES</notes> <priority>PRIORITY</priority> </radius-group></pre>

HTTP Response

HTTP Code	Meaning	Content
422	UNPROCESSABLE ENTITY	<pre><?xml version="1.0" encoding="UTF-8"?> <errors> <error>error1</error> <error>error2</error> ... <error>errorN</error> </errors></pre>
201	CREATED	<pre><?xml version="1.0" encoding="UTF-8"?> <radius-group> <name>RADIUS GROUP NAME</name> <created-at type="datetime">CREATION DATE</created-at> <updated-at type="datetime">UPDATE DATE</updated-at> <notes>NOTES</notes> <priority type="integer">PRIORITY</priority> <id type="integer">ID</id> </radius-group></pre>

Examples

Failed request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X POST http://localhost:3000/radius_groups.xml?
locale=en -d "
<radius-group>
  <name>Disabled</name>
  <notes/>
  <priority>1</priority>
</radius-group>
"
HTTP/1.1 422
X-Ua-Compatible: IE=Edge
Location: http://localhost:3000/radius_groups
Connection: Keep-Alive
Content-Type: application/xml; charset=utf-8
Date: Mon, 14 May 2012 10:33:00 GMT
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)
X-Runtime: 0.155841
Content-Length: 103
Cache-Control: no-cache
Set-Cookie: _session_id=4aa00c265a928c13700f9b85b773ebc9; path=/; HttpOnly

<?xml version="1.0" encoding="UTF-8"?>
<errors>
  <error>Name has already been taken</error>
</errors>
```

Successful request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X POST http://localhost:3000/radius_groups.xml?
locale=en -d "
<radius-group>
  <name>BadGuys</name>
  <notes/>
  <priority>1</priority>
</radius-group>
"
HTTP/1.1 201 Created
X-Ua-Compatible: IE=Edge
Location: http://localhost:3000/radius_groups
Connection: Keep-Alive
Content-Type: application/xml; charset=utf-8
Date: Mon, 14 May 2012 10:33:37 GMT
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)
X-Runtime: 0.162498
Content-Length: 328
Cache-Control: no-cache
Set-Cookie: _session_id=7f49d252645fbeb3128df72a81112998; path=/; HttpOnly

<?xml version="1.0" encoding="UTF-8"?>
<radius-group>
  <name>BadGuys</name>
  <created-at type="datetime">2012-05-14T12:33:37+02:00</created-at>
  <notes nil="true"></notes>
  <updated-at type="datetime">2012-05-14T12:33:37+02:00</updated-at>
  <priority type="integer">1</priority>
  <id type="integer">5</id>
</radius-group>
```

Read

Required roles

radius_groups_viewer

HTTP Request - List

Verb	URLs	POSTDATA (XML)
GET	/radius_groups.xml	

HTTP Response - List

HTTP Code	Meaning	Content
200	OK	<pre><?xml version="1.0" encoding="UTF-8"?> <radius-groups type="array"> <radius-group> <created-at type="datetime">CREATION DATE</created-at> <updated-at type="datetime">UPDATE DATE</updated-at> <id type="integer">ID</id> <name>RADIUS GROUP NAME</name> <notes>NOTES</notes> <priority>PRIORITY</priority> </radius-group> ... <radius-group> <created-at type="datetime">Another CREATION DATE</created-at> <updated-at type="datetime">Another UPDATE DATE</updated-at> <id type="integer">Another ID</id> <name>Another RADIUS GROUP NAME</name> <notes>Another NOTES</notes> <priority>Another PRIORITY</priority> </radius-group> </radius-groups></pre>

HTTP Request - Show

Verb	URLs	POSTDATA (XML)
GET	/radius_groups/:id.xml	

HTTP Response - Show

HTTP Code	Meaning	Content
200	OK	<pre><?xml version="1.0" encoding="UTF-8"?> <radius-group> <created-at type="datetime">CREATION DATE</created-at> <updated-at type="datetime">UPDATE DATE</updated-at> <id type="integer">ID</id> <name>RADIUS GROUP NAME</name> <notes>NOTES</notes> <priority>PRIORITY</priority> </radius-group></pre>
404	NOT FOUND	

Examples

Failed request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X GET http://localhost:3000/radius_groups/8.xml?
locale=en
HTTP/1.1 404 Not Found
X-Ua-Compatible: IE=Edge
Connection: Keep-Alive
Content-Type: text/html; charset=utf-8
Date: Mon, 14 May 2012 10:38:44 GMT
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)
X-Runtime: 0.129446
Content-Length: 1
Cache-Control: no-cache
Set-Cookie: _session_id=af82ac737f3493c519171a5bdb81b51b; path=/; HttpOnly
```

Successful request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X GET http://localhost:3000/radius_groups/5.xml?
locale=en
HTTP/1.1 200 OK
X-Ua-Compatible: IE=Edge
Etag: "a795beb4e52f94ec005a577661a70531"
Connection: Keep-Alive
Content-Type: application/xml; charset=utf-8
Date: Mon, 14 May 2012 10:37:21 GMT
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)
X-Runtime: 0.181116
Content-Length: 328
Cache-Control: max-age=0, private, must-revalidate
Set-Cookie: _session_id=71c3016bfbld626769a6e0bbd5f66eal; path=/; HttpOnly

<?xml version="1.0" encoding="UTF-8"?>
<radius-group>
  <name>BadGuys</name>
  <created-at type="datetime">2012-05-14T12:33:37+02:00</created-at>
  <notes nil="true"></notes>
  <updated-at type="datetime">2012-05-14T12:33:37+02:00</updated-at>
  <priority type="integer">1</priority>
  <id type="integer">5</id>
</radius-group>
```

Update

Required roles

radius_groups_manager

HTTP Request

Verb	URLs	POSTDATA (XML)
PUT	/radius_groups/:id.xml	<pre><radius-group> <name>NEW RADIUS GROUP NAME</name> <notes>NEW NOTES</notes> <priority>NEW PRIORITY</priority> </radius-group></pre>

HTTP Response

HTTP Code	Meaning	Content
200	OK	
404	NOT FOUND	
422	UNPROCESSABLE ENTITY	<pre><?xml version="1.0" encoding="UTF-8"?> <errors> <error>error1</error> <error>error2</error> ... <error>errorN</error> </errors></pre>

Examples

Failed request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X PUT http://localhost:3000/radius_groups/5.xml?
locale=en -d "
<radius-group>
  <name>BadGuys</name>
  <notes>This group contains users with limited bandwidth</notes>
  <priority>there are priorities...</priority>
</radius-group>
"
HTTP/1.1 422
X-Ua-Compatible: IE=Edge
Location: http://localhost:3000/radius_groups
Connection: Keep-Alive
Content-Type: application/xml; charset=utf-8
Date: Mon, 14 May 2012 10:46:26 GMT
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)
X-Runtime: 0.169848
Content-Length: 100
Cache-Control: no-cache
Set-Cookie: _session_id=20fa7f99d7cda54638b3362deff009d2; path=/; HttpOnly

<?xml version="1.0" encoding="UTF-8"?>
<errors>
  <error>Priority is not a number</error>
</errors>
```

Successful request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X PUT http://localhost:3000/radius_groups/5.xml?
locale=en -d "
<radius-group>
  <name>BadGuys</name>
  <notes>This group contains users with limited bandwidth</notes>
  <priority>2</priority>
</radius-group>
"
HTTP/1.1 200 OK
X-Ua-Compatible: IE=Edge
Connection: Keep-Alive
Content-Type: application/xml; charset=utf-8
Date: Mon, 14 May 2012 10:51:47 GMT
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)
X-Runtime: 0.156573
Content-Length: 1
Cache-Control: no-cache
Set-Cookie: _session_id=bc4d23ac2f5dca6f3b00b74b8cd86e2e; path=/; HttpOnly
```

Destroy

Required roles

radius_groups_destroyer

HTTP Request

Verb	URLs	POSTDATA (XML)
DELETE	/radius_groups/: <i>id</i> .xml	

HTTP Response

HTTP Code	Meaning	Content
200	OK	
404	NOT FOUND	

Examples

Failed request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X DELETE http://localhost:3000/radius_groups/5.xml?
locale=en
HTTP/1.1 404 Not Found
X-Ua-Compatible: IE=Edge
Connection: Keep-Alive
Content-Type: text/html; charset=utf-8
Date: Mon, 14 May 2012 10:48:09 GMT
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)
X-Runtime: 0.075196
Content-Length: 1
Cache-Control: no-cache
Set-Cookie: _session_id=c8952115c25f7b6a79a1b70f72e38f60; path=/; HttpOnly
```

Successful request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X DELETE http://localhost:3000/radius_groups/5.xml?
locale=en
HTTP/1.1 200 OK
X-Ua-Compatible: IE=Edge
Connection: Keep-Alive
Content-Type: application/xml; charset=utf-8
Date: Mon, 14 May 2012 11:06:11 GMT
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)
X-Runtime: 0.250730
Content-Length: 1
Cache-Control: no-cache
Set-Cookie: _session_id=450f4a3117f7972157e83aba0b4afd0c; path=/; HttpOnly
```


Users' Radius Checks

External documentation

<http://wiki.freeradius.org/Operators>

Create

Required roles

radius_checks_creator

HTTP Request

Verb	URLs	POSTDATA (XML)
POST	/users/: user_id /radius_checks.xml /users/: username /radius_checks.xml	<pre><radius-check> <check-attribute>RADIUS CHECK ATTRIBUTE</check-attribute> <op>RADIUS CHECK OPERATOR</op> <value>RADIUS CHECK VALUE</value> </radius-check></pre>

HTTP Response

HTTP Code	Meaning	Content
200	OK	<pre><?xml version="1.0" encoding="UTF-8"?> <radius-check> <radius-entity-type>AccountCommon</radius-entity-type> <created-at type="datetime">CREATION DATE</created-at> <op>RADIUS CHECK OPERATOR</op> <radius-entity-id type="integer">USER_ID</radius-entity-id> <updated-at type="datetime">UPDATE DATE</updated-at> <id type="integer">ID</id> <value>RADIUS CHECK VALUE</value> <check-attribute>RADIUS CHECK ATTRIBUTE</check-attribute> </radius-check></pre>
404	NOT FOUND	
422	UNPROCESSABLE ENTITY	<pre><?xml version="1.0" encoding="UTF-8"?> <errors> <error>error1</error> <error>error2</error> ... <error>errorN</error> </errors></pre>

Examples

Failed request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X POST http://localhost:3000/users/1/radius_checks.xml?locale=en -d "
<radius-check>
  <check-attribute>Max-Daily-Session</check-attribute>
  <op>invalid operator</op>
  <value>360</value>
</radius-check>
"
HTTP/1.1 422
X-Ua-Compatible: IE=Edge
Location: http://localhost:3000/users/1
Connection: Keep-Alive
Content-Type: application/xml; charset=utf-8
Date: Mon, 14 May 2012 15:36:41 GMT
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)
X-Runtime: 0.424751
Content-Length: 162
Cache-Control: no-cache
Set-Cookie: _session_id=2db790005fa8bc7245200a4d52bdf5ac; path=/; HttpOnly

<?xml version="1.0" encoding="UTF-8"?>
<errors>
  <error>Check attribute has already been taken</error>
  <error>Op is not included in the list</error>
</errors>
```

Successful request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X POST http://localhost:3000/users/1/radius_checks.xml?locale=en -d "
<radius-check>
<check-attribute>Max-Daily-Session</check-attribute>
<op>=</op>
<value>360</value>
</radius-check>
"
HTTP/1.1 201 Created
X-Ua-Compatible: IE=Edge
Location: http://localhost:3000/users/1
Connection: Keep-Alive
Content-Type: application/xml; charset=utf-8
Date: Mon, 14 May 2012 15:33:29 GMT
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)
X-Runtime: 0.392679
Content-Length: 440
Cache-Control: no-cache
Set-Cookie: _session_id=9da67da731971e07c270729432593f6b; path=/; HttpOnly

<?xml version="1.0" encoding="UTF-8"?>
<radius-check>
  <radius-entity-type>AccountCommon</radius-entity-type>
  <created-at type="datetime">2012-05-14T17:33:29+02:00</created-at>
  <op>=</op>
  <radius-entity-id type="integer">1</radius-entity-id>
  <updated-at type="datetime">2012-05-14T17:33:29+02:00</updated-at>
  <id type="integer">23</id>
  <value>360</value>
  <check-attribute>Max-Daily-Session</check-attribute>
</radius-check>
```

Read

HTTP Request - List

Verb	URLs	POSTDATA (XML)
GET	/users/: user_id /radius_checks.xml /users/: username /radius_checks.xml	

HTTP Response - List

HTTP Code	Meaning	Content
200	OK	<pre><?xml version="1.0" encoding="UTF-8"?> <radius-checks type="array"> <radius-check> <radius-entity-type>AccountCommon</radius-entity-type> <created-at type="datetime">CREATION DATE</created-at> <op>RADIUS CHECK OPERATOR</op> <radius-entity-id type="integer">USER_ID</radius-entity-id> <updated-at type="datetime">UPDATE DATE</updated-at> <id type="integer">ID</id> <value>RADIUS CHECK VALUE</value> <check-attribute>RADIUS CHECK ATTRIBUTE</check-attribute> </radius-check> ... <radius-check> <radius-entity-type>AccountCommon</radius-entity-type> <created-at type="datetime">Another CREATION DATE</created-at> <op>Another RADIUS CHECK OPERATOR</op> <radius-entity-id type="integer">USER_ID</radius-entity-id> <updated-at type="datetime">Another UPDATE DATE</updated-at> <id type="integer">Another ID</id> <value>Another RADIUS CHECK VALUE</value> <check-attribute>Another RADIUS CHECK ATTRIBUTE</check-attribute> </radius-check> </radius-checks></pre>
404	NOT FOUND	

HTTP Request - Show

Verb	URLs	POSTDATA (XML)
GET	/users/: user_id /radius_checks/: id .xml /users/: username /radius_checks/: id .xml	

HTTP Response - Show

HTTP Code	Meaning	Content
200	OK	<pre><?xml version="1.0" encoding="UTF-8"?> <radius-check> <radius-entity-type>AccountCommon</radius-entity-type> <created-at type="datetime">CREATION DATE</created-at> <op>RADIUS CHECK OPERATOR</op> <radius-entity-id type="integer">USER ID</radius-entity-id> <updated-at type="datetime">UPDATE DATE</updated-at> <id type="integer">ID</id> <value>RADIUS CHECK VALUE</value> <check-attribute>RADIUS CHECK ATTRIBUTE</check-attribute> </radius-check></pre>
404	NOT FOUND	

Examples

Failed request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X GET http://localhost:3000/users/nonexistaetuser/
radius_checks.xml?locale=en
HTTP/1.1 404 Not Found
X-Ua-Compatible: IE=Edge
Connection: Keep-Alive
Content-Type: text/html; charset=utf-8
Date: Mon, 14 May 2012 15:03:05 GMT
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)
X-Runtime: 0.466966
Content-Length: 1
Cache-Control: no-cache
Set-Cookie: _session_id=a9ae5f4ab329f341431e7ac2a882cd18; path=/; HttpOnly
```

Successful request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X GET http://localhost:3000/users/1/
radius_checks.xml?locale=en
HTTP/1.1 200 OK
X-Ua-Compatible: IE=Edge
Etag: "93e91e7302837789def657348b326894"
Connection: Keep-Alive
Content-Type: application/xml; charset=utf-8
Date: Mon, 14 May 2012 14:59:42 GMT
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)
X-Runtime: 0.399107
Content-Length: 520
Cache-Control: max-age=0, private, must-revalidate
Set-Cookie: _session_id=1f81bd2e8982861cdb935ae0fa430e9e; path=/; HttpOnly

<?xml version="1.0" encoding="UTF-8"?>
<radius-checks type="array">
  <radius-check>
    <radius-entity-type>AccountCommon</radius-entity-type>
    <created-at type="datetime">2012-05-10T12:53:16+02:00</created-at>
    <op>=</op>
    <radius-entity-id type="integer">1</radius-entity-id>
    <updated-at type="datetime">2012-05-10T12:53:16+02:00</updated-at>
    <id type="integer">22</id>
    <value>3000000000</value>
    <check-attribute>Max-Daily-Session-Traffic</check-attribute>
  </radius-check>
</radius-checks>
```

Update

HTTP Request

Verb	URLs	POSTDATA (XML)
PUT	/users/: user_id /radius_checks/: id .xml /users/: username /radius_checks/: id .xml	<pre><radius-check> <check-attribute>New RADIUS CHECK ATTRIBUTE</check-attribute> <op>New RADIUS CHECK OPERATOR</op> <value>New RADIUS CHECK VALUE</value> </radius-check></pre>

HTTP Response

HTTP Code	Meaning	Content
200	OK	
404	NOT FOUND	
422	UNPROCESSABLE ENTITY	<pre><?xml version="1.0" encoding="UTF-8"?> <errors> <error>error1</error> <error>error2</error> ... <error>errorN</error> </errors></pre>

Examples

Failed request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X PUT http://localhost:3000/users/1/radius_checks/
23.xml?locale=en -d "
<radius-check>
  <value></value>
</radius-check>
"
HTTP/1.1 422
X-Ua-Compatible: IE=Edge
Location: http://localhost:3000/users/1
Connection: Keep-Alive
Content-Type: application/xml; charset=utf-8
Date: Mon, 14 May 2012 15:44:04 GMT
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)
X-Runtime: 0.527406
Content-Length: 96
Cache-Control: no-cache
Set-Cookie: _session_id=593306e56c35db97728e579a62c213d0; path=/; HttpOnly

<?xml version="1.0" encoding="UTF-8"?>
<errors>
  <error>Value can't be blank</error>
</errors>
```

Successful request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X PUT http://localhost:3000/users/1/radius_checks/23.xml?locale=en -d "
<radius-check>
  <value>360</value>
</radius-check>
"
HTTP/1.1 200 OK
X-Ua-Compatible: IE=Edge
Connection: Keep-Alive
Content-Type: application/xml; charset=utf-8
Date: Mon, 14 May 2012 15:43:08 GMT
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)
X-Runtime: 0.419544
Content-Length: 1
Cache-Control: no-cache
Set-Cookie: _session_id=f8adbae37924b9f49320ba2cc6b80584; path=/; HttpOnly
```

Destroy

HTTP Request

Verb	URLs	POSTDATA (XML)
DELETE	/users/: user_id /radius_checks/: id .xml /users/: username /radius_checks/: id .xml	

HTTP Response

HTTP Code	Meaning	Content
200	OK	
404	NOT FOUND	

Examples

Failed request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X DELETE http://localhost:3000/users/1/radius_checks/24.xml?locale=en
HTTP/1.1 200 OK
X-Ua-Compatible: IE=Edge
Connection: Keep-Alive
Content-Type: application/xml; charset=utf-8
Date: Mon, 14 May 2012 15:54:07 GMT
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)
X-Runtime: 0.343375
Content-Length: 1
Cache-Control: no-cache
Set-Cookie: _session_id=46f91545873e861b54a915fc9497643d; path=/; HttpOnly
```

Successful request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X DELETE http://localhost:3000/users/1/radius_checks/21.xml?locale=en
HTTP/1.1 404 Not Found
X-Ua-Compatible: IE=Edge
Connection: Keep-Alive
Content-Type: text/html; charset=utf-8
Date: Mon, 14 May 2012 15:51:51 GMT
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)
X-Runtime: 0.341959
Content-Length: 1
Cache-Control: no-cache
Set-Cookie: _session_id=816a1e1ff1ea2d4ca0440b24ec128c63; path=/; HttpOnly
```

Users' Radius Replies

External documentation

<http://wiki.freeradius.org/Operators>

Create

Required roles

radius_replies_creator

HTTP Request

Verb	URLs	POSTDATA (XML)
POST	/users/: user_id /radius_replies.xml /users/: username /radius_replies.xml	<pre><radius-reply> <reply-attribute>RADIUS REPLY ATTRIBUTE</reply-attribute> <op>RADIUS REPLY OPERATOR</op> <value>RADIUS REPLY VALUE</value> </radius-reply></pre>

HTTP Response

HTTP Code	Meaning	Content
200	OK	<pre><?xml version="1.0" encoding="UTF-8"?> <radius-reply> <radius-entity-type>AccountCommon</radius-entity-type> <created-at type="datetime">CREATION DATE</created-at> <op>RADIUS REPLY OPERATOR</op> <radius-entity-id type="integer">USER_ID</radius-entity-id> <updated-at type="datetime">UPDATE DATE</updated-at> <id type="integer">ID</id> <value>RADIUS REPLY VALUE</value> <reply-attribute>RADIUS REPLY ATTRIBUTE</reply-attribute> </radius-reply></pre>
404	NOT FOUND	
422	UNPROCESSABLE ENTITY	<pre><?xml version="1.0" encoding="UTF-8"?> <errors> <error>error1</error> <error>error2</error> ... <error>errorN</error> </errors></pre>

Examples

Failed request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X POST http://localhost:3000/users/1/radius_replies.xml?locale=en -d "  
<radius-reply>  
  <reply-attribute>WISPr-Bandwidth-Max-Up</reply-attribute>  
  <op>invalid operator</op>  
  <value>10240</value>  
</radius-reply>  
"  
HTTP/1.1 422  
X-Ua-Compatible: IE=Edge  
Location: http://localhost:3000/users/1  
Connection: Keep-Alive  
Content-Type: application/xml; charset=utf-8  
Date: Tue, 15 May 2012 08:03:22 GMT  
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)  
X-Runtime: 0.411560  
Content-Length: 106  
Cache-Control: no-cache  
Set-Cookie: _session_id=e1ee668bfd9b7e80e77ce3852068a879; path=/; HttpOnly  
  
<?xml version="1.0" encoding="UTF-8"?>  
<errors>  
  <error>Op is not included in the list</error>  
</errors>
```

Successful request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X POST http://localhost:3000/users/1/radius_replies.xml?locale=en -d "  
<radius-reply>  
  <reply-attribute>WISPr-Bandwidth-Max-Up</reply-attribute>  
  <op>:=</op>  
  <value>10240</value>  
</radius-reply>  
"  
HTTP/1.1 201 Created  
X-Ua-Compatible: IE=Edge  
Location: http://localhost:3000/users/1  
Connection: Keep-Alive  
Content-Type: application/xml; charset=utf-8  
Date: Tue, 15 May 2012 08:03:48 GMT  
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)  
X-Runtime: 0.542533  
Content-Length: 447  
Cache-Control: no-cache  
Set-Cookie: _session_id=0930979d1837e1c67dca3db25b7f09ef; path=/; HttpOnly  
  
<?xml version="1.0" encoding="UTF-8"?>  
<radius-reply>  
  <radius-entity-type>AccountCommon</radius-entity-type>  
  <created-at type="datetime">2012-05-15T10:03:48+02:00</created-at>  
  <op>:=</op>  
  <radius-entity-id type="integer">1</radius-entity-id>  
  <updated-at type="datetime">2012-05-15T10:03:48+02:00</updated-at>  
  <id type="integer">13</id>  
  <value>10240</value>  
  <reply-attribute>WISPr-Bandwidth-Max-Up</reply-attribute>  
</radius-reply>
```

Read

HTTP Request - List

Verb	URLs	POSTDATA (XML)
GET	/users/: user_id /radius_replies.xml /users/: username /radius_replies.xml	

HTTP Response - List

HTTP Code	Meaning	Content
200	OK	<pre><?xml version="1.0" encoding="UTF-8"?> <radius-replies type="array"> <radius-reply> <radius-entity-type>AccountCommon</radius-entity-type> <created-at type="datetime">CREATION DATE</created-at> <op>RADIUS REPLY OPERATOR</op> <radius-entity-id type="integer">USER_ID</radius-entity-id> <updated-at type="datetime">UPDATE DATE</updated-at> <id type="integer">ID</id> <value>RADIUS REPLY VALUE</value> <reply-attribute>RADIUS REPLY ATTRIBUTE</reply-attribute> </radius-reply> ... <radius-reply> <radius-entity-type>AccountCommon</radius-entity-type> <created-at type="datetime">Another CREATION DATE</created-at> <op>Another RADIUS REPLY OPERATOR</op> <radius-entity-id type="integer">USER_ID</radius-entity-id> <updated-at type="datetime">Another UPDATE DATE</updated-at> <id type="integer">Another ID</id> <value>Another RADIUS REPLY VALUE</value> <reply-attribute>Another RADIUS REPLY ATTRIBUTE</reply-attribute> </radius-reply> </radius-replies ></pre>
404	NOT FOUND	

HTTP Request - Show

Verb	URLs	POSTDATA (XML)
GET	/users/: user_id /radius_replies/: id .xml /users/: username /radius_replies/: id .xml	

HTTP Response - Show

HTTP Code	Meaning	Content
200	OK	<pre><?xml version="1.0" encoding="UTF-8"?> <radius-reply> <radius-entity-type>AccountCommon</radius-entity-type> <created-at type="datetime">CREATION DATE</created-at> <op>RADIUS REPLY OPERATOR</op> <radius-entity-id type="integer">USER ID</radius-entity-id> <updated-at type="datetime">UPDATE DATE</updated-at> <id type="integer">ID</id> <value>RADIUS REPLY VALUE</value> <reply-attribute>RADIUS REPLY ATTRIBUTE</reply-attribute> </radius-reply></pre>
404	NOT FOUND	

Examples

Failed request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X GET http://localhost:3000/users/nonexistaetuser/
radius_replies.xml?locale=en
HTTP/1.1 404 Not Found
X-Ua-Compatible: IE=Edge
Connection: Keep-Alive
Content-Type: text/html; charset=utf-8
Date: Tue, 15 May 2012 08:07:22 GMT
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)
X-Runtime: 9.118337
Content-Length: 1
Cache-Control: no-cache
Set-Cookie: _session_id=86d79c7234484a1e63bdbc9d87d98853; path=/; HttpOnly
```

Successful request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X GET http://localhost:3000/users/1/radius_replies.xml?locale=en
HTTP/1.1 200 OK
X-Ua-Compatible: IE=Edge
Etag: "df84240836109b3053ec5a83630fcf6d"
Connection: Keep-Alive
Content-Type: application/xml; charset=utf-8
Date: Tue, 15 May 2012 08:07:47 GMT
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)
X-Runtime: 1.482649
Content-Length: 1364
Cache-Control: max-age=0, private, must-revalidate
Set-Cookie: _session_id=5dfc93df4bc7ccc3865f4d7e86a144b1; path=/; HttpOnly

<?xml version="1.0" encoding="UTF-8"?>
<radius-replies type="array">
  <radius-reply>
    <radius-entity-type>AccountCommon</radius-entity-type>
    <created-at type="datetime">2012-05-10T12:51:53+02:00</created-at>
    <op>=</op>
    <radius-entity-id type="integer">1</radius-entity-id>
    <updated-at type="datetime">2012-05-10T12:52:05+02:00</updated-at>
    <id type="integer">11</id>
    <value>2048</value>
    <reply-attribute>WISPr-Bandwidth-Max-Down</reply-attribute>
  </radius-reply>
  <radius-reply>
    <radius-entity-type>AccountCommon</radius-entity-type>
    <created-at type="datetime">2012-05-10T12:52:48+02:00</created-at>
    <op>=</op>
    <radius-entity-id type="integer">1</radius-entity-id>
    <updated-at type="datetime">2012-05-10T12:52:48+02:00</updated-at>
    <id type="integer">12</id>
    <value>3600</value>
    <reply-attribute>Session-Timeout</reply-attribute>
  </radius-reply>
  <radius-reply>
    <radius-entity-type>AccountCommon</radius-entity-type>
    <created-at type="datetime">2012-05-15T10:03:48+02:00</created-at>
    <op>=</op>
    <radius-entity-id type="integer">1</radius-entity-id>
    <updated-at type="datetime">2012-05-15T10:03:48+02:00</updated-at>
    <id type="integer">13</id>
    <value>10240</value>
    <reply-attribute>WISPr-Bandwidth-Max-Up</reply-attribute>
  </radius-reply>
</radius-replies>
```

Update

HTTP Request

Verb	URLs	POSTDATA (XML)
PUT	/users/: user_id /radius_replies/: id .xml /users/: username /radius_replies/: id .xml	<pre><radius-reply> <reply-attribute>New RADIUS REPLY ATTRIBUTE</reply-attribute> <op>New RADIUS REPLY OPERATOR</op> <value>New RADIUS REPLY VALUE</value> </radius-reply></pre>

HTTP Response

HTTP Code	Meaning	Content
200	OK	
404	NOT FOUND	
422	UNPROCESSABLE ENTITY	<pre><?xml version="1.0" encoding="UTF-8"?> <errors> <error>error1</error> <error>error2</error> ... <error>errorN</error> </errors></pre>

Examples

Failed request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X PUT http://localhost:3000/users/1/radius_replies/
11.xml?locale=en -d "
<radius-reply>
  <value></value>
</radius-reply>
"
HTTP/1.1 422
X-Ua-Compatible: IE=Edge
Location: http://localhost:3000/users/1
Connection: Keep-Alive
Content-Type: application/xml; charset=utf-8
Date: Tue, 15 May 2012 08:11:36 GMT
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)
X-Runtime: 0.395970
Content-Length: 96
Cache-Control: no-cache
Set-Cookie: _session_id=0ce8eb422d8c00a231e415d1e09e92e3; path=/; HttpOnly

<?xml version="1.0" encoding="UTF-8"?>
<errors>
  <error>Value can't be blank</error>
</errors>
```

Successful request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X PUT http://localhost:3000/users/1/radius_replies/
11.xml?locale=en -d "
<radius-reply>
  <value>4096</value>
</radius-reply>
"
HTTP/1.1 200 OK
X-Ua-Compatible: IE=Edge
Connection: Keep-Alive
Content-Type: application/xml; charset=utf-8
Date: Tue, 15 May 2012 08:12:17 GMT
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)
X-Runtime: 0.453938
Content-Length: 1
Cache-Control: no-cache
Set-Cookie: _session_id=31c8c996491c4a1e04e73c8e15b79b28; path=/; HttpOnly
```

Destroy

HTTP Request

Verb	URLs	POSTDATA (XML)
DELETE	/users/: user_id /radius_replies/: id .xml /users/: username /radius_replies/: id .xml	

HTTP Response

HTTP Code	Meaning	Content
200	OK	
404	NOT FOUND	

Examples

Failed request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X DELETE http://localhost:3000/users/1/radius_replies/11.xml?locale=en
HTTP/1.1 404 Not Found
X-Ua-Compatible: IE=Edge
Connection: Keep-Alive
Content-Type: text/html; charset=utf-8
Date: Tue, 15 May 2012 08:16:05 GMT
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)
X-Runtime: 0.371625
Content-Length: 1
Cache-Control: no-cache
Set-Cookie: _session_id=ab83aa46540ba5f98a3d304cc405927b; path=/; HttpOnly
```

Successful request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X DELETE http://localhost:3000/users/1/radius_replies/11.xml?locale=en
HTTP/1.1 200 OK
X-Ua-Compatible: IE=Edge
Connection: Keep-Alive
Content-Type: application/xml; charset=utf-8
Date: Tue, 15 May 2012 08:16:02 GMT
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)
X-Runtime: 0.462937
Content-Length: 1
Cache-Control: no-cache
Set-Cookie: _session_id=f43af7dabcb0e4c2cb4c57cbb5804b1; path=/; HttpOnly
```

RADIUS Groups' Radius Checks

External documentation

<http://wiki.freeradius.org/Operators>

Create

Required roles

radius_checks_creator

HTTP Request

Verb	URLs	POSTDATA (XML)
POST	/radius_groups/:radius_group_id/radius_checks.xml	<pre><radius-check> <check-attribute>RADIUS CHECK ATTRIBUTE</check-attribute> <op>RADIUS CHECK OPERATOR</op> <value>RADIUS CHECK VALUE</value> </radius-check></pre>

HTTP Response

HTTP Code	Meaning	Content
200	OK	<pre><?xml version="1.0" encoding="UTF-8"?> <radius-check> <radius-entity-type>AccountCommon</radius-entity-type> <created-at type="datetime">CREATION DATE</created-at> <op>RADIUS CHECK OPERATOR</op> <radius-entity-id type="integer">USER_ID</radius-entity-id> <updated-at type="datetime">UPDATE DATE</updated-at> <id type="integer">ID</id> <value>RADIUS CHECK VALUE</value> <check-attribute>RADIUS CHECK ATTRIBUTE</check-attribute> </radius-check></pre>
422	UNPROCESSABLE ENTITY	<pre><?xml version="1.0" encoding="UTF-8"?> <errors> <error>error1</error> <error>error2</error> ... <error>errorN</error> </errors></pre>

Examples

Failed request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X POST http://localhost:3000/radius_groups/4/radius_checks.xml?locale=en -d "
<radius-check>
  <check-attribute>Max-Daily-Session</check-attribute>
  <op>invalid operator</op>
  <value>360</value>
</radius-check>
"
HTTP/1.1 422
X-Ua-Compatible: IE=Edge
Location: http://localhost:3000/radius_groups/4
Connection: Keep-Alive
Content-Type: application/xml; charset=utf-8
Date: Tue, 15 May 2012 08:21:32 GMT
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)
X-Runtime: 0.377727
Content-Length: 106
Cache-Control: no-cache
Set-Cookie: _session_id=5f74dfe82d209d308eff1d394a499e45; path=/; HttpOnly

<?xml version="1.0" encoding="UTF-8"?>
<errors>
  <error>Op is not included in the list</error>
</errors>
```

Successful request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X POST http://localhost:3000/radius_groups/4/radius_checks.xml?locale=en -d "
<radius-check>
  <check-attribute>Max-Daily-Session</check-attribute>
  <op>=</op>
  <value>360</value>
</radius-check>
"
HTTP/1.1 201 Created
X-Ua-Compatible: IE=Edge
Location: http://localhost:3000/radius_groups/4
Connection: Keep-Alive
Content-Type: application/xml; charset=utf-8
Date: Tue, 15 May 2012 08:21:52 GMT
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)
X-Runtime: 0.645789
Content-Length: 438
Cache-Control: no-cache
Set-Cookie: _session_id=8a3556aa0172340bb3592eee2aec1634; path=/; HttpOnly

<?xml version="1.0" encoding="UTF-8"?>
<radius-check>
  <radius-entity-type>RadiusGroup</radius-entity-type>
  <created-at type="datetime">2012-05-15T10:21:51+02:00</created-at>
  <op>=</op>
  <radius-entity-id type="integer">4</radius-entity-id>
  <updated-at type="datetime">2012-05-15T10:21:51+02:00</updated-at>
  <id type="integer">25</id>
  <value>360</value>
  <check-attribute>Max-Daily-Session</check-attribute>
</radius-check>
```

Read

HTTP Request - List

Verb	URLs	POSTDATA (XML)
GET	/radius_groups/:radius_group_id/radius_checks.xml	

HTTP Response - List

HTTP Code	Meaning	Content
200	OK	<pre><?xml version="1.0" encoding="UTF-8"?> <radius-checks type="array"> <radius-check> <radius-entity-type>AccountCommon</radius-entity-type> <created-at type="datetime">CREATION DATE</created-at> <op>RADIUS CHECK OPERATOR</op> <radius-entity-id type="integer">USER_ID</radius-entity-id> <updated-at type="datetime">UPDATE DATE</updated-at> <id type="integer">ID</id> <value>RADIUS CHECK VALUE</value> <check-attribute>RADIUS CHECK ATTRIBUTE</check-attribute> </radius-check> ... <radius-check> <radius-entity-type>AccountCommon</radius-entity-type> <created-at type="datetime">Another CREATION DATE</created-at> <op>Another RADIUS CHECK OPERATOR</op> <radius-entity-id type="integer">USER_ID</radius-entity-id> <updated-at type="datetime">Another UPDATE DATE</updated-at> <id type="integer">Another ID</id> <value>Another RADIUS CHECK VALUE</value> <check-attribute>Another RADIUS CHECK ATTRIBUTE</check-attribute> </radius-check> </radius-checks></pre>
404	NOT FOUND	

HTTP Request - Show

Verb	URLs	POSTDATA (XML)
GET	/radius_groups/:radius_group_id/radius_checks/:id.xml	

HTTP Response - Show

HTTP Code	Meaning	Content
200	OK	<pre><?xml version="1.0" encoding="UTF-8"?> <radius-check> <radius-entity-type>AccountCommon</radius-entity-type> <created-at type="datetime">CREATION DATE</created-at> <op>RADIUS CHECK OPERATOR</op> <radius-entity-id type="integer">USER_ID</radius-entity-id> <updated-at type="datetime">UPDATE DATE</updated-at> <id type="integer">ID</id> <value>RADIUS CHECK VALUE</value> <check-attribute>RADIUS CHECK ATTRIBUTE</check-attribute> </radius-check></pre>
404	NOT FOUND	

Examples

Failed request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X GET http://localhost:3000/radius_groups/
nonexisttaetgroup/radius_checks.xml?locale=en
HTTP/1.1 404 Not Found
X-Ua-Compatible: IE=Edge
Connection: Keep-Alive
Content-Type: text/html; charset=utf-8
Date: Tue, 15 May 2012 08:23:31 GMT
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)
X-Runtime: 0.442479
Content-Length: 1
Cache-Control: no-cache
Set-Cookie: _session_id=f39004aa242f44d51ec71ble7577212e; path=/; HttpOnly
```

Successful request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X GET http://localhost:3000/radius_groups/4/
radius_checks.xml?locale=en
HTTP/1.1 200 OK
X-Ua-Compatible: IE=Edge
Etag: "2942b479761621604d747d7cc64a6b53"
Connection: Keep-Alive
Content-Type: application/xml; charset=utf-8
Date: Tue, 15 May 2012 08:24:08 GMT
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)
X-Runtime: 0.251624
Content-Length: 932
Cache-Control: max-age=0, private, must-revalidate
Set-Cookie: _session_id=72b9d101cad2e018f2472bacd3cb6e7d; path=/; HttpOnly

<?xml version="1.0" encoding="UTF-8"?>
<radius-checks type="array">
  <radius-check>
    <radius-entity-type>RadiusGroup</radius-entity-type>
    <created-at type="datetime">2009-12-28T14:36:50+01:00</created-at>
    <op>=</op>
    <radius-entity-id type="integer">4</radius-entity-id>
    <updated-at type="datetime">2009-12-28T14:36:50+01:00</updated-at>
    <id type="integer">3</id>
    <value>change_me_please!</value>
    <check-attribute>User-Password</check-attribute>
  </radius-check>
  <radius-check>
    <radius-entity-type>RadiusGroup</radius-entity-type>
    <created-at type="datetime">2012-05-15T10:21:51+02:00</created-at>
    <op>=</op>
    <radius-entity-id type="integer">4</radius-entity-id>
    <updated-at type="datetime">2012-05-15T10:21:51+02:00</updated-at>
    <id type="integer">25</id>
    <value>360</value>
    <check-attribute>Max-Daily-Session</check-attribute>
  </radius-check>
</radius-checks>
```

Update

HTTP Request

Verb	URLs	POSTDATA (XML)
PUT	/radius_groups/:radius_group_id/radius_checks/:id.xml	<pre><radius-check> <check-attribute>New RADIUS CHECK ATTRIBUTE</check-attribute> <op>New RADIUS CHECK OPERATOR</op> <value>New RADIUS CHECK VALUE</value> </radius-check></pre>

HTTP Response

HTTP Code	Meaning	Content
200	OK	
404	NOT FOUND	
422	UNPROCESSABLE ENTITY	<pre><?xml version="1.0" encoding="UTF-8"?> <errors> <error>error1</error> <error>error2</error> ... <error>errorN</error> </errors></pre>

Examples

Failed request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X PUT http://localhost:3000/radius_groups/4/
radius_checks/3.xml?locale=en -d "
<radius-check>
  <value></value>
</radius-check>
"
HTTP/1.1 422
X-Ua-Compatible: IE=Edge
Location: http://localhost:3000/radius_groups/4
Connection: Keep-Alive
Content-Type: application/xml; charset=utf-8
Date: Tue, 15 May 2012 08:26:36 GMT
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)
X-Runtime: 0.661261
Content-Length: 96
Cache-Control: no-cache
Set-Cookie: _session_id=982ad3058e980e586081f0550d45ea47; path=/; HttpOnly

<?xml version="1.0" encoding="UTF-8"?>
<errors>
  <error>Value can't be blank</error>
</errors>
```

Successful request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X PUT http://localhost:3000/radius_groups/4/
radius_checks/3.xml?locale=en -d "
<radius-check>
  <value>supercalifragilistichepiralidoso</value>
</radius-check>
"
HTTP/1.1 200 OK
X-Ua-Compatible: IE=Edge
Connection: Keep-Alive
Content-Type: application/xml; charset=utf-8
Date: Tue, 15 May 2012 08:32:33 GMT
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)
X-Runtime: 0.376108
Content-Length: 1
Cache-Control: no-cache
Set-Cookie: _session_id=f42e30e0d934763b6972397cf3412a9f; path=/; HttpOnly
```

Destroy

HTTP Request

Verb	URLs	POSTDATA (XML)
DELETE	/radius_groups/:radius_group_id/radius_checks/:id.xml	

HTTP Response

HTTP Code	Meaning	Content
200	OK	
404	NOT FOUND	

Examples

Failed request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X DELETE http://localhost:3000/radius_groups/4/radius_checks/111.xml?locale=en
HTTP/1.1 404 Not Found
X-Ua-Compatible: IE=Edge
Connection: Keep-Alive
Content-Type: text/html; charset=utf-8
Date: Tue, 15 May 2012 08:35:35 GMT
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)
X-Runtime: 0.170062
Content-Length: 1
Cache-Control: no-cache
Set-Cookie: _session_id=dea94f6593a64304bb9468639abfb884; path=/; HttpOnly
```

Successful request

```
curl -i -u admin:admin -H 'Content-type: text/xml' -X DELETE http://localhost:3000/radius_groups/4/radius_checks/3.xml?locale=en
HTTP/1.1 200 OK
X-Ua-Compatible: IE=Edge
Connection: Keep-Alive
Content-Type: application/xml; charset=utf-8
Date: Tue, 15 May 2012 08:35:59 GMT
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)
X-Runtime: 0.185366
Content-Length: 1
Cache-Control: no-cache
Set-Cookie: _session_id=2e15b51444c904b4b9af16f624fcfdbb; path=/; HttpOnly
```

RADIUS Groups' Radius Replies

External documentation

<http://wiki.freeradius.org/Operators>

Create

Required roles

radius_replies_creator

HTTP Request

Verb	URLs	POSTDATA (XML)
POST	/radius_groups/:radius_group_id/radius_replies.xml	<pre><radius-reply> <reply-attribute>RADIUS REPLY ATTRIBUTE</reply-attribute> <op>RADIUS REPLY OPERATOR</op> <value>RADIUS REPLY VALUE</value> </radius-reply></pre>

HTTP Response

HTTP Code	Meaning	Content
201	CREATED	<pre><?xml version="1.0" encoding="UTF-8"?> <radius-reply> <radius-entity-type>AccountCommon</radius-entity-type> <created-at type="datetime">CREATION DATE</created-at> <op>RADIUS REPLY OPERATOR</op> <radius-entity-id type="integer">USER_ID</radius-entity-id> <updated-at type="datetime">UPDATE DATE</updated-at> <id type="integer">ID</id> <value>RADIUS REPLY VALUE</value> <reply-attribute>RADIUS REPLY ATTRIBUTE</reply-attribute> </radius-reply></pre>
404	NOT FOUND	
422	UNPROCESSABLE ENTITY	<pre><?xml version="1.0" encoding="UTF-8"?> <errors> <error>error1</error> <error>error2</error> ... <error>errorN</error> </errors></pre>

Examples

Failed request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X POST http://localhost:3000/radius_groups/4/radius_replies.xml?locale=en -d "  
<radius-reply>  
  <reply-attribute>WISPr-Bandwidth-Max-Up</reply-attribute>  
  <op>invalid operator</op>  
  <value>10240</value>  
</radius-reply>  
"  
HTTP/1.1 422  
X-Ua-Compatible: IE=Edge  
Location: http://localhost:3000/radius_groups/4  
Connection: Keep-Alive  
Content-Type: application/xml; charset=utf-8  
Date: Tue, 15 May 2012 09:22:24 GMT  
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)  
X-Runtime: 0.384184  
Content-Length: 106  
Cache-Control: no-cache  
Set-Cookie: _session_id=190339e1c3e3a2fe8b8f4b19190b1e9f; path=/; HttpOnly  
  
<?xml version="1.0" encoding="UTF-8"?>  
<errors>  
  <error>Op is not included in the list</error>  
</errors>
```

Successful request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X POST http://localhost:3000/radius_groups/4/radius_replies.xml?locale=en -d "  
<radius-reply>  
  <reply-attribute>WISPr-Bandwidth-Max-Up</reply-attribute>  
  <op>:=</op>  
  <value>10240</value>  
</radius-reply>  
"  
HTTP/1.1 201 Created  
X-Ua-Compatible: IE=Edge  
Location: http://localhost:3000/radius_groups/4  
Connection: Keep-Alive  
Content-Type: application/xml; charset=utf-8  
Date: Tue, 15 May 2012 09:23:10 GMT  
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)  
X-Runtime: 7.255229  
Content-Length: 445  
Cache-Control: no-cache  
Set-Cookie: _session_id=5a0a70a9a7b2c2b506511205608a785c; path=/; HttpOnly  
  
<?xml version="1.0" encoding="UTF-8"?>  
<radius-reply>  
  <radius-entity-type>RadiusGroup</radius-entity-type>  
  <created-at type="datetime">2012-05-15T11:23:06+02:00</created-at>  
  <op>:=</op>  
  <radius-entity-id type="integer">4</radius-entity-id>  
  <updated-at type="datetime">2012-05-15T11:23:06+02:00</updated-at>  
  <id type="integer">14</id>  
  <value>10240</value>  
  <reply-attribute>WISPr-Bandwidth-Max-Up</reply-attribute>  
</radius-reply>
```

Read

HTTP Request - List

Verb	URLs	POSTDATA (XML)
GET	/radius_groups/:radius_group_id/radius_replies.xml	

HTTP Response - List

HTTP Code	Meaning	Content
200	OK	<pre><?xml version="1.0" encoding="UTF-8"?> <radius-replies type="array"> <radius-reply> <radius-entity-type>AccountCommon</radius-entity-type> <created-at type="datetime">CREATION DATE</created-at> <op>RADIUS REPLY OPERATOR</op> <radius-entity-id type="integer">USER_ID</radius-entity-id> <updated-at type="datetime">UPDATE DATE</updated-at> <id type="integer">ID</id> <value>RADIUS REPLY VALUE</value> <reply-attribute>RADIUS REPLY ATTRIBUTE</reply-attribute> </radius-reply> ... <radius-reply> <radius-entity-type>AccountCommon</radius-entity-type> <created-at type="datetime">Another CREATION DATE</created-at> <op>Another RADIUS REPLY OPERATOR</op> <radius-entity-id type="integer">USER_ID</radius-entity-id> <updated-at type="datetime">Another UPDATE DATE</updated-at> <id type="integer">Another ID</id> <value>Another RADIUS REPLY VALUE</value> <reply-attribute>Another RADIUS REPLY ATTRIBUTE</reply-attribute> </radius-reply> </radius-replies ></pre>
404	NOT FOUND	

HTTP Request - Show

Verb	URLs	POSTDATA (XML)
GET	/radius_groups/:radius_group_id/radius_replies/:id.xml	

HTTP Response - Show

HTTP Code	Meaning	Content
200	OK	<pre><?xml version="1.0" encoding="UTF-8"?> <radius-reply> <radius-entity-type>AccountCommon</radius-entity-type> <created-at type="datetime">CREATION DATE</created-at> <op>RADIUS REPLY OPERATOR</op> <radius-entity-id type="integer">USER ID</radius-entity-id> <updated-at type="datetime">UPDATE DATE</updated-at> <id type="integer">ID</id> <value>RADIUS REPLY VALUE</value> <reply-attribute>RADIUS REPLY ATTRIBUTE</reply-attribute> </radius-reply></pre>
404	NOT FOUND	

Examples

Failed request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X GET http://localhost:3000/radius_groups/
nonexistaetuser/radius_replies.xml?locale=en
HTTP/1.1 404 Not Found
X-Ua-Compatible: IE=Edge
Connection: Keep-Alive
Content-Type: text/html; charset=utf-8
Date: Tue, 15 May 2012 11:07:24 GMT
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)
X-Runtime: 0.666754
Content-Length: 1
Cache-Control: no-cache
Set-Cookie: _session_id=ce548ed493e403289432cf209ec4f3d5; path=/; HttpOnly
```


Successful request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X GET http://localhost:3000/radius_groups/3/
radius_replies.xml?locale=en
HTTP/1.1 200 OK
X-Ua-Compatible: IE=Edge
Etag: "c9120086115377126ff9b0ba31ce83f9"
Connection: Keep-Alive
Content-Type: application/xml; charset=utf-8
Date: Tue, 15 May 2012 11:08:33 GMT
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)
X-Runtime: 0.172419
Content-Length: 916
Cache-Control: max-age=0, private, must-revalidate
Set-Cookie: _session_id=fd72033f69ef410f799105cc7d77c077; path=/; HttpOnly

<?xml version="1.0" encoding="UTF-8"?>
<radius-replies type="array">
  <radius-reply>
    <radius-entity-type>RadiusGroup</radius-entity-type>
    <created-at type="datetime">2009-12-28T14:36:50+01:00</created-at>
    <op>=</op>
    <radius-entity-id type="integer">3</radius-entity-id>
    <updated-at type="datetime">2009-12-28T14:36:50+01:00</updated-at>
    <id type="integer">3</id>
    <value>1200</value>
    <reply-attribute>Idle-Timeout</reply-attribute>
  </radius-reply>
  <radius-reply>
    <radius-entity-type>RadiusGroup</radius-entity-type>
    <created-at type="datetime">2009-12-28T14:36:50+01:00</created-at>
    <op>=</op>
    <radius-entity-id type="integer">3</radius-entity-id>
    <updated-at type="datetime">2009-12-28T14:36:50+01:00</updated-at>
    <id type="integer">4</id>
    <value>1800</value>
    <reply-attribute>Session-Timeout</reply-attribute>
  </radius-reply>
</radius-replies>
```

Update

HTTP Request

Verb	URLs	POSTDATA (XML)
PUT	/radius_groups/:radius_group_id/radius_replies/:id.xml	<pre><radius-reply> <reply-attribute>New RADIUS REPLY ATTRIBUTE</ reply-attribute> <op>New RADIUS REPLY OPERATOR</op> <value>New RADIUS REPLY VALUE</value> </radius-reply></pre>

HTTP Response

HTTP Code	Meaning	Content
200	OK	
404	NOT FOUND	

HTTP Code	Meaning	Content
422	UNPROCESSABLE ENTITY	<pre><?xml version="1.0" encoding="UTF-8"?> <errors> <error>error1</error> <error>error2</error> ... <error>errorN</error> </errors></pre>

Examples

Failed request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X PUT http://localhost:3000/radius_groups/3/
radius_replies/3.xml?locale=en -d "
<radius-reply>
  <value></value>
</radius-reply>
"
HTTP/1.1 422
X-Ua-Compatible: IE=Edge
Location: http://localhost:3000/radius_groups/3
Connection: Keep-Alive
Content-Type: application/xml; charset=utf-8
Date: Tue, 15 May 2012 12:17:35 GMT
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)
X-Runtime: 0.390501
Content-Length: 96
Cache-Control: no-cache
Set-Cookie: _session_id=18fc5dfb0f04c4c75596cbe14af4a3e7; path=/; HttpOnly

<?xml version="1.0" encoding="UTF-8"?>
<errors>
  <error>Value can't be blank</error>
</errors>
```

Successful request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X PUT http://localhost:3000/radius_groups/3/
radius_replies/3.xml?locale=en -d "
<radius-reply>
  <value>testvalue</value>
</radius-reply>
"
HTTP/1.1 200 OK
X-Ua-Compatible: IE=Edge
Connection: Keep-Alive
Content-Type: application/xml; charset=utf-8
Date: Tue, 15 May 2012 12:17:57 GMT
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)
X-Runtime: 0.877199
Content-Length: 1
Cache-Control: no-cache
Set-Cookie: _session_id=ccc1c2453af44ba20f068df3c30515ba; path=/; HttpOnly
```

Destroy

HTTP Request

Verb	URLs	POSTDATA (XML)
DELETE	/radius_groups/:radius_group_id/radius_replies/:id.xml	

HTTP Response

HTTP Code	Meaning	Content
200	OK	
404	NOT FOUND	

Examples

Failed request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X DELETE http://localhost:3000/radius_groups/3/radius_replies/3.xml?locale=en
HTTP/1.1 404 Not Found
X-Ua-Compatible: IE=Edge
Connection: Keep-Alive
Content-Type: text/html; charset=utf-8
Date: Tue, 15 May 2012 12:18:35 GMT
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)
X-Runtime: 0.210340
Content-Length: 1
Cache-Control: no-cache
Set-Cookie: _session_id=78ce415f4c3a5f0cfc74e8b2762f2657; path=/; HttpOnly
```

Successful request

```
# curl -i -u admin:admin -H 'Content-type: text/xml' -X DELETE http://localhost:3000/radius_groups/3/radius_replies/3.xml?locale=en
HTTP/1.1 200 OK
X-Ua-Compatible: IE=Edge
Connection: Keep-Alive
Content-Type: application/xml; charset=utf-8
Date: Tue, 15 May 2012 12:18:35 GMT
Server: WEBrick/1.3.1 (Ruby/1.8.7/2011-02-18)
X-Runtime: 0.201142
Content-Length: 1
Cache-Control: no-cache
Set-Cookie: _session_id=9e6cf4a771cbe2f72f843788ef614668; path=/; HttpOnly
```