

PThreads

dr. Andrea E. Naimoli

Università degli Studi di Trento
Dipartimento di Ingegneria e Scienza dell'Informazione
via Sommarive 14
I - 38050 Trento - Povo, Italy

Concurrent programming

- Threads, like processes, allow a program to do more than one thing at a time
- The linux kernel schedules processes and threads asynchronously, interrupting each of them from time to time to give others a chance to execute.

Threads

- After the invocation of a program, Linux kernel creates a new process and in that process creates a single thread.
- The program is run sequentially.
- The thread can create additional threads
 - The new threads run the same program in the same process
 - Each thread may be executing a different part of the program

Process and threads

- `fork()` generates a child process by copying the virtual memory, file descriptors, etc.
- The child process cannot interact with the memory of the parent (and vice-versa).
 - There is no shared memory
 - Process communication is achieved by means of PIPE/FIFO
- When a process creates a new thread **nothing is copied**.
- The creating and the (new) created thread share the same memory space, file descriptors, and other system resources.
- If a thread changes the value of a variable, closes a file descriptor then other threads share the result of the operation.

Pthreads

- POSIX Threads, usually referred to as Pthreads, is a POSIX standard for threads.
- The standard, POSIX.1c, Threads extensions (IEEE Std 1003.1c-1995), defines an API for creating and manipulating threads.
- Each thread is identified by a thread ID, all the threads have the same PID (getpid()).
- The thread ID is referred in C by the variable type: **pthread_t**

Pthread execution

- Upon execution, each thread executes a thread function.
- The function contains the code that the thread should run.
- The life of the thread begins and ends with the execution of the function.
- The function accepts a **void*** parameter and returns a **void***.

Pthread creation

```
void* func(void* arg)
{return NULL;}
```

```
int main()
{
    pthread_t thread_id;
    pthread_create (&thread_id, NULL, &func, &arg);
}
```

- The argument **arg** is passed to the function **func** by means of the **pthread_create**.
- **pthread_create** returns immediately and the original thread continues the execution.

Pthread joining

```
pthread_join (thread_id, NULL);
```


- The main thread might wait for another one.
- pthread_join allows the main thread to wait for the thread with thread ID thread_id.
- The second argument is constituted by the thread return value (NULL in this case).

Pthread – race conditions

- What if multiple threads change the value of the same variable ?

```
...  
pthread_create(..., &pth_func, ...)  
...
```

- Multiple threads access pth_func
- There is no control on concurrency
 - Thread 1 reads var
 - Thread 2 reads var
 - Thread 3 reads var and write var
 - Thread 1, 2 write var
- var value is random



```
void *pth_func()  
{  
    read(var);  
    ...  
    write(var);  
}
```

Pthread semaphores/mutex

- Implementation of concurrencies using *mutex*:

- Define a mutex controller:

```
pthread_mutex_t mutex;
```

- Protect the shared variable with:

```
pthread_mutex_lock(&mutex); // lock mutex
```

```
// Change var value here...
```

```
pthread_mutex_unlock(&mutex); // unlock mutex
```

- Clear the mutex:

```
pthread_mutex_destroy(&mutex);
```

- Retrieve thread identifier:

```
pthread_self();
```