

## EEPROMManager

- outputEnable
- writeEnable
- addresses
- dataIO
- readonlySegments
- hasBeenInit
- TIME\_WAIT\_READ
- TIME\_RECOVERY\_FROM\_READ
- TIME\_HOLD\_WRITE\_SIGNAL
- TIME\_WRITE
- TIME\_RECOVERY\_FROM\_WRITE
- IMPRECISION
- ADDRESSING\_PIN
- DATA\_EXCHANGING\_PIN
- SEGMENT\_DEPTH
- READONLY\_SEGMENTS\_ALLOWED
- READONLY\_SEGMENTS
- PADDING\_CHECK\_ONE
- PADDING\_CHECK\_TWO
- ADDRESSES
- LOWEST\_ADDRESS
- HIGHEST\_ADDRESS
- VALID\_DATA\_VALUES
- LOWEST\_VALID\_DATA\_VALUE
- HIGHEST\_VALID\_DATA\_VALUE

- + EEPROMManager()
- + EEPROMManager()
- + ~EEPROMManager()
- + init()
- + readAddress()
- + readSegment()
- + readAll()
- + writeAddress()
- + writeSegment()
- + writeAll()
- + clear()
- + hardClear()
- setAddress()
- setOutputEnable()
- setWriteEnable()
- setDataIO()
- sample()
- resultStringBuilder()
- format()
- put()
- isReadonly()