

**Travlendar+ project Andrea Mafessoni,
Andrea Mazzeo, Daniele Moltisanti**



POLITECNICO
MILANO 1863

Requirement Analysis and Specification Document

Deliverable:	RASD
Title:	Requirement Analysis and Verification Document
Authors:	Andrea Mafessoni, Andrea Mazzeo, Daniele Moltisanti
Version:	1.0
Date:	29-October-2017
Download page:	https://github.com/AndreaMazzeo289/MafessoniMazzeoMoltisanti.git
Copyright:	Copyright © 2017, Andrea Mafessoni, Andrea Mazzeo, Daniele Moltisanti – All rights reserved

Contents

Table of Contents	3
List of Figures	6
List of Tables	6
1 Introduction	7
1.1 Purpose	7
1.2 Scope	7
1.3 Definition, Acronyms, Abbreviations	7
1.3.1 definition	7
1.3.2 acronyms	8
1.3.3 abbreviations	8
1.4 Revision history	8
1.5 Reference documents	8
1.6 Document structure	8
2 Overall Description	9
2.1 Product perspective	9
2.2 Product functions	9
2.3 User characteristics	9
2.4 Dependencies	10
2.5 Constrains	10
3 Specific Requirements	11
3.1 External interface requirements	11
3.1.1 User interface	11
3.1.2 Software interface	21
3.2 Functional requirements	21
3.2.1 [G1] Allow a Guest to create a registered Travlendar+ account.	21
3.2.2 [G2] Allow an User to log in into his Travlendar+ account.	21
3.2.3 [G3] Allow an User to create a new appointment in his calendar.	21
3.2.4 [G4] Allow an User to delete an existing appointment from his calendar.	21
3.2.5 [G5] Allow an User to edit an existing appointment in his calendar.	22
3.2.6 [G6] Allow an User to view his appointments.	22
3.2.7 [G7] Allow an User to view his Daily Schedule	22
3.2.8 [G8] Allow an User to navigate and choose between different travel alternatives.	23
3.2.9 [G9] Allow an User to manage alerts for each appointment.	23
3.2.10 [G10] Allow an User to manage his travel preferences.	23
3.2.11 [G11] Allow an User to buy public transportation tickets.	24
3.3 Design constraints	24
3.3.1 Standards compliance	24
3.3.2 Hardware limitations	24
3.4 Software system attributes	24
3.4.1 Reliability	24
3.4.2 Availability	24
3.4.3 Security	24
3.4.4 Maintainability	25
3.4.5 Portability	25

4	Scenarios	26
4.1	Scenario 1	26
4.2	Scenario 2	26
4.3	Scenario 3	26
4.4	Scenario 4	26
5	UML modelling	27
5.1	Use case	27
5.1.1	Sign up	28
5.1.2	Log in	29
5.1.3	Manage preferences	29
5.1.4	View daily schedule	30
5.1.5	View travel details	31
5.1.6	Edit travel	31
5.1.7	View specific movement details	32
5.1.8	Choose prior appointment	32
5.1.9	Buy ticket	33
5.1.10	Delete appointment	34
5.1.11	Create appointment	35
5.1.12	Edit appointment	36
5.1.13	Create flexible appointment	37
5.1.14	Create repeatable appointment	37
5.1.15	Create alert	38
5.1.16	Edit alert	39
5.1.17	Delete alert	40
5.1.18	Check appointments on calendar	40
5.1.19	Change calendar view	41
5.1.20	View bought tickets	41
5.2	Sequence diagram	42
5.2.1	Guest registration	42
5.2.2	User Login	43
5.2.3	Appointment creation	44
5.2.4	Appointment editing	45
5.2.5	Appointment deletion	46
5.2.6	Alert editing	47
5.2.7	Alert deletion	48
5.2.8	Scheduling and view travels	49
5.2.9	View and edit movements	50
5.3	Activity diagram	51
5.3.1	Create appointment	51
5.3.2	Edit appointment	52
5.3.3	Delete appointment	53
5.3.4	Create alert	53
5.3.5	Edit travel	54
5.3.6	Buy ticket	55
6	Formal Analysis Using Alloy	56

7	Effort Spent	60
7.1	Hours of work	60
7.1.1	Andrea Mafessoni	60
7.1.2	Andrea Mazzeo	60
7.1.3	Daniele Moltisanti	60

List of Figures

1	Login page	11
2	Connection of an existent account	11
3	Registration form	12
4	Daily view of calendar	12
5	Weekly view of calendar	13
6	Monthly view of calendar	13
7	Menu	14
8	Preferences menu	14
9	Transport means settings	15
10	Travel preferences	15
11	Daily schedule	16
12	New appointment	16
13	New alert	17
14	appointment options	17
15	Edit or delete appointment	18
16	Edit appointment	18
17	Edit or delete alert	19
18	Travel details	19
19	Movement details	20
20	Use case diagram	27

List of Tables

1	Caption for the table.	60
---	------------------------	----

1 Introduction

1.1 Purpose

This document represents the Requirement Analysis and Specification Document (RASD). The goal of this document is to describe the software application and focus on all its features. Furthermore, it's interested to describe the functional and non-functional requirements of the system. Show the constraint, imposed by stakeholders and application environment, the limits of the software. This document is intended to all people that are interested to the project, such as stakeholders, investors and all developer and programmer that have to implement the application.

1.2 Scope

The application to develop is a mobile application that is called Travlendar+. This software is intended to help people with many commitments to manage the calendar on their smartphone. The only action that the user has to do is insert his daily appointments. The application should be able to organize the whole user's day, providing advice and reminding all inserted appointment. The application aims to be an advanced calendar management system, since it isn't a simple appointments reminder but it has a lot functionality that allow to the user to be always well organized. Lot are the functionality that the application provides, such as the complete transport management, that allow to compute the travel time and to identify the better travel solution basing on user's preferences and environment information, such as weather conditions. The user can choose if travel with own car or walk. He can decide to travel also in public transport and the application provides to the user the transport schedules and which transport choose. The system allows also the functionality to buy a ticket in-app. Furthermore, the application is able to find the car sharing or bike sharing points nearest to the user. It has an advices system when the appointment and the travel times overlaps. Daily the application can set a little time window (at most half an hour) reserved for the lunch. As this functionality, the user can schedule little break that the application set in day autonomously.

1.3 Definition, Acronyms, Abbreviations

1.3.1 definition

- **Daily view:**
- **Monthly view:**
- **Weekly view:**
- **Daily schedule:**
- **Appointment:**
- **Alert:**
- **Travel:**
- **Movement:**
- **Unreachability:**
- **Overlapping:**
- **Green:**
- **Cheaper:**

- **Faster:**
- **Repeatable:**
- **Flexible:**

1.3.2 acronyms

- **RASD:** Requirement Analysis and Specification Document.
- **API:** Application Programming Interface.

1.3.3 abbreviations

1.4 Revision history

1.5 Reference documents

1.6 Document structure

This RASD is composed by 5 parts and an appendix:

1. The first part of RASD document is an introduction to the problem. The base information needed to understand the project scope are given in this section.
2. The second part consists of an overall description of the system. Are described the characteristics that regard the user, and all the application boundaries.
3. The third part is composed by the specific requirements identified, both functional and non functional.
4. In the fourth part a list of eight scenarios is provided; each of them describes a particular situation with the system might have to cope with.
5. The fifth part is entirely composed by the UML diagrams that model the system in details.
6. Sixth part is embodied with the Alloy model of the system and includes all the relevant details; a proof of consistency and an example of the generated world are also provided.

2.4 Dependencies

- The application requires a stable internet connection, by Wi-Fi or mobile network.
- The application makes use of GPS localization to access to the user position.
- Based on the user choice, the application may require a connection to an existing Facebook or Google account.
- The application makes use of external APIs to achieve information about maps, public transport and weather condition.
- The application depends entirely on the ATM and Trenord public transport Payment Service for everything concerning the tickets purchase.

2.5 Constrains

- The application requires the user to be registred and logged into the system to work properly.
- The application works only on smartphones that implement Android v. 4.0.3 or later.
- The application is in alpha version and works only inside the urban area of Milan.
- 30 Mb(?) of storage memory must be available on the device in order to correctly install the application.

3 Specific Requirements

3.1 External interface requirements

3.1.1 User interface




Figure 1: Login page






Figure 2: Connection of an existent account



The image shows a mobile app interface for the 'Travlendar+' registration form. At the top, there's a status bar with signal, Wi-Fi, 54% battery, and the time 16:43. Below it is the app's header 'Travlendar+' in orange. The main section is titled 'Registration' in white text on an orange background. The form contains five input fields: 'First Name:', 'Last Name:', 'Email:', 'Password:', and 'Confirm password:'. Below these fields is a grey button with a gear icon and the text 'Preferences'. At the bottom of the form is a large orange button labeled 'Confirm'. The Android navigation bar is visible at the very bottom.

Figure 3: Registration form



The image shows the 'Daily view of calendar' in the 'Travlendar+' app. The status bar at the top shows 54% battery and 16:43. The app header 'Travlendar+' is in orange, with a menu icon on the left and a refresh icon on the right. Below the header is a calendar navigation bar showing days from SAT 7 to WED 11, with 'MON 9' highlighted. The main area displays three events: 'BREAKFAST AT STARBUCKS' at 08:00 with a coffee cup icon, 'LESSON STARTS' from 09:30 - 12:00 with an open book icon, and 'WORK MEETING' at 16:00 with a briefcase icon. At the bottom, there's an orange button with a clock icon and the text 'VIEW DAILY SCHEDULE', and a circular orange button with a white plus sign. The Android navigation bar is at the bottom.

Figure 4: Daily view of calendar




Figure 5: Weekly view of calendar




Figure 6: Monthly view of calendar




Figure 7: Menu




Figure 8: Preferences menu




Figure 9: Transport means settings




Figure 10: Travel preferences




Figure 11: Daily schedule




Figure 12: New appointment




Figure 13: New alert




Figure 14: appointment options




Figure 15: Edit or delete appointment




Figure 16: Edit appointment




Figure 17: Edit or delete alert




Figure 18: Travel details




Figure 19: Movement details

3.1.2 Software interface

The application makes uses of the following APIs:

- Weather API: <https://openweathermap.org/api>
- Google Maps API: <https://developers.google.com/maps/>
- Trenord API: <https://github.com/bluviolin/TrainMonitor/wiki/API-del-sistema-Viaggiatreno>
- Car2go API: <https://github.com/car2go/openAPI>
- Enjoy API: <https://github.com/mattiaongit/enjoy/blob/master/enjoy.py>
- BikeMi API: <https://github.com/pierlauro/bikemi-unofficial-api>
- MoBike API: <https://github.com/ubahnverleih/WoBike>

3.2 Functional requirements

3.2.1 [G1] Allow a Guest to create a registered Travlendar+ account.

3.2.2 [G2] Allow an User to log in into his Travlendar+ account.

3.2.3 [G3] Allow an User to create a new appointment in his calendar.

- [R9] The user must be logged into the system to access application features.
- [R10] The system must be able to provide the user with an overview of his calendar and the user must be able to view all appointments fixed in a certain period.
- [R11] The user must be able to pick a chosen day from the overview of his calendar.
- [R12] The user must be able to choose the option of creating a new appointment.
- [R13] The system must ask the user to provide all information needed for the creation of a new appointment, such as place and time of start and overall duration.
- [R14] The system must check if an appointment overlaps with other events and must eventually notify it to the user.
- [R15] The user must confirm the creation of the new appointment.
- [R16] The system must save the user modifications in memory and the calendar must be updated.
- [D2] All information provided by the user in the process of appointment creation or modification must be formally corrected.

3.2.4 [G4] Allow an User to delete an existing appointment from his calendar.

- [R17] The appointment intended to be modified must have been previously successfully created and not already deleted.
- [R9] The user must be logged into the system to access application features.
- [R10] The system must be able to provide the user with an overview of his calendar and the user must be able to view all appointments fixed in a certain period.
- [R11] The user must be able to pick a chosen day from the overview of his calendar.

- [R18] The user must be able to choose the option of deleting the appointment.
- [R19] The user must confirm the deletion.
- [R20] The system must remove a deleted appointment from the memory and cancel every alert related to it.
- [R16] The system must save the user modifications in memory and the calendar must be updated.
- [R21] Deleting process is not reversible.

3.2.5 [G5] Allow an User to edit an existing appointment in his calendar.

- [R17] The appointment intended to be modified must have been previously successfully created and not already deleted.
- [R9] The user must be logged into the system to access application features.
- [R10] The system must be able to provide the user with an overview of his calendar and the user must be able to view all appointments fixed in a certain period.
- [R22] The user must be able to select a specific appointment in his calendar.
- [R23] The system must give the user access to all details of a selected appointment and the user must be allowed to edit the information needed.
- [R14] The system must check if an appointment overlaps with other events and must eventually notify it to the user.
- [R24] The user must confirm the modifications.
- [R16] The system must save the user modifications in memory and the calendar must be updated.
- [D2] All information provided by the user in the process of appointment creation or modification must be formally corrected.

3.2.6 [G6] Allow an User to view his appointments.

- [R9] The user must be logged into the system to access application features.
- [R10] The system must be able to provide the user with an overview of his calendar and the user must be able to view all appointments fixed in a certain period.
- [R25] The user must be able to switch between different possible calendar, such as daily calendar, weekly calendar and monthly calendar.

3.2.7 [G7] Allow an User to view his Daily Schedule

- [R9] The user must be logged into the system to access application features.
- [R26] The user must be able to select a specific day from his calendar.
- [R27] The system must be able to provide detailed information about the scheduled travels for a chosen day, showing the trace route and the estimated time required from each movement.
- [R28] The system must be able to choose a route between the possible travel alternatives according to the preferences expressed in the user profile settings and the information about external weather.

- [D3] Travel data are provided by an external agent.
- [D4] Information about weather are provided by an external agent.
- [D5] If the system displays a travel alternative, it means that it's actually possible to successfully perform that travel in the way and in the time displayed.

3.2.8 [G8] Allow an User to navigate and choose between different travel alternatives.

- [R9] The user must be logged into the system to access application features.
- [R26] The user must be able to select a specific day from his calendar.
- [R27] The user must be able to select a specific travel in the chosen day.
- [R28] The system must be able to provide the user with an overview of the possible travel alternatives for the chosen travel, specifying all details for each one.
- [R29] The user must be able to filter the travel alternatives furnished by the system according to defined parameters, such as time of travelling or overall cost.
- [R30] The user must be able to choose a favourite travel option different from the displayed default one.
- [R31] The system must update the daily schedule according to the travel option chosen by the user and the user must be able to see the new updated schedule.
- [D5] If the system displays a travel alternative, it means that it's actually possible to successfully perform the travel in the way and in the time displayed.

3.2.9 [G9] Allow an User to manage alerts for each appointment.

- [R32] The system must give the user the possibility of adding an alert to an appointment while it is being created or modified.
- [R33] The user must be able to choose a desired interval of time for the warning alert.
- [R34] The user must confirm the alert creation and the system must save the insertion in the memory.
- [R35] The user must be able to modify or remove the inserted alert when needed.
- [R36] In case of any alert modification made by the user, the user must confirm the modification and the system must save all changes.
- [D6] If a user creates a new alert, he must receive the notification after the specified amount of time.

3.2.10 [G10] Allow an User to manage his travel preferences.

- [R9] The user must be logged into the system to access application features.
- [R39] The user must be able to access the preferences panel of his account.
- [R40] The system must give the user the possibility of setting various preferences, such as owned and preferred travel means, address of Home and other general travel preferences.
- [R41] The user must be able to edit the provided preferences when needed.

3.2.11 [G11] Allow an User to buy public transportation tickets.

- [R9] The user must be already logged into the system to access his calendar.
- [R26] The user must be able to select a specific day from his calendar.
- [R27] The user must be able to select a specific travel in the chosen day.
- [R37] The system must give to the user the possibility of buying the ticket for the selected travel.
- [R38] The system must save a copy of the bought tickets and the user must be able to view them when needed.
- [D7] The payment process and ticket acquisition is made by an external public transport service.

3.3 Design constraints

3.3.1 Standards compliance

The application must require to the user different permissions:

- Accesso to the calendar;
- Get hit position with GPS;
- Access to device storage.

3.3.2 Hardware limitations

The application, at the moment, runs only on Android 4.0.3 version or newer.

The device needs:

- Internet connection;
- GPS;
- Space for save application in memory.

Actual devices on the market satisfy all these requirements.

3.4 Software system attributes

3.4.1 Reliability

The system must guarantee a 24/7 service.

3.4.2 Availability

The system requires a GPS service and internet connection in order to work properly. When the connection is down the system works with the last updated information available in the device memory.

3.4.3 Security

The application must provide secure storage for all sensitive data inserted by the user. One way to achieve it is the use of cryptographical techniques.

3.4.4 Maintainability

The application now is in beta version, this means that can present some bugs. Certainly, the application will be periodically upgraded and each release allow to remove known bugs and add more functionality. Periodically all information that are stored inside the application must be backed up, in order to reduce danger of lost information in case of malfunction of the application.

3.4.5 Portability

Now the application has been developed only for android device (more specifically only for android version 4.0.3 Ice Cream Sandwich or newer versions). Further developments will lead this application also in iOS devices. Another possible development is the creation of a web site that is synchronized with application, and allow to the user to control their appointment also on desktop pc and laptop.

4 Scenarios

4.1 Scenario 1

Andrea has just booked a last minute flight from Milan Orio al Serio airport to Prague, in Czech Republic, but being not a frequent flyer, he's pretty worried about the idea of losing his plane. Furthermore, he lives far away from the airport and he needs to reach it by public transportation. Two days before his departure, he decides to download Travlendar+ app. He creates a new account by connecting his Facebook profile and fills out the essential account settings, giving his basic preferences (he doesn't have any car or bike and he prefers cheaper travels). Then he creates a new appointment called "Prague" in his calendar, inserting the date of Saturday 11/11/17, the time 13:00 and the location of the airport. He chooses the option "I want to be there..." and select "2 hours before". Then he creates the new appointment. His calendar now shows the "Prague" event, and the app easily displays how to reach the airport in time, by leaving home at 9:32, walking until the nearest metro station, taking the metro until Stazione Centrale and then taking a public bus to the airport at 10:10. Now Andrea feels much more confident!

4.2 Scenario 2

Serena has been using the Travlendar+ app since a couple of weeks. She has just bought a new car that allows her to move through the city in a easier way, and wants the app to consider that when it display the optimal travel solution. She opens the app and moves to the preferences panel of her account. She then select "Travel means owned" and puts a tick in the "car" option. Then, she open her calendar and check her daily schedules for the next three days. Some of the travels suggested by the app are now changed and replaced with faster and more comfortable movements with car.

4.3 Scenario 3

Marco has a scheduled appointment in program for the following day, and the app used to suggest a 7 minutes-movement by bike until the train station. But now the weather widget seems to announce a rainy day, and the app switched to a warmer travel by metro. But Marco is not afraid of rain and likes walking, so he opens the daily schedule, selects the metro movement and checks the possible travel alternatives. He then chooses the option "by walk". The app nows shows the updated schedule, and the system will remember the choice for the future.

4.4 Scenario 4

Riccardo is a pretty absent-minded man, and has a morning full of appointments in schedule for the next day. He has added all the meetings in his calendar, but must absolutely not forget them, so he decides to add an alarm to each of them, in order to remember his commitments. He opens the app and select one by one all his appointments of Tuesday. For each one, he taps on "add an alert to this appointment" and chooses to be warned 15 minutes before the start.

5.1.1 Sign up

Name	Sign up
Actors	Guest
Entry conditions	The guest is on the log in page of the application and clicks on “Register” button.
Flow of events	<ol style="list-style-type: none"> 1. A pop-up shows up asking to the guest if he wants to connect an existing account, such as Google or Facebook, or if he want to create a new account. <ol style="list-style-type: none"> (a) If the guest connects his account, the system accepts the request and creates a new Travlendar+ account based on provided account. (b) If the guest chooses to create a new account, he is redirected to the registration page which contains all the fields to be filled. 2. The guest fills out all the mandatory fields. 3. (Optional) The guest adjusts the preferences settings. 4. The guest clicks on button “Confirm”. 5. The system checks data provided and eventually creates and registers the user account.
Exit conditions	The guest has successfully created a new account and he can log into the system with his credentials.
Exceptions	<ul style="list-style-type: none"> • Email provided is already in use. The system does not proceed in the registration process and the account is not created. It is possible to repeat the procedure. • Data provided are incorrect. The system highlights the incorrect fields and asks the user to repeat the procedure.

5.1.2 Log in

Name	Log in
Actors	User
Entry conditions	The user launches the application and clicks on the “Log In” button.
Flow of events	<ol style="list-style-type: none"> 1. The user inserts his email. 2. The user inserts his password. 3. The user clicks on the “Log In” button.
Exit conditions	The login procedure is successfully completed. The user is logged into the system and is able to access to all the functionalities.
Exceptions	The credentials provided are not associated to any existing account. The login procedure is rejected and the guest is brought back to the login page. It is possible to repeat the procedure.

5.1.3 Manage preferences

Name	Manage preferences
Actors	User
Entry conditions	The user clicks on “Preferences” from the side menu on the homepage.
Flow of events	<ol style="list-style-type: none"> 1. The system shows the preferences settings, that include transport means owned, favorite kind of travel and other advanced options. 2. The user accesses to the desired settings and adjusts the preferences as wanted. 3. The user saves the changes.
Exit conditions	The changes are saved and remembered from the system. The preferences have been updated.
Exceptions	The user clicks on “back” without having confirmed the creation. The new preferences are not saved and the application returns to the homepage. It is possible to repeat the procedure.

5.1.4 View daily schedule

Name	View daily schedule
Actors	User, External APIs
Entry conditions	The user clicks on the “View daily schedule” button while checking an appointment on his calendar.
Flow of events	<ol style="list-style-type: none"> 1. The system receives data from different external APIs about routes, traffic, weather and available transport means and computes the best travel option according to the user preferences. 2. The system provides a graphic overview of all the travels scheduled for the day, with the relative movements. 3. The user checks all the information needed and eventually clicks on a specific travel or movement to get further information.
Exit conditions	User has obtained all the information needed and has clicked “back” to return to the homepage or has selected a specific travel/movement to get further information.
Exceptions	<ul style="list-style-type: none"> • Some of the appointments overlap. The system is not able to compute travels between the appointments and forces the user to choose a prior appointment. • Some of the appointments are not reachable in the allotted time. The system doesn’t show the travel and signals the problem to the user with a warning.

5.1.5 View travel details

Name	View travel details
Actors	User, External APIs
Entry conditions	The user is checking his daily schedule and clicks on a specific travel.
Flow of events	<ol style="list-style-type: none"> 1. The system receives data from different external APIs and collects detailed information about the travel, such as the specific itinerary on the map and the weather conditions. 2. The user is redirected to a new page that displays all the information about the selected travel. 3. The user checks all the information needed and eventually clicks on a specific movement to get further information or buy a ticket.
Exit conditions	User has obtained all the information needed and has clicked “back” to return to the daily schedule or has selected a specific movement to get further information.
Exceptions	No exceptions expected

5.1.6 Edit travel

Name	Edit travel
Actors	User
Entry conditions	The user is checking a specific travel.
Flow of events	<ol style="list-style-type: none"> 1. The user provides modifications to the travel as followed: <ol style="list-style-type: none"> (a) Clicking on the travel preferences and switching to a different alternative. (b) Clicking on a specific movement and changing the transport mean. 2. The user saves the changes.
Exit conditions	The changes are saved and the system displays the new modified travel.
Exceptions	There are no possible alternatives for the selected travel. The system displays a warning to notify the user.

5.1.7 View specific movement details

Name	View specific movement details
Actors	User
Entry conditions	User is checking a specific travel and select a specific movement.
Flow of events	<ol style="list-style-type: none"> 1. The system receives data from different external APIs and collects detailed information about the movement, such as the specific itinerary on the map, the weather conditions and the eventual availability of tickets. 2. The user is redirected to a new page that displays all the information about the selected movement. 3. The user checks all the information needed and eventually proceeds in buying a ticket.
Exit conditions	User has obtained all the information needed and has clicked “back” to return to the travel page or has proceeded in buying a ticket.
Exceptions	No exceptions expected

5.1.8 Choose prior appointment

Name	Choose prior appointment
Actors	User
Entry conditions	The user is checking the schedule and two appointments overlap.
Flow of events	<ol style="list-style-type: none"> 1. The system signals the user the exactly time overlapping of the appointments. 2. The user clicks on the preferred appointment. 3. The system re-computes the daily schedule giving priority to the chosen appointment.
Exit conditions	No more appointments overlap. The system shows the daily schedule without errors.
Exceptions	No exceptions expected

5.1.9 Buy ticket

Name	Buy ticket
Actors	User, Ticket provider
Entry conditions	User is checking a specific movement and clicks on “Buy ticket”
Flow of events	<ol style="list-style-type: none"> 1. The system connects trough APIs to the external system of the ticket provider. 2. The system shows the user a form to fill with all the payment information. 3. The user fills out all the fields and confirm the payment. 4. The system sends information to the ticket provider and waits for confirmation and ticket data.
Exit conditions	Payment is successfully fulfilled and bought tickets are available for the view. The user is brought back to the movement page.
Exceptions	Payment is rejected. The system notifies the user with a warning. It is possible to repeat the procedure.

5.1.10 Delete appointment

Name	Delete appointment
Actors	User
Entry conditions	The user selects a specific appointment in his calendar (through daily or weekly view) and clicks on “Delete” button.
Flow of events	<ol style="list-style-type: none"> 1. A pop-up shows up, asking the user to confirm the deletion. 2. The user confirms the deletion. 3. The system removes all the appointment information from the memory, alert included.
Exit conditions	The appointment has been deleted and removed from the system. The user is redirected to his calendar page, which has been updated with the removal of the appointment.
Exceptions	The user does not confirm the deletion. The appointment has not been deleted and the user is redirected to his calendar page. It is possible to repeat the procedure.

5.1.11 Create appointment

Name	Create appointment
Actors	User
Entry conditions	The user is checking his calendar and clicks on “Create appointment” button.
Flow of events	<ol style="list-style-type: none"> 1. The user is redirected to the appointment creation page, which contains all the fields required to perform the creation. 2. The user fills out all mandatory fields. The following steps aren’t mandatory: <ol style="list-style-type: none"> (a) User chooses among the available icons. (b) User adds an alert to remember the appointment. (c) User clicks on “More options” and provides more detailed options. 3. User confirms the creation. 4. The system saves the appointment information.
Exit conditions	The appointment is created and inserted in the system. The user is redirected to his calendar page, which has been updated with the new appointment.
Exceptions	<ul style="list-style-type: none"> • The user has provided incorrect information: the appointment is not created and the user must repeat the procedure. • The user clicks on “back” without having confirmed the creation. The appointment is not created and the application returns to the calendar page. It is possible to repeat the procedure. • The appointment overlaps with other previously created appointments. The appointment is created and inserted anyway, but the user receives a notification of the overlapping.

5.1.12 Edit appointment

Name	Edit appointment
Actors	User
Entry conditions	The user selects a specific appointment in his calendar (through daily or weekly view) and clicks on “Edit” button.
Flow of events	<ol style="list-style-type: none"> 1. The user is redirected to the appointment editing page which contains all the previously inserted information. 2. The user can perform the following actions: <ol style="list-style-type: none"> (a) Changing the appointment icon. (b) Editing the information. (c) Adding an alert to the appointment. (d) Clicking on “More options” and providing more detailed options. 3. The user saves the changes. 4. The system saves the updated appointment information.
Exit conditions	The changes are saved and the appointment has been modified. The user is redirected to his calendar page, which has been updated with the new information provided.
Exceptions	<ul style="list-style-type: none"> • The user has provided incorrect information: the changes are not saved and the user must repeat the procedure. • The user clicks on “back” without having saved the changes. The appointment has not been modified and the application returns to the calendar page. It is possible to repeat the procedure. • The appointment now overlaps with other previously created appointments. The changes are saved anyway, but the user receives a notification of the overlapping.

5.1.13 Create flexible appointment

Name	Create flexible appointment
Actors	User
Entry conditions	The user is creating/editing an appointment, clicks on “More options” and clicks on the “Flexible” field.
Flow of events	<ol style="list-style-type: none"> 1. A pop-up shows up, containing the fields to be filled. 2. The user fills out the fields, specifying the time range of the appointment. 3. The user confirms the choice.
Exit conditions	The choice is saved for later and the user is back on the More option page. At the end of the creation process, the appointment will be created at a time compatible with the time interval provided.
Exceptions	The user clicks on “back” without having confirmed the choice. The appointment has not been modified and the application returns to the More options page. It is possible to repeat the procedure.

5.1.14 Create repeatable appointment

Name	Create repeatable appointment
Actors	User
Entry conditions	The user is creating/editing an appointment, clicks on “More options” and clicks on the “Flexible” field.
Flow of events	<ol style="list-style-type: none"> 1. A pop-up shows up, containing the fields to be filled. 2. The user fills out the fields, specifying the days in which the appointment is wanted to be created. 3. The user confirms the choice.
Exit conditions	The choice is saved for later and the user is back on the More option page. The appointment is now a repeatable appointment.
Exceptions	The user clicks on “back” without having confirmed the choice. The appointment has not been modified and the application returns to the More options page. It is possible to repeat the procedure.

5.1.15 Create alert

Name	Create alert
Actors	User
Entry conditions	The user is on the appointment creation/editing page and clicks on the “Add alert” button.
Flow of events	<ol style="list-style-type: none"> 1. The user is redirected to the alert creation/editing page. 2. The user fills the field specifying the time of the alert. 3. The user confirms the creation. 4. The system saves the alert information.
Exit conditions	The alert has been created and inserted in the system. The application returns to the appointment creation/editing page and it is now possible to edit the alert.
Exceptions	The user clicks on “back” without having confirmed the creation. The alert is not created and the application returns to the event creation page. It is possible to repeat the procedure.

5.1.16 Edit alert

Name	Edit alert
Actors	User
Entry conditions	The user is on the appointment creation/editing page and clicks on the “Edit alert” button.
Flow of events	<ol style="list-style-type: none"> 1. The user is redirected to the alert creation/editing page. 2. The user replaces needed information with updated ones. 3. The user saves the changes. 4. The system saves the alert information.
Exit conditions	All the changes have been saved and inserted in the system. The application returns to the appointment creation/editing page and it is possible to repeat the procedure.
Exceptions	The user clicks on “back” without having saved the changes. The changes have not been saved and the application returns to the appointment creation/modification page. It is possible to repeat the procedure.

5.1.17 Delete alert

Name	Delete alert
Actors	User
Entry conditions	The user is on the appointment creation/editing page and clicks on the “Edit alert” button.
Flow of events	<ol style="list-style-type: none"> 1. The user is redirected to the alert creation/editing page. 2. The user clicks on “Delete”. 3. The user confirms the deletion. 4. The system removes all the alert information from the memory.
Exit conditions	The alert has been deleted and removed from the system. The application returns to the appointment creation/editing page and it is now possible to add a new alert.
Exceptions	The user does not confirm the deletion. The alert has not been deleted and the application returns to the alert editing page. It is possible to repeat the procedure.

5.1.18 Check appointments on calendar

Name	Check appointments on calendar
Actors	User
Entry conditions	The user is logged in and he is on the homepage of the application.
Flow of events	<ol style="list-style-type: none"> 1. The system shows an overview of the existing appointments. 2. The user moves between the appointments and collects the needed information.
Exit conditions	The user has collected the needed information and moves to a different page.
Exceptions	No exception expected.

5.1.19 Change calendar view


Name	Change calendar view
Actors	User
Entry conditions	The user is on the homepage of the application and he is checking his appointments.
Flow of events	<ol style="list-style-type: none"> 1. The user opens the lateral menu. 2. The user clicks on one of available view (daily, weekly or monthly). 3. The system changes the layout according to the user's choice.
Exit conditions	The layout is changed and the user is back on the calendar view.
Exceptions	No exception expected.

5.1.20 View bought tickets


Name	View bought tickets
Actors	User
Entry conditions	The user is logged into the system and clicks on "My tickets" button on the side menu.
Flow of events	<ol style="list-style-type: none"> 1. The system loads the tickets saved in memory and displays the list to the user. 2. The user chooses a specific ticket and clicks on it. 3. The system displays the full screen ticket.
Exit conditions	The user has checked the needed tickets and clicks "back" to return to the homepage.
Exceptions	No tickets saved in memory. The system notifies the absence of saved tickets to the user.

5.2 Sequence diagram


5.2.1 Guest registration




5.2.2 User Login




5.2.3 Appointment creation




5.2.4 Appointment editing




5.2.5 Appointment deletion




5.2.6 Alert editing




5.2.7 Alert deletion



5.2.8 Scheduling and view travels




5.2.9 View and edit movements




5.3 Activity diagram


5.3.1 Create appointment




5.3.2 Edit appointment




5.3.3 Delete appointment




5.3.4 Create alert



5.3.5 Edit travel



5.3.6 Buy ticket



6 Formal Analysis Using Alloy

```
open util/integer

//-----MODEL:-----/

sig Name {}

sig Place {
  latitude: one Int,
  longitude: one Int,
  name: one Name,
  address: one Name
} {
  latitude > 0
  longitude > 0
}

sig Appointment {
  place: one Place,
  date: one Int,
  time: Int,
  duration: lone Int,
  alert: lone Alert,
  travel: one Travel
} {
  date > 0
  time > 0
  alert.appointment = this
  travel.placeOfArrival = place
}

sig Alert {
  appointment: one Appointment,
  date: one Int,
  time: one Int
} {
  date > 0
  time > 0
  appointment.alert = this
}

sig Calendar {
  appointm
  ents: some Appointment
}

sig User {
  calendar: one Calendar,
  email: one Name,
```



```
password: one Name
}
```

```
sig Movement {
  placeOfDeparture: one Place,
  placeOfArrival: one Place,
  extimatedTime: one Int,
} {
  placeOfDeparture != placeOfArrival
  extimatedTime > 0
}
```

```
sig Travel {
  placeOfDeparture: one Place,
  placeOfArrival: one Place,
  extimatedTime: one Int,
  movements: some Movement,
  alternatives: set Travel
} {
  placeOfDeparture != placeOfArrival
  extimatedTime > 0
}
```

```
//-----FACTS:-----//
```

```
//different users have different email addresses
fact mailUnique {
  no disjoint u1, u2: User | u1.email = u2.email
}
```

```
//different users must have different calendars
fact calendarUnique {
  no disjoint u1, u2: User | u1.calendar = u2.calendar
}
```

```
//no different places with same name, address or coordinates
fact placesAreDifferent {
  no disjoint p1, p2: Place | p1.name = p2.name or
  p1.address = p2.address or
  (p1.latitude = p2.latitude and p1.longitude = p2.longitude)
}
```

```
//a movement cannot exist without its travel
fact noMovementWithoutTravel {
  Travel.movements = Movement
}
```

```

/*
//every travel is related to an appointment or is an alternative to a travel rel
fact noTravelWithoutAppointment {
Travel = Travel.alternatives + Appointment.travel
}
*/

//an appointment cannot exist without its calendar
fact noAppointmentWithoutCalendar {
Calendar.appointments = Appointment
}

//a calendar cannot exist without its user
fact noCalendarWithoutUser {
User.calendar = Calendar
}

//the alert of an appointment cannot be scheduled after the beginning of the app
fact alertBeforeAppointment {
all a: Appointment | a.date < a.alert.date or a.time < a.alert.time
}

//travel alternatives depart from and lead to the same place
fact alternativesAreEquivalent {
all t: Travel | (all t1 : t.alternatives | t1.placeOfDeparture = t.placeOfDeparture)
}

//a travel cant be an alternative of itself
fact alternativesDontContainThemselves {
all t: Travel | (t not in t.alternatives)
}

//alternatives of a travel are also alternatives of the alternatives of the trav
fact alternativesAreSymmetrical {
all t: Travel | (all t1 : t.alternatives | t1.alternatives = t.alternatives + t - t1)
}

//every travel is composed by a sequence of connected movements
fact travelIsMadeByMovements {

//every travel starts with a movement
all t: Travel | (one m: t.movements | m.placeOfDeparture = t.placeOfDeparture)
//every travel ends with a movement
all t: Travel | (one m: t.movements | m.placeOfArrival = t.placeOfArrival)
}

```

```

//the ending of a movement is the beginning of a new one or the end of the travel
all t: Travel | (all m: t.movements | m.placeOfArrival = t.placeOfArrival
or
(one m1: t.movements | m1!=m and m.placeOfArrival = m1.placeOfDeparture))
//the beginning of a movement is the ending of an old one or the beginning of the travel
all t: Travel | (all m: t.movements | m.placeOfDeparture = t.placeOfDeparture
or
(one m1: t.movements | m1!=m and m.placeOfDeparture = m1.placeOfArrival ))
//different movements cannot start or end at the same position
all t: Travel | (no disjoint m1, m2: t.movements | m1.placeOfDeparture = m2.placeOfDeparture
or
m1.placeOfArrival = m2.placeOfArrival )
//no close path
all t: Travel | (no m: t.movements | m.placeOfArrival = t.placeOfDeparture)

}

fact travelTimeSumOfMovementsTime {
all t: Travel | t.estimatedTime = sum (t.movements.estimatedTime)

}

//-----ASSERTIONS:-----//

assert numberOfMovementsPerTravel {
all t: Travel | #t.movements = #t.movements.placeOfDeparture
}

run {} for 4 but exactly 2 Travel, exactly 0 Appointment, exactly 2 Movement

```

7 Effort Spent

7.1 Hours of work

7.1.1 Andrea Mafessoni

Task name	Start date	End date	Hours(h)	Day
RASD	02/10/2017	28/10/2017	34.5	
Thinking about project ideas	02/10/2017	10/10/2017	5	9
3. Specific Requirements (Functional requirements)	05/10/2017	10/10/2017	5	6
4. Scenarios	11/10/2017	14/10/2017	3.5	4
5.1 Uml modelling (Use case)	08/10/2017	20/10/2017	4	13
5.1 Uml modelling (Class diagram)	10/10/2017	20/10/2017	5	11
6. Alloy	14/10/2017	22/10/2017	7	9
Final revision	25/10/2017	28/10/2017	5	9

7.1.2 Andrea Mazzeo

Task name	Start date	End date	Hours(h)	Day
RASD	02/10/2017	28/10/2017	35	
Thinking about project ideas	02/10/2017	10/10/2017	5	9
1. Introduction	04/10/2017	5/10/2017	2.5	1
3. Specific Requirements (User Interface)	06/10/2017	15/10/2017	10	10
3. Specific Requirements (Functional requirements)	07/10/2017	08/10/2017	2.5	2
3.4 Software system attributes	14/10/2017	14/10/2017	1	1
5.3 Activity diagram	10/10/2017	22/10/2017	2	3
5.1 Uml modelling (Use case)	10/10/2017	10/10/2017	2	1
Latex	23/10/2017	28/10/2017	5	6
Final revision	25/10/2017	28/10/2017	5	9

7.1.3 Daniele Moltisanti

Task name	Start date	End date	Hours(h)	Day
RASD	02/10/2017	28/10/2017	33.5	
Thinking about project ideas	02/10/2017	10/10/2017	5	9
2. Overall Description	04/10/2017	06/10/2017	2	2
3. Specific Requirements (Functional requirements)	7/10/2017	10/10/2017	3.5	1
5.1 Uml modelling (Use case)	08/10/2017	15/10/2017	5	8
5.2 Sequence diagram	16/10/2017	24/10/2017	12	9
3.4 Software system attributes	14/10/2017	15/10/2017	1	2
Final revision	25/10/2017	28/10/2017	5	9