

OpenCL SYCL API

Generated by Doxygen 1.8.7

Sun May 25 2014 09:35:02

Contents

1	Main Page	1
2	Todo List	3
3	Module Index	7
3.1	Modules	7
4	Namespace Index	9
4.1	Namespace List	9
5	Hierarchical Index	11
5.1	Class Hierarchy	11
6	Class Index	13
6.1	Class List	13
7	File Index	15
7.1	File List	15
8	Module Documentation	17
8.1	Data access and storage in SYCL	17
8.1.1	Detailed Description	17
8.2	Expressing parallelism through kernels	18
8.2.1	Detailed Description	18
8.2.2	Function Documentation	18
8.2.2.1	kernel_lambda	18
8.2.2.2	parallel_for	18
8.2.2.3	parallel_for	19
8.2.2.4	single_task	19
8.3	Platforms, contexts, devices and queues	20
8.3.1	Detailed Description	20
9	Namespace Documentation	21
9.1	cl Namespace Reference	21

9.1.1	Detailed Description	21
9.2	cl::sycl::access Namespace Reference	21
9.2.1	Detailed Description	21
9.2.2	Enumeration Type Documentation	21
9.2.2.1	target	21
10	Class Documentation	23
10.1	cl::sycl::accessor< dataType, dimensions, mode, target > Struct Template Reference	23
10.1.1	Detailed Description	24
10.1.2	Member Typedef Documentation	25
10.1.2.1	element	25
10.1.3	Member Function Documentation	25
10.1.3.1	operator[]	25
10.1.3.2	operator[]	25
10.1.3.3	operator[]	25
10.1.4	Member Data Documentation	25
10.1.4.1	dimensionality	25
10.2	cl::sycl::buffer< T, dimensions > Struct Template Reference	25
10.2.1	Detailed Description	27
10.2.2	Member Typedef Documentation	27
10.2.2.1	element	27
10.2.3	Constructor & Destructor Documentation	27
10.2.3.1	buffer	27
10.2.3.2	buffer	27
10.2.3.3	buffer	27
10.2.3.4	buffer	28
10.2.4	Member Function Documentation	28
10.2.4.1	get_access	28
10.3	cl::sycl::command_group Struct Reference	28
10.3.1	Detailed Description	28
10.4	cl::sycl::context Struct Reference	28
10.4.1	Detailed Description	29
10.5	cl::sycl::device Struct Reference	29
10.5.1	Detailed Description	29
10.6	cl::sycl::device_selector Struct Reference	29
10.6.1	Detailed Description	30
10.7	cl::sycl::gpu_selector Struct Reference	30
10.7.1	Detailed Description	30
10.8	cl::sycl::group< dims > Struct Template Reference	31
10.8.1	Detailed Description	32

10.8.2	Constructor & Destructor Documentation	32
10.8.2.1	group	32
10.8.3	Member Function Documentation	32
10.8.3.1	get	32
10.8.3.2	get_global_range	32
10.8.3.3	get_local_range	32
10.8.3.4	get_nr_range	33
10.8.3.5	operator[]	33
10.8.4	Member Data Documentation	33
10.8.4.1	dimensionality	33
10.9	cl::sycl::id< dims > Struct Template Reference	33
10.9.1	Detailed Description	34
10.9.2	Constructor & Destructor Documentation	35
10.9.2.1	id	35
10.9.2.2	id	35
10.9.2.3	id	35
10.9.2.4	id	35
10.9.3	Member Function Documentation	35
10.9.3.1	get	35
10.9.3.2	operator[]	35
10.9.4	Member Data Documentation	36
10.9.4.1	dimensionality	36
10.10	cl::sycl::item< dims > Struct Template Reference	36
10.10.1	Detailed Description	37
10.10.2	Constructor & Destructor Documentation	37
10.10.2.1	item	37
10.10.2.2	item	37
10.10.3	Member Function Documentation	37
10.10.3.1	get_local	37
10.10.3.2	get_local	37
10.10.4	Member Data Documentation	38
10.10.4.1	dimensionality	38
10.11	cl::sycl::nd_range< dims > Struct Template Reference	38
10.11.1	Detailed Description	39
10.11.2	Constructor & Destructor Documentation	39
10.11.2.1	nd_range	39
10.11.3	Member Function Documentation	39
10.11.3.1	get_offset	39
10.11.4	Member Data Documentation	39
10.11.4.1	dimensionality	39

10.12 <code>cl::sycl::queue</code> Struct Reference	40
10.12.1 Detailed Description	40
10.13 <code>cl::sycl::range< dims ></code> Struct Template Reference	40
10.13.1 Detailed Description	41
10.13.2 Constructor & Destructor Documentation	42
10.13.2.1 <code>range</code>	42
10.13.3 Member Function Documentation	42
10.13.3.1 <code>get</code>	42
10.13.4 Member Data Documentation	42
10.13.4.1 <code>dimensionality</code>	42
11 File Documentation	43
11.1 <code>include/CL/sycl.hpp</code> File Reference	43
Index	45

Chapter 1

Main Page

This is a simple C++ sequential OpenCL SYCL C++ header file to experiment with the OpenCL CL provisional specification.

For more information about OpenCL SYCL: <http://www.khronos.org/opencl/sycl/>

The aim of this file is mainly to define the interface of SYCL so that the specification documentation can be derived from it through tools like Doxygen or Sphinx. This explains why there are many functions and classes that are here only to do some forwarding in some inelegant way. This file is documentation driven and not implementation-style driven.

The source of this file can be found on <https://github.com/amd/triSYCL> and the Doxygen version of the API in <http://amd.github.io/triSYCL/Doxygen/SYCL/html> and <http://amd.github.io/triSYCL/Doxygen/SYCL/SYCL-API-refman.pdf>

Ronan.Keryell at AMD point com

This file is distributed under the University of Illinois Open Source License. See LICENSE.TXT for details.

Chapter 2

Todo List

Namespace `cl::sycl::access`

This values should be normalized to allow separate compilation with different implementations?

Class `cl::sycl::accessor< dataType, dimensions, mode, target >`

Implement it for images according so section 3.3.4.5

Member `cl::sycl::accessor< dataType, dimensions, mode, target >::dimensionality`

in the specification: store the dimension for user request

Member `cl::sycl::accessor< dataType, dimensions, mode, target >::element`

in the specification: store the types for user request as STL

Member `cl::sycl::accessor< dataType, dimensions, mode, target >::operator[] (id< dimensionality > Index) const`

Implement the "const dataType &" version in the case the accessor is not for writing, as required by the specification

Member `cl::sycl::accessor< dataType, dimensions, mode, target >::operator[] (size_t Index) const`

This is not in the specification but looks like a cool common feature. Or solving it with an implicit constructor of `id<1>?`

Member `cl::sycl::accessor< dataType, dimensions, mode, target >::operator[] (item< dimensionality > Index) const`

Add in the specification because use by HPC-GPU slide 22

Class `cl::sycl::buffer< T, dimensions >`

there is a naming inconsistency in the specification between buffer and accessor on T versus datatype

Member `cl::sycl::buffer< T, dimensions >::buffer (const T *start_iterator, const T *end_iterator)`

Member `cl::sycl::buffer< T, dimensions >::element`

Extension to SYCL specification: provide pieces of STL container interface?

Class `cl::sycl::device`

The implementation is quite minimal for now. :-)

Class `cl::sycl::gpu_selector`

to be implemented

to be named `device_selector::gpu` instead in the specification?

Member `cl::sycl::group< dims >::dimensionality`

add this `Boost::multi_array` or STL concept to the specification?

Member `cl::sycl::group< dims >::get (int index)`

add it to the specification?

is it supposed to be an int? A `cl_int`? a `size_t`?

Member `cl::sycl::group< dims >::get_global_range()`

Update the specification to return a `range<dims>` instead of an `id<>`

Member `cl::sycl::group< dims >::get_local_range()`

Update the specification to return a `range<dims>` instead of an `id<>`

Member `cl::sycl::group< dims >::get_nr_range()`

Why the offset is not available here?

Also provide this access to the current `nd_range`

Member `cl::sycl::group< dims >::group(const group &g)`

in the specification, only provide a copy constructor. Any other constructors should be unspecified

Member `cl::sycl::group< dims >::operator[] (int index)`

add it to the specification?

is it supposed to be an int? A `cl_int`? a `size_t`?

Class `cl::sycl::id< dims >`

The definition of `id` and `item` seem completely broken in the current specification. The whole 3.4.1 is to be updated.

It would be nice to have `[]` working everywhere, provide both `get_...()` and `get_...(int dim)` equivalent to `get_...()[int dim]` Well it is already the case for `item`. So not needed for `id`? Indeed `[]` is mentioned in text of page 59 but not in class description.

Member `cl::sycl::id< dims >::dimensionality`

add this `Boost::multi_array` or STL concept to the specification?

Member `cl::sycl::id< dims >::get (int index)`

is it supposed to be an int? A `cl_int`? a `size_t`?

Member `cl::sycl::id< dims >::id (std::initializer_list< std::intptr_t > l)`

Add this to the specification? Since it is said to be usable as a `std::vector<>...`

Member `cl::sycl::id< dims >::id ()`

Add it to the specification?

Member `cl::sycl::id< dims >::id (const range< dims > &r)`

Is this necessary?

why in the specification `id<int dims>(range<dims>global_size, range<dims> local_size) ?`

Member `cl::sycl::id< dims >::id (std::intptr_t s)`

Extension to the specification

Member `cl::sycl::id< dims >::operator[] (int index)`

explain in the specification (table 3.29, not only in the text) that `[]` works also for `id`, and why not `range`?

add also `[]` for `range` in the specification

is it supposed to be an int? A `cl_int`? a `size_t`?

Class `cl::sycl::item< dims >`

Add to the specification: `get_nd_range()` to be coherent with providing `get_local...()` and `get_global...()` and what about the offset?

Member `cl::sycl::item< dims >::dimensionality`

add this `Boost::multi_array` or STL concept to the specification?

Member `cl::sycl::item< dims >::item (nd_range< dims > ndr)`

a constructor from a `nd_range` too in the specification if the previous one has a meaning?

Member `cl::sycl::item< dims >::item (range< dims > global_size, range< dims > local_size)`

what is the meaning of this constructor for a programmer?

Member `cl::sycl::kernel_lambda (Functor F)`

This seems to have also the `kernel_functor` name in the specification

Class `cl::sycl::nd_range< dims >`

add copy constructors in the specification

Member `cl::sycl::nd_range< dims >::dimensionality`

add this Boost::multi_array or STL concept to the specification?

Member `cl::sycl::nd_range< dims >::get_offset ()`

get_offset() is lacking in the specification

Member `cl::sycl::parallel_for (range< Dimensions > r, ParallelForFunctor f)`

It is not clear if the ParallelForFunctor is called with an id<> or with an item. Let's use id<> when called with a range<> and item<> when called with a nd_range<>

Member `cl::sycl::parallel_for (nd_range< Dimensions > r, ParallelForFunctor f)`

Add an OpenMP implementation

Deal with incomplete work-groups

Implement with `parallel_for_workgroup()`/`parallel_for_workitem()`

Class `cl::sycl::queue`

The implementation is quite minimal for now. :-)

Class `cl::sycl::range< dims >`

use `std::size_t` dims instead of `int` dims in the specification?

add to the norm this default parameter value?

add to the norm some way to specify an offset?

Member `cl::sycl::range< dims >::dimensionality`

add this Boost::multi_array or STL concept to the specification?

Member `cl::sycl::range< dims >::get (int index)`

explain in the specification (table 3.29, not only in the text) that [] works also for id, and why not range?

add also [] for range in the specification

is it supposed to be an int? A `cl_int`? a `size_t`?

Member `cl::sycl::range< dims >::range (std::initializer_list< std::intptr_t > l)`

This is not the same as the `range(dim1,...)` constructor from the specification

Chapter 3

Module Index

3.1 Modules

Here is a list of all modules:

Data access and storage in SYCL	17
Expressing parallelism through kernels	18
Platforms, contexts, devices and queues	20

Chapter 4

Namespace Index

4.1 Namespace List

Here is a list of all documented namespaces with brief descriptions:

cl	SYCL dwells in the <code>cl::sycl</code> namespace	21
cl::sycl::access	21

Chapter 5

Hierarchical Index

5.1 Class Hierarchy

This inheritance list is sorted roughly, but not completely, alphabetically:

AccessorImpl	
cl::sycl::accessor< dataType, dimensions, mode, target >	23
BufferImpl	
cl::sycl::buffer< T, dimensions >	25
cl::sycl::command_group	28
cl::sycl::context	28
cl::sycl::device	29
cl::sycl::device_selector	29
cl::sycl::gpu_selector	30
GroupImpl	
cl::sycl::group< dims >	31
IdImpl	
cl::sycl::id< dims >	33
ItemImpl	
cl::sycl::item< dims >	36
NDRangeImpl	
cl::sycl::nd_range< dims >	38
cl::sycl::queue	40
RangeImpl	
cl::sycl::range< dims >	40

Chapter 6

Class Index

6.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

cl::sycl::accessor< dataType, dimensions, mode, target >	23
cl::sycl::buffer< T, dimensions >	25
cl::sycl::command_group	28
cl::sycl::context	28
cl::sycl::device	29
cl::sycl::device_selector	29
cl::sycl::gpu_selector	30
cl::sycl::group< dims >	31
cl::sycl::id< dims >	33
cl::sycl::item< dims >	36
cl::sycl::nd_range< dims >	38
cl::sycl::queue	40
cl::sycl::range< dims >	40

Chapter 7

File Index

7.1 File List

Here is a list of all documented files with brief descriptions:

include/CL/ sycl.hpp	43
--	----

Chapter 8

Module Documentation

8.1 Data access and storage in SYCL

Namespaces

- [cl::sycl::access](#)

Classes

- struct [cl::sycl::buffer](#)< T, dimensions >
- struct [cl::sycl::accessor](#)< dataType, dimensions, mode, target >

8.1.1 Detailed Description

8.2 Expressing parallelism through kernels

Classes

- struct `cl::sycl::range< dims >`
- struct `cl::sycl::id< dims >`
- struct `cl::sycl::nd_range< dims >`
- struct `cl::sycl::item< dims >`
- struct `cl::sycl::group< dims >`

Functions

- `template<size_t Dimensions>`
`range< Dimensions > cl::sycl::operator/ (range< Dimensions > dividend, range< Dimensions > divisor)`
- `template<size_t Dimensions>`
`range< Dimensions > cl::sycl::operator* (range< Dimensions > a, range< Dimensions > b)`
- `template<size_t Dimensions>`
`range< Dimensions > cl::sycl::operator+ (range< Dimensions > a, range< Dimensions > b)`
- `template<typename KernelName , typename Functor >`
`Functor cl::sycl::kernel_lambda (Functor F)`
- `void cl::sycl::single_task (std::function< void(void)> F)`
- `template<int Dimensions = 1, typename ParallelForFunctor >`
`void cl::sycl::parallel_for (range< Dimensions > r, ParallelForFunctor f)`
- `template<int Dimensions = 1, typename ParallelForFunctor >`
`void cl::sycl::parallel_for (nd_range< Dimensions > r, ParallelForFunctor f)`
- `template<typename Range , typename Program , typename ParallelForFunctor >`
`void cl::sycl::parallel_for (Range r, Program p, ParallelForFunctor f)`
SYCL parallel_for version that allows a Program object to be specified.
- `template<int Dimensions = 1, typename ParallelForFunctor >`
`void cl::sycl::parallel_for_workgroup (nd_range< Dimensions > r, ParallelForFunctor f)`
SYCL parallel_for_workgroup.
- `template<int Dimensions = 1, typename ParallelForFunctor >`
`void cl::sycl::parallel_for_workitem (group< Dimensions > g, ParallelForFunctor f)`
SYCL parallel_for_workitem.

8.2.1 Detailed Description

8.2.2 Function Documentation

8.2.2.1 `template<typename KernelName , typename Functor > Functor cl::sycl::kernel_lambda (Functor F)`

`kernel_lambda` specify a kernel to be launch with a `single_task` or `parallel_for`

Todo This seems to have also the `kernel_functor` name in the specification

8.2.2.2 `template<int Dimensions = 1, typename ParallelForFunctor > void cl::sycl::parallel_for (range< Dimensions > r, ParallelForFunctor f)`

`SYCL parallel_for` launches a data parallel computation with parallelism specified at launch time by a `range<>`.

This implementation use OpenMP 3 if compiled with the right flag.

Todo It is not clear if the `ParallelForFunctor` is called with an `id<>` or with an `item`. Let's use `id<>` when called with a `range<>` and `item<>` when called with a `nd_range<>`


```
8.2.2.3  template<int Dimensions = 1, typename ParallelForFunctor > void cl::sycl::parallel_for ( nd_range< Dimensions > r,  
ParallelForFunctor f )
```

A variation of SYCL `parallel_for` to take into account a `nd_range<>`

Todo Add an OpenMP implementation

Todo Deal with incomplete work-groups

Todo Implement with `parallel_for_workgroup()/parallel_for_workitem()`

```
8.2.2.4  void cl::sycl::single_task ( std::function< void(void)> F )
```

SYCL `single_task` launches a computation without parallelism at launch time.

Right now the implementation does nothing else than forwarding the execution of the given functor

8.3 Platforms, contexts, devices and queues

Classes

- struct [cl::sycl::device](#)
- struct [cl::sycl::device_selector](#)
- struct [cl::sycl::gpu_selector](#)
- struct [cl::sycl::context](#)
- struct [cl::sycl::queue](#)
- struct [cl::sycl::command_group](#)

8.3.1 Detailed Description

Chapter 9

Namespace Documentation

9.1 cl Namespace Reference

SYCL dwells in the `cl::sycl` namespace.

9.1.1 Detailed Description

SYCL dwells in the `cl::sycl` namespace.

9.2 cl::sycl::access Namespace Reference

Enumerations

- enum `mode` {
 read = 42, **write**, **atomic**, **read_write**,
 discard_read_write }
This describes the type of the access mode to be used via accessor.
- enum `target` {
 global_buffer = 2014, **constant_buffer**, **local**, **image**,
 host_buffer, **host_image**, **image_array**, **cl_buffer**,
 cl_image }

9.2.1 Detailed Description

Describe the type of access by kernels.

Todo This values should be normalized to allow separate compilation with different implementations?

9.2.2 Enumeration Type Documentation

9.2.2.1 enum `cl::sycl::access::target`

The target enumeration describes the type of object to be accessed via the accessor


Chapter 10

Class Documentation


10.1 `cl::sycl::accessor< dataType, dimensions, mode, target >` Struct Template Reference

```
#include <sycl.hpp>
```

Inheritance diagram for `cl::sycl::accessor< dataType, dimensions, mode, target >`:



Collaboration diagram for `cl::sycl::accessor< dataType, dimensions, mode, target >`:



Public Types

- using `element` = `dataType`
- using `value_type` = `dataType`
- using `Impl` = `AccessorImpl< dataType, dimensions, mode, target >`

Public Member Functions

- `accessor` (`buffer< dataType, dimensions > &targetBuffer`)
Create an accessor to the given buffer.
- `dataType & operator[]` (`id< dimensionality > Index`) `const`
- `dataType & operator[]` (`size_t Index`) `const`
- `dataType & operator[]` (`item< dimensionality > Index`) `const`

Static Public Attributes

- static `const auto dimensionality` = `dimensions`

10.1.1 Detailed Description

```
template<typename dataType, size_t dimensions, access::mode mode, access::target target = access::global_buffer>struct cl_
::sycl::accessor< dataType, dimensions, mode, target >
```

The accessor abstracts the way buffer data are accessed inside a kernel in a multidimensional variable length array way.

Todo Implement it for images according so section 3.3.4.5

10.1.2 Member Typedef Documentation

10.1.2.1 `template<typename dataType , size_t dimensions, access::mode mode, access::target target = access::global_buffer>
using cl::sycl::accessor< dataType, dimensions, mode, target >::element = dataType`

Todo in the specification: store the types for user request as STL

10.1.3 Member Function Documentation

10.1.3.1 `template<typename dataType , size_t dimensions, access::mode mode, access::target target = access::global_buffer>
dataType& cl::sycl::accessor< dataType, dimensions, mode, target >::operator[] (id< dimensionality >
Index) const [inline]`

Get the element specified by the given id

Todo Implement the "const dataType &" version in the case the accessor is not for writing, as required by the specification

10.1.3.2 `template<typename dataType , size_t dimensions, access::mode mode, access::target target = access::global_buffer>
dataType& cl::sycl::accessor< dataType, dimensions, mode, target >::operator[] (size_t Index) const
[inline]`

Get the element specified by the given index in the case we are mono-dimensional

Todo This is not in the specification but looks like a cool common feature. Or solving it with an implicit constructor of id<1>?

10.1.3.3 `template<typename dataType , size_t dimensions, access::mode mode, access::target target = access::global_buffer>
dataType& cl::sycl::accessor< dataType, dimensions, mode, target >::operator[] (item< dimensionality >
Index) const [inline]`

Get the element specified by the given item

Todo Add in the specification because use by HPC-GPU slide 22

10.1.4 Member Data Documentation

10.1.4.1 `template<typename dataType , size_t dimensions, access::mode mode, access::target target = access::global_buffer>
const auto cl::sycl::accessor< dataType, dimensions, mode, target >::dimensionality = dimensions
[static]`

Todo in the specification: store the dimension for user request


The documentation for this struct was generated from the following file:

- `include/CL/sycl.hpp`


10.2 cl::sycl::buffer< T, dimensions > Struct Template Reference

```
#include <sycl.hpp>
```

Inheritance diagram for `cl::sycl::buffer< T, dimensions >`:



Collaboration diagram for `cl::sycl::buffer< T, dimensions >`:



Public Types

- using `element` = `T`
- using `value_type` = `T`
- using `Impl` = `BufferImpl< T, dimensions >`

Public Member Functions

- `buffer` (`const range< dimensions > &r`)
Create a new buffer of size.
- `buffer` (`T *host_data, range< dimensions > r`)
- `buffer` (`const T *host_data, range< dimensions > r`)
- `buffer` (`const T *start_iterator, const T *end_iterator`)
Create a new allocated 1D buffer from the given elements.
- `buffer` (`buffer< T, dimensions > &b`)
Create a new buffer from an old one, with a new allocation.

- `template<access::mode mode, access::target target = access::global_buffer>
accessor< T, dimensions, mode,
target > get_access ()`

Return an accessor of the required mode.

10.2.1 Detailed Description

`template<typename T, int dimensions> struct cl::sycl::buffer< T, dimensions >`

A SYCL buffer is a multidimensional variable length array (à la C99 VLA or even Fortran before) that is used to store data to work on.

In the case we initialize it from a pointer, for now we just wrap the data with `boost::multi_array_ref` to provide the VLA semantics without any storage.

Todo there is a naming inconsistency in the specification between buffer and accessor on T versus datatype

10.2.2 Member Typedef Documentation

10.2.2.1 `template<typename T, int dimensions> using cl::sycl::buffer< T, dimensions >::element = T`

Todo Extension to SYCL specification: provide pieces of STL container interface?

10.2.3 Constructor & Destructor Documentation

10.2.3.1 `template<typename T, int dimensions> cl::sycl::buffer< T, dimensions >::buffer (const range< dimensions > & r) [inline]`

Create a new buffer of size.

Parameters

<i>r</i>	
----------	--

10.2.3.2 `template<typename T, int dimensions> cl::sycl::buffer< T, dimensions >::buffer (T * host_data, range< dimensions > r) [inline]`

Create a new buffer from

Parameters

<i>host_data</i>	of size
<i>r</i>	without further allocation

10.2.3.3 `template<typename T, int dimensions> cl::sycl::buffer< T, dimensions >::buffer (const T * host_data, range< dimensions > r) [inline]`

Create a new read only buffer from

Parameters

<i>host_data</i>	of size
<i>r</i>	without further allocation

10.2.3.4 `template<typename T, int dimensions> cl::sycl::buffer< T, dimensions >::buffer (const T * start_iterator, const T * end_iterator) [inline]`

Create a new allocated 1D buffer from the given elements.

Todo

10.2.4 Member Function Documentation

10.2.4.1 `template<typename T, int dimensions> template<access::mode mode, access::target target = access::global_buffer> accessor<T, dimensions, mode, target> cl::sycl::buffer< T, dimensions >::get_access () [inline]`

Return an accessor of the required mode.

Create a new sub-buffer without allocation to have separate accessors later

Parameters

<i>M</i>	
----------	--

The documentation for this struct was generated from the following file:

- [include/CL/sycl.hpp](#)

10.3 cl::sycl::command_group Struct Reference

```
#include <sycl.hpp>
```

Public Member Functions

- `template<typename Functor >`
`command_group (queue Q, Functor F)`

10.3.1 Detailed Description

SYCL command group gather all the commands needed to execute one or more kernels in a kind of atomic way. Since all the parameters are captured at command group creation, one can execute the content in an asynchronous way and delayed schedule.

For now just execute the command group directly.

The documentation for this struct was generated from the following file:

- [include/CL/sycl.hpp](#)

10.4 cl::sycl::context Struct Reference

```
#include <sycl.hpp>
```

Public Member Functions

- **context** ([gpu_selector](#) s)
- **context** ([device_selector](#) &s)

10.4.1 Detailed Description

SYCL context

The implementation is quite minimal for now. :-)

The documentation for this struct was generated from the following file:

- [include/CL/sycl.hpp](#)

10.5 cl::sycl::device Struct Reference

```
#include <sycl.hpp>
```

10.5.1 Detailed Description

SYCL device

Todo The implementation is quite minimal for now. :-)


The documentation for this struct was generated from the following file:

- [include/CL/sycl.hpp](#)

10.6 cl::sycl::device_selector Struct Reference

```
#include <sycl.hpp>
```

Inheritance diagram for `cl::sycl::device_selector`:



Public Member Functions

- virtual int **operator()** ([device](#) dev)=0

10.6.1 Detailed Description

The SYCL heuristics to select a device

The device with the highest score is selected


The documentation for this struct was generated from the following file:

- [include/CL/sycl.hpp](#)


10.7 cl::sycl::gpu_selector Struct Reference

```
#include <sycl.hpp>
```

Inheritance diagram for cl::sycl::gpu_selector:



Collaboration diagram for cl::sycl::gpu_selector:



Public Member Functions

- `int operator() (device dev) override`

10.7.1 Detailed Description

Select the best GPU, if any

Todo to be implemented

Todo to be named `device_selector::gpu` instead in the specification?


The documentation for this struct was generated from the following file:

- `include/CL/sycl.hpp`


10.8 `cl::sycl::group< dims >` Struct Template Reference

```
#include <sycl.hpp>
```

Inheritance diagram for `cl::sycl::group< dims >`:



Collaboration diagram for `cl::sycl::group< dims >`:



Public Types

- using **Impl** = `GroupImpl< dims >`

Public Member Functions

- `group` (const `group` &g)

- **group** (const NDRangeImpl< dims > &NDR, const IdImpl< dims > &ID)
- **group** (const NDRangeImpl< dims > &NDR)
- **id**< dims > **get_group_id** ()
- **range**< dims > **get_local_range** ()
- **range**< dims > **get_global_range** ()
- **nd_range**< dims > **get_nr_range** ()
- int **get** (int index)
- auto & **operator[]** (int index)

Static Public Attributes

- static const auto **dimensionality** = dims

10.8.1 Detailed Description

template<int dims = 1> struct cl::sycl::group< dims >

A group index used in a parallel_for_workitem to specify a work_group

10.8.2 Constructor & Destructor Documentation

10.8.2.1 template<int dims = 1> cl::sycl::group< dims >::group (const group< dims > & g) [inline]

Todo in the specification, only provide a copy constructor. Any other constructors should be unspecified

10.8.3 Member Function Documentation

10.8.3.1 template<int dims = 1> int cl::sycl::group< dims >::get (int index) [inline]

Return the group coordinate in the given dimension

Todo add it to the specification?

Todo is it supposed to be an int? A cl_int? a size_t?

10.8.3.2 template<int dims = 1> range<dims> cl::sycl::group< dims >::get_global_range () [inline]

Get the local range for this work_group

Todo Update the specification to return a range<dims> instead of an id<>

10.8.3.3 template<int dims = 1> range<dims> cl::sycl::group< dims >::get_local_range () [inline]

Get the local range for this work_group

Todo Update the specification to return a range<dims> instead of an id<>

10.8.3.4 `template<int dims = 1> nd_range<dims> cl::sycl::group< dims >::get_nr_range () [inline]`

Todo Why the offset is not available here?

Todo Also provide this access to the current `nd_range`

10.8.3.5 `template<int dims = 1> auto& cl::sycl::group< dims >::operator[] (int index) [inline]`

Return the group coordinate in the given dimension

Todo add it to the specification?

Todo is it supposed to be an int? A `cl_int`? a `size_t`?

10.8.4 Member Data Documentation

10.8.4.1 `template<int dims = 1> const auto cl::sycl::group< dims >::dimensionality = dims [static]`

Todo add this `Boost::multi_array` or STL concept to the specification?


The documentation for this struct was generated from the following file:

- `include/CL/sycl.hpp`


10.9 cl::sycl::id< dims > Struct Template Reference

```
#include <sycl.hpp>
```

Inheritance diagram for `cl::sycl::id< dims >`:



Collaboration diagram for `cl::sycl::id< dims >`:



Public Types

- using **Impl** = `IdImpl< dims >`

Public Member Functions

- `id()`
- `id(const id &init)`
Create an `id` with the same value of another one.
- `id(const range< dims > &r)`
- `id(const Impl &init)`
- `id(std::initializer_list< std::intptr_t > l)`
- `id(std::intptr_t s)`
- `int get(int index)`
- `auto & operator[] (int index)`

Static Public Attributes

- static const auto `dimensionality` = `dims`

10.9.1 Detailed Description

```
template<int dims = 1>struct cl::sycl::id< dims >
```

Define a multi-dimensional index, used for example to locate a work item

Todo The definition of `id` and `item` seem completely broken in the current specification. The whole 3.4.1 is to be updated.

Todo It would be nice to have `[]` working everywhere, provide both `get_...()` and `get_...(int dim)` equivalent to `get_↔...()[int dim]` Well it is already the case for `item`. So not needed for `id`? Indeed `[]` is mentioned in text of page 59 but not in class description.

10.9.2 Constructor & Destructor Documentation

10.9.2.1 `template<int dims = 1> cl::sycl::id< dims >::id () [inline]`

Create a zero id

Todo Add it to the specification?

10.9.2.2 `template<int dims = 1> cl::sycl::id< dims >::id (const range< dims > & r) [inline]`

Create an id from a given range

Todo Is this necessary?

Todo why in the specification `id<int dims>(range<dims>global_size, range<dims> local_size) ?`

10.9.2.3 `template<int dims = 1> cl::sycl::id< dims >::id (std::initializer_list< std::intptr_t > l) [inline]`

Create a n-D range from a positive integer-like list

Todo Add this to the specification? Since it is said to be usable as a `std::vector<>...`

10.9.2.4 `template<int dims = 1> cl::sycl::id< dims >::id (std::intptr_t s) [inline]`

To have implicit conversion from 1 integer

Todo Extension to the specification

10.9.3 Member Function Documentation

10.9.3.1 `template<int dims = 1> int cl::sycl::id< dims >::get (int index) [inline]`

Return the id size in the given dimension

Todo is it supposed to be an int? A `cl_int`? a `size_t`?

10.9.3.2 `template<int dims = 1> auto& cl::sycl::id< dims >::operator[] (int index) [inline]`

Return the id size in the given dimension

Todo explain in the specification (table 3.29, not only in the text) that `[]` works also for id, and why not range?

Todo add also `[]` for range in the specification

Todo is it supposed to be an int? A `cl_int`? a `size_t`?

10.9.4 Member Data Documentation

10.9.4.1 `template<int dims = 1> const auto cl::sycl::id< dims >::dimensionality = dims` `[static]`

Todo add this Boost::multi_array or STL concept to the specification?


The documentation for this struct was generated from the following file:

- `include/CL/sycl.hpp`


10.10 `cl::sycl::item< dims >` Struct Template Reference

```
#include <sycl.hpp>
```

Inheritance diagram for `cl::sycl::item< dims >`:



Collaboration diagram for `cl::sycl::item< dims >`:



Public Types

- using **Impl** = `ItemImpl< dims >`

Public Member Functions

- `item` (`range< dims > global_size`, `range< dims > local_size`)
- `item` (`nd_range< dims > ndr`)
- `int get_global` (`int dimension`)
Return the global coordinate in the given dimension.
- `int get_local` (`int dimension`)
- `id< dims > get_global` ()
Get the whole global id coordinate.
- `id< dims > get_local` ()
- `range< dims > get_global_range` ()
Get the global range where this item rely in.
- `range< dims > get_local_range` ()
Get the local range (the dimension of the work-group) for this item.

Static Public Attributes

- static const auto `dimensionality` = `dims`

10.10.1 Detailed Description

`template<int dims = 1> struct cl::sycl::item< dims >`

A SYCL item stores information on a work-item within a work-group, with some more context such as the definition ranges.

Todo Add to the specification: `get_nd_range()` to be coherent with providing `get_local...()` and `get_global...()` and what about the offset?

10.10.2 Constructor & Destructor Documentation

10.10.2.1 `template<int dims = 1> cl::sycl::item< dims >::item (range< dims > global_size, range< dims > local_size) [inline]`

Create an item from a local size and local size

Todo what is the meaning of this constructor for a programmer?

10.10.2.2 `template<int dims = 1> cl::sycl::item< dims >::item (nd_range< dims > ndr) [inline]`

Todo a constructor from a `nd_range` too in the specification if the previous one has a meaning?

10.10.3 Member Function Documentation

10.10.3.1 `template<int dims = 1> int cl::sycl::item< dims >::get_local (int dimension) [inline]`

Return the local coordinate (that is in the work-group) in the given dimension

10.10.3.2 `template<int dims = 1> id<dims> cl::sycl::item< dims >::get_local () [inline]`

Get the whole local id coordinate (which is respective to the work-group)

10.10.4 Member Data Documentation

10.10.4.1 `template<int dims = 1> const auto cl::sycl::item< dims >::dimensionality = dims` [static]

Todo add this Boost::multi_array or STL concept to the specification?


The documentation for this struct was generated from the following file:

- `include/CL/sycl.hpp`


10.11 `cl::sycl::nd_range< dims >` Struct Template Reference

```
#include <sycl.hpp>
```

Inheritance diagram for `cl::sycl::nd_range< dims >`:



Collaboration diagram for `cl::sycl::nd_range< dims >`:



Public Types

- using **Impl** = `NDRangeImpl< dims >`

Public Member Functions

- `nd_range` (`range< dims > global_size`, `range< dims > local_size`, `id< dims > offset=id< dims >()`)
- `nd_range` (`const Impl &init`)
- `range< dims > get_global_range ()`
Get the global iteration space range.
- `range< dims > get_local_range ()`
Get the local part of the iteration space range.
- `range< dims > get_group_range ()`
Get the range of work-groups needed to run this ND-range.
- `range< dims > get_offset ()`

Static Public Attributes

- static const auto `dimensionality` = `dims`

10.11.1 Detailed Description

```
template<int dims = 1> struct cl::sycl::nd_range< dims >
```

A ND-range, made by a global and local range, to specify work-group and work-item organization.

The local offset is used to translate the iteration space origin if needed.

Todo add copy constructors in the specification

10.11.2 Constructor & Destructor Documentation

10.11.2.1 `template<int dims = 1> cl::sycl::nd_range< dims >::nd_range (range< dims > global_size, range< dims > local_size, id< dims > offset = id< dims >()) [inline]`

Construct a ND-range with all the details available in OpenCL

By default use a zero offset, that is iterations start at 0

10.11.3 Member Function Documentation

10.11.3.1 `template<int dims = 1> range<dims> cl::sycl::nd_range< dims >::get_offset () [inline]`

Todo `get_offset()` is lacking in the specification

10.11.4 Member Data Documentation

10.11.4.1 `template<int dims = 1> const auto cl::sycl::nd_range< dims >::dimensionality = dims [static]`

Todo add this `Boost::multi_array` or STL concept to the specification?

The documentation for this struct was generated from the following file:

- `include/CL/sycl.hpp`

10.12 cl::sycl::queue Struct Reference

```
#include <sycl.hpp>
```

Public Member Functions

- **queue** ([context](#) c)

10.12.1 Detailed Description

SYCL queue, similar to the OpenCL queue concept.

Todo The implementation is quite minimal for now. :-)


The documentation for this struct was generated from the following file:

- include/CL/[sycl.hpp](#)


10.13 cl::sycl::range< dims > Struct Template Reference

```
#include <sycl.hpp>
```

Inheritance diagram for `cl::sycl::range< dims >`:



Collaboration diagram for cl::sycl::range< dims >:



Public Types

- using **Impl** = RangeImpl< dims >

Public Member Functions

- **range** (range< dims > &r)
- **range** (const range< dims > &r)
- **range** (Impl &r)
- **range** (const Impl &r)
- **range** (std::initializer_list< std::intptr_t > l)
- **range** (std::intptr_t x)
To have implicit conversion from 1 integer.
- **range** (std::intptr_t x, std::intptr_t y)
A 2-D constructor from 2 integers.
- **range** (std::intptr_t x, std::intptr_t y, std::intptr_t z)
A 3-D constructor from 3 integers.
- int **get** (int index)

Static Public Attributes

- static const auto **dimensionality** = dims

10.13.1 Detailed Description

```
template<int dims = 1>struct cl::sycl::range< dims >
```

A SYCL range defines a multi-dimensional index range that can be used to launch parallel computation.

Todo use std::size_t dims instead of int dims in the specification?

Todo add to the norm this default parameter value?

Todo add to the norm some way to specify an offset?

10.13.2 Constructor & Destructor Documentation

10.13.2.1 `template<int dims = 1> cl::sycl::range< dims >::range (std::initializer_list< std::intptr_t > /) [inline]`

Create a n-D range from a positive integer-like list

Todo This is not the same as the `range(dim1,...)` constructor from the specification

10.13.3 Member Function Documentation

10.13.3.1 `template<int dims = 1> int cl::sycl::range< dims >::get (int index) [inline]`

Return the range size in the give dimension

Todo explain in the specification (table 3.29, not only in the text) that `[]` works also for `id`, and why not `range`?

Todo add also `[]` for `range` in the specification

Todo is it supposed to be an `int`? A `cl_int`? a `size_t`?

10.13.4 Member Data Documentation

10.13.4.1 `template<int dims = 1> const auto cl::sycl::range< dims >::dimensionality = dims [static]`

Todo add this `Boost::multi_array` or STL concept to the specification?

The documentation for this struct was generated from the following file:


- `include/CL/sycl.hpp`

Chapter 11

File Documentation

11.1 include/CL/sycl.hpp File Reference

```
#include <cstddef>
#include <initializer_list>
#include "implementation/sycl-implementation.hpp"
Include dependency graph for sycl.hpp:
```



Classes

- struct `cl::sycl::range< dims >`
- struct `cl::sycl::id< dims >`
- struct `cl::sycl::nd_range< dims >`
- struct `cl::sycl::item< dims >`
- struct `cl::sycl::group< dims >`
- struct `cl::sycl::device`
- struct `cl::sycl::device_selector`
- struct `cl::sycl::gpu_selector`
- struct `cl::sycl::context`
- struct `cl::sycl::queue`
- struct `cl::sycl::command_group`
- struct `cl::sycl::buffer< T, dimensions >`
- struct `cl::sycl::accessor< dataType, dimensions, mode, target >`
- struct `cl::sycl::buffer< T, dimensions >`

Namespaces

- `cl`
 - *SYCL dwells in the `cl::sycl` namespace.*
- `cl::sycl::access`

Enumerations

- enum `cl::sycl::access::mode` {
`read` = 42, `write`, `atomic`, `read_write`,
`discard_read_write` }
This describes the type of the access mode to be used via accessor.
- enum `cl::sycl::access::target` {
`global_buffer` = 2014, `constant_buffer`, `local`, `image`,
`host_buffer`, `host_image`, `image_array`, `cl_buffer`,
`cl_image` }

Functions

- template<size_t Dimensions>
range< Dimensions > `cl::sycl::operator/` (range< Dimensions > dividend, range< Dimensions > divisor)
- template<size_t Dimensions>
range< Dimensions > `cl::sycl::operator*` (range< Dimensions > a, range< Dimensions > b)
- template<size_t Dimensions>
range< Dimensions > `cl::sycl::operator+` (range< Dimensions > a, range< Dimensions > b)
- template<typename KernelName , typename Functor >
Functor `cl::sycl::kernel_lambda` (Functor F)
- void `cl::sycl::single_task` (std::function< void(void)> F)
- template<int Dimensions = 1, typename ParallelForFunctor >
void `cl::sycl::parallel_for` (range< Dimensions > r, ParallelForFunctor f)
- template<int Dimensions = 1, typename ParallelForFunctor >
void `cl::sycl::parallel_for` (nd_range< Dimensions > r, ParallelForFunctor f)
- template<typename Range , typename Program , typename ParallelForFunctor >
void `cl::sycl::parallel_for` (Range r, Program p, ParallelForFunctor f)
SYCL parallel_for version that allows a Program object to be specified.
- template<int Dimensions = 1, typename ParallelForFunctor >
void `cl::sycl::parallel_for_workgroup` (nd_range< Dimensions > r, ParallelForFunctor f)
SYCL parallel_for_workgroup.
- template<int Dimensions = 1, typename ParallelForFunctor >
void `cl::sycl::parallel_for_workitem` (group< Dimensions > g, ParallelForFunctor f)
SYCL parallel_for_workitem.
- void `cl::sycl::barrier` (int barrier_type)

Variables

- int const `cl::sycl::CL_LOCAL_MEM_FENCE` = 123

Index

cl, [21](#)

Expressing parallelism through kernels, [18](#)

Platforms, contexts, devices and queues, [20](#)