

ASYMPTOTICALLY OPTIMAL EXPLORATION IN CONTEXTUAL LINEAR BANDITS

Andrea Tirinzoni¹, Matteo Pirotta², Marcello Restelli¹, Alessandro Lazaric²

¹ Politecnico di Milano

² Facebook AI Research

To appear at NeurIPS 2020



POLITECNICO
MILANO 1863

FACEBOOK AI

Contextual Linear Bandits

At each time t , the learner

- Observes *context* $X_t \in \mathcal{X}$, $X_t \sim \rho$
- Plays *arm* $A_t \in \mathcal{A}$
- Receives *reward* $Y_t = \underbrace{\phi(X_t, A_t)^T \theta^*}_{\mu_{\theta^*}(X_t, A_t)} + \mathcal{N}(0, \sigma^2)$ with $\theta^* \in \mathbb{R}^d$ *unknown*

Contextual Linear Bandits

At each time t , the learner

- Observes *context* $X_t \in \mathcal{X}$, $X_t \sim \rho$
- Plays *arm* $A_t \in \mathcal{A}$
- Receives *reward* $Y_t = \underbrace{\phi(X_t, A_t)^T \theta^\star}_{\mu_{\theta^\star}(X_t, A_t)} + \mathcal{N}(0, \sigma^2)$ with $\theta^\star \in \mathbb{R}^d$ *unknown*

Goal: minimize cumulative regret

$$\mathbb{E}[R_n(\theta^\star)] := \mathbb{E} \left[\sum_{t=1}^n \left(\max_{a \in \mathcal{A}} \mu_{\theta^\star}(X_t, a) - \mu_{\theta^\star}(X_t, A_t) \right) \right]$$

Contextual Linear Bandits

At each time t , the learner

- Observes *context* $X_t \in \mathcal{X}$, $X_t \sim \rho$
- Plays *arm* $A_t \in \mathcal{A}$
- Receives *reward* $Y_t = \underbrace{\phi(X_t, A_t)^T \theta^*}_{\mu_{\theta^*}(X_t, A_t)} + \mathcal{N}(0, \sigma^2)$ with $\theta^* \in \mathbb{R}^d$ *unknown*

Goal: minimize cumulative regret

$$\mathbb{E}[R_n(\theta^*)] := \mathbb{E} \left[\sum_{t=1}^n \left(\max_{a \in \mathcal{A}} \mu_{\theta^*}(X_t, a) - \mu_{\theta^*}(X_t, A_t) \right) \right]$$

Assumptions: \mathcal{X}, \mathcal{A} **finite**, $\rho(x) > 0$ for all $x \in \mathcal{X}$, $\theta^* \in \Theta := \{\theta \in \mathbb{R}^d : \|\theta\|_2 \leq B\}$,
unique optimal arm $a_{\theta^*}^*(x)$ for all $x \in \mathcal{X}$

State of the Art

- Algorithms based on **optimism** [Abbasi-Yadkori et al., 2011] or **Thompson sampling** [Agrawal and Goyal, 2013] are **not asymptotically optimal** [Lattimore and Szepesvári, 2017]

State of the Art

- Algorithms based on **optimism** [Abbasi-Yadkori et al., 2011] or **Thompson sampling** [Agrawal and Goyal, 2013] are **not asymptotically optimal** [Lattimore and Szepesvári, 2017]
- Algorithms derived from **asymptotic problem-dependent lower bounds**

OSSB	CROP	SPL	OAM	SOLID
[Combes et al., 2017]	[Jun and Zhang, 2020]	[Degenne et al., 2020]	[Hao et al., 2020]	[ours]

State of the Art

- Algorithms based on **optimism** [Abbasi-Yadkori et al., 2011] or **Thompson sampling** [Agrawal and Goyal, 2013] are **not asymptotically optimal** [Lattimore and Szepesvári, 2017]
- Algorithms derived from **asymptotic problem-dependent lower bounds**

	OSSB [Combes et al., 2017]	CROP [Jun and Zhang, 2020]	SPL [Degenne et al., 2020]	OAM [Hao et al., 2020]	SOLID [ours]
<i>Linear contextual</i>	✗	✗	✗	✓	✓

State of the Art

- Algorithms based on **optimism** [Abbasi-Yadkori et al., 2011] or **Thompson sampling** [Agrawal and Goyal, 2013] are **not asymptotically optimal** [Lattimore and Szepesvári, 2017]
- Algorithms derived from **asymptotic problem-dependent lower bounds**

	OSSB	CROP	SPL	OAM	SOLID
	[Combes et al., 2017]	[Jun and Zhang, 2020]	[Degenne et al., 2020]	[Hao et al., 2020]	[ours]
<i>Linear contextual</i>	✗	✗	✗	✓	✓
<i>Asympt. optimal</i>	✗	✗	✓	✓	✓

State of the Art

- Algorithms based on **optimism** [Abbasi-Yadkori et al., 2011] or **Thompson sampling** [Agrawal and Goyal, 2013] are **not asymptotically optimal** [Lattimore and Szepesvári, 2017]
- Algorithms derived from **asymptotic problem-dependent lower bounds**

	OSSB	CROP	SPL	OAM	SOLID
	[Combes et al., 2017]	[Jun and Zhang, 2020]	[Degenne et al., 2020]	[Hao et al., 2020]	[ours]
<i>Linear contextual</i>	✗	✗	✗	✓	✓
<i>Asympt. optimal</i>	✗	✗	✓	✓	✓
<i>No forced explore</i>	✗	✓	✓	✗	✓

State of the Art

- Algorithms based on **optimism** [Abbasi-Yadkori et al., 2011] or **Thompson sampling** [Agrawal and Goyal, 2013] are **not asymptotically optimal** [Lattimore and Szepesvári, 2017]
- Algorithms derived from **asymptotic problem-dependent lower bounds**

	OSSB	CROP	SPL	OAM	SOLID
	[Combes et al., 2017]	[Jun and Zhang, 2020]	[Degenne et al., 2020]	[Hao et al., 2020]	[ours]
<i>Linear contextual</i>	✗	✗	✗	✓	✓
<i>Asympt. optimal</i>	✗	✗	✓	✓	✓
<i>No forced explore</i>	✗	✓	✓	✗	✓
<i>Efficient/scalable</i>	✗	✗	✓	✗	✓

State of the Art

- Algorithms based on **optimism** [Abbasi-Yadkori et al., 2011] or **Thompson sampling** [Agrawal and Goyal, 2013] are **not asymptotically optimal** [Lattimore and Szepesvári, 2017]
- Algorithms derived from **asymptotic problem-dependent lower bounds**

	OSSB	CROP	SPL	OAM	SOLID
	[Combes et al., 2017]	[Jun and Zhang, 2020]	[Degenne et al., 2020]	[Hao et al., 2020]	[ours]
<i>Linear contextual</i>	✗	✗	✗	✓	✓
<i>Asympt. optimal</i>	✗	✗	✓	✓	✓
<i>No forced explore</i>	✗	✓	✓	✗	✓
<i>Efficient/scalable</i>	✗	✗	✓	✗	✓
<i>Dep. $\log(\mathcal{A})$</i>	✗	✗	✗	✗	✓

State of the Art

- Algorithms based on **optimism** [Abbasi-Yadkori et al., 2011] or **Thompson sampling** [Agrawal and Goyal, 2013] are **not asymptotically optimal** [Lattimore and Szepesvári, 2017]
- Algorithms derived from **asymptotic problem-dependent lower bounds**

	OSSB	CROP	SPL	OAM	SOLID
	[Combes et al., 2017]	[Jun and Zhang, 2020]	[Degenne et al., 2020]	[Hao et al., 2020]	[ours]
<i>Linear contextual</i>	✗	✗	✗	✓	✓
<i>Asympt. optimal</i>	✗	✗	✓	✓	✓
<i>No forced explore</i>	✗	✓	✓	✗	✓
<i>Efficient/scalable</i>	✗	✗	✓	✗	✓
<i>Dep. $\log(\mathcal{A})$</i>	✗	✗	✗	✗	✓
<i>Minimax optimal</i>	✗	✗	✗	✗	✓*

* Only for linear non-contextual problems

Lower Bound

Any **uniformly consistent** bandit strategy satisfies

$$\liminf_{n \rightarrow \infty} \frac{\mathbb{E}[R_n(\theta^*)]}{\log(n)} \geq v^*(\theta^*)$$

where $v^*(\theta^*)$ is the value of the **optimization problem**

$$\begin{aligned} & \inf_{\eta(x,a) \geq 0} \sum_{x \in \mathcal{X}} \sum_{a \in \mathcal{A}} \eta(x,a) \Delta_{\theta^*}(x,a) \\ & \text{s.t.} \quad \inf_{\theta' \in \Theta_{\text{alt}}} \sum_{x \in \mathcal{X}} \sum_{a \in \mathcal{A}} \eta(x,a) d_{x,a}(\theta^*, \theta') \geq 1 \end{aligned} \tag{P}$$

Sub-optimality gap

KL divergence

$$\Theta_{\text{alt}} := \{\theta' \in \Theta \mid \exists x \in \mathcal{X}, a_{\theta^*}^*(x) \neq a_{\theta'}^*(x)\}$$

Lower Bound Reformulation

(1) Constrain number of pulls for each context

$$\begin{aligned}
 & \inf_{\eta(x,a) \geq 0} \quad \sum_{x \in \mathcal{X}} \sum_{a \in \mathcal{A}} \eta(x, a) \Delta_{\theta^*}(x, a) \\
 & \text{s.t.} \quad \inf_{\theta' \in \Theta_{\text{alt}}} \sum_{x \in \mathcal{X}} \sum_{a \in \mathcal{A}} \eta(x, a) d_{x,a}(\theta^*, \theta') \geq 1 \\
 & \quad \sum_a \eta(x, a) = z \rho(x) \quad \forall x \in \mathcal{X}
 \end{aligned}$$

Sample budget z :

$$\sum_{x \in \mathcal{X}} \sum_{a \in \mathcal{A}} \eta(x, a) = z$$

Lower Bound Reformulation

(2) Change of variables $\eta(x, a) \rightarrow z\rho(x)\omega(x, a)$

$$\begin{aligned}
 & \min_{\omega(x,a) \geq 0} \quad z \cdot \sum_{x \in \mathcal{X}} \rho(x) \sum_{a \in \mathcal{A}} \omega(x, a) \Delta_{\theta^*}(x, a) && \text{Expectation under } \rho \\
 & \text{s.t.} \quad \inf_{\theta' \in \Theta_{\text{alt}}} \sum_{x \in \mathcal{X}} \rho(x) \sum_{a \in \mathcal{A}} \omega(x, a) d_{x,a}(\theta^*, \theta') \geq 1/z && (P_z) \\
 & \quad \omega(x, \cdot) \in \Omega \quad \forall x \in \mathcal{X} && \text{Conditional arm probabilities}
 \end{aligned}$$

Probability simplex

Lower Bound Reformulation

(2) Change of variables $\eta(x, a) \rightarrow z\rho(x)\omega(x, a)$

$$\begin{aligned}
 & \min_{\omega(x,a) \geq 0} \quad z \cdot \sum_{x \in \mathcal{X}} \rho(x) \sum_{a \in \mathcal{A}} \omega(x, a) \Delta_{\theta^*}(x, a) && \text{Expectation under } \rho \\
 & \text{s.t.} \quad \inf_{\theta' \in \Theta_{\text{alt}}} \sum_{x \in \mathcal{X}} \rho(x) \sum_{a \in \mathcal{A}} \omega(x, a) d_{x,a}(\theta^*, \theta') \geq 1/z && (P_z) \\
 & \quad \omega(x, \cdot) \in \Omega \quad \forall x \in \mathcal{X} && \text{Conditional arm probabilities}
 \end{aligned}$$

Probability simplex

Lemma

- (P_z) is **feasible** for $1/z \leq \max_{\omega \in \Omega} \inf_{\theta' \in \Theta_{\text{alt}}} \sum_{x \in \mathcal{X}} \rho(x) \sum_{a \in \mathcal{A}} \omega(x, a) d_{x,a}(\theta^*, \theta')$
- Let $u_z^*(\theta^*)$ be the optimal solution of (P_z) , then $u_z^*(\theta^*) \leq v^*(\theta^*) + \mathcal{O}(1/\sqrt{z})$

Lagrangian Relaxation

$$\begin{aligned}
 & \sum_{x \in \mathcal{X}} \rho(x) \sum_{a \in \mathcal{A}} \omega(x, a) \mu_{\theta^*}(x, a) \\
 & \min_{\lambda \geq 0} \max_{\omega \in \Omega} \left\{ f(\omega; \theta^*) + \lambda g(\omega; z, \theta^*) \right\} \quad (P_\lambda) \\
 & \inf_{\theta' \in \Theta_{\text{alt}}} \sum_{x \in \mathcal{X}} \rho(x) \sum_{a \in \mathcal{A}} \omega(x, a) d_{x,a}(\theta^*, \theta') - \frac{1}{z}
 \end{aligned}$$

Initialize $\omega_1, \lambda_1, \hat{\theta}_0, \hat{\rho}_0, z_1$

for $t = 1, 2, \dots, n$ **do**

Receive context $X_t \sim \rho$

if $\inf_{\theta' \in \bar{\Theta}_{t-1}} \|\hat{\theta}_{t-1} - \theta'\|_{\bar{V}_{t-1}}^2 > \beta_{t-1}$ **then**

Exploitation: $A_t \leftarrow \operatorname{argmax}_{a \in \mathcal{A}} \mu_{\hat{\theta}_{t-1}}(X_t, a)$

else

Exploration: sample arm: $A_t \sim \omega_t(X_t, \cdot)$

Optimization: Update $(\lambda_{t+1}, \omega_{t+1})$ by optimistic primal-dual sub-gradient

Phases: Update z_{t+1} (increase after sufficient exploration steps)

end if

Pull A_t and observe outcome Y_t

Estimation: update $\hat{\theta}_t, \hat{\rho}_t$

end for

Theoretical Results

Theorem (Problem-dependent regret bound)

For any finite n , the expected regret of SOLID is bounded as

$$\mathbb{E}[R_n(\theta^*)] \leq v^*(\theta^*) \log n + \mathcal{O}((\log n)^{3/4}) + \mathcal{O}(1)$$

Theoretical Results

Theorem (Problem-dependent regret bound)

For any finite n , the expected regret of SOLID is bounded as

$$\mathbb{E}[R_n(\theta^*)] \leq v^*(\theta^*) \log n + \mathcal{O}((\log n)^{3/4}) + \mathcal{O}(1)$$

- SOLID is **asymptotically optimal**

Theoretical Results

Theorem (Problem-dependent regret bound)

For any finite n , the expected regret of SOLID is bounded as

$$\mathbb{E}[R_n(\theta^*)] \leq v^*(\theta^*) \log n + \mathcal{O}((\log n)^{3/4}) + \mathcal{O}(1)$$

- SOLID is **asymptotically optimal**
- $\mathcal{O}((\log n)^{3/4})$ regret due to *incremental* and *phased* nature (can be improved...)

Theoretical Results

Theorem (Problem-dependent regret bound)

For any finite n , the expected regret of SOLID is bounded as

$$\mathbb{E}[R_n(\theta^*)] \leq v^*(\theta^*) \log n + \mathcal{O}((\log n)^{3/4}) + \mathcal{O}(1)$$

- SOLID is **asymptotically optimal**
- $\mathcal{O}((\log n)^{3/4})$ regret due to *incremental* and *phased* nature (can be improved...)
- $\mathcal{O}(1)$ regret mostly due to the optimization problem initially being *infeasible*

Theoretical Results

Theorem (Problem-dependent regret bound)

For any finite n , the expected regret of SOLID is bounded as

$$\mathbb{E}[R_n(\theta^*)] \leq v^*(\theta^*) \log n + \mathcal{O}((\log n)^{3/4}) + \mathcal{O}(1)$$

- SOLID is **asymptotically optimal**
- $\mathcal{O}((\log n)^{3/4})$ regret due to *incremental* and *phased* nature (can be improved...)
- $\mathcal{O}(1)$ regret mostly due to the optimization problem initially being *infeasible*
- Regret bound scales only with $\log |\mathcal{A}|$ and does not depend on $1/\min_x \rho(x)$

Theoretical Results

Theorem (Worst-case regret bound)

For any finite n , the expected regret of SOLID is bounded as

$$\mathbb{E}[R_n(\theta^*)] \leq \tilde{O}(|\mathcal{X}| \sqrt{nd})$$

Theoretical Results

Theorem (Worst-case regret bound)

For any finite n , the expected regret of SOLID is bounded as

$$\mathbb{E}[R_n(\theta^*)] \leq \tilde{O}(|\mathcal{X}| \sqrt{nd})$$

- SOLID is **minimax optimal** in non-contextual linear bandits ($|\mathcal{X}| = 1$)

Theoretical Results

Theorem (Worst-case regret bound)

For any finite n , the expected regret of SOLID is bounded as

$$\mathbb{E}[R_n(\theta^*)] \leq \tilde{O}(|\mathcal{X}|\sqrt{nd})$$

- SOLID is **minimax optimal** in non-contextual linear bandits ($|\mathcal{X}| = 1$)
- Open question whether the **dependence on $|\mathcal{X}|$** could be reduced

At each step t , SOLID estimates

- θ^* via RLS¹: $\hat{\theta}_t = \bar{V}_t^{-1} \sum_{s=1}^t \phi_s Y_s$, where $\bar{V}_t := \sum_{s=1}^t \phi_s \phi_s^T + \nu I$
- the context distribution: $\hat{\rho}_t(x) = \frac{1}{t} \sum_{s=1}^t \mathbb{1}\{X_s = x\}$

¹To carry out the analysis, we also need to project $\hat{\theta}_t$ onto Θ

At each step t , SOLID

- builds a **confidence ellipsoid** $\mathcal{C}_t := \{\theta \in \mathbb{R}^d : \|\theta - \hat{\theta}_t\|_{\bar{V}_t}^2 \leq \beta_t\}$

At each step t , SOLID

- builds a **confidence ellipsoid** $\mathcal{C}_t := \{\theta \in \mathbb{R}^d : \|\theta - \hat{\theta}_t\|_{\hat{V}_t}^2 \leq \beta_t\}$
- tests whether all alternative reward parameters (w.r.t. $\hat{\theta}_t$) are outside \mathcal{C}_t

At each step t , SOLID

- builds a **confidence ellipsoid** $\mathcal{C}_t := \{\theta \in \mathbb{R}^d : \|\theta - \hat{\theta}_t\|_{\hat{V}_t}^2 \leq \beta_t\}$
- tests whether all alternative reward parameters (w.r.t. $\hat{\theta}_t$) are outside \mathcal{C}_t
 - If true \rightarrow the **empirical optimal arm** for the current context is pulled

At each step t , SOLID

- builds a **confidence ellipsoid** $\mathcal{C}_t := \{\theta \in \mathbb{R}^d : \|\theta - \hat{\theta}_t\|_{\bar{V}_t}^2 \leq \beta_t\}$
- tests whether all alternative reward parameters (w.r.t. $\hat{\theta}_t$) are outside \mathcal{C}_t
 - If true \rightarrow the **empirical optimal arm** for the current context is pulled

Theorem

For $c_{n,\delta}$ of order $\mathcal{O}(\log(1/\delta) + d \log \log n)$,²

$$\mathbb{P} \left\{ \exists t \in [n] : \|\hat{\theta}_t - \theta^*\|_{\bar{V}_t}^2 \geq c_{n,\delta} \right\} \leq \delta,$$

² This improves the concentration bound of [Abbasi-Yadkori et al., 2011] which scales as $d \log(1/\delta)$

SOLID builds an (almost) **optimistic Lagrangian**

Confidence interval at x, a

$$f_t(\omega) := \sum_{x \in \mathcal{X}} \hat{\rho}_{t-1}(x) \sum_{a \in \mathcal{A}} \omega(x, a) \left(\mu_{\hat{\theta}_{t-1}}(x, a) + \sqrt{\gamma_t} \|\phi(x, a)\|_{\bar{V}_{t-1}^{-1}} \right)$$

$$g_t(\omega, z) := \inf_{\theta' \in \bar{\Theta}_{t-1}} \sum_{x \in \mathcal{X}} \hat{\rho}_{t-1}(x) \sum_{a \in \mathcal{A}} \omega(x, a) \left(d_{x,a}(\hat{\theta}_{t-1}, \theta') + c\sqrt{\gamma_t} \|\phi(x, a)\|_{\bar{V}_{t-1}^{-1}} \right) - \frac{1}{z}$$

Alternative parameters w.r.t. $\hat{\theta}_{t-1}$

SOLID uses a **primal-dual sub-gradient method** [Beck and Teboulle, 2003]

SOLID uses a **primal-dual sub-gradient method** [Beck and Teboulle, 2003]

- Update rule for ω : **online mirror ascent** on the simplex

$$\omega_{t+1}(x, a) \leftarrow \frac{\omega_t(x, a) e^{\alpha_t q_t(x, a)}}{\sum_{a' \in \mathcal{A}} \omega_t(x, a') e^{\alpha_t q_t(x, a')}} \quad \leftarrow \begin{array}{l} \text{Sub-gradient} \\ q_t \in \partial(f_t(\omega_t) + \lambda_t g_t(\omega_t, z_t)) \end{array}$$

- Update rule for λ : **Projected sub-gradient descent**

$$\lambda_{t+1} \leftarrow \text{clip}\left(\lambda_t - \alpha_t g_t(\omega_t, z_t); 0, \lambda_{\max}\right)$$

- SOLID does not use any explicit *tracking* procedure...
[Garivier and Kaufmann, 2016, Combes et al., 2017, Degenne et al., 2019]

- SOLID does not use any explicit *tracking* procedure...
[Garivier and Kaufmann, 2016, Combes et al., 2017, Degenne et al., 2019]
- ...but it directly **samples** from ω_t

- SOLID does not use any explicit *tracking* procedure...
[Garivier and Kaufmann, 2016, Combes et al., 2017, Degenne et al., 2019]
- ...but it directly **samples** from ω_t
- Analysis of action sampling crucial for *removing* polynomial dependence on $|\mathcal{A}|$

- SOLID does not use any explicit *tracking* procedure...
[Garivier and Kaufmann, 2016, Combes et al., 2017, Degenne et al., 2019]
- ...but it directly **samples** from ω_t
- Analysis of action sampling crucial for *removing* polynomial dependence on $|\mathcal{A}|$
- **Intuition:** we only need to concentrate *expectations* of the form

$$\left| \sum_{s \leq t: E_s} \left(\varphi(X_s, A_s) - \sum_{x \in \mathcal{X}} \rho(x) \sum_{a \in \mathcal{A}} \omega_s(x, a) \varphi(x, a) \right) \right| \leq ?$$

- SOLID uses an increasing schedule with **phases**: $\{z_k\}_{k \geq 1}$


- SOLID uses an increasing schedule with **phases**: $\{z_k\}_{k \geq 1}$
- Change phase when the number of exploration rounds exceeds given thresholds

- SOLID uses an increasing schedule with **phases**: $\{z_k\}_{k \geq 1}$
- Change phase when the number of exploration rounds exceeds given thresholds
- Theoretical results for **exponential** schedule $z_k = z_0 e^k$

Numerical Results

Toy problem with $|\mathcal{X}| = 2$, $|\mathcal{A}| = 3$, $d = 3$

- Asymptotic lower bound: explore in x_2 , go greedy in x_1



- Minimax optimality in contextual problems?

Open Questions

- Minimax optimality in contextual problems?
- How to deal with continuous contexts?

- Minimax optimality in contextual problems?
- How to deal with continuous contexts?
- Finite-time problem-dependent optimality?

Open Questions

- Minimax optimality in contextual problems?
- How to deal with continuous contexts?
- Finite-time problem-dependent optimality?
- How to handle misspecified linear models?

The End

Details are in the paper:






An Asymptotically Optimal Primal-Dual Incremental Algorithm for Contextual Linear Bandits

NeurIPS 2020


Andrea Tirinzoni, Matteo Pirota, Marcello Restelli, Alessandro Lazaric

Thank you!

References

- 
- Abbasi-Yadkori, Y., Pál, D., and Szepesvári, C. (2011).
Improved algorithms for linear stochastic bandits.
In Advances in Neural Information Processing Systems, pages 2312–2320.
- 
- Agrawal, S. and Goyal, N. (2013).
Thompson sampling for contextual bandits with linear payoffs.
In International Conference on Machine Learning, pages 127–135.
- 
- Beck, A. and Teboulle, M. (2003).
Mirror descent and nonlinear projected subgradient methods for convex optimization.
Operations Research Letters, 31(3):167–175.
- 
- Combes, R., Magureanu, S., and Proutière, A. (2017).
Minimal exploration in structured stochastic bandits.
In NIPS, pages 1763–1771.
- 
- Degenne, R., Koolen, W. M., and Ménard, P. (2019).
Non-asymptotic pure exploration by solving games.
In NeurIPS, pages 14465–14474.

References (cont.)

- 
- Degenne, R., Shao, H., and Koolen, W. (2020).
Structure adaptive algorithms for stochastic bandits.
In *International Conference on Machine Learning*, Vienna, Austria.
Virtual conference.
- 
- Garivier, A. and Kaufmann, E. (2016).
Optimal best arm identification with fixed confidence.
In *Conference on Learning Theory*, pages 998–1027.
- 
- Hao, B., Lattimore, T., and Szepesvari, C. (2020).
Adaptive exploration in linear contextual bandit.
volume 108 of *Proceedings of Machine Learning Research*, pages 3536–3545, Online. PMLR.
- 
- Jun, K.-S. and Zhang, C. (2020).
Crush optimism with pessimism: Structured bandits beyond asymptotic optimality.
arXiv preprint arXiv:2006.08754.
- 
- Lattimore, T. and Szepesvári, C. (2017).
The end of optimism? an asymptotic analysis of finite-armed linear bandits.
In *AISTATS*, volume 54 of *Proceedings of Machine Learning Research*, pages 728–737. PMLR.