
What the hell is the title of this paper?

Anonymous Author(s)

Affiliation

Address

email

Abstract

The abstract paragraph should be indented $\frac{1}{2}$ inch (3 picas) on both the left- and right-hand margins. Use 10 point type, with a vertical spacing (leading) of 11 points. The word **Abstract** must be centered, bold, and in point size 12. Two line spaces precede the abstract. The abstract must be limited to one paragraph.

1 Introduction

Recent advances have allowed reinforcement learning (RL) [29] to achieve impressive results in a wide variety of complex tasks, ranging from Atari [22], to the game of Go [28], to the control of sophisticated robotics systems [14, 20, 19]. The main limitation is that RL algorithms still require an enormous amount of experience samples before successfully learning such complicated tasks. One of the most promising solutions is transfer learning, which focuses on reusing past knowledge available to the agent in order to reduce the sample-complexity for learning new tasks. In the typical settings of transfer in RL [31], the agent is assumed to have already solved a set of *source tasks* generated from some unknown distribution. Then, given a *target task* drawn from the same distribution, or a slightly different one, the agent can rely on knowledge from the source tasks to speed-up the learning process. This constitutes a significant advantage over plain RL, where the agent learns each new task from scratch independently of previous learning experience. Several algorithms have been proposed in the literature to transfer experience samples [18, 30], policies/options [10, 16], rewards [15], features [4], parameters [9, 13], and so on. We refer the reader to [31] for a thorough survey on transfer in RL.

Under the assumption that tasks follow a certain distribution, an intuitive choice for designing a transfer algorithm is to attempt at characterizing the uncertainty over the target task. Then, an ideal algorithm would leverage prior knowledge from the source tasks to interact with the target task in such a way that this uncertainty is reduced as quickly as possible. This simple intuition makes Bayesian methods appealing approaches for transfer in RL, and many previous works have been proposed in this direction. [33] assume tasks share similarities in their dynamics and rewards and propose a hierarchical Bayesian model for the distribution of these two elements. Similarly, [17] assume tasks are similar in their value functions and design a different hierarchical Bayesian model for transferring such information. More recently, [9], and its extension [13], consider tasks whose dynamics are governed by some hidden parameters, and propose efficient Bayesian models for quickly learning such parameters in new tasks. However, all these algorithms require specific, and sometimes restrictive, assumptions (e.g., on the distributions involved or the function approximators adopted), which might limit their practical applicability. The importance of having transfer algorithms that alleviate the need of strong assumptions and can be easily adapted to different contexts motivates us to take a more general approach.

Similarly to [17], we assume tasks to share similarities in their value functions and use the given source tasks to learn a distribution over such functions. Then, we use this distribution as a prior for learning the target task and we propose an efficient variational approximation of the corresponding posterior. Leveraging on recent ideas from randomized value functions [23], we design a Thompson sampling-based algorithm which efficiently explores the target task by repeatedly sampling from the posterior

probabilistic?
distribu-
tional?

and acting greedily w.r.t. (with respect to) the sampled value function. We show that our approach is very general, in the sense that it does not require any specific choice of function approximator or prior/posterior distribution models. We propose a finite-sample analysis that theoretically validates our approach, while empirically evaluating its performance on three domains with increasing level of difficulty.

2 Preliminaries

We consider a distribution \mathcal{D} over tasks, where each task is modeled as a discounted Markov decision process (MDP). We define an MDP as a tuple $\mathcal{M} = \langle \mathcal{S}, \mathcal{A}, \mathcal{P}, \mathcal{R}, p_0, \gamma \rangle$, where \mathcal{S} is the state-space, \mathcal{A} is a finite set of actions, $\mathcal{P}(\cdot|s, a)$ is the distribution of the next state s' given that action a is taken in state s , $\mathcal{R} : \mathcal{S} \times \mathcal{A} \rightarrow \mathbb{R}$ is the reward function, p_0 is the initial-state distribution, and $\gamma \in [0, 1)$ is the discount factor. We assume the reward function to be uniformly bounded by a constant $R_{max} > 0$. A deterministic policy $\pi : \mathcal{S} \rightarrow \mathcal{A}$ is a mapping from states to actions. At the beginning of each episode of interaction, the initial state s_0 is drawn from p_0 . Then, the agent takes the action $a_0 = \pi(s_0)$, receives a reward $\mathcal{R}(s_0, a_0)$, transitions to the next state $s_1 \sim \mathcal{P}(\cdot|s_0, a_0)$, and the process is repeated. The goal is to find the policy maximizing the long-term return over a possibly infinite horizon: $\max_{\pi} J(\pi) \triangleq \mathbb{E}[\sum_{t=0}^{\infty} \gamma^t r_t | \mathcal{M}, \pi]$. To this end, we define the optimal value function $Q^*(s, a)$ as the expected return obtained by taking action a in state s and following an optimal policy thereafter. Then, an optimal policy π^* is a policy that is greedy with respect to the optimal value function, i.e., $\pi^*(s) = \operatorname{argmax}_a Q^*(s, a)$ for all states s . It can be shown (e.g., [24]) that Q^* is the unique fixed-point of the optimal Bellman operator T defined by $TQ(s, a) = \mathcal{R}(s, a) + \gamma \mathbb{E}_{\mathcal{P}}[\max_{a'} Q(s', a')]$ for any value function Q . From now on, we adopt the term Q -function to denote any plausible value function, i.e., any function $Q : \mathcal{S} \times \mathcal{A} \rightarrow \mathbb{R}$ uniformly bounded by $\frac{R_{max}}{1-\gamma}$.

Should we provide a more transfer-oriented definition?

We consider a parametric family of Q -functions, $\mathcal{Q} = \{Q_{\mathbf{w}} : \mathcal{S} \times \mathcal{A} \rightarrow \mathbb{R} \mid \mathbf{w} \in \mathbb{R}^K\}$, and we assume each function in \mathcal{Q} to be uniformly bounded by $\frac{R_{max}}{1-\gamma}$. When learning the optimal value function, a quantity of interest is how close a given function $Q_{\mathbf{w}}$ is to the fixed-point of the Bellman operator. A possible measure is its Bellman error (or Bellman residual), defined by $B(\mathbf{w}) \triangleq TQ_{\mathbf{w}} - Q_{\mathbf{w}}$. Notice that $Q_{\mathbf{w}}$ is optimal if, and only if, $B(\mathbf{w})(s, a) = 0$ for all s, a . If we assume the existence of a distribution ν over $\mathcal{S} \times \mathcal{A}$, an appealing objective is to directly minimize the squared Bellman error of $Q_{\mathbf{w}}$ under ν , denoted by $\|B(\mathbf{w})\|_{\nu}^2$. Unfortunately, it is well-known that an unbiased estimator of this quantity requires two independent samples of the next state s' for each s, a (e.g., [21]). In practice, the Bellman error is typically replaced by the TD error $b(\mathbf{w})$, which approximates the former using a single transition sample, $b(\mathbf{w}) = r + \gamma \max_{a'} Q_{\mathbf{w}}(s', a') - Q_{\mathbf{w}}(s, a)$. Finally, given a dataset $D = \langle s_i, a_i, r_i, s'_i \rangle_{i=1}^N$ of N samples, the squared TD error is computed as $\|B(\mathbf{w})\|_D^2 = \frac{1}{N} \sum_{i=1}^N (r_i + \gamma \max_{a'} Q_{\mathbf{w}}(s'_i, a') - Q_{\mathbf{w}}(s_i, a_i))^2 = \frac{1}{N} \sum_{i=1}^N b_i(\mathbf{w})^2$. Whenever the distinction is clear from the context, with slight abuse of terminology, we refer to the squared Bellman error and squared TD error as Bellman error and TD error, respectively.

Should we define norms before?

3 Variational Transfer Learning

In this section, we describe our variational approach to transfer in RL. In Section 3.1, we start by introducing our algorithm from a high-level perspective, in such a way that it can be used for any choice of prior and posterior distributions. Then, in Sections 3.2 and 3.3, we propose practical implementations based on Gaussians and mixtures of Gaussians, respectively. We conclude with some considerations on how to optimize the proposed objective in Sec. 3.4.

3.1 Algorithm

We begin with a simple consideration: the distribution \mathcal{D} over tasks clearly induces a distribution over optimal Q -functions. Moreover, for any MDP, learning its optimal Q -function is sufficient for solving the problem. Thus, one can safely replace the distribution over tasks with the distribution over their optimal value functions. In our parametric settings, we reduce the latter to a distribution $p(\mathbf{w})$ over weights.

Should we just make the assumption that Q -functions share knowledge in their weights?

Algorithm 1 Variational Transfer

Require: Target task τ , source Q -function weights \mathcal{W}_s , batch size M

```
1: Estimate prior  $p(\mathbf{w})$  from  $\mathcal{W}_s$ 
2: Initialize variational parameters:  $\xi \leftarrow \operatorname{argmin}_{\xi} KL(q_{\xi} || p)$ 
3: Initialize replay buffer:  $D = \emptyset$ 
4: repeat
5:   Sample initial state:  $s_0 \sim p_0^{(\tau)}$ 
6:   while  $s_h$  is not terminal do
7:     Sample weights:  $\mathbf{w} \sim q_{\xi}(\mathbf{w})$ 
8:     Take action  $a_h = \operatorname{argmax}_a Q_{\mathbf{w}}(s_h, a)$ 
9:     Observe transition  $s_{h+1} \sim \mathcal{P}^{(\tau)}(\cdot | s_h, a_h)$  and collect reward  $r_h = \mathcal{R}^{(\tau)}(s_h, a_h)$ 
10:    Add sample to the replay buffer:  $D \leftarrow D \cup \langle s_h, a_h, r_h, s_{h+1} \rangle$ 
11:    Sample mini-batch  $D' = \langle s_i, a_i, r_i, s'_{i+1} \rangle_{i=1}^M$  from  $D$ 
12:    Estimate the gradient  $\nabla_{\xi} \mathcal{L}(\xi)$  using  $D'$ 
13:    Update  $\xi$  in the direction of  $-\nabla_{\xi} \mathcal{L}(\xi)$  using any stochastic optimizer (e.g., ADAM)
14:  end while
15: until forever
```

87 Assume, for the moment, that we know the distribution $p(\mathbf{w})$ and consider a dataset $D =$
88 $\{(s_i, a_i, s'_i, r_i) \mid i = 1, 2, \dots, N\}$ of samples from some task τ that we want to solve. Then, the
89 posterior distribution over weights given such dataset can be computed by applying Bayes theorem
90 as $p(\mathbf{w}|D) \propto p(D|\mathbf{w})p(\mathbf{w})$. Unfortunately, this cannot be directly used in practice since we do not
91 have a model of the likelihood $p(D|\mathbf{w})$. In such case, it is very common to make strong assumptions
92 on the MDPs or the Q -functions so as to get tractable posteriors. However, in our transfer settings
93 all distributions involved depend on the family of tasks under consideration, and making such as-
94 sumptions is likely to limit the applicability to specific problems. Thus, we take a different approach
95 to derive a more general, but still well-grounded, solution. Recall that our final goal is move all
96 probability mass over the weights minimizing some empirical loss measure, which in our case is the
97 TD error $\|B(\mathbf{w})\|_D^2$. Then, given a prior $p(\mathbf{w})$, we know from PAC-Bayesian theory that the optimal
98 Gibbs posterior q takes the form (e.g., [8]):

$$q(\mathbf{w}) = \frac{e^{-\Lambda \|B(\mathbf{w})\|_D^2} p(\mathbf{w})}{\int e^{-\Lambda \|B(\mathbf{w}')\|_D^2} p(d\mathbf{w}')} \quad (1)$$

99 for some parameter $\Lambda > 0$. Since Λ is typically chosen to increase with the number of samples
100 N , in the remaining we set it to $\lambda^{-1}N$, for some constant $\lambda > 0$. Notice that, whenever the term
101 $e^{-\Lambda \|B(\mathbf{w})\|_D^2}$ can be interpreted as the actual likelihood of D , q becomes a classic Bayesian posterior.
102 Although we now have an appealing distribution, the integral at the denominator of (1) is intractable
103 to compute even for simple Q -function models. Thus, we propose a variational approximation q_{ξ} by
104 considering a simpler family of distributions parameterized by $\xi \in \Xi$. Then, our problem reduces to
105 finding the variational parameters ξ such that q_{ξ} minimizes the Kullback-Leibler (KL) divergence
106 w.r.t. the Gibbs posterior q . From the theory of variational inference (e.g., [5]), this can be shown to
107 be equivalent to minimizing the well-known (negative) *evidence lower bound* (ELBO):

$$\min_{\xi \in \Xi} \mathcal{L}(\xi) = \mathbb{E}_{\mathbf{w} \sim q_{\xi}} [\|B(\mathbf{w})\|_D^2] - \frac{\lambda}{N} KL(q_{\xi}(\mathbf{w}) || p(\mathbf{w})) \quad (2)$$

108 Intuitively, the approximate posterior trades-off between placing probability mass over those weights
109 \mathbf{w} that have low expected TD error (first term), and staying close to the prior distribution (second
110 term). Assuming that we are able to compute the gradients of (2) w.r.t. the variational parameters ξ ,
111 our objective can be easily optimized using any stochastic optimization algorithm.

112 We now highlight our general transfer procedure in Alg. 1, while deferring a description of specific
113 choices for the distributions involved to the next two sections. Given a set of weights \mathcal{W}_s from
114 the source tasks' optimal Q -functions, we start by estimating the prior distribution (line 1) and we
115 initialize the variational parameters by minimizing the KL divergence w.r.t. such distribution¹ (line

¹If the prior and approximate posterior were in the same family of distributions we could simply set ξ to the prior parameters. However, we are not making this assumption at this point.

Maybe say
how this is
obtained

116 2). Then, at each time step of interaction, we re-sample the weights from the current approximate
 117 posterior and act greedily w.r.t. the corresponding Q -function (lines 7,8). After collecting and storing
 118 the new experience (lines 9-10), we draw a mini-batch of samples from the replay buffer (line 11), use
 119 this to estimate the objective function gradient (line 12), and, finally, update the variational parameters
 120 (line 13).

121 The key property of our approach is the weight resampling at line 7. This resembles the well-known
 122 Thompson sampling approach adopted in multi-armed bandits [7] and closely relates to the recent
 123 value function randomization [23]. In some sense, at each time we guess what is the task we are
 124 trying to solve based on our current belief and we act as if such guess were actually true. This allows
 125 an efficient adaptive exploration of the target task. Intuitively, during the first steps of interaction,
 126 the agent is very uncertain about the current task and such uncertainty induces stochasticity in the
 127 chosen actions, allowing rather informed exploration to take place. Consider, for instance, that actions
 128 that are bad on average for all tasks are very unlikely to be sampled, while this cannot happen in
 129 uninformed exploration strategies, like ϵ -greedy, before learning takes place. As the learning process
 130 goes on, the algorithm will quickly figure out which task is being solved, thus moving all probability
 131 mass over the weights minimizing the TD error. From that point, sampling from the posterior is
 132 approximately equivalent to deterministically taking such weights, and no more exploration will be
 133 performed.

134 Finally, notice the generality of the proposed approach: as far as the objective \mathcal{L} is differentiable
 135 in the variational parameters ξ , and its gradients can be efficiently computed, any approximator for
 136 the Q -function and any prior/posterior distributions can be adopted. For the latter, we describe two
 137 practical choices in the next two sections.

138 3.2 Gaussian Variational Transfer

139 We now restrict to a specific choice of the prior and posterior families that makes our algorithm
 140 very efficient and easy to implement. We assume that optimal Q -functions (or better, their weights)
 141 follow a multivariate Gaussian distribution. That is, we model the prior as $p(\mathbf{w}) = \mathcal{N}(\boldsymbol{\mu}_p, \boldsymbol{\Sigma}_p)$
 142 and we learn its parameters from the set of source weights using maximum likelihood estimation
 143 (with small regularization to make sure the covariance is positive definite). Then, our variational
 144 family is the set of all well-defined Gaussian distributions, i.e., the variational parameters are
 145 $\Xi = \{(\boldsymbol{\mu}, \boldsymbol{\Sigma}) \mid \boldsymbol{\mu} \in \mathbb{R}^K, \boldsymbol{\Sigma} \in \mathbb{R}^{K \times K}, \boldsymbol{\Sigma} \succ 0\}$. To prevent the covariance from becoming not pos-
 146 itive definite, we consider its Cholesky decomposition $\boldsymbol{\Sigma} = \mathbf{L}\mathbf{L}^T$ and learn the lower-triangular
 147 Cholesky factor \mathbf{L} instead. In this case, deriving the gradient of the objective is very simple. Both the
 148 KL between two multivariate Gaussians and its gradients have a simple closed-form expression. The
 149 expected log-likelihood, on the other hand, can be easily differentiated by adopting the reparameteri-
 150 zation trick (e.g., [12, 25]). Although these results are well-known in the literature, we report them in
 151 App. ?? to have a more self-contained description.

152 3.3 Mixture of Gaussian Variational Transfer

153 Although the Gaussian assumption of the previous section is very appealing as it allows for a simple
 154 and efficient way of computing the variational objective and its gradients, we believe that such
 155 assumption almost never holds in practice. In fact, even for families of tasks in which the reward and
 156 transition models are Gaussian, the Q -values might be far from it. Depending on the family of tasks
 157 under consideration and, since we are learning a distribution over weights, on the chosen function
 158 approximator, the prior might have arbitrarily complex shapes. When the information loss due to
 159 the Gaussian approximation becomes too severe, the algorithm is likely to fail at capturing any
 160 similarities between the tasks. We now propose a variant to successfully solve this problem, while
 161 keeping the algorithm simple and efficient enough to be applied in practice.

162 Given the source tasks' weights \mathcal{W}_s , we model our estimated prior as a mixture of Gaussians with one
 163 equally weighted isotropic Gaussian centered at each weight: $p(\mathbf{w}) = \frac{1}{|\mathcal{W}_s|} \sum_{\mathbf{w}_s \in \mathcal{W}_s} \mathcal{N}(\mathbf{w}|\mathbf{w}_s, \sigma_p^2 \mathbf{I})$.
 164 This resembles a kernel density estimator [27] and, due to its nonparametric nature, it allows capturing
 165 arbitrarily complex distribution. Consistently with the prior, we model our approximate posterior as a
 166 mixture of Gaussians. However, we allow a different number of components (typically much less
 167 than the prior's) and we adopt full covariances instead of only diagonals, so that our posterior has the
 168 potential to match complex distributions with less components. Using C components, our posterior

169 is $q_{\xi}(\mathbf{w}) = \frac{1}{C} \sum_{i=1}^C \mathcal{N}(\mathbf{w} | \boldsymbol{\mu}_i, \boldsymbol{\Sigma}_i)$, with variational parameters $\xi = (\boldsymbol{\mu}_1, \dots, \boldsymbol{\mu}_C, \boldsymbol{\Sigma}_1, \dots, \boldsymbol{\Sigma}_C)$.
 170 Once again, we learn Cholesky factors instead of full covariances.

171 Although this new model has the potential to capture much more complex distributions, it poses
 172 a major complication: the KL divergence between two mixture of Gaussians has no closed-form
 173 expression. To solve this issue, we rely on an upper bound to such quantity, so that negative ELBO
 174 still upper bounds the KL between the approximate and true posterior. Among the many upper bounds
 175 available in the literature, we adopt the one proposed in [11], which we report here for the sake of
 176 completeness. We refer the reader to the original paper for the proof.

177 **Theorem 1** ([11]). *Let $p = \sum_i c_i^{(p)} f_i^{(p)}$ and $q = \sum_j c_j^{(q)} f_j^{(q)}$ be two mixture of Gaussian distri-*
 178 *butions, where $f_i^{(p)} = \mathcal{N}(\boldsymbol{\mu}_i^{(p)}, \boldsymbol{\Sigma}_i^{(p)})$ denotes the i -th component of p , $c_i^{(p)}$ denotes its weight, and*
 179 *similarly for q . Introduce two vectors $\chi^{(1)}$ and $\chi^{(2)}$ such that $c_i^{(p)} = \sum_j \chi_{j,i}^{(2)}$ and $c_j^{(q)} = \sum_i \chi_{i,j}^{(1)}$.*
 180 *Then:*

$$KL(p||q) \leq KL(\chi^{(2)}||\chi^{(1)}) + \sum_{i,j} \chi_{j,i}^{(2)} KL(f_i^{(p)}||f_j^{(q)}) \quad (3)$$

181 Our new algorithm replaces the KL with the above-mentioned upper bound. Each time we require
 182 its value, we have to recompute the parameters $\chi^{(1)}$ and $\chi^{(2)}$ that tighten the bound. As shown in
 183 [11], this can be achieved by a simple fixed-point procedure. Finally, both terms in the objective are
 184 now linear combinations of functions of the variational parameters of different components, and their
 185 gradients are easily derived from the ones of the Gaussian case. We report the derivation in App. ??.

186 3.4 Optimizing the TD error

187 From Sections 3.2 and 3.3, we know that differentiating the negative ELBO \mathcal{L} w.r.t. ξ requires
 188 differentiating $\|B(\mathbf{w})\|_D^2$ w.r.t. \mathbf{w} . Unfortunately, the TD error is well-known to be non-differentiable
 189 due to the presence of the max operator. This rarely represents a problem since typical value-based
 190 algorithms are actually semi-gradient methods, i.e., they do not differentiate the targets (see, e.g.,
 191 Chapter 11 of [29]). However, our transfer settings are rather different than common RL. In fact, our
 192 algorithm is likely to start from Q -functions that are very close to an optimum, and the only thing that
 193 needs to be done is to adapt the weights in a direction of lower error (i.e., higher likelihood) so as to
 194 quickly converge to the solution of the task that is being solved. Unfortunately, this property cannot
 195 be guaranteed for most semi-gradient algorithms. Even worse, many online RL algorithms combined
 196 with complex function approximators (e.g., DQNs) are well-known to be unstable, especially when
 197 approaching an optimum, and require many tricks and tuning to work well [26, 32]. This is obviously
 198 an undesirable property in our case, as we only aim at adapting already good solutions. Thus, we
 199 consider using a residual gradient algorithm [3]. In order to differentiate the targets, we replace
 200 the optimal Bellman operator with the mellow Bellman operator introduced in [1], which adopts a
 201 softened version of max called *mellowmax*:

$$\text{mm}_a Q_{\mathbf{w}}(s, a) = \frac{1}{\kappa} \log \frac{1}{|\mathcal{A}|} \sum_a e^{\kappa Q_{\mathbf{w}}(s, a)} \quad (4)$$

202 where κ is a hyperparameter and $|\mathcal{A}|$ is the number of actions. The mellow Bellman operator, which
 203 we denote as \tilde{T} , has several appealing properties that make it suitable for our settings: (i) it converges
 204 to the maximum as $\kappa \rightarrow \infty$, (ii) it has a unique fixed point, and (iii) it is *differentiable*. Denoting
 205 by $\tilde{B}(\mathbf{w}) = \tilde{T}Q_{\mathbf{w}} - Q_{\mathbf{w}}$ the Bellman residual w.r.t. the mellow Bellman operator \tilde{T} , we have that
 206 the corresponding TD error, $\|\tilde{B}(\mathbf{w})\|_D^2$, is now differentiable with respect to \mathbf{w} . Although residual
 207 algorithms have guaranteed convergence, they are typically much slower than their semi-gradient
 208 counterpart. [3] proposed to project the gradient in a direction that achieves higher learning speed,
 209 while preserving convergence. This can be easily done by including a parameter $\psi \in [0, 1]$ in the TD
 210 error gradient such that:

$$\nabla_{\mathbf{w}} \|\tilde{B}(\mathbf{w})\|_D^2 = \frac{2}{N} \sum_{i=1}^N b_i(\mathbf{w}) \left(\gamma \psi \nabla_{\mathbf{w}} \text{mm}_{a'} Q_{\mathbf{w}}(s'_i, a') - \nabla_{\mathbf{w}} Q_{\mathbf{w}}(s_i, a_i) \right) \quad (5)$$

211 where $b_i(\mathbf{w}) = r_i + \gamma \text{mm}_{a'} Q_{\mathbf{w}}(s'_i, a') - Q_{\mathbf{w}}(s_i, a_i)$. Notice that ψ trades-off between the semi-
 212 gradient ($\psi = 0$) and the full residual gradient ($\psi = 1$). A good criterion for choosing such

parameter is to start with values close to zero (to have faster learning) and move to higher values when approaching the optimum (to guarantee converge).

4 Theoretical Analysis

In this section, we theoretically analyze our variational transfer algorithm...

A first important question that we need to answer is whether replacing max with mellow-max in the Bellman operator constitutes a strong approximation or not. It has been proved [] that the mellow Bellman operator is a contraction under the L_∞ -norm and, thus, has a unique fixed-point. However, how such fixed-point differs from the one of the optimal Bellman operator remains an open question. Since mellow-max monotonically converges to max as $\kappa \rightarrow \infty$, it would be desirable if the corresponding operator also monotonically converged to the optimal one. We confirm that this property actually holds in the following theorem.

Cite MM

Theorem 2. *Let V be the fixed-point of the optimal Bellman operator T , and Q the corresponding action-value function. Define the action-gap function $g(s)$ as the difference between the value of the best action and the second best action at each state s . Let \tilde{V} be the fixed-point of the mellow Bellman operator \tilde{T} with parameter $\kappa > 0$ and denote by $\beta > 0$ the inverse temperature of the induced Boltzmann distribution (as in [1]). Let ν be a probability measure over the state-space. Then, for any $p \geq 1$:*

$$\|V - \tilde{V}\|_{\nu,p}^p \leq \frac{2R_{max}}{(1-\gamma)^2} \left\| 1 - \frac{1}{1 + |\mathcal{A}| e^{-\beta g}} \right\|_{\nu,p}^p \quad (6)$$

Theorem 3. *Let Q^* be the fixed-point of the optimal Bellman operator T . Define the action-gap function $g(s)$ as the difference between the value of the best action and the second best action at each state s . Let \tilde{Q} be the fixed-point of the mellow Bellman operator \tilde{T} with parameter $\kappa > 0$ and denote by $\beta_\kappa > 0$ the inverse temperature of the induced Boltzmann distribution (as in [1]). Let ν be a probability measure over the state-action space. Then, for any $p \geq 1$:*

$$\|Q^* - \tilde{Q}\|_{\nu,p}^p \leq \frac{2\gamma R_{max}}{(1-\gamma)^2} \left\| \frac{1}{1 + \frac{1}{|\mathcal{A}|} e^{\beta_\kappa g}} \right\|_{\nu,p}^p \quad (7)$$

5 Related Works

Our approach is mostly related to [17]. Although we both assume the tasks to share similarities in their value functions, [17] consider only linear approximators and adopt a hierarchical Bayesian model of the corresponding weights' distribution, which is assumed Gaussian. On the other hand, our variational approximation allows for more general distribution families and can be combined with non-linear approximators. Furthermore, [17] propose a Dirichlet process model for the case where weights cluster into different classes, which relates to our mixture formulation and proves again the importance of capturing more complicated task distributions. In [33], the authors propose a hierarchical Bayesian model for the distribution over tasks. Differently from our approach and [17], they consider a distribution over transition probabilities and rewards, rather than value functions. In the same spirit of our method, they consider a Thompson sampling-based procedure which, at each iteration, samples a new task from the posterior and solves it. However, [33] consider only finite MDPs, which poses a severe limitation on the algorithm's applicability. On the contrary, our approach can handle high-dimensional tasks. In [9], the authors consider a family of tasks whose dynamics are governed by some hidden parameters and use Gaussian processes (GPs) to model such dynamics across tasks. Recently, [13] extended this approach by replacing GPs with Bayesian neural networks, so as to obtain a more scalable approach.

In the RL community, our approach is related to value function randomization[23], which extends the well-known LSTD [6] by adopting Bayesian linear regression to model the uncertainty over the predicted value function weights, and use that to perform a form of Thompson sampling. Such approach was recently extended by [2], where the approximator is replaced by a Bayesian neural network, leading to an algorithm capable of solving much more complicated problems. Both these algorithms rely on the Gaussian assumption and, since they work in plain RL settings, have no

More comments about HiP-MDPs? Should we discuss more related works?




Figure 1: (a) the rooms environment, (b) transfer from 10 source tasks with both doors moving, (c) transfer from 10 source tasks with only one door moving, and (d) transfer performance as a function of how likely the target task is according to the prior.

informative prior available. On the other hand, our variational approximation allows more complex distributions (e.g., mixtures) to be adopted, while knowledge from the source tasks allows us to learn very informative priors.

6 Experiments

In this section, we provide an experimental evaluation of our approach in three different domains with increasing level of difficulty. In all experiments, we compare our Gaussian variational transfer algorithm (GVT) and the version using a c -component mixture of Gaussians (c -MGVT) to plain no-transfer RL (NT) with ϵ -greedy exploration. To the best of our knowledge, no existing transfer algorithm is directly comparable to our approach from an experimental perspective.

Any better motivation?

6.1 The Rooms Problem

We consider an agent navigating in the rooms environment depicted in Fig. ?? . The agent starts in the bottom-left corner and must move from one room to another to reach the goal position in the top-right corner. The rooms are connected by small doors whose positions are unknown to the agent. The state-space is modeled as a 10×10 continuous grid, while the action-space is the set of 4 movement directions (up, right, down, left). After each action, the agent moves by 1 in the chosen direction and the final position is corrupted by Gaussian noise with 0.2 standard deviation. In case the agent hits a wall, its position remains unchanged. The reward is 1 when reaching the goal (after which the process terminates) and 0 otherwise, while the discount factor is $\gamma = 0.99$. We consider a distribution over tasks in which doors have a fixed width of 1, while their positions are sampled uniformly in $[0.5, 9.5]$. Since the agent does not know where the doors are located in advance and receives only very sparse feedback, it must efficiently explore the environment to figure out (i) their positions, and (ii) how to reach the goal. While this might be a complicated problem for plain RL, our transfer algorithm should be able to quickly figure out the door positions. In fact, notice that, although different, the optimal Q -functions for all tasks share some similarities. For example, once the agent has passed the last door before the goal, the Q -values are exactly the same in all tasks. This does not hold for positions nearby the start state. However, it is clear that there should be a preference over actions up and right, rather than down and left (which are worse in all tasks). Thus, we expect our algorithm to efficiently explore any target task.

In order to prove that our guesses are correct, we generate a set of 50 source tasks for the three-room environment of Fig. ?? by sampling both door positions uniformly, and solve all of them by directly minimizing the TD error as presented in Sec. 3.4. In order to make sure that their solutions are accurate enough, we allow sampling the initial state uniformly in the environment and run until converge. Then, we use our algorithms to transfer from 10 source tasks sampled from the previously generated set. The average return over the last 50 learning episodes as a function of the number of iterations is shown in Fig. ?? . Each curve is the result of 20 independent runs, each resampling the target and source tasks. 95% confidence intervals are shown. Further details on the parameters adopted in this experiment are given in App. ?? . As expected, the no-transfer algorithm NT fails at learning the task in so few iterations due to the limited exploration provided by an ϵ -greedy policy. On the other hand, all our algorithms achieve a significant speed-up and are able to converge to the

297 optimal performance in few iterations, with GVT being slightly slower. Interestingly, we notice that
298 there is no advantage in adopting more than 1 component for the posterior in MGVT. This is intuitive
299 since, when the algorithm quickly figures out which task is being solved, it will move all components
300 in the same direction.

301 To better understand the differences between GVT and MGVT, we now consider transferring from a
302 slightly different distribution than the one from which target tasks are drawn. We generate again 50
303 source tasks but this time with the bottom door fixed in the center and the other one moving. Then,
304 we repeat the previous experiment, allowing both doors to move when sampling target tasks. The
305 results are shown in Fig. ???. Interestingly, MGVT seems almost unaffected by this change, proving
306 that it has sufficient representation power to generalize to slightly different task distributions. The
307 same does not hold for GVT, which now is not able to solve many of the sampled target tasks (this is
308 the reason for the very high variance). This proves again that assuming Gaussian distributions can
309 pose severe limitations in our transfer settings.

310 Finally, we analyze the transfer performance as a function of how likely the target task is according to
311 the prior. We consider a two-room version of the environment of Fig. ???. Differently from before, we
312 generate tasks by sampling the door position from a Gaussian with mean 5, and standard deviation
313 1.8, so that tasks where the door is close to the sides are very unlikely. Fig. ?? shows the performance
314 reached by GVT and MGVT with 1 component at fixed iterations as a function of how likely the
315 target task is according to such distribution. As expected GVT achieves poor performance on very
316 unlikely tasks, even after many iterations. In fact, estimating a single Gaussian distribution definitely
317 implies some information loss, especially about the unlikely tasks. On the other hand, MGVT keeps
318 such information and, consequently, performs much better. Perhaps not surprisingly, MGVT reaches
319 the optimal performance in $4k$ iterations no matter what task is being solved.

320 6.2 Classic Control

321 6.3 Maze Navigation

322 For this setting we propose a maze environment, such as those in Fig. *, for a robotic agent to
323 navigate. We created a set of 20 mazes of size 10×10 with continuous space within which we
324 ensured four groups: each group with the goal position in one of the corners of the maze. In order to
325 simulate a robotic agent, we set an action space that allows to control the linear and angular motion by
326 a fixed distance/angle each time an action is performed: *move forward*, *rotate counter-* and *clockwise*.
327 Moreover, we enhanced the state space to include, in addition to the absolute position and orientation,
328 a set of distance measures to the nearest obstacles from the agent's perspective with maximum range
329 of 2 and a field of vision from -90° to 90° relative to its orientation. In this way, we provide the agent
330 with information that a robot would normally collect from LIDARs, sonars and other sensors alike.
331 Finally, in the same field of perception, we provide a boolean vector indicating whether the goal is
332 within the range of observation. Regarding rewards, the agent gets 1 whenever it enters the goal area
333 and 0 in any other situation.

334 The main motivation for this set-up is that a robot is able to exploit locally-sensed information
335 in addition to its estimation of the actual position—as opposed to the Rooms problem presented
336 above—and it is such information that the robotic agent could learn to use and, also, exploit in
337 different maze configurations leveraging its previous experience. Moreover, simple variations in the
338 maze structure could, potentially, produce big differences in the value function with respect to the
339 ones seen in previous tasks which makes the setting very good to assess how robust our algorithm is
340 robust to negative transfer.

341 These mazes were solved using Deep Q Networks (DQN) [] with a multilayer perceptron with hidden
342 layers 32×32 and, in order to perform the knowledge transfer, the target maze would be excluded
343 from the source tasks given to the algorithm. Finally, the MGVT algorithm, with one component for
344 the posterior distribution, was used to solve the target tasks shown in Fig. *.

cite DQN?

7 Conclusion

References

- [1] Kavosh Asadi and Michael L Littman. An alternative softmax operator for reinforcement learning. In *International Conference on Machine Learning*, pages 243–252, 2017.
- [2] Kamyar Azizzadenesheli, Emma Brunskill, and Animashree Anandkumar. Efficient exploration through bayesian deep q-networks. *arXiv preprint arXiv:1802.04412*, 2018.
- [3] Leemon Baird. Residual algorithms: Reinforcement learning with function approximation. In *Machine Learning Proceedings 1995*, pages 30–37. Elsevier, 1995.
- [4] André Barreto, Will Dabney, Rémi Munos, Jonathan J Hunt, Tom Schaul, Hado P van Hasselt, and David Silver. Successor features for transfer in reinforcement learning. In *Advances in neural information processing systems*, pages 4055–4065, 2017.
- [5] David M Blei, Alp Kucukelbir, and Jon D McAuliffe. Variational inference: A review for statisticians. *Journal of the American Statistical Association*, 112(518):859–877, 2017.
- [6] Justin A Boyan. Least-squares temporal difference learning.
- [7] Sébastien Bubeck, Nicolo Cesa-Bianchi, et al. Regret analysis of stochastic and nonstochastic multi-armed bandit problems. *Foundations and Trends® in Machine Learning*, 5(1):1–122, 2012.
- [8] Olivier Catoni. Pac-bayesian supervised classification: the thermodynamics of statistical learning. *arXiv preprint arXiv:0712.0248*, 2007.
- [9] Finale Doshi-Velez and George Konidaris. Hidden parameter markov decision processes: A semiparametric regression approach for discovering latent task parametrizations. In *IJCAI: proceedings of the conference*, volume 2016, page 1432. NIH Public Access, 2016.
- [10] Fernando Fernández and Manuela Veloso. Probabilistic policy reuse in a reinforcement learning agent. In *Proceedings of the fifth international joint conference on Autonomous agents and multiagent systems*, pages 720–727. ACM, 2006.
- [11] John R Hershey and Peder A Olsen. Approximating the kullback leibler divergence between gaussian mixture models. In *Acoustics, Speech and Signal Processing, 2007. ICASSP 2007. IEEE International Conference on*, volume 4, pages IV–317. IEEE, 2007.
- [12] Matthew D Hoffman, David M Blei, Chong Wang, and John Paisley. Stochastic variational inference. *The Journal of Machine Learning Research*, 14(1):1303–1347, 2013.
- [13] Taylor W Killian, Samuel Daulton, George Konidaris, and Finale Doshi-Velez. Robust and efficient transfer learning with hidden parameter markov decision processes. In *Advances in Neural Information Processing Systems*, pages 6250–6261, 2017.
- [14] Jens Kober and Jan R Peters. Policy search for motor primitives in robotics. In *Advances in neural information processing systems*, pages 849–856, 2009.
- [15] George Konidaris and Andrew Barto. Autonomous shaping: Knowledge transfer in reinforcement learning. In *Proceedings of the 23rd international conference on Machine learning*, pages 489–496. ACM, 2006.
- [16] George Konidaris and Andrew G Barto. Building portable options: Skill transfer in reinforcement learning.
- [17] Alessandro Lazaric and Mohammad Ghavamzadeh. Bayesian multi-task reinforcement learning. In *ICML-27th International Conference on Machine Learning*, pages 599–606. Omnipress, 2010.
- [18] Alessandro Lazaric, Marcello Restelli, and Andrea Bonarini. Transfer of samples in batch reinforcement learning. In *Proceedings of the 25th international conference on Machine learning*, pages 544–551. ACM, 2008.
- [19] Sergey Levine, Chelsea Finn, Trevor Darrell, and Pieter Abbeel. End-to-end training of deep visuomotor policies. *The Journal of Machine Learning Research*, 17(1):1334–1373, 2016.
- [20] Timothy P Lillicrap, Jonathan J Hunt, Alexander Pritzel, Nicolas Heess, Tom Erez, Yuval Tassa, David Silver, and Daan Wierstra. Continuous control with deep reinforcement learning. *arXiv preprint arXiv:1509.02971*, 2015.

- 392 [21] Odalric-Ambrym Maillard, Rémi Munos, Alessandro Lazaric, and Mohammad Ghavamzadeh. Finite-
393 sample analysis of bellman residual minimization. In *Proceedings of 2nd Asian Conference on Machine*
394 *Learning*, pages 299–314, 2010.
- 395 [22] Volodymyr Mnih, Koray Kavukcuoglu, David Silver, Andrei A Rusu, Joel Veness, Marc G Bellemare,
396 Alex Graves, Martin Riedmiller, Andreas K Fidjeland, Georg Ostrovski, et al. Human-level control through
397 deep reinforcement learning. *Nature*, 518(7540):529, 2015.
- 398 [23] Ian Osband, Benjamin Van Roy, and Zheng Wen. Generalization and exploration via randomized value
399 functions. *arXiv preprint arXiv:1402.0635*, 2014.
- 400 [24] Martin L. Puterman. *Markov Decision Processes: Discrete Stochastic Dynamic Programming*. John Wiley
401 & Sons, Inc., New York, NY, USA, 1994.
- 402 [25] Danilo Jimenez Rezende, Shakir Mohamed, and Daan Wierstra. Stochastic backpropagation and approxi-
403 mate inference in deep generative models. *arXiv preprint arXiv:1401.4082*, 2014.
- 404 [26] Tom Schaul, John Quan, Ioannis Antonoglou, and David Silver. Prioritized experience replay. *arXiv*
405 *preprint arXiv:1511.05952*, 2015.
- 406 [27] David W Scott. *Multivariate density estimation: theory, practice, and visualization*. John Wiley & Sons,
407 2015.
- 408 [28] David Silver, Aja Huang, Chris J Maddison, Arthur Guez, Laurent Sifre, George Van Den Driessche, Julian
409 Schrittwieser, Ioannis Antonoglou, Veda Panneershelvam, Marc Lanctot, et al. Mastering the game of go
410 with deep neural networks and tree search. *nature*, 529(7587):484–489, 2016.
- 411 [29] Richard S Sutton and Andrew G Barto. *Reinforcement learning: An introduction*, volume 1. MIT press
412 Cambridge, 1998.
- 413 [30] Matthew E Taylor, Nicholas K Jong, and Peter Stone. Transferring instances for model-based reinforcement
414 learning. In *Joint European Conference on Machine Learning and Knowledge Discovery in Databases*,
415 pages 488–505. Springer, 2008.
- 416 [31] Matthew E Taylor and Peter Stone. Transfer learning for reinforcement learning domains: A survey.
417 *Journal of Machine Learning Research*, 10(Jul):1633–1685, 2009.
- 418 [32] Hado Van Hasselt, Arthur Guez, and David Silver. Deep reinforcement learning with double q-learning.
419 2016.
- 420 [33] Aaron Wilson, Alan Fern, Soumya Ray, and Prasad Tadepalli. Multi-task reinforcement learning: a
421 hierarchical bayesian approach. In *Proceedings of the 24th international conference on Machine learning*,
422 pages 1015–1022. ACM, 2007.

423 A Proofs

424 **Theorem 2.** Let V be the fixed-point of the optimal Bellman operator T , and Q the corresponding
 425 action-value function. Define the action-gap function $g(s)$ as the difference between the value of
 426 the best action and the second best action at each state s . Let \tilde{V} be the fixed-point of the mellow
 427 Bellman operator \tilde{T} with parameter $\kappa > 0$ and denote by $\beta > 0$ the inverse temperature of the
 428 induced Boltzmann distribution (as in [1]). Let ν be a probability measure over the state-space. Then,
 429 for any $p \geq 1$:

$$\|V - \tilde{V}\|_{\nu,p}^p \leq \frac{2R_{max}}{(1-\gamma)^2} \left\| 1 - \frac{1}{1 + |\mathcal{A}| e^{-\beta g}} \right\|_{\nu,p}^p \quad (6)$$

430 *Proof.* We begin by noticing that:

$$\begin{aligned} \|V - \tilde{V}\|_{\nu,p}^p &= \|TV - \tilde{T}\tilde{V}\|_{\nu,p}^p \\ &= \|TV - \tilde{T}V + \tilde{T}V - \tilde{T}\tilde{V}\|_{\nu,p}^p \\ &\leq \|TV - \tilde{T}V\|_{\nu,p}^p + \|\tilde{T}V - \tilde{T}\tilde{V}\|_{\nu,p}^p \\ &\leq \|TV - \tilde{T}V\|_{\nu,p}^p + \gamma \|V - \tilde{V}\|_{\nu,p}^p \end{aligned}$$

431 where the first inequality follows from Minkowsky's inequality and the second one from the contrac-
 432 tion property of the mellow Bellman operator. This implies that:

$$\|V - \tilde{V}\|_{\nu,p}^p \leq \frac{1}{1-\gamma} \|TV - \tilde{T}V\|_{\nu,p}^p \quad (8)$$

433 Let us bound the norm on the right-hand side separately. In order to do that, we will bound the
 434 function $|TV(s) - \tilde{T}V(s)|$ point-wisely for any state s . By applying the definition of the optimal
 435 and mellow Bellman operators, we obtain:

$$\begin{aligned} |TV(s) - \tilde{T}V(s)| &= \left| \max_a \{R(s, a) + \gamma \mathbb{E}[V(s')]\} - \text{mm}_a \{R(s, a) + \gamma \mathbb{E}[V(s')]\} \right| \\ &= \left| \max_a Q(s, a) - \text{mm}_a Q(s, a) \right| \end{aligned}$$

436 Recall that applying the mellow-max is equivalent to computing an expectation under a Boltzmann
 437 distribution with inverse temperature β induced by κ []. Thus, we can write:

Cite MM

$$\begin{aligned} \left| \max_a Q(s, a) - \text{mm}_a Q(s, a) \right| &= \left| \sum_a \pi^*(a|s) Q(s, a) - \sum_a \pi_\beta(a|s) Q(s, a) \right| \\ &= \left| \sum_a Q(s, a) (\pi^*(a|s) - \pi_\beta(a|s)) \right| \\ &\leq \sum_a |Q(s, a)| |\pi^*(a|s) - \pi_\beta(a|s)| \\ &\leq \frac{R_{max}}{1-\gamma} \sum_a |\pi^*(a|s) - \pi_\beta(a|s)| \end{aligned} \quad (9)$$

438 where π^* is the optimal (deterministic) policy w.r.t. Q and π_β is the Boltzmann distribution induced
 439 by Q with inverse temperature β :

$$\pi_\beta(a|s) = \frac{e^{\beta Q(s,a)}}{\sum_{a'} e^{\beta Q(s,a')}}$$

440 Denote by $a_1(s)$ the optimal action for state s under Q . We can then write:

$$\begin{aligned}
\sum_a |\pi^*(a|s) - \pi_\beta(a|s)| &= |\pi^*(a_1(s)|s) - \pi_\beta(a_1(s)|s)| + \sum_{a \neq a_1(s)} |\pi^*(a|s) - \pi_\beta(a|s)| \\
&= |1 - \pi_\beta(a_1(s)|s)| + \sum_{a \neq a_1(s)} |\pi_\beta(a|s)| \\
&= 2 |1 - \pi_\beta(a_1(s)|s)|
\end{aligned} \tag{10}$$

441 Finally, let us bound this last term:

$$\begin{aligned}
|1 - \pi_\beta(a_1(s)|s)| &= \left| 1 - \frac{e^{\beta Q(s, a_1(s))}}{\sum_{a'} e^{\beta Q(s, a')}} \right| \\
&= \left| 1 - \frac{e^{\beta(Q(s, a_1(s)) - Q(s, a_2(s)))}}{\sum_{a'} e^{\beta(Q(s, a') - Q(s, a_2(s)))}} \right| \\
&= \left| 1 - \frac{e^{\beta g(s)}}{\sum_{a'} e^{\beta(Q(s, a') - Q(s, a_2(s)))}} \right| \\
&= \left| 1 - \frac{e^{\beta g(s)}}{e^{\beta g(s)} + \sum_{a' \neq a_1(s)} e^{\beta(Q(s, a') - Q(s, a_2(s)))}} \right| \\
&\leq \left| 1 - \frac{e^{\beta g(s)}}{e^{\beta g(s)} + |\mathcal{A}|} \right| \\
&= \left| 1 - \frac{1}{1 + |\mathcal{A}| e^{-\beta g(s)}} \right|
\end{aligned} \tag{11}$$

442 Combining Eq. (14), (15), and (16), we obtain:

$$\left| \max_a Q(s, a) - \min_a Q(s, a) \right| \leq \frac{2R_{max}}{1 - \gamma} \left| 1 - \frac{1}{1 + |\mathcal{A}| e^{-\beta g(s)}} \right|$$

443 Taking the norm and plugging this into Eq. (12) concludes the proof. \square

444 **Theorem 3.** Let Q^* be the fixed-point of the optimal Bellman operator T . Define the action-gap
445 function $g(s)$ as the difference between the value of the best action and the second best action at
446 each state s . Let \tilde{Q} be the fixed-point of the mellow Bellman operator \tilde{T} with parameter $\kappa > 0$ and
447 denote by $\beta_\kappa > 0$ the inverse temperature of the induced Boltzmann distribution (as in [1]). Let ν be
448 a probability measure over the state-action space. Then, for any $p \geq 1$:

$$\left\| Q^* - \tilde{Q} \right\|_{\nu, p}^p \leq \frac{2\gamma R_{max}}{(1 - \gamma)^2} \left\| \frac{1}{1 + \frac{1}{|\mathcal{A}|} e^{\beta_\kappa g}} \right\|_{\nu, p}^p \tag{7}$$

449 *Proof.* We begin by noticing that:

$$\begin{aligned}
\left\| Q^* - \tilde{Q} \right\|_{\nu, p}^p &= \left\| TQ^* - \tilde{T}\tilde{Q} \right\|_{\nu, p}^p \\
&= \left\| TQ^* - \tilde{T}Q^* + \tilde{T}Q^* - \tilde{T}\tilde{Q} \right\|_{\nu, p}^p \\
&\leq \left\| TQ^* - \tilde{T}Q^* \right\|_{\nu, p}^p + \left\| \tilde{T}Q^* - \tilde{T}\tilde{Q} \right\|_{\nu, p}^p \\
&\leq \left\| TQ^* - \tilde{T}Q^* \right\|_{\nu, p}^p + \gamma \left\| Q^* - \tilde{Q} \right\|_{\nu, p}^p
\end{aligned}$$

450 where the first inequality follows from Minkowsky's inequality and the second one from the contrac-
451 tion property of the mellow Bellman operator. This implies that:

$$\left\| Q^* - \tilde{Q} \right\|_{\nu, p}^p \leq \frac{1}{1 - \gamma} \left\| TQ^* - \tilde{T}Q^* \right\|_{\nu, p}^p \tag{12}$$

452 Let us bound the norm on the right-hand side separately. In order to do that, we will bound the
 453 function $|TQ^*(s, a) - \tilde{T}Q^*(s, a)|$ point-wisely for any state s, a . By applying the definition of the
 454 optimal and mellow Bellman operators, we obtain:

$$\begin{aligned} |TQ^*(s, a) - \tilde{T}Q^*(s, a)| &= |R(s, a) + \gamma \mathbb{E} \left[\max_{a'} Q^*(s', a') \right] - R(s, a) - \gamma \mathbb{E} \left[\text{mm}_{a'} Q^*(s', a') \right]| \\ &= \gamma \left| \mathbb{E} \left[\max_{a'} Q^*(s', a') \right] - \mathbb{E} \left[\text{mm}_{a'} Q^*(s', a') \right] \right| \\ &\leq \gamma \mathbb{E} \left[\left| \max_{a'} Q^*(s', a') - \text{mm}_{a'} Q^*(s', a') \right| \right] \end{aligned} \quad (13)$$

455 Thus, bounding this quantity reduces to bounding $|\max_a Q^*(s, a) - \text{mm}_a Q^*(s, a)|$ point-wisely
 456 for any s . Recall that applying the mellow-max is equivalent to computing an expectation under a
 457 Boltzmann distribution with inverse temperature β_κ induced by κ []. Thus, we can write:

Cite MM

$$\begin{aligned} \left| \max_a Q^*(s, a) - \text{mm}_a Q^*(s, a) \right| &= \left| \sum_a \pi^*(a|s) Q^*(s, a) - \sum_a \pi_{\beta_\kappa}(a|s) Q^*(s, a) \right| \\ &= \left| \sum_a Q^*(s, a) (\pi^*(a|s) - \pi_{\beta_\kappa}(a|s)) \right| \\ &\leq \sum_a |Q^*(s, a)| |\pi^*(a|s) - \pi_{\beta_\kappa}(a|s)| \\ &\leq \frac{R_{max}}{1 - \gamma} \sum_a |\pi^*(a|s) - \pi_{\beta_\kappa}(a|s)| \end{aligned} \quad (14)$$

458 where π^* is the optimal (deterministic) policy w.r.t. Q^* and π_{β_κ} is the Boltzmann distribution induced
 459 by Q^* with inverse temperature β_κ :

$$\pi_{\beta_\kappa}(a|s) = \frac{e^{\beta_\kappa Q^*(s, a)}}{\sum_{a'} e^{\beta_\kappa Q^*(s, a')}}.$$

460 Denote by $a_1(s)$ the optimal action for state s under Q^* . We can then write:

$$\begin{aligned} \sum_a |\pi^*(a|s) - \pi_{\beta_\kappa}(a|s)| &= |\pi^*(a_1(s)|s) - \pi_{\beta_\kappa}(a_1(s)|s)| + \sum_{a \neq a_1(s)} |\pi^*(a|s) - \pi_{\beta_\kappa}(a|s)| \\ &= |1 - \pi_{\beta_\kappa}(a_1(s)|s)| + \sum_{a \neq a_1(s)} |\pi_{\beta_\kappa}(a|s)| \\ &= 2 |1 - \pi_{\beta_\kappa}(a_1(s)|s)| \end{aligned} \quad (15)$$

461 Finally, let us bound this last term:

$$\begin{aligned} |1 - \pi_{\beta_\kappa}(a_1(s)|s)| &= \left| 1 - \frac{e^{\beta_\kappa Q^*(s, a_1(s))}}{\sum_{a'} e^{\beta_\kappa Q^*(s, a')}} \right| \\ &= \left| 1 - \frac{e^{\beta_\kappa (Q^*(s, a_1(s)) - Q^*(s, a_2(s)))}}{\sum_{a'} e^{\beta_\kappa (Q^*(s, a') - Q^*(s, a_2(s)))}} \right| \\ &= \left| 1 - \frac{e^{\beta_\kappa g(s)}}{\sum_{a'} e^{\beta_\kappa (Q^*(s, a') - Q^*(s, a_2(s)))}} \right| \\ &= \left| 1 - \frac{e^{\beta_\kappa g(s)}}{e^{\beta_\kappa g(s)} + \sum_{a' \neq a_1(s)} e^{\beta_\kappa (Q^*(s, a') - Q^*(s, a_2(s)))}} \right| \\ &\leq \left| 1 - \frac{e^{\beta_\kappa g(s)}}{e^{\beta_\kappa g(s)} + |\mathcal{A}|} \right| \\ &= \left| \frac{1}{1 + \frac{1}{|\mathcal{A}|} e^{\beta_\kappa g(s)}} \right| \end{aligned} \quad (16)$$

Combining Eq. (14), (15), and (16), we obtain:

$$\left| \max_a Q(s, a) - \min_a Q(s, a) \right| \leq \frac{2R_{max}}{1-\gamma} \left| \frac{1}{1 + \frac{1}{|\mathcal{A}|} e^{\beta_{\kappa} g(s)}} \right|$$

Finally, using Eq. (13) we get:

$$\left| TQ^*(s, a) - \tilde{T}Q^*(s, a) \right| \leq \frac{2\gamma R_{max}}{1-\gamma} \left| \frac{1}{1 + \frac{1}{|\mathcal{A}|} e^{\beta_{\kappa} g(s)}} \right|$$

Taking the norm and plugging this into Eq. (12) concludes the proof. \square

Lemma 1. Let p and ν denote probability measures over Q -functions and state-action pairs, respectively. Assume Q^* is the unique fixed-point of the optimal Bellman operator T . Then, for any $\delta > 0$, with probability at least $1 - \delta$ over the choice of a Q -function Q , the following holds:

$$\|Q - Q^*\|_{\nu}^2 \leq \frac{\mathbb{E}_p [\|B(Q)\|_{\nu}^2]}{(1-\gamma)\delta} \quad (17)$$

Proof. First notice that:

$$\begin{aligned} \|Q - Q^*\| &= \|Q + TQ - TQ - TQ^*\| \\ &\leq \|Q - TQ\| + \|TQ - TQ^*\| \\ &\leq \|Q - TQ\| + \gamma \|Q - Q^*\| \\ &= \|B(Q)\| + \gamma \|Q - Q^*\| \end{aligned}$$

which implies that:

$$\|Q - Q^*\| \leq \frac{1}{1-\gamma} \|B(Q)\|$$

Then we can write:

$$P(\|Q - Q^*\| > \epsilon) \leq P(\|B(Q)\| > \epsilon(1-\gamma)) \leq \frac{\mathbb{E}_p [\|B(Q)\|_{\nu}^2]}{(1-\gamma)\epsilon}$$

Settings the right-hand side equal to δ and solving for ϵ concludes the proof. \square

Corollary 1. Let p and ν denote probability measures over Q -functions and state-action pairs, respectively. Assume \tilde{Q} is the unique fixed-point of the mellow Bellman operator \tilde{T} . Then, for any $\delta > 0$, with probability at least $1 - \delta$ over the choice of a Q -function Q , the following holds:

$$\|Q - \tilde{Q}\|_{\nu}^2 \leq \frac{\mathbb{E}_p [\|\tilde{B}(Q)\|_{\nu}^2]}{(1-\gamma)\delta} \quad (18)$$

Lemma 2. Assume Q -functions belong to a parametric space of functions bounded by $\frac{R_{max}}{1-\gamma}$. Let p and q be arbitrary distributions over the parameter space \mathcal{W} , and ν be a probability measure over $\mathcal{S} \times \mathcal{A}$. Consider a dataset D of N samples and define $v(\mathbf{w}) \triangleq \mathbb{E}_{\nu} [\text{Var}_{\mathcal{P}} [b(\mathbf{w})]]$. Then, for any $\delta > 0$, with probability at least $1 - \delta$, the following two inequalities hold simultaneously:

$$\mathbb{E}_q [\|B(\mathbf{w})\|_{\nu}^2] \leq \mathbb{E}_q [\|B(\mathbf{w})\|_D^2] - \mathbb{E}_q [v(\mathbf{w})] + \frac{\lambda}{N} KL(q||p) + 4 \frac{R_{max}^2}{(1-\gamma)^2} \sqrt{\frac{\log \frac{2}{\delta}}{2N}} \quad (19)$$

479

$$\mathbb{E}_q [\|B(\mathbf{w})\|_D^2] \leq \mathbb{E}_q [\|B(\mathbf{w})\|_{\nu}^2] + \mathbb{E}_q [v(\mathbf{w})] + \frac{\lambda}{N} KL(q||p) + 4 \frac{R_{max}^2}{(1-\gamma)^2} \sqrt{\frac{\log \frac{2}{\delta}}{2N}} \quad (20)$$

480 *Proof.* From Hoeffding's inequality we have:

$$P \left(\left| \mathbb{E}_{\nu, \mathcal{P}} \left[\|B(\mathbf{w})\|_D^2 \right] - \|B(\mathbf{w})\|_D^2 \right| > \epsilon \right) \leq 2 \exp \left(- \frac{2N\epsilon^2}{\left(2 \frac{R_{max}}{1-\gamma} \right)^4} \right)$$

481 which implies that, for any $\delta > 0$, with probability at least $1 - \delta$:

$$\left| \mathbb{E}_{\nu, \mathcal{P}} \left[\|B(\mathbf{w})\|_D^2 \right] - \|B(\mathbf{w})\|_D^2 \right| \leq 4 \frac{R_{max}^2}{(1-\gamma)^2} \sqrt{\frac{\log \frac{2}{\delta}}{2N}}$$

482 Under independence assumptions, the expected TD error can be re-written as:

$$\begin{aligned} \mathbb{E}_{\nu, \mathcal{P}} \left[\|B(\mathbf{w})\|_D^2 \right] &= \mathbb{E}_{\nu, \mathcal{P}} \left[\frac{1}{N} \sum_{i=1}^N (r_i + \gamma \min_{a'} Q_{\mathbf{w}}(s'_i, a') - Q_{\mathbf{w}}(s_i, a_i))^2 \right] \\ &= \mathbb{E}_{\nu, \mathcal{P}} \left[(R(s, a) + \gamma \min_{a'} Q_{\mathbf{w}}(s', a') - Q_{\mathbf{w}}(s, a))^2 \right] \\ &= \mathbb{E}_{\nu} [\mathbb{E}_{\mathcal{P}} [b(\mathbf{w})^2]] \\ &= \mathbb{E}_{\nu} [Var_{\mathcal{P}} [b(\mathbf{w})] + \mathbb{E}_{\mathcal{P}} [b(\mathbf{w})]^2] \\ &= v(\mathbf{w}) + \|B(\mathbf{w})\|_{\nu}^2 \end{aligned}$$

483 where $v(\mathbf{w}) \triangleq \mathbb{E}_{\nu} [Var_{\mathcal{P}} [b(\mathbf{w})]]$. Thus:

$$\left| \|B(\mathbf{w})\|_{\nu}^2 + v(\mathbf{w}) - \|B(\mathbf{w})\|_D^2 \right| \leq 4 \frac{R_{max}^2}{(1-\gamma)^2} \sqrt{\frac{\log \frac{2}{\delta}}{2N}} \quad (21)$$

484 From the change of measure inequality [], we have that, for any measurable function $f(\mathbf{w})$ and any
485 two probability measures p and q :

$$\log \mathbb{E}_p \left[e^{f(\mathbf{w})} \right] \geq \mathbb{E}_q [f(\mathbf{w})] - KL(q||p)$$

Find a reference for this

486 Thus, multiplying both sides of (21) by $\lambda^{-1}N$ and applying the change of measure inequality with
487 $f(\mathbf{w}) = \lambda^{-1}N \left| \|B(\mathbf{w})\|_{\nu}^2 + v(\mathbf{w}) - \|B(\mathbf{w})\|_D^2 \right|$, we obtain:

$$\mathbb{E}_q [f(\mathbf{w})] - KL(q||p) \leq \log \mathbb{E}_p \left[e^{f(\mathbf{w})} \right] \leq 4 \frac{R_{max}^2 \lambda^{-1}N}{(1-\gamma)^2} \sqrt{\frac{\log \frac{2}{\delta}}{2N}}$$

488 where the second inequality holds since the right-hand side of (21) does not depend on \mathbf{w} . Finally,
489 we can explicitly write:

$$\mathbb{E}_q \left[\left| \|B(\mathbf{w})\|_{\nu}^2 + v(\mathbf{w}) - \|B(\mathbf{w})\|_D^2 \right| \right] \leq \frac{\lambda}{N} KL(q||p) + 4 \frac{R_{max}^2}{(1-\gamma)^2} \sqrt{\frac{\log \frac{2}{\delta}}{2N}}$$

490 from which the lemma follows straightforwardly. \square

491 **Lemma 3.** Let p be a prior distribution over the parameter space \mathcal{W} , and ν be a probability measure
492 over $\mathcal{S} \times \mathcal{A}$. Assume $\hat{\xi}$ is the minimizer of $ELBO(\xi) = \mathbb{E}_{q_{\xi}} \left[\|B(\mathbf{w})\|_D^2 \right] + \frac{\lambda}{N} KL(q_{\xi}||p)$ for a
493 dataset D of N samples. Define $v(\mathbf{w}) \triangleq \mathbb{E}_{\nu} [Var_{\mathcal{P}} [b(\mathbf{w})]]$. Then, for any $\delta > 0$, with probability at
494 least $1 - \delta$:

$$\mathbb{E}_{q_{\hat{\xi}}} \left[\|B(\mathbf{w})\|_{\nu}^2 \right] \leq \inf_{\xi \in \Xi} \left\{ \mathbb{E}_{q_{\xi}} \left[\|B(\mathbf{w})\|_{\nu}^2 \right] + \mathbb{E}_{q_{\xi}} [v(\mathbf{w})] + 2 \frac{\lambda}{N} KL(q_{\xi}||p) \right\} + 2 \frac{R_{max}^2}{(1-\gamma)^2} \sqrt{\frac{\log \frac{2}{\delta}}{N}}$$

495 *Proof.* Let us use Lemma 2 for the specific choice $q = q_{\hat{\xi}}$. From Eq. (19), we have:

$$\begin{aligned} \mathbb{E}_{q_{\hat{\xi}}} [\|B(\mathbf{w})\|_{\nu}^2] &\leq \mathbb{E}_{q_{\hat{\xi}}} [\|B(\mathbf{w})\|_D^2] - \mathbb{E}_{q_{\hat{\xi}}} [v(\mathbf{w})] + \frac{\lambda}{N} KL(q_{\hat{\xi}} \| p) + 4 \frac{R_{max}^2}{(1-\gamma)^2} \sqrt{\frac{\log \frac{2}{\delta}}{2N}} \\ &\leq \mathbb{E}_{q_{\hat{\xi}}} [\|B(\mathbf{w})\|_D^2] + \frac{\lambda}{N} KL(q_{\hat{\xi}} \| p) + 4 \frac{R_{max}^2}{(1-\gamma)^2} \sqrt{\frac{\log \frac{2}{\delta}}{2N}} \\ &= \inf_{\xi \in \Xi} \left\{ \mathbb{E}_{q_{\xi}} [\|B(\mathbf{w})\|_D^2] + \frac{\lambda}{N} KL(q_{\xi} \| p) \right\} + 4 \frac{R_{max}^2}{(1-\gamma)^2} \sqrt{\frac{\log \frac{2}{\delta}}{2N}} \end{aligned}$$

496 where the second inequality holds since $v(\mathbf{w}) > 0$, while the equality holds from the definition of $\hat{\xi}$.

497 We can now use Eq. (20) to bound $\mathbb{E}_{q_{\hat{\xi}}} [\|B(\mathbf{w})\|_D^2]$, thus obtaining:

$$\mathbb{E}_{q_{\hat{\xi}}} [\|B(\mathbf{w})\|_{\nu}^2] \leq \inf_{\xi \in \Xi} \left\{ \mathbb{E}_{q_{\xi}} [\|B(\mathbf{w})\|_{\nu}^2] + \mathbb{E}_{q_{\xi}} [v(\mathbf{w})] + 2 \frac{\lambda}{N} KL(q_{\xi} \| p) \right\} + 2 \frac{R_{max}^2}{(1-\gamma)^2} \sqrt{\frac{\log \frac{2}{\delta}}{N}}$$

498 This concludes the proof. \square

499 B Additional Details on the Algorithms

500 B.1 Gaussian Variational Transfer

501 Under Gaussian distributions, all quantities of interest for using Alg. 1 can be computed very easily.
502 The KL divergence between the prior and approximate posterior can be computed in closed-form as:

$$KL(q_{\xi}(\mathbf{w}) \| p(\mathbf{w})) = \frac{1}{2} \left(\log \frac{|\Sigma_p|}{|\Sigma|} + \text{Tr}(\Sigma_p^{-1} \Sigma) + (\boldsymbol{\mu} - \boldsymbol{\mu}_p)^T \Sigma_p^{-1} (\boldsymbol{\mu} - \boldsymbol{\mu}_p) - K \right) \quad (22)$$

503 for $\xi = (\boldsymbol{\mu}, \mathbf{L})$ and $\Sigma = \mathbf{L}\mathbf{L}^T$. Its gradients with respect to the variational parameters are:

$$\nabla_{\boldsymbol{\mu}} KL(q_{\xi}(\mathbf{w}) \| p(\mathbf{w})) = \Sigma_p^{-1} (\boldsymbol{\mu} - \boldsymbol{\mu}_p) \quad (23)$$

504

$$\nabla_{\mathbf{L}} KL(q_{\xi}(\mathbf{w}) \| p(\mathbf{w})) = \Sigma_p^{-1} \mathbf{L} - (\mathbf{L}^{-1})^T \quad (24)$$

505 Finally, the gradients w.r.t. the expected likelihood term of the variational objective (2) can be
506 computed using the reparameterization trick (e.g., [12, 25]):

$$\nabla_{\boldsymbol{\mu}} \mathbb{E}_{\mathbf{w} \sim \mathcal{N}(\boldsymbol{\mu}, \mathbf{L}\mathbf{L}^T)} [\|B(\mathbf{w})\|_D^2] = \mathbb{E}_{\mathbf{v} \sim \mathcal{N}(\mathbf{0}, \mathbf{I})} [\nabla_{\mathbf{w}} \|B(\mathbf{w})\|_D^2] \quad \text{for } \mathbf{w} = \mathbf{L}\mathbf{v} + \boldsymbol{\mu} \quad (25)$$

507

$$\nabla_{\mathbf{L}} \mathbb{E}_{\mathbf{w} \sim \mathcal{N}(\boldsymbol{\mu}, \mathbf{L}\mathbf{L}^T)} [\|B(\mathbf{w})\|_D^2] = \mathbb{E}_{\mathbf{v} \sim \mathcal{N}(\mathbf{0}, \mathbf{I})} [\nabla_{\mathbf{w}} \|B(\mathbf{w})\|_D^2 \cdot \mathbf{v}^T] \quad \text{for } \mathbf{w} = \mathbf{L}\mathbf{v} + \boldsymbol{\mu} \quad (26)$$

508 B.2 Mixture of Gaussian Variational Transfer

509 C Additional Details on the Experiments

510 C.1 The Rooms Problem

511 C.2 Classic Control

512 C.3 Maze Navigation