$\langle X_i X_i \rangle = M \langle X_i X_i \rangle M^T + \Delta_{ii}$, (85)where $X_i = (x, p_x, y, p_y, z, \delta)$ is the deviation from the closed orbit at the entrance of the beam line, M the one-turn

The equilibrium beam envelope (second order moment) $\langle X_i X_j \rangle$ is calculated by the EMITTANCE (EMIT) command

scattering. The excitation Δ_{ij} is affected by the envelope in the case of intrabeam (INTRA). The transfer matrix M can be affected by the envelope due to space-charge in the case of WSPAC. Thus iterations are done for such cases.

transfer matrix including the damping, and Δ_{ij} the one-turn excitation due to synchrotron radiation and intrabeam

In the case of an ideal ring, as the intrinsic vertical emittance might be too small, the intrabema or space charge effects can be unrealistically large. For such cases, a global variable MINCOUP is useful to specify their minimum values as:

values as:
$$\varepsilon_{x,y} = \text{Max} \left[\varepsilon_{x,y}^{0}, \text{MINCOUP} \times (\varepsilon_{y}^{0} + \varepsilon_{y}^{0}) \right], \tag{86}$$

where $\varepsilon_{x,y}^0$ are the emittances given only by the lattice.

and Emittance[] function by solving: