ADC Interfacing on eYFi-Mega Board

e-Yantra Team

Embedded Real-Time Systems (ERTS) Lab
Indian Institute of Technology, Bombay

IIT Bombay
July 5, 2022

What is ADC and why do we need it?

What is ADC and why do we need it?

Analog-to-Digital Converter (ADC) is a circuitry that takes an analog signal as input and provides the digital form of it as output.

Need for ADC:

What is ADC and why do we need it?

Analog-to-Digital Converter (ADC) is a circuitry that takes an analog signal as input and provides the digital form of it as output.

Need for ADC:

1. Most of the physical quantities around us are continuous: the quantity can take any value within the certain range, for example: atmospheric temperature.

What is ADC and why do we need it?

Analog-to-Digital Converter (ADC) is a circuitry that takes an analog signal as input and provides the digital form of it as output.

Need for ADC:

1. Most of the physical quantities around us are continuous: the quantity can take any value within the certain range, for example: atmospheric temperature.
2. Since micro-controller is a digital device for further processing, the Analog Signal needs to converted into digital signal.

What is ADC and why do we need it?

Analog-to-Digital Converter (ADC) is a circuitry that takes an analog signal as input and provides the digital form of it as output.

Need for ADC:

1. Most of the physical quantities around us are continuous: the quantity can take any value within the certain range, for example: atmospheric temperature.
2. Since micro-controller is a digital device for further processing, the Analog Signal needs to converted into digital signal.
3. Hence, we need to convert the analog signal into digital format using ADC.

What is ADC and why do we need it?

Analog-to-Digital Converter (ADC) is a circuitry that takes an analog signal as input and provides the digital form of it as output.

Need for ADC:

1. Most of the physical quantities around us are continuous: the quantity can take any value within the certain range, for example: atmospheric temperature.
2. Since micro-controller is a digital device for further processing, the Analog Signal needs to converted into digital signal.
3. Hence, we need to convert the analog signal into digital format using ADC.

Steps in ADC

Steps involved in A-D conversion are:

Steps in ADC

Steps involved in A-D conversion are:

- **Sampling**
- Quantization
- Encoding

Steps in ADC

Steps involved in A-D conversion are:

- **Sampling**
- Quantization
- Encoding

- Sampling: Converts continuous time analog signal into discrete version of input

Steps in ADC

Steps involved in A-D conversion are:

- **Sampling**
- Quantization
- Encoding

- Sampling: Converts continuous time analog signal into discrete version of input

Steps in ADC

Steps involved in A-D conversion are:

- **Sampling**
- Quantization
- Encoding

- Sampling: Converts continuous time analog signal into discrete version of input



Steps in ADC

Steps involved in A-D conversion are:

- Sampling
- **Quantization**
- Encoding

- Quantization: Maps range of input analog values to nearest integer value

Steps in ADC

Steps involved in A-D conversion are:

- Sampling
- **Quantization**
- Encoding

- Quantization: Maps range of input analog values to nearest integer value



Steps in ADC

Steps involved in A-D conversion are:

- Sampling
- Quantization
- **Encoding**

- Encoding: Encodes quantized signal into sequence of binary bits

Steps in ADC

Steps involved in A-D conversion are:

- Sampling
- Quantization
- **Encoding**

- Encoding: Encodes quantized signal into sequence of binary bits



Features of in-built ADC

Features of in-built ADC

- 10-bit Resolution
- 13 - 260 μs Conversion Time
- 16 Multiplexed Single Ended Input Channels
- 14 Differential Input Channels
- 0 - VCC ADC Input Voltage Range
- Selectable 2.56V or 1.1V ADC Reference Voltage
- Free Running or Single Conversion Mode
- Interrupt on ADC Conversion Complete

ADC Channels

ADC Channels

Pin Name	ADC Channel
PF0	ADC0
PF1	ADC1
PF2	ADC2
PF3	ADC3
PF4	ADC4
PF5	ADC5
PF6	ADC6
PF7	ADC7

Pin Name	ADC Channel
PK0	ADC8
PK1	ADC9
PK2	ADC10
PK3	ADC11
PK4	ADC12
PK5	ADC13
PK6	ADC14
PK7	ADC15

ADC Header on eYFi-Mega Board

ADC Header on eYFi-Mega Board



Introduction to Light Dependent Resistor

Introduction to Light Dependent Resistor



- It is an electronic device which is responsive to light

Introduction to Light Dependent Resistor



- It is an electronic device which is responsive to light
- The resistance values of LDR:

Introduction to Light Dependent Resistor



- It is an electronic device which is responsive to light
- The resistance values of LDR:
  1. Darkness: several mega-ohms

Introduction to Light Dependent Resistor



- It is an electronic device which is responsive to light
- The resistance values of LDR:
  1. Darkness: several mega-ohms
  2. Brightness: hundred ohms

Introduction to Light Dependent Resistor



- It is an electronic device which is responsive to light
- The resistance values of LDR:
  1. Darkness: several mega-ohms
  2. Brightness: hundred ohms

Interfacing Diagram

Interfacing Diagram



Assignment 1

Assignment 1

1. **Problem Statement:**
   Printing the values of LDR in Serial Monitor

Assignment 1

1. **Problem Statement:**
   Printing the values of LDR in Serial Monitor
   - **LDR Pin » A0**

Assignment 1

1. **Problem Statement:**
   Printing the values of LDR in Serial Monitor
   - **LDR Pin » A0**
2. **Code:**

Assignment 1

1. **Problem Statement:**
   Printing the values of LDR in Serial Monitor
   - **LDR Pin » A0**
2. **Code:**

```
//Select the input pin for LDR
SensorPin = A0

//Getting LDR values using the function analogRead()
SensorVal = analogRead(SensorPin)

//Printing the values in Serial Monitor
Serial.println(SensorVal)
```

Assignment 1

1. **Problem Statement:**
   Printing the values of LDR in Serial Monitor
   - **LDR Pin » A0**
2. **Code:**

```
//Select the input pin for LDR
SensorPin = A0

//Getting LDR values using the function analogRead()
SensorVal = analogRead(SensorPin)

//Printing the values in Serial Monitor
Serial.println(SensorVal)
```

Getting the Analog Voltage

Getting the Analog Voltage



Getting the Analog Voltage



Getting the Analog Voltage



- Voltage received by A0 pin can be found by using following formula:

Getting the Analog Voltage



- Voltage received by A0 pin can be found by using following formula:

$$Vo = \frac{R2}{R1 + R2} * Vin$$

Getting the Analog Voltage



- Voltage received by A0 pin can be found by using following formula:

$$Vo = \frac{R2}{R1 + R2} * Vin$$

- Given: R2 = 100K ohms and Vin = 5V

Getting the Analog Voltage



- Voltage received by A0 pin can be found by using following formula:

$$Vo = \frac{R2}{R1 + R2} * Vin$$

- Given: R2 = 100K ohms and Vin = 5V

1. Darkness: 1 mega-ohms

Getting the Analog Voltage



- Voltage received by A0 pin can be found by using following formula:

$$Vo = \frac{R2}{R1 + R2} * Vin$$

- Given: R2 = 100K ohms and Vin = 5V

1. Darkness: 1 mega-ohms :: Vo =

Getting the Analog Voltage



- Voltage received by A0 pin can be found by using following formula:

$$Vo = \frac{R2}{R1 + R2} * Vin$$

- Given: R2 = 100K ohms and Vin = 5V

1. Darkness: 1 mega-ohms :: Vo = 0.45V

Getting the Analog Voltage



- Voltage received by A0 pin can be found by using following formula:

$$Vo = \frac{R2}{R1 + R2} * Vin$$

- Given: R2 = 100K ohms and Vin = 5V

1. Darkness: 1 mega-ohms :: Vo = 0.45V
2. Brightness: hundred ohms

Getting the Analog Voltage



- Voltage received by A0 pin can be found by using following formula:

$$Vo = \frac{R2}{R1 + R2} * Vin$$

- Given: R2 = 100K ohms and Vin = 5V

1. Darkness: 1 mega-ohms :: Vo = 0.45V
2. Brightness: hundred ohms :: Vo =

Getting the Analog Voltage



- Voltage received by A0 pin can be found by using following formula:

$$Vo = \frac{R2}{R1 + R2} * Vin$$

- Given: R2 = 100K ohms and Vin = 5V

1. Darkness: 1 mega-ohms :: Vo = 0.45V
2. Brightness: hundred ohms :: Vo = 4.99V

Creating your own ADC Calculator

Creating your own ADC Calculator

- Following is the conversion formula for ADC:

Creating your own ADC Calculator

- Following is the conversion formula for ADC:

$$\text{Digital Value} = \frac{\text{Resolution of ADC} * \text{Analog Voltage Measured}}{\text{Reference Voltage}}$$

Creating your own ADC Calculator

- Following is the conversion formula for ADC:

$$\text{Digital Value} = \frac{\text{Resolution of ADC} * \text{Analog Voltage Measured}}{\text{Reference Voltage}}$$

- ADC on eYFi-Mega: 10-bit ADC

Creating your own ADC Calculator

- Following is the conversion formula for ADC:

$$\text{Digital Value} = \frac{\text{Resolution of ADC} * \text{Analog Voltage Measured}}{\text{Reference Voltage}}$$

- ADC on eYFi-Mega: 10-bit ADC
- For example: Resolution of ADC = 1023, Reference Voltage = 5V

Creating your own ADC Calculator

- Following is the conversion formula for ADC:

$$\text{Digital Value} = \frac{\text{Resolution of ADC} * \text{Analog Voltage Measured}}{\text{Reference Voltage}}$$

- ADC on eYFi-Mega: 10-bit ADC
- For example: Resolution of ADC = 1023, Reference Voltage = 5V

1. Analog voltage = 2.12 V => Digital value =

Creating your own ADC Calculator

- Following is the conversion formula for ADC:

$$\text{Digital Value} = \frac{\text{Resolution of ADC} * \text{Analog Voltage Measured}}{\text{Reference Voltage}}$$

- ADC on eYFi-Mega: 10-bit ADC
- For example: Resolution of ADC = 1023, Reference Voltage = 5V

1. Analog voltage = 2.12 V => Digital value = 433

Creating your own ADC Calculator

- Following is the conversion formula for ADC:

$$\text{Digital Value} = \frac{\text{Resolution of ADC} * \text{Analog Voltage Measured}}{\text{Reference Voltage}}$$

- ADC on eYFi-Mega: 10-bit ADC
- For example: Resolution of ADC = 1023, Reference Voltage = 5V

1. Analog voltage = 2.12 V => Digital value = 433
2. Digital value = 863 => Analog voltage =

Creating your own ADC Calculator

- Following is the conversion formula for ADC:

$$\text{Digital Value} = \frac{\text{Resolution of ADC} * \text{Analog Voltage Measured}}{\text{Reference Voltage}}$$

- ADC on eYFi-Mega: 10-bit ADC
- For example: Resolution of ADC = 1023, Reference Voltage = 5V

1. Analog voltage = 2.12 V => Digital value = 433
2. Digital value = 863 => Analog voltage = 4.22 V

Creating your own ADC Calculator

- Following is the conversion formula for ADC:

$$\text{Digital Value} = \frac{\text{Resolution of ADC} * \text{Analog Voltage Measured}}{\text{Reference Voltage}}$$

- ADC on eYFi-Mega: 10-bit ADC
- For example: Resolution of ADC = 1023, Reference Voltage = 5V

1. Analog voltage = 2.12 V => Digital value = 433
2. Digital value = 863 => Analog voltage = 4.22 V

Assignment 2

Assignment 2

1. **Problem Statement:**
   Setting threshold for turning the LED On or Off

Assignment 2

1. **Problem Statement:**
   Setting threshold for turning the LED On or Off
   - **LDR Pin » A0**
   - **LED Pin » 6**

Assignment 2

1. **Problem Statement:**
   Setting threshold for turning the LED On or Off
   - **LDR Pin » A0**
   - **LED Pin » 6**
2. **Code:**

Assignment 2

1. **Problem Statement:**
   Setting threshold for turning the LED On or Off
   - **LDR Pin » A0**
   - **LED Pin » 6**
2. **Code:**

```
//setting led as output
pinMode(13, OUTPUT)

//logic for turning the led on or off
if(SensorVal < threshold)
==> turn on led
else
==> turn off led
```

Assignment 2

1. **Problem Statement:**
   Setting threshold for turning the LED On or Off
   - **LDR Pin » A0**
   - **LED Pin » 6**
2. **Code:**

```
//setting led as output
pinMode(13, OUTPUT)

//logic for turning the led on or off
if(SensorVal < threshold)
==> turn on led
else
==> turn off led
```

Thank You!

Post your queries on: helpdesk@e-yantra.org