

Realistic Optimization-based Driving Using a Constrained Double-Integrator Model

Andreas Belavic

Technical University of Munich

March 31, 2025

Motivation & Problem Statement

- Autonomous driving demands safe, real-time trajectory planning.
- Balancing model accuracy with computational efficiency is critical.
- Our approach uses convex optimization with a constrained double-integrator model.

[Placeholder: Schematic diagram of motion planning challenges]

```

ers/andreasbelavic/bachelor-thesis/code/benchmark-
rs/andreasbelavic/bachelor-thesis/code/benchmark-r
s{video-thumbnail.png}}{VPlayer.swf}

$[1]$ M.

based prediction of traffic participants on arbitr
Vehicles, 2016.}

```

- Reformulates trajectory planning as a convex optimization problem.
- Simplifies vehicle dynamics via the double-integrator model.
- Applies feedback linearization and convex inner approximations.

[Placeholder: Block diagram of the planning framework]

- Simplified dynamics: considers only position and velocity.
- Ignores orientation for computational efficiency.
- Leads to a convex formulation ideal for real-time planning.

[Placeholder: Diagram of double integrator dynamics]

- Captures vehicle orientation and steering dynamics.
- More realistic than the double integrator but computationally heavier.
- Often used for validation against simplified models.

[Placeholder: Diagram of the bicycle model representation]

- Transforms global coordinates into a path-following system.
- Simplifies handling of road curvature and lateral deviations.

[Placeholder: Illustration of the Frenet frame]

- Multi-layered approach: global route, behavioral layer, local trajectory optimization.
- Our focus: the local planner using convex optimization.

[Placeholder: Block diagram of planning layers]

- Ensures smooth and dynamically feasible trajectories.
- Allows efficient solution of sub-problems to global optimality.
- Supports real-time implementation.

See related discussions in Chapters 3 and 4.

- Linearizes nonlinear vehicle dynamics via state feedback.
- Decouples acceleration and steering commands.
- Simplifies controller design.

[Placeholder: Schematic showing feedback linearization]

- Incorporates physical limits: acceleration, velocity, and road boundaries.
- Uses convex inner approximations for non-convex constraints.
- Maintains safety and feasibility.

[Placeholder: Diagram of constraint mapping]

- Two approaches: interval fitting and Cylindrical Algebraic Decomposition (CAD).
- Derives an inscribed polytope for the feasible set.
- Balances computational efficiency with accuracy.

[Placeholder: Graphical comparison of interval fitting and CAD]

- Road segments, planner configurations, and soft constraints are defined.
- Simulation scenarios mimic realistic driving conditions.
- Ensures the evaluation is comprehensive.

[Placeholder: Table summarizing simulation parameters]

- Metrics: trajectory feasibility, computational time, and safety margins.
- Multiple scenarios: straight roads, curved segments, and dynamic obstacles.

[Placeholder: Diagram or chart of evaluation metrics]

- Scenario: Moderate-speed driving on a straight road.
- Result: Smooth trajectory with rapid solver convergence.

[Placeholder: Simulation snapshot of Scenario 1]

- Scenario: Handling a sharp curve.
- Result: Effective management of lateral deviations.

[Placeholder: Simulation snapshot of Scenario 2]

- Optimization runs in real time under dynamic conditions.
- Solver times validate the framework's efficiency.

[Placeholder: Plot of solver runtime vs. scenario complexity]

- Double integrator: Fast and efficient, less detailed.
- Bicycle model: Higher fidelity but increased computational load.
- Trade-offs guide model selection based on application needs.

[Placeholder: Comparative table/graph]

- Convex formulation ensures global optimality within sub-problems.
- Robust to dynamic environmental changes.
- Provides a foundation for scalable autonomous driving solutions.

- Trade-off: Simplified models may sacrifice some accuracy.
- Conservative approximations can limit optimality.
- Extension to highly dynamic scenarios remains challenging.

[Placeholder: Diagram illustrating limitations]

- Incorporate full dynamic models for enhanced accuracy.
- Integrate with sensor data for real-world validation.
- Develop adaptive control strategies to improve performance.

[Placeholder: Flowchart of future research directions]

Key Findings and Contributions

- Proposed a convex optimization framework for motion planning.
- Demonstrated realistic, safe trajectories with a constrained double-integrator.
- Validated through extensive simulations and performance evaluations.

- Enhances real-time trajectory planning capabilities.
- Improves safety and efficiency in autonomous vehicle operations.
- Lays groundwork for further advancements in motion planning.

Impact discussed in the thesis discussion section.

- How does convex approximation affect optimality?
- What are the trade-offs of using a double-integrator model?
- How scalable is the approach for complex, dynamic scenarios?

[Placeholder: List of potential discussion questions]

- Reviewed the modeling, optimization, and simulation of our framework.
- Highlighted benefits, limitations, and future research directions.
- Emphasized the importance of real-time feasibility and safety.

[Placeholder: Summary diagram of the presentation]

- Presented a comprehensive, convex optimization framework for motion planning.
- Balanced computational efficiency with realistic vehicle dynamics.
- Contributed to advancing motion planning in autonomous driving.

[Placeholder: Final summary graphic]

Temporary page!

\LaTeX was unable to guess the total number of pages correctly. There was some unprocessed data that should have been added to the document, so this extra page has been added to receive it.

If you rerun the document (without altering it) this surplus page will disappear, because \LaTeX now knows how many pages to expect for the document.