



**UNIVERSITÄT
BAYREUTH**

University of Bayreuth
Institute for Computer Science

Bachelor Thesis

in Applied Computer Science

Topic: Randomly Generated CFGs, The CYK-Algorithm
And A GUI

Author: Andreas Braun <andreasbraun5@aol.com>
Matrikel-Nr. 1200197

Version date: February 12, 2017

1. Supervisor: Prof. Dr. Wim Martens
2. Supervisor: Tina Trautner

To my parents.

Abstract

The abstract of this thesis will be found here.

Zusammenfassung

Hier steht die Zusammenfassung dieser Bachelorarbeit.

Contents

1	Introduction	9
2	Technology Overview	10
3	Algorithms	11
4	Course of Action	13
	Used software	15
	Listings	17
	Tables	19
	References	21

1 Introduction

2 Technology Overview

3 Algorithms

Algorithm descriptions here.

RightHandSideElements (rhse) are terminals like "a, b, ..." and compound variables like "AB, AC, ...".

LeftHandSideElements (lhse) are variables like "A, B, ...".

```

1 Algorithm: distributeDiceRollRightHandSideElements
2 Input: grammar, setRhse, minCount, maxCount, listVariables;
3 Output: grammar;
4
5 for(RightHandSideElement rhse : setRightHandSideElements){
6     // countWillBeAdded is between [minCount, maxCount].
7     countWillBeAdded = diceRoll();
8     while(listVariables.size() > countWillBeAdded){
9         Remove one variable of listVariables via dice roll;
10    }
11    for(Variable var : listVariables){
12        grammar.addProduction "var --> rhse";
13    }
14 }
15 return grammar;

```

Listing 1: distributeDiceRollRightHandSideElements

```

1 Algorithm: CYK.calculateSetVAdvanced
2 Input: grammar, word;
3 Output: Set<VariableK>[][] cYKMatrix;
4
5 Set<VariableK>[][] cYKMatrix = new Set<VariableK>[wordSize][wordSize];
6 cYKMatrix = calculateCYKMatrix;
7 return cYKMatrix;

```

Listing 2: CYK.calculateSetVAdvanced

```

1 Algorithm: GeneratorGrammarDiceRollTopDownMartens
2 Input: word, settings;
3 Output: grammar;
4 Note: Keep in mind that the setV matrix is a upper right matrix. But the
5 description of how the algorithm works is done, as if the setV pyramid
6 points downwards (reflection on the diagonal + rotation to the left).
7 Regarding one cell, its upper left cell and its upper right cell
8 are looked at. setV[i][j] = down cell. setV[i + 1][j] = upper right cell
9 setV[i][j - 1] = upper left cell. With wordSize = 5, the Visited indexes
10 are as following: [01->12->23->34; 02->13->24; 03->14; 04;]
11
12 Grammar grammar = new Grammar();
13 // Distribute the terminals.
14 grammar = distributeDiceRollRightHandSideElements(
15     grammar, settingsTerminals, minCountTerminals,
16     maxCountTerminals, settingsListVariables
17 );
18 // Distribute the compound variables.
19 Set<VariableKWrapper> [][] setVAdvanced;
20 // Fill the diagonal of the matrix with:
21 setVAdvanced = CYK.calculateSetVAdvanced( grammar, word );
22
23 for(Cell cellToBeVisited : setVAdvanced){
24     setVariableCompound = calculate all the possible tupels of
25         ({varLeft}, {varRight});
26     for(VariableCompound varComp : setVariableCompound){
27         // Because of dice rolling anyways and lots of grammars
28         // being generated, no varComp is added if the production
29         // already exists.
30         grammar = distributeDiceRollRightHandSideElements(
31             grammar, varComp, minCountVarComp,
32             maxCountVarComp, settingsListVariables
33         );
34         setVAdvanced = CYK.calculateSetVAdvanced( grammar, word );
35     }
36 }
37 return grammar;

```

Listing 3: GeneratorGrammarDiceRollTopDownMartens

4 Course of Action

The informal goal is to find a suitable combination of a grammar and a word that meets the demands of an exam exercise. Also the CYK pyramid and one derivation tree of the word must be generated automatically as a "solution picture".

Firstly the exam exercise must have an upper limit of variables per cell while computing the CYK-pyramid.

Secondly the exam exercise must have one or more "special properties" so that it can be checked if the students have clearly understood the algorithm, e.g. "Excluding the possibility of luck."

The more formal goal is identify and determine parameters that in general can be used to define the properties of a grammar, so that the demanded restrictions are met. Also parameters could be identified for words, but "which is less likely to contribute, than the parameters of the grammar." [Second appointment with Martens]

Some introductory stuff:

Possible basic approaches for getting these parameters are the Rejection Sampling method and the "Tina+Wim" method.

Also backtracking plays some role, but right now I don't know where to put it. Backtracking is underapproach to Rejection Sampling.

Note: Starting with one half of a word and one half of a grammar.

Identify restrictions (=parameters) regarding the grammar.

Maybe find restrictions regarding the words, too.

Procedures for automated generation. Each generation procedure considers different restrictions and restriction combinations. The restrictions within one generation procedure can be optimized on its own. Up till now:

Generating grammars: DiceRolling, ...

Generating words: DiceRolling, ...

Parameter optimisation via theoretical and/or benchmarking approach.

Benchmarking = generate N grammars and test them, (N=100000).

Define a success rate and try to increase it.

The overall strategy is as following:

- 1.) Identify theoretically a restriction/parameter for the grammar. Think about the influence it will have. Think also about correlations between the restrictions.
- 2.) Validate the theoretical conclusion with the benchmark. Test out the influence of this parameter upon the success rate. Try different parameter settings.

The ordering of step 1 and step 2 can be changed.

Used software

Listings

Following are some interesting classes referenced in the thesis that were too long to fit into the text.

Tables

This section contains all tables referenced in this thesis.

References

- [1] JSR 220: Enterprise Java Beans 3.0 <https://jcp.org/en/jsr/detail?id=220>, 09/09/2015

