



**Fabrik der Zukunft**

# **FDZ network commands**

Thomas Herpich

SS2017 - Network commands

## **Abstract**

This document describes the network commands used by the FDZ.

# Inhaltsverzeichnis

<b>1 JSAP</b>	<b>4</b>
1.1 Commands between Java-SAP interface (JS) and CentralControl (ST)	4
1.1.1 Common errors	4
1.1.2 Start a product-pallet fill order	4
1.1.3 Request the stock	5
1.1.4 Cancel order	5
1.2 Commands between GUI (GU) and JSAP (JS)	5
1.2.1 New order	5
1.2.2 Request status of an order	6
<b>2 Robot</b>	<b>7</b>
2.1 Commands between CentralControl (ST) and RobotControl(Sr)	7
2.1.1 Common errors	7
2.1.2 Take pallet from transport belt	7
2.1.3 Fill product-pallet	8
2.1.4 Move Pallet to transport belt	8
2.1.5 Swap storage-pallets	8
2.1.6 Resort stock-pallet	9
2.1.7 Shut down control	9
2.2 Commands between RobotControl (Sr) and Robot (ro)	9
2.2.1 Common errors	9
2.2.2 Move pallet from transport belt to place ABX	9
2.2.3 Move pallet from place ABX to transport belt	10
2.2.4 Move smarite form pallet and index to pallet and index	10
2.2.5 Shut down robot	10
<b>3 Stock</b>	<b>11</b>
3.1 Commands between CentralControl (ST) and StockControl (SI)	11
3.1.1 Common errors	11
3.1.2 Remove pallet	11
3.1.3 Store pallet	12
3.1.4 Request amount of empty places in storage	12
3.1.5 Request amount of stored smarties of a color	12
3.2 Request the availability of a color	13
3.2.1 Shut down system	13
3.3 Commands between StockControl (SI) and Storage (Ia)	13
3.3.1 Common errors	13
3.3.2 Remove pallet	14
3.3.3 Store pallet	14
<b>4 Transport</b>	<b>15</b>
4.1 Commands between CentralControl (ST) and TransportControl (St)	15
4.1.1 Common errors	15
4.1.2 Request empty carriage	15
4.1.3 Release carriage	16
4.1.4 Reposition carriage	16
4.1.5 Shut down transport system	16
4.2 Commands between TransportControl (St) and transport belt (tr)	16
4.2.1 Set switch	17
4.2.2 Set loadstation	17

## *Inhaltsverzeichnis*

4.2.3	Set stopper . . . . .	17
4.2.4	Request RFID . . . . .	17
4.2.5	Set RFID . . . . .	17
4.2.6	Request sensors . . . . .	18
4.2.7	Shut down . . . . .	18
<b>5</b>	<b>IO-Station (EA)</b>	<b>19</b>
5.1	Commands between CentralControl (ST) and IOStation-Control (Se) . . . . .	19
5.1.1	Common errors . . . . .	19
5.1.2	Remove empty stock-pallet . . . . .	19
5.1.3	Remove product-pallet . . . . .	19
5.1.4	Fill stock-pallet . . . . .	20
5.1.5	Add stock-pallet . . . . .	20
5.1.6	Add empty product-pallet . . . . .	20
5.1.7	Shut down system . . . . .	20
5.1.8	Remove non-empty stock-pallet . . . . .	21

# 1 JSAP

## 1.1 Commands between Java-SAP interface (JS) and CentralControl (ST)

### 1.1.1 Common errors

- STJSF000<Message-ID>0000  
Command not understood.

### 1.1.2 Start a product-pallet fill order

- JSSTK000<Message-ID>0063{rgybw-}\*63  
Start a fill order with the requested pattern (string with 63 characters).
- STJSA001<Message-ID>0000  
Confirm the command (ACK001).
- STJSA002<Message-ID>0000  
Requested pattern can be produced.
- STJSA003<Message-ID>0018rxxgxxxyxxbxxwxttt  
The order was completed successfully. The amount of used smarties for every color (xx) and the needed time in seconds (001 - 999, if more time was needed 0) is returned.

Possible errors:

- STJSF001<Message-ID>0015rxxgxxxyxxbxxwxx  
Error while production. The amount of smarties already used is returned.
- STJSF002<Message-ID>0000  
Not enough smarties for the order.
- STJSF003<Message-ID>0000  
Error: Request while production.

## 1.2 Commands between GUI (GU) and JSAP (JS)

### 1.1.3 Request the stock

- JSSTK001<Message-ID>0000  
Request the actual stock.
- STJSA001<Message-ID>0000  
Confirm the command (ACK001).
- STJSA005<Message-ID>0020rxxgxxxxyxxbxxxwxxx  
Command executed successfully. The amount of smarties available of every color is returned.

Possible errors:

- STJSF003<Message-ID>0000  
Error: Request while production.

### 1.1.4 Cancel order

- JSSTK002<Message-ID>0000  
Cancel the actual order.
- STJSA001<Message-ID>0000  
Confirm the command (ACK001).
- STJSA004<Message-ID>0000  
The order was cancelled by JSAP.

Possible errors:

- STJSF004<Message-ID>0000  
No order that can be cancelled (= no active order).
- STJSF005<Message-ID>0000  
The active order is not the order to be cancelled.

## 1.2 Commands between GUI (GU) and JSAP (JS)

### 1.2.1 New order

- GUJSK000<Message-ID>0072{rgbybw-}\*63<User-ID>  
Add new production order to the system. The requested pattern is given as string with 63 characters. The user-id is given as integer with 9 digits.
- JSGUA001<Message-ID>0009xxxxxxxxx  
Order received successfully. The order-id (xxxxxxxxx) is returned.

## *1.2 Commands between GUI (GU) and JSAP (JS)*

### **1.2.2 Request status of an order**

- GUJSK001<Message-ID>0009xxxxxxxxxx  
Request the status of the order with order-id xxxxxxxxx.
- JSGUA001<Message-ID>0006ttttttt  
The estimated time the order will take to complete in seconds (ttttt) from now is returned.

## 2 Robot

### 2.1 Commands between CentralControl (ST) and RobotControl(Sr)

#### 2.1.1 Common errors

Common errors among all commands:

- SrSTF000<Message-ID>0000  
Command not understood.
- SrSTF001<Message-ID>0000  
Command not executed.
- SrSTF002<Message-ID>0000  
No stock-pallet at place A or B.
- SrSTF003<Message-ID>0000  
No product-pallet at place X.
- SrSTF004<Message-ID>0000  
Place A or B is occupied.
- SrSTF005<Message-ID>0000  
Place X is occupied.
- SrSTF999<Message-ID>0000  
Critical error.

#### 2.1.2 Take pallet from transport belt

- STSrK000<Message-ID>0091{rgybw-}\*91  
Take stock-pallet from transport belt to a free workspace (place A or B). The stock of that pallet is the string with 91 characters. OR:
- STSrK001<Message-ID>0000  
Take product-pallet from transport belt to workspace X.
- SrSTA001<Message-ID>0000  
Confirm the command (ACK001).
- SrSTA002<Message-ID>0000  
Command executed successfully (ACK002).

## 2.1 Commands between CentralControl (ST) and RobotControl(Sr)

### 2.1.3 Fill product-pallet

- STSrK002<Message-ID>0063{rgybw-}\*63  
The command to fill the product-pallet with smarties. The pattern is given as string with 63 characters (The product-pallet has only 63 places).
- SrSTA001<Message-ID>0000  
Confirm the command (ACK001).
- SrSTA002<Message-ID>0063{rgybw-X}\*63  
Command executed successfully (ACK002). The filled pattern is returned (X = place that could not be filled (missing smarties)).

Possible errors:

- SrSTF006<Message-ID>0063{rgybw-}\*63  
Requested position on product-pallet is occupied. The actual stock of the product-pallet is returned.

### 2.1.4 Move Pallet to transport belt

- STSrK003<Message-ID>0000  
Move stock-pallet to transport belt. OR:
- STSrK004<Message-ID>0000  
Move product-pallet to transport belt.
- SrSTA001<Message-ID>0000  
Confirm the command (ACK001).
- K003: SrSTA002<Message-ID>0091{rgybw-}\*91  
Command executed successfully (ACK002). The Stock of the moved pallet is returned.  
OR:
- K004: SrSTA002<Message-ID>0000  
Command executed successfully (ACK002).

### 2.1.5 Swap storage-pallets

- STSrK005<Message-ID>0091{rgybw-}\*91  
Take a stock-pallet from the transport belt to a free place (A or B) and move the pallet on the other place back to the transport belt.
- SrSTA001<Message-ID>0000  
Confirm the command (ACK001).
- SrSTA002<Message-ID>0091{rgybw-}\*91  
Command completed successfully (ACK002). The stock of the pallet that was moved to the transport belt is returned.



## 2.2 Commands between RobotControl (Sr) and Robot (ro)

### 2.1.6 Resort stock-pallet

- STSrK007<Message-ID>0000  
Resort the smarties on pallet A or B (if only one pallet is there) or resort smarties from the emptier pallet to the other.
- SrSTA001<Message-ID>0000  
Confirm the command (ACK001).
- SrSTA002<Message-ID>0000  
Command completed successfully (ACK002).

### 2.1.7 Shut down control

- STSrK006<Message-ID>0000  
Shut down robot and RobotControl.
- SrSTA001<Message-ID>0000  
Confirm the command (ACK001).
- SrSTA002<Message-ID>0000  
Command completed successfully (ACK002).

## 2.2 Commands between RobotControl (Sr) and Robot (ro)

### 2.2.1 Common errors

- roSrF000<Message-ID>0000  
Command not understood.
- roSrF001<Message-ID>0000  
Command not executed.

### 2.2.2 Move pallet from transport belt to place ABX

- SrroK000<Message-ID>0001{ABX}  
Move a pallet from the transport belt to the specified place (A, B or X).
- roSrA001<Message-ID>0000  
Confirm the command (ACK001).
- roSrA002<Message-ID>0000  
Command executed successfully (ACK002).

## 2.2 Commands between RobotControl (Sr) and Robot (ro)

### 2.2.3 Move pallet from place ABX to transport belt

- `SrroK001<Message-ID>0001{ABX}`  
Move a pallet from specified place (A, B or X) to the transport belt.
- `roSrA001<Message-ID>0000`  
Confirm the command (ACK001).
- `roSrA002<Message-ID>0000`  
Command executed successfully (ACK002).

### 2.2.4 Move smarite form pallet and index to pallet and index

- `SrroK002<Message-ID>0006{ABX}xx{ABX}yy`  
Move a smartie from pallet at place ABX at index xx to the pallet at place ABX and index yy.
- `roSrA001<Message-ID>0000`  
Confirm the command (ACK001).
- `roSrA002<Message-ID>0000`  
Command executed successfully (ACK002).

### 2.2.5 Shut down robot

- `SrroK003<Message-ID>0000`  
Move the robot to its start position and shut down.
- `roSrA001<Message-ID>0000`  
Confirm the command (ACK001).
- `roSrA002<Message-ID>0000`  
Command executed successfully (ACK002). This is defined but not used!

## 3 Stock

### 3.1 Commands between CentralControl (ST) and StockControl (SI)

#### 3.1.1 Common errors

Common errors among all commands:

- `SlSTF000<Message-ID>0000`  
Command not understood.
- `SrSTF999<Message-ID>0000`  
Critical error / Recovery cancelled.

#### 3.1.2 Remove pallet

- `STSlK005<Message-ID>0004{rgybw}xxx`  
Remove a pallet with xxx smarties (valid range: 001 - 999) of the requested color (r = red, g = green, y = yellow, b = blue, w = brown). OR:
- `STSlK007<Message-ID>0020rxxxgxxxxyxxxwxxxx`  
Remove a pallet with an amount for every available color (range: 000 - 999).
- `SlSTA001<Message-ID>0000`  
Confirm the command (ACK001).
- `SlSTA002<Message-ID>0094xxx{rgybw-}*91`  
Command executed successfully (ACK002). This includes the content of the removed pallet as string with 91 characters (r, g, y, b, w, -) and the id of this pallet (xxx).

Possible errors:

- `SlSTF003<Message-ID>0000`  
Invalid color requested.
- `SlSTF004<Message-ID>0000`  
Invalid amount requested.
- `SlSTF010<Message-ID>0000`  
Not enough smarties in the storage (counted over all pallets).
- `SlSTF011<Message-ID>0000`  
Mechanical error.

### 3.1 Commands between CentralControl (ST) and StockControl (SI)

#### 3.1.3 Store pallet

- STSlK004<Message-ID>0094xxx{rgybw-}\*91  
Store the pallet with id xxx and the content defined as string with 91 characters.
- SlSTA001<Message-ID>0000  
Confirm the command (ACK001).
- SlSTA002<Message-ID>0000  
Command executed successfully (ACK002).

Possible errors:

- SlSTF006<Message-ID>0000  
No free place in storage.
- SlSTF007<Message-ID>0000  
Pallet is empty.
- SlSTF009<Message-ID>0000  
Pallet-id already stored.
- SlSTF008<Message-ID>0000  
Mechanical error.

#### 3.1.4 Request amount of empty places in storage

- STSlK003<Message-ID>0000  
Request the amount of empty places in storage.
- STSlA001<Message-ID>0000  
Confirm the command (ACK001).
- SlSTA002<Message-ID>0003xxx  
Command executed successfully (ACK002). The amount will be sent as xxx.

#### 3.1.5 Request amount of stored smarties of a color

- STSlK001<Message-ID>0001{rgybw}  
Request the amount of stored smarties of color r,g,y,b or w.
- STSlA001<Message-ID>0000  
Confirm the command (ACK001).
- SlSTA002<Message-ID>0004xxxx  
Command executed successfully (ACK002). The amount will be sent as xxx.

Possible errors:

- SlSTF003<Message-ID>0000  
Requested undefined color.

## 3.2 Request the availability of a color

- STSlK002<Message-ID>0004{rgybw}xxx  
Request, if the amount xxx of color (rgbyw) is available in the storage.
- STSlA001<Message-ID>0000  
Confirm the command (ACK001).
- SlSTA002<Message-ID>0000  
Command executed successfully (ACK002). Requested amount is available.

Possible errors:

- SlSTF003<Message-ID>0000  
Requested undefined color.
- SlSTF004<Message-ID>0000  
Requested invalid amount.
- SlSTF002<Message-ID>0003xxx  
The requested amount is not available. The available amount will be sent as xxx.

### 3.2.1 Shut down system

- STSlK006<Message-ID>0000  
Shut down the system.
- SlSTA001<Message-ID>0000  
Confirm the command (ACK001).
- SlSTA002<Message-ID>0000  
Command executed successfully (ACK002). This is defined but not used in the system!

## 3.3 Commands between StockControl (Sl) and Storage (Ia)

### 3.3.1 Common errors

- IaSlF000<Message-ID>0000  
Command not understood.

### 3.3 Commands between StockControl (Sl) and Storage (Ia)

#### 3.3.2 Remove pallet

- S1laK002<Message-ID>0003xxx  
Remove pallet from place xxx.
- 1aSlA001<Message-ID>0000  
Confirm the command (ACK001).
- 1aSlA002<Message-ID>0000  
Command executed successfully (ACK002).

Possible errors:

- 1aSlF000<Message-ID>0000  
Invalid place-id.
- 1aSlF002<Message-ID>0000  
Mechanical error.

#### 3.3.3 Store pallet

- S1laK001<Message-ID>0003xxx  
Send command to storage: Store the pallet at place xxx.
- 1aSlA001<Message-ID>0000  
Confirm the command (ACK001).
- 1aSlA002<Message-ID>0000  
Command executed successfully (ACK002).

Possible errors:

- 1aSlF000<Message-ID>0000  
Invalid place-id.
- 1aSlF001<Message-ID>0000  
Mechanical error.

## 4 Transport

### 4.1 Commands between CentralControl (ST) and TransportControl (St)

#### 4.1.1 Common errors

- StSTF000<Message-ID>0000  
Command not understood.
- StSTF001<Message-ID>0000  
Command not executed.
- StSTF002<Message-ID>0002xx  
The carriage with id xx did not reach the destination.
- StSTF003<Message-ID>0003xxx  
Hardware error: The error is specified in the id xxx (000: SPS not working, 001: No pressure, 002: Fuse error, 003/4/5: Drive transport belt 1/2/3 not working, 006: Emergency-stop pressed).
- StSTF999<Message-ID>0000  
Critical error.

#### 4.1.2 Request empty carriage

- STStK001<Message-ID>0002xx  
Request a empty carriage to position xx (ro = Robot, la = Stock, ea = IO-Station).
- StSTA001<Message-ID>0000  
Confirm the command (ACK001).
- StSTA002<Message-ID>0002xx  
Command completed successfully (ACK002). The new id (xx) of the carriage is returned.

## 4.2 Commands between TransportControl (St) and transport belt (tr)

### 4.1.3 Release carriage

- STStK002<Message-ID>0002xx  
Release carriage with id xx (00 - 99).
- StSTA001<Message-ID>0000  
Confirm the command (ACK001).
- StSTA002<Message-ID>0000  
Command completed successfully (ACK002).

### 4.1.4 Reposition carriage

- STStK003<Message-ID>0004xxyy  
Reposition the carriage with id xx (0 - 99) to position yy (ro, la, ea).
- StSTA001<Message-ID>0000  
Confirm the command (ACK001).
- StSTA002<Message-ID>0000  
Command completed successfully (ACK002).

### 4.1.5 Shut down transport system

- STStK004<Message-ID>0000  
Shut down the system.
- StSTA001<Message-ID>0000  
Confirm the command (ACK001).
- StSTA002<Message-ID>0000  
Command completed successfully (ACK002).

## 4.2 Commands between TransportControl (St) and transport belt (tr)

This part uses its own network protocol. It is binary and does not send ASCII-strings. Message-structure:

- 1 Byte command-id
- 2 Bytes payload length
- 0 - x Bytes payload
- Bytes filled up with zeros until the packet size reaches 12 bytes (tr to St) or 8 bytes (St to tr).



## 4.2 Commands between TransportControl (St) and transport belt (tr)

### 4.2.1 Set switch

- 1 2 xy  
Set the switch with id x (1 Byte) to position y (1 Byte; 0 = to main transport belt, 1 = to side transport belt).
- 130 0  
Command executed successfully.

### 4.2.2 Set loadstation

- 2 2 xy  
Set the loadstation with id x (1 = Stock, 2 = Robot, 3 = IO) to status y (0 = not locked, 1 = locked).
- 130 0  
Command executed successfully.

### 4.2.3 Set stopper

- 4 2 xy  
Set the stopper with id x to position y (0 = down, 1 = up).
- 130 0  
Command executed successfully.

### 4.2.4 Request RFID

- 5 1 x  
Read the content with the RFID-reader with id x (1 = Stock, 2 = Robot, 3 = IO, 4 = Before top switch).
- 131 1 x  
Command executed successfully. The content of the RFID tag (or 0) is returned.

### 4.2.5 Set RFID

- 7 2 xy  
Write data y with RFID-reader x.
- 130 0  
Command executed successfully.

## 4.2 Commands between TransportControl (St) and transport belt (tr)

### 4.2.6 Request sensors

- 6 0

Request the state of all sensors.

- 128 5 xxxxx

Command executed successfully. The state of the sensors is returned.

The 5 Bytes representing the states of the following sensors (Top = IO, Bottom = Robot):

Byte	Bit							
	0	1	2	3	4	5	6	7
0 (top left)	B3.3	B9	B9.1	B14	B14.1	B7	B5.1	
1 (bottom left)	B2.3	B10	B10.1	B6	B6.1	B8	B8.1	
2 (Top)	B19	B16.1	B16	B18.1	B18	B11.2	B4.1	B4
3 (Middle left)	B3.5	B3	B2.1	B2.2				
4 (Bottom)	B2.4	B2	B1.4	B1.1	B1	B15.1	B15	B17

### 4.2.7 Shut down

- 127 0

Shut down.

- 130 0

Command executed successfully.

## 5 IO-Station (EA)

### 5.1 Commands between CentralControl (ST) and IOStation-Control (Se)

#### 5.1.1 Common errors

- SeSTF000<Message-ID>0000  
Command not understood.
- SeSTF001<Message-ID>0000  
Command not executed.
- SeSTF999<Message-ID>0000  
Critical error

#### 5.1.2 Remove empty stock-pallet

- STSeK000<Message-ID>0003xxx  
Remove the pallet with id xxx from the transport belt.
- SeSTA001<Message-ID>0000  
Confirm the command (ACK001).
- SeSTA002<Message-ID>0000  
Command executed successfully (ACK002).

#### 5.1.3 Remove product-pallet

- STSeK001<Message-ID>0063{rgybw-}\*63  
Remove the product-pallet with the specified stock from the transport belt.
- SeSTA001<Message-ID>0000  
Confirm the command (ACK001).
- SeSTA002<Message-ID>0000  
Command executed successfully (ACK002).

## 5.1 Commands between CentralControl (ST) and IOStation-Control (Se)

### 5.1.4 Fill stock-pallet

- STSeK002<Message-ID>0091{rgybw-}\*91  
Fill a empty stock-pallet with the specified pattern.
- SeSTA001<Message-ID>0000  
Confirm the command (ACK001).
- SeSTA002<Message-ID>0094xxx{rgybw-}\*91  
Command executed successfully (ACK002). The id and the stock of the pallet is returned.

### 5.1.5 Add stock-pallet

- STSeK003<Message-ID>0003xxx  
Add the previously filled stock-pallet with id xxx on the transport belt.
- SeSTA001<Message-ID>0000  
Confirm the command (ACK001).
- SeSTA002<Message-ID>0094xxx{rgybw-}\*91  
Command executed successfully (ACK002). The id and the stock of the pallet is returned.

### 5.1.6 Add empty product-pallet

- STSeK004<Message-ID>0000  
Add an empty product-pallet on the transport belt.
- SeSTA001<Message-ID>0000  
Confirm the command (ACK001).
- SeSTA002<Message-ID>0000  
Command executed successfully (ACK002).

### 5.1.7 Shut down system

- STSeK005<Message-ID>0000  
Shut down the system.
- SeSTA001<Message-ID>0000  
Confirm the command (ACK001).
- SeSTA002<Message-ID>0000  
Command executed successfully (ACK002).

## 5.1 Commands between CentralControl (ST) and IOStation-Control (Se)

### 5.1.8 Remove non-empty stock-pallet

- STSeK006<Message-ID>0094xxx{rgybw-}\*91  
Remove the storage-pallet with id xxx and the specified stock from the transport belt.
- SeSTA001<Message-ID>0000  
Confirm the command (ACK001).
- SeSTA002<Message-ID>0000  
Command executed successfully (ACK002).