

---

## Table of Contents

This script visualize the linear and non-linear preddictions of tau .....	1
1 - Define paths .....	1
2 - Define data .....	1
3 - Calculate predicted values .....	2
4 - Calculate residuals and performance metrics .....	2
5 Plot comparison between predicted and observed KH instability growth times .....	2
6 - Define ranges to visualize Equaiton 2 .....	4
7 - Define contour levels .....	5
8 - Visualize model over the considered ranges for t1 .....	5
9 - Visualize model over the considered ranges for t2 as a function of l and v with n fixed .....	7
10 - Visualize model over the considered ranges for t2 as a function of l and n with v fixed .....	8
11 - Visualize model over the considered ranges for t2 as a function of v and n with l fixed .....	10

## This script visualize the linear and non-linear preddictions of tau

### 1 - Define paths

```
workpath = '/Users/akv020/Projects/conditions_KHI/source/Figure4';
```

### 2 - Define data

Define the parameter values

```
v = [0.8, 1.3, 1.8]*1e3;
l = [2, 6, 10]*1e3;
n = [1e11, 5e11, 10e11];

% Generate all combinations of parameters
[V, N, L] = ndgrid(v, n, l);
params = [V(:), L(:), N(:)];

% Define the output data
y = [5.0, 3.2, 2.2, 8.0, 4.0, 2.3, 12.3, ...
     4.7, 2.3, 20.8, 10.3, 6.2, NaN, 10.8, ...
     5.3, NaN, 10.2, 5.2, NaN, 12.2, 9.3, ...
     NaN, 13.7, 7.7, NaN, 12.2, 7.0]'*60;

% Remove NaN values
valid_indices = ~isnan(y);
params = params(valid_indices, :);
y = y(valid_indices);

% Extract parameter values
v = params(:, 1);
l = params(:, 2);
n = params(:, 3);
```

---

## 3 - Calculate predicted values

Calculate estimated outputs using the first equation

```
y1_est = 115.4 * (1 ./ v);
```

```
% Calculate estimated outputs using the second equation
```

```
y2_est = 0.0002130 * (n ./ v.^2) + 1.213e+05 * (1 ./ v.^2) + 596.6 * ((1 .*  
v.^2) ./ n);
```

## 4 - Calculate residuals and performance metrics

Residuals

```
residuals_y1 = y - y1_est;
```

```
residuals_y2 = y - y2_est;
```

```
% RMSE (Root Mean Squared Error)
```

```
rmse_y1 = sqrt(mean(residuals_y1.^2));
```

```
rmse_y2 = sqrt(mean(residuals_y2.^2));
```

```
% MAD (Median Absolute Deviation)
```

```
mad_y1 = median(abs(residuals_y1));
```

```
mad_y2 = median(abs(residuals_y2));
```

```
% R^2 (Coefficient of Determination)
```

```
ss_tot = sum((y - mean(y)).^2);
```

```
ss_res_y1 = sum(residuals_y1.^2);
```

```
ss_res_y2 = sum(residuals_y2.^2);
```

```
r2_y1 = 1 - (ss_res_y1 / ss_tot);
```

```
r2_y2 = 1 - (ss_res_y2 / ss_tot);
```

## 5 Plot comparison between predicted and observed KH instability growth times

```
% Define figure properties
```

```
FIG = figure('units','centimeters','position',[0,0,36.0,39.0]);
```

```
sx = 0.075;
```

```
sy = 0.075;
```

```
fz = 18;
```

```
lw = 3;
```

```
al = 0.8;
```

```
mz = 100;
```

```
colormap(inferno)
```

```
% Plot and compare the t1 growth times
```

```
subplot_tight(3,2,1,[sx, sy])
```

```
plot([0 1300],[0 1300],'k','LineWidth',lw)
```

```
hold on
```


---

```

scatter(y,y1_est,mz,'filled','color',[0.6350, 0.0780, 0.1840])
xlabel('Observed  $\tau$ ','Interpreter','latex','FontSize',fz)
ylabel('Predicted  $\tau$ ','Interpreter','latex','FontSize',fz)
xlim([0 1300])
ylim([0 1300])
title('a)  $\tau_1 = 115 (\ell / \Delta v)$ ','Interpreter','latex','FontWeight','normal')
legend([' $R^2 = 0.641$ ', newline, 'RMSE = 162 s'],'Simualtions','Location','northwest','FontSize',fz,'interpreter','latex')
grid on
axisproperties= get(gca, 'XAxis');
axisproperties.TickLabelInterpreter = 'latex'; % latex for x-axis
axisproperties= get(gca, 'YAxis');
axisproperties(1).TickLabelInterpreter = 'latex'; % tex for y-axis
set(gca,'fontsize',fz)

% Plot and compare the t2 growth times
subplot_tight(3,2,2,[sx, sy])
plot([0 1300],[0 1300],'k','LineWidth',lw)
hold on
scatter(y,y2_est,mz,'filled','color',[0.6350, 0.0780, 0.1840])
xlabel('Observed  $\tau$ ','FontSize',fz,'Interpreter','latex')
ylabel('Predicted  $\tau$ ','FontSize',fz,'Interpreter','latex')
xlim([0 1300])
ylim([0 1300])
title('b)  $\tau_2 = 1/(\Delta v^2)(c_1 n_p + c_2 \ell) + c_3 (\ell \Delta v^2)/n_p$ ','interpreter','latex','FontWeight','normal')
legend([' $R^2 = 0.944$ ', newline, 'RMSE = 63.8 s'],'Simualtions','Location','northwest','FontSize',fz,'interpreter','latex')
grid on
axisproperties= get(gca, 'XAxis');
axisproperties.TickLabelInterpreter = 'latex'; % latex for x-axis
axisproperties= get(gca, 'YAxis');
axisproperties(1).TickLabelInterpreter = 'latex'; % tex for y-axis
set(gca,'fontsize',fz)

```



## 6 - Define ranges to visualize Equaiton 2

Define the ranges for  $\ell$ ,  $v$ , and  $n$

```
l_range = linspace(1e3, 12e3, 300); % Range for l in meters
v_range = linspace(0.5e3, 2e3, 300); % Range for v in meters/second
n_range = linspace(0.8e11, 1.2e12, 300); % Range for n in particles per cubic
meter

% Fixed values for the subplots
```

---

```

l_fixed = 5e3; % l fixed at 5000 meters
v_fixed = 1.3e3; % v fixed at 1500 meters/second
n_fixed = 5e11; % n fixed at 5 * 1e11 particles per cubic meter

```

## 7 - Define contour levels

```

contour_levels = (1.7:0.2:3.1);

```

## 8 - Visualize model over the considered ranges for t1

```

% Define meshgrid
[L, V] = meshgrid(l_range, v_range);

% Predict y1_est as a function of l and v for n = 1e11 (most points) for y1
predictions
y1_idx = [(1:3),(10:12),(17:18)];
y1_est_lv = 115.4 * (L ./ V);
y1_lv = y(y1_idx);
l_lv = l(y1_idx);
v_lv = v(y1_idx);

% Plot first for t1 predictions
subplot_tight(3,2,3,[sx, sy])
hold on
contourf(l_range/1e3,v_range/1e3,log10(y1_est_lv),contour_levels,'k','LineWidth',lw)
clim([1.5 3.2])

% Get current colormap and color limits
cmap = colormap('inferno');
cmin = 1.5; % from clim
cmax = 3.2; % from clim
% Normalize the scatter data to fit within the color limits
scatter_data = log10(y1_lv);
norm_data = (scatter_data - cmin) / (cmax - cmin);
% Ensure the normalized data is within [0, 1]
norm_data(norm_data < 0) = 0;
norm_data(norm_data > 1) = 1;
% Map the normalized data to the colormap
color_idx = round(norm_data * (size(cmap, 1) - 1)) + 1;
scatter_colors = cmap(color_idx, :);
% Create the scatter plot of observed values
scatter(l_lv/1e3, v_lv/1e3, mz,
    scatter_colors, 'filled','MarkerEdgeColor','k','LineWidth',lw);

% Define axis and title properties
xlabel('$\ell$ [km'],'interpreter','latex','FontSize',fz,'interpreter','latex')
ylabel('$\Delta v$ [km/s'],'interpreter','latex','FontSize',fz,'interpreter','latex')
title('c) $\tau_1$ predictions of KH instability growth
    times','interpreter','latex','fontSize',fz,'FontWeight','normal')


```

---

```

axisproperties= get(gca, 'XAxis');
axisproperties.TickLabelInterpreter = 'latex'; % latex for x-axis
axisproperties= get(gca, 'YAxis');
axisproperties(1).TickLabelInterpreter = 'latex'; % tex for y-axis
set(gca, 'fontsize', fz)

```



---

## 9 - Visualize model over the considered ranges for $t_2$ as a function of $l$ and $v$ with $n$ fixed


```
% Get observed values
n_idx = [(4:6),13,14,19,20]; % Define indexes with n = 5e11 for y2 predictions
y2_lv = y(n_idx); %

% Get predicted values t2
[L, V] = meshgrid(l_range, v_range);
y2_est_lv = 0.0002130 * (n_fixed ./ V.^2) + 1.213e+05 * (L ./ V.^2) + 596.6 *
    ((L .* V.^2) ./ n_fixed);

% Plot the t2 predictions
subplot_tight(3,2,4,[sx, sy])
pcolor(l_range/1e3,v_range/1e3,log10(y2_est_lv))
hold on
contourf(l_range/1e3,v_range/1e3,log10(y2_est_lv),contour_levels,'k','LineWidth',lw)
clim([1.5 3.2])

% Normalize the scatter data to fit within the color limits
scatter_data = log10(y2_lv);
norm_data = (scatter_data - cmin) / (cmax - cmin);
% Ensure the normalized data is within [0, 1]
norm_data(norm_data < 0) = 0;
norm_data(norm_data > 1) = 1;
% Map the normalized data to the colormap
color_idx = round(norm_data * (size(cmap, 1) - 1)) + 1;
scatter_colors = cmap(color_idx, :);
% Create the scatter plot
scatter(l(n_idx)/1e3, v(n_idx)/1e3, mz,
    scatter_colors, 'filled','MarkerEdgeColor','k','LineWidth',lw);

% Define axis and title properties
xlabel('$\ell$ [km'],'interpreter','latex','FontSize',fz)
ylabel('$\Delta v$ [km/s'],'interpreter','latex','FontSize',fz)
c = colorbar;
c.Label.String = 'Logarithmic growth time [s]';
c.FontSize = fz;
c.Label.Interpreter = 'latex';
set(c,'TickLabelInterpreter','latex')
set(c,'Position',[0.9319,0.3807,0.0157,0.233]);
title('d) $\tau_2$ predictions with fixed $n_p$', 'interpreter','latex','fontsize',fz,'FontWeight','normal')
axisproperties= get(gca, 'XAxis');
axisproperties.TickLabelInterpreter = 'latex'; % latex for x-axis
axisproperties= get(gca, 'YAxis');
axisproperties(1).TickLabelInterpreter = 'latex'; % tex for y-axis
set(gca,'fontsize',fz)
```



## 10 - Visualize model over the considered ranges for t2 as a function of l and n with v fixed

```
% Get observed values
v_idx = [2,5,8,11,13,15,17,19,21];
y2_ln = y(v_idx);
```



---

```

l_ln = l(v_idx);
n_ln = n(v_idx);

% Get predicted values t2
[L, N] = meshgrid(l_range, n_range);
y2_est_ln = 0.0002130 * (N ./ v_fixed.^2) + 1.213e+05 * (L ./ v_fixed.^2) +
    596.6 * ((L .* v_fixed.^2) ./ N);


% Plot the t2 predictions
subplot_tight(3,2,5,[sx, sy])
pcolor(l_range/1e3,n_range/1e11,log10(y2_est_ln))
hold on
contourf(l_range/1e3,n_range/1e11,log10(y2_est_ln),contour_levels,'k','LineWidth',lw)
clim([1.5 3.2])

% Normalize the scatter data to fit within the color limits
scatter_data = log10(y2_ln);
norm_data = (scatter_data - cmin) / (cmax - cmin);
% Ensure the normalized data is within [0, 1]
norm_data(norm_data < 0) = 0;
norm_data(norm_data > 1) = 1;
% Map the normalized data to the colormap
color_idx = round(norm_data * (size(cmap, 1) - 1)) + 1;
scatter_colors = cmap(color_idx, :);
% Create the scatter plot
scatter(l_ln/1e3, n_ln/1e11, mz,
    scatter_colors, 'filled','MarkerEdgeColor','k','LineWidth',lw);

% Define axis and title properties
xlabel('$\ell$ [km'],'interpreter','latex','FontSize',fz)
ylabel('$n_p$ $[10^{11}$ \,
\mathrm{m}^{-3}]$', 'interpreter','latex','FontSize',fz)
title('e) $\tau_2$ predictions with fixed $\Delta v$
$', 'interpreter','latex','fontSize',fz,'FontWeight','normal')
axisproperties= get(gca, 'XAxis');
axisproperties.TickLabelInterpreter = 'latex'; % latex for x-axis
axisproperties= get(gca, 'YAxis');
axisproperties(1).TickLabelInterpreter = 'latex'; % tex for y-axis
set(gca,'fontSize',fz)

```

---



## 11 - Visualize model over the considered ranges for t2 as a function of v and n with l fixed

```
% Get observed values
l_idx = (10:16);
y2_vn = y(l_idx);
```

---

```

v_vn = v(l_idx);
n_vn = n(l_idx);

% Get predicted values t2
[V, N] = meshgrid(v_range, n_range);
y2_est_vn = 0.0002130 * (N ./ V.^2) + 1.213e+05 * (l_fixed ./ V.^2) + 596.6 *
    ((l_fixed .* V.^2) ./ N);


% Plot the t2 predictions
subplot_tight(3,2,6,[sx, sy])
pcolor(v_range/1e3,n_range/1e11,log10(y2_est_vn))
hold on
contourf(v_range/1e3,n_range/1e11,log10(y2_est_vn),contour_levels,'k','LineWidth',lw)
clim([1.5 3.2])

% Normalize the scatter data to fit within the color limits
scatter_data = log10(y2_vn);
norm_data = (scatter_data - cmin) / (cmax - cmin);
% Ensure the normalized data is within [0, 1]
norm_data(norm_data < 0) = 0;
norm_data(norm_data > 1) = 1;
% Map the normalized data to the colormap
color_idx = round(norm_data * (size(cmap, 1) - 1)) + 1;
scatter_colors = cmap(color_idx, :);
% Create the scatter plot
scatter(v_vn/1e3, n_vn/1e11, mz,
    scatter_colors, 'filled','MarkerEdgeColor','k','LineWidth',lw);

% Define axis and title properties
xlabel('$\Delta v$ [km/s'],'interpreter','latex','FontSize',fz)
ylabel('$n_p$ $[10^{11}$ \,
\mathrm{m}^{-3}]$', 'interpreter','latex','FontSize',fz)
c = colorbar;
c.Label.String = 'Logarithmic growth time [s]';
c.FontSize = fz;
c.Label.Interpreter = 'latex';
set(c,'Position',[0.9319,0.07325,0.0157,0.233]);
set(c,'TickLabelInterpreter','latex')
title('f) $\tau_2$ predictions with fixed $\ell$
$', 'interpreter','latex','fontsize',fz,'FontWeight','normal')
axisproperties= get(gca, 'XAxis');
axisproperties.TickLabelInterpreter = 'latex'; % latex for x-axis
axisproperties= get(gca, 'YAxis');
axisproperties(1).TickLabelInterpreter = 'latex'; % tex for y-axis
set(gca,'fontsize',fz)

```

---



Published with MATLAB® R2022b