




Lesson 8: Regularization, Optimization and Searching

CARSTEN EIE FRIGAARD

AUTUMN 2020



L08: Agenda

- ▶ **ML Algorithm and Model Selection:**
 k -fold Cross-Validation revisited,
 k -fold CV for Hyperparameter Tuning revisited.
- ▶ **Regularization and Optimization:**
 Regularizers,
 Exercise: `L09/regulizers.ipynb`
 Optimizers (no-exe).
- ▶ **Searching:**
 Gridsearch,
 Randomsearch,
 Exercise: `L09/gridsearch.ipynb`

ML Algorithm Selection and Model Selection

Manually Choosing an Algorithm and Tuning a Model..

- ▶ algorithm selection.

ML Algorithm Selection and Model Selection

Manually Choosing an Algorithm and Tuning a Model..

- ▶ algorithm selection.
- ▶ model selection,
- ▶ model evaluation,

ML Algorithm Selection and Model Selection

Manually Choosing an Algorithm and Tuning a Model..

- ▶ algorithm selection.
- ▶ model selection,
- ▶ model evaluation,
- ▶ re-iteration and re-selection!

ML Algorithm Selection and Model Selection

Manually Choosing an Algorithm and Tuning a Model..

- ▶ algorithm selection.
- ▶ model selection,
- ▶ model evaluation,
- ▶ re-iteration and re-selection!


Model Evaluation, Model Selection, and Algorithm Selection in Machine Learning

Sebastian Raschka
University of Wisconsin-Madison
Department of Statistics
November 2018
sr@stat.wisc.edu

Abstract

The correct use of model evaluation, model selection, and algorithm selection techniques is vital in academic machine learning research as well as in many industrial settings. This article reviews different techniques that can be used for each of these three subtasks and discusses the main advantages and disadvantages of each technique with references to theoretical and empirical studies. Further recommendations are given to encourage best yet feasible practices in research and applications of machine learning. Common methods such as the holdout method for model evaluation and selection are covered, which are not recommended when working with small datasets. Different flavors of the bootstrap technique are introduced for estimating the uncertainty of performance estimates, as an alternative to confidence intervals via normal approximation if bootstrapping is computationally feasible. Common cross-validation techniques such as leave-one-out cross-validation and k-fold cross-validation are reviewed, the bias-variance trade-off for choosing k is discussed, and practical tips for the optimal choice of k are given based on empirical evidence. Different statistical tests for algorithm comparisons are presented, and strategies for dealing with multiple comparisons such as omnibus tests and multiple comparison corrections are discussed. Finally, alternative methods for algorithm selection, such as the combined k -fold N -fold cross-validation and nested cross-validation, are recommended for comparing machine learning algorithms when datasets are small.


*"Model Evaluation, Model Selection, and Algorithm Selection in Machine Learning",
Sebastian Raschka, 2018.*



ML Algorithm Selection and Model Selection

Manually Choosing an Algorithm and Tuning a Model..

- ▶ algorithm selection.
- ▶ model selection,
- ▶ model evaluation,
- ▶ **re-iteration and re-selection!**




Model Evaluation, Model Selection, and Algorithm Selection in Machine Learning

Sebastian Raschka
University of Wisconsin-Madison
Department of Statistics
November 2018
sraschka@stat.wisc.edu

Abstract

The correct use of model evaluation, model selection, and algorithm selection techniques is vital in academic machine learning research as well as in many industrial settings. This article reviews different techniques that can be used for each of these three subtasks and discusses the main advantages and disadvantages of each technique with references to theoretical and empirical studies. Further recommendations are given to encourage best yet feasible practices in research and applications of machine learning. Common methods such as the bootstrap method for model evaluation and selection are covered, which are not recommended when working with small datasets. Different flavors of the bootstrap technique are introduced for estimating the uncertainty of performance estimates, as an alternative to confidence intervals via normal approximation if bootstrapping is computationally feasible. Common cross-validation techniques such as leave-one-out cross-validation and k-fold cross-validation are reviewed, the bias-variance trade-off for choosing k is discussed, and practical tips for the optimal choice of k are given based on empirical evidence. Different statistical tests for algorithm comparisons are presented, and strategies for dealing with multiple comparisons such as omnibus tests and multiple comparison corrections are discussed. Finally, alternative methods for algorithm selection, such as the combined k -test S_{k2} cross-validation and nested cross-validation, are recommended for comparing machine learning algorithms when datasets are small.

"Model Evaluation, Model Selection, and Algorithm Selection in Machine Learning".
Sebastian Raschka. 2018.



ML Algorithm Selection and Model Selection

Manually Choosing an Algorithm and Tuning a Model..

- ▶ algorithm selection:
 - ▶ choose an algo that '*fits*' the problem,
...perhaps via searching??

ML Algorithm Selection and Model Selection

Manually Choosing an Algorithm and Tuning a Model..

- ▶ algorithm selection:
 - ▶ choose an algo that '*fits*' the problem,
...perhaps via searching??
- ▶ model selection:
 - ▶ looking for 'optimal' model capacity,
 - ▶ tuning model **hyperparameters**..
 - ▶ ...
 - ▶ ...

ML Algorithm Selection and Model Selection

Manually Choosing an Algorithm and Tuning a Model..

- ▶ algorithm selection:
 - ▶ choose an algo that '*fits*' the problem,
...perhaps via searching??
- ▶ model selection:
 - ▶ looking for 'optimal' model capacity,
 - ▶ tuning model **hyperparameters**..
 - ▶ model weights **regularizers**..(for NN's)
 - ▶ ...

ML Algorithm Selection and Model Selection

Manually Choosing an Algorithm and Tuning a Model..

- ▶ algorithm selection:
 - ▶ choose an algo that '*fits*' the problem, ...perhaps via searching??
- ▶ model selection:
 - ▶ looking for 'optimal' model capacity,
 - ▶ tuning model **hyperparameters**..
 - ▶ model weights **regularizers**..(for NN's)
 - ▶ gradient descent **optimizers**..(for NN's)



ML Algorithm Selection and Model Selection

Manually Choosing an Algorithm and Tuning a Model..

- ▶ algorithm selection:
 - ▶ choose an algo that '*fits*' the problem, ...perhaps via searching??
- ▶ model selection:
 - ▶ looking for 'optimal' model capacity,
 - ▶ tuning model **hyperparameters**..
 - ▶ model weights **regularizers**..(for NN's)
 - ▶ gradient descent **optimizers**..(for NN's)
- ▶ model evaluation:
 - ▶ the performance metric score function,
 - ▶ how do you evaluate **generalization** performance?
 - ▶ holdout method (train-test split) and k -fold CV,
 - ▶ three-way split (train-validate-test split)..



ML Algorithm Selection and Model Selection

Manually Choosing an Algorithm and Tuning a Model..


- ▶ algorithm selection:
 - ▶ choose an algo that '*fits*' the problem, ...perhaps via searching??
- ▶ model selection:
 - ▶ looking for 'optimal' model capacity,
 - ▶ tuning model **hyperparameters**..
 - ▶ model weights **regularizers**..(for NN's)
 - ▶ gradient descent **optimizers**..(for NN's)
- ▶ model evaluation:
 - ▶ the performance metric score function,
 - ▶ how do you evaluate **generalization** performance?
 - ▶ holdout method (train-test split) and k -fold CV,
 - ▶ three-way split (train-validate-test split)..
- ▶ **re-iteration and re-selection!**



NOTE: Model selection: ~ selection the best capacity/hyperparameter for a given model—NOT choosing the ML algo/model itself!

Model Evaluation

k-fold Cross-Validation Procedure, for *k*=5..





Model Evaluation

k -fold Cross-Validation Procedure, for $k=5$..

Model Evaluation


k-fold Cross-Validation Procedure, for *k*=5..






Model Evaluation and Selection

k-fold Cross-Validation for Hyperparameter Tuning (Somewhat Similar to Treeway Holdout..)



Model Evaluation and Selection

k-fold Cross-Validation for Hyperparameter Tuning (Somewhat Similar to Treeway Holdout)



Regularization

Adding a Penalty to the Cost Function

For a linear regressor, our cost function was

$$J(\mathbf{X}, \mathbf{y}; \mathbf{w}) = ||\mathbf{X}\mathbf{w} - \mathbf{y}||_2^2 \propto \text{MSE}(\mathbf{X}, \mathbf{y}; \mathbf{w})$$

Regularization

Adding a Penalty to the Cost Function

For a linear regressor, our cost function was

$$J(\mathbf{X}, \mathbf{y}; \mathbf{w}) = ||\mathbf{X}\mathbf{w} - \mathbf{y}||_2^2 \propto \text{MSE}(\mathbf{X}, \mathbf{y}; \mathbf{w})$$

But now enters a **penalty factor**, Ω , that scaled with α adds extra cost to J ,

$$\tilde{J}(\mathbf{X}, \mathbf{y}; \mathbf{w}) = ||\mathbf{X}\mathbf{w} - \mathbf{y}||_2^2 + \alpha\Omega(\mathbf{w})$$

Regularization

Adding a Penalty to the Cost Function

For a linear regressor, our cost function was

$$J(\mathbf{X}, \mathbf{y}; \mathbf{w}) = \|\mathbf{X}\mathbf{w} - \mathbf{y}\|_2^2 \propto \text{MSE}(\mathbf{X}, \mathbf{y}; \mathbf{w})$$

But now enters a **penalty factor**, Ω , that scaled with α adds extra cost to J ,

$$\tilde{J}(\mathbf{X}, \mathbf{y}; \mathbf{w}) = \|\mathbf{X}\mathbf{w} - \mathbf{y}\|_2^2 + \alpha\Omega(\mathbf{w})$$

so this becomes **a-tug-of-war** between the two terms in \tilde{J} .

Regularization

Adding a Penalty to the Cost Function

For a linear regressor, our cost function was

$$J(\mathbf{X}, \mathbf{y}; \mathbf{w}) = ||\mathbf{X}\mathbf{w} - \mathbf{y}||_2^2 \propto \text{MSE}(\mathbf{X}, \mathbf{y}; \mathbf{w})$$

But now enters a **penalty factor**, Ω , that scaled with α adds extra cost to J ,

$$\tilde{J}(\mathbf{X}, \mathbf{y}; \mathbf{w}) = ||\mathbf{X}\mathbf{w} - \mathbf{y}||_2^2 + \alpha\Omega(\mathbf{w})$$

so this becomes **a-tug-of-war** between the two terms in \tilde{J} .

The effect of the added penalty is to:

- ▶ put a **constraint** on the norm of the weights, \mathbf{w} , disallowing 'em to grow wildly,
- ▶ leading to **reduced overfitting**, disabling the model to learn the background noise in the data.

\mathcal{L}_2 Regularization

Ridge Penalization

Aka Weight Decay, aka Tikhonov regularization

$$\Omega(\mathbf{w}) = \|\mathbf{w}\|_2^2 = \mathbf{w}^\top \mathbf{w}$$

$$\tilde{J}_{\text{ridge}}(\mathbf{X}, \mathbf{y}; \mathbf{w}) = J(\mathbf{X}, \mathbf{y}; \mathbf{w}) + \alpha \mathbf{w}^\top \mathbf{w}$$

\mathcal{L}_2 Regularization

Ridge Penalization

Aka Weight Decay, aka Tikhonov regularization

$$\Omega(\mathbf{w}) = \|\mathbf{w}\|_2^2 = \mathbf{w}^\top \mathbf{w}$$

$$\tilde{J}_{\text{ridge}}(\mathbf{X}, \mathbf{y}; \mathbf{w}) = J(\mathbf{X}, \mathbf{y}; \mathbf{w}) + \alpha \mathbf{w}^\top \mathbf{w}$$

with $\mathbf{w} = [w_1 \ w_2 \ \cdots \ w_n]^\top$ without the bias element w_0 in the regularizer term, Ω , and recalling the Euclidean norm


$$\mathcal{L}_2^2 : \|\mathbf{x}\|_2^2 = \mathbf{x}^\top \mathbf{x}$$

NOTE: ..and give-or-take some additional $1/2$ or $1/n$ constant, that we do not care about.

\mathcal{L}_2 Regularization

Ridge Penalization


A graphical view for a linear regressor




\mathcal{L}_2 Regularization

Ridge Penalization

A graphical view for a linear regressor




3D: ideal convex loss in $J - \mathbf{w}$ space.




\mathcal{L}_2 Regularization

Ridge Penalization


A graphical view for a linear regressor



3D: ideal convex loss in $J - \mathbf{w}$ space.



1D featurespace




2D: flat $w_2 - w_1$ view with some feature scaling.


\mathcal{L}_2 Regularization

Ridge Penalization


A graphical view for a linear regressor



3D: ideal convex loss in $J - \mathbf{w}$ space.



1D featurespace



2D: flat $w_2 - w_1$ view with some feature scaling.

The tug-of-war: what happens with \tilde{w} ,
if w^* is far from the origin $[w_1, w_2] = (0, 0)$?

\mathcal{L}_1 Regularization

Lasso penalization

Now, just replace the \mathcal{L}_2 with \mathcal{L}_1 and we have the Lasso regularizer

$$\Omega(\mathbf{w}) = \|\mathbf{w}\|_1$$

$$\tilde{J}_{\text{lasso}}(\mathbf{X}, \mathbf{y}; \mathbf{w}) = J(\mathbf{X}, \mathbf{y}; \mathbf{w}) + \alpha \|\mathbf{w}\|_1$$

\mathcal{L}_1 Regularization

Lasso penalization

Now, just replace the \mathcal{L}_2 with \mathcal{L}_1 and we have the Lasso regularizer

$$\Omega(\mathbf{w}) = \|\mathbf{w}\|_1$$


$$\tilde{J}_{\text{lasso}}(\mathbf{X}, \mathbf{y}; \mathbf{w}) = J(\mathbf{X}, \mathbf{y}; \mathbf{w}) + \alpha \|\mathbf{w}\|_1$$

with the Manhattan norm

$$\mathcal{L}_1 : \|\mathbf{x}\|_1 = \sum_{i=1}^n \text{abs}(x_i)$$

and the \mathcal{L}_1 penalty tends to drive weights to zero:

- ▶ automatic feature selection,
- ▶ outputs a sparse model,
- ▶ i.e few nonzero w 's.



\mathcal{L}_1 and \mathcal{L}_2 Regularization

Elastic-net Penalization

And finally a combination of the two: an Elastic-net regularizer

$$\Omega(\mathbf{w}) = \beta \|\mathbf{w}\|_1 + (1 - \beta) \|\mathbf{w}\|_2^2$$

$$\tilde{J}_{\text{elastic}}(\mathbf{X}, \mathbf{y}; \mathbf{w}) = J(\mathbf{X}, \mathbf{y}; \mathbf{w}) + \alpha (\beta \|\mathbf{w}\|_1 + (1 - \beta) \|\mathbf{w}\|_2^2)$$


\mathcal{L}_1 and \mathcal{L}_2 Regularization

Elastic-net Penalization

And finally a combination of the two: an Elastic-net regularizer

$$\Omega(\mathbf{w}) = \beta \|\mathbf{w}\|_1 + (1 - \beta) \|\mathbf{w}\|_2^2$$

$$\tilde{J}_{\text{elastic}}(\mathbf{X}, \mathbf{y}; \mathbf{w}) = J(\mathbf{X}, \mathbf{y}; \mathbf{w}) + \alpha (\beta \|\mathbf{w}\|_1 + (1 - \beta) \|\mathbf{w}\|_2^2)$$



\mathcal{L}_1 and \mathcal{L}_2 Regularization


Elastic-net Penalization

And finally a combination of the two: an Elastic-net regularizer

$$\Omega(\mathbf{w}) = \beta \|\mathbf{w}\|_1 + (1 - \beta) \|\mathbf{w}\|_2^2$$

$$\tilde{J}_{\text{elastic}}(\mathbf{X}, \mathbf{y}; \mathbf{w}) = J(\mathbf{X}, \mathbf{y}; \mathbf{w}) + \alpha (\beta \|\mathbf{w}\|_1 + (1 - \beta) \|\mathbf{w}\|_2^2)$$

Regularization selection: via searching..



Optimizers

Momentum Optimization

Normal GD algo

$$\mathbf{w} \leftarrow \mathbf{w} - \eta \nabla_{\mathbf{w}} J$$

but now with added (physical) momentum

$$\mathbf{m} \leftarrow \beta \mathbf{m} - \eta \nabla_{\mathbf{w}} J$$

$$\mathbf{w} \leftarrow \mathbf{w} + \mathbf{m}$$

Optimizers

Momentum Optimization


Normal GD algo

$$\mathbf{w} \leftarrow \mathbf{w} - \eta \nabla_{\mathbf{w}} J$$

but now with added (physical) momentum

$$\mathbf{m} \leftarrow \beta \mathbf{m} - \eta \nabla_{\mathbf{w}} J$$

$$\mathbf{w} \leftarrow \mathbf{w} + \mathbf{m}$$



Optimizers

Momentum Optimization


Normal GD algo

$$\mathbf{w} \leftarrow \mathbf{w} - \eta \nabla_{\mathbf{w}} J$$

but now with added (physical) momentum

$$\mathbf{m} \leftarrow \beta \mathbf{m} - \eta \nabla_{\mathbf{w}} J$$

$$\mathbf{w} \leftarrow \mathbf{w} + \mathbf{m}$$



Optimizers

Momentum Optimization


Normal GD algo

$$\mathbf{w} \leftarrow \mathbf{w} - \eta \nabla_{\mathbf{w}} J$$

but now with added (physical) momentum

$$\mathbf{m} \leftarrow \beta \mathbf{m} - \eta \nabla_{\mathbf{w}} J$$

$$\mathbf{w} \leftarrow \mathbf{w} + \mathbf{m}$$



Optimizers

Momentum Optimization


Normal GD algo

$$\mathbf{w} \leftarrow \mathbf{w} - \eta \nabla_{\mathbf{w}} J$$

but now with added (physical) momentum

$$\mathbf{m} \leftarrow \beta \mathbf{m} - \eta \nabla_{\mathbf{w}} J$$

$$\mathbf{w} \leftarrow \mathbf{w} + \mathbf{m}$$



Optimizers

Momentum Optimization


Normal GD algo

$$\mathbf{w} \leftarrow \mathbf{w} - \eta \nabla_{\mathbf{w}} J$$

but now with added (physical) momentum

$$\mathbf{m} \leftarrow \beta \mathbf{m} - \eta \nabla_{\mathbf{w}} J$$

$$\mathbf{w} \leftarrow \mathbf{w} + \mathbf{m}$$



Optimizers

Momentum Optimization



Normal GD algo

$$\mathbf{w} \leftarrow \mathbf{w} - \eta \nabla_{\mathbf{w}} J$$

but now with added (physical) momentum

$$\mathbf{m} \leftarrow \beta \mathbf{m} - \eta \nabla_{\mathbf{w}} J$$

$$\mathbf{w} \leftarrow \mathbf{w} + \mathbf{m}$$



Optimizers

Momentum Optimization



Normal GD algo

$$\mathbf{w} \leftarrow \mathbf{w} - \eta \nabla_{\mathbf{w}} J$$

but now with added (physical) momentum

$$\mathbf{m} \leftarrow \beta \mathbf{m} - \eta \nabla_{\mathbf{w}} J$$

$$\mathbf{w} \leftarrow \mathbf{w} + \mathbf{m}$$



Optimizers

Momentum Optimization



Normal GD algo

$$\mathbf{w} \leftarrow \mathbf{w} - \eta \nabla_{\mathbf{w}} J$$

but now with added (physical) momentum

$$\mathbf{m} \leftarrow \beta \mathbf{m} - \eta \nabla_{\mathbf{w}} J$$

$$\mathbf{w} \leftarrow \mathbf{w} + \mathbf{m}$$



Optimizers

Momentum Optimization



Normal GD algo

$$\mathbf{w} \leftarrow \mathbf{w} - \eta \nabla_{\mathbf{w}} J$$

but now with added (physical) momentum

$$\mathbf{m} \leftarrow \beta \mathbf{m} - \eta \nabla_{\mathbf{w}} J$$

$$\mathbf{w} \leftarrow \mathbf{w} + \mathbf{m}$$



Optimizers

Momentum Optimization



Normal GD algo

$$\mathbf{w} \leftarrow \mathbf{w} - \eta \nabla_{\mathbf{w}} J$$

but now with added (physical) momentum

$$\mathbf{m} \leftarrow \beta \mathbf{m} - \eta \nabla_{\mathbf{w}} J$$

$$\mathbf{w} \leftarrow \mathbf{w} + \mathbf{m}$$



Optimizers

Momentum Optimization



Normal GD algo

$$\mathbf{w} \leftarrow \mathbf{w} - \eta \nabla_{\mathbf{w}} J$$

but now with added (physical) momentum

$$\mathbf{m} \leftarrow \beta \mathbf{m} - \eta \nabla_{\mathbf{w}} J$$

$$\mathbf{w} \leftarrow \mathbf{w} + \mathbf{m}$$



Optimizers

Momentum Optimization



Normal GD algo

$$\mathbf{w} \leftarrow \mathbf{w} - \eta \nabla_{\mathbf{w}} J$$

but now with added (physical) momentum

$$\mathbf{m} \leftarrow \beta \mathbf{m} - \eta \nabla_{\mathbf{w}} J$$

$$\mathbf{w} \leftarrow \mathbf{w} + \mathbf{m}$$



Optimizers

Momentum Optimization


Normal GD algo

$$\mathbf{w} \leftarrow \mathbf{w} - \eta \nabla_{\mathbf{w}} J$$

but now with added (physical) momentum

$$\mathbf{m} \leftarrow \beta \mathbf{m} - \eta \nabla_{\mathbf{w}} J$$

$$\mathbf{w} \leftarrow \mathbf{w} + \mathbf{m}$$



Optimizer selection: (perhaps) via searching..

`sklearn.neural_network.MLPRegressor`

```
class sklearn.neural_network.MLPRegressor(hidden_layer_sizes=(100, ), activation='relu', *, solver='adam', alpha=0.0001,
batch_size='auto', learning_rate='constant', learning_rate_init=0.001, power_t=0.5, max_iter=200, shuffle=True,
random_state=None, tol=0.0001, verbose=False, warm_start=False, momentum=0.9, nesterovs_momentum=True,
early_stopping=False, validation_fraction=0.1, beta_1=0.9, beta_2=0.999, epsilon=1e-08, n_iter_no_change=10,
max_fun=15000)
```

[\[source\]](#)

Multi-layer Perceptron regressor.

This model optimizes the squared-loss using LBFGS or stochastic gradient descent.

New in version 0.18.

Parameters: `hidden_layer_sizes : tuple, length = n_layers - 2, default=(100,)`

The *i*th element represents the number of neurons in the *i*th hidden layer.

`solver : {'lbfgs', 'sgd', 'adam'}, default='adam'`

The solver for weight optimization.

- 'lbfgs' is an optimizer in the family of quasi-Newton methods.
- 'sgd' refers to stochastic gradient descent.
- 'adam' refers to a stochastic gradient-based optimizer proposed by Kingma, Diederik, and Jimmy Ba

Note: The default solver 'adam' works pretty well on relatively large datasets (with thousands of training samples or more) in terms of both training time and validation score. For small datasets, however, 'lbfgs' can converge faster and perform better.

`activation : {'identity', 'logistic', 'tanh', 'relu'}, default='relu'`

Activation function for the hidden layer.

Optimizers

Or optimizers in Keras..



About Keras

Getting started

Developer guides

Keras API reference

Models API

Layers API

Callbacks API

Data preprocessing

Optimizers

Metrics

Losses

Built-in small datasets

Keras Applications

Utilities

Code examples

Why choose Keras?

Available optimizers

- SGD
- RMSprop
- Adam
- Adadelta
- Adagrad
- Adamax
- Nadam
- Ftrl



Search Keras documentation...

» Keras API reference / Optimizers

Optimizers

Usage with `compile()` & `fit()`

An optimizer is one of the two arguments required for compiling a Keras model:

```
from tensorflow import keras
from tensorflow.keras import layers

model = keras.Sequential()
model.add(layers.Dense(64, kernel_initializer='uniform', input_shape=(10,)))
model.add(layers.Activation('softmax'))

opt = keras.optimizers.Adam(learning_rate=0.01)
model.compile(loss='categorical_crossentropy', optimizer=opt)
```

You can either instantiate an optimizer before passing it to `model.compile()`, as in the above example, or you can pass it by its string identifier. In the latter case, the default parameters for the optimizer will be used.

```
# pass optimizer by name: default parameters will be used
model.compile(loss='categorical_crossentropy', optimizer='adam')
```

Optimizers


- ▷ Usage with `compile()` & `fit()`
- ▷ Usage in a custom training loop
- ▷ Learning rate decay scheduling
- ▷ Available optimizers
- ▷ Core Optimizer API
 - apply_gradients method
 - weights property
 - get_weights method
 - set_weights method

ML Models (or ML algorithms)

Models encountered so far


Some classifiers and regressors..

```
sklearn.neighbors.KNeighborsRegressor  
sklearn.linear_model.LinearRegression  
sklearn.linear_model.SGDClassifier  
sklearn.linear_model.SGDRegressor
```




The screenshot shows the scikit-learn website. At the top is the 'lemla' logo and navigation links: 'Install', 'User Guide', 'API', 'Examples', and 'More'. Below this is the 'scikit-learn' logo and the tagline 'Machine Learning in Python'. There are three buttons: 'Getting Started', 'What's New in 0.22.1', and 'Github'. To the right, a list of features includes: 'Simple and efficient tools for predictive data analysis', 'Accessible to everybody and reusable in various contexts', 'Built on NumPy, SciPy, and matplotlib', and 'Open source, commercially usable - BSD license'.


Classification
Identifying which category an object belongs to.
Applications: Spam detection, image recognition.
Algorithms: SVM, nearest neighbors, random forest, and more...



Regression
Predicting a continuous-valued attribute associated with an object.
Applications: Drug responses, stock prices.
Algorithms: SVM, nearest neighbors, random forest, and more.



Clustering
Automatic grouping of similar objects.
Applications: Customer segmentation, experiment outcomes.
Algorithms: k-Means, spectral clustering, and more.



ML Models (or ML algorithms)


Models encountered so far

Some classifiers and regressors..

```
sklearn.neighbors.KNeighborsRegressor  
sklearn.linear_model.LinearRegression  
sklearn.linear_model.SGDClassifier  
sklearn.linear_model.SGDRegressor
```

Perhaps..

```
sklearn.naive_bayes.GaussianNB  
sklearn.naive_bayes.MultinomialNB  
sklearn.svm.SVC  
sklearn.svm.SVR
```



The screenshot shows the scikit-learn website. At the top, there's a navigation bar with links: Home, Install, User Guide, API, Examples, and More. Below this, the 'scikit-learn' logo is prominently displayed, followed by the tagline 'Machine Learning in Python'. To the right of the logo, there are four bullet points highlighting key features: 'Simple and efficient tools for predictive data analysis', 'Accessible to everybody and reusable in various contexts', 'Built on NumPy, SciPy, and matplotlib', and 'Open source, commercially usable - BSD license'. Below the main header, there are three main content sections: 'Classification', 'Regression', and 'Clustering'. Each section has a brief description, a list of applications, and a list of algorithms. The 'Classification' section includes a small image grid. The 'Regression' section includes a line graph. The 'Clustering' section includes a scatter plot with colored clusters.

scikit-learn
Machine Learning in Python

- Simple and efficient tools for predictive data analysis
- Accessible to everybody and reusable in various contexts
- Built on NumPy, SciPy, and matplotlib
- Open source, commercially usable - BSD license

[Getting Started](#) [What's New in 0.22.1](#) [Github](#)

Classification

Identifying which category an object belongs to.

Applications: Spam detection, image recognition, and more...

Algorithms: SVM, nearest neighbors, random forest, and more...

Regression

Predicting a continuous-valued attribute associated with an object.

Applications: Drug responses, stock prices, and more...

Algorithms: SVM, nearest neighbors, random forest, and more...

Clustering

Automatic grouping of similar objects

Applications: Customer segmentation, experiment outcomes, and more...

Algorithms: k-Means, spectral clustering, and more...

ML Models (or ML algorithms)

Models encountered so far

Some classifiers and regressors..


```
sklearn.neighbors.KNeighborsRegressor  
sklearn.linear_model.LinearRegression  
sklearn.linear_model.SGDClassifier  
sklearn.linear_model.SGDRegressor
```

Perhaps..

```
sklearn.naive_bayes.GaussianNB  
sklearn.naive_bayes.MultinomialNB  
sklearn.svm.SVC  
sklearn.svm.SVR
```

and to some degree..

```
sklearn.linear_model.LogisticRegression  
sklearn.linear_model.Perceptron  
sklearn.neural_network.MLPClassifier  
sklearn.neural_network.MLPRegressor  
keras.Sequential
```



The screenshot shows the scikit-learn website. At the top is a navigation bar with links: Install, User Guide, API, Examples, and More. Below this is the scikit-learn logo and the tagline "Machine Learning in Python". To the right of the logo are four bullet points: "Simple and efficient tools for predictive data analysis", "Accessible to everybody and reusable in various contexts", "Built on NumPy, SciPy, and matplotlib", and "Open source, commercially usable - BSD license". Below the main header are three columns. The "Classification" column describes identifying object categories, lists applications like spam detection and image recognition, and lists algorithms like SVM, k-nearest neighbors, and random forest. It includes a 4x4 grid of small images. The "Regression" column describes predicting continuous values, lists applications like drug responses and stock prices, and lists algorithms like SVR, k-nearest neighbors, and random forest. It includes a line graph showing a fluctuating trend. The "Clustering" column describes automatic grouping of similar objects, lists applications like customer segmentation and experiment outcomes, and lists algorithms like k-Means, spectral clustering, and more. It includes a scatter plot with points colored by cluster.

ML Models (or ML algorithms)

Models encountered so far

Some classifiers and regressors..

```
sklearn.neighbors.KNeighborsRegressor  
sklearn.linear_model.LinearRegression  
sklearn.linear_model.SGDClassifier  
sklearn.linear_model.SGDRegressor
```

Perhaps..


```
sklearn.naive_bayes.GaussianNB  
sklearn.naive_bayes.MultinomialNB  
sklearn.svm.SVC  
sklearn.svm.SVR
```

and to some degree..

```
sklearn.linear_model.LogisticRegression  
sklearn.linear_model.Perceptron  
sklearn.neural_network.MLPClassifier  
sklearn.neural_network.MLPRegressor  
keras.Sequential
```

Or even more exotic models like..

- ▶ supervised ensemble: AdaBoost, Bagging, DecisionTree, RandomForest,...
- ▶ semi-supervised: ??
- ▶ unsupervised: K-means, manifolds, restricted Boltzmann machines,...
- ▶ clustering: K-means



ML Algorithm + Model Selection via Searching

What ML algorithm to choose?

- ▶ manual:
 - algorithm characteristics, \mathcal{O} complexity, etc.
 - browsing through Scikit-learn documentation,
 - ...and also based on data assumptions.

ML Algorithm + Model Selection via Searching

What ML algorithm to choose?

- ▶ manual:
 - algorithm characteristics, \mathcal{O} complexity, etc.
 - browsing through Scikit-learn documentation,
...and also based on data assumptions.
- ▶ semi-automatic:
 - brute-force model search, and fun with python!

ML Algorithm + Model Selection via Searching

What ML algorithm to choose?

- ▶ manual:
 - algorithm characteristics, \mathcal{O} complexity, etc.
 - browsing through Scikit-learn documentation,
 - ...and also based on data assumptions.
- ▶ semi-automatic:
 - brute-force model search, and fun with python!

```
1  models = {  
2      SVC(gamma="scale"),  
3      SGDClassifier(tol=1e-3, eta0=0.1),  
4      GaussianNB()  
5  }  
6  
7  for i in models:  
8      i.fit(X_train, y_train)  
9      y_pred_test = i.predict(X_test)  
10     p = precision_score(y_test, y_pred_test, average='micro')  
11     print(f'{type(i).__name__:13s}: precision={p:0.2f}')
```

NOTE: Python set = {a, b}
Python dictionary = {a: x, b: y}

ML Algorithm + Model Selection via Searching

What ML algorithm to choose?

- ▶ manual:
 - algorithm characteristics, \mathcal{O} complexity, etc.
 - browsing through Scikit-learn documentation,
 - ...and also based on data assumptions.
- ▶ semi-automatic:
 - brute-force model search, and fun with python!

```
1 models = {  
2     SVC(gamma="scale"),  
3     SGDClassifier(tol=1e-3, eta0=0.1),  
4     GaussianNB()  
5 }  
6  
7 for i in models:  
8     i.fit(X_train, y_train)  
9     y_pred_test = i.predict(X_test)  
10    p = precision_score(y_test, y_pred_test, average='micro')  
11    print(f'{type(i).__name__:13s}: precision={p:0.2f}')
```

prints..

GaussianNB:	p=1.00
SGDClassifier:	p=0.93
SVC:	p=0.98

NOTE: Python set = {a, b}
Python dictionary = {a:x, b:y}

Model Selection via Grid Search

The hyperparameter-set for SGD linear regressor

```
1  class sklearn.linear_model.SGDRegressor(  
2      loss      ='squared_loss', penalty      ='l2',  
3      alpha     =0.0001,      l1_ratio      =0.15,  
4      tol       =None,        shuffle       =True,  
5      verbose   =0,           epsilon       =0.1,  
6      eta0      =0.01,        power_t     =0.25,  
7      n_iter_no_change=5,      warm_start  =False,  
8      fit_intercept =True,    max_iter    =None,  
9      average     =False,    n_iter      =None  
10     random_state =None,    learning_rate='invscaling',  
11     early_stopping =False,  validation_fraction=0.1  
12 )
```

Model Selection via Grid Search

The hyperparameter-set for SGD linear regressor

```
1 class sklearn.linear_model.SGDRegressor(  
2     loss      ='squared_loss', penalty      ='l2',  
3     alpha     =0.0001,               l1_ratio    =0.15,  
4     tol       =None,                  shuffle     =True,  
5     verbose   =0,                     epsilon     =0.1,  
6     eta0      =0.01,                  power_t     =0.25,  
7     n_iter_no_change=5,                warm_start  =False,  
8     fit_intercept =True,               max_iter    =None,  
9     average     =False,               n_iter      =None  
10    random_state  =None,               learning_rate='invscaling',  
11    early_stopping =False,             validation_fraction=0.1  
12 )
```



Model Selection via Grid Search

The hyperparameter-set for SGD linear regressor

```
1  class sklearn.linear_model.SGDRegressor(  
2      loss      ='squared_loss', penalty      ='l2',  
3      alpha     =0.0001,          l1_ratio    =0.15,  
4      tol       =None,            shuffle     =True,  
5      verbose   =0,              epsilon     =0.1,  
6      eta0      =0.01,           power_t    =0.25,  
7      n_iter_no_change=5,        warm_start  =False,  
8      fit_intercept =True,       max_iter    =None,  
9      average     =False,       n_iter      =None  
10     random_state  =None,       learning_rate='invscaling',  
11     early_stopping =False,     validation_fraction=0.1  
12 )
```



Search best hyperparameters in a (smaller) set, say

Model Selection via Grid Search

The hyperparameter-set for SGD linear regressor

```
1 class sklearn.linear_model.SGDRegressor(  
2     loss      = 'squared_loss', penalty      = 'l2',  
3     alpha     = 0.0001,               l1_ratio   = 0.15,  
4     tol       = None,                 shuffle    = True,  
5     verbose   = 0,                   epsilon    = 0.1,  
6     eta0      = 0.01,                power_t    = 0.25,  
7     n_iter_no_change=5,               warm_start  = False,  
8     fit_intercept = True,             max_iter    = None,  
9     average     = False,             n_iter      = None,  
10    random_state  = None,             learning_rate='invscaling',  
11    early_stopping = False,          validation_fraction=0.1  
12 )
```



Search best hyperparameters in a (smaller) set, say

```
1 model = SGDClassifier()  
2 tuning_parameters = {  
3     'alpha': [ 0.001, 0.01, 0.1],  
4     'max_iter': [1, 10, 100, 100],  
5     'learning_rate': ('constant', 'optimal', 'invscaling', 'adaptive')  
6 }  
7 ..  
8 grid_tuned = GridSearchCV(model, tuning_parameters, ..
```

Model Selection via Grid Search

How to select 'best' set of hyperparameter—using brute force?

Gridsearch seen in 3D for the two hyperspace dimensions:


- ▶ `alpha` $\in [1, 2, 3, ..]$ (NOTE: linear range for this plot only,
- ▶ `max_iter` $\in [1, 2, 3, ..]$ should be 1, 10, 100 or similar.)

Model Selection via Grid Search

How to select 'best' set of hyperparameter—using brute force?

Gridsearch seen in 3D for the two hyperspace dimensions:

- ▶ `alpha` $\in [1, 2, 3, \dots]$ (NOTE: linear range for this plot only,
- ▶ `max_iter` $\in [1, 2, 3, \dots]$ should be 1, 10, 100 or similar.)




Model Selection via Grid Search

How to select 'best' set of hyperparameter—using brute force?

Gridsearch seen in 3D for the two hyperspace dimensions:

- ▶ $\alpha \in [1, 2, 3, \dots]$ (NOTE: linear range for this plot only, should be 1, 10, 100 or similar.)
- ▶ $\text{max_iter} \in [1, 2, 3, \dots]$




- ▶ why score and not J on z-axis?

Model Selection via Grid Search

How to select 'best' set of hyperparameter—using brute force?

Gridsearch seen in 3D for the two hyperspace dimensions:

- ▶ $\alpha \in [1, 2, 3, \dots]$ (NOTE: linear range for this plot only, should be 1, 10, 100 or similar.)
- ▶ $\text{max_iter} \in [1, 2, 3, \dots]$



- ▶ why score and not J on z-axis?
- ▶ and what if there are many hyperparameters and many combinations? → Zzzzzzz!

Model Selection via Randomized Search

How to select 'best' set of hyperparameters—faster than brute force?

Replace `GridSearchCV()` with


`RandomizedSearchCV(n_iter=100,...)`

Model Selection via Randomized Search

How to select 'best' set of hyperparameters—faster than brute force?

Replace `GridSearchCV()` with

`RandomizedSearchCV(n_iter=100,...)`




Model Selection via Randomized Search

How to select 'best' set of hyperparameters—faster than brute force?

Replace `GridSearchCV()` with

```
RandomizedSearchCV(n_iter=100,...)
```




- faster, but will not yield the (sub) optimal score maximum,

Model Selection via Randomized Search

How to select 'best' set of hyperparameters—faster than brute force?

Replace `GridSearchCV()` with

```
RandomizedSearchCV(n_iter=100,...)
```




- ▶ faster, but will not yield the (sub) optimal score maximum,
- ▶ ...but does it matter in a huge hyperparameter search-space?

Extra Slides..

Keras and Tensorflow





Using the Keras API instead of Scikit-learn or TensorFlow



Keras and Tensorflow



Using the Keras API instead of Scikit-learn or TensorFlow



Docs » Home

Edit on GitHub

Keras: The Python Deep Learning library



You have just found Keras.

Keras is a high-level neural networks API, written in Python and capable of running on top of TensorFlow, CNTK, or Theano. It was developed with a focus on enabling fast experimentation. Being able to go from idea to result with the least possible delay is key to doing good research.

Use Keras if you need a deep learning library that:

- Allows for easy and fast prototyping (through user-friendliness, modularity, and extensibility).
- Supports both convolutional networks and recurrent networks, as well as combinations of the two.
- Runs seamlessly on CPU and GPU.



NOTE:

- documentation: <https://keras.io/>

Keras and Tensorflow



Using the Keras API instead of Scikit-learn or TensorFlow



Docs » Home

Edit on GitHub

Keras: The Python Deep Learning library



You have just found Keras.

Keras is a high-level neural networks API, written in Python and capable of running on top of TensorFlow, CNTK, or Theano. It was developed with a focus on enabling fast experimentation. Being able to go from idea to result with the least possible delay is key to doing good research.

Use Keras if you need a deep learning library that:



- Allows for easy and fast prototyping (through user-friendliness, modularity, and extensibility).
- Supports both convolutional networks and recurrent networks, as well as combinations of the two.
- Runs seamlessly on CPU and GPU.

NOTE:

- ▶ documentation: <https://keras.io/>
- ▶ keras provides a `fit-predict`-interface,
- ▶ many similarities to Scikit-learn,
- ▶ but also many differences!


High-Performance-Computing (HPC)

Running on the ASE GPU cluster, your group login=e20malXY



High-Performance-Computing (HPC)

Running on the ASE GPU cluster, your group login=e20malXY



NOTE:

manuel GPU hukommelses Garbage Collection...

For keras GPU kald:

```
StartupSequence_EnableGPU(gpu_mem_fraction=0.1, gpus=1)
```

NOTE2: script found in /home/shared/00_init.py that runs for all users!