

Deep Illumination-Driven Light Probe Placement

Andreas Tarasidis

Diploma Thesis

Supervisor: Ioannis Fudos

Ioannina, July 2025



ΤΜΗΜΑ ΜΗΧ. Η/Υ & ΠΛΗΡΟΦΟΡΙΚΗΣ

ΠΑΝΕΠΙΣΤΗΜΙΟ ΙΩΑΝΝΙΝΩΝ

DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING

UNIVERSITY OF IOANNINA

Dedication

To my mother, father, and brother, who always helped me achieve my goals.

Acknowledgments

First and foremost, I would like to express my sincere gratitude to my supervisor, Prof, Ioannis Fudos, for his invaluable guidance, feedback, and support. As an advisor, he always made time, was extraordinarily patient, and his suggestions were instrumental in the completion of this thesis.

I am also grateful to the friends I've made over the years. Their camaraderie has made my academic journey truly worthwhile.

This journey wouldn't have been possible without them, so finally, but certainly not least, I extend my deepest gratitude to my family. Without their encouragement, boundless support, and unwavering belief in my potential, my works would never have reached fruition.

I dedicate this thesis to them.

Abstract

Realistic lighting is a cornerstone of visually compelling 3D graphics. Unity’s LightProbe system offers an efficient way to capture and interpolate baked Global Illumination (GI) data across dynamic objects in scenes. However, manual placement of light probes in complex scenes is both time-consuming and error-prone, greatly delaying the iteration process when making 3D applications. This thesis presents an automated, deep learning-based approach that predicts per-point importance scores for light probe placement using a PointNet++-inspired neural network.

We first generate a regular 3D point grid that conforms to the user-defined arbitrarily-shaped bounds of the scene. We sample per-point lighting information, including spherical harmonics, light-, normal-, and RGB- variance, and occlusion factor as well. These features capture important information that drive GI accuracy. The data is then converted into a concise feature vector at each location, used to then train the PointNet++-style AI model that consumes an arbitrary-length list of such feature vectors and outputs a probability in the range 0-1, depicting how vital it is to place a light probe at each point on the grid.

To deploy in Unity, the trained model is then exported to an .ONNX file and imported via Sentic, the official Unity package for handling AI models inside a Unity Runtime; at edit-time, it ingests per-point scene data and returns per-point importance values. Predicted high-importance locations are then used to populate a Unity LightProbeGroup object, giving developers immediate, visually appropriate probe distributions, with easy to control thresh-holding if higher- or lower-importance locations are desired.

We demonstrate that our AI model generalizes across grid sizes and shapes without retraining, as well as giving immediate results for any scene. Although our evaluation remains mostly qualitative, based on visual inspection of GI results and light-probe placement across a variety of indoor and outdoor scenes, we consistently observe that the generated probe layouts capture important scene light-data with minimal or no manual tweaking. By replacing manual probe placement with a simpler AI-based workflow, artists and developers save time and achieve a faster iteration process throughout the development of a 3D application.

Περίληψη

TODO

List of Figures

1.1	Scene lighting with direct illumination only. By Barahag - Own work, CC BY-SA 4.0	8
1.2	Scene lighting with Global illumination. By Barahag - Own work, CC BY-SA 4.0	8

List of Algorithms

Table of Contents

1	Introduction	8
1.1	Related Work	9
1.1.1	Offline Methods	9
1.1.2	Online Methods	9
1.2	Thesis Structure	11
2	Review of the Literature	12
2.1	Light Probes	12
3	Our Approach	13
4	Experiments	14
5	Conclusions and Future Work	15

Chapter 1

Introduction

Modern interactive 3D applications, like video games, VR/AR apps, simulators etc., depend on believable lighting interactions with the objects of a 3D scene to achieve the desired visual goals, while trying to maintain real-time frame-rate budgets, typically above 30 Frames per Second (FPS). Achieving visual fidelity and performance can be a difficult task and sometimes impossible with the given hardware specifications of the device. For that reason, modern real-time rendering engines, e.g. Unity, Unreal Engine, Godot and others, depend on a number of methods to balance those metrics.

The illumination of any scene can be split into two very simple categories. Direct Illumination, the light that travels unoccluded from a light source to a surface of an object, is typically handled with techniques like shadow-mapping or screen-space shadows, yielding crisp, high-framerate-capable shadows, but lack in inter-surface light transport situations. In contrast, Indirect Illumination, or Global Illumination (GI), captures light that has bounced or refracted off one or more surfaces, producing soft shadows, color bleeding, and contextually rich shading.




Figure 1.1: Scene lighting with direct illumination only. By Barahag - Own work, CC BY-SA 4.0

<https://commons.wikimedia.org/w/index.php?curid=88541991>




Figure 1.2: Scene lighting with Global illumination. By Barahag - Own work, CC BY-SA 4.0

<https://commons.wikimedia.org/w/index.php?curid=88540888>

The field-standard for accurate lighting and shadows in a scene is Path-Tracing, a method that tracks every light ray and any interactions it has with the objects of a 3D scene and calculates the resulting color for each pixel of the screen. Such approach remains prohibitively expensive for most interactive applications, so real-time systems employ pre-computation and approximation of the illumination of the scene; static geometry is baked into lightmaps that store per-textel irradiance, while dynamic elements sample from irra-

diancance volumes or light probes, sparse 3D points whose spherical-harmonic coefficients are interpolated at runtime.

Screen-space GI methods typically approximate a limited number of light-ray bounces directly from the camera’s depth buffer, but suffer from missing contextual information outside the camera’s view frustum and temporal instability. Voxel-based approaches (e.g., cone-tracing through a low resolution 3D grid) enable more dynamic multi-bounce effects at the cost of memory, processing cost and potential blurring of fine detail.

Across all these techniques, the central challenge is allocating a strict millisecond-scale budget to indirect illumination while maintaining consistency across static and dynamic scene content, avoiding visible seams when blending baked and runtime solutions and fitting within GPU memory constraints.

Light probes, in particular, represent a compelling middle-ground, flexible enough to illuminate moving objects without rebaking yet compact enough for real-time evaluation, making their optimal placement a critical factor in any high-quality GI pipeline.

1.1 Related Work

There is an abundance of work in the literature addressing the problem of Global Illumination. These studies aim to achieve realistic lighting in 3D scenes by employing various approaches and techniques, each offering unique advantages and disadvantages, but they share a common goal: to maximize visual fidelity while minimizing computational costs.

1.1.1 Offline Methods

Offline Illumination methods refer to techniques that are not viable for real-time applications and are therefore used only in situations where the importance of high visual fidelity far outweighs the need for computational speed, typically in non-interactive 3D renders, most commonly in movies or pre-rendered scenes. Classic Path-Tracing, first introduced in 1986 (Kajiya 1986), tracks the movement of a photon ray emitted from a source, typically the camera, and simulates physics interactions to calculate the color of each screen pixel accurately. The immense computational cost of path-tracing led to the development of performance improvements, such as the Metropolis Light Transport (MLT) method introduced in 1997 (Veach and Guibas 1997), and variants like bi-directional Path-Trace (Lafortune and Willems 1993), which build on Monte-Carlo algorithms (Lafortune 1996).

1.1.2 Online Methods

In contrast, online methods aim to calculate GI interactions in real-time, most commonly used in interactive applications like video games or simulations. They try to balance performance and accuracy, a task that is often difficult due to the processing cost of the calculations for a realistic result. Therefore, these methods take shortcuts, either approximating the GI interactions to a certain degree to maintain framerate budgets, or by precomputing some of the data, wherever possible.

Traditional Methods

Techniques that precompute the illumination of a scene only do so for static geometry; objects in the scene that will never change their position, rotation or scale. The algorithms “bake” the required information onto texture maps, which are rendered as such when needed. Light-mapping is one such technique. It precomputes surface brightness and

has a low runtime cost. The game Quake was the first interactive application that used lightmaps for rendering GI (Wikipedia contributors 2025).

Another early technique is the Irradiance Volumes algorithm (Greger et al. 1998), which scatters spherical-harmonic (SH) irradiance samples on a 3D grid on the scene. At runtime, lighting is interpolated from the nearest SH cells; this underlies many probe systems, like Unity’s light-probe system that implicitly implements a sparse irradiance volume.

More recent static-GI algorithms include Light Field Probes (McGuire et al. 2017). Light Field Probes extend standard irradiance probes by additionally storing per-textel visibility for each probe. Furthermore, Xu et al. 2022 introduce Discrete Visibility Fields for static ray-traced lighting. The method precomputes occlusion masks stored in a uniform voxel grid, and at runtime, rays that hit a cell use the stored precomputed masks to quickly cull visibility, skipping geometry already known to be occluded.

Unity’s new Adaptive Probe Volumes (APV) build on irradiance volumes by automatically populating a grid, with density matched to local geometry. APV then performs per-pixel probe sampling; each pixel blends from the eight nearest probes (Unity 2025).

Additionally, there are methods that don’t focus on Probes for GI. A prevalent example is Unreal Engine’s Lumen, a dynamic GI and reflections system that uses a hybrid tracing approach; It starts with a cheap screen-space or signed-distance-field ray cast, and then falls back to more expensive methods like hardware ray tracing (EpicGames 2025).

NVIDIA has also developed RTXGI, a GPU-accelerated library implementing Dynamic Diffuse GI, using a volumetric grid of irradiance probes, which update every frame using hardware-accelerated ray tracing, creating accurate results at the cost of hardware-restricted algorithms and a relatively escalated cost of calculation (Nvidia 2024).

Crassin et al. 2011 introduced Voxel Cone Tracing (VCT) to approximate real-time GI. In VCT, the scene’s static geometry and lighting are ”voxelized” into a 3D texture with multiple levels of mipmapping, containing radiance and opacity. At runtime, indirect illumination is approximated by tracing a few low-resolution ”cones” from each surface sample into the aforementioned voxel grid, summing the values from regions of voxels.

Even though there are numerous methods trying to solve real-time GI issues, a big percentage of them tend to revolve around probes of various types; most commonly calculating irradiance values among other high-importance metrics. Therefore, it is vital for a 3D scene to have proper probe placement for best results. There are a few methods that try to automate that process, often by placing the probes in a regular grid and only removing the probes that are inside objects, but that can lead to over-sampling, leading to performance costs, mainly in memory usage budgets. Furthermore, some techniques try to remove additional probes using heuristic methods, therefore approaching optimal placement, but with a significant precomputational cost.

Wang et al. 2019 introduce an automatic non-uniform placing scheme using 3D scene skeletons and gradient-descent refinement to cover important locations without redundant probes. A very recent work by Teuber et al. 2024 formulates geometry-based optimization of probe placement using various mesh features, to further improve the lighting in VR/AR scenarios.

Similarly, Vardis, Vasilakis, and Papaioannou 2021 approach the problem by starting with a probe set on a dense grid and iteratively removing the least-important probes using radiance error tests, preserving the global light field while minimizing probe count.

AI-based Methods

Recently, AI-assisted methods have started to be developed in order to improve GI in 3D applications, specifically in probe-based solutions. Guo et al. 2022 propose a hybrid

neural probe GI. They use a gradient-based search to re-project stored probe radiance for any view, therefore eliminating parallax, and then apply a small neural network to reconstruct high-quality images from low-resolution probe data. Related, You, Geiger, and Chen 2024 created Neural Light Field Probes, which works by decomposing a scene into a grid of trainable light field probes. Each of these probes encodes local radiance and visibility in a compact feature map. Finally, a neural network optimizes these probes so that the summation of their contributions reproduces the full scene lighting.

1.2 Thesis Structure

The structure of the remainder of this thesis will be described shortly. Chapter 2, titled Background, covers important information about light probes and their implementation, describes the AI model basis that was used for our implementation, and introduces the tools and technologies that were used in this thesis. Chapter 3, titled Our Approach (?), presents our method, describes the implementation of the algorithms used, and explains how each part is combined to create the Light-Probe Neural Network (LPNN), our neural network system that attempts to speed up light probe placement in Unity 3D scenes by predicting importance values for the given grid set and placing only the most vital light probes, affected by a user-controlled threshold value. Each grid position gathers samples of a few metrics, which are then used by the neural network to decide whether or not it is vital to place a light probe in each individual cell of the 3D grid. A step-by-step process of creating the grid, getting the features out of the grid cells, and placing the probes and baking the global illumination inside Unity. Additionally, the feature set can be used to retrain the AI model, we explain how to create the labels needed for the process, and how to import the new model to Unity using Sentis for usage. Chapter 4, titled Experiments, presents an experimental comparative and qualitative evaluation between the proposed method and some of the already introduced algorithms. Finally, Chapter 5, titled Conclusions and Future Works, concludes the thesis and proposes directions for future work based on this thesis.

Chapter 2

Background

theoretical background, what light probes are, technologies used

2.1 Light Probes

TODO

Chapter 3

Our Approach

what we did and how why etc

Chapter 4

Experiments

examples and stuff

Chapter 5

Conclusions and Future Work

conclusions and future works

Bibliography

- Crassin, Cyril et al. (2011). “Interactive indirect illumination using voxel-based cone tracing: an insight”. In: *ACM SIGGRAPH 2011 Talks*. SIGGRAPH ’11. Vancouver, British Columbia, Canada: Association for Computing Machinery. ISBN: 9781450309745. DOI: [10.1145/2037826.2037853](https://doi.org/10.1145/2037826.2037853). URL: <https://doi.org/10.1145/2037826.2037853>.
- EpicGames (2025). *Lumen GI*. URL: <https://dev.epicgames.com/documentation/en-us/unreal-engine/lumen-global-illumination-and-reflections-in-unreal-engine>.
- Greger, G. et al. (1998). “The irradiance volume”. In: *IEEE Computer Graphics and Applications* 18.2, pp. 32–43. DOI: [10.1109/38.656788](https://doi.org/10.1109/38.656788).
- Guo, Jie et al. (Nov. 2022). “Efficient Light Probes for Real-Time Global Illumination”. In: *ACM Transactions on Graphics* 41, pp. 1–14. DOI: [10.1145/3550454.3555452](https://doi.org/10.1145/3550454.3555452).
- Kajiya, James T. (Aug. 1986). “The rendering equation”. In: *SIGGRAPH Comput. Graph.* 20.4, 143–150. ISSN: 0097-8930. DOI: [10.1145/15886.15902](https://doi.org/10.1145/15886.15902). URL: <https://doi.org/10.1145/15886.15902>.
- Lafortune, E (1996). “Mathematical Models and Monte Carlo Algorithms for Physically Based Rendering”. URL: <https://web.archive.org/web/20160617231944/http://www.graphics.cornell.edu/~eric/thesis/index.html>.
- Lafortune, Eric P. and Yves D. Willems (1993). “Bi-directional path tracing”. In: *Proceedings of Third International Conference on Computational Graphics and Visualization Techniques (Compugraphics ’93)*. Alvor, Portugal, pp. 145–153. URL: <https://graphics.cs.kuleuven.be/publications/BDPT/>.
- McGuire, Morgan et al. (2017). “Real-time global illumination using precomputed light field probes”. In: *Proceedings of the 21st ACM SIGGRAPH Symposium on Interactive 3D Graphics and Games*. I3D ’17. San Francisco, California: Association for Computing Machinery. ISBN: 9781450348867. DOI: [10.1145/3023368.3023378](https://doi.org/10.1145/3023368.3023378). URL: <https://doi.org/10.1145/3023368.3023378>.
- Nvidia (2024). *RTXGI Dynamic Diffuse GI*. URL: <https://github.com/NVIDIAGameWorks/RTXGI-DDGI>.
- Teuber, Maurice et al. (2024). “Geometry-Based Optimization of Light Probe Placement in Virtual Environments”. In: *2024 International Conference on Cyberworlds (CW)*, pp. 9–16. DOI: [10.1109/CW64301.2024.00011](https://doi.org/10.1109/CW64301.2024.00011).
- Unity (2025). *Adaptive Probe Volumes*. URL: <https://docs.unity3d.com/Packages/com.unity.render-pipelines.high-definition@17.0/manual/probevolumes-concept.html>.

- Vardis, Konstantinos, Andreas Vasilakis, and Georgios Papaioannou (May 2021). “Illumination-driven Light Probe Placement”. In: DOI: [10.2312/egp.20211026](https://doi.org/10.2312/egp.20211026).
- Veach, Eric and Leonidas J. Guibas (1997). “Metropolis light transport”. In: *Proceedings of the 24th Annual Conference on Computer Graphics and Interactive Techniques*. SIGGRAPH '97. USA: ACM Press/Addison-Wesley Publishing Co., 65–76. ISBN: 0897918967. DOI: [10.1145/258734.258775](https://doi.org/10.1145/258734.258775). URL: <https://doi.org/10.1145/258734.258775>.
- Wang, Yue et al. (2019). “Fast non-uniform radiance probe placement and tracing”. In: *Proceedings of the ACM SIGGRAPH Symposium on Interactive 3D Graphics and Games*. ACM, p. 5.
- Wikipedia contributors (2025). *Lightmap* — *Wikipedia, The Free Encyclopedia*. [Online; accessed 15-June-2025]. URL: <https://en.wikipedia.org/w/index.php?title=Lightmap&oldid=1285782125>.
- Xu, Yang et al. (2022). “Precomputed Discrete Visibility Fields for Real-Time Ray-Traced Environment Lighting.” In: *EGSR (ST)*, pp. 81–92. ISBN: 978-3-03868-187-8. DOI: [10.2312/sr.20221158](https://doi.org/10.2312/sr.20221158).
- You, Zinuo, Andreas Geiger, and Anpei Chen (2024). *NeLF-Pro: Neural Light Field Probes for Multi-Scale Novel View Synthesis*. arXiv: [2312.13328](https://arxiv.org/abs/2312.13328) [cs.CV]. URL: <https://arxiv.org/abs/2312.13328>.