Author: Andreas Traut
Date: 08.05.2020 (Updates 24.07.2020)
Download as PDF

Machine Learning with Python

- 0. Introduction
  - a) Aim of this repository
  - b) Motivation for IDEs
  - c) Structure of this repository
    - (i) First part
    - (ii) Second part
    - (iii) Third part
  - d) Future learnings and coding & data sources
- 1. Movies Database Example
- 2. Step-by-step Python-Code for Machine Learning using "scikit-learn"
  - 1. create index
    - 1.1 Alternative 1: generate id with static data
    - 1.2 Alternative 2: generate stratified sampling
    - 1.3 verify if stratified example is good
  - 2. Discover and visualize the data to gain insights
  - 3. prepare for Machine Learning
    - 3.1 find all NULL-values
    - 3.2 remove all NULL-values
  - 4. Use "Imputer" to clean NaNs
  - 5. treat "categorial" inputs
  - 6. custom transformer and pipelines
    - 6.1 custom transformer
    - 6.2 pipelines
  - 7. select and train model
    - 7.1 LinearRegression model
    - 7.2 DecisionTreeRegressor model
  - 8. crossvalidation
    - 8.1 for DecisionTreeRegressor
    - 8.2 for LinearRegression
    - 8.3 for RandomForestRegressor
    - 8.4 for ExtraTreesRegressor
  - 9. Save Model
  - 10. Optimize Model
    - 10.1 GridSearchCV
      - 10.1.1 GridSearchCV on RandomForestRegressor
      - 10.1.2 GridSearchCV on LinearRegressor
    - 10.2 Randomized Search
    - 10.3 Analyze best models
  - 11. Evaluate final model on test dataset
- 3. Step-by-step Python-Code for Machine Learning using "Apache Machine-Learning" Libary (Big Data)
  - 0. Initialize Spark
    - 0.1 Create Spark Context and Spark Session
    - 0.2 Read CSV
    - 0.3 Dataset Properties and some Select, Group and Aggregate Methods
    - 0.4 Write as Parquet or CSV
    - 0.5 Read Parquet
    - 0.6 How to stop a Spark Session and Spark Context
  - 1. Cleaning the data
    - 1.1 Show number of rows and columns and do some visualizations
    - 1.2 Replacing and Casting

1.3 Null-Values
1.4 String Values
2. Model-specific preprocessing
2.0 Check missing entries and define userdefined scatter plot
2.1 StringIndexer
2.2 OntHotEncoder
2.3 VectorAssembler
2.4 CountVectorizer
3. Aligning and numerating Features and Labels
3.1 Aligning
3.2 Numerating
4. Pipelines
5. Training data and Testing data
6. Apply models and evaluate
6.1 Ordinary Least Square Regression
6.2 Ridge Regression
6.3 Lasso Regression
6.4 Decision Tree
7. Minhash und Local-Sensitive-Hashing (LSH)
8. Alternative-Least-Square (ALS)
8.1. Datapreparation for ALS
8.2 Build the recommendation model using alternating least squares (ALS)
8.3 Get recommendations
8.4 Clustering of Users with K-Means
8.5 Perform a PCA and draw the 2-dim projection

MIT License

Machine Learning with Python

0. Introduction

a) Aim of this repository

After having learnt visualization techniques in Python (which I showed in my repository "Visualization-of-Data-with-Python", see https://github.com/AndreasTraut/Visualization-of-Data-with-Python) I started working on different datasets with the aim to apply machine learning algorithms (e.g. Decision Tree to name only one).

In my *first example* in this repository here I will use Jupyter-Notebooks, which is a widespread standard today. The first Jupyter-Notebooks have been developed 5 years ago (in 2015). Since my first programming experience was more than 25 years ago (I started with GW-Basic then Turbo-Pascal and so on...) I quickly learnt the advantages of using Jupyter-Notebooks.

But I missed the comfort of an IDE from the very first days!

Therefore: in my examples in this repository here I will also work with Python ".py" files. These ".py" can be executed in an IDE, like e.g. Spyder-IDE (see https://www.spyder-ide.org/)



b) Motivation for IDEs

Why is it important for me to mention the IDEs out so early in a learning process? In my opinion Jupyter-Notebooks are good for the first examinations of data and for documenting procedures and up to a certain degree also for sophisticated data science. But it might be a good idea to learn very early how to work with an IDE. Think about how to use what has been developed so far later in a bigger environment (for example a Lambda-Architecture, but you can take whatever other environment, which requires robustness&stability). I point this out here, because after having read several e-Books and having participated in seminars I see that IDEs are not in the focus.

c) Structure of this repository

(i) First part

Therefore the *first example* uses a Jupyter-Noteook in order to learn the standard procedures (e.g. data-cleaning&preparing, model-training,...).

(ii) Second part

The *second example* is for being used in an IDE. It will use the "Scikit-Learn" python machine learning library (you may call it "SmallData" if you want).

(iii) Third part

The *third example* is a "Big Data" example and will use the "Apache MLib" scalable machine learning library. Here I also show some Big Data Visualizations and the K-Means Clustering Algorithm.

d) Future learnings and coding & data sources

For all of these topics various tutorials, documentation, coding examples and guidelines can be found in the internet **for free**! The Open Source Community is an incredible treasure trove and enrichment that positively drives many digital developments: Scikit-Learn, Apache Spark, Spyder, GitHub, Tensorflow and also Firefox, Signal, Threema, ... to be mentionned. There are many positive examples of sharing code and data "for free".

Coding:

If you google for example *"how to prepare and clean the data with spark"*, you will find tons of documents around *removing null values* or *encoders* (like the OneHotEncoder for treating categorial inputs) or *pipelines* (for putting all the steps in an efficient, customizable order) so on. You will be overwhelmed of all this. What I will do here is nothing more than putting it together so that it works for my problem. Adapting it for your needs should be easier from this point on.

Data:

If you would like to do further analysis or produce alternate visualisations of the Airbnb-data, you can download them from here. It is available below under a Creative Commons CC0 1.0 Universal (CC0 1.0) "Public Domain Dedication" license. The data for the Vermont-Vendor-Payments can be downloaded from here and are available under the Open Data Commons Open Database License. The movies database doesn't even mention a licence and is from Kaggle. There you find a lot of more datasets and also coding examples for your studies.

1. Movies Database Example

A good starting point for finding useful datasets is "Kaggle" (www.kaggle.com). I downloaded the movies dataset from here. The dataset from Kaggle contains the following columns:

Rank | Title | Year | Score | Metascore | Genre | Vote | Director | Runtime | **Revenue** | Description | RevCat

In this example I want to predict the **"Revenue"** based on the other information, which I have for each movie (e.g. every movie has a year, a scoring, a title ...). There are some "NaN"-values in the column "Revenue" and instead of filling them with an assumption (e.g. median-value) as I did in another Jupiter-Notebook (see here), I wanted to predict these values. You might guess the conclusion already: predicting the revenue based on the available information as shown above (the columns) might not work. But essential to me is more to follow a well established standard-process of data-cleaning, data-preparing, model-training and error-calculation in this example in order to learn how to apply this process to better datasets, than the movies-dataset, later.

Therefore, here is how I approached the problem step-by-step:

- I separated the rows with "NaN"-values in column "Revenue"

These are the datarows, where column "Revenue" is null:

```
In [10]: movies_RevenueNaN = movies[movies["Revenue"].isnull()]
         movies_RevenueNaN.head()
```

Out[10]:

	Rank	Title	Year	Score	Metascore	Genre	Vote	Director	Runtime	Revenue	Description
82	83	A Clockwork Orange	1971	8.3	80.0	Crime, Drama, Sci-Fi	662768	Stanley Kubrick	136	NaN	In the future, a sadistic gang leader is impri...
513	514	To Kill a Mockingbird	1962	8.3	87.0	Crime, Drama	262064	Robert Mulligan	129	NaN	Atticus Finch, a lawyer in the Depression-era ...
581	582	Death Proof	2007	7.0	NaN	Action, Thriller	236539	Quentin Tarantino	113	NaN	Two separate sets of voluptuous women are stal...
620	621	My Neighbour Totoro	1988	8.2	86.0	Animation, Family, Fantasy	226126	Hayao Miyazaki	86	NaN	When two girls move to the country to be near ...
685	686	Hachi: A Dog's Tale	2009	8.1	NaN	Drama, Family	212349	Lasse Hallström	93	NaN	A college professor's bond with the abandoned ...

```
In [11]: len_movies_RevenueNaN = len(movies_RevenueNaN)
         len_movies_RevenueNaN
```

Out[11]: 2527

- I drew a stratified sample (based on "Revenue") on this remaining dataset and I received a training dataset and testing dataset:

```
In [24]: split = StratifiedShuffleSplit(n_splits=1, test_size=0.9, random_state=42)
         for train_index, test_index in split.split(movies_NotNullC, movies_NotNullC["RevCat"]):
             strat_train_set = movies_NotNullC.iloc[train_index]
             strat_test_set = movies_NotNullC.iloc[test_index]
```

```
In [25]: strat_test_set["RevCat"].value_counts() / len(strat_test_set)

Out[25]: 1    0.903657
         2    0.069878
         3    0.016057
         4    0.010407
         Name: RevCat, dtype: float64
```

```
In [26]: movies_NotNullC["RevCat"].value_counts() / len(movies_NotNullC)

Out[26]: 1    0.903653
         2    0.069851
         3    0.016058
         4    0.010438
         Name: RevCat, dtype: float64
```



- I created a pipeline to fill the "NaN"-value in other columns (e.g. "Metascore", "Score").

```
In [38]: num_pipeline = Pipeline([
             ('imputer', SimpleImputer(strategy='median')),
         ])

         num_attribs = ['Rank', 'Year', 'Score', 'Metascore', 'Vote', 'Runtime']

         full_pipeline = ColumnTransformer([
             ('num', num_pipeline, num_attribs)
         ])
```

Now apply the Pipeline:

```
In [40]: movies_train_prepared = full_pipeline.fit_transform(movies_train)
```

Now let's count the "nan" values in the new prepared datast "movies_train_prepared". I have to transform it back to a Pandas-Dataframe format first:

```
In [41]: tmp_num = movies_train.select_dtypes(include=[np.number])
         tmp_prep = pd.DataFrame(movies_train_prepared, columns=tmp_num.columns,index=movies_train.index)
         tmp = tmp_prep[tmp_prep["Metascore"].isnull()]
         tmp

Out[41]:
```

Rank	Year	Score	Metascore	Vote	Runtime

Zero, as we wanted! All "nan"-values in "movies_train_prepared" have been removed by the "median" value (this was how the pipeline was built). Great,

- used the training dataset and fittet it with the "DecisionTreeRegressor" model

```
In [42]: tree_reg = DecisionTreeRegressor(random_state=42)
         tree_reg.fit(movies_train_prepared, movies_train_labels)

         movies_predictions = tree_reg.predict(movies_train_prepared)
```

- verified with a cross-validation, how good this model/parameters are

```
In [46]: scores = cross_val_score(tree_reg,
                                  movies_train_prepared,
                                  movies_train_labels,
                                  scoring="neg_mean_squared_error",
                                  cv=10)

         rmse_scores = np.sqrt(-scores)

         def display_scores(scores):
             print("Scores:", scores)
             print("Mean:", scores.mean())
             print("Standard deviation:", scores.std())

         display_scores(rmse_scores)

         Scores: [ 69.66166984  62.59977724  62.6450061  112.98391756  47.99491086
           52.16787811  42.65104005  83.21059338  41.09199207  63.84158945]
         Mean: 63.88483746577791
         Standard deviation: 20.447326452253154
```

- did a prediction on a subset of the testing dataset and did a side-by-side comparison of prediction and true value

```
In [53]: side_by_side = [(true, pred) for true, pred in zip(list(some_data_label), list(some_data_predictions))]
         side_by_side

Out[53]: [(5.78, 10.91),
          (0.05, 0.44),
          (0.3, 2.68),
          (159.6, 11.99),
          (33.63, 2.19),
          (44.9, 26.83),
          (38.52, 22.52),
          (33.04, 2.19),
          (3.2, 11.99),
          (37.49, 16.38),
          (17.88, 64.19),
          (41.19, 191.45),
          (16.19, 12.19),
          (0.05, 3.02),
          (16.68, 64.19),
          (35.11, 11.54),
          (36.0, 40.22),
          (3.61, 19.64),
          (0.59, 0.05),
          (0.99, 5.48)]
```

- performed a prediction on the testing dataset and calculated the mean-squared error

```
In [55]: movies_test_prepared =full_pipeline.fit_transform(movies_test)
         movies_test_predictions = tree_reg.predict(movies_test_prepared)
         lin_mse = mean_squared_error(movies_test_labels, movies_test_predictions)
         lin_rmse = np.sqrt(lin_mse)
         lin_rmse

Out[55]: 54.68522284077671
```

The conclusion of this machine learning example is obvious: it is rather not possible to predict the "Revenue" based on the available information (the most useful numerical features were "year", "score", ... and the other categorical like "genre" don't seem to have much more added value in my opinion).

Please find the complete Jupyter Notebook here:

https://github.com/AndreasTraut/Machine-Learning-with-Python/blob/master/Movies%20Machine%20Learning%20-%20Predict%20NaNs.ipynb

If you want to run the code immediately without installing the required "Jupyter environment" then you can use this Deepnote-Link:

https://beta.deepnote.com/project/754094f0-3c01-4c29-b2f3-e07f507da460

2. Step-by-step Python-Code for Machine Learning using "scikit-learn"

As said above, the *second example* is for being used in an IDE. If will use the "Scikit-Learn" python machine learning library. As Jupyter Notebooks are not always the best environment for Python coding (e.g. Debugging), I extracted the most essential parts of Chapter 2 of Aurelien Geron "Machine Learning with Scikit-Learn & Tensorflow", sorted and arranged the code fragments slightly and created the following structured Python code for being used for example in the Spyder-IDE. The structure of the Python code is a bit similar to the steps, which I followed in the Jupyter Notebooks above and are as follows (you will find these sections also in the ".py" file). Let's start with the "scikit-learn" ("SmallData", if you want):



1. create index

1.1 Alternative 1: generate id with static data

```
# 1.1 Alternative 1: generate id with static data
housing_with_id["id"] = housing["longitude"] * 1000 + housing["latitude"]
train_set, test_set = split_train_test_by_id(housing_with_id, 0.2, "id")
```

1.2 Alternative 2: generate stratified sampling

```
# from sklearn.model_selection import StratifiedShuffleSplit
split = StratifiedShuffleSplit(n_splits=1, test_size=0.2, random_state=42)
for train_index, test_index in split.split(housing, housing["income_cat"]):
    strat_train_set = housing.loc[train_index]
    strat_test_set = housing.loc[test_index]
```

1.3 verify if stratified example is good

```
compare_props["Rand. %error"] = 100 * compare_props["Random"] / compare_props["Overall"] - 100
compare_props["Strat. %error"] = 100 * compare_props["Stratified"] / compare_props["Overall"] - 100
```

2. Discover and visualize the data to gain insights

```
# from pandas.plotting import scatter_matrix
attributes = ["median_house_value", "median_income", "total_rooms",
              "housing_median_age"]
scatter_matrix(housing[attributes], figsize=(12, 8))
plt.suptitle("scatter_matrix_plot")
save_fig("scatter_matrix_plot")
```

3. prepare for Machine Learning

3.1 find all NULL-values

```
print("Are there nans in column total_bedrooms?\n", housing["total_bedrooms"].isnull().any())
print("Show rows with nan:\n", housing[housing["total_bedrooms"].isnull()])
```

3.2 remove all NULL-values

```
sample_incomplete_rows = housing[housing.isnull().any(axis=1)].head()
# sample_incomplete_rows.dropna(subset=["total_bedrooms"])    # option 1
# sample_incomplete_rows.drop("total_bedrooms", axis=1)       # option 2

median = housing["total_bedrooms"].median()
sample_incomplete_rows["total_bedrooms"].fillna(median, inplace=True) # option 3
```

4. Use "Imputer" to clean NaNs

```
imputer = SimpleImputer(strategy="median")
# Remove all text attributes because median can only be calculated on numerical attributes:
housing_num = housing.select_dtypes(include=[np.number])
imputer.fit(housing_num)
print("imputer.strategy\n", imputer.strategy)
print("imputer.statistics_\n", imputer.statistics_)
print("housing_num.median\n", housing_num.median().values)  # <- Check that this is the same as \
                                                             # manually computing the median of \
                                                             # each attribute
print("housing_num.mean\n", housing_num.mean().values)       # <- Check that this is the same as \
                                                             # manually computing the median of \
                                                             # each attribute
X = imputer.transform(housing_num) # Transform the training set:
housing_tr = pd.DataFrame(X, columns=housing_num.columns,
                          index=housing.index)
```

5. treat "categorial" inputs

```
cat_encoder = OneHotEncoder()
housing_cat_1hot = cat_encoder.fit_transform(housing_cat)
```

6. custom transformer and pipelines

6.1 custom transformer

```python
def add_extra_features(X, add_bedrooms_per_room=True):
    rooms_per_household = X[:, rooms_ix] / X[:, household_ix]
    population_per_household = X[:, population_ix] / X[:, household_ix]
    if add_bedrooms_per_room:
        bedrooms_per_room = X[:, bedrooms_ix] / X[:, rooms_ix]
        return np.c_[X, rooms_per_household, population_per_household,
                     bedrooms_per_room]
    else:
        return np.c_[X, rooms_per_household, population_per_household]

# from sklearn.preprocessing import FunctionTransformer
attr_adder = FunctionTransformer(add_extra_features, validate=False,
                                 kw_args={"add_bedrooms_per_room": False})
housing_extra_attribs = attr_adder.fit_transform(housing.values)

housing_extra_attribs = pd.DataFrame(
    housing_extra_attribs,
    columns=list(housing.columns)+["rooms_per_household", "population_per_household"],
    index=housing.index)
print("housing_extra_attribs.head()\n", housing_extra_attribs.head())
```

6.2 pipelines

```python
num_pipeline = Pipeline([
        ('imputer', SimpleImputer(strategy="median")),
        ('attribs_adder', FunctionTransformer(add_extra_features,
                                              validate=False)),
        ('std_scaler', StandardScaler()),
    ])
housing_num_tr = num_pipeline.fit_transform(housing_num)
print("housing_num_tr\n", housing_num_tr)

try:
    from sklearn.compose import ColumnTransformer
except ImportError:
    from future_encoders import ColumnTransformer # Scikit-Learn < 0.20

num_attribs = list(housing_num)
cat_attribs = ["ocean_proximity"]

full_pipeline = ColumnTransformer([
        ("num", num_pipeline, num_attribs),
        ("cat", OneHotEncoder(), cat_attribs),
    ])
housing_prepared = full_pipeline.fit_transform(housing)
print("housing_prepared\n", housing_prepared)
```

7. select and train model

7.1 LinearRegression model

```python
# from sklearn.linear_model import LinearRegression
lin_reg = LinearRegression()
lin_reg.fit(housing_prepared, housing_labels)
# let's try the full preprocessing pipeline on a few training instances
some_data = housing.iloc[:1]
some_labels = housing_labels.iloc[:1]
some_data_prepared = full_pipeline.transform(some_data)
print("Predictions:\n", lin_reg.predict(some_data_prepared))
print("Labels:\n", list(some_labels)) # Compare against the actual values:

# from sklearn.metrics import mean_squared_error
housing_predictions = lin_reg.predict(housing_prepared)
lin_mse = mean_squared_error(housing_labels, housing_predictions)
lin_rmse = np.sqrt(lin_mse)
print("lin_rmse\n", lin_rmse)
```

7.2 DecisionTreeRegressor model

```
# from sklearn.tree import DecisionTreeRegressor
tree_reg = DecisionTreeRegressor(random_state=42)
tree_reg.fit(housing_prepared, housing_labels)
housing_predictions = tree_reg.predict(housing_prepared)

tree_mse = mean_squared_error(housing_labels, housing_predictions)
tree_rmse = np.sqrt(tree_mse)
print("tree_rmse\n", tree_rmse)
```

8. crossvalidation

8.1 for DecisionTreeRegressor

```
# from sklearn.model_selection import cross_val_score
scores = cross_val_score(tree_reg, housing_prepared, housing_labels,
                         scoring="neg_mean_squared_error", cv=10)
```

8.2 for LinearRegression

```
lin_scores = cross_val_score(lin_reg, housing_prepared, housing_labels,
                             scoring="neg_mean_squared_error", cv=10)
```

8.3 for RandomForestRegressor

```
# from sklearn.ensemble import RandomForestRegressor
forest_reg = RandomForestRegressor(n_estimators=10, random_state=42)
forest_reg.fit(housing_prepared, housing_labels)

housing_predictions = forest_reg.predict(housing_prepared)
forest_mse = mean_squared_error(housing_labels, housing_predictions)
forest_rmse = np.sqrt(forest_mse)
print(forest_rmse)
# from sklearn.model_selection import cross_val_score
forest_scores = cross_val_score(forest_reg, housing_prepared, housing_labels,
                                scoring="neg_mean_squared_error", cv=10)
forest_rmse_scores = np.sqrt(-forest_scores)
display_scores(forest_rmse_scores)
```

8.4 for ExtraTreesRegressor

```
from sklearn.ensemble import ExtraTreesRegressor
extratree_reg = ExtraTreesRegressor(n_estimators=10, random_state=42)
extratree_reg.fit(housing_prepared, housing_labels)

housing_predictions = extratree_reg.predict(housing_prepared)
extratree_mse = mean_squared_error(housing_labels, housing_predictions)
extratree_rmse = np.sqrt(extratree_mse)
print(extratree_rmse)
extratree_scores = cross_val_score(extratree_reg, housing_prepared,
                                   housing_labels,
                                   scoring = "neg_mean_squared_error", cv=10)
extratree_rmse_scores = np.sqrt(-extratree_scores)
display_scores(extratree_rmse_scores)
```

9. Save Model

```
# from sklearn.externals import joblib
joblib.dump(forest_reg, "forest_reg.pkl")
# und später zum Laden des Modells...
my_model_loaded = joblib.load("forest_reg.pkl")
```

10. Optimize Model

10.1 GridSearchCV

10.1.1 GridSearchCV on RandomForestRegressor

```
# from sklearn.model_selection import GridSearchCV
param_grid = [
    # try 12 (3×4) combinations of hyperparameters
    {'n_estimators': [30, 40, 50], 'max_features': [2, 4, 6, 8, 10]},
    # then try 6 (2×3) combinations with bootstrap set as False
    {'bootstrap': [False], 'n_estimators': [3, 10], 'max_features': [2, 3, 4]},
  ]

forest_reg = RandomForestRegressor(random_state=42)
# train across 5 folds, that's a total of (12+6)*5=90 rounds of training
grid_search = GridSearchCV(forest_reg, param_grid, cv=5,
                           scoring='neg_mean_squared_error',
                           return_train_score=True)
grid_search.fit(housing_prepared, housing_labels)
print(grid_search.best_params_)
print(grid_search.best_estimator_)
cvres = grid_search.cv_results_
for mean_score, params in zip(cvres["mean_test_score"], cvres["params"]):
    print(np.sqrt(-mean_score), params)
```

10.1.2 GridSearchCV on LinearRegressor

```
# from sklearn.model_selection import GridSearchCV
param_grid = [
    # try 12 (3×4) combinations of hyperparameters
    {'fit_intercept': [True], 'n_jobs': [2, 4, 6, 8, 10]},
    # then try 6 (2×3) combinations with bootstrap set as False
    {'normalize': [False], 'n_jobs': [3, 10]},
  ]

lin_reg = LinearRegression()
# train across 5 folds, that's a total of (12+6)*5=90 rounds of training
lin_grid_search = GridSearchCV(lin_reg, param_grid, cv=5,
                           scoring='neg_mean_squared_error',
                           return_train_score=True)
lin_grid_search.fit(housing_prepared, housing_labels)
# print(lin_grid_search.best_params_)
print(lin_grid_search.best_estimator_)
cvres = lin_grid_search.cv_results_
for mean_score, params in zip(cvres["mean_test_score"], cvres["params"]):
    print(np.sqrt(-mean_score), params)
```

10.2 Randomized Search

```
# from sklearn.model_selection import RandomizedSearchCV
# from scipy.stats import randint
param_distribs = {
        'n_estimators': randint(low=1, high=200),
        'max_features': randint(low=1, high=8),
    }

forest_reg = RandomForestRegressor(random_state=42)
rnd_search = RandomizedSearchCV(forest_reg,
                                param_distributions=param_distribs,
                                n_iter=10, cv=5,
                                scoring='neg_mean_squared_error',
                                random_state=42)
rnd_search.fit(housing_prepared, housing_labels)
cvres = rnd_search.cv_results_
for mean_score, params in zip(cvres["mean_test_score"], cvres["params"]):
    print(np.sqrt(-mean_score), params)
```

10.3 Analyze best models

```
feature_importances = grid_search.best_estimator_.feature_importances_
feature_importances
extra_attribs = ["rooms_per_hhold", "pop_per_hhold", "bedrooms_per_room"]
cat_encoder = full_pipeline.named_transformers_["cat"]
cat_one_hot_attribs = list(cat_encoder.categories_[0])
attributes = num_attribs + extra_attribs + cat_one_hot_attribs
sorted(zip(feature_importances, attributes), reverse=True)
```

11. Evaluate final model on test dataset

```
final_model = grid_search.best_estimator_

X_test = strat_test_set.drop("median_house_value", axis=1)
y_test = strat_test_set["median_house_value"].copy()

X_test_prepared = full_pipeline.transform(X_test)
final_predictions = final_model.predict(X_test_prepared)

final_mse = mean_squared_error(y_test, final_predictions)
final_rmse = np.sqrt(final_mse)

print ("final_predictions\n", final_predictions )
print ("final_rmse \n", final_rmse )

confidence = 0.95
squared_errors = (final_predictions - y_test) ** 2
mean = squared_errors.mean()
m = len(squared_errors)

# from scipy import stats
print("95% confidence interval: ",
      np.sqrt(stats.t.interval(confidence, m - 1,
                               loc=np.mean(squared_errors),
                               scale=stats.sem(squared_errors)))
      )
```

3. Step-by-step Python-Code for Machine Learning using "Apache Machine-Learning" Libary (Big Data)

This will be an example for a "Big-Data" environment and uses the "Apache MLib" scalable machine learning library. Various tutorials, documentation, "code-fragments" and guidelines can be found in the internet **for free**.

Conerning "Big Data" I want to add the following: understanding the concept of "Big-Data" and how to differenciate "standard" machine learning from a "scalable" environment is not easy. I recommend a separate training. Some steps are a bit similar to "scikit-learn" (e.g. data-cleaning, preprocessing), but the technical environment for running the code is different and also the code itself is different.

Let's start with the structure, which I put into a mind map (you can download it from this repository).



There are differents ways to approach the Apache Spark and Hadoop environment: you can install it on your own computer (which I found rather difficult because of lack of userfriendly and easy understandable documentation). Or you can dive into a Cloud environment, like e.g. Microsoft Azure or Amazon EWS or Google Cloud and try to get a virtual machine up and running for your purposes. Have a look at my documentation, where I shared my experiences, which I had with Microsoft Azure here.

For the following explanation I decided to use Docker. What is Docker? Docker is "an open-source project that automates the deployment of software applications inside containers by providing an additional layer of abstraction and automation of OS-level virtualization on Linux." Learn from the Docker-Curriculum how it works. I found an container, which had Apache Spark Version 3.0.0 and Hadoop 3.2 installed and built my machine-learning code (using pyspark) on top of this container.

I shared my code and developments on Docker-Hub in the following repository here. After having installed the Docker application you will need to pull my "machine-learning-pyspark" image to your computer:

```
docker pull andreastraut/machine-learning-pyspark
```

Then open Windows Powershell and type the following:

```
docker run -dp 8888:8888 andreastraut/machine-learning-pyspark:latest
```



You will see in your Docker Dashborad that a container is running:



After having opened your browser (e.g. Firefox-Browser), navigate to "localhost:8888" (8888 is the port, which will be opened).



The folder "data" contains the datasets. If you would like to do further analysis or produce alternate visualisations of the Airbnb-data, you can download them from here. It is available below under a Creative Commons CC0 1.0 Universal (CC0 1.0) "Public Domain Dedication" license. The data for the Vermont-Vendor-Payments can be downloaded from here and are available under the Open Data Commons Open Database License.



Excurs to Big Data Visualization and K-Means Clustering Algorithm

You will see a Jupyter-Notebook (which contains the Machine-Learning Code) and a folder named "data" (which contains the raw-data and preprocessed data). As you can see: I also worked on a 298 MB big csv-file ("Vermont_Vendor_Payments.csv"), which I coulnd't open in Excel, because of the huge size. This file contains a list of all state of Vermont payments to vendors (Open Data Commons Licence) and has more than 1.6 million lines (exactly 1'648'466 lines). I already mentionned in my repository "Visualization-of-Data-with-Python", that the **visualization of big datasets** can be difficult when using "standard" office tools, like Excel. If you are not able to open such csv-files in Excel you have to find other solutions. One is to use PySpark which I will show you here. Another solution would have been to use the Excel built-in connection, PowerQuery or something similar, maybe Access or whatever, which is not the topic here, because we also want to be able to apply machine-learning algorithms from the Spark Machine Learning Library. And there are more benefits of using PySpark instead of Excel: it can handle distributed processing, it's a lot faster, you can use pipelines, it can read many file systems (not only csv), it can process real-time data.

Additionally I will work on this dataset to show how the **K-Means Clustering Algorithm** can be applied by using the Spark Marchine-Learning Libary.

When you open the Jupyter-Notebook, you will see, that Apache Spark Verison 3.0.0 and Hadoop Version 3.2 is installed:



Initializing a Spark sessions works with the following commands:

0. Initialize Spark

In [3]:
```
import pyspark
from pyspark.sql import SparkSession
from pyspark.sql import functions as F
```

0.1 Create Spark Context and Spark Sessio

In [4]:
```
sc = pyspark.SparkContext(appName='Spark Modelling Context')
```

In [5]:
```
spark = SparkSession.builder \
        .appName('Spark Modelling Session') \
        .config('spark.executor.memory','5g') \
        .config('spark.executor.cores','4') \
        .getOrCreate()
```

0.2 Read CSV

In [6]:
```
import os
datapath = os.environ['PWD']
filename = datapath + "/data/listings.csv"
#read in data from csv
data = spark.read.csv(path=filename,
                      sep=',',
                      encoding='utf-8',
                      header=True,
                      inferSchema=True)
```

After then the data-cleaning and data preparation (eliminating of null values, visualization techniques) work pretty similar to the "Small data" (Sklearn) approach. If you want to persist (=save) your intermediate you can do it as follows:

Persisting the preprocessed data

In [22]:
```
data.select(*data.columns[:]).write.format("parquet") \
.save("data/inputdata_preprocessed.parquet", mode='overwrite')

data.select(*data.columns[:]).write.csv('data/inputdata_preprocessed.csv', mode='overwrite', header='
```

In [23]:
```
filename = "data/inputdata_preprocessed.parquet"
data = spark.read.parquet(filename)
data.show(5)
```

```
+----+--------------------+-------+----------+--------------------+--------------------+--------+-
--------+---------------+-----+--------------+-----------------+-----------+-----------------+----
-------------------------+----------------+
|  id|                name|host_id| host_name| neighbourhood_group|       neighbourhood|latitude|l
ongitude|      room_type|price|minimum_nights|number_of_reviews|last_review|reviews_per_month|calc
ulated_host_listings_count|availability_365|
+----+--------------------+-------+----------+--------------------+--------------------+--------+-
--------+---------------+-----+--------------+-----------------+-----------+-----------------+----
-------------------------+----------------+
|3176|Fabulous Flat in ...|   3718|    Britta|              Pankow|Prenzlauer Berg S...|  52.535|
13.41758|Entire home/apt| 90.0|            62|              145| 2019-06-27|             1.11|
1.0|             140|
|3309|BerlinSpot Schöne...|   4108|      Jana|Tempelhof - Schön...|     Schöneberg-Nord|52.49885|
13.34906|   Private room| 28.0|             7|               27| 2019-05-31|             0.34|
1.0|             320|
|6883|Stylish East Side...|  16149|   Steffen|Friedrichshain-Kr...|Frankfurter Allee...|52.51171|
13.45477|Entire home/apt|125.0|             3|              133| 2020-02-16|             1.08|
1.0|               0|
|7071|BrightRoom with s...|  17391|BrightRoom|              Pankow|      Helmholtzplatz|52.54316|
13.41509|   Private room| 33.0|             1|              292| 2020-03-06|             2.27|
2.0|              45|
|9991|Geourgeous flat -...|  33852|   Philipp|              Pankow|Prenzlauer Berg S...|52.53303|
13.41605|Entire home/apt|180.0|             6|                8| 2020-01-04|             0.14|
1.0|               8|
+----+--------------------+-------+----------+--------------------+--------------------+--------+-
--------+---------------+-----+--------------+-----------------+-----------+-----------------+----
-------------------------+----------------+
only showing top 5 rows
```

I included some examples of how features can be extracted, transformed and selected in the Jupyter-Notebook. Just to mention a few here: the "StringIndexer", "OneHotEncoder" and "VectorAssembler" work as follows:

2.1 StringIndexer

In [25]:
```
data.select('neighbourhood_group').distinct().count()
```

Out[25]: 38

In [26]:
```
from pyspark.ml.feature import StringIndexer
neighbourhood_indexer = StringIndexer(inputCol='neighbourhood_group', outputCol='neighbourhood_group_
neighbourhood_indexer_model = neighbourhood_indexer.fit(data)
data = neighbourhood_indexer_model.transform(data)
```

In [27]:
```
data.groupby('neighbourhood_group').agg(F.collect_set('neighbourhood_group_index').alias('neighbourh
```

```
+--------------------+-------------------------+
| neighbourhood_group|neighbourhood_group_index|
+--------------------+-------------------------+
|Friedrichshain-Kr...|                    [0.0]|
|               Mitte|                    [1.0]|
|              Pankow|                    [2.0]|
|            Neukölln|                    [3.0]|
|Charlottenburg-Wilm.|                    [4.0]|
|Tempelhof - Schön...|                    [5.0]|
|         Lichtenberg|                    [6.0]|
|  Treptow - Köpenick|                    [7.0]|
|Steglitz - Zehlen...|                    [8.0]|
|       Reinickendorf|                    [9.0]|
|Marzahn - Hellers...|                   [10.0]|
|             Spandau|                   [11.0]|
| Downtown Apartments|                   [12.0]|
|Downtown Apartmen...|                   [13.0]|
|     Neue Kantstraße|                   [14.0]|
|      Alexanderplatz|                   [15.0]|
|Prenzlauer Berg Nord|                   [16.0]|
|     Alt-Lichtenberg|                   [17.0]|
|           Barstraße|                   [18.0]|
|Blankenfelde/Nied...|                   [19.0]|
|    Brunnenstr. Nord|                   [20.0]|
|Frankfurter Allee...|                   [21.0]|
|           Grunewald|                   [22.0]|
|      Kurfürstendamm|                   [23.0]|
|                Lisa|                   [24.0]|
```

2.2 OneHotEncoder

In [28]:
```
from pyspark.ml.feature import OneHotEncoder
one_hot_encoder = OneHotEncoder(
    inputCol = 'neighbourhood_group_index',
    outputCol = 'one_hot_neighbourhood_group',
    dropLast=False)
one_hot_encoder_model = one_hot_encoder.fit(data)
data = one_hot_encoder_model.transform(data)
```

2.3 VectorAssembler

In [29]:
```
from pyspark.ml.feature import VectorAssembler
data = data.withColumn('number_of_reviews', data['number_of_reviews'].cast('double'))
data.select('number_of_reviews').show()
```

```
+-----------------+
|number_of_reviews|
+-----------------+
|            145.0|
|             27.0|
|            133.0|
|            292.0|
|              8.0|
|             24.0|
|             48.0|
|            262.0|
|             86.0|
|             60.0|
|             86.0|
|            307.0|
|            130.0|
|             21.0|
|              5.0|
|            188.0|
|             31.0|
|             74.0|
|            296.0|
|             39.0|
+-----------------+
only showing top 20 rows
```

After having extracted, transformed and selected features you will want to apply some models, for example the "OLS Regression":

6. Apply models and evaluate

6.1 Ordinary Least Square Regression

In [38]:
```
from pyspark.ml.regression import LinearRegression
lr = LinearRegression(featuresCol='num_features', labelCol='label',maxIter=1000, fitIntercept=True)
```

In [39]:
```
lr_model = lr.fit(data_train)
lr_model.coefficients
```

Out[39]:
```
DenseVector([-0.4689])
```

In [40]:
```
pred = lr_model.transform(data_test)
```

To summarize the whole coding structure have a look at this mind-map and structure below:



0. Initialize Spark

0.1 Create Spark Context and Spark Session

0.2 Read CSV

0.3 Dataset Properties and some Select, Group and Aggregate Methods

0.4 Write as Parquet or CSV

0.5 Read Parquet

0.6 How to stop a Spark Session and Spark Context

1. Cleaning the data

1.1 Show number of rows and columns and do some visualizations

1.2 Replacing and Casting

1.3 Null-Values

1.4 String Values

2. Model-specific preprocessing

2.0 Check missing entries and define userdefined scatter plot

2.1 StringIndexer

2.2 OntHotEncoder

2.3 VectorAssembler

2.4 CountVectorizer

3. Aligning and numerating Features and Labels

3.1 Aligning

3.2 Numerating

4. Pipelines

5. Training data and Testing data

6. Apply models and evaluate

6.1 Ordinary Least Square Regression

6.2 Ridge Regression

6.3 Lasso Regression

6.4 Decision Tree

7. Minhash und Local-Sensitive-Hashing (LSH)

see: https://github.com/AndreasTraut/Deep_learning_explorations

8. Alternative-Least-Square (ALS)

8.1. Datapreparation for ALS

8.2 Build the recommendation model using alternating least squares (ALS)

8.3 Get recommendations

8.4 Clustering of Users with K-Means

see https://hub.docker.com/repository/docker/andreastraut/machine-learning-pyspark

8.5 Perform a PCA and draw the 2-dim projection

MIT License

Copyright (c) 2020 Andras Traut

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.