



SCHEMATIC

PJ-324A	PJ-324A-1	PJ-324A-2	PJ-324A-3

SPECIFICATION

1. Rating : DC 30V 0.5A ;
2. Contact resistance : $\leq 0.03\Omega$;
3. Insulation resistance : $100M\Omega$ (DC250V) ;
4. Withstand voltage : 500VAC ;
5. Insertion and extraction force : 3-20N ;
6. Life test : 5,000 cycles .

8	HOUSING	1	PA66/PBT	
7	COVER	1	PC	
6	AXIS SUPPORT	1	H59 BRASS	Ni-Plating
5	5#CONTACT	1	PHOSPHOR BRONZE	Cu-Sn-Plating
4	4#CONTACT	1	H62 BRASS	Cu-Sn-Plating
3	3#CONTACT	1	H62 BRASS	Cu-Sn-Plating
2	2#CONTACT	1	PHOSPHOR BRONZE	Cu-Sn-Plating
1	1#CONTACT	1	H62 BRASS	Cu-Sn-Plating
NO.	DESCRIPTION	QTY	MATERIAL	PLATING
UNIT: MM	TYPE:	MODEL NO:	PAPER NO:	PAGE 1 OF 1
	PHONE JACK	L-KLS1-TSJ3.5-024	TOLERANCE	SCALE
DESIGNER			±0.15	1
CHECK			±1.5*	3:1
APPROVED				



NINGBO KLS ELECTRONIC CO.,LTD.