



WCAG 2.1 Level AA Success Criteria

COMPLIANCE AUDIT

For www.flashscore.com | Verdict: **Non-compliant**

accessiBe is the web accessibility **market leader**, powering the accessibility of **tens-of-thousands** of websites, from **small businesses** to industry-leading **enterprises**.

This audit evaluates the adherence level of **www.flashscore.com** as of Wed Nov 23 2022, to the "Web Content Accessibility Guidelines" (WCAG) 2.1 level AA success criteria.

Below you'll find the results for dozens of tests that focus mainly on 3 categories: **screen-reader** adjustments (for blind users), **keyboard navigation** adjustments (for the motor impaired) and **UI, design, and readability** adjustments (for the vision impaired).

#	Requirement	Relevant	Successes	Failures	Score
1	Elements that behave as buttons but are built using other tags such as span, div, a or others, should include a "role" attribute that equals to "button".	Yes	6	1134	1%

Code snapshots of some successful elements

```
<div id="user-menu" role="button" tabindex="0" class="header__button header__button--user" ><svg class="header__icon header__icon--user"><use xlink:href="/res/_fs/image/13_symbols/action.svg#user"></use></svg><span class="header__text header__text--u...
```

```
<div role="button" tabindex="0" class="header__button" ><svg class="header__icon header__icon--menu"><use xlink:href="/res/_fs/image/13_symbols/action.svg#menu"></use></svg></div>
```

```
<button class="ot-link-btn onetrust-vendors-list-handler" > List of Partners (vendors) </button>
```

```
<button id="onetrust-accept-btn-handler" >I Accept</button>
```

```
<button id="onetrust-reject-all-handler" >Reject All</button>
```

```
<button id="onetrust-pc-btn-handler" >Show Purposes</button>
```

Code snapshots of some failed elements

```
<div id="search-window" class="header__button" ><span class="searchIcon"><div class="header__fakeHover"></div><svg class="search header__icon--search"><title>Search</title><use xlink:href="/res/_fs/build/action.803f661.svg#search"></use></svg></span>...
```

```
<div class="menuMinority__title" onclick="cjs.Api.loader.get('sportMenu').call(function(sportMenu) { sportMenu.toggleMinority() });" > <svg class="menuMinority__arrow"> <use xlink:href="/res/_fs/image/13_symbols/action.svg#dropdown"></use> </s...
```

```
<div class="filters__tab" ><div class="filters__text filters__text--long">LIVE Games</div><div class="filters__text filters__text--short">LIVE</div></div>
```

```
<div class="filters__tab" ><div class="filters__text filters__text--default">Odds</div></div>
```

```
<div class="filters__tab" ><div class="filters__text filters__text--default">Finished</div></div>
```

```
<div class="filters__tab" ><div class="filters__text filters__text--default">Scheduled</div></div>
```

```
<div class="calendar__navigation calendar__navigation--yesterday" title="Previous day" ><svg><use xlink:href="/res/_fs/image/13_symbols/action.svg#arrow"></use></svg></div>
```

```
<div class="calendar__datepicker " ><svg class="calendar__icon"><use xlink:href="/res/_fs/image/13_symbols/action.svg#calendar"></use></svg>23/11 We</div>
```

```
<div class="calendar__navigation calendar__navigation--tomorrow" title="Next day" ><svg><use xlink:href="/res/_fs/image/13_symbols/action.svg#arrow"></use></svg></div>
```

```
<span class="eventSubscriber eventSubscriber__star eventSubscriber__star-active" ><svg class="star-ico eventStar eventStar--active"><title></title><use xlink:href="/res/_fs/build/action.803f661.svg#star"></use></svg></span>
```

-
- 2 [Buttons should include text explaining their functionality, and if icons are used as buttons, a screen-reader only text or an "aria-label" attribute should be used for that description.](#)

Yes

719

421

63%

Code snapshots of some successful elements

```
<div id="search-window" class="header__button" ><span class="searchIcon">
<div class="header__fakeHover"></div><svg class="search header__icon--sea
rch"><title>Search</title><use xlink:href="/res/_fs/build/action.803f661.
svg#search"></use></svg></span>...
```

```
<div id="user-menu" role="button" tabindex="0" class="header__button head
er__button--user" ><svg class="header__icon header__icon--user"><use xlin
k:href="/res/_fs/image/13_symbols/action.svg#user"></use></svg><span clas
s="header__text header__text--u...
```

```
<div class="filters__tab" ><div class="filters__text filters__text--lon
g">LIVE Games</div><div class="filters__text filters__text--short">LIVE</
div></div>
```

```
<div class="filters__tab" ><div class="filters__text filters__text--defau
lt">Odds</div></div>
```

```
<div class="filters__tab" ><div class="filters__text filters__text--defau
lt">Finished</div></div>
```

```
<div class="filters__tab" ><div class="filters__text filters__text--defau
lt">Scheduled</div></div>
```

```
<div class="calendar__datepicker " ><svg class="calendar__icon"><use xlin
k:href="/res/_fs/image/13_symbols/action.svg#calendar"></use></svg>23/11
We</div>
```

```
<span class="event__title--name" title="World Cup" >World Cup</span>
```

```
<a href="#" class="event__info active" >Live Standings</a>
```

```
<div class="event__stage" ><div class="event__stage--block">Finished</div
></div>
```

Code snapshots of some failed elements

```
<div role="button" tabindex="0" class="header__button" ><svg class="heade
r__icon header__icon--menu"><use xlink:href="/res/_fs/image/13_symbols/ac
tion.svg#menu"></use></svg></div>
```

```
<div class="menuMinority__title" onclick="cjs.Api.loader.get('sportMenu').call(function(sportMenu) { sportMenu.toggleMinority() });" > <svg class="menuMinority__arrow" > <use xlink:href="/res/_fs/image/13_symbols/action.svg#dropdown"></use> </s...
```

```
<div class="calendar__navigation calendar__navigation--yesterday" title="Previous day" ><svg><use xlink:href="/res/_fs/image/13_symbols/action.svg#arrow"></use></svg></div>
```

```
<div class="calendar__navigation calendar__navigation--tomorrow" title="Next day" ><svg><use xlink:href="/res/_fs/image/13_symbols/action.svg#arrow"></use></svg></div>
```

```
<span class="eventSubscriber eventSubscriber__star eventSubscriber__star--active" ><svg class="star-ico eventStar eventStar--active"><title></title><use xlink:href="/res/_fs/build/action.803f661.svg#star"></use></svg></span>
```

```
<span class="event__expanderBlock" title="Hide all matches of this league!" ><svg class="arrow event__expander event__expander--open"><title></title><use xlink:href="/res/_fs/build/action.803f661.svg#arrow"></use></svg></span>
```

```
<div class="eventSubscriber eventSubscriber__star eventSubscriber__star--event " ><svg class="star-ico eventStar eventStar--live " ><title></title><use xlink:href="/res/_fs/build/action.803f661.svg#star"></use></svg></div>
```

```

```

```

```

```

```

used for that description.

Code snapshots of some successful elements

```
<a href="/" class="header__item--active header__item" > <svg class="header__itemIcon"> <use xlink:href="/res/_fs/image/13_symbols/sport.svg#live-table"></use> </svg> ...
```

```
<a href="/news/" class="header__item" > <svg class="header__itemIcon"> <use xlink:href="/res/_fs/image/13_symbols/sport.svg#news"></use> </svg> <div class="header__it...
```

```
<a href="/favorites/" class="menuTop__item menuTop__myfs" data-sport-count="0" title="Today's Matches: 0" > <svg class="menuTop__icon"> <use xlink:href="/res/_fs/image/13_symbols/action.svg#star"></use> </svg> <div class="menuTop__text">...
```

```
<a href="/" class="menuTop__item--active menuTop__item" data-sport-id="1" > <svg class="menuTop__icon"> <use xlink:href="/res/_fs/image/13_symbols/sport.svg#soccer"></use> </svg> <div class="menuTop__text">Football</div> </a>
```

```
<a href="/tennis/" class="menuTop__item" data-sport-id="2" > <svg class="menuTop__icon"> <use xlink:href="/res/_fs/image/13_symbols/sport.svg#tennis"></use> </svg> <div class="menuTop__text">Tennis</div> </a>
```

```
<a href="/basketball/" class="menuTop__item" data-sport-id="3" > <svg class="menuTop__icon"> <use xlink:href="/res/_fs/image/13_symbols/sport.svg#basketball"></use> </svg> <div class="menuTop__text">Basketball</div> </a>
```

```
<a href="/hockey/" class="menuTop__item" data-sport-id="4" > <svg class="menuTop__icon"> <use xlink:href="/res/_fs/image/13_symbols/sport.svg#hockey"></use> </svg> <div class="menuTop__text">Hockey</div> </a>
```

```
<a href="/golf/" class="menuTop__item" data-sport-id="23" > <svg class="menuTop__icon"> <use xlink:href="/res/_fs/image/13_symbols/sport.svg#golf"></use> </svg> <div class="menuTop__text">Golf</div> </a>
```

```
<a href="/baseball/" class="menuTop__item" data-sport-id="6" > <svg class="menuTop__icon"> <use xlink:href="/res/_fs/image/13_symbols/sport.svg#baseball"></use> </svg> <div class="menuTop__text">Baseball</div> </a>
```

```
<a href="/snooker/" class="menuTop__item" data-sport-id="15" > <svg class="menuTop__icon"> <use xlink:href="/res/_fs/image/13_symbols/sport.svg#snooker"></use> </svg> <div class="menuTop__text">Snooker</div> </a>
```

Code snapshots of some failed elements

```
<a class="header__logoWrapper" href="/" > <svg class="header__logo" preserveAspectRatio="xMinYMid meet" enable-background="new 0 0 615 100" height="100" viewBox="0 0 615 100" width="615" xmlns="http://www.w3.org/2000/svg"><g clip-rule="ev...
```

```
<a href="/mobile/" class="footer__mobileScreen" ></a>
```

4	Links that open in a new tab or a new window should either have an "aria-label" attribute or a screen-reader only element explaining to screen-readers that this opens in a new tab.	Yes	2	3	40%
---	--	-----	---	---	-----

Code snapshots of some successful elements

```
<a href="https://apps.apple.com/app/id766443283?mt=8" target="_blank" title="iPhone/iPad application" class="selfPromo__app selfPromo__app--ios">   <svg class="selfPromo__icon"> <use xlink:href="/res/_fs/image/13_symbols/social.svg#tw"></use> ...
```

```
<a href="https://instagram.com/flashscoreofficial" target="_blank" class="selfPromo__boxItem" > <svg class="selfPromo__icon"> <use xlink:href="/res/_fs/image/13_symbols/social.svg#in"></use>...
```

```
<a href="https://appgallery.huawei.com/app/C101497479?sharePrepath=ag" target="_blank" title="" class="selfPromo__app selfPromo__app--ios" > World Cup 2022, Football Live Scores, Latest Football Results, EPL, LaLiga, Serie A</h1>
```

6	HTML title elements (H1-6) should have texts. If images or links are used, they should include an alternative or screen-reader only text.	Yes	3	0	100%
---	---	-----	---	---	------

7	Elements that visually appear as titles but are coded with a non-heading HTML Tag should include a "role" attribute that equals to "heading" or have their tags fixed.	No	0	0	-
---	--	----	---	---	---

8	Title levels should not be skipped and should be built with consistent hierarchy. For example: you cannot have "h4" titles and "h2" titles without having "h3" titles.	Yes	Pass	-	100%
---	--	-----	------	---	------

9	Interactive elements such as links, buttons and form fields should all be navigable using the keyboard by either using a focusable element (a, button, input, etc.) or including the "tabindex" attribute that equals to "0".	No	2	1093	-
---	---	----	---	------	---

Code snapshots of some successful elements


```
<div id="user-menu" role="button" tabindex="0" class="header__button header__button--user" ><svg class="header__icon header__icon--user"><use xlink:href="/res/_fs/image/13_symbols/action.svg#user"></use></svg><span class="header__text header__text--u...
```

```
<div role="button" tabindex="0" class="header__button" ><svg class="header__icon header__icon--menu"><use xlink:href="/res/_fs/image/13_symbols/action.svg#menu"></use></svg></div>
```

Code snapshots of some failed elements

```
<div id="search-window" class="header__button" ><span class="searchIcon"><div class="header__fakeHover"></div><svg class="search header__icon--search"><title>Search</title><use xlink:href="/res/_fs/build/action.803f661.svg#search"></use></svg></span>...
```

```
<div class="menuMinority__title" onclick="cjs.Api.loader.get('sportMenu').call(function(sportMenu) { sportMenu.toggleMinority() });" > <svg class="menuMinority__arrow" > <use xlink:href="/res/_fs/image/13_symbols/action.svg#dropdown"></use> </s...
```

```
<div class="filters__tab" ><div class="filters__text filters__text--long">LIVE Games</div><div class="filters__text filters__text--short">LIVE</div></div>
```

```
<div class="filters__tab" ><div class="filters__text filters__text--default">Odds</div></div>
```

```
<div class="filters__tab" ><div class="filters__text filters__text--default">Finished</div></div>
```

```
<div class="filters__tab" ><div class="filters__text filters__text--default">Scheduled</div></div>
```

```
<div class="calendar__navigation calendar__navigation--yesterday" title="Previous day" ><svg><use xlink:href="/res/_fs/image/13_symbols/action.svg#arrow"></use></svg></div>
```

```
<div class="calendar__datepicker " ><svg class="calendar__icon"><use xlink:href="/res/_fs/image/13_symbols/action.svg#calendar"></use></svg>23/11 We</div>
```

```
<div class="calendar__navigation calendar__navigation--tomorrow" title="Next day" ><svg><use xlink:href="/res/_fs/image/13_symbols/action.svg#arrow"></use></svg></div>
```

```
<span class="eventSubscriber eventSubscriber__star eventSubscriber__star-active" ><svg class="star-ico eventStar eventStar--active"><title></title><use xlink:href="/res/_fs/build/action.803f661.svg#star"></use></svg></span>
```

10	Interactive elements that can be navigated using the keyboard should be surrounded by a visual outline whenever they are focused.	Yes	Pass	-	100%
11	Active popups should include an "aria-modal" attribute that equals to "true", and a "role" attribute that equals to "dialog", so screen-reader users know how to navigate within it.	No	0	0	-
12	Every page should include hidden links that by clicking on them (either using keyboard navigation or a screen-reader), the user will "skip" certain blocks directly to main landmarks such as main content, menu or footer.	No	Fail	-	-
13	Elements that are hidden using CSS manipulations (opacity, height, text-indent, off-canvas, etc.) should be wrapped inside an element with an "aria-hidden" attribute that equals to "false", or include it directly, and have it dynamically changed to "true" when they become visible.	No	0	0	-
14	Elements that are hidden using CSS manipulations (opacity, height, text-indent, off-canvas, etc.) should include a "tabindex" attribute that is below 0, and have it dynamically changed to 0 when they become visible.	No	0	0	-

15	Menus should either be built using the HTML5 "nav" element or include a "role" attribute that equals to "menu" or "navigation" to indicate a navigation landmark for screen-readers.	No	0	0	-
16	Menu items that have a dropdown menu include an "aria-haspopup" attribute that equals to "true".	No	0	0	-
17	Menu items that have a dropdown menu include an "aria-expanded" attribute that equals to "false" that changes to "true" and back when opening or closing the dropdown.	No	0	0	-
18	Images should have an alternative text description that describes both the objects and the embedded text that the image contains, using the "alt" attribute.	Yes	3	190	2%

Code snapshots of some successful elements

```

```

```

```

```

```

Code snapshots of some failed elements

```

```

```

```

```

```

```

```

```

```

```

```

```

```

```

```

```

```

```

```

-
- 19 [Background images that are not just for decoration purposes and should have the same treatment as standard images and include a "role" attribute that equals to "img" and an alternative text description in an "aria-label" attribute.](#)

No

Fail

-

-

Code snapshots of some failed elements

```
<div class="otPlaceholder"> <div class="skOT skOT--ot"> <div class="skOT__co"> <div class="skOT__ti"></div> <div class="skOT__te"></div> <div class="skOT__te"></div> <div class="skOT__te"></div> <div class="skOT__te"></div> </div>...
```

used as spacers, decorations or their purpose is already described by the content should include a "role" attribute that equals to "presentation" or "none".

Code snapshots of some successful elements

```
<span id="mlc-4ck3s9wd8c" ></span>
```

```
<span id="mlc-aks81bkdz" ></span>
```

```
<span ></span>
```

```
<svg xmlns="http://www.w3.org/2000/svg" xmlns:xlink="http://www.w3.org/1999/xlink" x="0px" y="0px" viewBox="0 -30 110 110" aria-hidden="true" ><path fill="#2e3644" d="M55.146,51.887L41.588,37.786c3.486-4.144,5.396-9.358,5.396-14.786c0-12.682-10.318-2...
```

```
<span class="ot-scrn-rdr" aria-atomic="true" aria-live="polite" ></span>
```

Code snapshots of some failed elements

```
<svg class="header__logo" preserveAspectRatio="xMinYMid meet" enable-background="new 0 0 615 100" height="100" viewBox="0 0 615 100" width="615" xmlns="http://www.w3.org/2000/svg" ><g clip-rule="evenodd" fill-rule="evenodd" ><g fill="#fff" ><path d="...
```

```
<svg class="header__itemIcon" > <use xlink:href="/res/_fs/image/13_symbols/sport.svg#live-table" ></use> </svg>
```

```
<svg class="header__itemIcon" > <use xlink:href="/res/_fs/image/13_symbols/sport.svg#news" ></use> </svg>
```

```
<svg class="header__icon header__icon--user" ><use xlink:href="/res/_fs/image/13_symbols/action.svg#user" ></use></svg>
```

```
<svg class="header__icon header__icon--menu" ><use xlink:href="/res/_fs/image/13_symbols/action.svg#menu" ></use></svg>
```

```
<svg class="menuTop__icon" > <use xlink:href="/res/_fs/image/13_symbols/a  
ction.svg#star" ></use> </svg>
```

```
<svg class="menuTop__icon" > <use xlink:href="/res/_fs/image/13_symbols/s  
port.svg#soccer" ></use> </svg>
```

```
<svg class="menuTop__icon" > <use xlink:href="/res/_fs/image/13_symbols/s  
port.svg#tennis" ></use> </svg>
```

```
<svg class="menuTop__icon" > <use xlink:href="/res/_fs/image/13_symbols/s  
port.svg#basketball" ></use> </svg>
```

```
<svg class="menuTop__icon" > <use xlink:href="/res/_fs/image/13_symbols/s  
port.svg#hockey" ></use> </svg>
```

21	Figure elements that are used to display images should have a "role" attribute that equals to "none" and the image provide itself should provide the description using an "alt" attribute.	No	0	0	-
22	Every "area" element of a "map" tag should be regarded as a standard image and receive an alternative text description using an "alt" attribute.	No	0	0	-
23	Small or hidden tracker pixel images (often used for analytics or marketing purposes) should include a "role" attribute that equals to "none" or "presentation" so they are excluded from screen-readers.	No	0	0	-
24	Form fields should either include an "aria-label" attribute or a connected LABEL element describing the requirement of the field (email, phone, name, etc.).	No	0	0	-

provide false information.

26	Required form fields should include an "aria-required" attribute that equals to "true" so blind users using screen-readers know their validation.	No	0	0	-
27	The validity status of every form element must be represented in the code at all times using the "aria-invalid" attributes and the "true/false" values, and change dynamically when the status changes.	No	0	0	-
28	aria-describedby and aria-labelledby attributes should be connected by ID to an element that either has text description or an "aria-label" attribute.	Yes	11	0	100%

Code snapshots of some successful elements

```
<div role="alertdialog" aria-describedby="onetrust-policy-text" aria-label="We Care About Your Privacy"><div class="ot-sdk-container"><div class="ot-sdk-row"><div id="onetrust-group-container" class="ot-sdk-columns ot-sdk-ten"><div class="banner_logo...
```

```
<div id="onetrust-pc-sdk" class="otPcTab ot-hide ot-fade-in" role="alertdialog" aria-modal="true" aria-describedby="ot-pc-desc" lang="en" aria-label="About Your Privacy" ><!-- pc header --><div class="ot-pc-header" role="presentation" ><!-- Header lo...
```

```
<div class="sg-b-f sg-b-bar" style=" position: fixed; bottom: 0; width: 100%; box-sizing: border-box; left: 0; z-index:100;" role="dialog" aria-label="request to take survey" aria-describedby="sg-d-h-desc"><div id="sg-d-h-desc" class="sg-d-h"><a clas...
```

```
<div class="ot-desc-cntr" id="ot-tab-desc" tabindex="0" role="tabpanel" aria-labelledby="ot-pvcy-hdr" ><h4 id="ot-pvcy-hdr" >Your Privacy</h4><p id="ot-pc-desc" class="ot-grp-desc" >We process your data to deliver content or advertisements and measu...
```

```
<input type="checkbox" name="ot-group-id-C0002" id="ot-group-id-C0002" aria-checked="true" role="switch" class="category-switch-handler" data-optanongroupid="C0002" checked="" aria-labelledby="ot-header-id-C0002" >
```

```
<input type="checkbox" name="ot-group-id-C0003" id="ot-group-id-C0003" aria-checked="true" role="switch" class="category-switch-handler" data-optanongroupid="C0003" checked="" aria-labelledby="ot-header-id-C0003" >
```

```
<input type="checkbox" name="ot-group-id-C0004" id="ot-group-id-C0004" aria-checked="true" role="switch" class="category-switch-handler" data-optanongroupid="C0004" checked="" aria-labelledby="ot-header-id-C0004" >
```

```
<input type="checkbox" name="ot-group-id-IABV2_1" id="ot-group-id-IABV2_1" aria-checked="false" role="switch" class="category-switch-handler" data-optanongroupid="IABV2_1" aria-labelledby="ot-header-id-IABV2_1" >
```

```
<input type="checkbox" name="ot-group-id-STACK42" id="ot-group-id-STACK42" aria-checked="false" role="switch" class="category-switch-handler" data-optanongroupid="STACK42" aria-labelledby="ot-header-id-STACK42" >
```

```
<input type="checkbox" name="ot-group-id-ISFV2_2" id="ot-group-id-ISFV2_2" aria-checked="false" role="switch" class="category-switch-handler" data-optanongroupid="ISFV2_2" aria-labelledby="ot-header-id-ISFV2_2" >
```

29	All forms should have a submission button that is built as an input type "submit" or a "button" element, or include a "role" tag that equals to "button". Buttons can be hidden if the form can be submitted using the Enter key.	No	0	0	-
30	Search forms should include a "role" tag that equals to "search" (or be wrapped by one) to indicate a search landmark for screen-readers.	No	0	0	-
31	The title tag of the HEAD section (also the title that appears in the browser tab and Search Engine result pages) should exist and describe the name of the current	Yes	Pass	-	100%

Code snapshots of some successful elements

```
<title>World Cup 2022, Football Live Scores, Latest Football Results | Fl  
ashscore.com</title>
```

32	The HTML tag should include a "lang" attribute that represents the main language of the webpage so screen-readers can calibrate on it for blind users.	Yes	Pass	-	100%
----	--	-----	------	---	------

Code snapshots of some successful elements

```
<html xmlns="http://www.w3.org/1999/xhtml" xml:lang="en" lang="en"><head>  
<meta http-equiv="content-type" content="text/html; charset=utf-8"> <meta  
http-equiv="X-UA-Compatible" content="IE=11"> <title>World Cup 2022, Foot  
ball Live Scores, Latest Foot...
```

33	The meta viewport tag should allow vision impaired users to pinch-zoom at least double the standard scaling using the user-scalable="yes" and maximum-scale={2 or higher} content strings.	Yes	Pass	-	100%
----	--	-----	------	---	------

Code snapshots of some successful elements

```
<meta name="viewport" content="width=device-width, initial-scale=1, minim  
al-ui">
```

34	Landmarks such as main content and footer should be built using their corresponding HTML5 element or include a description using an "aria-label" attribute and a "role" tag that equals to "contentinfo" or "main". Landmarks such as search and navigation are tested in other sections.	Yes	3	0	100%
----	---	-----	---	---	------

Code snapshots of some successful elements

```
<main class="container__liveTableWrapper sport_page" id="mc"><div id="box-over-content-a" class="boxOverContent--a" ><style > #box_over_content_3136 { --color-boxOverContent-1: #008357; --color-boxOverContent-2: #FFFFFF; -...
```

```
<footer class="footerContainer"> <div class="footerContainer__content"> <div class="selfPromo"> <div class="selfPromo__mainGroup"> <div class="selfPromo__box selfPromo__box--project"> <div class="selfPromo__boxTitle">Flash...
```

35	Font sizes should be at least 11px in size in order to stay readable in the majority of font families. This should be verified also when using dynamic units such as REM or percents.	No	0	2	-
----	---	----	---	---	---

Code snapshots of some successful elements

```
<div class="ads__text ads__text--h">Advertisement</div>
```

```
<p id="sg-b-t-desc" class="sg-b-t">We would love to get your opinion on your experience with our site with a short survey</p>
```

36	Letter spacing should not be set to below -1px in order to stay readable in the majority of font families. This should be verified also when using dynamic units such as REM or percents.	Yes	Pass	-	100%
----	---	-----	------	---	------

37	Elements that have texts should meet a minimum contrast ratio of 4.5:1 between their foreground (usually text color) and background color.	Yes	739	152	83%
----	--	-----	-----	-----	-----

Code snapshots of some successful elements

```
<h1>World Cup 2022, Football Live Scores, Latest Football Results, EPL, LaLiga, Serie A</h1>
```

```
<div class="header__itemText" data-tag="New">News</div>
```

```
<span class="header__text header__text--user">LOGIN</span>
```

```
<div class="menuTop__text">Favorites</div>
```

```
<div class="menuTop__text">Tennis</div>
```

```
<div class="menuTop__text">Basketball</div>
```

```
<div class="menuTop__text">Hockey</div>
```

```
<div class="menuTop__text">Golf</div>
```

```
<div class="menuTop__text">Baseball</div>
```

Code snapshots of some failed elements

```
<div class="menuTop__text">Football</div>
```

```
<div class="filters__text filters__text--short">All</div>
```

```
<div class="event__part event__part--home event__part--1" >(0)</div>
```

```
<div class="event__part event__part--away event__part--1" >(0)</div>
```

```
<div class="event__part event__part--home event__part--1" >(1)</div>
```

```
<div class="event__stage--block">11<span class="blink">&nbsp;</span></div>  
>
```

```
<div class="event__score event__score--home" >0</div>
```

```
<div class="event__score event__score--away" >0</div>
```

```
<div class="event__stage--block">40<span class="blink">&nbsp;</span></div>
```

```
<div class="event__score event__score--away" >2</div>
```

38	Carousels should include an "aria-label" attribute that equals to "carousel"/"slider" or something else that indicates the functionality, as well as be tagged as a landmark for screen-readers using a "role" tag that equals to "contentinfo".	No	0	0	-
39	Control elements such as next and previous icons should include an "aria-label" attribute or a screen-reader only text that explains the functionality to screen-readers.	No	0	0	-
40	A common accessibility mistake is to treat carousels as live regions using the "aria-live" attribute and the "polite" or the "assertive" values. Using this practice will cause screen-readers to cut and skip announcements.	No	0	0	-
41	Carousel pagination items (usually used as small dots at the bottom of the carousel) should indicate their functionality and slide number they control using an "aria-label" and a screen-reader only text.	No	0	0	-
42	Tables that are being used as layout structures should include a "role" attribute that equals to "presentation" to indicate to screen-readers that it is not really a table.	No	0	0	-

When a table isn't, set the needed table's
"role" attribute to "presentation".

44	Tables that are missing a THEAD row with TH elements, should include a "role" attribute that equals to "rowheader" on the TD elements of the TR that represents the visual table headings.	No	0	0	-
45	Visually deleted texts (often used to show a previous price of a sale) should include an "aria-label" attribute or a screen-reader only text that explains this is deleted text.	No	0	0	-
46	Breadcrumbs main element should include a "role" attribute that equals to "navigation" and an "aria-label" attribute that describes the functionality."	No	Fail	-	-

Code snapshots of some failed elements

```
<h2 class="breadcrumb breadcrumb--hidden" ><svg class="breadcrumb__icon"
><use xlink:href="/res/_fs/image/13_symbols/sport.svg#soccer" ></use></sv
g><a class="breadcrumb__link" href="/football/" >Football</a></h2>
```

47	Ratings/scores that are represented visually using stars, meters or other indicators should either have an "aria-label" attribute or a screen-reader only texts conveying the score/rate.	No	0	0	-
48	Making use of an accessibility interface helps to ensure that vision impaired users can adjust some of the UI and the design (font-size, colors, spacing, etc.) to their needs. It is not a compliance requirement, but can help to improve compliance.	No	0	0	-
49	Iframe elements should include a "title" or an "aria-label" attribute explaining the	No	0	0	-

screen-readers if irrelevant.