Package 'PTC'

October 27, 2026

Type Package

Title Pseudo-temporal Causality Approach

Version 1.1.2

Description PTC package provides tools to find miRNA-mRNA causal regulatory relationships during biological processes. Causal inference is made by assuming a linear dependence model between the predictors (miRNAs) and a target mRNA (response variable). This model is assumed invariant throughout the whole process.
The model is created from gene expression sequential data. PTC transforms static gene expression datasets to sequential data (via a Pseudotime analysis). PTC identifies causal regulatory relationships by testing violations to the invariance property (Peters et al., 2015; Pfister et al., 2018) for those sets that contain only miRNAs that biologically can interact with each target gene.

License GPL-3

Encoding UTF-8

LazyData true

LazyDataCompression xz

Depends R (>= 3.6.1)

Imports miRBaseConverter,
stats,
utils

RoxygenNote 7.3.1

R topics documented:

Confirmed.fromList 2
Confirmed.fromMatrix 3
Extract.Parents 4
getDatabyMAD 5
GroundT 6
InterList.toMatrix 7
InterMatrix.toList 8
PTC 9

PTC.findPP 11
PTC.GeneSel 12
PTC.miRv21 13
PTC.ptime 14
PTC.RankByContext 15
PTC.TestInvariance 16
SC_miRNAsdata 17
SC_mRNAsdata 18
TCGA_BRCAdata 18
TS7.0_Conserved_Site_Context_Scores 19
TScan 19
wandTime 20

Index **21**

`Confirmed.fromList` *Confirmed.fromList*

Description

Returns a `list` with all experimentally confirmed interactions inferred by PTC.

Usage

```
Confirmed.fromList(InterList, GroundT)
```

Arguments

`InterList`	A `list` where each element has the following structure: • `name`: mRNA name. • `data`: Names of the miRNAs inferred as parents
`GroundT`	A `list` where each element has the following structure: • `name`: mRNA name. • `data`: Names of the miRNAs whose interactions with the mRNA have been experimentally confirmed.

Value

A `list` where each element has the following structure:

`name`	Name of a mRNA inferred by PTC with at least one confirmed interaction.
`data`	Names of the miRNAs whose miRNA-mRNA interactions are in the `GroundT`.

See Also

PTC, GroundT

Examples

```
## Not run:
data(TCGA_BRCAdata)
data(GroundT)
test1<-PTC(miRNAs=TCGA_BRCAdata$miRs,mRNAs=TCGA_BRCAdata$mRNAs, VIM=TCGA_BRCAdata$mRNAs[,"VIM"])
t1.Confirmed<-Confirmed.fromList(test1$Names,GroundT)

## End(Not run)
```

`Confirmed.fromMatrix` *Confirmed.fromMatrix*

Description

Given a matrix with miRNA-mRNA interactions, returns a `matrix` with all of those interactions that are present in the `GroundT`.

Usage

```
Confirmed.fromMatrix(InterMatrix, GroundT)
```

Arguments

`InterMatrix`	A `matrix` containing miRNA-mRNA interactions. The first columns corresponds to miRNAs. The second column corresponds to mRNA.
`GroundT`	A `list` where each element has the following structure: • `name`: mRNA name. • `data`: Names of the miRNAs whose interactions with the mRNA have been experimentally confirmed.

Value

A `matrix` containing all interactions in `InterMatrix` that are in the `GroundT`

See Also

PTC, GroundT Confirmed.fromList InterList.toMatrix

Examples

```
## Not run:
data(TCGA_BRCAdata)
data(GroundT)
test1<-PTC(miRNAs=TCGA_BRCAdata$miRs,mRNAs=TCGA_BRCAdata$mRNAs, VIM=TCGA_BRCAdata$mRNAs[,"VIM"])
aux<-InterList.toMatrix(test1$Names)
t1.Confirmed<-Confirmed.fromMatrix(aux,GroundT)

## End(Not run)
```

Extract.Parents *Extract.Parents*

Description

Uses the outcomes of PTC.GeneSel and PTC.TestInvariance to create a `list` of all mRNAs in `Predictors` with at least one causal parent.

Usage

```
Extract.Parents(PTC.outcome, Predictors)
```

Arguments

`PTC.outcome`	A `list` containing the results of the function PTC.TestInvariance. Each element of the `list` must have the following form: • `name`: mRNA name • `data`: indexes indicating the position of the inferred miRNAs in the vector of plausible parents.
`Predictors`	A `list` containing the set of miRNAs to be used as predictors (plausible parents) of each mRNA, obtained from PTC.GeneSel.

Value

A list of 3 elements.

`Index`	Indexes of miRNAs inferred as causal parents of each mRNA. The indexes correspond to miRNAs position in the set of plausible parents of each mRNA.
`Names`	A list where each element corresponds to a mRNA and contains the names of the miRNAs that are inferred as causal parents of that mRNA.
`genes`	Names of all mRNAs with at least one parent inferred by PTC.

See Also

PTC, PTC.TestInvariance, PTC.GeneSel

Examples

```
## Not run:
data(TCGA_BRCAdata)
data(TScan)
seqData<-PTC.ptime(TCGA_BRCAdata,TCGA_BRCAdata$mRNAs[,"VIM"])
SelData<-PTC.GeneSel(seqData, nmiR = 30, nmR = 1500)
PParents<-PTC.findPP(TScan, miRs=SelData$miRs, mRs="ONECUT2")
temp <-SelData$PParents[["ONECUT2"]]
ONECUT2.X.TScan=SelData$d[,temp]
set.seed(1)
```

```
ONECUT2.Parents<-PTC.TestInvariance(Y=SelData$d[,"ONECUT2", drop = F], X=ONECUT2.X.TScan)
ONECUT2.Parents<-Extract.Parents(ONECUT2.Parents,SelData$PParents["ONECUT2"])

## End(Not run)
```

`getDatabyMAD` *getDatabyMAD*

Description

Given a gene expression data including matched miRNAs-mRNAs, finds the `nmiR` miRNAs and the `nmR` mRNAs with the largest Median Absolute Deviation (MAD).

Usage

```
getDatabyMAD(seqData, nmiR, nmR)
```

Arguments

`seqData`	A list with two elements: • A matrix with miRNAs gene expression. • A matrix with mRNAs gene expression. Columns represent miRNAs/mRNAs and rows represent samples (time points). Columns names must correspond to miRNAs/mRNAs names.
`nmiR`	Number of miRNAs to be selected as predictor candidates.
`nmR`	Number of mRNAs to be selected as target variables.

Details

MAD selection is made as in the function `FSbyMAD` (`cut.type="topk"`) from the CancerSubtypes package. Since version 1.1.2 this selection is implemented in PTC, so CancerSubtypes is no longer required.

Value

A `list` containing samples of miRs and mRs. The elements of the `list` are:

`d`	The data with rows being samples and columns being miRs and mRs.
`miRs`	The names of the selected miRs.
`mRs`	The names of the selected mRs.

Author(s)

Vu VH Pham <vu_viet_hoang.pham@mymail.unisa.edu.au>, Taosheng Xu <taosheng.x@gmail.com>

References

Taosheng Xu, Thuc Duy Le, Lin Liu, Ning Su, Rujing Wang, Bingyu Sun, Antonio Colaprico, Gianluca Bontempi, Jiuyong Li. CancerSubtypes: an R/Bioconductor package for molecular cancer subtype identification, validation, and visualization. Bioinformatics 33(19): 3131–3133 (2017). https://doi.org/10.1093/bioinformatics/btx378

Examples

```
data(TCGA_BRCAdata)
nmiR <- 30
nmR <- 1500
l <- getDatabyMAD(TCGA_BRCAdata, nmiR, nmR)
```

GroundT *Confirmed interactions in miR-Tarbase 6.1, Tarbase 7.0 and miRWalk 2.0*

Description

File containing a `list` with the experimentally confirmed miRNA-mRNA interactions from the databases described above.

Usage

```
GroundT
```

Format

A `list` where each element has the following structure:

- `name`: mRNA name.
- `data`: names of miRNAs whose interactions with the mRNA can be found in at least one of the databases described above.

References

Chou, C.-H.; Chang, N.-W.; Shrestha, S.; Hsu, S.-D.; Lin, Y.-L.; Lee, W.-H.; Yang, C.-D.; Hong, H.-C.; Wei, T.-Y.; Tu, S.-J. & others miRTarBase 2016: updates to the experimentally validated miRNA-target interactions database Nucleic acids research, Oxford University Press , 2015, 44, D239-D247

Vlachos, I. S.; Paraskevopoulou, M. D.; Karagkouni, D.; Georgakilas, G.; Vergoulis, T.; Kanellos, I.; Anastasopoulos, I.-L.; Maniou, S.; Karathanou, K.; Kalfakakou, D. & others DIANA-TarBase v7. 0: indexing more than half a million experimentally supported miRNA: mRNA interactions Nucleic acids research, Oxford University Press, 2014, 43, D153-D159

Dweep, H.and Gretz, N. miRWalk2. 0: a comprehensive atlas of microRNA-target interactions Nature methods, Nature Publishing Group, 2015, 12, 697

`InterList.toMatrix` *InterList.toMatrix*

Description

Given a `list` where each element is a mRNA containing the set of the miRNAs (parents) such mRNA can interact with (e.g. the output of Extract.Parents), it returns a `matrix` with the miRNA-mRNA interactions. Each row represents an interaction. The first column contains miRNAs. The second column contains mRNAs.

Usage

```
InterList.toMatrix(InterList)
```

Arguments

`InterList`	A `list` where each element has the following structure: • `name`: mRNA name. • `data`: Names of the miRNAs inferred as parents

Value

A matrix with 2 columns containing the miRNA-mRNA interactions.

See Also

InterMatrix.toList, Extract.Parents

Examples

```
## Not run:
data(TCGA_BRCAdata)
data(TScan)
seqData<-PTC.ptime(TCGA_BRCAdata,TCGA_BRCAdata$mRNAs[,"VIM"])
SelData<-PTC.GeneSel(seqData, nmiR = 30, nmR = 1500)
PParents<-PTC.findPP(TScan, miRs=SelData$miRs, mRs="ONECUT2")
temp <-SelData$PParents[["ONECUT2"]]
ONECUT2.X.TScan=SelData$d[,temp]
set.seed(1)
ONECUT2.Parents<-PTC.TestInvariance(Y=SelData$d[,"ONECUT2", drop = F], X=ONECUT2.X.TScan)
ONECUT2.Parents<-Extract.Parents(ONECUT2.Parents,SelData$PParents["ONECUT2"])
ONECUT2.relMatrix<-InterList.toMatrix(ONECUT2.Parents$Names)

## End(Not run)
```

InterMatrix.toList *InterMatrix.toList*

Description

Given a matrix containing miRNA-mRNA interactions, creates a `list` where each element corresponds to a mRNA and contains the miRNAs related to that mRNA.

Usage

```
InterMatrix.toList(InterMatrix)
```

Arguments

`InterMatrix`	A two column `matrix` containing miRNA-mRNA relationships. The first column corresponds to miRNAs. The second column corresponds to mRNAs.

Value

A `list` where each element has the following structure:

`name:`	mRNA name.
`data:`	Names of the miRNAs linked to the current mRNA

See Also

InterList.toMatrix

Examples

```
## Not run:
data(TCGA_BRCAdata)
data(TScan)
VIM=TCGA_BRCAdata$mRNAs[,"VIM"]
GEData<-list(TCGA_BRCAdata$miRs,TCGA_BRCAdata$mRNAs)
names(GEData)<-c("miRs","mRNAs")
seqData<-PTC.ptime(GEData,VIM)
SelData<-PTC.GeneSel(seqData, nmiR = 30, nmR = 1500)
InteractionsM<-InterList.toMatrix(SelData$PParents)
InteractionsL<-InterMatrix.toList(InteractionsM)

## End(Not run)
```

PTC *PTC*

Description

PTC estimates the causal parents of a set of nmR mRNAs, given a set of nmiR predictors (miRNAs). This estimation assumes a linear model

$$Y_t = \beta X_t + \epsilon$$

With Y_t, X_t the sequential data of the target and the predictors respectively, and ϵ independent and identically distributed errors for the n time points in the time series. Y_t, X_t are the sequential data obtained after a pseudotime analysis.

Usage

```
PTC(
  miRNAs,
  mRNAs,
  VIM,
  nmiR = 30,
  nmR = 1500,
  ngrid = 2,
  alpha = 0.02,
  complements = TRUE,
  explore.all = TRUE,
  silent = TRUE,
  TScan = NULL
)
```

Arguments

miRNAs	A matrix containing miRNA gene expression. A total of nmiR miRNAs from this matrix are selected to be used as predictors candidates (i.e. plausible parents). Columns represent miRNAs, rows represent samples.
mRNAs	A matrix containing mRNA gene expression. A total of nmR mRNAs from this matrix are selected to be used as response variables. Columns represent mRNAs, rows represent samples.
VIM	VIM expression to be used for calculating VIM_Time.
nmiR	Number of miRNAs to be selected as predictor candidates.
nmR	Number of mRNAs to be selected as target variables.
ngrid	Number of segments of the time series data used for creating the different environments required for the statistical test. ngrid=2 by default.
alpha	Significance level for the statistical test. alpha=0.02 by default.

`complements` If `TRUE` (default), each environment is compared against its complement. If `FALSE` all environments are compared pairwise.

`explore.all` If `TRUE`(default), PTC explores all combinations of predictors and returns the union set of all combinations that does not violate the invariance property. If `FALSE` PTC returns the first set that does not violate the invariance property. Exploration is made starting from the set of all predictors and reducing the size of the set by one predictor at a time.

`silent` If `TRUE` (default), PTC only displays the number of sets to be explored in the current iteration. If `FALSE`, PTC also displays each evaluated and accepted set.

`TScan` A 2 column matrix containing the miRNA-mRNA relationships. For an appropriate functioning, miRNAs must be in lower case and mRNAs in upper case. If `NULL` (default), PTC uses a pre-loaded matrix (file TScan) with TargetScan 7.0 Human.

Value

A `list` consisting of the following elements:

`Index` A `list` where each element is a target mRNA. For each target gene with at least one parent. The index of the parents.

`names` A `list` where each element is a target mRNA. For each target gene with at least one parent. The name of the parents.

`genes` The names of all target genes with at least one parent.

`Summary` A matrix representing miRNA-mRNA regulatory interactions inferred by PTC. The columns of the matrix are:

1. `rank:` Rank of the inferred interaction
2. `miR:` Names of miRNA (Parent)
3. `mR:` Names of mRNA (Child)
4. `Score:` Score as calculated by PTC.RankByContext

Author(s)

Andres Mauricio Cifuentes_Bernal, Vu VH Pham, Xiaomei Li, Lin Liu, Jiuyong Li and Thuc Duy Le

References

A Pseudo-Temporal Causality Approach to Identifying miRNA-mRNA Interactions During Biological Processes
Andres M. Cifuentes-Bernal, Vu VH Pham, Xiaomei Li, Lin Liu, Jiuyong Li, Thuc Duy Le
bioRxiv 2020.07.07.192724; https://doi.org/10.1101/2020.07.07.192724

See Also

PTC.ptime, PTC.GeneSel, TScan PTC.TestInvariance.

Examples

```
## Not run:
   data(TCGA_BRCAdata)
   test1<-PTC(miRNAs=TCGA_BRCAdata$miRs, mRNAs=TCGA_BRCAdata$mRNAs
          , VIM=TCGA_BRCAdata$mRNAs[,"VIM"])

## End(Not run)
```

PTC.findPP *PTC.findPP*

Description

Given a vector of miRNA names and a vector of mRNAs names, creates a set of miRNAs (plausible parents) that can biologically target each mRNA as predicted by TargetScan.
For an adequate functioning miRNAs names in TScan and miRs must belong to the same version. miRBase version 21 is recommended (see PTC.miRv21)

Usage

```
PTC.findPP(TScan = NULL, miRs, mRs)
```

Arguments

TScan	A matrix containing miRNA-mRNA interactions predicted by TargetScan. If NULL (default): Loads the file TScan.rda, which contains interactions from TargetScan 7.0. miRNA names in this file belong to miRBase version 21.
miRs	A vector containing the names of miRNAs to be verified. These names correspond to the names of predictor candidates.
mRs	A vector containing the names of mRNAs to be verified. These names correspond to the names of target genes (response variables).

Value

A list where each element corresponds to a mRNA. Each element contains the set of miRNAs that can bind the mRNA.

See Also

PTC, PTC.GeneSel, TScan, PTC.miRv21

Examples

```
## Not run:
data(TCGA_BRCAdata)
data(TScan)
seqData<-PTC.ptime(TCGA_BRCAdata,TCGA_BRCAdata$mRNAs[,"VIM"])
SelData<-PTC.GeneSel(seqData, nmiR = 30, nmR = 1500)
PParents<-PTC.findPP(TScan, miRs=SelData$miRs, mRs=SelData$mRs)

## End(Not run)
```

`PTC.GeneSel` *PTC.GeneSel*

Description

Creates a set of miRNAs (plausible parents) for each mRNA among `nmR` mRNAs that can biologically target that mRNA. A total of `nmiR` miRNAs and `nmR` mRNAs with the largest gene expression Median Absolute Deviation (MAD) are selected as predictor candidates and target mRNAs respectively.
The set of plausible parents of each gene is a subset of the predictor candidates and contains those miRNA that can bind the gene as predicted by TargetScan 7.0. miRNAs names are converted to `miRBase v.21` during selection process

Usage

```
PTC.GeneSel(seqData, nmiR = 30, nmR = 1500, TScan = NULL)
```

Arguments

`seqData`	A list with two elements: • A matrix with miRNAs gene expression. • A matrix with mRNAs gene expression. Columns represent miRNAs/mRNAs and rows represent samples (time points). Columns names must correspond to miRNAs/mRNAs names.
`nmiR`	Number of miRNAs to be selected as predictor candidates.
`nmR`	Number of mRNAs to be selected as target variables.
`TScan`	A 2 column matrix containing the miRNA-mRNA relationships. For an appropriate functioning, miRNAs must be in lower case and mRNAs in upper case. If `NULL` (default), PTC uses a pre-loaded matrix (file TScan) with TargetScan 7.0 Human.

Value

A list containing four elements:

miRs	nmiR miRNAs names (version miRBase v.21) selected by MAD
mRs	nmR mRNAs names selected by MAD
d	A matrix with nmiR + nmR columns, containing miRNAs:mRNAs gene expression. Columns [1 : nmiR] correspond to miRNAs data. Columns [nmiR+1 : nmiR+nmR]

correspond to mRNAs data. Rows correspond to samples.

PParents	A list containing the set of miRNAs to be used as predictors (plausible parents) of each mRNA. This set contains the miRNAs among the predictor candidates that can bind the target gene as predicted by TargetScan 7.0

See Also

PTC, getDatabyMAD, miRNAVersionConvert, PTC.findPP

Examples

```
## Not run:
seqData<-PTC.ptime(TCGA_BRCAdata,TCGA_BRCAdata$mRNAs[,"VIM"])
SelData<-PTC.GeneSel(seqData, nmiR = 30, nmR = 1500)

## End(Not run)
```

PTC.miRv21 *PTC.miRv21*

Description

Takes a vector containing miRNAs names and returns the miRBase v.21 version of them.

Usage

```
PTC.miRv21(miRs)
```

Arguments

miRs	miRNAs names to be changed to version miRBase v.21

Value

nmiR A vector with the miRNAs names (version miRBase v.21)

See Also

PTC, miRNAVersionConvert, PTC.GeneSel

Examples

```
## Not run:
data(TCGA_BRCAdata)
miRnamesv21<-PTC.miRv21(colnames(TCGA_BRCAdata$miRs))

## End(Not run)
```

PTC.ptime *PTC.ptime*

Description

Orders the gene expression by VIM_Time order.

Usage

```
PTC.ptime(matchedData, VIM)
```

Arguments

matchedData	A List with two elements. A miRNA gene expressions matrix (1st element) and A mRNA gene expressions matrix (2nd element). Columns represent miRNAs and rows represent samples.
VIM	VIM expression to be used for calculating VIM_Time.

Value

Pseudotime ordered matched data.

See Also

PTC

Examples

```
## Not run:
  data(TCGA_BRCAdata)
  Time_series<-PTC.ptime(TCGA_BRCAdata, TCGA_BRCAdata$mRNAs[,"VIM"])

## End(Not run)
```

PTC.RankByContext *PTC.RankByContext*

Description

This function uses TS70 Conserved_Site_Context_Scores (from http://www.targetscan.org/cgi-bin/targetscan/data_download.cgi?db=vert_70) to rank a matrix of inferred miRNA-mRNA relationships.

Usage

```
PTC.RankByContext(TS70context, relationshipsM)
```

Arguments

TS70context	A matrix containing conserved site context++ scores. The headers of the matrix from TargetScan must be conserved when the file is imported into R.
relationshipsM	A matrix with two columns containing miRNAs and mRNAs names. First column represents miRNAs and second column mRNAs (e.g the output of InterList.toMatrix).

Value

A relationship matrix with four columns [Rank, miRNA, mRNA, Score]. The more negative the score, the better the rank of the corresponding miRNA-mRNA pair. Pairs without context score (NaN) are ranked last.

See Also

PTC

Examples

```
## Not run:
data(TCGA_BRCAdata)
data(TScan)
data(TS7.0_Conserved_Site_Context_Scores)

seqData<-PTC.ptime(TCGA_BRCAdata,TCGA_BRCAdata$mRNAs[,"VIM"])
SelData<-PTC.GeneSel(seqData, nmiR = 30, nmR = 1500)
PParents<-PTC.findPP(TScan, miRs=SelData$miRs, mRs="ONECUT2")
temp <-SelData$PParents[["ONECUT2"]]

ONECUT2.X.TScan=SelData$d[,temp]
set.seed(1)
ONECUT2.Parents<-PTC.TestInvariance(Y=SelData$d[,"ONECUT2", drop =F], X=ONECUT2.X.TScan)
ONECUT2.Parents<-Extract.Parents(ONECUT2.Parents,SelData$PParents["ONECUT2"])
ONECUT2.relMatrix<-InterList.toMatrix(ONECUT2.Parents$Names)
ONECUT2.Summary<-PTC.RankByContext(TS7.0_Conserved_Site_Context_Scores
```

```
                                ,ONECUT2.relMatrix)

## End(Not run)
```

PTC.TestInvariance *PTC.TestInvariance*

Description

Finds a set of miRNAs (predictors) that are causal parents of a target gene. This set is defined as the union of sets that are invariant. Invariance is determined by using the `decoupled test` from seqICP (Pfister et al., 2018). Since version 1.1.2 this test is implemented in PTC, so seqICP is no longer required.

Usage

```
PTC.TestInvariance(
  Y,
  X,
  ngrid = 2,
  alpha = 0.02,
  explore.all = TRUE,
  silent = TRUE,
  complements = TRUE
)
```

Arguments

`Y`	[nx1] A `named vector` containing the sequential gene expression of a target gene Y. Please use `drop = FALSE` when assigning a mRNA gene expression from a `matrix` to preserve the name of the mRNA.
`X`	[nxp] A `named matrix` containing the sequential gene expression of `p` plausible parents (miRNAs that can bind the target mRNA). For a correct functioning, column names must be the miRNA names.
`ngrid`	Number of segments of the time series data used for creating the different environments required for the statistical test. `ngrid=2` by default.
`alpha`	Significance level for the statistical test. `alpha=0.02` by default.
`explore.all`	If `TRUE`(default), PTC explores all combinations of predictors and returns the union set of all combinations that does not violate the invariance property. If `FALSE` PTC returns the first set that does not violate the invariance property. Exploration is made starting from the set of all predictors and reducing the size of the set by one predictor at a time.
`silent`	If `TRUE` (default), PTC only displays the number of sets to be explored in the current iteration. If `FALSE`, PTC also displays each evaluated and accepted set.
`complements`	If `TRUE` (default), each environment is compared against its complement. If `FALSE` all environments are compared pairwise.

Value

`Parents` A set containing the indexes of the parents inferred by PTC. These indexes correspond to the indexes of the miRNAs in the set `PParents` (Plausible Parents) obtained from PTC.GeneSel

References

A Pseudo-Temporal Causality Approach to Identifying miRNA-mRNA Interactions During Biological Processes
Andres M. Cifuentes-Bernal, Vu VH Pham, Xiaomei Li, Lin Liu, Jiuyong Li, Thuc Duy Le
bioRxiv 2020.07.07.192724; https://doi.org/10.1101/2020.07.07.192724

See Also

PTC

Examples

```
## Not run:
data(TCGA_BRCAdata)
data(TScan)
seqData<-PTC.ptime(TCGA_BRCAdata,TCGA_BRCAdata$mRNAs[,"VIM"])
SelData<-PTC.GeneSel(seqData, nmiR = 30, nmR = 1500)
PParents<-PTC.findPP(TScan, miRs=SelData$miRs, mRs="ONECUT2")
temp <-SelData$PParents[["ONECUT2"]]
ONECUT2.X.TScan=SelData$d[,temp, drop = FALSE]
set.seed(1)
ONECUT2.Parents<-PTC.TestInvariance(Y=SelData$d[,"ONECUT2", drop = F], X=ONECUT2.X.TScan)

## End(Not run)
```

SC_miRNAsdata *Original miRNAs dataset from GSE114071*

Description

GSE114071 file containing miRNA normalized and log2 transformed gene expression of 2822 miRNAs from 21 samples.

Usage

```
SC_miRNAsdata
```

Format

A `matrix` with 2822 rows and 23 columns. samples are represented in rows. Columns contain miRNA names, description and samples

References

Wang, N., Zheng, J., Chen, Z. et al. "Single-cell microRNA-mRNA co-sequencing reveals non-genetic heterogeneity and mechanisms of microRNA regulation." Nat Commun 10, 95 (2019). https://doi.org/10.1038/s41467-018-07981-6

`SC_mRNAsdata` *Original mRNAs dataset from GSE114071*

Description

GSE114071 file containing mRNA gene expression of 23284 mRNAs from 22 samples.

Usage

```
SC_mRNAsdata
```

Format

A `matrix` with 23285 rows and 24 columns. samples are represented in rows (from row 2). Columns contain mRNA names, description and samples

References

Wang, N., Zheng, J., Chen, Z. et al. "Single-cell microRNA-mRNA co-sequencing reveals non-genetic heterogeneity and mechanisms of microRNA regulation." Nat Commun 10, 95 (2019). https://doi.org/10.1038/s41467-018-07981-6

`TCGA_BRCAdata` *miRNA-mRNA matched bulk data from TCGA BRCA project*

Description

File containing BRCA gene expression matched data of 518 miRNAs and 17403 mRNAs from 503 samples.

Usage

```
TCGA_BRCAdata
```

Format

A `list` object with 2 elements: miRs and mRNAs

References

Pham, V., Zhang, J., Liu, L. et al. "Identifying miRNA-mRNA regulatory relationships in breast cancer with invariant causal prediction." BMC Bioinformatics 20, 143 (2019). https://doi.org/10.1186/s12859-019-2668-x

TS7.0_Conserved_Site_Context_Scores *TargetScan 7.0 Conserved Site Context Scores.*

Description

File containing a `matrix` with the TargetScan 7.0 Context++ scores and contributions for all conserved miRNA sites, downloaded from http://www.targetscan.org/cgi-bin/targetscan/data_download.cgi?db=vert_70

Usage

```
TS7.0_Conserved_Site_Context_Scores
```

Format

A `matrix` with TargetScan 7.0 Conserved Site Context Scores data.

References

Agarwal, V.; Bell, G. W.; Nam, J.-W. & Bartel, D. P. Predicting effective microRNA target sites in mammalian mRNAs eLife, eLife Sciences Publications, Ltd, 2015, 4

TScan *TargetScan 7.0*

Description

File containing a `matrix` with miRNAs and predicted targets from TargetScan Release 7.0. miRNA names were transformed to their miRBase v.21 by using PTC.miRv21

Usage

```
TScan
```

Format

A `matrix` with 2 columns

- miRNAs names v21
- predicted target (mRNA)

References

Agarwal, V.; Bell, G. W.; Nam, J.-W. & Bartel, D. P. Predicting effective microRNA target sites in mammalian mRNAs eLife, eLife Sciences Publications, Ltd, 2015, 4

wandTime *wandTime.csv*

Description

File containing the pseudotime obtained by using Wanderlust (Bendall et al) on the dataset SC_mRNAsdata. Parameters were set to k=4, l=2, ng=2 and snn =0.

Format

A `matrix` with 1 row and 19 columns with the pseudotime obtained by Wanderlust using the dataset SC_mRNAsdata. Please use `wandTime <- read.csv("./data/wandTime.csv", header=FALSE)` to load this file (`data(wandTime)` does not load it properly).

References

A Pseudo-Temporal Causality Approach to Identifying miRNA-mRNA Interactions During Biological Processes
Andres M. Cifuentes-Bernal, Vu VH Pham, Xiaomei Li, Lin Liu, Jiuyong Li, Thuc Duy Le
bioRxiv 2020.07.07.192724; https://doi.org/10.1101/2020.07.07.192724

Wang, N., Zheng, J., Chen, Z. et al. "Single-cell microRNA-mRNA co-sequencing reveals non-genetic heterogeneity and mechanisms of microRNA regulation." Nat Commun 10, 95 (2019). https://doi.org/10.1038/s41467-018-07981-6

Bendall SC, Davis KL, Amir el-AD, et al.
Single-cell trajectory detection uncovers progression and regulatory coordination in human B cell development.
Cell. 2014;157(3):714-725. doi:10.1016/j.cell.2014.04.005

Index

∗ **Single_Cell**
SC_miRNAsdata, 17
SC_mRNAsdata, 18
wandTime, 20
∗ **dataset**
GroundT, 6
SC_miRNAsdata, 17
SC_mRNAsdata, 18
TCGA_BRCAdata, 18
TS7.0_Conserved_Site_Context_Scores, 19
TScan, 19
∗ **mRNAs**
SC_mRNAsdata, 18
∗ **miRNAs**
SC_miRNAsdata, 17
∗ **pseudotime**
wandTime, 20

Confirmed.fromList, 2, *3*
Confirmed.fromMatrix, 3

Extract.Parents, 4, *7*

getDatabyMAD, 5, *13*
GroundT, *2, 3*, 6

InterList.toMatrix, *3*, 7, *8*, *15*
InterMatrix.toList, *7*, 8

miRNAVersionConvert, *13*

PTC, *2–4*, 9, *11*, *13–15*, *17*
PTC.findPP, 11, *13*
PTC.GeneSel, *4*, *10, 11*, 12, *13*, *17*
PTC.miRv21, *11*, 13, *19*
PTC.ptime, *10*, 14
PTC.RankByContext, *10*, 15
PTC.TestInvariance, *4*, *10*, 16

SC_miRNAsdata, 17
SC_mRNAsdata, 18, *20*

TCGA_BRCAdata, 18
TS7.0_Conserved_Site_Context_Scores, 19
TScan, *10, 11*, 19

wandTime, 20